

Network work group
Internet Draft
Intended status: Standards Track

Fatai Zhang
Young Lee
Jianrui Han
Huawei
G. Bernstein
Grotto Networking
Yunbin Xu
CATR
September 13, 2011

Expires: March 13, 2012

OSPF-TE Extensions for General Network Element Constraints

[draft-ietf-ccamp-gmpls-general-constraints-ospf-te-01.txt](#)

Status of this Memo

This Internet-Draft is submitted to IETF in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/1id-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

This Internet-Draft will expire on March 13, 2012.

Abstract

Generalized Multiprotocol Label Switching can be used to control a wide variety of technologies including packet switching (e.g., MPLS), time-division (e.g., SONET/SDH, OTN), wavelength (lambdas), and

<Zhang>

Expires March 2012

[Page 1]

spatial switching (e.g., incoming port or fiber to outgoing port or fiber). In some of these technologies network elements and links may impose additional routing constraints such as asymmetric switch connectivity, non-local label assignment, and label range limitations on links. This document describes OSPF routing protocol extensions to support these kinds of constraints under the control of Generalized MPLS (GMPLS).

Conventions used in this document

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC-2119](#) [[RFC2119](#)].

Table of Contents

1.	Introduction	2
2.	Node Information	3
2.1.	Connectivity Matrix.....	4
3.	Link Information	4
3.1.	Port Label Restrictions.....	5
3.2.	Available Labels.....	5
3.3.	Shared Backup Labels.....	6
4.	Routing Procedures	6
5.	Security Considerations.....	7
6.	IANA Considerations	7
6.1.	Node Information.....	7
6.2.	Link Information.....	7
7.	References	8
7.1.	Normative References.....	8
7.2.	Informative References.....	9
8.	Authors' Addresses	9
	Acknowledgment	11

[1. Introduction](#)

Some data plane technologies that wish to make use of a GMPLS control plane contain additional constraints on switching capability and label assignment. In addition, some of these technologies should be capable of performing non-local label assignment based on the nature of the technology, e.g., wavelength continuity constraint in WSON [[RFC6163](#)]. Such constraints can lead to the requirement for link by link label availability in path computation and label assignment.

[GEN-Encode] provides efficient encodings of information needed by the routing and label assignment process in technologies such as WSON and are potentially applicable to a wider range of technologies.

This document defines extensions to the OSPF routing protocol based on [GEN-Encode] to enhance the Traffic Engineering (TE) properties of GMPLS TE which are defined in [RFC3630], [RFC4202], and [RFC4203]. The enhancements to the Traffic Engineering (TE) properties of GMPLS TE links can be announced in OSPF TE LSAs. The TE LSA, which is an opaque LSA with area flooding scope [RFC3630], has only one top-level Type/Length/Value (TLV) triplet and has one or more nested sub-TLVs for extensibility. The top-level TLV can take one of three values (1) Router Address [RFC3630], (2) Link [RFC3630], (3) Node Attribute [RFC5786]. In this document, we enhance the sub-TLVs for the Link TLV and Node Attribute TLV in support of the general network element constraints under the control of GMPLS.

The detailed encoding of OSPF extensions are not defined in this document. [GEN-Encode] provides encoding detail.

2. Node Information

According to [GEN-Encode], the additional node information representing node switching asymmetry constraints includes Node ID, connectivity matrix. Except for the Node ID which should comply with Routing Address described in [RFC3630], the other pieces of information are defined in this document.

[RFC5786] defines a new top TLV named the Node Attribute TLV which carries attributes related to a router/node. This Node Attribute TLV contains one or more sub-TLVs.

Per [GEN-Encode], we have identified the following new Sub-TLVs to the Node Attribute TLV. Detail description for each newly defined Sub-TLV is provided in subsequent sections:

Sub-TLV Type	Length	Name
TBD	variable	Connectivity Matrix

In some specific technologies, e.g., WSON networks, Connectivity Matrix sub-TLV may be optional, which depends on the control plane implementations. Usually, for example, in WSON networks, Connectivity Matrix sub-TLV may appear in the LSAs because WSON switches are asymmetric at present. It is assumed that the switches are symmetric switching, if there is no Connectivity Matrix sub-TLV in the LSAs.

2.1. Connectivity Matrix

It is necessary to identify which ingress ports and labels can be switched to some specific labels on a specific egress port, if the switching devices in some technology are highly asymmetric.

The Connectivity Matrix is used to identify these restrictions, which can represent either the potential connectivity matrix for asymmetric switches (e.g. ROADMs and such) or fixed connectivity for an asymmetric device such as a multiplexer as defined in [WSON-Info].

The Connectivity Matrix is a sub-TLV (the type is TBD by IANA) of the Node Attribute TLV. The length is the length of value field in octets. The meaning and format of this sub-TLV are defined in Section 5.3 of [GEN-Encode]. One sub-TLV contains one matrix. The Connectivity Matrix sub-TLV may occur more than once to contain multi-matrices within the Node Attribute TLV.

3. Link Information

The most common link sub-TLVs nested to link top-level TLV are already defined in [RFC3630], [RFC4203]. For example, Link ID, Administrative Group, Interface Switching Capability Descriptor (ISCD), Link Protection Type, Shared Risk Link Group Information (SRLG), and Traffic Engineering Metric are among the typical link sub-TLVs.

Per [GEN-Encode], we add the following additional link sub-TLVs to the link-TLV in this document.

Sub-TLV Type	Length	Name
TBD	variable	Port Label Restrictions
TBD	variable	Available Labels
TBD	variable	Shared Backup Labels

Generally all the sub-TLVs above are optional, which depends on the control plane implementations. If it is default no restrictions on labels, Port Label Restrictions sub-TLV may not appear in the LSAs. In order to be able to compute label assignment, Available Labels sub-TLV may appear in the LSAs. For example, in WSON networks, without available wavelength information, path computation need guess

what lambdas may be available (high blocking probability or distributed wavelength assignment may be used).

3.1. Port Label Restrictions

Port label restrictions describe the label restrictions that the network element (node) and link may impose on a port. These restrictions represent what labels may or may not be used on a link and are intended to be relatively static. More dynamic information is contained in the information on available labels. Port label restrictions are specified relative to the port in general or to a specific connectivity matrix for increased modeling flexibility.

For example, Port Label Restrictions describes the wavelength restrictions that the link and various optical devices such as OXCs, ROADMs, and waveband multiplexers may impose on a port in WSON. These restrictions represent what wavelength may or may not be used on a link and are relatively static. The detailed information about Port label restrictions is described in [[WSON-Info](#)].

The Port Label Restrictions is a sub-TLV (the type is TBD by IANA) of the Link TLV. The length is the length of value field in octets. The meaning and format of this sub-TLV are defined in Section 5.4 of [[GEN-Encode](#)]. The Port Label Restrictions sub-TLV may occur more than once to specify a complex port constraint within the link TLV.

3.2. Available Labels

Available Labels indicates the labels available for use on a link as described in [[GEN-Encode](#)]. The Available Labels is a sub-TLV (the type is TBD by IANA) of the Link TLV. The length is the length of value field in octets. The meaning and format of this sub-TLV are defined in Section 5.1 of [[GEN-Encode](#)]. The Available Labels sub-TLV may occur at most once within the link TLV.

Note that there are five approaches for Label Set which is used to represent the Available Labels described in [[GEN-Encode](#)]. Usually, it depends on the implementation to one of the approaches. In WSON networks, considering that the continuity of the available or unavailable wavelength set can be scattered for the dynamic wavelength availability, so it may burden the routing to reorganize the wavelength set information when the Inclusive (/Exclusive) List (/Range) approaches are used to represent Available Wavelengths information. Therefore, it is RECOMMENDED that only the Bitmap Set be used for representation Available Wavelengths information.

0										1										2										3									
0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9
+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-
Grid										C.S.										Reserved										n									
+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-

3.3. Shared Backup Labels

The Shared Backup Labels is a sub-TLV (the type is TBD by IANA) of the Link TLV. The length is the length of value field in octets. The meaning and format of this sub-TLV are defined in Section 5.2 of [[GEN-Encode](#)]. The Shared Backup Labels sub-TLV may occur at most once within the link TLV.

All the sub-TLVs are nested to top-level TLV(s) and contained in Opaque LSAs. The flooding of Opaque LSAs must follow the rules specified in [RFC2328], [RFC2370], [RFC3630], [RFC4203] and [RFC5786].

For node information, since the Connectivity Matrix information is static, the LSA containing the Node Attribute TLV can be updated with a lower frequency to avoid unnecessary updates.

For link information, a mechanism MAY be applied such that static information and dynamic information of one TE link are contained in separate Opaque LSAs. For example, the Port Label Restrictions

information sub-TLV and Available Labels information sub-TLV can be nested to the top level link TLVs and advertised in the separate LSAs.

Note that as with other TE information, an implementation SHOULD take measures to avoid rapid and frequent updates of routing information that could cause the routing network to become swamped. A threshold mechanism MAY be applied such that updates are only flooded when a number of changes have been made to the label availability information (e.g., wavelength availability) within a specific time. Such mechanisms MUST be configurable if they are implemented.

5. Security Considerations

This document does not introduce any further security issues other than those discussed in [[RFC 3630](#)], [[RFC 4203](#)].

6. IANA Considerations

[RFC3630] says that the top level Types in a TE LSA and Types for sub-TLVs for each top level Types must be assigned by Expert Review, and must be registered with IANA.

IANA is requested to allocate new Types for the sub-TLVs as defined in Sections [2.1](#), [3.1](#), [3.2](#) and [3.3](#) as follows:

6.1. Node Information

This document introduces the following sub-TLVs of Node Attribute TLV (Value TBD, see [[RFC5786](#)]):

Type	sub-TLV
TBD	Connectivity Matrix

6.2. Link Information

This document introduces the following sub-TLVs of TE Link TLV (Value 2):

Type	sub-TLV
TBD	Port Label Restrictions

TBD Available Labels

TBD Shared Backup Labels

7. References

7.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC2328] Moy, J., "OSPF Version 2", STD 54, [RFC 2328](#), April 1998.
- [RFC2370] Coltun, R., "The OSPF Opaque LSA Option", [RFC 2370](#), July 1998.
- [RFC3630] Katz, D., Kompella, K., and Yeung, D., "Traffic Engineering (TE) Extensions to OSPF Version 2", [RFC 3630](#), September 2003.
- [RFC4202] Kompella, K., Ed., and Y. Rekhter, Ed., "Routing Extensions in Support of Generalized Multi-Protocol Label Switching (GMPLS)", [RFC 4202](#), October 2005
- [RFC4203] Kompella, K., Ed., and Y. Rekhter, Ed., "OSPF Extensions in Support of Generalized Multi-Protocol Label Switching (GMPLS)", [RFC 4203](#), October 2005.
- [RFC5786] R. Aggarwal and K. Kompella, "Advertising a Router's Local Addresses in OSPF Traffic Engineering (TE) Extensions", [RFC 5786](#), March 2010.
- [GEN-Encode] G. Bernstein, Y. Lee, D. Li, W. Imajuku, " General Network Element Constraint Encoding for GMPLS Controlled Networks", work in progress: [draft-ietf-ccamp-general-constraint-encode-05.txt](#), May 2011.
- [RFC6205] T. Otani, H. Guo, K. Miyazaki, D. Caviglia, " Generalized Labels for Lambda-Switching Capable Label Switching Routers", work in progress: [draft-ietf-ccamp-gmpls-g-694-lambda-labels-11.txt](#), January 2011.

7.2. Informative References

- [RFC6163] Y. Lee, G. Bernstein, W. Imajuku, "Framework for GMPLS and PCE Control of Wavelength Switched Optical Networks (WSON)", work in progress: [draft-ietf-ccamp-rwa-WSON-Framework-12.txt](#), February 2011.
- [WSON-Info] Y. Lee, G. Bernstein, D. Li, W. Imajuku, "Routing and Wavelength Assignment Information Model for Wavelength Switched Optical Networks", work in progress: [draft-ietf-ccamp-rwa-info-12.txt](#), September 2011.

8. Authors' Addresses

Fatai Zhang
Huawei Technologies
F3-5-B R&D Center, Huawei Base
Bantian, Longgang District
Shenzhen 518129 P.R.China

Phone: +86-755-28972912
Email: zhangfatai@huawei.com

Young Lee
Huawei Technologies
1700 Alma Drive, Suite 100
Plano, TX 75075
USA

Phone: (972) 509-5599 (x2240)
Email: ylee@huawei.com

Jianrui Han
Huawei Technologies Co., Ltd.
F3-5-B R&D Center, Huawei Base
Bantian, Longgang District
Shenzhen 518129 P.R.China

Phone: +86-755-28977943

Email: hanjianrui@huawei.com

Greg Bernstein
Grotto Networking
Fremont CA, USA

Phone: (510) 573-2237
Email: gregb@grotto-networking.com

Yunbin Xu
China Academy of Telecommunication Research of MII
11 Yue Tan Nan Jie Beijing, P.R.China
Phone: +86-10-68094134
Email: xuyunbin@mail.ritt.com.cn

Guoying Zhang
China Academy of Telecommunication Research of MII
11 Yue Tan Nan Jie Beijing, P.R.China
Phone: +86-10-68094272
Email: zhangguoying@mail.ritt.com.cn

Dan Li
Huawei Technologies Co., Ltd.
F3-5-B R&D Center, Huawei Base
Bantian, Longgang District
Shenzhen 518129 P.R.China

Phone: +86-755-28973237
Email: danli@huawei.com

Ming Chen
European Research Center
Huawei Technologies
Riesstr. 25, 80992 Munchen, Germany

Phone: 0049-89158834072

Email: minc@huawei.com

Yabin Ye
European Research Center
Huawei Technologies
Riesstr. 25, 80992 Munchen, Germany

Phone: 0049-89158834074
Email: yabin.ye@huawei.com

Acknowledgment

We thank Ming Chen and Yabin Ye from DICONNET Project who provided valuable information for this document.

Intellectual Property

The IETF Trust takes no position regarding the validity or scope of any Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described in any IETF Document or the extent to which any license under such rights might or might not be available; nor does it represent that it has made any independent effort to identify any such rights.

Copies of Intellectual Property disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF on-line IPR repository at <http://www.ietf.org/ipr>

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement any standard or specification contained in an IETF Document. Please address the information to the IETF at ietf-ipr@ietf.org.

The definitive version of an IETF Document is that published by, or under the auspices of, the IETF. Versions of IETF Documents that are published by third parties, including those that are translated into

other languages, should not be considered to be definitive versions of IETF Documents. The definitive version of these Legal Provisions is that published by, or under the auspices of, the IETF. Versions of these Legal Provisions that are published by third parties, including those that are translated into other languages, should not be considered to be definitive versions of these Legal Provisions.

For the avoidance of doubt, each Contributor to the IETF Standards Process licenses each Contribution that he or she makes as part of the IETF Standards Process to the IETF Trust pursuant to the provisions of [RFC 5378](#). No language to the contrary, or terms, conditions or rights that differ from or are inconsistent with the rights and licenses granted under [RFC 5378](#), shall have any effect and shall be null and void, whether published or posted by such Contributor, or included with or in such Contribution.

Disclaimer of Validity

All IETF Documents and the information contained therein are provided on an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY, THE IETF TRUST AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION THEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Full Copyright Statement

Copyright (c) 2010 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in [Section 4.e](#) of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.