

Network Working Group
Internet Draft
Proposed Status: Standards Track
Expires: December 2005

Thomas D. Nadeau, Ed.
Cisco Systems, Inc.

Adrian Farrel, Ed.
Old Dog Consulting

June 2005

Generalized Multiprotocol Label Switching (GMPLS)
Label Switching Router (LSR) Management Information Base

[draft-ietf-ccamp-gmpls-lsr-mib-08.txt](#)

Status of this Memo

By submitting this Internet-Draft, each author represents that any applicable patent or other IPR claims of which he or she is aware have been or will be disclosed, and any of which he or she becomes aware will be disclosed, in accordance with [Section 6 of BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/lid-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

Abstract

This memo defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. In particular, it describes managed objects to configure and/or monitor a Generalized Multiprotocol Label Switching (GMPLS) Label Switching Router (LSR).

Internet Draft [draft-ietf-ccamp-gmpls-lsr-mib-08.txt](#)

June 2005

Table of Contents

1.	Introduction	2
1.1.	Migration Strategy	2
2.	Terminology	3
3.	The SNMP Management Framework	3
4.	Outline	3
4.1.	Summary of the GMPLS LSR MIB Module	4
4.1.1	Summary of the GMPLS LSR MIB Module	4
4.1.2	Summary of the GMPLS Label MIB Module	5
5.	Bidirectional LSPs	5
6.	Example of LSP Setup	5
7.	GMPLS Label Switching Router MIB Definitions	9
8.	GMPLS Label MIB Definitions	20
9.	Security Considerations	35
10.	Acknowledgments	36
11.	IANA Considerations	36
11.1.	IANA Considerations for GMPLS-LSR-STD-MIB	36
11.2.	IANA Considerations FOR GMPLS-LABEL-STD-MIB ..	36
12.	References	37
12.1.	Normative References	37
12.2.	Informational References	38
13.	Authors' Addresses	39
14.	Intellectual Property Notice	40
15.	Full Copyright Statement	40

[1.](#) Introduction

This memo defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. In particular, it describes managed objects for modeling a Generalized Multiprotocol Label Switching (GMPLS) [[RFC3945](#)] Label Switching Router (LSR).

Comments should be made directly to the CCAMP mailing list at ccamp@ops.ietf.org.

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [BCP 14](#), [RFC 2119](#), reference [[RFC2119](#)].

1.1. Migration Strategy

There are two MIB modules in this document. The GMPLS LSR MIB module extends the LSR MIB module defined for use with MPLS [[RFC3813](#)]. The only changes made are additions for support of GMPLS or changes that are necessary to support the increased complexity of a GMPLS system. The GMPLS Label MIB module may be referenced using a row pointer from objects within the LSR MIB module.

The companion document modeling and managing GMPLS based traffic engineering [[GMPLSTEMIB](#)] extends the MPLS TE MIB module [[RFC3812](#)] with the same intentions.

Textual conventions and OBJECT-IDENTIFIERS are defined in [[GMPLSTCMIB](#)] which extends the set of textual conventions originally defined in [[RFC3811](#)].

2. Terminology

This document uses terminology from the document describing the MPLS architecture [[RFC3031](#)] and the GMPLS architecture [[RFC3945](#)].

A label switched path (LSP) is modeled as a connection consisting of one or more incoming segments (in-segments) and/or one or more outgoing segments (out-segments) at an LSR. The association or interconnection of the in-segments and out-segments is accomplished by using a cross-connect. We use the terminology "connection" and "LSP" interchangeably where the meaning is clear from the context.

in-segment	This is analogous to a GMPLS label on an interface.
out-segment	This is analogous to a GMPLS label on an interface.
cross-connect	This describes the conceptual connection between a set of in-segments and out-segments. Note that either set may be empty; for example, a cross-connect may connect only out-segments together with no in-segments in the case where an LSP originates on an LSR.

3. The SNMP Management Framework

For a detailed overview of the documents that describe the current Internet-Standard Management Framework, please refer to [section 7 of RFC 3410](#) [[RFC3410](#)].

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. MIB objects are generally accessed through the Simple Network Management Protocol (SNMP). Objects in the MIB are defined using the mechanisms defined in the Structure of Management Information (SMI). This memo specifies a MIB module that is compliant to the SMIV2, which is described in STD 58, [RFC 2578](#) [[RFC2578](#)], STD 58, [RFC 2579](#) [[RFC2579](#)] and STD 58, [RFC 2580](#) [[RFC2580](#)].

[4.](#) Outline

Configuring statically provisioned GMPLS LSPs through an LSR involves the following steps:

- Configuring an interface using the MPLS LSR MIB module.
- Enabling GMPLS on GMPLS capable interfaces using this MIB module.

Nadeau and Farrel (Editors)

[Page 3]

Internet Draft

[draft-ietf-ccamp-gmpls-lsr-mib-08.txt](#)

June 2005

- Configuring in and out-segments using the MPLS LSR MIB module.
- Configuring GMPLS extensions to the in-segments and out-segments using this MIB module.
- Setting up the cross-connect table in the MPLS LSR MIB module to associate segments and/or to indicate connection origination and termination.
- Optionally setting up labels in the label table in this MIB module if the textual convention `MplsLabel` is not capable of holding the required label (for example, if the label requires more than 32 bits to encode it), or if the operator wishes to disambiguate GMPLS label types.
- Optionally specifying label stack actions in the MPLS LSR MIB module.
- Optionally specifying segment traffic parameters in the MPLS LSR MIB module.

[4.1](#) MIB Modules

There are two MIB modules defined in this document.

The GMPLS LSR MIB module contains tables that extend tables defined

in the MPLS LSR MIB module. This MIB module is used in conjunction with the MPLS LSR MIB module in systems that support GMPLS.

The GMPLS Label MIB module contains objects for managing GMPLS labels when they cannot be represented using the textual conventions of the MPLS TC MIB module, or when more detailed access to the sub-fields of the labels is required.

[4.1.1](#) Summary of the GMPLS LSR MIB Module

The MIB tables in this MIB module are as follows.

- The interface configuration table (`gmplsInterfaceTable`), which extends `mplsInterfaceTable` to enable the GMPLS protocol on MPLS-capable interfaces.
- The in-segment (`gmplsInSegmentTable`) and out-segment (`gmplsOutSegmentTable`) tables extend `mplsInSegmentTable` and `mplsOutSegmentTable` to configuring GMPLS-specific parameters for LSP segments at an LSR.

These tables are described in the subsequent sections.

[4.1.2](#) Summary of the GMPLS Label MIB Module

There is one MIB table in this MIB module as follows.

- The `gmplsLabelTable` allows Generalized Labels to be defined and managed in a central location. Generalized Labels can be of variable length and have distinct bit-by-bit interpretations according to the use that is made of them.

These tables are described in the subsequent sections.

[5](#). Bidirectional LSPs

This MIB module supports bidirectional LSPs as required for GMPLS. A single value of `mplsXCIndex` is shared by all of the segments for the entire bidirectional LSP. This facilitates a simple reference from [[RFC3812](#)] and [[GMPLSTEMIB](#)], and makes fate-sharing more obvious.

It is, however, important that the direction of segments is understood to avoid connecting all in-segments to all out-segments. This is achieved by an object in each segment that indicates the direction of the segment with respect to data flow.

A segment that is marked as 'forward' carries data from the 'head' of the LSP to the 'tail'. A segment marked as 'reverse' carries data in the reverse direction.

Where an LSP is signaled using a conventional signaling protocol, the 'head' of the LSP is the source of the signaling (also known as the ingress) and the 'tail' is the destination (also known as the egress). For manually configured LSPs an arbitrary decision must be made about which segments are 'forward' and which 'reverse'. For consistency this decision should be made across all LSRs that participate in the LSP by assigning 'head' and 'tail' ends to the LSP.

6. Example of LSP Setup

In this section we provide a brief example of using the MIB objects described in sections [7](#) and [8](#) to set up an LSP. While this example is not meant to illustrate every nuance of the MIB, it is intended as an aid to understanding some of the key concepts. It is meant to be read after going through the MIB itself. A prerequisite is an understanding of [\[RFC3813\]](#).

Suppose that one would like to manually create a best-effort, bi-directional LSP. Assume that, in the forward direction, the LSP enters the LSR via MPLS interface A with ifIndex 12 and exits the LSR via MPLS interface B with ifIndex 13. For the reverse direction, we assume the LSP enters via interface B and leaves via interface A

(i.e. the forward and reverse directions use the same bi-directional interfaces). Let us also assume that we do not wish to have a label stack beneath the top label on the outgoing labeled packets. The following example illustrates which rows and corresponding objects might be created to accomplish this.

We must first create rows in the `gmplsLabelTable` corresponding to the labels required for each of the forward and reverse direction in- and out-segments. For the purpose of this example the forward and reverse labels on each interface will be the same, hence we need to create just two rows in the `gmplsLabelTable` - one for each interface.

```

In gmplsLabelTable:
{
    gmplsLabelInterface      = 12,
    gmplsLabelIndex          = 1,
    gmplsLabelSubindex       = 0,
    gmplsLabelType           = gmplsFreeformGeneralizedLabel(3),
    gmplsLabelFreeform       = 0x123456789ABCDEF0
    gmplsLabelRowStatus      = createAndGo(4)
}

```

```

In gmplsLabelTable:
{
    gmplsLabelInterface      = 13,
    gmplsLabelIndex          = 1,
    gmplsLabelSubindex       = 0,
    gmplsLabelType           = gmplsFreeformGeneralizedLabel(3),
    gmplsLabelFreeform       = 0xFEDCBA9876543210
    gmplsLabelRowStatus      = createAndGo(4)
}

```

We must next create the appropriate in-segment and out-segment entries. These are done in [\[RFC3813\]](#) using the `mplsInSegmentTable` and `mplsOutSegmentTable`. Note that we use a row pointer to the two rows in the `gmplsLabelTable` rather than specifying the labels explicitly in the in- and out-segment tables. Also note that the row status for each row is set to `createAndWait(5)` to allow corresponding entries in the `gmplsInSegmentTable` and `gmplsOutSegmentTable` to be created.

For the forward direction.

```

In mplsInSegmentTable:
{
    mplsInSegmentIndex      = 0x00000015
    mplsInSegmentLabel      = 0, -- incoming label in label table
    mplsInSegmentNPop       = 1,
    mplsInSegmentInterface  = 12, -- incoming interface
    -- RowPointer MUST point to the first accesible column.
    mplsInSegmentTrafficParamPtr = 0.0,
    mplsInSegmentLabelPtr   = gmplsLabelTable (12, 1, 0)
}

```

```

    mplsInSegmentRowStatus      = createAndWait(5)
}

```

```

In mplsOutSegmentTable:
{

```

```

mplsOutSegmentIndex      = 0x00000012,
mplsOutSegmentInterface  = 13, -- outgoing interface
mplsOutSegmentPushTopLabel = true(1),
mplsOutSegmentTopLabel   = 0, -- outgoing label in label table

-- RowPointer MUST point to the first accesible column.
mplsOutSegmentTrafficParamPtr = 0.0,
mplsOutSegmentLabelPtr       = gmplsLabelTable (13, 1, 0)
mplsOutSegmentRowStatus      = createAndWait(5)
}

```

For the reverse direction.

In mplsInSegmentTable:

```

{
  mplsInSegmentIndex      = 0x00000016

  mplsInSegmentLabel      = 0, -- incoming label in label table
  mplsInSegmentNPop       = 1,
  mplsInSegmentInterface  = 13, -- incoming interface

  -- RowPointer MUST point to the first accesible column.
  mplsInSegmentTrafficParamPtr = 0.0,
  mplsInSegmentLabelPtr     = gmplsLabelTable (13, 1, 0)

  mplsInSegmentRowStatus  = createAndWait(5)
}

```

In mplsOutSegmentTable:

```

{
  mplsOutSegmentIndex      = 0x00000013,
  mplsOutSegmentInterface  = 12, -- outgoing interface
  mplsOutSegmentPushTopLabel = true(1),
  mplsOutSegmentTopLabel   = 0, -- outgoing label in label table

  -- RowPointer MUST point to the first accesible column.
  mplsOutSegmentTrafficParamPtr = 0.0,
  mplsOutSegmentLabelPtr     = gmplsLabelTable (12, 1, 0)

  mplsOutSegmentRowStatus  = createAndWait(5)
}

```


These table entries are extended by entries in `gmplsInSegmentTable` and `gmplsOutSegmentTable`. Note that the nature of the 'extends' relationship is that the entry in `gmplsInSegmentTable` has the same index values as the entry in `mplsInSegmentTable`. Similarly, the entry in `gmplsOutSegmentTable` has the same index values as the entry in `mplsOutSegmentTable`.

First for the forward direction:

```
In gmplsInSegmentTable(0x00000015)
{
  gmplsInSegmentDirection      = forward (1)
}
```

```
In gmplsOutSegmentTable(0x00000012)
{
  gmplsOutSegmentDirection     = forward (1)
}
```

Next for the reverse direction:

```
In gmplsInSegmentTable(0x00000016)
{
  gmplsInSegmentDirection      = reverse (2)
}
```

```
In gmplsOutSegmentTable(0x00000013)
{
  gmplsOutSegmentDirection     = reverse (2)
}
```

Next, two cross-connect entries are created in the `mplsXCTable` of the MPLS LSR MIB, thereby associating the newly created segments together.

```
In mplsXCTable:
{
  mplsXCIndex                = 0x01,
  mplsXCInSegmentIndex       = 0x00000015,
  mplsXCOutSegmentIndex      = 0x00000012,
  mplsXCLspId                = 0x0102 -- unique ID
  mplsXCLabelStackIndex      = 0x00, -- only a single outgoing label
  mplsXCRowStatus            = createAndGo(4)
}
```

```
In mplsXCTable:
{
  mplsXCIndex                = 0x02,
```


;

gmplsLsrStdMIB MODULE-IDENTITY

LAST-UPDATED

"200505200001Z" -- 20 May 2005 00:00:01 GMT

ORGANIZATION

"Common Control And Measurement Plane (CCAMP) Working Group"

CONTACT-INFO

" Thomas D. Nadeau
 Cisco Systems, Inc.
Email: tnadeau@cisco.com

 Adrian Farrel
 Old Dog Consulting
Email: adrian@olddog.co.uk

Comments about this document should be emailed direct to the
CCAMP working group mailing list at ccamp@ops.ietf.org"

DESCRIPTION

"Copyright (C) The Internet Society (2005). The initial version
of this MIB module was published in RFC XXXX. For full legal
notices see the RFC itself or see:

<http://www.ietf.org/copyrights/ianamib.html>

This MIB module contains managed object definitions for the
Generalized Multiprotocol (GMPLS) Label Switching Router as
defined in: Generalized Multi-Protocol Label Switching (GMPLS)
Architecture, Mannie et al., [RFC 3945](#), October 2004."

-- Revision history.

REVISION

"200505200001Z" -- 20 May 2005 00:00:01 GMT

DESCRIPTION

-- RFC-editor please fill in XXXX and see IANA section

"Initial version issued as part of RFC XXXX."

```

 ::= { mplsStdMIB XXX }

-- Top level components of this MIB module.

-- Notifications
-- no notifications are currently defined.
gmplsLsrNotifications OBJECT IDENTIFIER ::= { gmplsLsrStdMIB 0 }

-- Tables, Scalars
gmplsLsrObjects          OBJECT IDENTIFIER ::= { gmplsLsrStdMIB 1 }

-- Conformance
gmplsLsrConformance     OBJECT IDENTIFIER ::= { gmplsLsrStdMIB 2 }

```

```

-- GMPLS Interface Table.

```

```

gmplsInterfaceTable OBJECT-TYPE
    SYNTAX          SEQUENCE OF GmplsInterfaceEntry
    MAX-ACCESS      not-accessible
    STATUS          current
    DESCRIPTION
        "This table specifies per-interface GMPLS capability and
        associated information. It extends the information in
        mplsInterfaceTable."
    ::= { gmplsLsrObjects 1 }

gmplsInterfaceEntry OBJECT-TYPE
    SYNTAX          GmplsInterfaceEntry
    MAX-ACCESS      not-accessible
    STATUS          current
    DESCRIPTION
        "A conceptual row in this table is created automatically by an
        LSR for every interface capable of supporting GMPLS and which
        is configured to do so. A conceptual row in this table will
        exist if and only if a corresponding entry in mplsInterfaceTable
        exists, and a corresponding entry in ifTable exists with
        ifType = mpls(166). If the associated entry in ifTable is
        operationally disabled (thus removing the GMPLS capabilities on
        the interface) or the entry in mplsInterfaceTable is deleted,
        the corresponding entry in this table MUST be deleted shortly
        thereafter.

```

The indexing is the same as that for `mplsInterfaceTable`. Thus, the entry with index 0 represents the per-platform label space and contains parameters that apply to all interfaces that participate in the per-platform label space."

```
INDEX { mplsInterfaceIndex }
 ::= { gmplsInterfaceTable 1 }

GmplsInterfaceEntry ::= SEQUENCE {
    gmplsInterfaceSignalingCaps    BITS,
    gmplsInterfaceRsvpHelloPeriod  Unsigned32
}
```

```
gmplsInterfaceSignalingCaps OBJECT-TYPE
    SYNTAX  BITS {
        unknown (0),
        rsvpGmpls (1),
        crldpGmpls (2), -- note the use of CR-LDP is deprecated
        otherGmpls (3)
    }
    MAX-ACCESS    read-create
    STATUS        current
    DESCRIPTION
        "Defines the signaling capabilities on this interface. Multiple
        bits may legitimately be set at once. Setting no bits implies
        that GMPLS signaling cannot be performed on this interface and
        all LSPs must be manually provisioned or that this table entry
        is only present to supplement an entry in the mplsInterfaceTable
        by providing the information carried in other objects in this
        row."
    DEFVAL { { rsvpGmpls } }
 ::= { gmplsInterfaceEntry 1 }
```

```

gmplsInterfaceRsvpHelloPeriod OBJECT-TYPE
    SYNTAX      Unsigned32
    UNITS       "milliseconds"
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "Period, in milliseconds, between sending RSVP Hello messages on
         this interface. A value of 0 indicates that no Hello messages
         should be sent on this interface."
    REFERENCE
        "Generalized MPLS Signaling - RSVP-TE Extensions, Berger, L.
         (Editor), RFC 3473, January 2003."
    DEFVAL { 3000 }
    ::= { gmplsInterfaceEntry 2 }

-- End of gmplsInterfaceTable

-- In-segment table.

```

```

gmplsInSegmentTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF GmplsInSegmentEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "This table extends the mplsInSegmentTable to provide
         GMPLS-specific information about incoming segments to an LSR."
    ::= { gmplsLsrObjects 2 }

```

```

gmplsInSegmentEntry OBJECT-TYPE
    SYNTAX      GmplsInSegmentEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "An entry in this table extends the representation of an incoming
         segment represented by an entry in mplsInSegmentTable. An entry
         can be created by a network administrator or an SNMP agent, or a
         GMPLS signaling protocol.

        Note that the storage type for this entry SHOULD be inherited
        from the corresponding entry in the mplsInSegmentTable given by
        the value of the mplsInSegmentStorageType object."

```

```

    INDEX { mplsInSegmentIndex }
 ::= { gmplsInSegmentTable 1 }

GmplsInSegmentEntry ::= SEQUENCE {
    gmplsInSegmentDirection      GmplsSegmentDirection,
    gmplsInSegmentExtraParamsPtr RowPointer
}

gmplsInSegmentDirection OBJECT-TYPE
    SYNTAX      GmplsSegmentDirection
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "This object indicates the direction of data flow on this
        segment. This object cannot be modified if
        mplsInSegmentRowStatus for the associated entry in the
        mplsInSegmentTable is active(1)."
```

```

    DEFVAL      { forward }
 ::= { gmplsInSegmentEntry 1 }

gmplsInSegmentExtraParamsPtr OBJECT-TYPE
    SYNTAX      RowPointer
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "Some Tunnels will run over transports that can usefully support
        technology-specific additional parameters (for example, SONET
        resource usage). Such can be supplied from an external table and
        referenced from here. A value of zeroDotzero in this attribute
        indicates that there is no such additional information."
```

```

    DEFVAL      { zeroDotZero }
 ::= { gmplsInSegmentEntry 2 }

-- End of gmplsInSegmentTable
```

```
-- Out-segment table.
```

```
gmplsOutSegmentTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF GmplsOutSegmentEntry
    MAX-ACCESS  not-accessible
    STATUS      current
```

DESCRIPTION

"This table extends the mplsOutSegmentTable to provide GMPLS-specific information about outgoing segments from an LSR."
 ::= { gmplsLsrObjects 3 }

gmplsOutSegmentEntry OBJECT-TYPE

SYNTAX GmplsOutSegmentEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"An entry in this table extends the representation of an outgoing segment represented by an entry in mplsOutSegmentTable. An entry can be created by a network administrator or an SNMP agent, or a GMPLS signaling protocol.

Note that the storage type for this entry SHOULD be inherited from the corresponding entry in the mplsOutSegmentTable given by the value of the mplsOutSegmentStorageType object."

INDEX { mplsOutSegmentIndex }

::= { gmplsOutSegmentTable 1 }

GmplsOutSegmentEntry ::= SEQUENCE {

gmplsOutSegmentDirection GmplsSegmentDirection,

gmplsOutSegmentTTLDecrement Unsigned32,

gmplsOutSegmentExtraParamsPtr RowPointer

}

gmplsOutSegmentDirection OBJECT-TYPE

SYNTAX GmplsSegmentDirection

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"This object indicates the direction of data flow on this segment. This object cannot be modified if mplsOutSegmentRowStatus for the associated entry in the mplsOutSegmentTable is active(1)."

DEFVAL { forward }

::= { gmplsOutSegmentEntry 1 }

gmplsOutSegmentTTLDecrement OBJECT-TYPE

SYNTAX Unsigned32 (0..255)

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"This object indicates the amount by which to decrement the TTL of any payload packets forwarded on this segment if per-hop decrementing is being done.

A value of zero indicates that no decrement should be made or that per-hop decrementing is not in force.

See the gmplsTunnelTTLDecrement object in the gmplsTunnelTable of [[GMPLSTEMIB](#)] for a value by which to decrement the TTL for the whole of a tunnel.

This object cannot be modified if mplsOutSegmentRowStatus for the associated entry in the mplsOutSegmentTable is active(1)."

REFERENCE

"Time To Live (TTL) Processing in Multi-Protocol Label Switching (MPLS) Networks, Agarwal, P., Akyol, B., [RFC 3443](#), January 2003"

DEFVAL { 0 }

::= { gmplsOutSegmentEntry 2 }

gmplsOutSegmentExtraParamsPtr OBJECT-TYPE

SYNTAX RowPointer

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"Some Tunnels will run over transports that can usefully support technology-specific additional parameters (for example, SONET resource usage). Such can be supplied from an external table and referenced from here.

A value of zeroDotzero in this attribute indicates that there is no such additional information."

DEFVAL { zeroDotZero }

::= { gmplsOutSegmentEntry 3 }

-- End of gmplsOutSegmentTable

-- Module compliance.

gmplsLsrGroups

OBJECT IDENTIFIER ::= { gmplsLsrConformance 1 }

gmplsLsrCompliances

OBJECT IDENTIFIER ::= { gmplsLsrConformance 2 }

Internet Draft

[draft-ietf-ccamp-gmpls-lsr-mib-08.txt](#)

June 2005

```
-- Compliance requirement for fully compliant implementations.
```

```
gmplsLsrModuleFullCompliance MODULE-COMPLIANCE
```

```
STATUS current
```

```
DESCRIPTION
```

```
"Compliance statement for agents that provide full support for  
GMPLS-LSR-STD-MIB."
```

```
MODULE IF-MIB -- The Interfaces Group MIB, RFC 2863.
```

```
MANDATORY-GROUPS {
```

```
  ifGeneralInformationGroup,  
  ifCounterDiscontinuityGroup
```

```
}
```

```
MODULE MPLS-LSR-STD-MIB -- The MPLS LSR MIB
```

```
MANDATORY-GROUPS {
```

```
  mplsInterfaceGroup,  
  mplsInSegmentGroup,  
  mplsOutSegmentGroup,  
  mplsXCGroup,  
  mplsPerfGroup,  
  mplsLsrNotificationGroup
```

```
}
```

```
MODULE -- this module
```

```
MANDATORY-GROUPS {
```

```
  gmplsInterfaceGroup,  
  gmplsInSegmentGroup,  
  gmplsOutSegmentGroup
```

```
}
```

```
-- gmplsInSegmentTable
```

```
OBJECT gmplsInSegmentDirection
```

```
SYNTAX GmplsSegmentDirection
```

```
MIN-ACCESS read-write
```

```
DESCRIPTION
```

```
"Only forward(1) needs to be supported by implementations that  
only support unidirectional LSPs."
```

-- gmplsOutSegmentTable

OBJECT gmplsOutSegmentDirection

SYNTAX GmplsSegmentDirection

MIN-ACCESS read-write

DESCRIPTION

"Only forward(1) needs to be supported by implementations that only support unidirectional LSPs."

Nadeau and Farrel (Editors)

[Page 16]

Internet Draft

[draft-ietf-ccamp-gmpls-lsr-mib-08.txt](#)

June 2005

OBJECT gmplsOutSegmentTTLDecrement

SYNTAX Unsigned32 (0..255)

MIN-ACCESS read-only

DESCRIPTION

"Write access is not required."

::= { gmplsLsrCompliances 1 }

-- Compliance requirement for implementations that provide read-only
-- access.

gmplsLsrModuleReadOnlyCompliance MODULE-COMPLIANCE

STATUS current

DESCRIPTION

"Compliance requirement for implementations that only provide read-only support for GMPLS-LSR-STD-MIB. Such devices can then be monitored but cannot be configured using this MIB modules."

MODULE IF-MIB -- The interfaces Group MIB, [RFC 2863](#)

MANDATORY-GROUPS {

ifGeneralInformationGroup,

ifCounterDiscontinuityGroup

}

MODULE MPLS-LSR-STD-MIB

MANDATORY-GROUPS {

mplsInterfaceGroup,

mplsInSegmentGroup,

mplsOutSegmentGroup,

mplsXCGroup,

mplsPerfGroup

}

MODULE -- this module

```
MANDATORY-GROUPS {
    gmplsInterfaceGroup,
    gmplsInSegmentGroup,
    gmplsOutSegmentGroup
}
```

```
-- gmplsInterfaceGroup
```

```
OBJECT      gmplsInterfaceSignalingCaps
SYNTAX     BITS {
    unknown (0),
    rsvpGmpls (1),
    crldpGmpls (2),
    otherGmpls (3)
}
MIN-ACCESS  read-only
DESCRIPTION
    "Write access is not required."
```

```
OBJECT      gmplsInterfaceRsvpHelloPeriod
SYNTAX      Unsigned32
MIN-ACCESS  read-only
DESCRIPTION
    "Write access is not required."
```

```
-- gmplsInSegmentTable
```

```
OBJECT      gmplsInSegmentDirection
SYNTAX      GmplsSegmentDirection
MIN-ACCESS  read-only
DESCRIPTION
    "Write access is not required. Only forward(1) needs to be
    supported by implementations that only support unidirectional
    LSPs."
```

OBJECT gmplsInSegmentExtraParamsPtr
SYNTAX RowPointer
MIN-ACCESS read-only
DESCRIPTION

"Write access is not required."

-- gmplsOutSegmentTable

OBJECT gmplsOutSegmentDirection
SYNTAX GmplsSegmentDirection
MIN-ACCESS read-only
DESCRIPTION

"Write access is not required. Only forward(1) needs to be supported by implementations that only support unidirectional LSPs."

OBJECT gmplsOutSegmentTTLDcrement
SYNTAX Unsigned32 (0..255)
MIN-ACCESS read-only
DESCRIPTION

"Write access is not required."

OBJECT gmplsOutSegmentExtraParamsPtr
SYNTAX RowPointer
MIN-ACCESS read-only
DESCRIPTION

"Write access is not required."

::= { gmplsLsrCompliances 2 }

-- Units of conformance.

gmplsInterfaceGroup OBJECT-GROUP
OBJECTS {
 gmplsInterfaceSignalingCaps,
 gmplsInterfaceRsvpHelloPeriod
}
STATUS current
DESCRIPTION

"Collection of objects needed for GMPLS interface configuration and performance information."

::= { gmplsLsrGroups 1 }

gmplsInSegmentGroup OBJECT-GROUP

```

OBJECTS {
    gmplsInSegmentDirection,
    gmplsInSegmentExtraParamsPtr
}
STATUS current
DESCRIPTION
    "Collection of objects needed to implement a GMPLS
    in-segment."
::= { gmplsLsrGroups 2 }

gmplsOutSegmentGroup OBJECT-GROUP
OBJECTS {
    gmplsOutSegmentDirection,
    gmplsOutSegmentTTLDcrement,
    gmplsOutSegmentExtraParamsPtr
}
STATUS current
DESCRIPTION
    "Collection of objects needed to implement a GMPLS out-segment."
::= { gmplsLsrGroups 3 }
END

```

8. GMPLS Label MIB Definitions

```
GMPLS-LABEL-STD-MIB DEFINITIONS ::= BEGIN
```

IMPORTS

```

MODULE-IDENTITY, OBJECT-TYPE, Unsigned32,
Integer32
    FROM SNMPv2-SMI                    -- RFC2578
MODULE-COMPLIANCE, OBJECT-GROUP
    FROM SNMPv2-CONF                 -- RFC2580
RowStatus, StorageType
    FROM SNMPv2-TC                    -- RFC2579
InterfaceIndexOrZero
    FROM IF-MIB                        -- RFC2863
IndexIntegerNextFree

```

```
FROM DIFFSERV-MIB -- RFC3289
MplsLabel
FROM MPLS-TC-STD-MIB -- RFC3811
GmplsGeneralizedLabelTypes, GmplsFreeformLabel
FROM GMPLS-TC-STD-MIB -- GMPLSTCMIB
-- RFC-Editor please resolve the reference above
mplsStdMIB
FROM MPLS-TC-STD-MIB -- RFC3811
;
```

gmplsLabelStdMIB MODULE-IDENTITY

LAST-UPDATED

"200505200001Z" -- 20 May 2005 00:00:01 GMT

ORGANIZATION

"Common Control And Measurement Plane (CCAMP) Working Group"

CONTACT-INFO

" Thomas D. Nadeau
Cisco Systems, Inc.
Email: tnadeau@cisco.com

Adrian Farrel
Old Dog Consulting
Email: adrian@olddog.co.uk

Comments about this document should be emailed direct to the
CCAMP working group mailing list at ccamp@ops.ietf.org"

DESCRIPTION

"Copyright (C) The Internet Society (2005). The initial version
of this MIB module was published in RFC YYYY. For full legal
notices see the RFC itself or see:

<http://www.ietf.org/copyrights/ianamib.html>

This MIB module contains managed object definitions for labels
within GMPLS systems as defined in:

Nadeau and Farrel (Editors)

[Page 20]

Internet Draft

[draft-ietf-ccamp-gmpls-lsr-mib-08.txt](#)

June 2005

Generalized Multi-Protocol Label Switching (GMPLS) Signaling
Functional Description, Berger, L. (Editor), [RFC 3471](#),
January 2003."

-- Revision history.

REVISION

"200505200001Z" -- 20 May 2005 00:00:01 GMT

DESCRIPTION

```

-- RFC-editor please fill in YYYY and see IANA section
"Initial version issued as part of RFC YYYY."
 ::= { mplsStdMIB YYY }

-- Top level components of this MIB module.

-- Notifications
-- no notifications are currently defined.
gmplsLabelNotifications OBJECT IDENTIFIER ::= { gmplsLabelStdMIB 0 }

-- Tables, Scalars
gmplsLabelObjects          OBJECT IDENTIFIER ::= { gmplsLabelStdMIB 1 }

-- Conformance
gmplsLabelConformance     OBJECT IDENTIFIER ::= { gmplsLabelStdMIB 2 }

-- GMPLS Label Table.

gmplsLabelIndexNext OBJECT-TYPE
SYNTAX          IndexIntegerNextFree
MAX-ACCESS     read-only
STATUS         current
DESCRIPTION
    "This object contains an unused value for gmplsLabelIndex,
    or a zero to indicate that no unused value exists or is
    available.
    A management application wishing to create a row in the
    gmplsLabelTable may read this object and then attempt to
    create a row in the table. If row creation fails (because
    another application has already created a row with the
    supplied index) the management application should read this
    object again to get a new index value.

    When a row is created in the gmplsLabelTable with the
    gmplsLabelIndex value held by this object, an implementation
    MUST change the value in this object."
 ::= { gmplsLabelObjects 1 }

```


SYNTAX SEQUENCE OF GmplsLabelEntry
MAX-ACCESS not-accessible
STATUS current

DESCRIPTION

"Table of GMPLS Labels. This table allows the representation of the more complex label forms required for GMPLS which cannot be held within the textual convention MplsLabel. That is labels that cannot be encoded within 32 bits. It is, nevertheless also capable of holding 32 bit labels or regular MPLS labels if desired.

Each entry in this table represents an individual GMPLS label value. Labels in the tables in other MIBs are referred to using row pointer into this table. The indexing of this table provides for arbitrary indexing and also for concatenation of labels."

::= { gmplsLabelObjects 2 }

gmplsLabelEntry OBJECT-TYPE

SYNTAX GmplsLabelEntry
MAX-ACCESS not-accessible
STATUS current

DESCRIPTION

"An entry in this table represents a single label value. There are three indexes into the table.

- The interface index may be helpful to distinguish which labels are in use on which interfaces or to handle cases where there are a very large number of labels in use in the system. When label representation is desired to apply to the whole system or when it is not important to distinguish labels by their interfaces, this index MAY be set to zero.
- The label index provides a way of identifying the label.
- The label sub-index is only used for concatenated labels. It identifies each component label. When non-concatenated labels are used, this index SHOULD be set to zero.

A storage type object is supplied to control the storage type for each entry, but implementations should note that the storage type of conceptual rows in other tables that include row pointers to an entry in this table SHOULD dictate the storage type of the rows in this table where the row in the other table is more persistent."

INDEX {
 gmplsLabelInterface,
 gmplsLabelIndex,
 gmplsLabelSubindex }

::= { gmplsLabelTable 1 }

Internet Draft [draft-ietf-ccamp-gmpls-lsr-mib-08.txt](#)

June 2005

```
GmplsLabelEntry ::= SEQUENCE {
    gmplsLabelInterface      InterfaceIndexOrZero,
    gmplsLabelIndex          Unsigned32,
    gmplsLabelSubindex       Unsigned32,
    gmplsLabelType           GmplsGeneralizedLabelTypes,
    gmplsLabelMplsLabel      MplsLabel,
    gmplsLabelPortWavelength Unsigned32,
    gmplsLabelFreeform       GmplsFreeformLabel,
    gmplsLabelSonetSdhSignalIndex Integer32,
    gmplsLabelSdhVc          Integer32,
    gmplsLabelSdhVcBranch    Integer32,
    gmplsLabelSonetSdhBranch Integer32,
    gmplsLabelSonetSdhGroupBranch Integer32,
    gmplsLabelWavebandId     Unsigned32,
    gmplsLabelWavebandStart  Unsigned32,
    gmplsLabelWavebandEnd    Unsigned32,
    gmplsLabelRowStatus      RowStatus,
    gmplsLabelStorageType    StorageType
}
```

gmplsLabelInterface OBJECT-TYPE

SYNTAX InterfaceIndexOrZero

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The interface on which this label is used. If the label has or could have applicability across the whole system, this object SHOULD be set to zero."

::= { gmplsLabelEntry 1 }

gmplsLabelIndex OBJECT-TYPE

SYNTAX Unsigned32 (0..4294967295)

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"An arbitrary index into the table to identify a label.

Note that implementations that are representing 32 bit labels within this table MAY choose to align this index with the value of the label, but should be aware of the implications of sparsely populated tables.

A management application may read the gmplsLabelIndexNext object to find a suitable value for this object."

```
::= { gmplsLabelEntry 2 }
```

gmplsLabelSubindex OBJECT-TYPE

SYNTAX Unsigned32 (0..4294967295)

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"In conjunction with gmplsLabelInterface and gmplsLabelIndex, this object uniquely identifies this row. This sub-index allows a single GMPLS label to be defined as a concatenation of labels. This is particularly useful in TDM.

The ordering of sub-labels is strict with the sub-label with lowest gmplsLabelSubindex appearing first. Note that all sub-labels of a single GMPLS label must share the same gmplsLabelInterface and gmplsLabelIndex values. For labels that are not composed of concatenated sub-labels, this value SHOULD be set to zero."

```
::= { gmplsLabelEntry 3 }
```

gmplsLabelType OBJECT-TYPE

SYNTAX GmplsGeneralizedLabelTypes

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"Identifies the type of this label. Note that this object does not determine whether MPLS or GMPLS signaling is in use: a value of gmplsMplsLabel (1) denotes that a 23 bit MPLS packet label is present, but does not describe whether this is signaled using MPLS or GMPLS.

The value of this object helps determine which of the following objects are valid. This object cannot be modified if gmplsLabelRowStatus is active(1)."

REFERENCE

"Generalized Multi-Protocol Label Switching (GMPLS) Signaling Functional Description, Berger, L. (Editor), [RFC 3471](#), January 2003."

```
::= { gmplsLabelEntry 4 }
```

Internet Draft [draft-ietf-ccamp-gmpls-lsr-mib-08.txt](#)

June 2005

`gmplsLabelMplsLabel OBJECT-TYPE`

```
SYNTAX      MplsLabel
MAX-ACCESS  read-create
STATUS      current
```

`DESCRIPTION`

"The value of an MPLS label (that is a packet label) if this table is used to store it. This may be used in MPLS systems even though the label values can be adequately stored in the MPLS MIB modules. Further, in mixed MPLS and GMPLS systems it may be advantageous to store all labels in a single label table. Lastly, in GMPLS systems where packet labels are used (that is in systems that use GMPLS signaling and GMPLS labels for packet switching) it may be desirable to use this table.

This object is only valid if `gmplsLabelType` is set to `gmplsMplsLabel` (1). This object cannot be modified if `gmplsLabelRowStatus` is active(1)."

`REFERENCE`

"MPLS Label Stack Encoding, Rosen, E. et al, [RFC 3032](#), January 2001."

```
DEFVAL      { 0 }
```

```
::= { gmplsLabelEntry 6 }
```

`gmplsLabelPortWavelength OBJECT-TYPE`

```
SYNTAX      Unsigned32
MAX-ACCESS  read-create
STATUS      current
```

`DESCRIPTION`

"The value of a Port or Wavelength Label when carried as a Generalized Label. Only valid if `gmplsLabelType` is set to

gmplsPortWavelengthLabel(2). This object cannot be modified if gmplsLabelRowStatus is active(1)."

REFERENCE

"Generalized Multi-Protocol Label Switching (GMPLS) Signaling Functional Description, Berger, L. (Editor), [RFC 3471](#), January 2003."

DEFVAL { 0 }

::= { gmplsLabelEntry 7 }

gmplsLabelFreeform OBJECT-TYPE

SYNTAX GmplsFreeformLabel

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The value of a freeform Generalized Label that does not conform to one of the standardized label encoding or that an implementation chooses to represent as an octet string without further decoding. Only valid if gmplsLabelType is set to gmplsFreeformGeneralizedLabel(3). This object cannot be modified if gmplsLabelRowStatus is active(1)."

::= { gmplsLabelEntry 8 }

Nadeau and Farrel (Editors)

[Page 25]

Internet Draft

[draft-ietf-ccamp-gmpls-lsr-mib-08.txt](#)

June 2005

gmplsLabelSonetSdhSignalIndex OBJECT-TYPE

SYNTAX Integer32 (0..4095)

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The Signal Index value (S) of a SONET or SDH Generalized Label. Zero indicates that this field is not significant. Only valid if gmplsLabelType is set to gmplsSonetLabel(4) or gmplsSdhLabel(5). This object cannot be modified if gmplsLabelRowStatus is active(1)."

REFERENCE

"Generalized Multi-Protocol Label Switching Extensions for SONET and SDH Control, Mannie, E., Papadimitriou, D. (Editors), [draft-ietf-ccamp-gmpls-sonet-sdh](#), work in progress."

DEFVAL { 0 }

::= { gmplsLabelEntry 9 }

gmplsLabelSdhVc OBJECT-TYPE

SYNTAX Integer32 (0..15)

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The VC Indicator (U) of an SDH Generalized Label. Zero indicates

that this field is non-significant.
Only valid if gmplsLabelType is set to gmplsSdhLabel(5).
This object cannot be modified if gmplsLabelRowStatus is active(1)."

REFERENCE

"Generalized Multi-Protocol Label Switching Extensions for SONET and SDH Control, Mannie, E., Papadimitriou, D. (Editors), [draft-ietf-ccamp-gmpls-sonet-sdh](#), work in progress."

DEFVAL { 0 }

::= { gmplsLabelEntry 10 }

gmplsLabelSdhVcBranch OBJECT-TYPE

SYNTAX Integer32 (0..15)

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The VC Branch Indicator (K) of an SDH Generalized Label. Zero indicates that this field is non-significant.

Only valid if gmplsLabelType is set to gmplsSdhLabel(5). This object cannot be modified if gmplsLabelRowStatus is active(1)."

REFERENCE

"Generalized Multi-Protocol Label Switching Extensions for SONET and SDH Control, Mannie, E., Papadimitriou, D. (Editors), [draft-ietf-ccamp-gmpls-sonet-sdh](#), work in progress."

DEFVAL { 0 }

::= { gmplsLabelEntry 11 }

gmplsLabelSonetSdhBranch OBJECT-TYPE

SYNTAX Integer32 (0..15)

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The Branch Indicator (L) of a SONET or SDH Generalized Label. Zero indicates that this field is non-significant.

Only valid if gmplsLabelType is set to gmplsSonetLabel(4) or gmplsSdhLabel(5). This object cannot be modified if gmplsLabelRowStatus is active(1)."

REFERENCE

"Generalized Multi-Protocol Label Switching Extensions for SONET and SDH Control, Mannie, E., Papadimitriou, D. (Editors), [draft-ietf-ccamp-gmpls-sonet-sdh](#), work in progress."

DEFVAL { 0 }

::= { gmplsLabelEntry 12 }

gmplsLabelSonetSdhGroupBranch OBJECT-TYPE

SYNTAX Integer32 (0..15)

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The Group Branch Indicator (M) of a SONET or SDH Generalized Label.

Zero indicates that this field is non-significant.

Only valid if gmplsLabelType is set to gmplsSonetLabel(4) or gmplsSdhLabel(5). This object cannot be modified if gmplsLabelRowStatus is active(1)."

REFERENCE

"Generalized Multi-Protocol Label Switching Extensions for SONET and SDH Control, Mannie, E., Papadimitriou, D. (Editors), [draft-ietf-ccamp-gmpls-sonet](#), work in progress."

DEFVAL { 0 }

::= { gmplsLabelEntry 13 }

gmplsLabelWavebandId OBJECT-TYPE

SYNTAX Unsigned32

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The waveband identifier component of a waveband label. Only valid if gmplsLabelType is set to gmplsWavebandLabel(6). This object cannot be modified if gmplsLabelRowStatus is active(1)."

REFERENCE

"Generalized Multi-Protocol Label Switching (GMPLS) Signaling Functional Description, Berger, L. (Editor), [RFC 3471](#), January 2003."

DEFVAL { 0 }

::= { gmplsLabelEntry 14 }

gmplsLabelWavebandStart OBJECT-TYPE

SYNTAX Unsigned32

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The starting label component of a waveband label.

Only valid if gmplsLabelType is set to gmplsWavebandLabel(6).

This object cannot be modified if gmplsLabelRowStatus is active(1)."

REFERENCE

"Generalized Multi-Protocol Label Switching (GMPLS) Signaling Functional Description, Berger, L. (Editor), [RFC 3471](#), January 2003."

DEFVAL { 0 }

::= { gmplsLabelEntry 15 }

gmplsLabelWavebandEnd OBJECT-TYPE

SYNTAX Unsigned32

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The end label component of a waveband label. Only valid if gmplsLabelType is set to gmplsWavebandLabel(6). This object cannot be modified if gmplsLabelRowStatus is active(1)."

REFERENCE

"Generalized Multi-Protocol Label Switching (GMPLS) Signaling Functional Description, Berger, L. (Editor), [RFC 3471](#), January 2003."

DEFVAL { 0 }

::= { gmplsLabelEntry 16 }

gmplsLabelRowStatus OBJECT-TYPE

SYNTAX RowStatus

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"This variable is used to create, modify, and/or delete a row in this table. When a row in this table has a row in the active(1) state, no objects in this row can be modified except the gmplsLabelRowStatus and gmplsLabelStorageType."

::= { gmplsLabelEntry 17 }

gmplsLabelStorageType OBJECT-TYPE

SYNTAX StorageType


```

MAX-ACCESS      read-create
STATUS          current
DESCRIPTION
    "This variable indicates the storage type for this object. The
    agent MUST ensure that this object's value remains consistent
    with the storage type of any rows in other tables that contain
    pointers to this row. In particular, the storage type of this
    row must be at least as permanent as that of any row that point
    to it.

    Conceptual rows having the value 'permanent' need not
    allow write-access to any columnar objects in the row."
REFERENCE
    "See RFC2579."
DEFVAL { volatile }
::= { gmplsLabelEntry 18 }

-- End of GMPLS Label Table

-- Module compliance.

gmplsLabelGroups
    OBJECT IDENTIFIER ::= { gmplsLabelConformance 1 }

gmplsLabelCompliances
    OBJECT IDENTIFIER ::= { gmplsLabelConformance 2 }

gmplsLabelModuleROCompliance MODULE-COMPLIANCE
    STATUS current
    DESCRIPTION
        "Compliance requirement for implementations that only
        provide read-only support for GMPLS-LABEL-STD-MIB. Such
        devices can then be monitored but cannot be configured
        using this MIB modules."

    MODULE -- this module

    -- The mandatory groups have to be implemented by LSRs claiming
    -- support for this MIB module. This MIB module is, however, not
    -- mandatory for a working implementation of a GMPLS LSR with full
    -- MIB support if the GMPLS labels in use can be represented within
    -- a 32 bit quantity.

    MANDATORY-GROUPS {
        gmplsLabelTableGroup
    }

```

-- Units of conformance.

GROUP gmplsLabelTableGroup

DESCRIPTION

"This group is mandatory for devices which support the gmplsLabelTable."

GROUP gmplsLabelPacketGroup

DESCRIPTION

"This group extends gmplsLabelTableGroup for implementations that support packet labels."

GROUP gmplsLabelPortWavelengthGroup

DESCRIPTION

"This group extends gmplsLabelTableGroup for implementations that support port and wavelength labels."

GROUP gmplsLabelFreeformGroup

DESCRIPTION

"This group extends gmplsLabelTableGroup for implementations that support freeform labels."

GROUP gmplsLabelSonetSdhGroup

DESCRIPTION

"This group extends gmplsLabelTableGroup for implementations that support SONET or SDH labels."

GROUP gmplsLabelWavebandGroup

DESCRIPTION

"This group extends gmplsLabelTableGroup for implementations that support Waveband labels."

-- gmplsLabelTable

OBJECT gmplsLabelType

MIN-ACCESS read-only

DESCRIPTION

"Write access is not required."

OBJECT gmplsLabelMplsLabel

MIN-ACCESS read-only

DESCRIPTION

"Write access is not required."

OBJECT gmplsLabelPortWavelength

MIN-ACCESS read-only

DESCRIPTION

"Write access is not required."

OBJECT gmplsLabelFreeform
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT gmplsLabelSonetSdhSignalIndex
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT gmplsLabelSdhVc
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT gmplsLabelSdhVcBranch
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT gmplsLabelSonetSdhBranch
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT gmplsLabelSonetSdhGroupBranch
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT gmplsLabelWavebandId
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT gmplsLabelWavebandStart
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT gmplsLabelWavebandEnd
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT gmplsLabelRowStatus
SYNTAX RowStatus {
active(1),
notInService(2)
}

Nadeau and Farrel (Editors)

[Page 31]

Internet Draft [draft-ietf-ccamp-gmpls-lsr-mib-08.txt](#)

June 2005

WRITE-SYNTAX RowStatus {
active(1),
notInService(2),
createAndGo(4),
destroy(6)
}

DESCRIPTION
"Support for notInService, createAndWait and notReady is not required."

OBJECT gmplsLabelStorageType
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

::= { gmplsLabelCompliances 1 }

gmplsLabelModuleFullCompliance MODULE-COMPLIANCE

STATUS current

DESCRIPTION

"Compliance statement for agents that support the complete GMPLS Label MIB module."

MODULE -- this module

-- The mandatory groups have to be implemented by GMPLS LSRs
-- claiming support for this MIB module. This MIB module is,
-- however, not mandatory for a working implementation of a GMPLS
-- LSR with full MIB support if the GMPLS labels in use can be
-- represented within a 32 bit quantity.

MANDATORY-GROUPS {
gmplsLabelTableGroup,

```
    gmplsLabelPacketGroup,  
    gmplsLabelPortWavelengthGroup,  
    gmplsLabelFreeformGroup,  
    gmplsLabelSonetSdhGroup,  
    gmplsLabelWavebandGroup  
}
```

```
OBJECT      gmplsLabelRowStatus  
SYNTAX      RowStatus { active(1), notInService(2) }  
WRITE-SYNTAX RowStatus { active(1), notInService(2),  
                        createAndGo(4), destroy(6)  
}
```

```
DESCRIPTION  
    "Support for notInService, createAndWait and notReady is not  
    required."
```

```
::= { gmplsLabelCompliances 2 }
```

```
-- Units of conformance.
```

```
gmplsLabelTableGroup OBJECT-GROUP  
OBJECTS {  
    gmplsLabelIndexNext,  
    gmplsLabelType,  
    gmplsLabelRowStatus,  
    gmplsLabelStorageType  
}
```

```
STATUS current
```

```
DESCRIPTION
```

```
"Necessary, but not sufficient, set of objects to implement label  
table support. In addition, depending on the type of labels  
supported (for example, wavelength labels), the following other  
groups defined below are mandatory:
```

```
    gmplsLabelPacketGroup and/or  
    gmplsLabelPortWavelengthGroup and/or  
    gmplsLabelFreeformGroup and/or  
    gmplsLabelSonetSdhGroup."
```

```
::= { gmplsLabelGroups 1 }
```

```
gmplsLabelPacketGroup OBJECT-GROUP  
OBJECTS {  
    gmplsLabelMplsLabel  
}
```

```

STATUS current
DESCRIPTION
  "Object needed to implement Packet (MPLS) labels."
 ::= { gmplsLabelGroups 2 }

gmplsLabelPortWavelengthGroup OBJECT-GROUP
  OBJECTS {
    gmplsLabelPortWavelength
  }
  STATUS current
  DESCRIPTION
    "Object needed to implement Port and Wavelength labels."
 ::= { gmplsLabelGroups 3 }

gmplsLabelFreeformGroup OBJECT-GROUP
  OBJECTS {
    gmplsLabelFreeform
  }
  STATUS current
  DESCRIPTION
    "Object needed to implement Freeform labels."
 ::= { gmplsLabelGroups 4 }

```

```

gmplsLabelSonetSdhGroup OBJECT-GROUP
  OBJECTS {
    gmplsLabelSonetSdhSignalIndex,
    gmplsLabelSdhVc,
    gmplsLabelSdhVcBranch,
    gmplsLabelSonetSdhBranch,
    gmplsLabelSonetSdhGroupBranch
  }
  STATUS current
  DESCRIPTION
    "Object needed to implement SONET and SDH labels."
 ::= { gmplsLabelGroups 5 }

gmplsLabelWavebandGroup OBJECT-GROUP
  OBJECTS {
    gmplsLabelWavebandId,
    gmplsLabelWavebandStart,
    gmplsLabelWavebandEnd
  }

```

```
STATUS current
DESCRIPTION
  "Object needed to implement Waveband labels."
 ::= { gmplsLabelGroups 6 }
END
```

9. Security Considerations

It is clear that the MIB modules described in this document in association with the MPLS-LSR-STD-MIB are potentially useful for monitoring of GMPLS LSRs. These MIB modules can also be used for configuration of certain objects, and anything that can be configured can be incorrectly configured, with potentially disastrous results.

There are a number of management objects defined in these MIB modules with a MAX-ACCESS clause of read-write and/or read-create. Such objects may be considered sensitive or vulnerable in some network environments. The support for SET operations in a non-secure

environment without proper protection can have a negative effect on network operations. These are the tables and objects and their sensitivity/vulnerability:

- o the gmplsInterfaceTable, gmplsInSegmentTable, gmplsOutSegmentTable and gmplsLabelTable collectively contain objects to provision GMPLS interfaces, LSPs and their associated parameters on a Label Switching Router (LSR). Unauthorized write access to objects in these tables, could result in disruption of traffic on the network. This is especially true if an LSP has already been established. The use of stronger mechanisms such as SNMPv3 security should be considered where possible. Specifically, SNMPv3 VACM and USM MUST be used with any SNMPv3 agent which implements these MIB modules.

Some of the readable objects in these MIB modules "i.e., objects with a MAX-ACCESS other than not-accessible" may be considered sensitive or vulnerable in some network environments. It is thus important to control even GET and/or NOTIFY access to these objects and possibly to even encrypt the values of these objects when sending them over the network via SNMP. These are the tables and objects and their sensitivity/vulnerability:

- o the gmplsInterfaceTable, gmplsInSegmentTable, gmplsOutSegmentTable and gmplsLabelTable collectively show the LSP network topology and its capabilities. If an Administrator does not want to reveal this information, then these tables should be considered sensitive/vulnerable.

SNMP versions prior to SNMPv3 did not include adequate security. Even if the network itself is secure "for example by using IPsec", even then, there is no control as to who on the secure network is allowed to access and GET/SET "read/change/create/delete" the objects in these MIB modules. It is RECOMMENDED that implementers consider the security features as provided by the SNMPv3 framework "see [\[RFC3410\]](#), [section 8](#)", including full support for the SNMPv3 cryptographic mechanisms "for authentication and privacy".

Further, deployment of SNMP versions prior to SNMPv3 is NOT RECOMMENDED. Instead, it is RECOMMENDED to deploy SNMPv3 and to enable cryptographic security. It is then a customer/operator responsibility to ensure that the SNMP entity giving access to an instance of this MIB module, is properly configured to give access to

the objects only to those principals "users" that have legitimate rights to indeed GET or SET "change/create/delete" them.

10. Acknowledgments

This draft is the work of the five authors listed in the Authors' Addresses section.

This document extends [[RFC3813](#)]. The authors would like to express their gratitude to all those who worked on that earlier MIB document.

The authors would like to express their thanks to Dan Joyle for his careful review and comments on early versions of the Label Table. Special thanks to Joan Cucchiara and Len Nieman for their help with compilation issues. Tom Petch provided useful input in the final stages of review.

11. IANA Considerations

MPLS related standards track MIB modules are rooted under the mplsStdMIB subtree.

One of the MIB modules contained in this document extends tables contained in MPLS MIB modules.

The two MIB modules contained in this document, like that in GMPLS-TC-STD-MIB [[GMPLSTCMIB](#)], should be placed in the mplsStdMIB subtree.

New assignments in the mplsStdMIB subtree can only be made via a Standards Action as specified in [[RFC2434](#)].

11.1. IANA Considerations for GMPLS-LSR-STD-MIB

The IANA is requested to assign { mplsStdMIB XXX } to the GMPLS-LSR-STD-MIB module specified in this document.

11.2. IANA Considerations for GMPLS-LABEL-STD-MIB

The IANA is requested to assign { mplsStdMIB YYY } to the GMPLS-LABEL-STD-MIB module specified in this document.

[12.](#) References

[12.1.](#) Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC2578] McCloghrie, K., Perkins, D., Schoenwaelder, J., Case, J., Rose, M., and S. Waldbusser, "Structure of Management Information Version 2 (SMIv2)", STD 58, [RFC 2578](#), April 1999.
- [RFC2579] McCloghrie, K., Perkins, D., Schoenwaelder, J., Case, J., Rose, M., and S. Waldbusser, "Textual Conventions for SMIv2", STD 58, [RFC 2579](#), April 1999.
- [RFC2580] McCloghrie, K., Perkins, D., Schoenwaelder, J., Case, J., Rose, M., and S. Waldbusser, "Conformance Statements for SMIv2", STD 58, [RFC 2580](#), April 1999.
- [RFC2863] McCloghrie, K. and F. Kastenholz, "The Interfaces Group MIB", [RFC 2863](#), June 2000.
- [RFC3289] Baker, F., Chan, K., and A. Smith, "Management Information Base for the Differentiated Services Architecture", [RFC 3289](#), May 2002.
- [RFC3443] Agarwal, P. and Akyol, B., "Time To Live (TTL) Processing in Multi-Protocol Label Switching (MPLS) Networks", [RFC 3443](#), January 2003.
- [RFC3811] Nadeau, T. and J. Cucchiara, "Definition of Textual Conventions and for Multiprotocol Label Switching (MPLS) Management", [RFC 3811](#), June 2004.
- [RFC3813] Srinivasan, C., Viswanathan, A., and T. Nadeau, "Multiprotocol Label Switching (MPLS) Label Switching (LSR) Router Management Information Base (MIB)", [RFC 3813](#), June 2004.
- [RFC3945] Mannie, E. (Editor), "Generalized Multiprotocol Label Switching (GMPLS) Architecture", [RFC 3945](#), October 2004.
- [GMPLSTCMIB] Nadeau, T., Farrel, A., (Editors) "Definitions of Textual Conventions for Multiprotocol Label

Switching (MPLS) Management",
[draft-ietf-ccamp-gmpls-tc-mib](#), work in progress.

Internet Draft [draft-ietf-ccamp-gmpls-lsr-mib-08.txt](#) June 2005

[GMPLSTEMIB] Nadeau, T., Farrel, A. (Editors) "Generalized Multiprotocol Label Switching (GMPLS) Traffic Engineering Management Information Base",
[draft-ietf-ccamp-gmpls-te-mib](#), work in progress.

12.2. Informational References

- [RFC2026] S. Bradner, "The Internet Standards Process -- Revision 3", [RFC 2026](#), October 1996.
- [RFC2434] Narten, T. and H. Alvestrand, "Guidelines for Writing an IANA Considerations Section in RFCs", BCP: 26, [RFC 2434](#), October 1998.
- [RFC3031] Rosen, E., Viswanathan, A., and R. Callon, "Multiprotocol Label Switching Architecture", [RFC 3031](#), January 2001.
- [RFC3032] Rosen, E. et al, "MPLS Label Stack Encoding", [RFC 3032](#), January 2001.
- [RFC3209] Awduche, D., Berger, L., Gan, D., Li, T., Srinivasan, V., and G. Swallow, "RSVP-TE: Extensions to RSVP for LSP Tunnels", [RFC 3209](#), December 2001.
- [RFC3212] Jamoussi, B., Aboul-Magd, O., Andersson, L., Ashwood-Smith, P., Hellstrand, F., Sundell, K., Callon, R., Dantu, R., Wu, L., Doolan, P., Worster, T., Feldman, N., Fredette, A., Girish, M., Gray, E., Halpern, J., Heinanen, J., Kilty, T., Malis, A., and P. Vaananen, "Constraint-Based LSP Setup using LDP", [RFC 3212](#), December 2001."
- [RFC3410] Case, J., Mundy, R., Partain, D. and B. Stewart, "Introduction and Applicability Statements for Internet-Standard Management Framework", [RFC 3410](#), December 2002.
- [RFC3411] Harrington, D., Presuhn, R., and B. Wijnen, "An Architecture for Describing Simple Network

Management Protocol (SNMP) Management Frameworks",
[RFC 3411](#), December 2002.

[RFC3413] Levi, D., Meyer, P., Stewart, B., "SNMP
Applications", [RFC 3413](#), December 2002.

[RFC3471] Berger, L. (Editor), "Generalized Multi-Protocol
Label Switching (GMPLS) Signaling Functional
Description", [RFC 3471](#), January 2003.

Nadeau and Farrel (Editors)

[Page 38]

Internet Draft [draft-ietf-ccamp-gmpls-lsr-mib-08.txt](#) June 2005

[RFC3472] Ashwood-Smith, P., Berger, L. (Editors),
"Generalized MPLS Signaling - CR-LDP Extensions",
[RFC 3472](#), January 2003.

[RFC3473] Berger, L. (Editor), "Generalized MPLS Signaling -
RSVP-TE Extensions", [RFC 3473](#) January 2003.

[RFC3812] Srinivasan, C., Viswanathan, A., and T. Nadeau,
"Multiprotocol Label Switching (MPLS) Traffic
Engineering (TE) Management Information Base
(MIB)", [RFC 3812](#), June 2004.

[GMPLSSonetSDH] Mannie, E., Papadimitriou, D. (Editors),
"Generalized Multi-Protocol Label Switching
Extensions for SONET and SDH Control",
[draft-ietf-ccamp-gmpls-sonet-sdh](#), work in progress.

13. Authors' Addresses

Thomas D. Nadeau
Cisco Systems, Inc.
300 Apollo Drive
Chelmsford, MA 01824
Phone: +1-978-244-3051
Email: tnadeau@cisco.com

Cheenu Srinivasan
Bloomberg L.P.
731 Lexington Ave.
New York, NY 10022
Phone: +1-212-617-3682
Email: cheenu@bloomberg.net

Adrian Farrel

Old Dog Consulting
Phone: +44-(0)-1978-860944
Email: adrian@olddog.co.uk

Tim Hall
Data Connection Ltd.
100 Church Street
Enfield, Middlesex, EN2 6BQ, UK
Phone: +44 20 8366 1177
Email: tim.hall@dataconnection.com

Ed Harrison
Data Connection Ltd.
100 Church Street
Enfield, Middlesex, EN2 6BQ, UK
Phone: +44 20 8366 1177
Email: ed.harrison@dataconnection.com

Nadeau and Farrel (Editors)

[Page 39]

Internet Draft [draft-ietf-ccamp-gmpls-lsr-mib-08.txt](#)

June 2005

14. Intellectual Property Considerations

The IETF takes no position regarding the validity or scope of any Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; nor does it represent that it has made any independent effort to identify any such rights. Information on the procedures with respect to rights in RFC documents can be found in [BCP 78](#) and [BCP 79](#).

Copies of IPR disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF on-line IPR repository at <http://www.ietf.org/ipr>.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement this standard. Please address the information to the IETF at ietf-ipr@ietf.org.

15. Full Copyright Statement

Copyright (C) The Internet Society (2005). This document is subject

to the rights, licenses and restrictions contained in [BCP 78](#), and except as set forth therein, the authors retain all their rights.

This document and the information contained herein are provided on an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.