

CCAMP  
Internet-Draft  
Intended status: Informational  
Expires: March 12, 2021

G. Martinelli, Ed.  
Cisco  
H. Zheng, Ed.  
Huawei Technologies  
G. Galimberti  
Cisco  
Y. Lee  
Samsung  
F. Zhang  
Huawei Technologies  
September 08, 2020

Information Model for Wavelength Switched Optical Networks (WSONs) with  
Impairments Validation  
[draft-ietf-ccamp-wson-iv-info-12](#)

## Abstract

This document defines an information model to support Impairment-Aware (IA) Routing and Wavelength Assignment (RWA) functionality. This information model extends the information model for impairment-free RWA process in WSON to facilitate computation of paths where optical impairment constraints need to be considered.

## Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on March 12, 2021.

## Copyright Notice

Copyright (c) 2020 IETF Trust and the persons identified as the document authors. All rights reserved.

Internet-Draft

WSON Impairments Information Model

September 2020

This document is subject to [BCP 78](https://trustee.ietf.org/license-info) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

<a href="#">1.</a>	Introduction . . . . .	<a href="#">2</a>
<a href="#">2.</a>	Definitions, Applicability and Properties . . . . .	<a href="#">3</a>
<a href="#">2.1.</a>	Definitions . . . . .	<a href="#">3</a>
<a href="#">2.2.</a>	Applicability . . . . .	<a href="#">4</a>
<a href="#">2.3.</a>	Properties . . . . .	<a href="#">5</a>
<a href="#">3.</a>	ITU-T List of Optical Parameters . . . . .	<a href="#">6</a>
<a href="#">4.</a>	Background from WSON-RWA Information Model . . . . .	<a href="#">8</a>
<a href="#">5.</a>	Optical Impairment Information Model . . . . .	<a href="#">9</a>
<a href="#">5.1.</a>	The Optical Impairment Vector . . . . .	<a href="#">10</a>
<a href="#">5.2.</a>	Node Information . . . . .	<a href="#">10</a>
<a href="#">5.2.1.</a>	Impairment Matrix . . . . .	<a href="#">10</a>
<a href="#">5.2.2.</a>	Impairment Resource Block Information . . . . .	<a href="#">12</a>
<a href="#">5.3.</a>	Link Information . . . . .	<a href="#">12</a>
<a href="#">5.4.</a>	Path Information . . . . .	<a href="#">12</a>
<a href="#">6.</a>	Encoding Considerations . . . . .	<a href="#">13</a>
<a href="#">7.</a>	Control Plane Architectures . . . . .	<a href="#">13</a>
<a href="#">7.1.</a>	IV-Centralized . . . . .	<a href="#">14</a>
<a href="#">7.2.</a>	IV-Distributed . . . . .	<a href="#">14</a>
<a href="#">8.</a>	Acknowledgements . . . . .	<a href="#">14</a>
<a href="#">9.</a>	Contributing Authors . . . . .	<a href="#">14</a>
<a href="#">10.</a>	IANA Considerations . . . . .	<a href="#">15</a>
<a href="#">11.</a>	Security Considerations . . . . .	<a href="#">15</a>
<a href="#">12.</a>	References . . . . .	<a href="#">16</a>
<a href="#">12.1.</a>	Normative References . . . . .	<a href="#">16</a>
<a href="#">12.2.</a>	Informative References . . . . .	<a href="#">16</a>
<a href="#">Appendix A.</a>	FAQ . . . . .	<a href="#">17</a>
<a href="#">A.1.</a>	Why the Application Code does not suffice for Optical Impairment Validation? . . . . .	<a href="#">17</a>
<a href="#">A.2.</a>	Are DWDM network multivendor? . . . . .	<a href="#">18</a>
Authors' Addresses	. . . . .	<a href="#">18</a>

## 1. Introduction

In the context of Wavelength Switched Optical Network (WSON), [\[RFC6163\]](#) describes the basic framework for a GMPLS and PCE-based Routing and Wavelength Assignment (RWA) control plane. The

associated information model [\[RFC7446\]](#) defines information/parameters required by an RWA process without optical impairment considerations.

There are cases of WSON where optical impairments play a significant role and are considered as important constraints. The framework document [\[RFC6566\]](#) defines the problem scope and related control plane architectural options for the Impairment Aware RWA (IA-RWA) operation. Options include different combinations of Impairment Validation (IV) and RWA functions in term of different combination of control plane functions (i.e., PCE, Routing, Signaling).

A Control Plane with RWA-IA will not be able to solve the optical impairment problem in a detailed and exhaustive way, however, it may take advantage of some data plane knowledge to make better decisions during its path computing phase. The final outcome will be a path, instantiated through a wavelength in the data plane, that has a "better chance" to work than that path were calculated without IA information. "Better chance" means that path setup may still fail and the GMPLS control plane will follow its usual procedures upon errors and failures. A control plane will not replace a the network design phase that remains a fundamental step for DWDM Optical Networks. As the non-linear impairments which need to be considered in the calculation of an optical path will be vendor-dependent, the parameters considered in this document is not an exhaustive list.

This document provides an information model for the impairment aware case to allow the impairment validation function implemented in the control plane or enabled by control plane available information. This model goes in addition to [\[RFC7446\]](#) and shall support any control plane architectural option described by the framework document (see sections [4.2](#) and [4.3](#) of [\[RFC6566\]](#)) where a set of combinations of control plane functions vs. IV function is provided.

## 2. Definitions, Applicability and Properties

This section provides some concepts to help understand the model and

to make a clear separation from data plane definitions (ITU-T recommendations). The first sub-section provides definitions while the Applicability sections uses the defined definitions to scope this document.

## 2.1. Definitions

- o Computational Model / Optical Computational Model.  
Defined by ITU standard documents (e.g. [\[ITU.G680\]](#)). In this context we look for models able to compute optical impairments for a given lightpath.

- o Information Model.  
Defined by IETF (this document) and provides the set of information required by control plane to apply the Computational Model.
- o Level of Approximation.  
This concept refers to the Computational Model as it may compute optical impairment with a certain level of uncertainty. This level is generally not measured but [\[RFC6566\] Section 4.1.1](#) provides a rough classification about it.
- o Feasible Path.  
It is the output of the C-SPF with RWA-IV capability. It's an optical path that satisfies optical impairment constraints. The path, instantiated through wavelength(s), may actually work or not work depending of the level of approximation.
- o Existing Service Disruption.  
An effect known to optical network designers is the cross-interaction among spectrally adjacent wavelengths: an existing wavelength may experience increased BER due to the setup of an adjacent wavelength. Solving this problem is a typical optical network design activity. Just as an example, a simple solution is adding optical margins (e.g., additional OSNR), although complex and detailed methods exist.
- o DWDM Line Segments.  
[\[ITU.G680\]](#) provides definition and picture for the "Situation 1" DWDM Line segments: " Situation 1 - The optical path between two

consecutive 3R regenerators is composed of DWDM line segments from a single vendor and OADMs and PXC's from another vendor". Document [RFC6566] Figure 1 shows an LSP composed by two DWDM line segments according to [ITU.G680] definition.

## 2.2. Applicability

This document targets at Scenario C defined in [RFC6566] [section 4.1.1](#). as approximate impairment estimation. The Approximate concept refer to the fact that this Information Model covers information mainly provided by [ITU.G680] Computational Model.

Computational models having no or little approximation, referred as IV-Detailed in the [RFC6566], currently does not exist in term of ITU-T recommendation. They generally deal with non-linear optical impairment and are usually vendor specific.

The Information Model defined in this document does not speculate about the mathematical formulas used to fill up information model

parameters, hence it does not preclude changing the computational model. At the same time, the authors do not believe this Information Model is exhaustive and if necessary further documents will cover additional models after they become available.

The result of RWA-IV process implementing this Information Model is a path (and a wavelength in the data plane) that has better chance to be feasible than if it was computed without any IV function. The Existing Service Disruption, as per the definition above, would still be a problem left to a network design phase.

## 2.3. Properties

An information model may have several attributes or properties that need to be defined for each optical parameter made available to the control plane. The properties will help to determine how the control plane can deal with a specific impairment parameter, depending on architectural options chosen within the overall impairment framework [RFC6566]. In some case, properties value will help to identify the level of approximation supported by the IV process.

- o Time Dependency

This identifies how an impairment parameter may vary with time. There could be cases where there is no time dependency, while in other cases there may be need of re-evaluation after a certain time. In this category, variations in impairments due to environmental factors such as those discussed in [ITU.GSUP47] are considered. In some cases, an impairment parameter that has time dependency may be considered as a constant for approximation. In this information model, we do neglect this property.

- o Wavelength Dependency

This property identifies if an impairment parameter can be considered as constant over all the wavelength spectrum of interest or not. Also in this case a detailed impairment evaluation might lead to consider the exact value while an approximation IV might take a constant value for all wavelengths. In this information model, we consider both case: dependency / no dependency on a specific wavelength. This property appears directly in the information model definitions and related encoding.

- o Linearity

As impairments are representation of physical effects, there are some that have a linear behaviour while other are non-linear. Linear approximation is in scope of Scenario C of [RFC6566]. During the impairment validation process, this property implies that the optical effect (or quantity) satisfies the superposition

principle, thus a final result can be calculated by the sum of each component. The linearity implies the additivity of optical quantities considered during an impairment validation process. The non-linear effects in general do not satisfy this property. The information model presented in this document however, easily allow introduction of non-linear optical effects with a linear approximated contribution to the linear ones.

- o Multi-Channel

There are cases where a channel's impairments take different values depending on the aside wavelengths already in place, this is mostly due to non-linear impairments. The result would be a dependency among different LSPs sharing the same path. This information model do not consider this kind of property.

The following table summarise the above considerations where in the first column reports the list of properties to be considered for each optical parameter, while the second column states if this property is taken into account or not by this information model.

Property	Info Model Awareness
Time Dependency	no
Wavelength Dependency	yes
Linearity	yes
Multi-channel	no

Table 1: Optical Impairment Properties

### 3. ITU-T List of Optical Parameters

As stated by [Section 2.2](#) this Information Model does not intend to be exhaustive and targets an approximate computational model although not precluding future evolutions towards more detailed or different impairments estimation methods.

On the same line, ITU SG15/Q6 provides (through [\[LS78\]](#)) a list of optical parameters with following observations:

- (a) the problem of calculating the non-linear impairments in a multi-vendor environment is not solved. The transfer functions works only for the so called [\[ITU.G680\]](#) "Situation 1".
- (b) The generated list of parameters is not exhaustive however provide a guideline for control plane optical impairment awareness.

In particular, [\[ITU.G680\]](#) contains many parameters that would be required to estimate linear impairments. Some of the Computational Models defined within [\[ITU.G680\]](#) requires parameters defined in other documents like [\[ITU.G671\]](#). The purpose of the list here below makes this match between the two documents.

[\[ITU.G697\]](#) defines parameters can be monitored in an optical network. This Information Model and associated encoding document will reuse

[[ITU.G697](#)] parameters identifiers and encoding for the purpose of path computation.

The list of optical parameters starts from [[ITU.G680](#)] [Section 9](#) which provides the optical computational models for the following p:

G-1 OSNR. [Section 9.1](#)

G-2 Chromatic Dispersion (CD). [Section 9.2](#)

G-3 Polarization Mode Dispersion (PMD). [Section 9.3](#)

G-4 Polarization Dependent Loss (PDL). [Section 9.3](#)

In addition to the above, the following list of parameters has been mentioned by [[LS78](#)]:

L-1 "Channel frequency range", [[ITU.G671](#)]. This parameter is part of the application code and encoded through Optical Interface Class as defined in [[RFC7446](#)].

L-2 "Modulation format and rate". This parameter is part of the application code and encoded through Optical Interface Class as defined in [[RFC7446](#)].

L-3 "Channel power". Required by G-1.

L-4 "Ripple". According to [[ITU.G680](#)], this parameter can be taken into account as additional OSNR penalty.

L-5 "Channel signal-spontaneous noise figure", [[ITU.G680](#)]. Required by OSNR calculation (see G-1) above.

L-6 "Channel chromatic dispersion (for fibre segment or network element)". Already in G-2 above.

L-7 "Channel local chromatic dispersion (for a fibre segment)". Already in G-2 above (since consider both local and fiber dispersions).

L-8 "Differential group delay (for a network element)", [[ITU.G671](#)].



Required by G-3.

- L-9 "Polarisation mode dispersion (for a fibre segment)", [\[ITU.G650.2\]](#), [\[ITU.G680\]](#). Defined above as G-3.
- L-10 "Polarization dependent loss (for a network element)", [\[ITU.G671\]](#) and [\[ITU.G680\]](#). Defined above as G-4.
- L-11 "Reflectance". From [\[ITU.G671\]](#) [Section 3.2.2.37](#) is the ratio of reflected power  $P_r$  to incident power  $P_i$  at a given port of a passive component, for given conditions of spectral composition, polarization and geometrical distribution. Generally expressed in dB. Might be monitored in some critical cases. We neglect this effect as first approximation.
- L-12 "Channel Isolation". From [\[ITU.G671\]](#) [Section 3.2.2.2](#) (Adjacent Channel Isolation) and [Section 3.2.2.29](#) (Non Adjacent Channel Isolation). Document [\[ITU.GSUP39\]](#) provide the formula for calculation as channel cross-talk and measure it in dB. This parameter shall be considered for path computation.
- L-13 "Channel extinction". From [\[ITU.G671\]](#) [Section 3.2.2.9](#) needed for Interferometric Crosstalk. Document [\[ITU.GSUP39\]](#) has the formula for penalty computation. Unit of measurement is dB.
- L-14 "Attenuation coefficient (for a fibre segment)". Document [\[ITU.G650.1\]](#) [Section 3.6.2](#). The unit of measure is dB. This is a typical link parameter (as associated to a fiber).
- L-15 "Non-linear coefficient (for a fibre segment)", [\[ITU.G650.2\]](#). Required for Non-Linear Optical Impairment Computational Models. Neglected by this document.

The final list of parameters is G-1, G-2, G-3, G-4, L-3, L-4, L-5, L-8, L-12, L-13, L-14.

#### 4. Background from WSON-RWA Information Model

In this section we report terms already defined for the WSON-RWA (impairment free) as in [\[RFC7446\]](#) and [\[RFC7579\]](#). The purpose is to provide essential information that will be reused or extended for the impairment case.

In particular [\[RFC7446\]](#) [Section 4.1](#) defines the ConnectivityMatrix and states that such matrix does not represent any particular internal blocking behaviour but indicates which input ports and wavelengths could possibly be connected to a particular output port.

---

```
<ConnectivityMatrix> ::= <MatrixID> <ConnType> <Matrix>
```

According to [\[RFC7579\]](#), this definition is further detailed as:

```
<ConnectivityMatrix> ::=  
    <MatrixID> <ConnType> ((<LinkSet> <LinkSet>) ...)
```

This second formula highlights how the ConnectivityMatrix is built by pairs of LinkSet objects identifying the internal connectivity capability due to internal optical node constraint(s). It's essentially binary information and tell if a wavelength or a set of wavelengths can go from an input port to an output port.

As an additional note, ConnectivityMatrix belongs to node information, is uniquely identified by advertising node and is a static information. Dynamic information related to the actual state of connections is available through specific extension to link information.

The [\[RFC7446\]](#) introduces the concept of ResourceBlockInfo and ResourcePool for the WSOON nodes. The resource block is a collection of resources behaving in the same way and having similar characteristics. The ResourceBlockInfo is defined as follow:

```
<ResourceBlockInfo> ::= <ResourceBlockSet> [<InputConstraints>]  
    [<ProcessingCapabilities>] [<OutputConstraints>]
```

The usage of resource block and resource pool is an efficient way to model constraints within a WSOON node.

## [5.](#) Optical Impairment Information Model

The idea behind this document is to put optical impairment parameters into categories and extend the information model already defined for impairment-free WSOONs. The three categories are:

- o Node Information. The concept of connectivity matrix is reused and extended to introduce an impairment matrix, which represents the impairments suffered on the internal path between two ports. In addition, the concept of Resource Block is also reused and extended to provide an efficient representation of per-port impairment.
- o Link Information representing impairment information related to a specific link or hop.

- o Path Information representing the impairment information related to the whole path.

All the above three categories will make use of a generic container, the Impairment Vector, to transport optical impairment information.

This information model however will allow however to add additional parameters beyond the one defined by [\[ITU.G680\]](#) in order to support additional computational models. This mechanism could eventually be applicable to both linear and non-linear parameters.

This information model makes the assumption that each optical node in the network is able to provide the control plane protocols with its own parameter values. However, no assumption is made on how the optical nodes get those value information (e.g., internally computed, provisioned by a network management system, etc.). To this extent, the information model intentionally ignores all internal detailed parameters that are used by the formulas of the Optical Computational Model (i.e., "transfer function") and simply provides the object containers to carry results of the formulas.

### [5.1.](#) The Optical Impairment Vector

Optical Impairment Vector (OIV) is defined as a list of optical parameters to be associated to a WSO<sub>N</sub> node or a WSO<sub>N</sub> link. It is defined as:

`<OIV> ::= ([<LabelSet>] <OPTICAL_PARAM>) ...`

The optional LabelSet object enables wavelength dependency property as per Table 1. LabelSet has its definition in [\[RFC7579\]](#).

OPTICAL\_PARAM. This object represents an optical parameter. The Impairment vector can contain a set of parameters as identified by [\[ITU.G697\]](#) since those parameters match the terms of the linear impairments computational models provided by [\[ITU.G680\]](#). This information model does not speculate about the set of parameters (since defined elsewhere, e.g. ITU-T), however it does not preclude extensions by adding new parameters.

### [5.2.](#) Node Information

### 5.2.1. Impairment Matrix

Impairment matrix describes a list of the optical parameters that applies to a network element as a whole or ingress/egress port pairs of a network element. Wavelength dependency property of optical parameters is also considered.

```
ImpairmentMatrix ::= <MatrixID> <ConnType>
                    ((<LinkSet> <LinkSet> <OIV>) ...)
```

Where:


**MatrixID.** This ID is a unique identifier for the matrix. It shall be unique in scope among connectivity matrices defined in [[RFC7446](#)] and impairment matrices defined here.

**ConnType.** This number identifies the type of matrix and it shall be unique in scope with other values defined by impairment-free WSON documents.

**LinkSet.** Same object definition and usage as [[RFC7579](#)]. The pairs of LinkSet identify one or more internal node constrain.

**OIV.** The Optical Impairment Vector defined above.

The model can be represented as a multidimensional matrix shown in the following picture



	+++++	/	/	/	PDL
<LinkSet#1>	-	/	/	/	
	+++++	/	/	/	
<linkSet#2>	-	/	/	/	PND
	+++++	/	/	/	
<linkSet#3>	-	/	/	/	
	+++++	/	/	/	Chr.Disp.
<linkSet#4>	-	/	/	/	
	+++++	/	/	/	
<linkSet#5>	-	/	/	/	OSNR
	+++++	/	/	/	
	<LS#1> <LS#2> <LS#3> <LS#4> <LS#5>				

The connectivity matrix from [RFC7579] is only a two dimensional matrix, containing only binary information, through the LinkSet

pairs. In this model, a third dimension is added by generalizing the binary information through the Optical Impairment Vector associated with each LinkSet pair. Optical parameters in the picture are reported just as an example: proper list and encoding shall be defined by other documents.

This representation shows the most general case however, the total amount of information transported by control plane protocols can be greatly reduced by proper encoding when the same set of values apply to all LinkSet pairs.

### 5.2.2. Impairment Resource Block Information

This information model reuses the definition of Resource Block Information adding the associated impairment vector.

```
ResourceBlockInfo ::= <ResourceBlockSet> [<InputConstraints>]
                    [<ProcessingCapabilities>] [<OutputConstraints>] [<OIV>]
```

The object ResourceBlockInfo is then used as specified within [RFC7446].

### 5.3. Link Information

For the list of optical parameters associated to the link, the same

approach used for the node-specific impairment information can be applied. The link-specific impairment information is extended from [\[RFC7446\]](#) as the following:

```
<DynamicLinkInfo> ::= <LinkID> <AvailableLabels>  
                        [<SharedBackupLabels>] [<OIV>]
```

DynamicLinkInfo is already defined in [\[RFC7446\]](#) while OIV is the Optical Impairment Vector is defined in the previous section.

#### [5.4.](#) Path Information

There are cases where the optical impairments can only be described as a constraints on the overall end to end path. In such case, the optical impairment and/or parameter, cannot be derived (using a simple function) from the set of node / link contributions.

An equivalent case is the option reported by [\[RFC6566\]](#) on IV-Candidate paths where, the control plane knows a list of optically feasible paths so a new path setup can be selected among that list. Independent from the protocols and functions combination (i.e. RWA vs. Routing vs. PCE), the IV-Candidates imply a path property stating that a path is optically feasible.

The concept of Optical Impairment Vector (OIV) might be used or extended to report optical impairment information at path level however this is case is left for future studies.

## [6.](#) Encoding Considerations

Details about encoding will be defined in a separate document [\[I-D.ietf-ccamp-wson-iv-encode\]](#) however worth remembering that, within [\[ITU.G697\]](#) Appendix V, ITU already provides a guideline for encoding some optical parameters.

In particular [\[ITU.G697\]](#) indicates that each parameter shall be represented by a 32 bit floating point number.

Values for optical parameters are provided by optical node and it could provide by direct measurement or from some internal computation starting from indirect measurement. In such cases, it could be useful to understand the variance associated with the value of the

optical parameter hence, the encoding shall provide the possibility to include a variance as well.

This kind of information will enable IA-RWA process to make some additional considerations on wavelength feasibility. [\[RFC6566\]](#) [Section 4.1.3](#) reports some considerations regarding this degree of confidence during the impairment validation process.

## [7.](#) Control Plane Architectures

This section briefly describes how the definitions contained in this information model will match the architectural options described by [\[RFC6566\]](#). This section does not suggest suggested any specific protocol option.

The assumption is that WSON GMPLS extensions are available and operational. To such extent, the WSON-RWA will provide the following information through its path computation (and RWA process):

- o The wavelengths connectivity, considering also the connectivity constraints limited by reconfigurable optics, and wavelengths availability.
- o The interface compatibility at the physical level.
- o The Optical-Elettro-Optical (OEO) availability within the network (and related physical interface compatibility). As already stated by the framework this information it's very important for impairment validation:

- A. If the IV functions fail (path optically infeasible), the path computation function may use an available OEO point to find a feasible path. In normally operated networks OEO are mainly uses to support optically unfeasible path than mere wavelength conversion.
- B. The OEO points reset the optical impairment information since a new light is generated.

### [7.1.](#) IV-Centralized

Centralized IV process is performed by a single entity (e.g. a PCE or other external entities). Given sufficient impairment information, it can either be used to provide a list of paths between two nodes, which are valid in terms of optical impairments. Alternatively, it can help validate whether a particular selected path and wavelength is feasible or not.

Centralized IV functions requires exchange of impairment information to the entity performing the IV process from network nodes. This information exchange may requires implementation of this information model within an existing protocol (i.e. routing protocol vs PCEP vs BGP-LS vs others).

## [7.2.](#) IV-Distributed

Assuming the information model is implemented through a routing protocol, every node in the WSON network shall be able to perform an RWA-IV function.

The signalling phase may provide additional checking as others traffic engineering parameters.

## [8.](#) Acknowledgements

Authors would like to acknowledge Greg Bernstein and Moustafa Kattan as authors of a previous similar draft whose content partially converged here.

Authors would like to thank ITU SG15/Q6 and in particular Peter Stassar and Pete Anslow for providing useful information and text to CCAMP through joint meetings and liaisons.

## [9.](#) Contributing Authors

This document was the collective work of several authors. The text and content of this document was contributed by the editors and the co-authors listed below:



Shenzen 518129  
P.R. China

Phone: +86 755 28972913  
Email: zhang.xian@huawei.com

Domenico Siracusa  
CREATE-NET  
via alla Cascata 56/D, Povo  
Trento 38123  
Italy

Email: domenico.siracusa@create-net.org

Andrea Zanardi  
CREATE-NET  
via alla Cascata 56/D, Povo  
Trento 38123  
Italy

Email: andrea.zanardi@create-net.org

Federico Pederzolli  
CREATE-NET  
via alla Cascata 56/D, Povo  
Trento 38123  
Italy

Email: federico.pederzolli@create-net.org

## [10.](#) IANA Considerations

This document does not contain any IANA requirement.

## [11.](#) Security Considerations

This document defines an information model for impairments in optical networks. If such a model is put into use within a network it will by its nature contain details of the physical characteristics of an

optical network. Such information would need to be protected from intentional or unintentional disclosure.

## [12.](#) References

### [12.1.](#) Normative References

[ITU.G650.1]

International Telecommunications Union, "Transmission media and optical systems characteristics - Optical fibre cable", ITU-T Recommendation G.650.1, July 2010.

[ITU.G650.2]

International Telecommunications Union, "Definitions and test methods for statistical and non-linear related attributes of single-mode fibre and cable", ITU-T Recommendation G.650.2, August 2015.

[ITU.G671]

International Telecommunications Union, "Transmission characteristics of optical components and subsystems", ITU-T Recommendation G.671, February 2012.

[ITU.G680]

International Telecommunications Union, "Physical transfer functions of optical network elements", ITU-T Recommendation G.680, July 2007.

[ITU.G697]

International Telecommunications Union, "Optical monitoring for dense wavelength division multiplexing systems", ITU-T Recommendation G.697, February 2012.

[ITU.GSUP39]

International Telecommunications Union, "Optical System Design and Engineering Considerations", ITU-T Recommendation G. Supplement 39, September 2012.

[ITU.GSUP47]

International Telecommunications Union, "General aspects of optical fibres and cables", ITU-T Recommendation G. Supplement 47, September 2012.

### [12.2.](#) Informative References

- [I-D.ietf-ccamp-wson-iv-encode]  
Martinelli, G., Lee, Y., Galimberti, G., and F. Zhang,  
"Information Encoding for WSON with Impairments  
Validation", [draft-ietf-ccamp-wson-iv-encode-02](#) (work in  
progress), January 2019.
- [LS78] International Telecommunications Union SG15/Q6, "LS/s on  
CCAMP Liaison to ITU-T SG15 Q6 and Q12 on WSON",  
LS <https://datatracker.ietf.org/liaison/1288/>, October  
2013.
- [RFC6163] Lee, Y., Ed., Bernstein, G., Ed., and W. Imajuku,  
"Framework for GMPLS and Path Computation Element (PCE)  
Control of Wavelength Switched Optical Networks (WSONs)",  
[RFC 6163](#), DOI 10.17487/RFC6163, April 2011,  
<<https://www.rfc-editor.org/info/rfc6163>>.
- [RFC6566] Lee, Y., Ed., Bernstein, G., Ed., Li, D., and G.  
Martinelli, "A Framework for the Control of Wavelength  
Switched Optical Networks (WSONs) with Impairments",  
[RFC 6566](#), DOI 10.17487/RFC6566, March 2012,  
<<https://www.rfc-editor.org/info/rfc6566>>.
- [RFC7446] Lee, Y., Ed., Bernstein, G., Ed., Li, D., and W. Imajuku,  
"Routing and Wavelength Assignment Information Model for  
Wavelength Switched Optical Networks", [RFC 7446](#),  
DOI 10.17487/RFC7446, February 2015,  
<<https://www.rfc-editor.org/info/rfc7446>>.
- [RFC7579] Bernstein, G., Ed., Lee, Y., Ed., Li, D., Imajuku, W., and  
J. Han, "General Network Element Constraint Encoding for  
GMPLS-Controlled Networks", [RFC 7579](#),  
DOI 10.17487/RFC7579, June 2015,  
<<https://www.rfc-editor.org/info/rfc7579>>.

## [Appendix A](#). FAQ

### [A.1](#). Why the Application Code does not suffice for Optical Impairment Validation?

Application Codes are encoded within GMPLS WSON protocol through the Optical Interface Class as defined in [[RFC7446](#)].

The purpose of the Application Code in RWA is simply to assess the interface compatibility: same Application Code means that two interfaces can have an LSP connecting the two.

Application Codes contain other information useful for IV process (e.g., see the list of parameters) so they are required however Computational Models requires more parameters to assess the path feasibility.

#### [A.2.](#) Are DWDM network multivendor?

According to [[ITU.G680](#)] "Situation 1" the DWDM line segments are single are single vendor but an LSP can make use of different data planes entities from different vendors. For example: DWDM interfaces (represented in the control plane through the Optical Interface Class) from a vendor and network elements described by Stutation 1 from another vendor.

#### Authors' Addresses

Giovanni Martinelli (editor)  
Cisco  
via Santa Maria Molgora, 48/C  
Vimercate, MB 20871  
Italy

Phone: +39 039 2092044  
Email: [giomarti@cisco.com](mailto:giomarti@cisco.com)

Haomian Zheng (editor)  
Huawei Technologies  
H1, Huawei Xiliu Beipo Village, Songshan Lake  
Dongguan, Guangdong 523808  
China

Phone: +8613066975206

Email: zhenghaomian@huawei.com

Gabriele M. Galimberti  
Cisco  
Via Santa Maria Molgora, 48/C  
Vimercate, MB 20871  
Italy

Phone: +39 039 2091462  
Email: ggalimbe@cisco.com

Martinelli, et al.

Expires March 12, 2021

[Page 18]

---

Internet-Draft

WSO<sub>N</sub> Impairments Information Model

September 2020

Young Lee  
Samsung  
Seoul  
South Korea

Email: younglee.tx@gmail.com

Fatai Zhang  
Huawei Technologies  
H1, Huawei Xiliu Beipo Village, Songshan Lake  
Dongguan, Guangdong 523808  
China

Email: zhangfatai@huawei.com

