

CCAMP Working Group

Internet Draft

Intended status: Standard Track

Y. Lee (Editor)

D. Dhody

X. Zhang

Huawei

A. Guo

ADVA

V. Lopez

Telefonica

D. King

U. of Lancaster

B. Yoon

ETRI

Expires: September 15, 2016

March 21, 2016

A Yang Data Model for WSON Optical Networks

[draft-ietf-ccamp-wson-yang-00.txt](#)

Abstract

This document provides a YANG data model for the routing and wavelength assignment (RWA) TE topology in wavelength switched optical networks (WSONs).

Status of this Memo

This Internet-Draft is submitted to IETF in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/1id-abstracts.txt>

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>

This Internet-Draft will expire on June 21, 2016.

Copyright (c) 2015 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the [Trust Legal Provisions](#) and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1. Introduction.....	2
2. Routing and Wavelength Assignment Informational Model.....	3
2.1. Connectivity Matrix Model.....	3
2.2. Resource Pool Model.....	4
2.3. Port Label Restriction Model.....	8
2.4. Wavelength Availability on Links.....	9
3. YANG Model (Tree Structure).....	10
4. WSON-RWA YANG Model.....	11
5. Security Considerations.....	17
6. IANA Considerations.....	17
7. Acknowledgments.....	17
8. References.....	18
8.1. Normative References.....	18
8.2. Informative References.....	18
9. Contributors.....	18
Authors' Addresses.....	18

[1. Introduction](#)

This document provides a YANG data model for the routing and wavelength assignment (RWA) Traffic Engineering (TE) topology in wavelength switched optical networks (WSONs). The YANG model described in this document is a WSON technology-specific Yang model based on the information model developed in [\[RFC7446\]](#) and the two encoding documents [\[RFC7581\]](#) and [\[RFC7579\]](#) that developed protocol independent encodings based on [\[RFC7446\]](#). This document augments the generic TE topology draft [\[TE-TOP0\]](#).

What is not in scope of this document is both impairment-aware WSON and flex-grid.

2. Routing and Wavelength Assignment Informational Model

The relevant information model in this document comprises

- Connectivity Matrix Model ([Section 2.1](#))
- Resource Pool Model ([Section 2.2](#))
- Port Wavelength Restriction ([Section 2.3](#))
- Wavelength Availability on Links ([Section 2.4](#))

[Editor's Note: This version covers the corresponding YANG data model for the first two sections (Sections [2.1](#) and [2.2](#)) and leaves the YANG model for Sections [2.3](#) and [2.4](#) in the later version.]

Sections [2.1](#) - [2.4](#) rehashes key information models from [RWA-Info] to facilitate the development of the YANG model ([Section 3](#)).

2.1. Connectivity Matrix Model

The connectivity matrix (ConnectivityMatrix) represents either the potential connectivity matrix for asymmetric switches (e.g. ROADMs and such) or fixed connectivity for an asymmetric device such as a multiplexer.

Note that multiple connectivity matrices are allowed and the Node_ID would be an appropriate identifier for the node to point the Connectivity matrix within the WSON RWA context.

<Node_Information> ::= <Node_ID> [<ConnectivityMatrix>...]

<ConnectivityMatrix> ::= <MatrixID>

<ConnType>

<Matrix>

Where

<MatrixID> is a unique identifier for the matrix.

<ConnType> can be either 0 or 1 depending upon whether the connectivity is either fixed or switched.


<Matrix> represents the fixed or switched connectivity in that $\text{Matrix}(i, j) = 0$ or 1 depending on whether input port i can connect to output port j for one or more wavelengths.

2.2. Resource Pool Model

A WSON node may include regenerators or wavelength converters arranged in a shared pool. As discussed in [[RFC6163](#)] this can include Optical-Electronic-Optical (OEO) based Wavelength Division Multiplexing (WDM) switches as well. There are a number of different approaches used in the design of WDM switches containing regenerator or converter pools. However, from the point of view of path computation the following need to be known:

1. The nodes that support regeneration or wavelength conversion.
2. The accessibility and availability of a wavelength converter to convert from a given input wavelength on a particular input port to a desired output wavelength on a particular output port.
3. Limitations on the types of signals that can be converted and the conversions that can be performed.

The following Figures show resource pool architecture of WSON.



Note: Rb is a Resource Block.

Figure 1 Schematic diagram of resource pool model.

Since resources tend to be packaged together in blocks of similar devices, e.g., on line cards or other types of modules, the fundamental unit of identifiable resource in this document is the "resource block". A resource block may contain one or more resources. A resource is the smallest identifiable unit of processing allocation. One can group together resources into blocks if they have similar characteristics relevant to the optical system being modeled, e.g., processing properties, accessibility, etc.

This leads to the following formal high level model:

<Node_Information> ::= <Node_ID>


```
[<ConnectivityMatrix>...]
```

```
[<ResourcePool>]
```

Where

```
<ResourcePool> ::= <ResourceBlockInfo>...
```

```
    [<ResourceAccessibility>...]
```

```
    [<ResourceWaveConstraints>...]
```

```
    [<RBPoolState>]
```

```
<ResourceAccessibility> ::= <PoolInputMatrix>
```

```
    <PoolOutputMatrix>
```

```
<ResourceWaveConstraints> ::= <InputWaveConstraints>
```

```
    <OutputOutputWaveConstraints>
```

```
<RBSharedAccessWaveAvailability> ::= [<InAvailableWavelengths>]
```

```
    [<OutAvailableWavelengths>]
```

```
<RBPoolState> ::=    <ResourceBlockID>
```

```
    <NumResourcesInUse>
```

```
    [<RBSharedAccessWaveAvailability>]
```

```
    [<RBPoolState>]
```

```
<ResourceBlockInfo> ::= <ResourceBlockSet>
```

[<InputConstraints>]

[<ProcessingCapabilities>]

[<OutputConstraints>]

Where <ResourceBlockSet> is a list of resource block identifiers with the same characteristics. If this set is missing the constraints are applied to the entire network element.

<InputConstraints> ::= <SharedInput>

[<OpticalInterfaceClassList>]

[<ClientSignalList>]

<ProcessingCapabilities> ::= [<NumResources>]

[<RegenerationCapabilities>]

[<FaultPerfMon>]

[<VendorSpecific>]

<OutputConstraints> := <SharedOutput>

[<OpticalInterfaceClassList>]

[<ClientSignalList>]

<OpticalInterfaceClassList> ::= <OpticalInterfaceClass> ...

<ClientSignalList>::=[<G-PID>]...

1. Number of Resources within the block
2. Regeneration capability
3. Fault and performance monitoring
4. Vendor Specific capability

Note that the code points for Fault and performance monitoring and vendor specific capability are subject to further study.

2.3. Port Label Restriction Model

```
<LinkInfo> ::= <LinkID>

               [<AdministrativeGroup>]

               [<InterfaceCapDesc>]

               [<Protection>]

               [<SRLG>...]

               [<TrafficEngineeringMetric>]

               [<PortLabelRestriction>...]
```

Note that these additional link characteristics only applies to line side ports of WDM system or add/drop ports pertaining to Resource Pool (e.g., Regenerator or Wavelength Converter Pool). The advertisement of input/output tributary ports is not intended here.

```
<PortLabelRestriction> ::= <MatrixID>

                           <Restriction parameters list>

<Restriction parameters list> ::=

                           <LabelSet> ...
```

Where

MatrixID is the ID of the corresponding connectivity matrix.

LabelSet is a conceptual set of labels (wavelengths).

MaxNumChannels is the maximum number of channels that can be simultaneously used (relative to either a port or a matrix).

LinkSet is a conceptual set of ports.

2.4. Wavelength Availability on Links

In the previously presented information model there are a limited number of information elements that are dynamic, i.e., subject to change with subsequent establishment and teardown of connections. Depending on the protocol used to convey this overall information model it may be possible to send this dynamic information separate from the relatively larger amount of static information needed to characterize WSON's and their network elements.

```
<DynamicLinkInfo> ::= <LinkID>  
  
                        <AvailableLabels>  
  
                        [<SharedBackupLabels>]
```

AvailableLabels is a set of labels (wavelengths) currently available on the link. Given this information and the port wavelength restrictions one can also determine which wavelengths are currently in use. This parameter could potential be used with other technologies that GMPLS currently covers or may cover in the future.

SharedBackupLabels is a set of labels (wavelengths) currently used for shared backup protection on the link. An example usage of this information in a WSON setting is given in [Shared]. This parameter could potential be used with other technologies that GMPLS currently covers or may cover in the future.

3. YANG Model (Tree Structure)

(Editor's Note: This version is based on the augmentation of [draft-ietf-teas-yang-te-topo](#) [TE-TOP0].)

```
module: ietf-wson-topology
augment /tet:te-topologies/tet:topology/tet:topology-types/tet:te-
topology:
  +--rw wson-topology
augment /tet:te-topologies/tet:topology/tet:node/tet:te-node-
attributes/tet:connectivity-matrix:
  +--rw wson-matrix
    +--rw device-type?      devicetype
    +--rw dir?              directionality
    +--rw matrix-interface* [in-port-id]
      +--rw in-port-id      wson-interface-ref
      +--rw out-port-id?    wson-interface-ref
augment /tet:te-topologies/tet:topology/tet:node/tet:te-node-
attributes/tet:te-link:
  +--rw wavelength-available-bitmap*  boolean
augment /tet:te-topologies/tet:topology/tet:node:
  +--rw resource-pool* [resource-pool-id]
    +--rw resource-pool-id  uint32
    +--rw pool-state?       boolean
    +--rw matrix-interface* [in-port-id]
      +--rw in-port-id      wson-interface-ref
      +--rw out-port-id?    wson-interface-ref
```

[4.](#) WSON-RWA YANG Model

```
<CODE BEGINS> file "ietf-wson-topology@2015-10-14.yang"

module ietf-wson-topology {
  namespace "urn:ietf:params:xml:ns:yang:ietf-wson-topology";

  prefix wson;

  import ietf-inet-types {
    prefix inet;
  }

  import ietf-te-topology {
    prefix "tet";
  }

  organization
    "IETF CCAMP Working Group";

  contact
    "Editor:  Young Lee  <leeyoung@huawei.com>";

  description
    "This module contains a collection of YANG definitions for
    RWA WSON.

    Copyright (c) 2015 IETF Trust and the persons identified as
    authors of the code.  All rights reserved.

    Redistribution and use in source and binary forms, with or
    without modification, is permitted pursuant to, and subject
    to the license terms contained in, the Simplified BSD
    License set forth in Section 4.c of the IETF Trust's Legal
```

```
Provisions Relating to IETF Documents
(http://trustee.ietf.org/license-info).";

revision 2015-10-14 {
  description
    "version 2.";

  reference
    "RFC XXX: A Yang Data Model for WSON Optical Networks ";
}

typedef wson-topology-id {
  type inet:uri;
  description
    "The WSON Topology ID";
}

typedef wson-node-id {
  type inet:ip-address;
  description
    "The WSON Node ID";
}

typedef devicetype {
  type enumeration {
    enum adm {
      value 1;
      description
        "Device is ADM";
    }

    enum roadm {
      value 2;
      description
        "Device is ROADMD/OXC";
    }
  }
  description
    "device type: fixed (ADM) or switched (ROADM/OXC)";
}
```

```
typedef directionality {
  type enumeration {
    enum bidir {
      value 0;
      description
        "bi-directional";
    }
    enum input {
      value 1;
      description
        "input direction";
    }
    enum output {
      value 2;
      description
        "output direction";
    }
  }
  description
    "The directionality of link set";
}
```

```
typedef wson-interface-ref {
  type leafref {
    path "/tet:te-topologies/tet:topology/tet:node"
      + "/tet:te-node-attributes/tet:te-link"
      + "/tet:te-link-id";
  }
  description
    "This type is used by data models that need to
    reference WSON interface.";
}
```

```
augment "/tet:te-topologies/tet:topology/tet:topology-types"
  + "/tet:te-topology" {
  description "WSON augmentation.";
  container wson-topology{
    description
      "An empty WSON container to identify
```

```
        the topology type.";
    }
}

augment "/tet:te-topologies/tet:topology/tet:node"
  +"/tet:te-node-attributes"
  +"/tet:connectivity-matrix" {
  when "/tet:te-topologies/tet:topology/tet:topology-types"
    +"/tet:te-topology/wson-topology" {
    description
      "This augment is only valid for WSON.";
  }
  description "WSON Connectivity Matrix augmentation.";
  container wson-matrix{
    description "WSON specific Matrix.";
    leaf device-type {
      type devicetype;
      description
        "device type: fixed (ADM) or switched
        (ROADM/OXC)";
    }
    leaf dir {
      type directionality;
      description
        "bi-directionality or input or output
        of link set";
    }
  }

  list matrix-interface {
    key "in-port-id";

    description
      "matrix-interface describes input-ports
      and out-ports around a connectivity
      matrix";

    leaf in-port-id {
      type wson-interface-ref;
      description
        "The reference to in-port";
    }
  }
}
```

```
        leaf out-port-id {
            type wson-interface-ref;
            description
                "The reference to out-port";
        }
    }
}

augment "/tet:te-topologies/tet:topology/tet:node"
+ "/tet:te-node-attributes/tet:te-link" {

    when "/tet:te-topologies/tet:topology/tet:topology-types"
    + "/tet:te-topology/wson-topology" {
        description
            "This augment is only valid for WSON.";
    }
    description "WSON Link augmentation.";

    leaf-list wavelength-available-bitmap {
        type boolean;
        description
            "array of bits (i.e., bitmap) that indicates
            if a wavelength is available or not on each
            channel.";
    }
}

augment "/tet:te-topologies/tet:topology/tet:node" {
    when "/tet:te-topologies/tet:topology/tet:topology-types"
    + "/tet:te-topology/wson-topology" {
        description
            "This augment is only valid for WSON.";
    }
    description "WSON Node augmentation.";

    list resource-pool {
        key "resource-pool-id";
        description
            "The resource pool list";
    }
}
```

```
    leaf resource-pool-id {
      type uint32;
      description
        "The resource pool ID";
    }

    leaf pool-state {
      type boolean;
      description
        "TRUE is state UP; FALSE is state down";
    }

    list matrix-interface {
      key "in-port-id";

      description
        "pool is described as matrix-interface
        with input-ports and output-ports
        around the pool";

      leaf in-port-id {
        type wson-interface-ref;
        description
          "The reference to in-interface";
      }

      leaf out-port-id {
        type wson-interface-ref;
        description
          "The reference to out-interface";
      }
    }
  }
}
```

<CODE ENDS>

5. Security Considerations

TDB

6. IANA Considerations

TDB

7. Acknowledgments

This document was prepared using 2-Word-v2.0.template.dot.

8. References

8.1. Normative References

- [RFC7446] Y. Lee, G. Bernstein, D. Li, W. Imajuku, "Routing and Wavelength Assignment Information Model for Wavelength Switched Optical Networks", [RFC 7446](#), February 2015.
- [RFC7579] G. Bernstein, Y. Lee, D. Li, W. Imajuku, "General Network Element Constraint Encoding for GMPLS Controlled Networks", [RFC 7579](#), June 2015.
- [RFC7581] G. Bernstein, Y. Lee, D. Li, W. Imajuku, "Routing and Wavelength Assignment Information Encoding for Wavelength Switched Optical Networks", [RFC 7581](#), June 2015.
- [TE-TOP0] X. Liu, et al., "YANG Data Model for TE Topologies", work in progress: [draft-ietf-teas-yang-te-topo](#).

8.2. Informative References

9. Contributors

Authors' Addresses

Young Lee (ed.)
Huawei Technologies
5340 Legacy Drive, Building 3
Plano, TX 75023
USA

Phone: (469) 277-5838
Email: leeyoung@huawei.com

Dhruv Dhody
Huawei Technologies India Pvt. Ltd,
Near EPIP Industrial Area, Kundalahalli Village, Whitefield,
Bangalore - 560 037 [H1-2A-245]

Email: dhruv.dhody@huawei.com

Xian Zhang
Huawei Technologies

Email: zhang.xian@huawei.com

Aihua Guo
ADVA
Email: AGuo@advaoptical.com

Victor Lopez
Telefonica
Email: victor.lopezalvarez@telefonica.com

Daniel King
University of Lancaster
Email: d.king@lancaster.ac.uk

Bin Yeong Yoon
ETRI
218 Gaijeongro, Yuseong-gu
Daejeon, Korea
Email: byyun@etri.re.kr