

CCAMP Working Group
Internet-Draft
Intended status: Standards Track
Expires: March 25, 2021

H. Zheng
Huawei Technologies
Y. Lee
Samsung
A. Guo
Futurewei
V. Lopez
Telefonica
D. King
University of Lancaster
September 21, 2020

**A YANG Data Model for WSON (Wavelength Switched Optical Networks)
draft-ietf-ccamp-wson-yang-26**

Abstract

This document provides a YANG data model for the routing and wavelength assignment (RWA) TE topology in wavelength switched optical networks (WSONs). The YANG data model defined in this document conforms to the Network Management Datastore Architecture (NMDA).

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on March 25, 2021.

Copyright Notice

Copyright (c) 2020 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents

(<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	2
1.1.	Terminology and Notations	3
1.2.	Tree Diagram	3
1.3.	Prefix in Data Node Names	4
2.	YANG Model (Tree Structure) for WSON topology	4
3.	The YANG Code for WSON topology	24
4.	Security Considerations	58
5.	IANA Considerations	59
6.	Contributors	59
7.	References	60
7.1.	Normative References	60
7.2.	Informative References	61
	Authors' Addresses	62

1. Introduction

This document provides a YANG data model for the routing and wavelength assignment (RWA) Traffic Engineering (TE) topology in transparent wavelength switched optical networks (WSONs). The YANG model described in this document is a WSON technology-specific YANG model based on the information model developed in [[RFC7446](#)] and the two encoding documents [[RFC7581](#)] and [[RFC7579](#)] that developed protocol independent encodings based on [[RFC7446](#)].

[ITU-Tg6982] defines amplified multichannel dense wavelength division multiplexing applications with single channel optical interfaces. The YANG data model defined in this document refers to the standard application mode defined in [[ITU-Tg6982](#)].

What is not in scope of this document is both impairment-aware optical networks and flexi-grid. Refer to [[I-D.ietf-ccamp-optical-impairment-topology-yang](#)] for impairment-aware optical network topology model and [[I-D.ietf-ccamp-flexigrid-yang](#)] for flexi-grid optical network topology model.

Additionally, transponders and resource blocks (e.g., 3R Regeneration) models are not in the scope of this document.

This document defines one YANG model: ietf-wson-topology ([Section 3](#)). This document augments the generic TE topology draft [[I-D.ietf-teas-yang-te-topo](#)].

There are multiple applications for the yang data model defined in this document. For example, nodes within the network can use the data model to capture their understanding of the overall WSON topology and expose it to a controller. A controller can further propagate the topology to other controllers. The YANG model is used by NETCONF [[RFC6020](#)], [[RFC8341](#)] or a RESTCONF [[RFC8040](#)] protocol. The YANG data model defined in this document conforms to the Network Management Datastore Architecture [[RFC8342](#)].

[1.1](#). Terminology and Notations

Refer to [[RFC7446](#)] and [[RFC7581](#)] for the key terms used in this document. The following terms are defined in [[RFC7950](#)] and are not redefined here:

- o client
- o server
- o augment
- o data model
- o data node

The following terms are defined in [[RFC6241](#)] and are not redefined here:

- o configuration data
- o state data

The terminology for describing YANG data models is found in [[RFC7950](#)].

[1.2](#). Tree Diagram

A simplified graphical representation of the data model is used in chapter 2 of this document. The meaning of the symbols in these diagrams is defined in [[RFC8340](#)].

1.3. Prefix in Data Node Names

In this document, names of data nodes and other data model objects are prefixed using the standard prefix associated with the corresponding YANG imported modules, as shown in the following table.

Prefix	YANG module	Reference
l0-types	ietf-layer0-types	[ietf-ccamp-layer0-types]
wson	ietf-wson-topology	[RFCXXXX]
nw	ietf-network	[RFC8345]
nt	ietf-network-topology	[RFC8345]
tet	ietf-te-topology	[ietf-teas-yang-te-topo]

Note: The RFC Editor will replace XXXX with the number assigned to the RFC once this draft becomes an RFC.

2. YANG Model (Tree Structure) for WSON topology

```

module: ietf-wson-topology
  augment /nw:networks/nw:network/nw:network-types/tet:te-topology:
    +-rw wson-topology!
  augment /nw:networks/nw:network/nw:node/tet:te
    /tet:te-node-attributes:
      +-rw wson-node!
      +-rw is-reconfigurable-node?  boolean
  augment /nw:networks/nw:network/nw:node/tet:te
    /tet:te-node-attributes/tet:connectivity-matrices
    /tet:label-restrictions/tet:label-restriction:
      +-rw grid-type?  identityref
      +-rw priority?   uint8
  augment /nw:networks/nw:network/nw:node/tet:te
    /tet:te-node-attributes/tet:connectivity-matrices
    /tet:label-restrictions/tet:label-restriction
    /tet:label-start/tet:te-label/tet:technology:
      +--:(wson)
        +-rw (grid-type)?
        +--:(dwdm)
          | +-rw dwdm-n?  l0-types:dwdm-n
        +--:(cwdm)
          +-rw cwdm-n?   l0-types:cwdm-n
  augment /nw:networks/nw:network/nw:node/tet:te
    /tet:te-node-attributes/tet:connectivity-matrices

```



```

        /tet:label-restrictions/tet:label-restriction
        /tet:label-end/tet:te-label/tet:technology:
+---:(wson)
  +---rw (grid-type)?
    +---:(dwdm)
      | +---rw dwdm-n?    l0-types:dwdm-n
    +---:(cwdm)
      +---rw cwdm-n?    l0-types:cwdm-n
augment /nw:networks/nw:network/nw:node/tet:te
  /tet:te-node-attributes/tet:connectivity-matrices
  /tet:label-restrictions/tet:label-restriction
  /tet:label-step/tet:technology:
+---:(wson)
  +---rw (l0-grid-type)?
    +---:(dwdm)
      | +---rw wson-dwdm-channel-spacing?  identityref
    +---:(cwdm)
      +---rw wson-cwdm-channel-spacing?  identityref
augment /nw:networks/nw:network/nw:node/tet:te
  /tet:te-node-attributes/tet:connectivity-matrices
  /tet:underlay/tet:primary-path/tet:path-element/tet:type
  /tet:label/tet:label-hop/tet:te-label/tet:technology:
+---:(wson)
  +---rw (grid-type)?
    +---:(dwdm)
      | +---rw (single-or-super-channel)?
      |   +---:(single)
      |     | +---rw dwdm-n?                l0-types:dwdm-n
      |     +---:(super)
      |       +---rw subcarrier-dwdm-n*    l0-types:dwdm-n
    +---:(cwdm)
      +---rw cwdm-n?                l0-types:cwdm-n
augment /nw:networks/nw:network/nw:node/tet:te
  /tet:te-node-attributes/tet:connectivity-matrices
  /tet:underlay/tet:backup-path/tet:path-element/tet:type
  /tet:label/tet:label-hop/tet:te-label/tet:technology:
+---:(wson)
  +---rw (grid-type)?
    +---:(dwdm)
      | +---rw (single-or-super-channel)?
      |   +---:(single)
      |     | +---rw dwdm-n?                l0-types:dwdm-n
      |     +---:(super)
      |       +---rw subcarrier-dwdm-n*    l0-types:dwdm-n
    +---:(cwdm)
      +---rw cwdm-n?                l0-types:cwdm-n
augment /nw:networks/nw:network/nw:node/tet:te
  /tet:te-node-attributes/tet:connectivity-matrices

```



```

        /tet:optimizations/tet:algorithm/tet:metric
        /tet:optimization-metric
        /tet:explicit-route-exclude-objects
        /tet:route-object-exclude-object/tet:type/tet:label
        /tet:label-hop/tet:te-label/tet:technology:
+---:(wson)
  +--rw (grid-type)?
    +---:(dwdm)
      | +--rw (single-or-super-channel)?
      |   +---:(single)
      |     | +--rw dwdm-n?                10-types:dwdm-n
      |     +---:(super)
      |       +--rw subcarrier-dwdm-n*    10-types:dwdm-n
    +---:(cwdm)
      +--rw cwdm-n?                      10-types:cwdm-n
augment /nw:networks/nw:network/nw:node/tet:te
  /tet:te-node-attributes/tet:connectivity-matrices
  /tet:optimizations/tet:algorithm/tet:metric
  /tet:optimization-metric
  /tet:explicit-route-include-objects
  /tet:route-object-include-object/tet:type/tet:label
  /tet:label-hop/tet:te-label/tet:technology:
+---:(wson)
  +--rw (grid-type)?
    +---:(dwdm)
      | +--rw (single-or-super-channel)?
      |   +---:(single)
      |     | +--rw dwdm-n?                10-types:dwdm-n
      |     +---:(super)
      |       +--rw subcarrier-dwdm-n*    10-types:dwdm-n
    +---:(cwdm)
      +--rw cwdm-n?                      10-types:cwdm-n
augment /nw:networks/nw:network/nw:node/tet:te
  /tet:te-node-attributes/tet:connectivity-matrices
  /tet:path-properties/tet:path-route-objects
  /tet:path-route-object/tet:type/tet:label/tet:label-hop
  /tet:te-label/tet:technology:
+---:(wson)
  +--ro (grid-type)?
    +---:(dwdm)
      | +--ro (single-or-super-channel)?
      |   +---:(single)
      |     | +--ro dwdm-n?                10-types:dwdm-n
      |     +---:(super)
      |       +--ro subcarrier-dwdm-n*    10-types:dwdm-n
    +---:(cwdm)
      +--ro cwdm-n?                      10-types:cwdm-n
augment /nw:networks/nw:network/nw:node/tet:te

```



```

        /tet:te-node-attributes/tet:connectivity-matrices
        /tet:connectivity-matrix/tet:from/tet:label-restrictions
        /tet:label-restriction:
+--rw grid-type?    identityref
+--rw priority?     uint8
augment /nw:networks/nw:network/nw:node/tet:te
    /tet:te-node-attributes/tet:connectivity-matrices
    /tet:connectivity-matrix/tet:from/tet:label-restrictions
    /tet:label-restriction/tet:label-start/tet:te-label
    /tet:technology:
+--:(wson)
+--rw (grid-type)?
+--:(dwdm)
|   +--rw dwdm-n?    10-types:dwdm-n
+--:(cwdm)
    +--rw cwdm-n?    10-types:cwdm-n
augment /nw:networks/nw:network/nw:node/tet:te
    /tet:te-node-attributes/tet:connectivity-matrices
    /tet:connectivity-matrix/tet:from/tet:label-restrictions
    /tet:label-restriction/tet:label-end/tet:te-label
    /tet:technology:
+--:(wson)
+--rw (grid-type)?
+--:(dwdm)
|   +--rw dwdm-n?    10-types:dwdm-n
+--:(cwdm)
    +--rw cwdm-n?    10-types:cwdm-n
augment /nw:networks/nw:network/nw:node/tet:te
    /tet:te-node-attributes/tet:connectivity-matrices
    /tet:connectivity-matrix/tet:from/tet:label-restrictions
    /tet:label-restriction/tet:label-step/tet:technology:
+--:(wson)
+--rw (l0-grid-type)?
+--:(dwdm)
|   +--rw wson-dwdm-channel-spacing?    identityref
+--:(cwdm)
    +--rw wson-cwdm-channel-spacing?    identityref
augment /nw:networks/nw:network/nw:node/tet:te
    /tet:te-node-attributes/tet:connectivity-matrices
    /tet:connectivity-matrix/tet:to/tet:label-restrictions
    /tet:label-restriction:
+--rw grid-type?    identityref
+--rw priority?     uint8
augment /nw:networks/nw:network/nw:node/tet:te
    /tet:te-node-attributes/tet:connectivity-matrices
    /tet:connectivity-matrix/tet:to/tet:label-restrictions
    /tet:label-restriction/tet:label-start/tet:te-label
    /tet:technology:

```



```

+--:(wson)
  +--rw (grid-type)?
    +--:(dwdm)
      | +--rw dwdm-n?    10-types:dwdm-n
    +--:(cwdm)
      +--rw cwdm-n?    10-types:cwdm-n
augment /nw:networks/nw:network/nw:node/tet:te
  /tet:te-node-attributes/tet:connectivity-matrices
  /tet:connectivity-matrix/tet:to/tet:label-restrictions
  /tet:label-restriction/tet:label-end/tet:te-label
  /tet:technology:
+--:(wson)
  +--rw (grid-type)?
    +--:(dwdm)
      | +--rw dwdm-n?    10-types:dwdm-n
    +--:(cwdm)
      +--rw cwdm-n?    10-types:cwdm-n
augment /nw:networks/nw:network/nw:node/tet:te
  /tet:te-node-attributes/tet:connectivity-matrices
  /tet:connectivity-matrix/tet:to/tet:label-restrictions
  /tet:label-restriction/tet:label-step/tet:technology:
+--:(wson)
  +--rw (l0-grid-type)?
    +--:(dwdm)
      | +--rw wson-dwdm-channel-spacing?  identityref
    +--:(cwdm)
      +--rw wson-cwdm-channel-spacing?  identityref
augment /nw:networks/nw:network/nw:node/tet:te
  /tet:te-node-attributes/tet:connectivity-matrices
  /tet:connectivity-matrix/tet:underlay/tet:primary-path
  /tet:path-element/tet:type/tet:label/tet:label-hop
  /tet:te-label/tet:technology:
+--:(wson)
  +--rw (grid-type)?
    +--:(dwdm)
      | +--rw (single-or-super-channel)?
      |   +--:(single)
      |     | +--rw dwdm-n?                10-types:dwdm-n
      |     +--:(super)
      |       +--rw subcarrier-dwdm-n*    10-types:dwdm-n
    +--:(cwdm)
      +--rw cwdm-n?                10-types:cwdm-n
augment /nw:networks/nw:network/nw:node/tet:te
  /tet:te-node-attributes/tet:connectivity-matrices
  /tet:connectivity-matrix/tet:underlay/tet:backup-path
  /tet:path-element/tet:type/tet:label/tet:label-hop
  /tet:te-label/tet:technology:
+--:(wson)

```



```

    +--rw (grid-type)?
      +--:(dwdm)
        | +--rw (single-or-super-channel)?
        |   +--:(single)
        |     | +--rw dwdm-n?                               10-types:dwdm-n
        |     +--:(super)
        |       +--rw subcarrier-dwdm-n*                   10-types:dwdm-n
      +--:(cwdm)
        +--rw cwdm-n?                                     10-types:cwdm-n
augment /nw:networks/nw:network/nw:node/tet:te
  /tet:te-node-attributes/tet:connectivity-matrices
  /tet:connectivity-matrix/tet:optimizations/tet:algorithm
  /tet:metric/tet:optimization-metric
  /tet:explicit-route-exclude-objects
  /tet:route-object-exclude-object/tet:type/tet:label
  /tet:label-hop/tet:te-label/tet:technology:
+--:(wson)
  +--rw (grid-type)?
    +--:(dwdm)
      | +--rw (single-or-super-channel)?
      |   +--:(single)
      |     | +--rw dwdm-n?                               10-types:dwdm-n
      |     +--:(super)
      |       +--rw subcarrier-dwdm-n*                   10-types:dwdm-n
    +--:(cwdm)
      +--rw cwdm-n?                                     10-types:cwdm-n
augment /nw:networks/nw:network/nw:node/tet:te
  /tet:te-node-attributes/tet:connectivity-matrices
  /tet:connectivity-matrix/tet:optimizations/tet:algorithm
  /tet:metric/tet:optimization-metric
  /tet:explicit-route-include-objects
  /tet:route-object-include-object/tet:type/tet:label
  /tet:label-hop/tet:te-label/tet:technology:
+--:(wson)
  +--rw (grid-type)?
    +--:(dwdm)
      | +--rw (single-or-super-channel)?
      |   +--:(single)
      |     | +--rw dwdm-n?                               10-types:dwdm-n
      |     +--:(super)
      |       +--rw subcarrier-dwdm-n*                   10-types:dwdm-n
    +--:(cwdm)
      +--rw cwdm-n?                                     10-types:cwdm-n
augment /nw:networks/nw:network/nw:node/tet:te
  /tet:te-node-attributes/tet:connectivity-matrices
  /tet:connectivity-matrix/tet:path-properties
  /tet:path-route-objects/tet:path-route-object/tet:type
  /tet:label/tet:label-hop/tet:te-label/tet:technology:

```



```

+--:(wson)
  +--ro (grid-type)?
    +--:(dwdm)
      | +--ro (single-or-super-channel)?
      |   +--:(single)
      |     | +--ro dwdm-n?          10-types:dwdm-n
      |     +--:(super)
      |       +--ro subcarrier-dwdm-n* 10-types:dwdm-n
    +--:(cwdm)
      +--ro cwdm-n?          10-types:cwdm-n
augment /nw:networks/nw:network/nw:node/tet:te
  /tet:information-source-entry/tet:connectivity-matrices
  /tet:label-restrictions/tet:label-restriction:
+--ro grid-type?  identityref
+--ro priority?   uint8
augment /nw:networks/nw:network/nw:node/tet:te
  /tet:information-source-entry/tet:connectivity-matrices
  /tet:label-restrictions/tet:label-restriction
  /tet:label-start/tet:te-label/tet:technology:
+--:(wson)
  +--ro (grid-type)?
    +--:(dwdm)
      | +--ro dwdm-n?  10-types:dwdm-n
    +--:(cwdm)
      +--ro cwdm-n?  10-types:cwdm-n
augment /nw:networks/nw:network/nw:node/tet:te
  /tet:information-source-entry/tet:connectivity-matrices
  /tet:label-restrictions/tet:label-restriction
  /tet:label-end/tet:te-label/tet:technology:
+--:(wson)
  +--ro (grid-type)?
    +--:(dwdm)
      | +--ro dwdm-n?  10-types:dwdm-n
    +--:(cwdm)
      +--ro cwdm-n?  10-types:cwdm-n
augment /nw:networks/nw:network/nw:node/tet:te
  /tet:information-source-entry/tet:connectivity-matrices
  /tet:label-restrictions/tet:label-restriction
  /tet:label-step/tet:technology:
+--:(wson)
  +--ro (l0-grid-type)?
    +--:(dwdm)
      | +--ro wson-dwdm-channel-spacing?  identityref
    +--:(cwdm)
      +--ro wson-cwdm-channel-spacing?  identityref
augment /nw:networks/nw:network/nw:node/tet:te
  /tet:information-source-entry/tet:connectivity-matrices
  /tet:underlay/tet:primary-path/tet:path-element/tet:type

```



```

        /tet:label/tet:label-hop/tet:te-label/tet:technology:
+--:(wson)
  +--ro (grid-type)?
    +--:(dwdm)
      | +--ro (single-or-super-channel)?
      |   +--:(single)
      |     | +--ro dwdm-n?                10-types:dwdm-n
      |     +--:(super)
      |       +--ro subcarrier-dwdm-n*    10-types:dwdm-n
    +--:(cwdm)
      +--ro cwdm-n?                10-types:cwdm-n
augment /nw:networks/nw:network/nw:node/tet:te
  /tet:information-source-entry/tet:connectivity-matrices
  /tet:underlay/tet:backup-path/tet:path-element/tet:type
  /tet:label/tet:label-hop/tet:te-label/tet:technology:
+--:(wson)
  +--ro (grid-type)?
    +--:(dwdm)
      | +--ro (single-or-super-channel)?
      |   +--:(single)
      |     | +--ro dwdm-n?                10-types:dwdm-n
      |     +--:(super)
      |       +--ro subcarrier-dwdm-n*    10-types:dwdm-n
    +--:(cwdm)
      +--ro cwdm-n?                10-types:cwdm-n
augment /nw:networks/nw:network/nw:node/tet:te
  /tet:information-source-entry/tet:connectivity-matrices
  /tet:optimizations/tet:algorithm/tet:metric
  /tet:optimization-metric
  /tet:explicit-route-exclude-objects
  /tet:route-object-exclude-object/tet:type/tet:label
  /tet:label-hop/tet:te-label/tet:technology:
+--:(wson)
  +--ro (grid-type)?
    +--:(dwdm)
      | +--ro (single-or-super-channel)?
      |   +--:(single)
      |     | +--ro dwdm-n?                10-types:dwdm-n
      |     +--:(super)
      |       +--ro subcarrier-dwdm-n*    10-types:dwdm-n
    +--:(cwdm)
      +--ro cwdm-n?                10-types:cwdm-n
augment /nw:networks/nw:network/nw:node/tet:te
  /tet:information-source-entry/tet:connectivity-matrices
  /tet:optimizations/tet:algorithm/tet:metric
  /tet:optimization-metric
  /tet:explicit-route-include-objects
  /tet:route-object-include-object/tet:type/tet:label

```



```

        /tet:label-hop/tet:te-label/tet:technology:
+--:(wson)
  +--ro (grid-type)?
    +--:(dwdm)
      | +--ro (single-or-super-channel)?
      |   +--:(single)
      |     | +--ro dwdm-n?          10-types:dwdm-n
      |     +--:(super)
      |       +--ro subcarrier-dwdm-n* 10-types:dwdm-n
    +--:(cwdm)
      +--ro cwdm-n?          10-types:cwdm-n
augment /nw:networks/nw:network/nw:node/tet:te
  /tet:information-source-entry/tet:connectivity-matrices
  /tet:path-properties/tet:path-route-objects
  /tet:path-route-object/tet:type/tet:label/tet:label-hop
  /tet:te-label/tet:technology:
+--:(wson)
  +--ro (grid-type)?
    +--:(dwdm)
      | +--ro (single-or-super-channel)?
      |   +--:(single)
      |     | +--ro dwdm-n?          10-types:dwdm-n
      |     +--:(super)
      |       +--ro subcarrier-dwdm-n* 10-types:dwdm-n
    +--:(cwdm)
      +--ro cwdm-n?          10-types:cwdm-n
augment /nw:networks/nw:network/nw:node/tet:te
  /tet:information-source-entry/tet:connectivity-matrices
  /tet:connectivity-matrix/tet:from/tet:label-restrictions
  /tet:label-restriction:
+--ro grid-type?    identityref
+--ro priority?     uint8
augment /nw:networks/nw:network/nw:node/tet:te
  /tet:information-source-entry/tet:connectivity-matrices
  /tet:connectivity-matrix/tet:from/tet:label-restrictions
  /tet:label-restriction/tet:label-start/tet:te-label
  /tet:technology:
+--:(wson)
  +--ro (grid-type)?
    +--:(dwdm)
      | +--ro dwdm-n?    10-types:dwdm-n
    +--:(cwdm)
      +--ro cwdm-n?    10-types:cwdm-n
augment /nw:networks/nw:network/nw:node/tet:te
  /tet:information-source-entry/tet:connectivity-matrices
  /tet:connectivity-matrix/tet:from/tet:label-restrictions
  /tet:label-restriction/tet:label-end/tet:te-label
  /tet:technology:

```



```

+--:(wson)
  +--ro (grid-type)?
    +--:(dwdm)
      | +--ro dwdm-n? 10-types:dwdm-n
    +--:(cwdm)
      +--ro cwdm-n? 10-types:cwdm-n
augment /nw:networks/nw:network/nw:node/tet:te
  /tet:information-source-entry/tet:connectivity-matrices
  /tet:connectivity-matrix/tet:from/tet:label-restrictions
  /tet:label-restriction/tet:label-step/tet:technology:
+--:(wson)
  +--ro (l0-grid-type)?
    +--:(dwdm)
      | +--ro wson-dwdm-channel-spacing? identityref
    +--:(cwdm)
      +--ro wson-cwdm-channel-spacing? identityref
augment /nw:networks/nw:network/nw:node/tet:te
  /tet:information-source-entry/tet:connectivity-matrices
  /tet:connectivity-matrix/tet:to/tet:label-restrictions
  /tet:label-restriction:
+--ro grid-type? identityref
+--ro priority? uint8
augment /nw:networks/nw:network/nw:node/tet:te
  /tet:information-source-entry/tet:connectivity-matrices
  /tet:connectivity-matrix/tet:to/tet:label-restrictions
  /tet:label-restriction/tet:label-start/tet:te-label
  /tet:technology:
+--:(wson)
  +--ro (grid-type)?
    +--:(dwdm)
      | +--ro dwdm-n? 10-types:dwdm-n
    +--:(cwdm)
      +--ro cwdm-n? 10-types:cwdm-n
augment /nw:networks/nw:network/nw:node/tet:te
  /tet:information-source-entry/tet:connectivity-matrices
  /tet:connectivity-matrix/tet:to/tet:label-restrictions
  /tet:label-restriction/tet:label-end/tet:te-label
  /tet:technology:
+--:(wson)
  +--ro (grid-type)?
    +--:(dwdm)
      | +--ro dwdm-n? 10-types:dwdm-n
    +--:(cwdm)
      +--ro cwdm-n? 10-types:cwdm-n
augment /nw:networks/nw:network/nw:node/tet:te
  /tet:information-source-entry/tet:connectivity-matrices
  /tet:connectivity-matrix/tet:to/tet:label-restrictions
  /tet:label-restriction/tet:label-step/tet:technology:

```



```

+--:(wson)
  +--ro (l0-grid-type)?
    +--:(dwdm)
      | +--ro wson-dwdm-channel-spacing?  identityref
    +--:(cwdm)
      +--ro wson-cwdm-channel-spacing?  identityref
augment /nw:networks/nw:network/nw:node/tet:te
  /tet:information-source-entry/tet:connectivity-matrices
  /tet:connectivity-matrix/tet:underlay/tet:primary-path
  /tet:path-element/tet:type/tet:label/tet:label-hop
  /tet:te-label/tet:technology:
+--:(wson)
  +--ro (grid-type)?
    +--:(dwdm)
      | +--ro (single-or-super-channel)?
      |   +--:(single)
      |     | +--ro dwdm-n?  l0-types:dwdm-n
      |     +--:(super)
      |       +--ro subcarrier-dwdm-n*  l0-types:dwdm-n
    +--:(cwdm)
      +--ro cwdm-n?  l0-types:cwdm-n
augment /nw:networks/nw:network/nw:node/tet:te
  /tet:information-source-entry/tet:connectivity-matrices
  /tet:connectivity-matrix/tet:underlay/tet:backup-path
  /tet:path-element/tet:type/tet:label/tet:label-hop
  /tet:te-label/tet:technology:
+--:(wson)
  +--ro (grid-type)?
    +--:(dwdm)
      | +--ro (single-or-super-channel)?
      |   +--:(single)
      |     | +--ro dwdm-n?  l0-types:dwdm-n
      |     +--:(super)
      |       +--ro subcarrier-dwdm-n*  l0-types:dwdm-n
    +--:(cwdm)
      +--ro cwdm-n?  l0-types:cwdm-n
augment /nw:networks/nw:network/nw:node/tet:te
  /tet:information-source-entry/tet:connectivity-matrices
  /tet:connectivity-matrix/tet:optimizations/tet:algorithm
  /tet:metric/tet:optimization-metric
  /tet:explicit-route-exclude-objects
  /tet:route-object-exclude-object/tet:type/tet:label
  /tet:label-hop/tet:te-label/tet:technology:
+--:(wson)
  +--ro (grid-type)?
    +--:(dwdm)
      | +--ro (single-or-super-channel)?
      |   +--:(single)

```



```

    |      | +--ro dwdm-n?          10-types:dwdm-n
    |      +--:(super)
    |      +--ro subcarrier-dwdm-n* 10-types:dwdm-n
+--:(cwdm)
    +--ro cwdm-n?          10-types:cwdm-n
augment /nw:networks/nw:network/nw:node/tet:te
    /tet:information-source-entry/tet:connectivity-matrices
    /tet:connectivity-matrix/tet:optimizations/tet:algorithm
    /tet:metric/tet:optimization-metric
    /tet:explicit-route-include-objects
    /tet:route-object-include-object/tet:type/tet:label
    /tet:label-hop/tet:te-label/tet:technology:
+--:(wson)
    +--ro (grid-type)?
    +--:(dwdm)
    | +--ro (single-or-super-channel)?
    |   +--:(single)
    |   | +--ro dwdm-n?          10-types:dwdm-n
    |   +--:(super)
    |   +--ro subcarrier-dwdm-n* 10-types:dwdm-n
    +--:(cwdm)
    +--ro cwdm-n?          10-types:cwdm-n
augment /nw:networks/nw:network/nw:node/tet:te
    /tet:information-source-entry/tet:connectivity-matrices
    /tet:connectivity-matrix/tet:path-properties
    /tet:path-route-objects/tet:path-route-object/tet:type
    /tet:label/tet:label-hop/tet:te-label/tet:technology:
+--:(wson)
    +--ro (grid-type)?
    +--:(dwdm)
    | +--ro (single-or-super-channel)?
    |   +--:(single)
    |   | +--ro dwdm-n?          10-types:dwdm-n
    |   +--:(super)
    |   +--ro subcarrier-dwdm-n* 10-types:dwdm-n
    +--:(cwdm)
    +--ro cwdm-n?          10-types:cwdm-n
augment /nw:networks/nw:network/nw:node/tet:te
    /tet:tunnel-termination-point
    /tet:local-link-connectivities/tet:label-restrictions
    /tet:label-restriction:
+--rw grid-type?    identityref
+--rw priority?     uint8
augment /nw:networks/nw:network/nw:node/tet:te
    /tet:tunnel-termination-point
    /tet:local-link-connectivities/tet:label-restrictions
    /tet:label-restriction/tet:label-start/tet:te-label
    /tet:technology:

```



```

+--:(wson)
  +--rw (grid-type)?
    +--:(dwdm)
      | +--rw dwdm-n?    10-types:dwdm-n
    +--:(cwdm)
      +--rw cwdm-n?    10-types:cwdm-n
augment /nw:networks/nw:network/nw:node/tet:te
  /tet:tunnel-termination-point
  /tet:local-link-connectivities/tet:label-restrictions
  /tet:label-restriction/tet:label-end/tet:te-label
  /tet:technology:
+--:(wson)
  +--rw (grid-type)?
    +--:(dwdm)
      | +--rw dwdm-n?    10-types:dwdm-n
    +--:(cwdm)
      +--rw cwdm-n?    10-types:cwdm-n
augment /nw:networks/nw:network/nw:node/tet:te
  /tet:tunnel-termination-point
  /tet:local-link-connectivities/tet:label-restrictions
  /tet:label-restriction/tet:label-step/tet:technology:
+--:(wson)
  +--rw (l0-grid-type)?
    +--:(dwdm)
      | +--rw wson-dwdm-channel-spacing?  identityref
    +--:(cwdm)
      +--rw wson-cwdm-channel-spacing?  identityref
augment /nw:networks/nw:network/nw:node/tet:te
  /tet:tunnel-termination-point
  /tet:local-link-connectivities/tet:underlay
  /tet:primary-path/tet:path-element/tet:type/tet:label
  /tet:label-hop/tet:te-label/tet:technology:
+--:(wson)
  +--rw (grid-type)?
    +--:(dwdm)
      | +--rw (single-or-super-channel)?
      |   +--:(single)
      |     | +--rw dwdm-n?                10-types:dwdm-n
      |     +--:(super)
      |       +--rw subcarrier-dwdm-n*    10-types:dwdm-n
    +--:(cwdm)
      +--rw cwdm-n?                10-types:cwdm-n
augment /nw:networks/nw:network/nw:node/tet:te
  /tet:tunnel-termination-point
  /tet:local-link-connectivities/tet:underlay
  /tet:backup-path/tet:path-element/tet:type/tet:label
  /tet:label-hop/tet:te-label/tet:technology:
+--:(wson)

```



```

    +--rw (grid-type)?
      +--:(dwdm)
        | +--rw (single-or-super-channel)?
        |   +--:(single)
        |     | +--rw dwdm-n?                                10-types:dwdm-n
        |     +--:(super)
        |       +--rw subcarrier-dwdm-n*                    10-types:dwdm-n
      +--:(cwdm)
        +--rw cwdm-n?                                      10-types:cwdm-n
augment /nw:networks/nw:network/nw:node/tet:te
  /tet:tunnel-termination-point
  /tet:local-link-connectivities/tet:optimizations
  /tet:algorithm/tet:metric/tet:optimization-metric
  /tet:explicit-route-exclude-objects
  /tet:route-object-exclude-object/tet:type/tet:label
  /tet:label-hop/tet:te-label/tet:technology:
+--:(wson)
  +--rw (grid-type)?
    +--:(dwdm)
      | +--rw (single-or-super-channel)?
      |   +--:(single)
      |     | +--rw dwdm-n?                                10-types:dwdm-n
      |     +--:(super)
      |       +--rw subcarrier-dwdm-n*                    10-types:dwdm-n
    +--:(cwdm)
      +--rw cwdm-n?                                      10-types:cwdm-n
augment /nw:networks/nw:network/nw:node/tet:te
  /tet:tunnel-termination-point
  /tet:local-link-connectivities/tet:optimizations
  /tet:algorithm/tet:metric/tet:optimization-metric
  /tet:explicit-route-include-objects
  /tet:route-object-include-object/tet:type/tet:label
  /tet:label-hop/tet:te-label/tet:technology:
+--:(wson)
  +--rw (grid-type)?
    +--:(dwdm)
      | +--rw (single-or-super-channel)?
      |   +--:(single)
      |     | +--rw dwdm-n?                                10-types:dwdm-n
      |     +--:(super)
      |       +--rw subcarrier-dwdm-n*                    10-types:dwdm-n
    +--:(cwdm)
      +--rw cwdm-n?                                      10-types:cwdm-n
augment /nw:networks/nw:network/nw:node/tet:te
  /tet:tunnel-termination-point
  /tet:local-link-connectivities/tet:path-properties
  /tet:path-route-objects/tet:path-route-object/tet:type
  /tet:label/tet:label-hop/tet:te-label/tet:technology:

```



```

+--:(wson)
  +--ro (grid-type)?
    +--:(dwdm)
      | +--ro (single-or-super-channel)?
      |   +--:(single)
      |     | +--ro dwdm-n?          10-types:dwdm-n
      |     +--:(super)
      |       +--ro subcarrier-dwdm-n* 10-types:dwdm-n
    +--:(cwdm)
      +--ro cwdm-n?          10-types:cwdm-n
augment /nw:networks/nw:network/nw:node/tet:te
  /tet:tunnel-termination-point
  /tet:local-link-connectivities
  /tet:local-link-connectivity/tet:label-restrictions
  /tet:label-restriction:
+--rw grid-type?    identityref
+--rw priority?     uint8
augment /nw:networks/nw:network/nw:node/tet:te
  /tet:tunnel-termination-point
  /tet:local-link-connectivities
  /tet:local-link-connectivity/tet:label-restrictions
  /tet:label-restriction/tet:label-start/tet:te-label
  /tet:technology:
+--:(wson)
  +--rw (grid-type)?
    +--:(dwdm)
      | +--rw dwdm-n?    10-types:dwdm-n
    +--:(cwdm)
      +--rw cwdm-n?    10-types:cwdm-n
augment /nw:networks/nw:network/nw:node/tet:te
  /tet:tunnel-termination-point
  /tet:local-link-connectivities
  /tet:local-link-connectivity/tet:label-restrictions
  /tet:label-restriction/tet:label-end/tet:te-label
  /tet:technology:
+--:(wson)
  +--rw (grid-type)?
    +--:(dwdm)
      | +--rw dwdm-n?    10-types:dwdm-n
    +--:(cwdm)
      +--rw cwdm-n?    10-types:cwdm-n
augment /nw:networks/nw:network/nw:node/tet:te
  /tet:tunnel-termination-point
  /tet:local-link-connectivities
  /tet:local-link-connectivity/tet:label-restrictions
  /tet:label-restriction/tet:label-step/tet:technology:
+--:(wson)
  +--rw (l0-grid-type)?

```



```

    +--:(dwdm)
    |   +--rw wson-dwdm-channel-spacing?  identityref
    +--:(cwdm)
    |   +--rw wson-cwdm-channel-spacing?  identityref
augment /nw:networks/nw:network/nw:node/tet:te
    /tet:tunnel-termination-point
    /tet:local-link-connectivities
    /tet:local-link-connectivity/tet:underlay
    /tet:primary-path/tet:path-element/tet:type/tet:label
    /tet:label-hop/tet:te-label/tet:technology:
+--:(wson)
+--rw (grid-type)?
+--:(dwdm)
|   +--rw (single-or-super-channel)?
|   |   +--:(single)
|   |   |   +--rw dwdm-n?                  10-types:dwdm-n
|   |   +--:(super)
|   |       +--rw subcarrier-dwdm-n*       10-types:dwdm-n
+--:(cwdm)
    +--rw cwdm-n?                          10-types:cwdm-n
augment /nw:networks/nw:network/nw:node/tet:te
    /tet:tunnel-termination-point
    /tet:local-link-connectivities
    /tet:local-link-connectivity/tet:underlay/tet:backup-path
    /tet:path-element/tet:type/tet:label/tet:label-hop
    /tet:te-label/tet:technology:
+--:(wson)
+--rw (grid-type)?
+--:(dwdm)
|   +--rw (single-or-super-channel)?
|   |   +--:(single)
|   |   |   +--rw dwdm-n?                  10-types:dwdm-n
|   |   +--:(super)
|   |       +--rw subcarrier-dwdm-n*       10-types:dwdm-n
+--:(cwdm)
    +--rw cwdm-n?                          10-types:cwdm-n
augment /nw:networks/nw:network/nw:node/tet:te
    /tet:tunnel-termination-point
    /tet:local-link-connectivities
    /tet:local-link-connectivity/tet:optimizations
    /tet:algorithm/tet:metric/tet:optimization-metric
    /tet:explicit-route-exclude-objects
    /tet:route-object-exclude-object/tet:type/tet:label
    /tet:label-hop/tet:te-label/tet:technology:
+--:(wson)
+--rw (grid-type)?
+--:(dwdm)
|   +--rw (single-or-super-channel)?

```



```

    |      +--:(single)
    |      | +--rw dwdm-n?          10-types:dwdm-n
    |      +--:(super)
    |      +--rw subcarrier-dwdm-n* 10-types:dwdm-n
+--:(cwdm)
    +--rw cwdm-n?          10-types:cwdm-n
augment /nw:networks/nw:network/nw:node/tet:te
    /tet:tunnel-termination-point
    /tet:local-link-connectivities
    /tet:local-link-connectivity/tet:optimizations
    /tet:algorithm/tet:metric/tet:optimization-metric
    /tet:explicit-route-include-objects
    /tet:route-object-include-object/tet:type/tet:label
    /tet:label-hop/tet:te-label/tet:technology:
+--:(wson)
    +--rw (grid-type)?
    +--:(dwdm)
    | +--rw (single-or-super-channel)?
    | +--:(single)
    | | +--rw dwdm-n?          10-types:dwdm-n
    | +--:(super)
    | +--rw subcarrier-dwdm-n* 10-types:dwdm-n
    +--:(cwdm)
    +--rw cwdm-n?          10-types:cwdm-n
augment /nw:networks/nw:network/nw:node/tet:te
    /tet:tunnel-termination-point
    /tet:local-link-connectivities
    /tet:local-link-connectivity/tet:path-properties
    /tet:path-route-objects/tet:path-route-object/tet:type
    /tet:label/tet:label-hop/tet:te-label/tet:technology:
+--:(wson)
    +--ro (grid-type)?
    +--:(dwdm)
    | +--ro (single-or-super-channel)?
    | +--:(single)
    | | +--ro dwdm-n?          10-types:dwdm-n
    | +--:(super)
    | +--ro subcarrier-dwdm-n* 10-types:dwdm-n
    +--:(cwdm)
    +--ro cwdm-n?          10-types:cwdm-n
augment /nw:networks/nw:network/nt:link/tet:te
    /tet:te-link-attributes/tet:underlay/tet:primary-path
    /tet:path-element/tet:type/tet:label/tet:label-hop
    /tet:te-label/tet:technology:
+--:(wson)
    +--rw (grid-type)?
    +--:(dwdm)
    | +--rw (single-or-super-channel)?

```



```

    |      +--:(single)
    |      | +--rw dwdm-n?          10-types:dwdm-n
    |      +--:(super)
    |      +--rw subcarrier-dwdm-n* 10-types:dwdm-n
+--:(cwdm)
    +--rw cwdm-n?          10-types:cwdm-n
augment /nw:networks/nw:network/nt:link/tet:te
    /tet:te-link-attributes/tet:underlay/tet:backup-path
    /tet:path-element/tet:type/tet:label/tet:label-hop
    /tet:te-label/tet:technology:
+--:(wson)
    +--rw (grid-type)?
    +--:(dwdm)
    | +--rw (single-or-super-channel)?
    | +--:(single)
    | | +--rw dwdm-n?          10-types:dwdm-n
    | +--:(super)
    | +--rw subcarrier-dwdm-n* 10-types:dwdm-n
    +--:(cwdm)
    +--rw cwdm-n?          10-types:cwdm-n
augment /nw:networks/nw:network/nt:link/tet:te
    /tet:te-link-attributes/tet:label-restrictions
    /tet:label-restriction:
    +--rw grid-type?    identityref
    +--rw priority?    uint8
augment /nw:networks/nw:network/nt:link/tet:te
    /tet:te-link-attributes/tet:label-restrictions
    /tet:label-restriction/tet:label-start/tet:te-label
    /tet:technology:
+--:(wson)
    +--rw (grid-type)?
    +--:(dwdm)
    | +--rw dwdm-n?    10-types:dwdm-n
    +--:(cwdm)
    +--rw cwdm-n?    10-types:cwdm-n
augment /nw:networks/nw:network/nt:link/tet:te
    /tet:te-link-attributes/tet:label-restrictions
    /tet:label-restriction/tet:label-end/tet:te-label
    /tet:technology:
+--:(wson)
    +--rw (grid-type)?
    +--:(dwdm)
    | +--rw dwdm-n?    10-types:dwdm-n
    +--:(cwdm)
    +--rw cwdm-n?    10-types:cwdm-n
augment /nw:networks/nw:network/nt:link/tet:te
    /tet:te-link-attributes/tet:label-restrictions
    /tet:label-restriction/tet:label-step/tet:technology:

```



```

+--:(wson)
  +--rw (l0-grid-type)?
    +--:(dwdm)
      | +--rw wson-dwdm-channel-spacing?  identityref
    +--:(cwdm)
      +--rw wson-cwdm-channel-spacing?  identityref
augment /nw:networks/nw:network/nt:link/tet:te
  /tet:information-source-entry/tet:label-restrictions
  /tet:label-restriction:
+--ro grid-type?  identityref
+--ro priority?    uint8
augment /nw:networks/nw:network/nt:link/tet:te
  /tet:information-source-entry/tet:label-restrictions
  /tet:label-restriction/tet:label-start/tet:te-label
  /tet:technology:
+--:(wson)
  +--ro (grid-type)?
  +--:(dwdm)
    | +--ro dwdm-n?  l0-types:dwdm-n
  +--:(cwdm)
    +--ro cwdm-n?  l0-types:cwdm-n
augment /nw:networks/nw:network/nt:link/tet:te
  /tet:information-source-entry/tet:label-restrictions
  /tet:label-restriction/tet:label-end/tet:te-label
  /tet:technology:
+--:(wson)
  +--ro (grid-type)?
  +--:(dwdm)
    | +--ro dwdm-n?  l0-types:dwdm-n
  +--:(cwdm)
    +--ro cwdm-n?  l0-types:cwdm-n
augment /nw:networks/nw:network/nt:link/tet:te
  /tet:information-source-entry/tet:label-restrictions
  /tet:label-restriction/tet:label-step/tet:technology:
+--:(wson)
  +--ro (l0-grid-type)?
  +--:(dwdm)
    | +--ro wson-dwdm-channel-spacing?  identityref
  +--:(cwdm)
    +--ro wson-cwdm-channel-spacing?  identityref
augment /nw:networks/tet:te/tet:templates/tet:link-template
  /tet:te-link-attributes/tet:underlay/tet:primary-path
  /tet:path-element/tet:type/tet:label/tet:label-hop
  /tet:te-label/tet:technology:
+--:(wson)
  +--rw (grid-type)?
  +--:(dwdm)
    | +--rw (single-or-super-channel)?

```



```

    |      +--:(single)
    |      |      +--rw dwdm-n?          10-types:dwdm-n
    |      +--:(super)
    |      +--rw subcarrier-dwdm-n*      10-types:dwdm-n
+--:(cwdm)
    +--rw cwdm-n?          10-types:cwdm-n
augment /nw:networks/tet:te/tet:templates/tet:link-template
    /tet:te-link-attributes/tet:underlay/tet:backup-path
    /tet:path-element/tet:type/tet:label/tet:label-hop
    /tet:te-label/tet:technology:
+--:(wson)
    +--rw (grid-type)?
    +--:(dwdm)
    |   +--rw (single-or-super-channel)?
    |   +--:(single)
    |   |   +--rw dwdm-n?          10-types:dwdm-n
    |   +--:(super)
    |   +--rw subcarrier-dwdm-n*      10-types:dwdm-n
    +--:(cwdm)
    +--rw cwdm-n?          10-types:cwdm-n
augment /nw:networks/tet:te/tet:templates/tet:link-template
    /tet:te-link-attributes/tet:label-restrictions
    /tet:label-restriction:
    +--rw grid-type?      identityref
    +--rw priority?       uint8
augment /nw:networks/tet:te/tet:templates/tet:link-template
    /tet:te-link-attributes/tet:label-restrictions
    /tet:label-restriction/tet:label-start/tet:te-label
    /tet:technology:
+--:(wson)
    +--rw (grid-type)?
    +--:(dwdm)
    |   +--rw dwdm-n?      10-types:dwdm-n
    +--:(cwdm)
    +--rw cwdm-n?      10-types:cwdm-n
augment /nw:networks/tet:te/tet:templates/tet:link-template
    /tet:te-link-attributes/tet:label-restrictions
    /tet:label-restriction/tet:label-end/tet:te-label
    /tet:technology:
+--:(wson)
    +--rw (grid-type)?
    +--:(dwdm)
    |   +--rw dwdm-n?      10-types:dwdm-n
    +--:(cwdm)
    +--rw cwdm-n?      10-types:cwdm-n
augment /nw:networks/tet:te/tet:templates/tet:link-template
    /tet:te-link-attributes/tet:label-restrictions
    /tet:label-restriction/tet:label-step/tet:technology:

```



```
+--:(wson)
  +--rw (l0-grid-type)?
    +--:(dwdm)
      | +--rw wson-dwdm-channel-spacing?  identityref
    +--:(cwdm)
      +--rw wson-cwdm-channel-spacing?  identityref
```

3. The YANG Code for WSON topology

```
<CODE BEGINS> file "ietf-wson-topology@2020-09-21.yang"
module ietf-wson-topology {

  yang-version 1.1;

  namespace "urn:ietf:params:xml:ns:yang:ietf-wson-topology";

  prefix "wson";

  import ietf-network {
    prefix "nw";
    reference
      "RFC 8345: A YANG Data Model for Network Topologies";
  }

  import ietf-network-topology {
    prefix "nt";
    reference
      "RFC 8345: A YANG Data Model for Network Topologies";
  }

  import ietf-te-topology {
    prefix "tet";
    reference
      "RFC 8795: YANG Data Model for
      Traffic Engineering (TE) Topologies";
  }

  /* Note: The RFC Editor will replace YYYY with the number assigned
     to the RFC once draft-ietf-teas-yang-te-topo becomes an RFC.*/

  import ietf-layer0-types {
    prefix "l0-types";
    reference
      "RFC XXXX: A YANG Data Model for Layer 0 Types";
  }
}
```



```
/* Note: The RFC Editor will replace XXXX with the number assigned
   to the RFC once draft-ietf-ccamp-layer0-types becomes an RFC.*/
```

```
organization
```

```
  "IETF CCAMP Working Group";
```

```
contact
```

```
  "Editor:  Haomian Zheng  <zhenghaomian@huawei.com>
```

```
  Editor:  Young Lee  <younglee.tx@gmail.com>
```

```
  Editor:  Aihua Guo  <aihuaguo.ietf@gmail.com>
```

```
  Editor:  Victor Lopez <victor.lopezalvarez@telefonica.com>
```

```
  Editor:  Daniel King  <d.king@lancaster.ac.uk>";
```

```
description
```

```
  "This module provides a YANG data model for the routing and
   wavelength assignment (RWA) Traffic Engineering (TE)
   topology in wavelength switched optical networks (WSONs).
   The YANG model described in this document is a WSON
   technology-specific YANG model augmenting the generic TE
   topology module (ietf-te-topology) based on the information
   model developed in RFC 7446 and the two encoding documents
   RFC 7579 and RFC 7581.
```

```
  Copyright (c) 2020 IETF Trust and the persons identified
  as authors of the code.  All rights reserved.
```

```
  Redistribution and use in source and binary forms, with
  or without modification, is permitted pursuant to, and
  subject to the license terms contained in, the Simplified
  BSD License set forth in Section 4.c of the IETF Trust's
  Legal Provisions Relating to IETF Documents
  (http://trustee.ietf.org/license-info).
```

```
  This version of this YANG module is part of RFC XXXX; see
  the RFC itself for full legal notices.";
```

```
revision 2020-09-21 {
```

```
  description
```

```
    "Initial Version";
```

```
  reference
```

```
    "RFC XXXX: A YANG Data Model for WSON (Wavelength Switched
    Optical Networks)";
```

```
}
```

```
/*
```

```
 * Data nodes
```

```
*/
```



```
augment "/nw:networks/nw:network/nw:network-types"
  + "/tet:te-topology" {
    description
      "Augment network types to define WSON topology type.";
    container wson-topology {
      presence
        "Its presence identifies the WSON topology type.";
      description
        "Introduce new network type for WSON topology.";
    }
  }

augment "/nw:networks/nw:network/nw:node/tet:te"
  + "/tet:te-node-attributes" {
    when "/nw:networks/nw:network/nw:network-types"
      + "/tet:te-topology/wson:wson-topology" {
      description
        "Augmentation parameters apply only for networks with
        WSON topology type.";
    }
    description "Augment TE node attributes.";
    container wson-node {
      presence "The TE node is a WSON node.";
      description "WSON node attributes";
      leaf is-reconfigurable-node {
        type boolean;
        default true;
        description
          "Indicates whether the WSON node is reconfigurable:
          - true: the node is reconfigurable, i.e.,
              it is representing a ROADM node;
          - false: the node is not reconfigurable, i.e.,
              it is representing a FOADM node.";
      }
    }
  }
}

/*
 * Augment TE label range information
 */

augment "/nw:networks/nw:network/nw:node/tet:te/"
  + "tet:te-node-attributes/tet:connectivity-matrices/"
  + "tet:label-restrictions/tet:label-restriction" {
    when "../..../nw:network-types/tet:te-topology/"
      + "wson:wson-topology" {
      description
        "Augmentation parameters apply only for networks with
```



```
        WSOON topology type.";
    }
    description
        "Augment TE label range information for the TE node
        connectivity matrices.";
    uses l0-types:l0-label-range-info;
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
    + "tet:te-node-attributes/tet:connectivity-matrices/"
    + "tet:connectivity-matrix/tet:from/"
    + "tet:label-restrictions/tet:label-restriction" {
    when "../../../../../../../nw:network-types/tet:te-topology/"
        + "wson:wson-topology" {
        description
            "Augmentation parameters apply only for networks with
            WSOON topology type.";
    }
    description
        "Augment TE label range information for the source LTP
        of the connectivity matrix entry.";
    uses l0-types:l0-label-range-info;
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
    + "tet:te-node-attributes/tet:connectivity-matrices/"
    + "tet:connectivity-matrix/tet:to/"
    + "tet:label-restrictions/tet:label-restriction" {
    when "../../../../../../../nw:network-types/tet:te-topology/"
        + "wson:wson-topology" {
        description
            "Augmentation parameters apply only for networks with
            WSOON topology type.";
    }
    description
        "Augment TE label range information for the destination LTP
        of the connectivity matrix entry.";
    uses l0-types:l0-label-range-info;
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
    + "tet:information-source-entry/"
    + "tet:connectivity-matrices/tet:label-restrictions/"
    + "tet:label-restriction" {
    when "../../../../../../../nw:network-types/tet:te-topology/"
        + "wson:wson-topology" {
        description
            "Augmentation parameters apply only for networks with
```



```
        WSON topology type.";
    }
    description
        "Augment TE label range information for the TE node
        connectivity matrices information source.";
    uses l0-types:l0-label-range-info;
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
    + "tet:information-source-entry/tet:connectivity-matrices/"
    + "tet:connectivity-matrix/"
    + "tet:from/tet:label-restrictions/tet:label-restriction" {
    when "../..//..//..//..//..//..//nw:network-types/tet:te-topology/"
        + "wson:wson-topology" {
        description
            "Augmentation parameters apply only for networks with
            WSON topology type.";
    }
    description
        "Augment TE label range information for the source LTP
        of the connectivity matrix entry information source.";
    uses l0-types:l0-label-range-info;
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
    + "tet:information-source-entry/tet:connectivity-matrices/"
    + "tet:connectivity-matrix/"
    + "tet:to/tet:label-restrictions/tet:label-restriction" {
    when "../..//..//..//..//..//..//nw:network-types/tet:te-topology/"
        + "wson:wson-topology" {
        description
            "Augmentation parameters apply only for networks with
            WSON topology type.";
    }
    description
        "Augment TE label range information for the destination LTP
        of the connectivity matrix entry information source.";
    uses l0-types:l0-label-range-info;
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
    + "tet:tunnel-termination-point/"
    + "tet:local-link-connectivities/"
    + "tet:label-restrictions/tet:label-restriction" {
    when "../..//..//..//..//..//nw:network-types/tet:te-topology/"
        + "wson:wson-topology" {
        description
            "Augmentation parameters apply only for networks with
```



```
        WSON topology type.";
    }
    description
        "Augment TE label range information for the TTP
        Local Link Connectivities.";
    uses l0-types:l0-label-range-info;
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
    + "tet:tunnel-termination-point/"
    + "tet:local-link-connectivities/"
    + "tet:local-link-connectivity/"
    + "tet:label-restrictions/tet:label-restriction" {
    when "../../../../../../../nw:network-types/tet:te-topology/"
        + "wson:wson-topology" {
        description
            "Augmentation parameters apply only for networks with
            WSON topology type.";
    }
    description
        "Augment TE label range information for the TTP
        Local Link Connectivity entry.";
    uses l0-types:l0-label-range-info;
}

augment "/nw:networks/nw:network/nt:link/tet:te/"
    + "tet:te-link-attributes/"
    + "tet:label-restrictions/tet:label-restriction" {
    when "../../../../../../../nw:network-types/tet:te-topology/"
        + "wson:wson-topology" {
        description
            "Augmentation parameters apply only for networks with
            WSON topology type.";
    }
    description
        "Augment TE label range information for the TE link.";
    uses l0-types:l0-label-range-info;
}

augment "/nw:networks/nw:network/nt:link/tet:te/"
    + "tet:information-source-entry/"
    + "tet:label-restrictions/tet:label-restriction" {
    when "../../../../../../../nw:network-types/tet:te-topology/"
        + "wson:wson-topology" {
        description
            "Augmentation parameters apply only for networks with
            WSON topology type.";
    }
}
```



```
description
  "Augment TE label range information for the TE link
  information source.";
uses l0-types:l0-label-range-info;
}

augment "/nw:networks/tet:te/tet:templates/"
  + "tet:link-template/tet:te-link-attributes/"
  + "tet:label-restrictions/tet:label-restriction" {
  description
    "Augment TE label range information for the TE link template.";
  uses l0-types:l0-label-range-info;
}

/*
 * Augment TE label
 */

augment "/nw:networks/nw:network/nw:node/tet:te/"
  + "tet:te-node-attributes/tet:connectivity-matrices/"
  + "tet:label-restrictions/tet:label-restriction/"
  + "tet:label-start/"
  + "tet:te-label/tet:technology" {
  when "../../../../../../../nw:network-types/tet:te-topology/"
    + "wson:wson-topology" {
    description
      "Augmentation parameters apply only for networks with
      WSON topology type.";
  }
  description
    "Augment TE label range start for the TE node
    connectivity matrices";
  case wson {
    uses l0-types:wson-label-start-end;
  }
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
  + "tet:te-node-attributes/tet:connectivity-matrices/"
  + "tet:label-restrictions/"
  + "tet:label-restriction/tet:label-end/"
  + "tet:te-label/tet:technology" {
  when "../../../../../../../nw:network-types/tet:te-topology/"
    + "wson:wson-topology" {
    description
      "Augmentation parameters apply only for networks with
      WSON topology type.";
  }
}
```



```
description
  "Augment TE label range end for the TE node
  connectivity matrices";
case wson {
  uses l0-types:wson-label-start-end;
}
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
  + "tet:te-node-attributes/tet:connectivity-matrices/"
  + "tet:label-restrictions/"
  + "tet:label-restriction/tet:label-step/"
  + "tet:technology" {
when "../../../../../../../nw:network-types/tet:te-topology/"
  + "wson:wson-topology" {
  description
    "Augmentation parameters apply only for networks with
    WSON topology type.";
}
description
  "Augment TE label range step for the TE node
  connectivity matrices";
case wson {
  uses l0-types:wson-label-step;
}
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
  + "tet:te-node-attributes/tet:connectivity-matrices/"
  + "tet:underlay/tet:primary-path/tet:path-element/"
  + "tet:type/tet:label/tet:label-hop/"
  + "tet:te-label/tet:technology" {
when "../../../../../../../nw:network-types/tet:te-topology/"
  + "wson:wson-topology" {
  description
    "Augmentation parameters apply only for networks with
    WSON topology type.";
}
description
  "Augment TE label hop for the underlay primary path of the
  TE node connectivity matrices";
case wson {
  uses l0-types:wson-label-hop;
}
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
```



```

    + "tet:te-node-attributes/tet:connectivity-matrices/"
    + "tet:underlay/tet:backup-path/tet:path-element/"
    + "tet:type/tet:label/tet:label-hop/"
    + "tet:te-label/tet:technology" {
when "../.../.../.../.../.../.../.../.../..."
    + "nw:network-types/tet:te-topology/"
    + "wson:wson-topology" {
description
    "Augmentation parameters apply only for networks with
      WSON topology type.";
}
description
    "Augment TE label hop for the underlay backup path of the
      TE node connectivity matrices";
case wson {
    uses l0-types:wson-label-hop;
}
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
    + "tet:te-node-attributes/tet:connectivity-matrices/"
    + "tet:optimizations/tet:algorithm/tet:metric/"
    + "tet:optimization-metric/"
    + "tet:explicit-route-exclude-objects/"
    + "tet:route-object-exclude-object/"
    + "tet:type/tet:label/tet:label-hop/"
    + "tet:te-label/tet:technology" {
when "../.../.../.../.../.../.../.../.../..."
    + "nw:network-types/tet:te-topology/"
    + "wson:wson-topology" {
description
    "Augmentation parameters apply only for networks with
      WSON topology type.";
}
description
    "Augment TE label hop for the explicit route objects excluded
      by the path computation of the TE node connectivity
      matrices";
case wson {
    uses l0-types:wson-label-hop;
}
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
    + "tet:te-node-attributes/tet:connectivity-matrices/"
    + "tet:optimizations/tet:algorithm/tet:metric/"
    + "tet:optimization-metric/"
    + "tet:explicit-route-include-objects/"

```



```

    + "tet:route-object-include-object/"
    + "tet:type/tet:label/tet:label-hop/"
    + "tet:te-label/tet:technology" {
when "../../../../../../../../../../../"
    + "nw:network-types/tet:te-topology/"
    + "wson:wson-topology" {
description
    "Augmentation parameters apply only for networks with
    WSON topology type.";
}
description
    "Augment TE label hop for the explicit route objects included
    by the path computation of the TE node connectivity
    matrices";
case wson {
    uses l0-types:wson-label-hop;
}
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
    + "tet:te-node-attributes/tet:connectivity-matrices/"
    + "tet:path-properties/tet:path-route-objects/"
    + "tet:path-route-object/tet:type/tet:label/tet:label-hop/"
    + "tet:te-label/tet:technology" {
when "../../../../../../../../../../../"
    + "nw:network-types/tet:te-topology/"
    + "wson:wson-topology" {
description
    "Augmentation parameters apply only for networks with
    WSON topology type.";
}
description
    "Augment TE label hop for the computed path route objects
    of the TE node connectivity matrices";
case wson {
    uses l0-types:wson-label-hop;
}
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
    + "tet:te-node-attributes/tet:connectivity-matrices/"
    + "tet:connectivity-matrix/tet:from/"
    + "tet:label-restrictions/tet:label-restriction/"
    + "tet:label-start/"
    + "tet:te-label/tet:technology" {
when "../../../../../../../../../../../"
    + "nw:network-types/tet:te-topology/"
    + "wson:wson-topology" {

```



```
    description
      "Augmentation parameters apply only for networks with
      WSON topology type.";
  }
  description
    "Augment TE label range start for the source LTP
    of the connectivity matrix entry.";
  case wson {
    uses l0-types:wson-label-start-end;
  }
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
+ "tet:te-node-attributes/tet:connectivity-matrices/"
+ "tet:connectivity-matrix/tet:from/"
+ "tet:label-restrictions/tet:label-restriction/"
+ "tet:label-end/"
+ "tet:te-label/tet:technology" {
when "../../../../../../../../../../../"
+ "nw:network-types/tet:te-topology/"
+ "wson:wson-topology" {
  description
    "Augmentation parameters apply only for networks with
    WSON topology type.";
}
  description
    "Augment TE label range end for the source LTP
    of the connectivity matrix entry.";
  case wson {
    uses l0-types:wson-label-start-end;
  }
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
+ "tet:te-node-attributes/tet:connectivity-matrices/"
+ "tet:connectivity-matrix/tet:from/"
+ "tet:label-restrictions/tet:label-restriction/"
+ "tet:label-step/"
+ "tet:technology" {
when "../../../../../../../../../../../"
+ "nw:network-types/tet:te-topology/"
+ "wson:wson-topology" {
  description
    "Augmentation parameters apply only for networks with
    WSON topology type.";
}
  description
    "Augment TE label range step for the source LTP
```



```

        of the connectivity matrix entry.";
    case wson {
        uses l0-types:wson-label-step;
    }
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
+ "tet:te-node-attributes/tet:connectivity-matrices/"
+ "tet:connectivity-matrix/tet:to/"
+ "tet:label-restrictions/tet:label-restriction/"
+ "tet:label-start/"
+ "tet:te-label/tet:technology" {
when "../../../../../../../../../../../"
+ "nw:network-types/tet:te-topology/"
+ "wson:wson-topology" {
description
    "Augmentation parameters apply only for networks with
    WSON topology type.";
}
description
    "Augment TE label range start for the destination LTP
    of the connectivity matrix entry.";
case wson {
    uses l0-types:wson-label-start-end;
}
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
+ "tet:te-node-attributes/tet:connectivity-matrices/"
+ "tet:connectivity-matrix/tet:to/"
+ "tet:label-restrictions/tet:label-restriction/"
+ "tet:label-end/"
+ "tet:te-label/tet:technology" {
when "../../../../../../../../../../../"
+ "nw:network-types/tet:te-topology/"
+ "wson:wson-topology" {
description
    "Augmentation parameters apply only for networks with
    WSON topology type.";
}
description
    "Augment TE label range end for the destination LTP
    of the connectivity matrix entry.";
case wson {
    uses l0-types:wson-label-start-end;
}
}
}

```



```
augment "/nw:networks/nw:network/nw:node/tet:te/"
  + "tet:te-node-attributes/tet:connectivity-matrices/"
  + "tet:connectivity-matrix/tet:to/"
  + "tet:label-restrictions/tet:label-restriction/"
  + "tet:label-step/"
  + "tet:technology" {
when "../.../.../.../.../.../.../.../.../..."
  + "nw:network-types/tet:te-topology/"
  + "wson:wson-topology" {
  description
    "Augmentation parameters apply only for networks with
    WSON topology type.";
}
description
  "Augment TE label range step for the destination LTP
  of the connectivity matrix entry.";
case wson {
  uses l0-types:wson-label-step;
}
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
  + "tet:te-node-attributes/tet:connectivity-matrices/"
  + "tet:connectivity-matrix/"
  + "tet:underlay/tet:primary-path/tet:path-element/"
  + "tet:type/tet:label/tet:label-hop/"
  + "tet:te-label/tet:technology" {
when "../.../.../.../.../.../.../.../.../..."
  + "nw:network-types/tet:te-topology/"
  + "wson:wson-topology" {
  description
    "Augmentation parameters apply only for networks with
    WSON topology type.";
}
description
  "Augment TE label hop for the underlay primary path
  of the connectivity matrix entry.";
case wson {
  uses l0-types:wson-label-hop;
}
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
  + "tet:te-node-attributes/tet:connectivity-matrices/"
  + "tet:connectivity-matrix/"
  + "tet:underlay/tet:backup-path/tet:path-element/"
  + "tet:type/tet:label/tet:label-hop/"
  + "tet:te-label/tet:technology" {
```



```

when "../../../../../../../../../../../"
  + "nw:network-types/tet:te-topology/"
  + "wson:wson-topology" {
  description
    "Augmentation parameters apply only for networks with
    WSON topology type.";
}
description
  "Augment TE label hop for the underlay backup path
  of the connectivity matrix entry.";
case wson {
  uses l0-types:wson-label-hop;
}
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
  + "tet:te-node-attributes/tet:connectivity-matrices/"
  + "tet:connectivity-matrix/tet:optimizations/"
  + "tet:algorithm/tet:metric/tet:optimization-metric/"
  + "tet:explicit-route-exclude-objects/"
  + "tet:route-object-exclude-object/tet:type/"
  + "tet:label/tet:label-hop/tet:te-label/tet:technology" {
when "../../../../../../../../../../../"
  + "nw:network-types/tet:te-topology/"
  + "wson:wson-topology" {
  description
    "Augmentation parameters apply only for networks with
    WSON topology type.";
}
description
  "Augment TE label hop for the explicit route objects excluded
  by the path computation of the connectivity matrix entry.";
case wson {
  uses l0-types:wson-label-hop;
}
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
  + "tet:te-node-attributes/tet:connectivity-matrices/"
  + "tet:connectivity-matrix/tet:optimizations/"
  + "tet:algorithm/tet:metric/tet:optimization-metric/"
  + "tet:explicit-route-include-objects/"
  + "tet:route-object-include-object/tet:type/"
  + "tet:label/tet:label-hop/tet:te-label/tet:technology" {
when "../../../../../../../../../../../"
  + "nw:network-types/tet:te-topology/"
  + "wson:wson-topology" {
  description

```



```
        "Augmentation parameters apply only for networks with
        WSON topology type.";
    }
    description
        "Augment TE label hop for the explicit route objects included
        by the path computation of the connectivity matrix entry.";
    case wson {
        uses l0-types:wson-label-hop;
    }
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
    + "tet:te-node-attributes/tet:connectivity-matrices/"
    + "tet:connectivity-matrix/"
    + "tet:path-properties/tet:path-route-objects/"
    + "tet:path-route-object/tet:type/"
    + "tet:label/tet:label-hop/tet:te-label/tet:technology" {
    when "../.../.../.../.../.../.../.../.../..."
        + "nw:network-types/tet:te-topology/"
        + "wson:wson-topology" {
        description
            "Augmentation parameters apply only for networks with
            WSON topology type.";
    }
    description
        "Augment TE label hop for the computed path route objects
        of the connectivity matrix entry.";
    case wson {
        uses l0-types:wson-label-hop;
    }
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
    + "tet:information-source-entry/"
    + "tet:connectivity-matrices/tet:label-restrictions/"
    + "tet:label-restriction/"
    + "tet:label-start/tet:te-label/tet:technology" {
    when "../.../.../.../.../.../.../.../.../..."
        + "nw:network-types/tet:te-topology/"
        + "wson:wson-topology" {
        description
            "Augmentation parameters apply only for networks with
            WSON topology type.";
    }
    description
        "Augment TE label range start for the TE node connectivity
        matrices information source.";
    case wson {
```



```
        uses l0-types:wson-label-start-end;
    }
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
+ "tet:information-source-entry/"
+ "tet:connectivity-matrices/tet:label-restrictions/"
+ "tet:label-restriction/"
+ "tet:label-end/tet:te-label/tet:technology" {
when "../.../.../.../.../.../.../.../..."
+ "nw:network-types/tet:te-topology/"
+ "wson:wson-topology" {
description
    "Augmentation parameters apply only for networks with
    WSON topology type.";
}
description
    "Augment TE label range end for the TE node connectivity
    matrices information source.";
case wson {
    uses l0-types:wson-label-start-end;
}
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
+ "tet:information-source-entry/"
+ "tet:connectivity-matrices/tet:label-restrictions/"
+ "tet:label-restriction/"
+ "tet:label-step/tet:technology" {
when "../.../.../.../.../.../.../.../..."
+ "nw:network-types/tet:te-topology/"
+ "wson:wson-topology" {
description
    "Augmentation parameters apply only for networks with
    WSON topology type.";
}
description
    "Augment TE label range step for the TE node connectivity
    matrices information source.";
case wson {
    uses l0-types:wson-label-step;
}
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
+ "tet:information-source-entry/tet:connectivity-matrices/"
+ "tet:underlay/tet:primary-path/tet:path-element/tet:type/"
+ "tet:label/tet:label-hop/tet:te-label/tet:technology" {
```



```

when "../../../../../../../"
  + "nw:network-types/tet:te-topology/"
  + "wson:wson-topology" {
    description
      "Augmentation parameters apply only for networks with
      WSON topology type.";
  }
description
  "Augment TE label hop for the underlay primary path
  of the TE node connectivity matrices of the information
  source entry.";
case wson {
  uses l0-types:wson-label-hop;
}
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
  + "tet:information-source-entry/tet:connectivity-matrices/"
  + "tet:underlay/tet:backup-path/tet:path-element/tet:type/"
  + "tet:label/tet:label-hop/tet:te-label/tet:technology" {
when "../../../../../../../"
  + "nw:network-types/tet:te-topology/"
  + "wson:wson-topology" {
    description
      "Augmentation parameters apply only for networks with
      WSON topology type.";
  }
description
  "Augment TE label hop for the underlay backup path
  of the TE node connectivity matrices of the information
  source entry.";
case wson {
  uses l0-types:wson-label-hop;
}
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
  + "tet:information-source-entry/tet:connectivity-matrices/"
  + "tet:optimizations/tet:algorithm/tet:metric/"
  + "tet:optimization-metric/"
  + "tet:explicit-route-exclude-objects/"
  + "tet:route-object-exclude-object/tet:type/"
  + "tet:label/tet:label-hop/tet:te-label/tet:technology" {
when "../../../../../../../"
  + "nw:network-types/tet:te-topology/"
  + "wson:wson-topology" {
    description
      "Augmentation parameters apply only for networks with

```



```
        WSON topology type.";
    }
    description
        "Augment TE label hop for the explicit route objects excluded
        by the path computation of the TE node connectivity matrices
        information source.";
    case wson {
        uses l0-types:wson-label-hop;
    }
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
+ "tet:information-source-entry/tet:connectivity-matrices/"
+ "tet:optimizations/tet:algorithm/tet:metric/"
+ "tet:optimization-metric/"
+ "tet:explicit-route-include-objects/"
+ "tet:route-object-include-object/tet:type/"
+ "tet:label/tet:label-hop/tet:te-label/tet:technology" {
when "../../../../../../../../../../../"
+ "nw:network-types/tet:te-topology/"
+ "wson:wson-topology" {
    description
        "Augmentation parameters apply only for networks with
        WSON topology type.";
}
description
    "Augment TE label hop for the explicit route objects included
    by the path computation of the TE node connectivity matrices
    information source.";
case wson {
    uses l0-types:wson-label-hop;
}
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
+ "tet:information-source-entry/tet:connectivity-matrices/"
+ "tet:path-properties/tet:path-route-objects/"
+ "tet:path-route-object/tet:type/"
+ "tet:label/tet:label-hop/tet:te-label/tet:technology" {
when "../../../../../../../../../../../"
+ "nw:network-types/tet:te-topology/"
+ "wson:wson-topology" {
    description
        "Augmentation parameters apply only for networks with
        WSON topology type.";
}
description
    "Augment TE label hop for the computed path route objects
```



```
    of the TE node connectivity matrices information source.";
  case wson {
    uses l0-types:wson-label-hop;
  }
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
  + "tet:information-source-entry/tet:connectivity-matrices/"
  + "tet:connectivity-matrix/"
  + "tet:from/tet:label-restrictions/"
  + "tet:label-restriction/"
  + "tet:label-start/tet:te-label/tet:technology" {
  when "../../../../../../../../../../../"
    + "nw:network-types/tet:te-topology/"
    + "wson:wson-topology" {
    description
      "Augmentation parameters apply only for networks with
      WSON topology type.";
  }
  description
    "Augment TE label range start for the source LTP
    of the connectivity matrix entry information source.";
  case wson {
    uses l0-types:wson-label-start-end;
  }
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
  + "tet:information-source-entry/tet:connectivity-matrices/"
  + "tet:connectivity-matrix/"
  + "tet:from/tet:label-restrictions/"
  + "tet:label-restriction/"
  + "tet:label-end/tet:te-label/tet:technology" {
  when "../../../../../../../../../../../"
    + "nw:network-types/tet:te-topology/"
    + "wson:wson-topology" {
    description
      "Augmentation parameters apply only for networks with
      WSON topology type.";
  }
  description
    "Augment TE label range end for the source LTP
    of the connectivity matrix entry information source.";
  case wson {
    uses l0-types:wson-label-start-end;
  }
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
```



```

    + "tet:information-source-entry/tet:connectivity-matrices/"
    + "tet:connectivity-matrix/"
    + "tet:from/tet:label-restrictions/"
    + "tet:label-restriction/"
    + "tet:label-step/tet:technology" {
when "../.../.../.../.../.../.../.../..."
    + "nw:network-types/tet:te-topology/"
    + "wson:wson-topology" {
description
    "Augmentation parameters apply only for networks with
      WSON topology type.";
}
description
    "Augment TE label range step for the source LTP
      of the connectivity matrix entry information source.";
case wson {
    uses l0-types:wson-label-step;
}
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
    + "tet:information-source-entry/tet:connectivity-matrices/"
    + "tet:connectivity-matrix/"
    + "tet:to/tet:label-restrictions/tet:label-restriction/"
    + "tet:label-start/tet:te-label/tet:technology" {
when "../.../.../.../.../.../.../.../..."
    + "nw:network-types/tet:te-topology/"
    + "wson:wson-topology" {
description
    "Augmentation parameters apply only for networks with
      WSON topology type.";
}
description
    "Augment TE label range start for the destination LTP
      of the connectivity matrix entry information source.";
case wson {
    uses l0-types:wson-label-start-end;
}
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
    + "tet:information-source-entry/tet:connectivity-matrices/"
    + "tet:connectivity-matrix/"
    + "tet:to/tet:label-restrictions/tet:label-restriction/"
    + "tet:label-end/tet:te-label/tet:technology" {
when "../.../.../.../.../.../.../.../..."
    + "nw:network-types/tet:te-topology/"
    + "wson:wson-topology" {

```



```
        description
            "Augmentation parameters apply only for networks with
            WSON topology type.";
    }
    description
        "Augment TE label range end for the destination LTP
        of the connectivity matrix entry information source.";
    case wson {
        uses l0-types:wson-label-start-end;
    }
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
    + "tet:information-source-entry/tet:connectivity-matrices/"
    + "tet:connectivity-matrix/"
    + "tet:to/tet:label-restrictions/tet:label-restriction/"
    + "tet:label-step/tet:technology" {
when "../.../.../.../.../.../.../.../.../..."
    + "nw:network-types/tet:te-topology/"
    + "wson:wson-topology" {
    description
        "Augmentation parameters apply only for networks with
        WSON topology type.";
    }
    description
        "Augment TE label range step for the destination LTP
        of the connectivity matrix entry information source.";
    case wson {
        uses l0-types:wson-label-step;
    }
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
    + "tet:information-source-entry/tet:connectivity-matrices/"
    + "tet:connectivity-matrix/"
    + "tet:underlay/tet:primary-path/tet:path-element/tet:type/"
    + "tet:label/tet:label-hop/tet:te-label/tet:technology" {
when "../.../.../.../.../.../.../.../.../..."
    + "nw:network-types/tet:te-topology/"
    + "wson:wson-topology" {
    description
        "Augmentation parameters apply only for networks with
        WSON topology type.";
    }
    description
        "Augment TE label hop for the underlay primary path
        of the connectivity matrix entry information source.";
    case wson {
```



```
    uses l0-types:wson-label-hop;
  }
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
  + "tet:information-source-entry/tet:connectivity-matrices/"
  + "tet:connectivity-matrix/"
  + "tet:underlay/tet:backup-path/tet:path-element/tet:type/"
  + "tet:label/tet:label-hop/tet:te-label/tet:technology" {
  when "../../../../../../../../../../../"
    + "nw:network-types/tet:te-topology/"
    + "wson:wson-topology" {
    description
      "Augmentation parameters apply only for networks with
      WSON topology type.";
  }
  description
    "Augment TE label hop for the underlay backup path
    of the connectivity matrix entry information source.";
  case wson {
    uses l0-types:wson-label-hop;
  }
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
  + "tet:information-source-entry/tet:connectivity-matrices/"
  + "tet:connectivity-matrix/"
  + "tet:optimizations/tet:algorithm/tet:metric/"
  + "tet:optimization-metric/"
  + "tet:explicit-route-exclude-objects/"
  + "tet:route-object-exclude-object/tet:type/"
  + "tet:label/tet:label-hop/tet:te-label/tet:technology" {
  when "../../../../../../../../../../../"
    + "nw:network-types/tet:te-topology/"
    + "wson:wson-topology" {
    description
      "Augmentation parameters apply only for networks with
      WSON topology type.";
  }
  description
    "Augment TE label hop for the explicit route objects excluded
    by the path computation of the connectivity matrix entry
    information source.";
  case wson {
    uses l0-types:wson-label-hop;
  }
}
```



```
augment "/nw:networks/nw:network/nw:node/tet:te/"
  + "tet:information-source-entry/tet:connectivity-matrices/"
  + "tet:connectivity-matrix/"
  + "tet:optimizations/tet:algorithm/tet:metric/"
  + "tet:optimization-metric/"
  + "tet:explicit-route-include-objects/"
  + "tet:route-object-include-object/tet:type/"
  + "tet:label/tet:label-hop/tet:te-label/tet:technology" {
when "../.../.../.../.../.../.../.../.../.../..."
  + "nw:network-types/tet:te-topology/"
  + "wson:wson-topology" {
  description
    "Augmentation parameters apply only for networks with
    WSON topology type.";
}
description
  "Augment TE label hop for the explicit route objects included
  by the path computation of the connectivity matrix entry
  information source.";
case wson {
  uses l0-types:wson-label-hop;
}
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
  + "tet:information-source-entry/tet:connectivity-matrices/"
  + "tet:connectivity-matrix/"
  + "tet:path-properties/tet:path-route-objects/"
  + "tet:path-route-object/tet:type/"
  + "tet:label/tet:label-hop/tet:te-label/tet:technology" {
when "../.../.../.../.../.../.../.../.../.../..."
  + "nw:network-types/tet:te-topology/"
  + "wson:wson-topology" {
  description
    "Augmentation parameters apply only for networks with
    WSON topology type.";
}
description
  "Augment TE label hop for the computed path route objects
  of the connectivity matrix entry information source.";
case wson {
  uses l0-types:wson-label-hop;
}
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
  + "tet:tunnel-termination-point/"
  + "tet:local-link-connectivities/"
```



```

    + "tet:label-restrictions/tet:label-restriction/"
    + "tet:label-start/"
    + "tet:te-label/tet:technology" {
when "../../../../../../../../../../../"
    + "nw:network-types/tet:te-topology/"
    + "wson:wson-topology" {
description
    "Augmentation parameters apply only for networks with
    WSON topology type.";
}
description
    "Augment TE label range start for the TTP
    Local Link Connectivities.";
case wson {
    uses l0-types:wson-label-start-end;
}
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
    + "tet:tunnel-termination-point/"
    + "tet:local-link-connectivities/"
    + "tet:label-restrictions/tet:label-restriction/"
    + "tet:label-end/"
    + "tet:te-label/tet:technology"{
when "../../../../../../../../../../../"
    + "nw:network-types/tet:te-topology/"
    + "wson:wson-topology" {
description
    "Augmentation parameters apply only for networks with
    WSON topology type.";
}
description
    "Augment TE label range end for the TTP
    Local Link Connectivities.";
case wson {
    uses l0-types:wson-label-start-end;
}
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
    + "tet:tunnel-termination-point/"
    + "tet:local-link-connectivities/"
    + "tet:label-restrictions/tet:label-restriction/"
    + "tet:label-step/"
    + "tet:technology"{
when "../../../../../../../../../../../"
    + "nw:network-types/tet:te-topology/"
    + "wson:wson-topology" {

```



```
        description
            "Augmentation parameters apply only for networks with
            WSON topology type.";
    }
    description
        "Augment TE label range step for the TTP
        Local Link Connectivities.";
    case wson {
        uses l0-types:wson-label-step;
    }
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
    + "tet:tunnel-termination-point/"
    + "tet:local-link-connectivities/"
    + "tet:underlay/tet:primary-path/tet:path-element/tet:type/"
    + "tet:label/tet:label-hop/tet:te-label/tet:technology" {
    when "../../../../../../../../../../../"
        + "nw:network-types/tet:te-topology/"
        + "wson:wson-topology" {
        description
            "Augmentation parameters apply only for networks with
            WSON topology type.";
    }
    description
        "Augment TE label hop for the underlay primary path
        of the TTP Local Link Connectivities.";
    case wson {
        uses l0-types:wson-label-hop;
    }
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
    + "tet:tunnel-termination-point/"
    + "tet:local-link-connectivities/"
    + "tet:underlay/tet:backup-path/tet:path-element/tet:type/"
    + "tet:label/tet:label-hop/tet:te-label/tet:technology" {
    when "../../../../../../../../../../../"
        + "nw:network-types/tet:te-topology/"
        + "wson:wson-topology" {
        description
            "Augmentation parameters apply only for networks with
            WSON topology type.";
    }
    description
        "Augment TE label hop for the underlay backup path
        of the TTP Local Link Connectivities.";
    case wson {
```



```
    uses l0-types:wson-label-hop;
  }
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
  + "tet:tunnel-termination-point/"
  + "tet:local-link-connectivities/"
  + "tet:optimizations/tet:algorithm/tet:metric/"
  + "tet:optimization-metric/"
  + "tet:explicit-route-exclude-objects/"
  + "tet:route-object-exclude-object/tet:type/"
  + "tet:label/tet:label-hop/tet:te-label/tet:technology" {
when "../../../../../../../../../../../"
  + "nw:network-types/tet:te-topology/"
  + "wson:wson-topology" {
  description
    "Augmentation parameters apply only for networks with
    WSON topology type.";
}
description
  "Augment TE label hop for the explicit route objects excluded
  by the path computation of the TTP Local Link
  Connectivities.";
case wson {
  uses l0-types:wson-label-hop;
}
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
  + "tet:tunnel-termination-point/"
  + "tet:local-link-connectivities/"
  + "tet:optimizations/tet:algorithm/tet:metric/"
  + "tet:optimization-metric/"
  + "tet:explicit-route-include-objects/"
  + "tet:route-object-include-object/tet:type/"
  + "tet:label/tet:label-hop/tet:te-label/tet:technology" {
when "../../../../../../../../../../../"
  + "nw:network-types/tet:te-topology/"
  + "wson:wson-topology" {
  description
    "Augmentation parameters apply only for networks with
    WSON topology type.";
}
description
  "Augment TE label hop for the explicit route objects included
  by the path computation of the TTP Local Link
  Connectivities.";
case wson {
```



```
    uses l0-types:wson-label-hop;
  }
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
  + "tet:tunnel-termination-point/"
  + "tet:local-link-connectivities/"
  + "tet:path-properties/tet:path-route-objects/"
  + "tet:path-route-object/tet:type/"
  + "tet:label/tet:label-hop/tet:te-label/tet:technology" {
when "../.../.../.../.../.../.../.../..."
  + "nw:network-types/tet:te-topology/"
  + "wson:wson-topology" {
  description
    "Augmentation parameters apply only for networks with
    WSON topology type.";
}
description
  "Augment TE label hop for the computed path route objects
  of the TTP Local Link Connectivities.";
case wson {
  uses l0-types:wson-label-hop;
}
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
  + "tet:tunnel-termination-point/"
  + "tet:local-link-connectivities/"
  + "tet:local-link-connectivity/"
  + "tet:label-restrictions/tet:label-restriction/"
  + "tet:label-start/tet:te-label/tet:technology" {
when "../.../.../.../.../.../.../.../..."
  + "nw:network-types/tet:te-topology/"
  + "wson:wson-topology" {
  description
    "Augmentation parameters apply only for networks with
    WSON topology type.";
}
description
  "Augment TE label range start for the TTP
  Local Link Connectivity entry.";
case wson {
  uses l0-types:wson-label-start-end;
}
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
  + "tet:tunnel-termination-point/"
```



```

    + "tet:local-link-connectivities/"
    + "tet:local-link-connectivity/"
    + "tet:label-restrictions/tet:label-restriction/"
    + "tet:label-end/tet:te-label/tet:technology" {
when "../.../.../.../.../.../.../.../..."
    + "nw:network-types/tet:te-topology/"
    + "wson:wson-topology" {
description
    "Augmentation parameters apply only for networks with
    WSON topology type.";
}
description
    "Augment TE label range end for the TTP
    Local Link Connectivity entry.";
case wson {
    uses l0-types:wson-label-start-end;
}
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
    + "tet:tunnel-termination-point/"
    + "tet:local-link-connectivities/"
    + "tet:local-link-connectivity/"
    + "tet:label-restrictions/tet:label-restriction/"
    + "tet:label-step/tet:technology" {
when "../.../.../.../.../.../.../..."
    + "nw:network-types/tet:te-topology/"
    + "wson:wson-topology" {
description
    "Augmentation parameters apply only for networks with
    WSON topology type.";
}
description
    "Augment TE label range step for the TTP
    Local Link Connectivity entry.";
case wson {
    uses l0-types:wson-label-step;
}
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
    + "tet:tunnel-termination-point/"
    + "tet:local-link-connectivities/"
    + "tet:local-link-connectivity/"
    + "tet:underlay/tet:primary-path/tet:path-element/tet:type/"
    + "tet:label/tet:label-hop/tet:te-label/tet:technology" {
when "../.../.../.../.../.../.../..."
    + "nw:network-types/tet:te-topology/"

```



```
    + "wson:wson-topology" {
description
    "Augmentation parameters apply only for networks with
      WSON topology type.";
}
description
    "Augment TE label hop for the underlay primary path
      of the TTP Local Link Connectivity entry.";
case wson {
    uses l0-types:wson-label-hop;
}
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
    + "tet:tunnel-termination-point/"
    + "tet:local-link-connectivities/"
    + "tet:local-link-connectivity/"
    + "tet:underlay/tet:backup-path/tet:path-element/tet:type/"
    + "tet:label/tet:label-hop/tet:te-label/tet:technology" {
when "../.../.../.../.../.../.../.../.../..."
    + "nw:network-types/tet:te-topology/"
    + "wson:wson-topology" {
description
    "Augmentation parameters apply only for networks with
      WSON topology type.";
}
description
    "Augment TE label hop for the underlay backup path
      of the TTP Local Link Connectivity entry.";
case wson {
    uses l0-types:wson-label-hop;
}
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
    + "tet:tunnel-termination-point/"
    + "tet:local-link-connectivities/"
    + "tet:local-link-connectivity/"
    + "tet:optimizations/tet:algorithm/tet:metric/"
    + "tet:optimization-metric/"
    + "tet:explicit-route-exclude-objects/"
    + "tet:route-object-exclude-object/tet:type/"
    + "tet:label/tet:label-hop/tet:te-label/tet:technology" {
when "../.../.../.../.../.../.../.../.../..."
    + "nw:network-types/tet:te-topology/"
    + "wson:wson-topology" {
description
    "Augmentation parameters apply only for networks with
```



```

        wson topology type.";
    }
    description
        "Augment TE label hop for the explicit route objects excluded
        by the path computation of the TTP Local Link
        Connectivity entry.";
    case wson {
        uses l0-types:wson-label-hop;
    }
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
    + "tet:tunnel-termination-point/"
    + "tet:local-link-connectivities/"
    + "tet:local-link-connectivity/"
    + "tet:optimizations/tet:algorithm/tet:metric/"
    + "tet:optimization-metric/"
    + "tet:explicit-route-include-objects/"
    + "tet:route-object-include-object/tet:type/"
    + "tet:label/tet:label-hop/tet:te-label/tet:technology" {
    when "../../../../../../../../../../../../../../../"
        + "nw:network-types/tet:te-topology/"
        + "wson:wson-topology" {
        description
            "Augmentation parameters apply only for networks with
            WSON topology type.";
    }
    description
        "Augment TE label hop for the explicit route objects included
        by the path computation of the TTP Local Link
        Connectivity entry.";
    case wson {
        uses l0-types:wson-label-hop;
    }
}

augment "/nw:networks/nw:network/nw:node/tet:te/"
    + "tet:tunnel-termination-point/"
    + "tet:local-link-connectivities/"
    + "tet:local-link-connectivity/"
    + "tet:path-properties/tet:path-route-objects/"
    + "tet:path-route-object/tet:type/"
    + "tet:label/tet:label-hop/tet:te-label/tet:technology" {
    when "../../../../../../../../../../../../../../../"
        + "nw:network-types/tet:te-topology/"
        + "wson:wson-topology" {
        description
            "Augmentation parameters apply only for networks with

```



```
        WSON topology type.";
    }
    description
        "Augment TE label hop for the computed path route objects
        of the TTP Local Link Connectivity entry.";
    case wson {
        uses l0-types:wson-label-hop;
    }
}

augment "/nw:networks/nw:network/nt:link/tet:te/"
    + "tet:te-link-attributes/"
    + "tet:underlay/tet:primary-path/tet:path-element/tet:type/"
    + "tet:label/tet:label-hop/tet:te-label/tet:technology" {
    when "../.../.../.../.../.../.../..."
        + "nw:network-types/tet:te-topology/"
        + "wson:wson-topology" {
        description
            "Augmentation parameters apply only for networks with
            WSON topology type.";
    }
    description
        "Augment TE label hop for the underlay primary path
        of the TE link.";
    case wson {
        uses l0-types:wson-label-hop;
    }
}

augment "/nw:networks/nw:network/nt:link/tet:te/"
    + "tet:te-link-attributes/"
    + "tet:underlay/tet:backup-path/tet:path-element/tet:type/"
    + "tet:label/tet:label-hop/tet:te-label/tet:technology" {
    when "../.../.../.../.../.../.../..."
        + "nw:network-types/tet:te-topology/"
        + "wson:wson-topology" {
        description
            "Augmentation parameters apply only for networks with
            WSON topology type.";
    }
    description
        "Augment TE label hop for the underlay backup path
        of the TE link.";
    case wson {
        uses l0-types:wson-label-hop;
    }
}

augment "/nw:networks/nw:network/nt:link/tet:te/"
```



```
+ "tet:te-link-attributes/"
+ "tet:label-restrictions/tet:label-restriction/"
+ "tet:label-start/tet:te-label/tet:technology" {
when "../...../nw:network-types/tet:te-topology/"
+ "wson:wson-topology" {
description
    "Augmentation parameters apply only for networks with
      WSON topology type.";
}
description
    "Augment TE label range start for the TE link.";
case wson {
    uses l0-types:wson-label-start-end;
}
}

augment "/nw:networks/nw:network/nt:link/tet:te/"
+ "tet:te-link-attributes/"
+ "tet:label-restrictions/tet:label-restriction/"
+ "tet:label-end/tet:te-label/tet:technology" {
when "../...../nw:network-types/tet:te-topology/"
+ "wson:wson-topology" {
description
    "Augmentation parameters apply only for networks with
      WSON topology type.";
}
description
    "Augment TE label range end for the TE link.";
case wson {
    uses l0-types:wson-label-start-end;
}
}

augment "/nw:networks/nw:network/nt:link/tet:te/"
+ "tet:te-link-attributes/"
+ "tet:label-restrictions/tet:label-restriction/"
+ "tet:label-step/tet:technology" {
when "../...../nw:network-types/tet:te-topology/"
+ "wson:wson-topology" {
description
    "Augmentation parameters apply only for networks with
      WSON topology type.";
}
description
    "Augment TE label range step for the TE link.";
case wson {
    uses l0-types:wson-label-step;
}
```



```

}

augment "/nw:networks/nw:network/nt:link/tet:te/"
  + "tet:information-source-entry/"
  + "tet:label-restrictions/tet:label-restriction/"
  + "tet:label-start/tet:te-label/tet:technology" {
when "../..../nw:network-types/tet:te-topology/"
  + "wson:wson-topology" {
  description
    "Augmentation parameters apply only for networks with
      WSON topology type.";
}
description
  "Augment TE label range start for the TE link
    information source.";
case wson {
  uses 10-types:wson-label-start-end;
}
}

augment "/nw:networks/nw:network/nt:link/tet:te/"
  + "tet:information-source-entry/"
  + "tet:label-restrictions/tet:label-restriction/"
  + "tet:label-end/tet:te-label/tet:technology" {
when "../..../nw:network-types/tet:te-topology/"
  + "wson:wson-topology" {
  description
    "Augmentation parameters apply only for networks with
      WSON topology type.";
}
description
  "Augment TE label range end for the TE link
    information source.";
case wson {
  uses 10-types:wson-label-start-end;
}
}

augment "/nw:networks/nw:network/nt:link/tet:te/"
  + "tet:information-source-entry/"
  + "tet:label-restrictions/tet:label-restriction/"
  + "tet:label-step/tet:technology" {
when "../..../nw:network-types/tet:te-topology/"
  + "wson:wson-topology" {
  description
    "Augmentation parameters apply only for networks with
      WSON topology type.";
}
}

```



```
description
  "Augment TE label range step for the TE link
  information source.";
case wson {
  uses l0-types:wson-label-step;
}
}

augment "/nw:networks/tet:te/tet:templates/"
  + "tet:link-template/tet:te-link-attributes/"
  + "tet:underlay/tet:primary-path/tet:path-element/tet:type/"
  + "tet:label/tet:label-hop/tet:te-label/tet:technology" {
  description
    "Augment TE label hop for the underlay primary path
    of the TE link template.";
  case wson {
    uses l0-types:wson-label-hop;
  }
}

augment "/nw:networks/tet:te/tet:templates/"
  + "tet:link-template/tet:te-link-attributes/"
  + "tet:underlay/tet:backup-path/tet:path-element/tet:type/"
  + "tet:label/tet:label-hop/tet:te-label/tet:technology" {
  description
    "Augment TE label hop for the underlay backup path
    of the TE link template.";
  case wson {
    uses l0-types:wson-label-hop;
  }
}

augment "/nw:networks/tet:te/tet:templates/"
  + "tet:link-template/tet:te-link-attributes/"
  + "tet:label-restrictions/tet:label-restriction/"
  + "tet:label-start/tet:te-label/tet:technology" {
  description
    "Augment TE label range start for the TE link template.";
  case wson {
    uses l0-types:wson-label-start-end;
  }
}

augment "/nw:networks/tet:te/tet:templates/"
  + "tet:link-template/tet:te-link-attributes/"
  + "tet:label-restrictions/tet:label-restriction/"
  + "tet:label-end/tet:te-label/tet:technology" {
  description
```



```
    "Augment TE label range end for the TE link template.";
  case wson {
    uses l0-types:wson-label-start-end;
  }
}

augment "/nw:networks/tet:te/tet:templates/"
  + "tet:link-template/tet:te-link-attributes/"
  + "tet:label-restrictions/tet:label-restriction/"
  + "tet:label-step/tet:technology" {
  description
    "Augment TE label range step for the TE link template.";
  case wson {
    uses l0-types:wson-label-step;
  }
}
}

<CODE ENDS>
```

4. Security Considerations

The YANG module specified in this document defines a schema for data that is designed to be accessed via network management protocols such as NETCONF [RFC6241] or RESTCONF [RFC8040]. The lowest NETCONF layer is the secure transport layer, and the mandatory-to-implement secure transport is Secure Shell (SSH) [RFC6242]. The lowest RESTCONF layer is HTTPS, and the mandatory-to-implement secure transport is TLS [RFC8446].

The NETCONF Protocol over Secure Shell (SSH) [RFC6242] describes a method for invoking and running NETCONF within a Secure Shell (SSH) session as an SSH subsystem. The NETCONF access control model [RFC8341] provides the means to restrict access for particular NETCONF or RESTCONF users to a preconfigured subset of all available NETCONF or RESTCONF protocol operations and content.

There are a number of data nodes defined in this YANG module that are writable/creatable/deletable (i.e., config true, which is the default). These data nodes may be considered sensitive or vulnerable in some network environments. Write operations (e.g., edit-config) to these data nodes without proper protection can have a negative effect on network operations. These are the subtrees and data nodes and their sensitivity/vulnerability:

```
/nw:networks/nw:network/nw:network-types/tet:te-topology
/nw:networks/nw:network/nt:link/tet:te/tet:te-link-attributes
```



```
/nw:networks/nw:network/nw:node/nt:termination-point/tet:te  
/nw:networks/nw:network/.../tet:te-bandwidth/tet:technology  
/nw:networks/nw:network/nw:node/tet:te/.../tet:label-restriction  
/nw:networks/nw:network/nw:node/.../tet:te-label/tet:technology
```

5. IANA Considerations

It is proposed to IANA to assign new URIs from the "IETF XML Registry" [[RFC3688](#)] as follows:

```
URI: urn:ietf:params:xml:ns:yang:ietf-wson-topology  
Registrant Contact: The IESG  
XML: N/A; the requested URI is an XML namespace.
```

This document registers a YANG module in the YANG Module Names registry [[RFC7950](#)] and [[RFC6020](#)].

```
name:          ietf-wson-topology  
namespace:     urn:ietf:params:xml:ns:yang:ietf-wson-topology  
prefix:        wson  
reference:     RFC XXXX
```

6. Contributors

Dhruv Dhody
Huawei Technologies
Email: dhruv.ietf@gmail.com

Bin Yeong Yoon
ETRI
Email: byyun@etri.re.kr

Ricard Vilalta
CTTC
Email: vricard.vilalta@cttc.es

Italo Busi
Huawei Technologies
Email: Italo.Busi@huawei.com

7. References

7.1. Normative References

- [I-D.ietf-ccamp-layer0-types]
Zheng, H., Lee, Y., Guo, A., Lopez, V., and D. King, "A YANG Data Model for Layer 0 Types", [draft-ietf-ccamp-layer0-types-06](#) (work in progress), May 2020.
- [I-D.ietf-teas-yang-te-topo]
Liu, X., Bryskin, I., Beeram, V., Saad, T., Shah, H., and O. Dios, "YANG Data Model for Traffic Engineering (TE) Topologies", [draft-ietf-teas-yang-te-topo-22](#) (work in progress), June 2019.
- [ITU-Tg6982]
International Telecommunication Union, "Amplified multichannel dense wavelength division multiplexing applications with single channel optical interfaces", ITU-T G.698.2, November 2018.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC6020] Bjorklund, M., Ed., "YANG - A Data Modeling Language for the Network Configuration Protocol (NETCONF)", [RFC 6020](#), DOI 10.17487/RFC6020, October 2010, <<https://www.rfc-editor.org/info/rfc6020>>.
- [RFC6241] Enns, R., Ed., Bjorklund, M., Ed., Schoenwaelder, J., Ed., and A. Bierman, Ed., "Network Configuration Protocol (NETCONF)", [RFC 6241](#), DOI 10.17487/RFC6241, June 2011, <<https://www.rfc-editor.org/info/rfc6241>>.
- [RFC6242] Wasserman, M., "Using the NETCONF Protocol over Secure Shell (SSH)", [RFC 6242](#), DOI 10.17487/RFC6242, June 2011, <<https://www.rfc-editor.org/info/rfc6242>>.
- [RFC7579] Bernstein, G., Ed., Lee, Y., Ed., Li, D., Imajuku, W., and J. Han, "General Network Element Constraint Encoding for GMPLS-Controlled Networks", [RFC 7579](#), DOI 10.17487/RFC7579, June 2015, <<https://www.rfc-editor.org/info/rfc7579>>.

- [RFC7950] Bjorklund, M., Ed., "The YANG 1.1 Data Modeling Language", [RFC 7950](#), DOI 10.17487/RFC7950, August 2016, <<https://www.rfc-editor.org/info/rfc7950>>.
- [RFC8040] Bierman, A., Bjorklund, M., and K. Watsen, "RESTCONF Protocol", [RFC 8040](#), DOI 10.17487/RFC8040, January 2017, <<https://www.rfc-editor.org/info/rfc8040>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in [RFC 2119](#) Key Words", [BCP 14](#), [RFC 8174](#), DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.
- [RFC8340] Bjorklund, M. and L. Berger, Ed., "YANG Tree Diagrams", [BCP 215](#), [RFC 8340](#), DOI 10.17487/RFC8340, March 2018, <<https://www.rfc-editor.org/info/rfc8340>>.
- [RFC8341] Bierman, A. and M. Bjorklund, "Network Configuration Access Control Model", STD 91, [RFC 8341](#), DOI 10.17487/RFC8341, March 2018, <<https://www.rfc-editor.org/info/rfc8341>>.
- [RFC8342] Bjorklund, M., Schoenwaelder, J., Shafer, P., Watsen, K., and R. Wilton, "Network Management Datastore Architecture (NMDA)", [RFC 8342](#), DOI 10.17487/RFC8342, March 2018, <<https://www.rfc-editor.org/info/rfc8342>>.
- [RFC8345] Clemm, A., Medved, J., Varga, R., Bahadur, N., Ananthakrishnan, H., and X. Liu, "A YANG Data Model for Network Topologies", [RFC 8345](#), DOI 10.17487/RFC8345, March 2018, <<https://www.rfc-editor.org/info/rfc8345>>.
- [RFC8446] Rescorla, E., "The Transport Layer Security (TLS) Protocol Version 1.3", [RFC 8446](#), DOI 10.17487/RFC8446, August 2018, <<https://www.rfc-editor.org/info/rfc8446>>.

7.2. Informative References

- [I-D.ietf-ccamp-flexigrid-yang]
Madrid, U., Perdices, D., King, D., Lee, Y., and H. Zheng, "YANG data model for Flexi-Grid Optical Networks", [draft-ietf-ccamp-flexigrid-yang-06](#) (work in progress), July 2020.
- [I-D.ietf-ccamp-optical-impairment-topology-yang]
Lee, Y., Auge, L., Lopez, V., Galimberti, G., and D. Beller, "A Yang Data Model for Optical Impairment-aware Topology", [draft-ietf-ccamp-optical-impairment-topology-yang-04](#) (work in progress), September 2020.

- [RFC3688] Mealling, M., "The IETF XML Registry", [BCP 81](#), [RFC 3688](#), DOI 10.17487/RFC3688, January 2004, <<https://www.rfc-editor.org/info/rfc3688>>.
- [RFC7446] Lee, Y., Ed., Bernstein, G., Ed., Li, D., and W. Imajuku, "Routing and Wavelength Assignment Information Model for Wavelength Switched Optical Networks", [RFC 7446](#), DOI 10.17487/RFC7446, February 2015, <<https://www.rfc-editor.org/info/rfc7446>>.
- [RFC7581] Bernstein, G., Ed., Lee, Y., Ed., Li, D., Imajuku, W., and J. Han, "Routing and Wavelength Assignment Information Encoding for Wavelength Switched Optical Networks", [RFC 7581](#), DOI 10.17487/RFC7581, June 2015, <<https://www.rfc-editor.org/info/rfc7581>>.

Authors' Addresses

Haomian Zheng
Huawei Technologies
H1, Huawei Xiliu Beipo Village, Songshan Lake
Dongguan, Guangdong 523808
China

Email: zhenghaomian@huawei.com

Young Lee
Samsung
South Korea

Email: younglee.tx@gmail.com

Aihua Guo
Futurewei

Email: aihuaguo.ietf@gmail.com

Victor Lopez
Telefonica

Email: victor.lopezalvarez@telefonica.com

Daniel King
University of Lancaster

Email: d.king@lancaster.ac.uk