

CDNI Working Group  
Internet-Draft  
Intended status: Standards Track  
Expires: March 13, 2021

F. Fieau, Ed.  
E. Stephan  
Orange  
S. Mishra  
Verizon  
September 09, 2020

**CDNI extensions for HTTPS delegation  
draft-ietf-cdni-interfaces-https-delegation-04**

Abstract

The delivery of content over HTTPS involving multiple CDNs raises credential management issues. This document proposes extensions in CDNI Control and Metadata interfaces to setup HTTPS delegation from an Upstream CDN (uCDN) to a Downstream CDN (dCDN).

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on March 13, 2021.

Copyright Notice

Copyright (c) 2020 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in [Section 4.e](#) of

the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

- [1. Introduction](#) . . . . . [2](#)
- [2. Terminology](#) . . . . . [3](#)
- [3. Known delegation methods](#) . . . . . [3](#)
- [4. Extending the CDNI metadata model](#) . . . . . [3](#)
  - [4.1. Extension to PathMetadata object](#) . . . . . [3](#)
  - [4.2. Delegation methods](#) . . . . . [4](#)
    - [4.2.1. AcmeStarDelegationMethod object](#) . . . . . [5](#)
    - [4.2.2. SubcertsDelegationMethod object](#) . . . . . [6](#)
- [5. Metadata Simple Data Type Descriptions](#) . . . . . [8](#)
  - [5.1. Periodicity](#) . . . . . [8](#)
- [6. IANA considerations](#) . . . . . [8](#)
  - [6.1. CDNI MI AcmeStarDelegationMethod Payload Type](#) . . . . . [9](#)
  - [6.2. CDNI MI SubCertsDelegationMethod Payload Type](#) . . . . . [9](#)
- [7. Security considerations](#) . . . . . [9](#)
- [8. Comments and questions](#) . . . . . [9](#)
- [9. References](#) . . . . . [10](#)
  - [9.1. Normative References](#) . . . . . [10](#)
  - [9.2. Informative References](#) . . . . . [10](#)
- Authors' Addresses . . . . . [11](#)

**1. Introduction**

Content delivery over HTTPS using one or more CDNs along the path requires credential management. This specifically applies when an entity delegates delivery of encrypted content to another trusted entity.

Several delegation methods are currently proposed within different IETF working groups. They specify different methods for provisioning HTTPS delivery credentials.

This document extends the CDNI Metadata interface to setup HTTPS delegation between an upstream CDN (uCDN) and downstream CDN (dCDN) using the Standardized delegation methods. Furthermore, it includes a proposal of IANA registry to enable adding of new methods.

[Section 2](#) is about terminology used in this document. [Section 3](#) presents delegation methods specified at the IETF. [Section 4](#) addresses the extension for handling HTTPS delegation in CDNI. [Section 5](#) describes simple data types. [Section 6](#) addresses IANA registry for delegation methods. [Section 7](#) covers the security issues. [Section 8](#) is about comments and questions.



## **2. Terminology**

This document uses terminology from CDNI framework documents such as: CDNI framework document [[RFC7336](#)], CDNI requirements [[RFC7337](#)] and CDNI interface specifications documents: CDNI Metadata interface [[RFC8006](#)] and CDNI Control interface / Triggers [[RFC8007](#)].

## **3. Known delegation methods**

There are currently two Internet drafts within the TLS and ACME working groups adopted to handle delegation of HTTPS delivery between entities.

This Internet Draft (I-D) proposes standardizing HTTPS delegation between the entities using CDNI interfaces.

This document considers the following two I-Ds that deals with HTTPS delegation:

- Sub-certificates [[I-D.ietf-tls-subcerts](#)] in the TLS Working Group.
- Short-term, Automatically-Renewed (STAR) certificates in Automated Certificate Management Environment(ACME) [[RFC8739](#)]

## **4. Extending the CDNI metadata model**

This section defines a CDNI extension to the current Metadata interface model that allows bootstrapping delegation methods between a uCDN and a delegate dCDN.

### **4.1. Extension to PathMetadata object**

This extension reuses PathMetadata object, as defined in [[RFC8006](#)], and adds new "Delegation methods" objects as specified in the following sections.

This allows to explicitly indicate support for a given method. Therefore, the presence (or lack thereof) of an AcmeStarDelegationMethod, SubcertsDelegationMethod, and/or further delegation methods, imply support (or lack thereof) for the given method.

Example:

The PathMatch object can reference a path-metadata that points at the delegation information. Delegation metadata are added to PathMetaData object.



Below shows both PathMatch and PathMetadata objects related to a path, for example, here /movies/\* located at <https://metadata.ucdn.example/video.example.com/movies>

PathMatch:

```
{
  "path-pattern": {
    "pattern": "/movies/*",
    "case-sensitive": true
  },
  "path-metadata": {
    "type": "MI.PathMetadata",
    "href": "https://metadata.ucdn.example/video.example.com/movies"
  }
}
```

Following the example above, the PathMetadata can be modeled for ACMEStarDelegationMethod as:

PathMetadata:

```
{
  "metadata": [
    {
      "generic-metadata-type": "MI.AcmeStarDelegationMethod",
      "generic-metadata-value": {
        "star-proxy": "10.2.2.2",
        "acme-server" : "10.2.3.3",
        "credentials-location-uri": "www.ucdn.com/credentials",
        "periodicity": 36000,
        "CSR-template": Json/Text representing the CSR template (see
section 4.2)
      }
    }
  ]
}
```

The existence of the "MI.AcmeStarDelegationMethod" object in a PathMetadata Object shall enable the use of one of the AcmeStarDelegation Methods, chosen by the delegating entity. The delegation method will be activated for the set of Path defined in the PathMatch. See [Section 4.2](#) for more details about delegation methods metadata specification.

#### **[4.2. Delegation methods](#)**

This section defines the delegation methods objects metadata. Those metadata allows bootstrapping a secured delegation by providing the dCDN with the needed parameters to set it up.



**4.2.1. AcmeStarDelegationMethod object**

This section defines the AcmeStarDelegationMethod object which describes metadata related to the use of ACME/STAR API presented in [RFC8739]

As expressed in [RFC8739], when an origin has set a delegation to a specific domain (i.e. dCDN), the dCDN should present to the end-user client, a short-term certificate bound to the master certificate.




Figure 1: Example call-flow of STAR delegation in CDNI showing 2 levels of delegation

Property: star-proxy

Description: Used to advertise the STAR Proxy to the dCDN.  
 Endpoint type defined in [RFC8006, Section 4.3.3](#).

Type: Endpoint

Mandatory-to-Specify: Yes





Property: acme-server

Description: used to advertise the ACME server to the dCDN.  
Endpoint type is defined in [RFC8006, Section 4.3.3](#).

Type: Endpoint

Mandatory-to-Specify: Yes

Property: credentials-location-uri

Description: expresses the location of the credentials to be  
fetched by the dCDN. Link type is as defined in [RFC8006,  
Section 4.3.1](#).

Type: Link

Mandatory-to-Specify: Yes

Property: periodicity

Description: expresses the credentials renewal periodicity. See  
[Section 5.1](#).

Type: Periodicity

Mandatory-to-Specify: Yes

Property: CSR-template

Description: The CSR template must be included in the metadata  
when dealing with AcmeStarDelegation Methods. It shall follow the  
description in [\[RFC8739\] section 3](#). It should be included in  
JSON/text format.

Type: JSON

Mandatory-to-Specify: Yes

#### **[4.2.2](#). SubcertsDelegationMethod object**

This section defines the SubcertsDelegationMethod object which  
describes metadata related to the use of Subcerts as presented in  
[\[I-D.ietf-tls-subcerts\]](#)






Figure 2: Example call-flow of SubCert delegation in CDNI

As expressed in [[I-D.ietf-tls-subcerts](#)], when an origin has set a delegation to a downstream entity such as a downstream CDN (i.e. dCDN), the dCDN should present the Origin or uCDN certificate or "delegated\_credential" during the TLS handshake [[RFC8446](#)] to the end-user client application, instead of its own certificate.

Property: credentials-delegating-entity

Description: Endpoint ID (IP) of the delegating Entity (uCDN). Endpoint type defined in [RFC8006, Section 4.3.3](#).

Type: Endpoint

Mandatory-to-Specify: Yes

Property: credential-recipient-entity



Description: Endpoint ID (IP) of the delegated entity (dCDN).  
Endpoint type is defined in [RFC8006, Section 4.3.3](#).

Type: Endpoint

Mandatory-to-Specify: Yes

Property: credentials-location-uri

Description: expresses the location of the credentials to be  
fetched by the dCDN. Link type is as defined in [RFC8006,  
Section 4.3.1](#).

Type: Link

Mandatory-to-Specify: Yes

Property: periodicity

Description: expresses the credentials renewal periodicity. See  
[Section 5.1](#).

Type: Periodicity

Mandatory-to-Specify: Yes

## **5. Metadata Simple Data Type Descriptions**

This section describes the simple data types that are used for  
properties for objects in this document.

### **5.1. Periodicity**

A time value expressed in seconds to indicate a periodicity.

Type: Integer

## **6. IANA considerations**

This document requests the registration of the following entries  
under the "CDNI Payload Types" registry hosted by IANA regarding  
"CDNI delegation":



Payload Type	Specification
MI.AcmeStarDelegationMethod	RFCthis
MI.SubCertDelegationMethod	RFCthis

[RFC Editor: Please replace RFCthis with the published RFC number for this document.]

### 6.1. CDNI MI AcmeStarDelegationMethod Payload Type

Purpose: The purpose of this Payload Type is to distinguish AcmeStarDelegationMethod MI objects (and any associated capability advertisement)

Interface: MI/FCI

Encoding: see [Section 4.2.1](#)

### 6.2. CDNI MI SubCertsDelegationMethod Payload Type

Purpose: The purpose of this Payload Type is to distinguish SubcertsDelegationMethod MI objects (and any associated capability advertisement)

Interface: MI/FCI

Encoding: see [Section 4.2.2](#)

## 7. Security considerations

Extensions proposed here do not alter nor change Security Considerations as outlined in the CDNI Metadata and Footprint and Capabilities RFCs [[RFC8006](#)].

## 8. Comments and questions

Should dCDN be visible from the Content Provider or not? This would lead to different solutions to handle delegation towards the CP. In most cases, the dCDNs should never be visible to the CP, in order to reduce the burden of certificates generation for dCDN.





## **9. References**

### **9.1. Normative References**

- [I-D.ietf-acme-star-delegation] Sheffer, Y., Lopez, D., Pastor, A., and T. Fossati, "An ACME Profile for Generating Delegated STAR Certificates", [draft-ietf-acme-star-delegation-04](#) (work in progress), August 2020.
- [I-D.ietf-tls-subcerts] Barnes, R., Iyengar, S., Sullivan, N., and E. Rescorla, "Delegated Credentials for TLS", [draft-ietf-tls-subcerts-09](#) (work in progress), June 2020.
- [RFC8006] Niven-Jenkins, B., Murray, R., Caulfield, M., and K. Ma, "Content Delivery Network Interconnection (CDNI) Metadata", [RFC 8006](#), DOI 10.17487/RFC8006, December 2016, <<https://www.rfc-editor.org/info/rfc8006>>.
- [RFC8007] Murray, R. and B. Niven-Jenkins, "Content Delivery Network Interconnection (CDNI) Control Interface / Triggers", [RFC 8007](#), DOI 10.17487/RFC8007, December 2016, <<https://www.rfc-editor.org/info/rfc8007>>.
- [RFC8739] Sheffer, Y., Lopez, D., Gonzalez de Dios, O., Pastor Perales, A., and T. Fossati, "Support for Short-Term, Automatically Renewed (STAR) Certificates in the Automated Certificate Management Environment (ACME)", [RFC 8739](#), DOI 10.17487/RFC8739, March 2020, <<https://www.rfc-editor.org/info/rfc8739>>.

### **9.2. Informative References**

- [RFC7336] Peterson, L., Davie, B., and R. van Brandenburg, Ed., "Framework for Content Distribution Network Interconnection (CDNI)", [RFC 7336](#), DOI 10.17487/RFC7336, August 2014, <<https://www.rfc-editor.org/info/rfc7336>>.
- [RFC7337] Leung, K., Ed. and Y. Lee, Ed., "Content Distribution Network Interconnection (CDNI) Requirements", [RFC 7337](#), DOI 10.17487/RFC7337, August 2014, <<https://www.rfc-editor.org/info/rfc7337>>.
- [RFC8446] Rescorla, E., "The Transport Layer Security (TLS) Protocol Version 1.3", [RFC 8446](#), DOI 10.17487/RFC8446, August 2018, <<https://www.rfc-editor.org/info/rfc8446>>.



Authors' Addresses

Frederic Fieau (editor)  
Orange  
40-48, avenue de la Republique  
Chatillon 92320  
France

Email: frederic.fieau@orange.com

Emile Stephan  
Orange  
2, avenue Pierre Marzin  
Lannion 22300  
France

Email: emile.stephan@orange.com

Sanjay Mishra  
Verizon  
13100 Columbia Pike  
Silver Spring MD 20904  
USA

Email: sanjay.mishra@verizon.com

