

CORE
Internet-Draft
Intended status: Standards Track
Expires: May 10, 2019

M. Boucadair
Orange
T. Reddy
McAfee
J. Shallow
NCC Group
November 6, 2018

Constrained Application Protocol (CoAP) Hop Limit Option
draft-ietf-core-hop-limit-01

Abstract

The presence of Constrained Application Protocol (CoAP) proxies may lead to infinite forwarding loops, which is undesirable. To prevent and detect such loops, this document specifies the Hop-Limit CoAP option.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on May 10, 2019.

Copyright Notice

Copyright (c) 2018 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in [Section 4.e](#) of

the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

| | | |
|----------------------|-----------------------------------|-------------------|
| 1. | Introduction | 2 |
| 2. | Terminology | 2 |
| 3. | Hop-Limit Option | 3 |
| 4. | IANA Considerations | 4 |
| 4.1. | CoAP Response Code | 4 |
| 4.2. | CoAP Option Number | 4 |
| 5. | Security Considerations | 5 |
| 6. | Acknowledgements | 5 |
| 7. | References | 5 |
| 7.1. | Normative References | 5 |
| 7.2. | Informative References | 6 |
| | Authors' Addresses | 6 |

[1.](#) Introduction

More and more applications are using Constrained Application Protocol (CoAP) [[RFC7252](#)] as a communication protocol between involved application agents. For example, [[I-D.ietf-dots-signal-channel](#)] specifies how CoAP is used as a distributed denial-of-service (DDoS) attack signaling protocol seeking for help from DDoS mitigation providers. In such contexts, a CoAP client can communicate directly with a server or indirectly via proxies.

When multiple proxies are involved, infinite forwarding loops may be experienced. To prevent such loops, this document defines a new CoAP option, called Hop-Limit ([Section 3](#)), which is inserted in particular by on-path proxies. Also, the document defines a new CoAP Response Code ([Section 4.1](#)) to report loops together with relevant diagnostic information to ease troubleshooting.

[2.](#) Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [BCP 14](#) [[RFC2119](#)][[RFC8174](#)] when, and only when, they appear in all capitals, as shown here.

Readers should be familiar with the terms and concepts defined in [[RFC7252](#)].

Within this document, CoAP agent refers to both CoAP client and CoAP proxy.

3. Hop-Limit Option

Hop-Limit option (see [Section 4.2](#)) is an elective option used to detect and prevent infinite loops when proxies are involved. Only one single instance of the option is allowed in a message. Therefore, any message carrying multiple Hop-Limit option instances MUST be rejected using 4.00 (Bad Request) error message.

The value of the Hop-Limit option is encoded as an 8-bit unsigned integer (see [Section 3.2 of \[RFC7252\]](#)). This value MUST be between 1 and 255 inclusive. CoAP messages received with a Hop-Limit option set to '0' or greater than '255' MUST be rejected by a CoAP agent using 4.00 (Bad Request).

The Hop-Limit option is safe to forward. That is, a CoAP proxy which does not understand the Hop-Limit option should forward it on.

If a CoAP proxy receives a request which does not include a Hop-Limit option, it SHOULD insert a Hop-Limit option when relaying the request to a next hop (absent explicit policy/configuration otherwise).

The initial Hop-Limit value SHOULD be configurable. If no initial value is explicitly provided, the default initial Hop-Limit value of 16 MUST be used. This value is chosen to be sufficiently large to guarantee that a CoAP request would not be dropped in networks when there were no loops, but not so large as to consume CoAP proxy resources when a loop does occur. Lower values should be used with caution and only in networks where topologies are known by the CoAP agent inserting the Hop-Limit option.

Because forwarding errors may occur if inadequate Hop-Limit values are used, proxies at the boundaries of an administrative domain MAY be instructed to remove or rewrite the value of Hop-Limit carried in received messages (i.e., ignore the value of Hop-Limit received in a message). This modification should be done with caution in case proxy-forwarded traffic repeatedly crosses the administrative domain boundary in a loop and so Hop-Limit detection gets broken.

Otherwise, each intermediate proxy, which understands the Hop-Limit option, involved in the handling of a CoAP message MUST decrement the Hop-Limit option value by 1 prior to forwarding upstream if this parameter exists.

CoAP messages MUST NOT be forwarded if the Hop-Limit option is set to '0' after decrement. Messages that cannot be forwarded because of exhausted Hop-Limit SHOULD be logged with a TBA1 (Hop Limit Reached) error message sent back to the CoAP peer. It is RECOMMENDED that

CoAP agents support means to alert administrators about loop errors so that appropriate actions are undertaken.

To ease debugging and troubleshooting, the CoAP proxy which detects a loop SHOULD include its information (e.g., proxy name, proxy alias, IP address) in the diagnostic payload under the conditions detailed in [Section 5.5.2 of \[RFC7252\]](#).

Each intermediate proxy involved in relaying a TBA1 (Hop Limit Reached) error message SHOULD prepend its own information in the diagnostic payload with a space character used as separator. Only one information per proxy SHOULD appear in the diagnostic payload. Doing so allows to limit the size of the TBA1 (Hop Limit Reached) error message, and to ease correlation with hops count.

4. IANA Considerations

4.1. CoAP Response Code

IANA is requested to add the following entry to the "CoAP Response Codes" sub-registry available at <https://www.iana.org/assignments/core-parameters/core-parameters.xhtml#response-codes>:

| +-----+-----+-----+ | | |
|---------------------|-------------------|-----------|
| Code | Description | Reference |
| +-----+-----+-----+ | | |
| TBA1 | Hop Limit Reached | [RFCXXXX] |
| +-----+-----+-----+ | | |

Table 1: CoAP Response Codes

This document suggests 5.06 as a code to be assigned for the new response code.

Editorial Note: Please update TBA1 statements within the document with the assigned code.

4.2. CoAP Option Number

IANA is requested to add the following entry to the "CoAP Option Numbers" sub-registry available at <https://www.iana.org/assignments/core-parameters/core-parameters.xhtml#option-numbers>:

| Number | C | U | N | R | Name | Reference |
|--------|---|---|---|---|-----------|-----------|
| TBA2 | | | x | | Hop-Limit | [RFCXXXX] |

C=Critical, U=Unsafe, N=NoCacheKey, R=Repeatable

Table 2: CoAP Option Number

5. Security Considerations

Security considerations related to CoAP proxying are discussed in [Section 11.2 of \[RFC7252\]](#).

The diagnostic payload of a TBA1 (Hop Limit Reached) error message may leak sensitive information revealing the topology of an administrative domain. To prevent that, a CoAP proxy which is located at the boundary of an administrative domain MAY be instructed to strip the diagnostic payload or part of it before forwarding on the TBA1 response.

6. Acknowledgements

This specification was part of [\[I-D.ietf-dots-signal-channel\]](#). Many thanks to those who reviewed DOTS specifications.

Thanks to Klaus Hartke, Carsten Bormann, Peter van der Stok, and Jim Schaad for the review.

7. References

7.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC7252] Shelby, Z., Hartke, K., and C. Bormann, "The Constrained Application Protocol (CoAP)", [RFC 7252](#), DOI 10.17487/RFC7252, June 2014, <<https://www.rfc-editor.org/info/rfc7252>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in [RFC 2119](#) Key Words", [BCP 14](#), [RFC 8174](#), DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.

7.2. Informative References

[I-D.ietf-dots-signal-channel]
K, R., Boucadair, M., Patil, P., Mortensen, A., and N.
Teague, "Distributed Denial-of-Service Open Threat
Signaling (DOTS) Signal Channel Specification", [draft-ietf-dots-signal-channel-25](#) (work in progress), September
2018.

Authors' Addresses

Mohamed Boucadair
Orange
Rennes 35000
France

Email: mohamed.boucadair@orange.com

Tirumaleswar Reddy
McAfee, Inc.
Embassy Golf Link Business Park
Bangalore, Karnataka 560071
India

Email: kondtir@gmail.com

Jon Shallow
NCC Group
United Kingdom

Email: jon.shallow@nccgroup.com

