

CoRE Link Format
draft-ietf-core-link-format-03

Abstract

This document defines Web Linking using a link format for use by constrained web servers to describe hosted resources, their attributes and other relationships between links. Based on the HTTP Link Header format defined in [RFC5988](#), the CoRE Link Format is carried as a payload and is assigned an Internet media type. A well-known URI is defined as a default entry-point for requesting the links hosted by a server.

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on September 15, 2011.

Copyright Notice

Copyright (c) 2011 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in [Section 4](#).e of

the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	3
1.1.	Web Linking in CoRE	3
1.2.	Use Cases	4
1.2.1.	Discovery	4
1.2.2.	Resource Collections	5
1.2.3.	Resource Directory	5
1.3.	Terminology	5
2.	Link Format	6
2.1.	Target and context URIs	7
2.2.	Link relations	7
2.3.	Use of anchors	8
3.	CoRE link extensions	8
3.1.	Resource type 'rt' attribute	8
3.2.	Interface description 'if' attribute	9
3.3.	Content-type code 'ct' attribute	9
3.4.	Maximum size estimate 'sz' attribute	9
4.	Well-known Interface	10
4.1.	Query Filtering	10
5.	Examples	11
6.	Security Considerations	13
7.	IANA Considerations	13
7.1.	Attribute Registry	13
7.2.	Well-known 'core' URI	14
7.3.	New 'hosts' relation type	14
7.4.	New link-format Internet media type	15
8.	Acknowledgments	15
9.	Changelog	16
10.	References	18
10.1.	Normative References	18
10.2.	Informative References	18
	Author's Address	19

Shelby

Expires September 15, 2011

[Page 2]

1. Introduction

The Constrained RESTful Environments (CoRE) working group aims at realizing the Representational State Transfer (REST) architecture [[REST](#)] in a suitable form for the most constrained nodes (e.g. 8-bit microcontrollers with limited memory) and networks (e.g. 6LoWPAN [[RFC4944](#)]). CoRE is aimed at Machine-to-Machine (M2M) applications such as smart energy and building automation.

The discovery of resources hosted by a constrained server is very important in machine-to-machine applications where there are no humans in the loop and static interfaces result in fragility. The discovery of resources provided by an HTTP [[RFC2616](#)] Web Server is typically called Web Discovery and the description of relations between resources is called Web Linking [[RFC5988](#)]. In this document we refer to the discovery of resources hosted by a constrained web server, their attributes and other resource relations as CoRE Resource Discovery.

The main function of such a discovery mechanism is to provide Universal Resource Indicators (URIs, called links) for the resources hosted by the server, complemented by attributes about those resources and possible further link relations. In CoRE this collection of links is carried as a resource of its own (as opposed to HTTP headers delivered with a specific resource). This document specifies a link format for use in CoRE Resource Discovery by extending the HTTP Link Header Format [[RFC5988](#)] to describe these link descriptions. The CoRE Link Format is carried as a payload and is assigned an Internet media type. A well-known URI `"/.well-known/core"` is defined as a default entry-point for requesting the list of links about resources hosted by a server, and thus performing CoRE Resource Discovery.

1.1. Web Linking in CoRE

What is the difference between the CoRE Link Format and [[RFC5988](#)]? Technically the CoRE Link Format is a serialization of a typed link as specified in [[RFC5988](#)], used to describe relationships between resources, so-called "Web Linking". In this specification Web Linking is extended with specific constrained M2M attributes, links are carried as a message payload rather than in an HTTP Link Header, and a default interface is defined to discover resources hosted by a server. This specification also defines a new relation type "hosts", which indicates that the resource is hosted by the server from which the link document was requested.

Why not just use the HTTP Link Header? In HTTP, the Link Header can be used to carry link information about a resource along with an HTTP

Shelby

Expires September 15, 2011

[Page 3]

response. This works well for the typical use case for a web server and browser, where further information about a particular resource is useful after accessing it. In CoRE the main use case for Web Linking is the discovery of which resources a server hosts in the first place. Although some resources may have further links associated with them, this is expected to be an exception. For that reason the CoRE Link Format serialization is carried as a resource representation of a well-known URI. The CoRE Link Format does re-use the format of the HTTP Link Header serialization defined in [\[RFC5988\]](#).

[1.2.](#) Use Cases

Typical use cases for Web Linking on today's web include e.g. describing the author of a web page, or describing relations between web pages (next chapter, previous chapter etc.). Web Linking can also be applied to M2M applications, where typed links are used to assist a machine client in finding and understanding how to use resources on a server. In this section a few use cases are described for how the CoRE Link Format could be used in M2M applications. For further technical examples see [Section 5](#). As there are a large range of M2M applications, these use cases are purposely generic. This document assumes that different deployments or application domains will define the appropriate REST interface descriptions along with Resource Types to make discovery meaningful.

[1.2.1.](#) Discovery

In M2M application, for example home or building automation, there is a need for local clients and servers to find and interact with each other without human intervention. The CoRE Link Format can be used by servers in such environments to enable Resource Discovery of the resources hosted by the server.

Resource Discovery can be performed either unicast or multicast. When a server's IP address is already known, either a priori or resolved via the Domain Name System (DNS), unicast discovery is performed in order to locate the entry point to the resource of interest. This is performed using a GET to `/.well-known/core` on the server, which returns a payload in the CoRE Link Format. A client would then match the appropriate Resource Type, Interface Description and possible Content-Type for its application. These attributes may also be included in the query string in order to filter the number of links returned in a response.

Multicast resource discovery is useful when a client needs to locate a resource within a limited scope, and that scope supports IP multicast. A GET request to the appropriate multicast address is

Shelby

Expires September 15, 2011

[Page 4]

made for /.well-known/core. In order to limit the number and size of responses, a query string is recommended with the known attributes. Typically a resource would be discovered based on its Resource Type and/or Interface Description, along with possible application specific attributes.

1.2.2. Resource Collections

RESTful designs of M2M interfaces often make use of collections of resources. For example an index of temperature sensors on a data collection node or a list of alarms on a home security controller. The CoRE Link Format can be used to make it possible to find the entry point to a collection and traverse its members. The entry point of a collection would always be included in /.well-known/core to enable its discovery. The members of the collection can be defined either through the interface description of the resource along with a parameter resource for the size of the collection, or by using the link format to describe each resource in the collection. These links could be located under /.well-known/core or hosted for example in the root resource of the collection.

1.2.3. Resource Directory

In many deployment scenarios, for example constrained networks with sleeping servers, or large M2M deployments with bandwidth limited access networks, it makes sense to deploy resource directory entities which store links to resources stored on other servers. Think of this as a limited search engine for constrained M2M resources.

The CoRE Link Format can be used by a server to register resources with a resource directory, or to allow a resource directory to poll for resources. Resource polling uses the same process as unicast or multicast discovery, however usually without filtering. Resource registration can be achieved by having each server POST their resources to /.well-known/core on the resource directory. This in turn adds links to the resource directory under an appropriate resource. These links can then be discovered by any client by performing a GET on the resource directory using a query string filter.

1.3. Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

This specification requires readers to be familiar with all the terms and concepts that are discussed in [[RFC5988](#)]. This specification

makes use of the following terminology:

Web Linking

A framework for indicating the relationships between web resources.

Link

Also called "typed links" in [RFC5988](#). A link is a typed connection between two resources identified by URIs. Made up of a context URI, a link relation type, a target URI, and optional target attributes.

Link Format

A particular serialisation of typed links.

CoRE Link Format

A particular serialization of typed links based the HTTP Link Header serialization defined in [Section 5 of RFC5988](#), but carried as a resource representation with a MIME type.

Attribute

Properly called "Target Attribute" in [RFC5988](#). A set of key/value pairs that describe the link or its target.

CoRE Resource Discovery

When a client discovers the list of resources hosted by a server, their attributes and other link relations by accessing /.well-known/core.

2. Link Format

The CoRE Link Format extends the HTTP Link Header format specified in [\[RFC5988\]](#), which is specified in Augmented Backus-Naur Form (ABNF) notation [\[RFC5234\]](#). The format does not require special XML or binary parsing, is fairly compact, and is extensible - all important characteristics for CoRE. It should be noted that this link format is just one serialization of typed links defined in [\[RFC5988\]](#), others include HTML link, Atom feed links [\[RFC4287\]](#) or HTTP Link Headers. It is expected that resources discovered in the CoRE Link Format may also be made available in alternative formats on the greater Internet. The CoRE Link Format is only expected to be supported in constrained networks and M2M systems.

[Section 5 of \[RFC5988\]](#) did not require an Internet media type for the defined link format, as it was defined to be carried in an HTTP header. This specification thus defines a Internet media type for the CoRE Link Format (see [Section 7.4](#)).

The CoRE link format uses the ABNF description and associated rules in [Section 5 of \[RFC5988\]](#). In addition, the pchar rule is taken from [\[RFC3986\]](#). The "Link:" text is omitted as that is part of the HTTP Link Header. As in [\[RFC5988\]](#), multiple link descriptions are separated by commas. Note that commas can also occur in quoted strings and URIs but do not end a description. The CoRE link format MUST use UTF-8 encoding, which SHOULD be in NFC (Unicode Normalization Form C). See [Section 3 of \[RFC5198\]](#), which explains why it useful to represent Unicode in a single unique form.

[2.1.](#) Target and context URIs

Each link conveys one target URI as a URI-reference inside angle brackets ("`<>`"). The context URI of a link (also called base URI in [\[RFC3986\]](#)) conveyed in the CoRE Link Format is by default built from the scheme and authority parts of the target URI. In the absence of this information in the target URI, the context URI is built from the scheme and authority that was used for referencing the resource returning the set of links, replacing the path with an empty path. Thus by default links can be thought of as describing a target resource hosted by the server. Other relations can be expressed by including an anchor parameter (which defines the context URI) along with an explicit relation parameter. This is an important difference to the way the HTTP Link Header format is used, as it is included in the header of an HTTP response for some URI (this URI is by default the context URI). Thus the HTTP Link Header is by default relating the target URI to the URI that was requested. In comparison, the CoRE link format includes one or more links, each describing a resource hosted by a server by default. Other relations can be expressed by using the anchor parameter. See [Section 5 of \[RFC3986\]](#) for a description of how URIs are constructed from URI references.

[2.2.](#) Link relations

Since links in the CoRE Link Format are typically used to describe resources hosted by a server, and thus in the absence of the relation parameter the new relation type "hosts" is assumed (see [Section 7.3](#)). The "hosts" relation type indicates that the target URI is a resource hosted by the server given by the base URI, or, if present, the anchor parameter.

To express other relations a links can make use of any registered relation parameter or target attributes by including the relation parameter. The context of a relation can be defined using the anchor parameter. In this way, relations between resources hosted on a server, or between hosted resources and external resources can be expressed.

2.3. Use of anchors

As per [Section 5.2 of \[RFC5988\]](#) a link description MAY include an "anchor" attribute, in which case the context is the URI included in that attribute. This is used to describe a relationship between two resources. A consuming implementation can however choose to ignore such links. It is not expected that all implementations will be able to derive useful information from explicitly anchored links.

3. CoRE link extensions

The following CoRE specific target attributes are defined. These attributes describe information useful in accessing the target link of the relation, and in some cases may be URIs. These URIs MUST be treated as indicators, and are not meant to be actually retrieved like a URL. When attributes are compared, they MUST be compared as strings. Relationships to resources that are meant to be retrieved should be expressed as separate links using the anchor attribute and the appropriate relation type.

```
link-extension    = ( "rt" "=" quoted-string )
link-extension    = ( "if" "=" quoted-string )
link-extension    = ( "ct" "=" integer )
link-extension    = ( "sz" "=" integer )
integer           = 1*DIGIT
```

3.1. Resource type 'rt' attribute

The resource type "rt" attribute is used to assign a semantically important type to a resource. One can think of this as a noun describing the resource. In the case of a temperature resource this could be an application-specific semantic type like "OutdoorTemperature", a Universal Resource Name (URN) like "urn:temperature:outdoor" or a URI referencing a specific concept in an ontology like "http://sweet.jpl.nasa.gov/2.0/phys.owl#Temperature". Multiple resource type attributes MAY appear in a link.

The resource type attribute is not meant to be used to assign a human readable name to a resource. The "title" attribute defined in [\[RFC5988\]](#) is meant for that purpose.

3.2. Interface description 'if' attribute

The interface description "if" attribute is used to provide a name, URI or URN indicating a specific interface definition used to interact with the target resource. One can think of this as describing verbs usable on a resource. The interface description attribute is meant to describe the generic REST interface to interact with a resource or a set of resources. It is expected that an interface description will be re-used by different resource types. For example the resource types "OutdoorTemperature", "DewPoint" and "RelHumidity" could all be accessible using the interface description "http://www.example.org/myapp.wadl#sensor".

The interface description could be for example the URI of a Web Application Description Language (WADL) definition of the target resource "http://www.example.org/myapp.wadl#sensor", a URN indicating the type of interface to the resource "urn:myapp:sensor", or an application-specific name "Sensor". Multiple interface description attributes MAY appear in a link.

3.3. Content-type code 'ct' attribute

The Content-type code "ct" attribute provides a hint about the Internet media type this resource returns. Note that this is only a hint, and does not override the Content-type Option of a CoAP response obtained by actually following the link. The value is in the CoAP identifier code format as a decimal ASCII integer [I-D.ietf-core-coap]. For example application/xml would be indicated as "ct=41". If no Content-type code attribute is present then nothing about the type can be assumed. The Content-type code attribute MUST NOT appear more than once in a link.

Alternatively, the "type" attribute MAY be used to indicate an Internet media type as a quoted-string [RFC5988]. It is not however expected that constrained implementations are able to parse quoted-string Content-type values. A link MAY include either a ct attribute or a type attribute, but MUST NOT include both.

3.4. Maximum size estimate 'sz' attribute

The maximum size estimate attribute "sz" gives an indication of the maximum size of the resource indicated by the target URI. This attribute is not expected to be included for small resources that can comfortably be carried in a single Maximum Transmission Unit (MTU), but SHOULD be included for resources larger than that. The maximum size estimate attribute MUST NOT appear more than once in a link.

4. Well-known Interface

Resource discovery in CoRE is accomplished through the use of a well-known resource URI which returns a list of links about resources hosted by that server and other link relations. Well-known resources have a path component that begins with `"/.well-known/"` as specified in [\[RFC5785\]](#). This document defines a new well-known resource for CoRE Resource Discovery `"/.well-known/core"`.

A server implementing this specification **MUST** support this resource on the default port appropriate for the protocol for the purpose of resource discovery. It is however up to the application which links are included and how they are organized. The resource `/.well-known/core` is meant to be used to return links to the entry points of resource interfaces on a server. More sophisticated link organization can be achieved by including links to CoRE Link Format resources located elsewhere on the server, for example to achieve an index. In the absence of any links, a zero-length payload is returned. The resource representation of this resource **MUST** be the CoRE Link Format described in [Section 2](#).

The CoRE resource discovery interface supports the following interactions:

- o Performing a GET on `/.well-known/core` to the default port returns a set of links available from the server (if any) in the CoRE Link Format. These links might describe resources hosted on that server, on other servers, or express other kinds of link relations as described in [Section 2](#).
- o Filtering may be performed on any of the link format attributes using a query string as specified in [Section 4.1](#). For example `[GET /.well-known/core?n=TemperatureC]` would request resources with the name TemperatureC. A server is not however required to support filtering.
- o More capable servers such as proxies could support a resource directory by requesting the resource descriptions of other endpoints or allowing servers to POST requests to `/.well-known/core`. The details of such resource directory functionality is however out of scope for this document, and is expected to be specified separately.

4.1. Query Filtering

A server implementing this document **MAY** recognize the query part of a resource discovery URI as a filter on the resources to be returned. The query part should conform to the following syntax. Note that

this only defines querying for a single parameter at a time.

```
filter-query = resource-param "=" query-pattern
resource-param = "uri" | parmname
query-pattern = 1*pchar [ "*" ]
```

The resource-param "uri" refers to the URI-reference between the "<" and ">" characters of a link. Other resource-param values refer to the link attribute they name. Filtering is performed by comparing the query-pattern against the value of the attribute identified by the resource-param for each link-value in the collection of resources identified by the URI path.

If the decoded query-pattern does not end with "*", a link value matches the query only if the value of the attribute or URI-reference denoted by the resource-param is bitwise identical to the query-pattern. If the decoded query-pattern ends with "*", it is sufficient that the remainder of the query-pattern be a prefix of the value denoted by the resource-param. It is not expected that very constrained nodes support filtering. Implementations not supporting filtering MUST simply ignore the query string and return the whole resource for unicast requests.

When using a transfer protocol like the Constrained Application Protocol (CoAP) that supports multicast requests, special care is taken. A multicast request with a query string MUST not be responded to if filtering is not supported (to avoid a needless response storm).

5. Examples

A few examples of typical link descriptions in this format follows. Multiple resource descriptions in a representation are separated by commas. Linefeeds never occur in the actual format, but are shown in the example for readability.

This example includes links to two different sensors sharing the same interface description.

```
REQ: GET /.well-known/core
```

```
RES: 200 OK
```

```
</sensors/temp>;ct=41;rt="TemperatureC";if="sensor",
</sensors/light>;ct=41;rt="LightLux";if="sensor"
```


This example arranges link descriptions hierarchically, with the entry point including a link to a sub-resource containing links about the sensors.

```
REQ: GET /.well-known/core
```

```
RES: 200 OK
</sensors>;rt="index";ct=40
```

```
REQ: GET /sensors
```

```
RES: 200 OK
</sensors/temp>;ct=41;rt="TemperatureC";if="sensor",
</sensors/light>;ct=41;rt="LightLux";if="sensor"
```

An example query filter may look like:

```
REQ: GET /.well-known/core?rt=LightLux
```

```
RES: 200 OK
</sensors/light>;ct=41;rt="LightLux";if="sensor"
```

This example shows the use of an anchor attribute to relate the temperature sensor resource to an external description and to an alternative URL.

```
REQ: GET /.well-known/core
```

```
RES: 200 OK
</sensors>;ct=40;rt="index";rt="Sensor Index",
</sensors/temp>;rt="TemperatureC";if="sensor",
</sensors/light>;ct=41;rt="LightLux";if="sensor",
<http://www.example.com/sensors/t123>;anchor="/sensors/temp"
;rel="describedby",
</t>;anchor="/sensors/temp";rel="alternate"
```

If a client is interested to find relations about a particular resource, it can perform a query on the anchor parameter:

```
REQ: GET /.well-known/core?anchor=/sensors/temp
```

```
RES: 200 OK
<http://www.example.com/sensors/temp123>;anchor="/sensors/temp"
;rel="describedby",
</t>;anchor="/sensors/temp";rel="alternate"
```


6. Security Considerations

This document needs the same security considerations as described in [Section 7 of \[RFC5988\]](#). The /.well-known/core resource may be protected e.g. using DTLS when hosted on a CoAP server as per [\[I-D.ietf-core-coap\] Section 10.2](#).

Multicast requests using CoAP for the well-known link-format resources could be used to perform denial of service on a constrained network. A multicast request SHOULD only be accepted if the request is sufficiently authenticated and secured.

CoRE link format parsers should be aware that a link description may be cyclical, i.e., contain a link to itself. These cyclical links could be direct or indirect (i.e., through referenced link resources). Care should be taken when parsing link descriptions and accessing cyclical links.

7. IANA Considerations

7.1. Attribute Registry

This document defines a registry for the link extension attributes defined for use with the CoRE Link Format. The name of the registry is "CoRE Link Format Attributes".

Each entry in the registry must include the attribute name, the attribute, the format of the attribute and a reference to the attribute's documentation.

Initial entries in this registry are as follows:

Name	Attribute	Type	Reference
Resource Type	rt	Quoted String	&SELF;
Interface Description	if	Quoted String	&SELF;
Content-Type	ct	Integer	&SELF;
Maximum Size Estimate	sz	Integer	&SELF;

Table 1: CoAP Option Numbers

New attributes defined for the CoRE Link Format MUST NOT collide with existing attributes defined in [\[RFC5988\]](#).

The IANA policy for future additions to this registry is "IETF

Review" as described in [[RFC5226](#)].

The documentation of an attribute should specify the semantics of the attribute, including the following properties:

- o The meaning of the attribute.
- o The format of the attribute's value.
- o Whether the attribute can occur multiple times.
- o The default value, if any.

[7.2.](#) Well-known 'core' URI

This memo registers the "core" well-known URI in the Well-Known URI Registry as defined by [[RFC5785](#)].

URI suffix: core

Change controller: IETF

Specification document(s): [[this document]]

Related information: None

[7.3.](#) New 'hosts' relation type

This memo registers the new "hosts" Web Linking relation type as per [[RFC5988](#)].

Relation Name: hosts

Description: Refers to a resource hosted by the server indicated by the link context.

Reference: [[this document]]

Notes: This relation is used in CoRE where links are retrieved as a /.well-known/core resource representation, and by default the context of the links is the server at coap://authority from which /.well-known/core was requested.

Application Data: None

7.4. New link-format Internet media type

This memo registers the a new Internet media type for the CoRE link format, application/link-format.

Type name: application

Subtype name: link-format

Required parameters: None

Optional parameters: The query string may contain uri= to match the URI, or any other attribute defined for the link format to match that attribute as defined in this document.

Encoding considerations: UTF-8 (NFC)

Security considerations: None

Interoperability considerations:

Published specification: [[this document]]

Applications that use this media type: CoAP server and client implementations for resource discovery and HTTP applications that use the link-format as a payload.

Additional information:

Magic number(s):

File extension(s):

Macintosh file type code(s):

Intended usage: COMMON

Restrictions on usage: None

Author: CoRE WG

Change controller: IETF

8. Acknowledgments

Special thanks to Peter Bigot, who has made a considerable number reviews and text contributions that greatly improved the document.

In particular, Peter is responsible for the ABNF descriptions and the idea for a new "hosts" relation type.

Thanks to Mark Nottingham and Eran Hammer-Lahav for the discussions and ideas that led to this draft, and to Carsten Bormann, Martin Thomson and Peter Saint-Andre for extensive comments and contributions that improved the text.

Thanks to Michael Stuber, Richard Kelsey, Cullen Jennings, Guido Moritz, Peter Van Der Stok, Adriano Pezzuto, Lisa Dussealt, Alexey Melnikov, Gilbert Clark, Salvatore Loreto, Petri Mutka, Szymon Sasin, Robert Quattlebaum, Robert Cragie, Angelo Castellani, Tom Herbst, Ed Beroet, Gilman Tolle, Robby Simpson, Colin O'Flynn and David Ryan for helpful comments and discussions that have shaped the document.

9. Changelog

Changes from ietf-02 to ietf-03:

- o Removed 'obs' attribute definition, now defined in the CoAP Observation spec (#99).
- o Changed Resource name (n=) to Resource type (rt=) and d= to if= (#121).
- o Hierarchical organization of links under /.well-known/core removed (#95).
- o Bug in [Section 3.1](#) on byte-wise query matching fixed (#91).
- o Explanatory text added about alternative Web link formats (#92).
- o Fixed a bug in [Section 2.2.4](#) (#93).
- o Added use case examples (#89).
- o Clarified how the CoRE link format is used and how it differs from [RFC5988](#) (#90, #98).
- o Changed the Interface definition format to quoted-string to match the resource type.
- o Added an IANA registry for CoRE Link Format attributes (#100).

Changes from ietf-01 to ietf-02:

- o Added references to [RFC5988](#) (#41).
- o Removed sh and id link-extensions (#42).
- o Defined the use of UTF-8 (#84).
- o Changed query filter definition for any parameter (#70).
- o Added more example, now as a separate section (#43).
- o Mentioned cyclical links in the security section (#57).
- o Removed the sh and id attributes, added obs and sz attributes (#42).
- o Improved the context and relation description wrt [RFC5988](#) and requested a new "hosts" default relation type (#85).

Changes from ietf-00 to ietf-01:

- o Editorial changes to correct references.
- o Formal definition for filter query string.
- o Removed URI-reference option from "n" and "id".
- o Added security text about multicast requests.

Changes from shelby-00 to ietf-00:

- o Fixed the ABNF link-extension definitions (quotes around URIs, integer definition).
- o Clarified that filtering is optional, and the query string is to be ignored if not supported (and the URL path processed as normally).
- o Required support of wildcard * processing if filtering is supported.
- o Removed the assumption of a default content-type assumption.

[10.](#) References

10.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC3986] Berners-Lee, T., Fielding, R., and L. Masinter, "Uniform Resource Identifier (URI): Generic Syntax", STD 66, [RFC 3986](#), January 2005.
- [RFC5234] Crocker, D. and P. Overell, "Augmented BNF for Syntax Specifications: ABNF", STD 68, [RFC 5234](#), January 2008.
- [RFC5988] Nottingham, M., "Web Linking", [RFC 5988](#), October 2010.

10.2. Informative References

- [I-D.ietf-core-coap] Shelby, Z., Hartke, K., Bormann, C., and B. Frank, "Constrained Application Protocol (CoAP)", [draft-ietf-core-coap-04](#) (work in progress), January 2011.
- [REST] Fielding, "Architectural Styles and the Design of Network-based Software Architectures", , 2000, <<http://www.ics.uci.edu/~fielding/pubs/dissertation/top.htm>>.
- [RFC2616] Fielding, R., Gettys, J., Mogul, J., Frystyk, H., Masinter, L., Leach, P., and T. Berners-Lee, "Hypertext Transfer Protocol -- HTTP/1.1", [RFC 2616](#), June 1999.
- [RFC4287] Nottingham, M., Ed. and R. Sayre, Ed., "The Atom Syndication Format", [RFC 4287](#), December 2005.
- [RFC4944] Montenegro, G., Kushalnagar, N., Hui, J., and D. Culler, "Transmission of IPv6 Packets over IEEE 802.15.4 Networks", [RFC 4944](#), September 2007.
- [RFC5198] Klensin, J. and M. Padlipsky, "Unicode Format for Network Interchange", [RFC 5198](#), March 2008.
- [RFC5226] Narten, T. and H. Alvestrand, "Guidelines for Writing an IANA Considerations Section in RFCs", [BCP 26](#), [RFC 5226](#), May 2008.
- [RFC5785] Nottingham, M. and E. Hammer-Lahav, "Defining Well-Known Uniform Resource Identifiers (URIs)", [RFC 5785](#), April 2010.

Author's Address

Zach Shelby
Sensinode
Kidekuja 2
Vuokatti 88600
FINLAND

Phone: +358407796297

Email: zach@sensinode.com