

Network Working Group
Internet-Draft
Intended status: Standards Track
Expires: 16 June 2021

J. Schaad
August Cellars
13 December 2020

CBOR Object Signing and Encryption (COSE): Header parameters for
carrying and referencing X.509 certificates
draft-ietf-cose-x509-08

Abstract

The CBOR Signing And Encrypted Message (COSE) structure uses references to keys in general. For some algorithms, additional properties are defined which carry parameters relating to keys as needed. The COSE Key structure is used for transporting keys outside of COSE messages. This document extends the way that keys can be identified and transported by providing attributes that refer to or contain X.509 certificates.

Contributing to this document

This note is to be removed before publishing as an RFC.

The source for this draft is being maintained in GitHub. Suggested changes should be submitted as pull requests at <https://github.com/cose-wg/X509>. Instructions are on that page as well. Editorial changes can be managed in GitHub, but any substantial issues need to be discussed on the COSE mailing list.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 16 June 2021.

Internet-Draft

COSE X.509

December 2020

Copyright Notice

Copyright (c) 2020 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the [Trust Legal Provisions](#) and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	2
1.1.	Requirements Terminology	3
2.	X.509 COSE Header Parameters	3
3.	X.509 certificates and static-static ECDH	7
4.	IANA Considerations	8
4.1.	COSE Header Parameter Registry	8
4.2.	COSE Header Algorithm Parameter Registry	8
5.	Security Considerations	9
6.	References	9
6.1.	Normative References	9
6.2.	Informative References	10
	Author's Address	11

[1.](#) Introduction

In the process of writing [[RFC8152](#)], the working group discussed X.509 certificates [[RFC5280](#)] and decided that no use cases were presented that showed a need to support certificates. Since that time, a number of cases have been defined in which X.509 certificate support is necessary, and by implication, applications will need a documented and consistent way to handle such certificates. This document defines a set of attributes that will allow applications to transport and refer to X.509 certificates in a consistent manner.

In some of these cases, a constrained device is being deployed in the context of an existing X.509 PKI: for example, in the 6TiSCH environment, [[I-D.richardson-enrollment-roadmap](#)] describes a device

enrollment solution that relies on the presence of a factory-installed certificate on the device. The [[I-D.ietf-lake-edhoc](#)] draft was also written with the idea that long term certificates could be used to provide for authentication of devices, and uses them to establish session keys. Another possible scenario is the use of COSE

as the basis for a secure messaging application. This scenario assumes the presence of long term keys and a central authentication authority. Basing such an application on public key certificates allows it to make use of well established key management disciplines.

[1.1](#). Requirements Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [BCP 14](#) [[RFC2119](#)] [[RFC8174](#)] when, and only when, they appear in all capitals, as shown here.

[2](#). X.509 COSE Header Parameters

The use of X.509 certificates allows for an existing trust infrastructure to be used with COSE. This includes the full suite of enrollment protocols, trust anchors, trust chaining and revocation checking that have been defined over time by the IETF and other organizations. The key structures that have been defined in COSE currently do not support all of these properties although some may be found in COSE Web Tokens (CWT) [[RFC8392](#)].

It is not necessarily expected that constrained devices themselves will evaluate and process X.509 certificates: it is perfectly reasonable for a constrained device to be provisioned with a certificate that it subsequently provides to a relying party - along with a signature or encrypted message - on the assumption that the relying party is not a constrained device, and is capable of performing the required certificate evaluation and processing. It is also reasonable that a constrained device would have the hash of a certificate associated with a public key and be configured to use a public key for that thumbprint, but without performing the certificate evaluation or even having the entire certificate. In any case, there still needs to be an entity that is responsible for handling the possible certificate revocation.

Parties that intend to rely on the assertions made by a certificate obtained from any of these methods still need to validate it. This validation can be done according to the PKIX rules in [[RFC5280](#)] or by using a different trust structure, such as a trusted certificate distributor for self-signed certificates. The PKIX validation includes matching against the trust anchors configured for the application. These rules apply when the validation succeeds in a single step as well as when certificate chains need to be built. If the application cannot establish trust in the certificate, the public key contained in the certificate cannot be used for cryptographic operations.

The header parameters defined in this document are:

x5bag: This header parameter contains a bag of X.509 certificates. The set of certificates in this header parameter is unordered and may contain self-signed certificates. Note that there could be duplicating certificates. The certificate bag can contain certificates which are completely extraneous to the message. (An example of this would be where a signed message is being used to transport a certificate containing a key agreement key.) As the certificates are unordered, the party evaluating the signature will need to be capable of building the certificate path as necessary. That party will also have to take into account that the bag may not contain the full set of certificates needed to build any particular chain.

The trust mechanism **MUST** process any certificates in this parameter as untrusted input. The presence of a self-signed certificate in the parameter **MUST NOT** cause the update of the set of trust anchors without some out-of-band confirmation. As the contents of this header parameter are untrusted input, the header parameter can be in either the protected or unprotected header bucket.

This header parameter allows for a single X.509 certificate or a bag of X.509 certificates to be carried in the message.

- * If a single certificate is conveyed, it is placed in a CBOR byte string.

- * If multiple certificates are conveyed, a CBOR array of byte strings is used, with each certificate being in its own byte string.

x5chain: This header parameter contains an ordered array of X.509 certificates. The certificates are to be ordered starting with the certificate containing the end-entity key followed by the certificate which signed it and so on. There is no requirement for the entire chain to be present in the element if there is reason to believe that the relying party already has, or can locate the missing certificates. This means that the relying party is still required to do path building, but that a candidate path is proposed in this header parameter.

The trust mechanism MUST process any certificates in this parameter as untrusted input. The presence of a self-signed certificate in the parameter MUST NOT cause the update of the set of trust anchors without some out-of-band confirmation. As the contents of this header parameter are untrusted input, the header parameter can be in either the protected or unprotected header bucket.

This header parameter allows for a single X.509 certificate or a chain of X.509 certificates to be carried in the message.

- * If a single certificate is conveyed, it is placed in a CBOR byte string.
- * If multiple certificates are conveyed, a CBOR array of byte strings is used, with each certificate being in its own byte string.

x5t: This header parameter provides the ability to identify an X.509 certificate by a hash value (a thumbprint). The 'x5t' header parameter can be represented as an array of two elements. The first element is an algorithm identifier which is an integer or a

string containing the hash algorithm identifier corresponding to either the Value (integer) or Name (string) column of the algorithm registered in the "COSE Algorithms" registry. The second element is a binary string containing the hash value computed over the DER encoded certificate.

As this header parameter does not provide any trust, the header parameter can be in either a protected or unprotected header bucket.

For interoperability, applications which use this header parameter MUST support the hash algorithm 'SHA-256', but can use other hash algorithms. This requirement allows for different implementations to be configured to use an interoperable algorithm, but does not preclude the use (by prior agreement) of other algorithms.

RFC Editor please remove the following two paragraphs:

During AD review, a question was raised about how effective the previous statement is in terms of dealing with a MTI algorithm. There needs to be some type of arrangement between the parties to agree that a specific hash algorithm is going to be used in computing the thumbprint. Making it a MUST use would make that true, but it then means that agility is going to be very difficult.

The worry is that while SHA-256 may be mandatory, if a sender supports SHA-256 but only sends SHA-512 then the recipient which only does SHA-256 would not be able to use the thumbprint. In that case both applications would conform to the specification, but still not be able to inter-operate.

x5u: This header parameter provides the ability to identify an X.509 certificate by a URI [[RFC3986](#)]. It contains a CBOR text string. The referenced resource can be any of the following media types:

- * application/pkix-cert [[RFC2585](#)]
- * application/pkcs7-mime; smime-type="certs-only" [[RFC8551](#)]

As this header parameter implies a trust relationship between the

party generating the x5u parameter and the party hosting the referred-to resource, this header parameter MUST be in the protected attribute bucket.

The URI provided MUST provide integrity protection and server authentication. For example, an HTTP or CoAP GET request to retrieve a certificate MUST use TLS [[RFC8446](#)] or DTLS [[I-D.ietf-tls-dtls13](#)]. If the retrieved certificate does not chain to an existing trust anchor, the certificate MUST NOT be trusted unless the server is configured as trusted to provide new trust anchors or if an out-of-band confirmation can be received for trusting the retrieved certificate.

The header parameters are used in the following locations:

- * COSE_Signature and COSE_Sign1 objects: in these objects they identify the certificate to be used for validating the signature.
- * COSE_recipient objects: in this location they identify the certificate for the recipient of the message.

The labels assigned to each header parameter can be found in the following table.

+=====+=====+=====+=====+			
Name	Label	Value Type	Description
+-----+-----+-----+-----+			
x5bag	TBD4	COSE_X509	An unordered bag of
			X.509 certificates
+-----+-----+-----+-----+			
x5chain	TBD3	COSE_X509	An ordered chain of
			X.509 certificates

x5t	TBD1	COSE_CertHash	Hash of an X.509	
			certificate	
x5u	TBD2	uri	URI pointing to an	
			X.509 certificate	

Table 1: X.509 COSE Header Parameters

Below is an equivalent CDDL [[RFC8610](#)] description of the text above.

```
COSE_X509 = bstr / [ 2*certs: bstr ]
COSE_CertHash = [ hashAlg: (int / tstr), hashValue: bstr ]
```

The content of the bstr are the bytes of a DER encoded certificate.

3. X.509 certificates and static-static ECDH

The header parameters defined in the previous section are used to identify the recipient certificates for the ECDH key agreement algorithms. In this section we define the algorithm specific parameters that are used for identifying or transporting the sender's key for static-static key agreement algorithms.

These attributes are defined analogously to those in the previous section. There is no definition for the certificate bag, as the same attribute would be used for both the sender and recipient certificates.

x5chain-sender: This header parameter contains the chain of certificates starting with the sender's key exchange certificate. The structure is the same as 'x5chain'.

x5t-sender: This header parameter contains the hash value for the sender's key exchange certificate. The structure is the same as 'x5t'.

x5u-sender: This header parameter contains a URI for the sender's

key exchange certificate. The structure and processing are the

same as 'x5u'.

Name	Label	Type	Algorithm	Description
x5t-sender	TBD	COSE_CertHash	ECDH-SS+HKDF-256, ECDH-SS+HKDF-512, ECDH-SS+A128KW, ECDH-SS+A192KW, ECDH-SS+A256KW	Thumbprint for the senders X.509 certificate
x5u-sender	TBD	uri	ECDH-SS+HKDF-256, ECDH-SS+HKDF-512, ECDH-SS+A128KW, ECDH-SS+A192KW, ECDH-SS+A256KW	URI for the senders X.509 certificate
x5chain-sender	TBD	COSE_X509	ECDH-SS+HKDF-256, ECDH-SS+HKDF-512, ECDH-SS+A128KW, ECDH-SS+A192KW, ECDH-SS+A256KW	static key X.509 certificate chain

Table 2: Static ECDH Algorithm Values

[4.](#) IANA Considerations

[4.1.](#) COSE Header Parameter Registry

IANA is requested to register the new COSE Header parameters in Table 1 in the "COSE Header Parameters" registry. The "Value Registry" field is empty for all of the items. For each item, the 'Reference' field points to this document.

[4.2.](#) COSE Header Algorithm Parameter Registry

IANA is requested to register the new COSE Header Algorithm parameters in Table 2 in the "COSE Header Algorithm Parameters" registry. For each item, the 'Reference' field points to this document.

[5.](#) Security Considerations

Establishing trust in a certificate is a vital part of processing. A major component of establishing trust is determining what the set of trust anchors are for the process. A new self-signed certificate appearing on the client cannot be a trigger to modify the set of trust anchors, because a well defined trust-establishment process is required. One common way for a new trust anchor to be added (or removed) from a device is by doing a new firmware upgrade.

In constrained systems, there is a trade-off between the order of checking the signature and checking the certificate for validity. Validating certificates can require that network resources be accessed in order to get revocation information or retrieve certificates during path building. The resulting network access can consume power and network bandwidth. On the other hand, if the certificates are validated after the signature is validated, an oracle can potentially be built based on detecting the network resources which is only done if the signature validation passes. In any event, both the signature and certificate validation **MUST** be completed successfully before acting on any requests.

Before using the key in a certificate, the key **MUST** be checked against the algorithm to be used and any algorithm specific checks need to be made. These checks can include validating that points are on curves for elliptical curve algorithms, and that sizes of RSA keys are of an acceptable size. The use of unvalidated keys can lead either to loss of security or excessive consumption of resources (for example using a 200K RSA key).

When processing x5u header parameter the security considerations of [\[RFC3986\]](#) and specifically those defined in [Section 7.1](#) also apply.

Regardless of the source, certification path validation is an important part of establishing trust in a certificate. [Section 6 of \[RFC5280\]](#) provides guidance for the path validation. The security considerations of [\[RFC5280\]](#) are also important for the correct usage of this document.

The security of the algorithm used for 'x5t' does not affect the security of the system as this header parameter selects which certificate that is already present on the system should be used, but it does not provide any trust.

[6.](#) References

6.1. Normative References

Schaad

Expires 16 June 2021

[Page 9]

Internet-Draft

COSE X.509

December 2020

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC5280] Cooper, D., Santesson, S., Farrell, S., Boeyen, S., Housley, R., and W. Polk, "Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile", [RFC 5280](#), DOI 10.17487/RFC5280, May 2008, <<https://www.rfc-editor.org/info/rfc5280>>.
- [RFC8152] Schaad, J., "CBOR Object Signing and Encryption (COSE)", [RFC 8152](#), DOI 10.17487/RFC8152, July 2017, <<https://www.rfc-editor.org/info/rfc8152>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in [RFC 2119](#) Key Words", [BCP 14](#), [RFC 8174](#), DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.

6.2. Informative References

- [RFC8446] Rescorla, E., "The Transport Layer Security (TLS) Protocol Version 1.3", [RFC 8446](#), DOI 10.17487/RFC8446, August 2018, <<https://www.rfc-editor.org/info/rfc8446>>.
- [I-D.ietf-tls-dtls13]
Rescorla, E., Tschofenig, H., and N. Modadugu, "The Datagram Transport Layer Security (DTLS) Protocol Version 1.3", Work in Progress, Internet-Draft, [draft-ietf-tls-dtls13-39](#), 2 November 2020, <<https://tools.ietf.org/html/draft-ietf-tls-dtls13-39>>.
- [RFC8551] Schaad, J., Ramsdell, B., and S. Turner, "Secure/Multipurpose Internet Mail Extensions (S/MIME) Version 4.0 Message Specification", [RFC 8551](#), DOI 10.17487/RFC8551, April 2019, <<https://www.rfc-editor.org/info/rfc8551>>.
- [RFC2585] Housley, R. and P. Hoffman, "Internet X.509 Public Key Infrastructure Operational Protocols: FTP and HTTP",

[RFC 2585](#), DOI 10.17487/RFC2585, May 1999,
<<https://www.rfc-editor.org/info/rfc2585>>.

[I-D.ietf-lake-edhoc]

Selander, G., Mattsson, J., and F. Palombini, "Ephemeral Diffie-Hellman Over COSE (EDHOC)", Work in Progress, Internet-Draft, [draft-ietf-lake-edhoc-02](#), 2 November 2020, <<https://tools.ietf.org/html/draft-ietf-lake-edhoc-02>>.

Schaad

Expires 16 June 2021

[Page 10]

Internet-Draft

COSE X.509

December 2020

[RFC8392] Jones, M., Wahlstroem, E., Erdtman, S., and H. Tschofenig, "CBOR Web Token (CWT)", [RFC 8392](#), DOI 10.17487/RFC8392, May 2018, <<https://www.rfc-editor.org/info/rfc8392>>.

[RFC8610] Birkholz, H., Vigano, C., and C. Bormann, "Concise Data Definition Language (CDDL): A Notational Convention to Express Concise Binary Object Representation (CBOR) and JSON Data Structures", [RFC 8610](#), DOI 10.17487/RFC8610, June 2019, <<https://www.rfc-editor.org/info/rfc8610>>.

[RFC3986] Berners-Lee, T., Fielding, R., and L. Masinter, "Uniform Resource Identifier (URI): Generic Syntax", STD 66, [RFC 3986](#), DOI 10.17487/RFC3986, January 2005, <<https://www.rfc-editor.org/info/rfc3986>>.

[I-D.richardson-enrollment-roadmap]

Richardson, M., "Device Enrollment in IETF protocols -- A Roadmap", Work in Progress, Internet-Draft, [draft-richardson-enrollment-roadmap-03](#), 7 October 2020, <<https://tools.ietf.org/html/draft-richardson-enrollment-roadmap-03>>.

Author's Address

Jim Schaad
August Cellars

Email: ietf@augustcellars.com

