

Internet Engineering Task Force
Internet-Draft
Intended status: Informational
Expires: August 6, 2020

T. Mizrahi
HUAWEI
E. Grossman, Ed.
DOLBY
A. Hacker
MISTIQ
S. Das
Applied Communication Sciences
J. Dowdell
Airbus Defence and Space
H. Austad
SINTEF Digital
N. Finn
HUAWEI
February 3, 2020

Deterministic Networking (DetNet) Security Considerations
draft-ietf-detnet-security-08

Abstract

A deterministic network is one that can carry data flows for real-time applications with extremely low data loss rates and bounded latency. Deterministic networks have been successfully deployed in real-time operational technology (OT) applications for some years. However, such networks are typically isolated from external access, and thus the security threat from external attackers is low. IETF Deterministic Networking (DetNet) specifies a set of technologies that enable creation of deterministic networks on IP-based networks of potentially wide area (on the scale of a corporate network) potentially bringing the OT network into contact with Information Technology (IT) traffic and security threats that lie outside of a tightly controlled and bounded area (such as the internals of an aircraft). These DetNet technologies have not previously been deployed together on a wide area IP-based network, and thus can present security considerations that may be new to IP-based wide area network designers. This document, intended for use by DetNet network designers, provides insight into these security considerations.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute

working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on August 6, 2020.

Copyright Notice

Copyright (c) 2020 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	4
2.	Abbreviations	5
3.	Security Threats	6
3.1.	Threat Model	6
3.2.	Threat Analysis	7
3.2.1.	Delay	7
3.2.1.1.	Delay Attack	7
3.2.2.	DetNet Flow Modification or Spoofing	7
3.2.3.	Resource Segmentation or Slicing	7
3.2.3.1.	Inter-segment Attack	7
3.2.4.	Packet Replication and Elimination	8
3.2.4.1.	Replication: Increased Attack Surface	8
3.2.4.2.	Replication-related Header Manipulation	8
3.2.5.	Path Choice	8
3.2.5.1.	Path Manipulation	8
3.2.5.2.	Path Choice: Increased Attack Surface	9
3.2.6.	Control Plane	9
3.2.6.1.	Control or Signaling Packet Modification	9
3.2.6.2.	Control or Signaling Packet Injection	9
3.2.7.	Scheduling or Shaping	9
3.2.7.1.	Reconnaissance	9

3.2.8.	Time Synchronization Mechanisms	9
3.3.	Threat Summary	9
4.	Security Threat Impacts	10
4.1.	Delay-Attacks	13
4.1.1.	Data Plane Delay Attacks	13
4.1.2.	Control Plane Delay Attacks	14
4.2.	Flow Modification and Spoofing	14
4.2.1.	Flow Modification	14
4.2.2.	Spoofing	14
4.2.2.1.	Dataplane Spoofing	14
4.2.2.2.	Control Plane Spoofing	15
4.3.	Segmentation attacks (injection)	15
4.3.1.	Data Plane Segmentation	15
4.3.2.	Control Plane segmentation	15
4.4.	Replication and Elimination	16
4.4.1.	Increased Attack Surface	16
4.4.2.	Header Manipulation at Elimination Bridges	16
4.5.	Control or Signaling Packet Modification	16
4.6.	Control or Signaling Packet Injection	16
4.7.	Reconnaissance	16
4.8.	Attacks on Time Sync Mechanisms	17
4.9.	Attacks on Path Choice	17
5.	Security Threat Mitigation	17
5.1.	Path Redundancy	17
5.2.	Integrity Protection	17
5.3.	DetNet Node Authentication	18
5.4.	Dummy Traffic Insertion	18
5.5.	Encryption	19
5.5.1.	Encryption Considerations for DetNet	19
5.6.	Control and Signaling Message Protection	20
5.7.	Dynamic Performance Analytics	21
5.8.	Mitigation Summary	21
6.	Association of Attacks to Use Cases	23
6.1.	Use Cases by Common Themes	23
6.1.1.	Network Layer - AVB/TSN Ethernet	23
6.1.2.	Central Administration	24
6.1.3.	Hot Swap	24
6.1.4.	Data Flow Information Models	25
6.1.5.	L2 and L3 Integration	25
6.1.6.	End-to-End Delivery	25
6.1.7.	Proprietary Deterministic Ethernet Networks	25
6.1.8.	Replacement for Proprietary Fieldbuses	26
6.1.9.	Deterministic vs Best-Effort Traffic	26
6.1.10.	Deterministic Flows	27
6.1.11.	Unused Reserved Bandwidth	27
6.1.12.	Interoperability	27
6.1.13.	Cost Reductions	27
6.1.14.	Insufficiently Secure Devices	28

6.1.15	DetNet Network Size	28
6.1.16	Multiple Hops	28
6.1.17	Level of Service	29
6.1.18	Bounded Latency	29
6.1.19	Low Latency	30
6.1.20	Bounded Jitter (Latency Variation)	30
6.1.21	Symmetrical Path Delays	30
6.1.22	Reliability and Availability	30
6.1.23	Redundant Paths	31
6.1.24	Security Measures	31
6.2	Attack Types by Use Case Common Theme	31
6.3	Security Considerations for OAM Traffic	34
7	DetNet Technology-Specific Threats	34
7.1	IP	35
7.2	MPLS	36
8	IANA Considerations	37
9	Security Considerations	37
10	Informative References	37
	Authors' Addresses	39

[1](#). Introduction

Security is of particularly high importance in DetNet networks because many of the use cases which are enabled by DetNet [[RFC8578](#)] include control of physical devices (power grid components, industrial controls, building controls) which can have high operational costs for failure, and present potentially attractive targets for cyber-attackers.

This situation is even more acute given that one of the goals of DetNet is to provide a "converged network", i.e. one that includes both IT traffic and OT traffic, thus exposing potentially sensitive OT devices to attack in ways that were not previously common (usually because they were under a separate control system or otherwise isolated from the IT network, for example [[ARINC664P7](#)]). Security considerations for OT networks are not a new area, and there are many OT networks today that are connected to wide area networks or the Internet; this document focuses on the issues that are specific to the DetNet technologies and use cases.

Given the above considerations, securing a DetNet starts with a scrupulously well-designed and well-managed engineered network following industry best practices for security at both the data plane and control plane; this is the assumed starting point for the considerations discussed herein. In this context we view the network design and management aspects of network security as being primarily concerned with denial-of service prevention by ensuring that DetNet traffic goes where it's supposed to and that an external attacker

can't inject traffic that disrupts the DetNet's delivery timing assurance. The time-specific aspects of DetNet security presented here take up where the design and management aspects leave off.

The security requirements for any given DetNet network are necessarily specific to the use cases handled by that network. Thus the reader is assumed to be familiar with the specific security requirements of their use cases, for example those outlined in the DetNet Use Cases [[RFC8578](#)] and the Security Considerations sections of the DetNet documents applicable to the network technologies in use, for example [[I-D.ietf-detnet-ip](#)]).

The DetNet technologies include ways to:

- o Reserve data plane resources for DetNet flows in some or all of the intermediate nodes (e.g. bridges or routers) along the path of the flow
- o Provide explicit routes for DetNet flows that do not rapidly change with the network topology
- o Distribute data from DetNet flow packets over time and/or space to ensure delivery of each packet's data in spite of the loss of a path

This document includes sections on threat modeling and analysis, threat impact and mitigation, and the association of attacks with use cases based on the Use Case Common Themes section of the DetNet Use Cases [[RFC8578](#)].

2. Abbreviations

IT Information technology (the application of computers to store, study, retrieve, transmit, and manipulate data or information, often in the context of a business or other enterprise - Wikipedia).

OT Operational Technology (the hardware and software dedicated to detecting or causing changes in physical processes through direct monitoring and/or control of physical devices such as valves, pumps, etc. - Wikipedia)

MITM Man in the Middle

SN Sequence Number

STRIDE Addresses risk and severity associated with threat categories: Spoofing identity, Tampering with data, Repudiation, Information disclosure, Denial of service, Elevation of privilege.

DREAD Compares and prioritizes risk represented by these threat categories: Damage potential, Reproducibility, Exploitability, how many Affected users, Discoverability.

PTP Precision Time Protocol [[IEEE1588](#)]

3. Security Threats

This section presents a threat model, and analyzes the possible threats in a DetNet-enabled network. The threats considered in this section are independent of any specific technologies used to implement the DetNet; [Section 7](#)) considers attacks that are associated with the DetNet technologies encompassed by [[I-D.ietf-detnet-data-plane-framework](#)].

We distinguish control plane threats from data plane threats. The attack surface may be the same, but the types of attacks as well as the motivation behind them, are different. For example, a delay attack is more relevant to data plane than to control plane. There is also a difference in terms of security solutions: the way you secure the data plane is often different than the way you secure the control plane.

3.1. Threat Model

The threat model used in this memo is based on the threat model of [Section 3.1 of \[RFC7384\]](#). This model classifies attackers based on two criteria:

- o Internal vs. external: internal attackers either have access to a trusted segment of the network or possess the encryption or authentication keys. External attackers, on the other hand, do not have the keys and have access only to the encrypted or authenticated traffic.
- o Man in the Middle (MITM) vs. packet injector: MITM attackers are located in a position that allows interception and modification of in-flight protocol packets, whereas a traffic injector can only attack by generating protocol packets.

Care has also been taken to adhere to [Section 5 of \[RFC3552\]](#), both with respect to which attacks are considered out-of-scope for this document, but also which are considered to be the most common threats (explored further in [Section 3.2](#). Most of the direct threats to DetNet are Active attacks, but it is highly suggested that DetNet application developers take appropriate measures to protect the content of the streams from passive attacks.

DetNet-Service, one of the service scenarios described in [[I-D.varga-detnet-service-model](#)], is the case where a service connects DetNet networking islands, i.e. two or more otherwise independent DetNet network domains are connected via a link that is not intrinsically part of either network. This implies that there could be DetNet traffic flowing over a non-DetNet link, which may provide an attacker with an advantageous opportunity to tamper with DetNet traffic. The security properties of non-DetNet links are outside of the scope of DetNet Security, but it should be noted that use of non-DetNet services to interconnect DetNet networks merits security analysis to ensure the integrity of the DetNet networks involved.

[3.2.](#) Threat Analysis

[3.2.1.](#) Delay

[3.2.1.1.](#) Delay Attack

An attacker can maliciously delay DetNet data flow traffic. By delaying the traffic, the attacker can compromise the service of applications that are sensitive to high delays or to high delay variation. The delay may be constant or modulated.

[3.2.2.](#) DetNet Flow Modification or Spoofing

An attacker can modify some header fields of en route packets in a way that causes the DetNet flow identification mechanisms to misclassify the flow. Alternatively, the attacker can inject traffic that is tailored to appear as if it belongs to a legitimate DetNet flow. The potential consequence is that the DetNet flow resource allocation cannot guarantee the performance that is expected when the flow identification works correctly.

[3.2.3.](#) Resource Segmentation or Slicing

[3.2.3.1.](#) Inter-segment Attack

An attacker can inject traffic, consuming network device resources, thereby affecting DetNet flows. This can be performed using non-DetNet traffic that affects DetNet traffic, or by using DetNet traffic from one DetNet flow that affects traffic from different DetNet flows.

3.2.4. Packet Replication and Elimination

3.2.4.1. Replication: Increased Attack Surface

Redundancy is intended to increase the robustness and survivability of DetNet flows, and replication over multiple paths can potentially mitigate an attack that is limited to a single path. However, the fact that packets are replicated over multiple paths increases the attack surface of the network, i.e., there are more points in the network that may be subject to attacks.

3.2.4.2. Replication-related Header Manipulation

An attacker can manipulate the replication-related header fields (R-TAG). This capability opens the door for various types of attacks. For example:

- o Forward both replicas - malicious change of a packet SN (Sequence Number) can cause both replicas of the packet to be forwarded. Note that this attack has a similar outcome to a replay attack.
- o Eliminate both replicas - SN manipulation can be used to cause both replicas to be eliminated. In this case an attacker that has access to a single path can cause packets from other paths to be dropped, thus compromising some of the advantage of path redundancy.
- o Flow hijacking - an attacker can hijack a DetNet flow with access to a single path by systematically replacing the SNs on the given path with higher SN values. For example, an attacker can replace every SN value S with a higher value $S+C$, where C is a constant integer. Thus, the attacker creates a false illusion that the attacked path has the lowest delay, causing all packets from other paths to be eliminated. Once the flow is hijacked the attacker can either replace en route packets with malicious packets, or simply injecting errors, causing the packets to be dropped at their destination.

3.2.5. Path Choice

3.2.5.1. Path Manipulation

An attacker can maliciously change, add, or remove a path, thereby affecting the corresponding DetNet flows that use the path.

3.2.5.2. Path Choice: Increased Attack Surface

One of the possible consequences of a path manipulation attack is an increased attack surface. Thus, when the attack described in the previous subsection is implemented, it may increase the potential of other attacks to be performed.

3.2.6. Control Plane

3.2.6.1. Control or Signaling Packet Modification

An attacker can maliciously modify en route control packets in order to disrupt or manipulate the DetNet path/resource allocation.

3.2.6.2. Control or Signaling Packet Injection

An attacker can maliciously inject control packets in order to disrupt or manipulate the DetNet path/resource allocation.

3.2.7. Scheduling or Shaping

3.2.7.1. Reconnaissance

A passive eavesdropper can identify DetNet flows and then gather information about en route DetNet flows, e.g., the number of DetNet flows, their bandwidths, their schedules, or other temporal properties. The gathered information can later be used to invoke other attacks on some or all of the flows.

Note that in some cases DetNet flows may be identified based on an explicit DetNet header, but in some cases the flow identification may be based on fields from the L3/L4 headers. If L3/L4 headers are involved, for purposes of this document we assume they are encrypted and/or integrity-protected from external attackers.

3.2.8. Time Synchronization Mechanisms

An attacker can use any of the attacks described in [\[RFC7384\]](#) to attack the synchronization protocol, thus affecting the DetNet service.

3.3. Threat Summary

A summary of the attacks that were discussed in this section is presented in Figure 1. For each attack, the table specifies the type of attackers that may invoke the attack. In the context of this summary, the distinction between internal and external attacks is under the assumption that a corresponding security mechanism is being

used, and that the corresponding network equipment takes part in this mechanism.

Attack	Attacker Type			
	Internal		External	
	MITM	Inj.	MITM	Inj.
Delay attack	+	+	+	+
DetNet Flow Modification or Spoofing	+	+		
Inter-segment Attack	+	+		
Replication: Increased Attack Surface	+	+	+	+
Replication-related Header Manipulation	+			
Path Manipulation	+	+		
Path Choice: Increased Attack Surface	+	+	+	+
Control or Signaling Packet Modification	+			
Control or Signaling Packet Injection		+		
Reconnaissance	+		+	
Attacks on Time Sync Mechanisms	+	+	+	+

Figure 1: Threat Analysis Summary

4. Security Threat Impacts

This section describes and rates the impact of the attacks described in [Section 3](#). In this section, the impacts as described assume that the associated mitigation is not present or has failed. Mitigations are discussed in [Section 5](#).

In computer security, the impact (or consequence) of an incident can be measured in loss of confidentiality, integrity or availability of information. In the case of time sensitive networks, the impact of a network exploit can also include failure or malfunction of mechanical and/or other OT systems.

DetNet raises these stakes significantly for OT applications, particularly those which may have been designed to run in an OT-only environment and thus may not have been designed for security in an IT environment with its associated devices, services and protocols.

The severity of various components of the impact of a successful vulnerability exploit to use cases by industry is available in more detail in [\[RFC8578\]](#). Each of the use cases in the DetNet Use Cases is represented in the table below, including Pro Audio, Electrical Utilities, Industrial M2M (split into two areas, M2M Data Gathering and M2M Control Loop), and others.

Components of Impact (left column) include Criticality of Failure, Effects of Failure, Recovery, and DetNet Functional Dependence. Criticality of failure summarizes the seriousness of the impact. The impact of a resulting failure can affect many different metrics that vary greatly in scope and severity. In order to reduce the number of variables, only the following were included: Financial, Health and Safety, People well being (People WB), Affect on a single organization, and affect on multiple organizations. Recovery outlines how long it would take for an affected use case to get back to its pre-failure state (Recovery time objective, RTO), and how much of the original service would be lost in between the time of service failure and recovery to original state (Recovery Point Objective, RPO). DetNet dependence maps how much the following DetNet service objectives contribute to impact of failure: Time dependency, data integrity, source node integrity, availability, latency/jitter.

The scale of the Impact mappings is low, medium, and high. In some use cases there may be a multitude of specific applications in which DetNet is used. For simplicity this section attempts to average the varied impacts of different applications. This section does not address the overall risk of a certain impact which would require the likelihood of a failure happening.

In practice any such ratings will vary from case to case; the ratings shown here are given as examples.

Table, Part One (of Two)

	Pro A	Util	Bldg	Wire-	Cell	M2M	M2M
				less		Data	Ctrl
Criticality	Med	Hi	Low	Med	Med	Med	Med
Effects							

Financial	Med	Hi	Med	Med	Low	Med	Med	
+-----+	+-----+	+-----+	+-----+	+-----+	+-----+	+-----+	+-----+	+-----+
Health/Safety	Med	Hi	Hi	Med	Med	Med	Med	
+-----+	+-----+	+-----+	+-----+	+-----+	+-----+	+-----+	+-----+	+-----+
People WB	Med	Hi	Hi	Low	Hi	Low	Low	
+-----+	+-----+	+-----+	+-----+	+-----+	+-----+	+-----+	+-----+	+-----+
Effect 1 org	Hi	Hi	Med	Hi	Med	Med	Med	
+-----+	+-----+	+-----+	+-----+	+-----+	+-----+	+-----+	+-----+	+-----+
Effect >1 org	Med	Hi	Low	Med	Med	Med	Med	
+-----+	+-----+	+-----+	+-----+	+-----+	+-----+	+-----+	+-----+	+-----+
Recovery								
+-----+	+-----+	+-----+	+-----+	+-----+	+-----+	+-----+	+-----+	+-----+
Recov Time Obj	Med	Hi	Med	Hi	Hi	Hi	Hi	
+-----+	+-----+	+-----+	+-----+	+-----+	+-----+	+-----+	+-----+	+-----+
Recov Point Obj	Med	Hi	Low	Med	Low	Hi	Hi	
+-----+	+-----+	+-----+	+-----+	+-----+	+-----+	+-----+	+-----+	+-----+
DetNet Dependence								
+-----+	+-----+	+-----+	+-----+	+-----+	+-----+	+-----+	+-----+	+-----+
Time Dependency	Hi	Hi	Low	Hi	Med	Low	Hi	
+-----+	+-----+	+-----+	+-----+	+-----+	+-----+	+-----+	+-----+	+-----+
Latency/Jitter	Hi	Hi	Med	Med	Low	Low	Hi	
+-----+	+-----+	+-----+	+-----+	+-----+	+-----+	+-----+	+-----+	+-----+
Data Integrity	Hi	Hi	Med	Hi	Low	Hi	Low	
+-----+	+-----+	+-----+	+-----+	+-----+	+-----+	+-----+	+-----+	+-----+
Src Node Integ	Hi	Hi	Med	Hi	Med	Hi	Hi	
+-----+	+-----+	+-----+	+-----+	+-----+	+-----+	+-----+	+-----+	+-----+
Availability	Hi	Hi	Med	Hi	Low	Hi	Hi	
+-----+	+-----+	+-----+	+-----+	+-----+	+-----+	+-----+	+-----+	+-----+

Table, Part Two (of Two)

+-----+	+-----+	+-----+	+-----+
	Mining	Block	Network
		Chain	Slicing
+-----+	+-----+	+-----+	+-----+
Criticality	Hi	Med	Hi
+-----+	+-----+	+-----+	+-----+
Effects			
+-----+	+-----+	+-----+	+-----+
Financial	Hi	Hi	Hi
+-----+	+-----+	+-----+	+-----+
Health/Safety	Hi	Low	Med
+-----+	+-----+	+-----+	+-----+
People WB	Hi	Low	Med
+-----+	+-----+	+-----+	+-----+
Effect 1 org	Hi	Hi	Hi
+-----+	+-----+	+-----+	+-----+
Effect >1 org	Hi	Low	Hi
+-----+	+-----+	+-----+	+-----+

Recovery				
+-----+-----+-----+-----+				
	Recov Time Obj		Hi	
+-----+-----+-----+-----+				
	Recov Point Obj		Hi	
+-----+-----+-----+-----+				
DetNet Dependence				
+-----+-----+-----+-----+				
	Time Dependency		Hi	
+-----+-----+-----+-----+				
	Latency/Jitter		Hi	
+-----+-----+-----+-----+				
	Data Integrity		Hi	
+-----+-----+-----+-----+				
	Src Node Integ		Hi	
+-----+-----+-----+-----+				
	Availability		Hi	
+-----+-----+-----+-----+				

Figure 2: Impact of Attacks by Use Case Industry

The rest of this section will cover impact of the different groups in more detail.

[4.1.](#) Delay-Attacks

[4.1.1.](#) Data Plane Delay Attacks

Note that 'delay attack' also includes the possibility of a 'negative delay' or early arrival of a packet, or possibly adversely changing the timestamp value.

Delayed messages in a DetNet link can result in the same behavior as dropped messages in ordinary networks as the services attached to the stream has strict deterministic requirements.

For a single path scenario, disruption is a real possibility, whereas in a multipath scenario, large delays or instabilities in one stream can lead to increased buffer and CPU resources on the elimination bridge.

A data-plane delay attack on a system controlling substantial moving devices, for example in industrial automation, can cause physical damage. For example, if the network promises a bounded latency of 2ms for a flow, yet the machine receives it with 5ms latency, the machine's control loop can become unstable.

4.1.2. Control Plane Delay Attacks

In and of itself, this is not directly a threat to the DetNet service, but the effects of delaying control messages can have quite adverse effects later.

- o Delayed tear-down can lead to resource leakage, which in turn can result in failure to allocate new streams finally giving rise to a denial of service attack.
- o Failure to deliver, or severely delaying, signalling messages adding an end-point to a multicast-group will prevent the new EP from receiving expected frames thus disrupting expected behavior.
- o Delaying messages removing an EP from a group can lead to loss of privacy as the EP will continue to receive messages even after it is supposedly removed.

4.2. Flow Modification and Spoofing

4.2.1. Flow Modification

If the contents of a packet header or body can be modified by the attacker, this can cause the packet to be routed incorrectly or dropped, or the payload to be corrupted or subtly modified.

4.2.2. Spoofing

4.2.2.1. Dataplane Spoofing

Spoofing dataplane messages can result in increased resource consumptions on the bridges throughout the network as it will increase buffer usage and CPU utilization. This can lead to resource exhaustion and/or increased delay.

If the attacker manages to create valid headers, the false messages can be forwarded through the network, using part of the allocated bandwidth. This in turn can cause legitimate messages to be dropped when the budget has been exhausted.

Finally, the endpoint will have to deal with invalid messages being delivered to the endpoint instead of (or in addition to) a valid message.

4.2.2.2. Control Plane Spoofing

A successful control plane spoofing-attack will potentially have adverse effects. It can do virtually anything from:

- o modifying existing streams by changing the available bandwidth
- o add or remove endpoints from a stream
- o drop streams completely
- o falsely create new streams (exhaust the systems resources, or to enable streams outside the Network engineer's control)

4.3. Segmentation attacks (injection)

4.3.1. Data Plane Segmentation

Injection of false messages in a DetNet stream could lead to exhaustion of the available bandwidth for a stream if the bridges accounts false messages to the stream's budget.

In a multipath scenario, injected messages will cause increased CPU utilization in elimination bridges. If enough paths are subject to malicious injection, the legitimate messages can be dropped. Likewise it can cause an increase in buffer usage. In total, it will consume more resources in the bridges than normal, giving rise to a resource exhaustion attack on the bridges.

If a stream is interrupted, the end application will be affected by what is now a non-deterministic stream.

4.3.2. Control Plane segmentation

A successful Control Plane segmentation attack control messages to be interpreted by nodes in the network, unbeknownst to the central controller or the network engineer. This has the potential to create

- o new streams (exhausting resources)
- o drop existing (denial of service)
- o add/remove end-stations to a multicast group (loss of privacy)
- o modify the stream attributes (affecting available bandwidth)

4.4. Replication and Elimination

The Replication and Elimination is relevant only to Data Plane messages as Signalling is not subject to multipath routing.

4.4.1. Increased Attack Surface

Covered briefly in [Section 4.3](#)

4.4.2. Header Manipulation at Elimination Bridges

Covered briefly in [Section 4.3](#)

4.5. Control or Signaling Packet Modification

If the control plane packets are subject to manipulation undetected, the network can be severely compromised.

4.6. Control or Signaling Packet Injection

If an attacker can inject control plane packets undetected, the network can be severely compromised.

4.7. Reconnaissance

Of all the attacks, this is one of the most difficult to detect and counter. Often, an attacker will start out by observing the traffic going through the network and use the knowledge gathered in this phase to mount future attacks.

The attacker can, at their leisure, observe over time all aspects of the messaging and signalling, learning the intent and purpose of all traffic flows. At some later date, possibly at an important time in an operational context, the attacker can launch a multi-faceted attack, possibly in conjunction with some demand for ransom.

The flow-id in the header of the data plane-messages gives an attacker a very reliable identifier for DetNet traffic, and this traffic has a high probability of going to lucrative targets.

Applications which are ported from a private OT network to the higher visibility DetNet environment may need to be adapted to limit distinctive flow properties that could make them susceptible to reconnaissance.

4.8. Attacks on Time Sync Mechanisms

Attacks on time sync mechanisms are addressed in [[RFC7384](#)].

4.9. Attacks on Path Choice

This is covered in part in [Section 4.3](#), and as with Replication and Elimination ([Section 4.4](#)), this is relevant for DataPlane messages.

5. Security Threat Mitigation

This section describes a set of measures that can be taken to mitigate the attacks described in [Section 3](#). These mitigations should be viewed as a toolset that includes several different and diverse tools. Each application or system will typically use a subset of these tools, based on a system-specific threat analysis.

5.1. Path Redundancy

Description

A DetNet flow that can be forwarded simultaneously over multiple paths. Path replication and elimination [[RFC8655](#)] provides resiliency to dropped or delayed packets. This redundancy improves the robustness to failures and to man-in-the-middle attacks.

Related attacks

Path redundancy can be used to mitigate various man-in-the-middle attacks, including attacks described in [Section 3.2.1](#), [Section 3.2.2](#), [Section 3.2.3](#), and [Section 3.2.8](#). However it is also possible that multiple paths may make it more difficult to locate the source of a MITM attacker.

A delay modulation attack could result in extensively exercising parts of the code that wouldn't normally be extensively exercised and thus might expose flaws in the system that might otherwise not be exposed.

5.2. Integrity Protection

Description

An integrity protection mechanism, such as a Hash-based Message Authentication Code (HMAC) can be used to mitigate modification attacks on IP packets. Integrity protection in the control plane is discussed in [Section 5.6](#).

Packet Sequence Number Integrity Considerations

The use of PREOF in a DetNet implementation implies the use of a sequence number for each packet. There is a trust relationship between the device that adds the sequence number and the device that removes the sequence number. The sequence number may be end-to-end source to destination, or may be added/deleted by network edge devices. The adder and remover(s) have the trust relationship because they are the ones that ensure that the sequence numbers are not modifiable. Between those two points, there may or may not be replication and elimination functions. The elimination functions must be able to see the sequence numbers. Therefore any encryption that is done between adders and removers must not obscure the sequence number. If the sequence removers and the eliminators are in the same physical device, it may be possible to obscure the sequence number, however that is a layer violation, and is not recommended practice.

Related attacks

Integrity protection mitigates attacks related to modification and tampering, including the attacks described in [Section 3.2.2](#) and [Section 3.2.4](#).

5.3. DetNet Node Authentication

Description

Source authentication verifies the authenticity of DetNet sources, enabling mitigation of spoofing attacks. Note that while integrity protection ([Section 5.2](#)) prevents intermediate nodes from modifying information, authentication can provide traffic origin verification, i.e. to verify that each packet in a DetNet flow is from a trusted source. Authentication may be implemented as part of ingress filtering, for example.

Related attacks

DetNet node authentication is used to mitigate attacks related to spoofing, including the attacks of [Section 3.2.2](#), and [Section 3.2.4](#).

5.4. Dummy Traffic Insertion

Description

With some queueing methods such as [[IEEE802.1Qch-2017](#)] it is possible to introduce dummy traffic in order to regularize the timing of packet transmission.

Related attacks

Removing distinctive temporal properties of individual packets or flows can be used to mitigate against reconnaissance attacks [Section 3.2.7](#).

5.5. Encryption

Description

DetNet flows can in principle be forwarded in encrypted form at the DetNet layer, however, regarding encryption of IP headers see [Section 7](#).

Alternatively, if the payload is end-to-end encrypted at the application layer, the DetNet nodes should not have any need to inspect the payload itself, and thus the DetNet implementation can be data-agnostic.

Related attacks

Encryption can be used to mitigate recon attacks ([Section 3.2.7](#)). However, for a DetNet network to give differentiated quality of service on a flow-by-flow basis, the network must be able to identify the flows individually. This implies that in a recon attack the attacker may also be able to track individual flows to learn more about the system.

5.5.1. Encryption Considerations for DetNet

Any compute time which is required for encryption and decryption processing ('crypto') must be included in the flow latency calculations. Thus, crypto algorithms used in a DetNet must have bounded worst-case execution times, and these values must be used in the latency calculations.

Some crypto algorithms are symmetric in encode/decode time (such as AES) and others are asymmetric (such as public key algorithms). There are advantages and disadvantages to the use of either type in a given DetNet context. The discussion in this document relates to the timing implications of crypto for DetNet; it is assumed that integrity considerations are covered elsewhere in the literature.

Asymmetrical crypto is typically not used in networks on a packet-by-packet basis due to its computational cost. For example, if only endpoint checks or checks at a small number of intermediate points are required, asymmetric crypto can be used to authenticate distribution or exchange of a secret symmetric crypto key; a successful check based on that key will provide traffic origin verification, as long as the key is kept secret by the participants. TLS and IKE (for IPsec) are examples of this for endpoint checks.

However, if secret symmetrical keys are used for this purpose the key must be given to all relays, which increases the probability of a secret key being leaked. Also, if any relay is compromised or misbehaving it may inject traffic into the flow.

Alternatively, asymmetric crypto can provide traffic origin verification at every intermediate node. For example, a DetNet flow can be associated with an (asymmetric) keypair, such that the private key is available to the source of the flow and the public key is distributed with the flow information, allowing verification at every node for every packet. However, this is more computationally expensive.

In either case, origin verification also requires replay detection as part of the security protocol to prevent an attacker from recording and resending traffic, e.g., as a denial of service attack on flow forwarding resources.

If crypto keys are to be regenerated over the duration of the flow then the time required to accomplish this must be accounted for in the latency calculations.

5.6. Control and Signaling Message Protection

Description

Control and signaling messages can be protected using authentication and integrity protection mechanisms.

Related attacks

These mechanisms can be used to mitigate various attacks on the control plane, as described in [Section 3.2.6](#), [Section 3.2.8](#) and [Section 3.2.5](#).

5.7. Dynamic Performance Analytics

Description

The expectation is that the network will have a way to monitor to detect if timing guarantees are not being met, and a way to alert the control plane in that event. Information about the network performance can be gathered in real-time in order to detect anomalies and unusual behavior that may be the symptom of a security attack. The gathered information can be based, for example, on per-flow counters, bandwidth measurement, and monitoring of packet arrival times. Unusual behavior or potentially malicious nodes can be reported to a management system, or can be used as a trigger for taking corrective actions. The information can be tracked by DetNet end systems and transit nodes, and exported to a management system, for example using NETCONF.

Related attacks

Performance analytics can be used to mitigate various attacks, including the ones described in [Section 3.2.1](#) (Delay Attack), [Section 3.2.3](#) (Resource Segmentation Attack), and [Section 3.2.8](#) (Time Sync Attack).

For example, in the case of data plane delay attacks, one possible mitigation is to timestamp the data at the source, and timestamp it again at the destination, and if the resulting latency exceeds the promised bound, discard that data and warn the operator (and/or enter a fail-safe mode). Note that DetNet specifies packet sequence numbering, however it does not specify use of packet timestamps, although they may be used by the underlying transport (for example TSN) to provide the service.

5.8. Mitigation Summary

The following table maps the attacks of [Section 3](#) to the impacts of [Section 4](#), and to the mitigations of the current section. Each row specifies an attack, the impact of this attack if it is successfully implemented, and possible mitigation methods.

Editor's note: Is this tabular summary of the above information useful or necessary in this draft? If we opt to maintain the tables then the WG needs to validate them for completeness and correctness after all other draft comments have been addressed.

+-----+-----+-----+

Attack	Impact	Mitigations
Delay Attack	-Non-deterministic delay -Data disruption -Increased resource consumption	-Path redundancy -Performance analytics
Reconnaissance	-Enabler for other attacks	-Encryption -Dummy traffic insertion
DetNet Flow Modification or Spoofing	-Increased resource consumption -Data disruption	-Path redundancy -Integrity protection -DetNet Node authentication
Inter-Segment Attack	-Increased resource consumption -Data disruption	-Path redundancy -Performance analytics
Replication: Increased attack surface	-All impacts of other attacks	-Integrity protection -DetNet Node authentication
Replication-related Header Manipulation	-Non-deterministic delay -Data disruption	-Integrity protection -DetNet Node authentication
Path Manipulation	-Enabler for other attacks	-Control message protection
Path Choice: Increased Attack Surface	-All impacts of other attacks	-Control message protection
Control or Signaling Packet Modification	-Increased resource consumption -Non-deterministic delay -Data disruption	-Control message protection
Control or Signaling Packet Injection	-Increased resource consumption -Non-deterministic delay -Data disruption	-Control message protection
Attacks on Time Sync	-Non-deterministic	-Path redundancy

Mechanisms	delay	-Control message	
	-Increased resource	protection	
	consumption	-Performance	
	-Data disruption	analytics	
+-----+	+-----+	+-----+	+

Figure 3: Mapping Attacks to Impact and Mitigations

6. Association of Attacks to Use Cases

Different attacks can have different impact and/or mitigation depending on the use case, so we would like to make this association in our analysis. However since there is a potentially unbounded list of use cases, we categorize the attacks with respect to the common themes of the use cases as identified in the Use Case Common Themes section of the DetNet Use Cases [[RFC8578](#)].

See also Figure 2 for a mapping of the impact of attacks per use case by industry.

6.1. Use Cases by Common Themes

In this section we review each theme and discuss the attacks that are applicable to that theme, as well as anything specific about the impact and mitigations for that attack with respect to that theme. The table Figure 5 then provides a summary of the attacks that are applicable to each theme.

6.1.1. Network Layer - AVB/TSN Ethernet

DetNet is expected to run over various transmission mediums, with Ethernet being explicitly supported. Attacks such as Delay or Reconnaissance might be implemented differently on a different transmission medium, however the impact on the DetNet as a whole would be essentially the same. We thus conclude that all attacks and impacts that would be applicable to DetNet over Ethernet (i.e. all those named in this document) would also be applicable to DetNet over other transmission mediums.

With respect to mitigations, some methods are specific to the Ethernet medium, for example time-aware scheduling using 802.1Qbv can protect against excessive use of bandwidth at the ingress - for other mediums, other mitigations would have to be implemented to provide analogous protection.

6.1.2. Central Administration

A DetNet network is expected to be controlled by a centralized network configuration and control system (CNC). Such a system may be in a single central location, or it may be distributed across multiple control entities that function together as a unified control system for the network.

In this document we distinguish between attacks on the DetNet Control plane vs. Data plane. But is an attack affecting control plane packets synonymous with an attack on the CNC itself? For purposes of this document let us consider an attack on the CNC itself to be out of scope, and consider all attacks named in this document which are relevant to control plane packets to be relevant to this theme, including Path Manipulation, Path Choice, Control Packet Modification or Injection, Reconnaissance and Attacks on Time Sync Mechanisms.

6.1.3. Hot Swap

A DetNet network is not expected to be "plug and play" - it is expected that there is some centralized network configuration and control system. However, the ability to "hot swap" components (e.g. due to malfunction) is similar enough to "plug and play" that this kind of behavior may be expected in DetNet networks, depending on the implementation.

An attack surface related to Hot Swap is that the DetNet network must at least consider input at runtime from devices that were not part of the initial configuration of the network. Even a "perfect" (or "hitless") replacement of a device at runtime would not necessarily be ideal, since presumably one would want to distinguish it from the original for OAM purposes (e.g. to report hot swap of a failed device).

This implies that an attack such as Flow Modification, Spoofing or Inter-segment (which could introduce packets from a "new" device (i.e. one heretofore unknown on the network) could be used to exploit the need to consider such packets (as opposed to rejecting them out of hand as one would do if one did not have to consider introduction of a new device).

Similarly if the network was designed to support runtime replacement of a clock device, then presence (or apparent presence) and thus consideration of packets from a new such device could affect the network, or the time sync of the network, for example by initiating a new Best Master Clock selection process. Thus attacks on time sync should be considered when designing hot swap type functionality (see [[RFC7384](#)]).

6.1.4. Data Flow Information Models

Data Flow Information Models specific to DetNet networks are specified by DetNet, and thus are 'new' and thus potentially present a new attack surface.

6.1.5. L2 and L3 Integration

A DetNet network integrates Layer 2 (bridged) networks (e.g. AVB/TSN LAN) and Layer 3 (routed) networks via the use of well-known protocols such as IP, MPLS-PW, and Ethernet.

There are no specific entries in our table, however that does not imply that there could be no relevant attacks related to L2,L3 integration.

6.1.6. End-to-End Delivery

Packets sent over DetNet are not to be dropped by the network due to congestion. (Packets may however intentionally be dropped for intended reasons, e.g. per security measures).

A Data plane attack may force packets to be dropped, for example a "long" Delay or Replication/Elimination or Flow Modification attack.

The same result might be obtained by a Control plane attack, e.g. Path Manipulation or Signaling Packet Modification.

It may be that such attacks are limited to Internal MITM attackers, but other possibilities should be considered.

An attack may also cause packets that should not be delivered to be delivered, such as by forcing packets from one (e.g. replicated) path to be preferred over another path when they should not be (Replication attack), or by Flow Modification, or by Path Choice or Packet Injection. A Time Sync attack could cause a system that was expecting certain packets at certain times to accept unintended packets based on compromised system time or time windowing in the scheduler.

Packets may also be dropped due to malfunctioning software or hardware.

6.1.7. Proprietary Deterministic Ethernet Networks

There are many proprietary non-interoperable deterministic Ethernet-based networks currently available; DetNet is intended to provide an open-standards-based alternative to such networks. In cases where a

DetNet intersects with remnants of such networks or their protocols, such as by protocol emulation or access to such a network via a gateway, new attack surfaces can be opened.

For example an Inter-Segment or Control plane attack such as Path Manipulation, Path Choice or Control Packet Modification/Injection could be used to exploit commands specific to such a protocol, or that are interpreted differently by the different protocols or gateway.

6.1.8. Replacement for Proprietary Fieldbuses

There are many proprietary "field buses" used in today's industrial and other industries; DetNet is intended to provide an open-standards-based alternative to such buses. In cases where a DetNet intersects with such fieldbuses or their protocols, such as by protocol emulation or access via a gateway, new attack surfaces can be opened.

For example an Inter-Segment or Control plane attack such as Path Manipulation, Path Choice or Control Packet Modification/Injection could be used to exploit commands specific to such a protocol, or that are interpreted differently by the different protocols or gateway.

6.1.9. Deterministic vs Best-Effort Traffic

Most of the themes described in this document address OT (reserved) streams - this item is intended to address issues related to IT traffic on a DetNet.

DetNet is intended to support coexistence of time-sensitive operational (OT, deterministic) traffic and information (IT, "best effort") traffic on the same ("unified") network.

With DetNet, this coexistence will become more common, and mitigations will need to be established. The fact that the IT traffic on a DetNet is limited to a corporate controlled network makes this a less difficult problem compared to being exposed to the open Internet, however this aspect of DetNet security should not be underestimated.

An Inter-segment attack can flood the network with IT-type traffic with the intent of disrupting handling of IT traffic, and/or the goal of interfering with OT traffic. Presumably if the stream reservation and isolation of the DetNet is well-designed (better-designed than the attack) then interference with OT traffic should not result from an attack that floods the network with IT traffic.

However the DetNet's handling of IT traffic may not (by design) be as resilient to DOS attack, and thus designers must be otherwise prepared to mitigate DOS attacks on IT traffic in a DetNet.

6.1.10. Deterministic Flows

Reserved bandwidth data flows (deterministic flows) must provide the allocated bandwidth, and must be isolated from each other.

A Spoofing or Inter-segment attack which adds packet traffic to a bandwidth-reserved stream could cause that stream to occupy more bandwidth than it is allocated, resulting in interference with other deterministic flows.

A Flow Modification or Spoofing or Header Manipulation or Control Packet Modification attack could cause packets from one flow to be directed to another flow, thus breaching isolation between the flows.

6.1.11. Unused Reserved Bandwidth

If bandwidth reservations are made for a stream but the associated bandwidth is not used at any point in time, that bandwidth is made available on the network for best-effort traffic. However, note that security considerations for best-effort traffic on a DetNet network is out of scope of the present document, provided that such an attack does not affect performance for DetNet OT traffic.

6.1.12. Interoperability

The DetNet network specifications are intended to enable an ecosystem in which multiple vendors can create interoperable products, thus promoting device diversity and potentially higher numbers of each device manufactured.

Given that the DetNet specifications are unambiguously written and that the implementations are accurate, then this should not in and of itself cause a security concern; however, in the real world, it could be. The network operator can mitigate this through sufficient interoperability testing.

6.1.13. Cost Reductions

The DetNet network specifications are intended to enable an ecosystem in which multiple vendors can create interoperable products, thus promoting higher numbers of each device manufactured, promoting cost reduction and cost competition among vendors. Such "low cost" hardware or software components might present security concerns.

Network operators can mitigate such concerns through sufficient product testing.

6.1.14. Insufficiently Secure Devices

The DetNet network specifications are intended to enable an ecosystem in which multiple vendors can create interoperable products, thus promoting device diversity and potentially higher numbers of each device manufactured. Software that was originally designed for operation in isolated OT networks (and thus may not have been designed to be sufficiently secure, or secure at all) but is then deployed on a DetNet network that is intended to be highly secure may present an attack surface. (For example IoT exploits like the Mirai video-camera botnet ([\[MIRAI\]](#))).

The DetNet network operator may need to take specific actions to protect such devices.

6.1.15. DetNet Network Size

DetNet networks range in size from very small, e.g. inside a single industrial machine, to very large, for example a Utility Grid network spanning a whole country.

The size of the network might be related to how the attack is introduced into the network, for example if the entire network is local, there is a threat that power can be cut to the entire network. If the network is large, perhaps only a part of the network is attacked.

A Delay attack might be as relevant to a small network as to a large network, although the amount of delay might be different.

Attacks sourced from IT traffic might be more likely in large networks, since more people might have access to the network, presenting a larger attack surface. Similarly Path Manipulation, Path Choice and Time Sync attacks seem more likely relevant to large networks.

6.1.16. Multiple Hops

Large DetNet networks (e.g. a Utility Grid network) may involve many "hops" over various kinds of links for example radio repeaters, microwave links, fiber optic links, etc..

An attack that takes advantage of flaws (or even normal operation) in the device drivers for the various links (through internal knowledge of how the individual driver or firmware operates, perhaps like the

Stuxnet attack) could take proportionately greater advantage of this topology. We don't currently have an attack like this defined; we have only "protocol" (time or packet) based attacks. Perhaps we need to define an attack like this? Or is that out of scope for DetNet?

It is also possible that this DetNet topology will not be in as common use as other more homogeneous topologies so there may be more opportunity for attackers to exploit software and/or protocol flaws in the implementations which have not been wrung out by extensive use, particularly in the case of early adopters.

Of the attacks we have defined, the ones identified above as relevant to "large" networks seem to be most relevant.

6.1.17. Level of Service

A DetNet is expected to provide means to configure the network that include querying network path latency, requesting bounded latency for a given stream, requesting worst case maximum and/or minimum latency for a given path or stream, and so on. It is an expected case that the network cannot provide a given requested service level. In such cases the network control system should reply that the requested service level is not available (as opposed to accepting the parameter but then not delivering the desired behavior).

Control plane attacks such as Signaling Packet Modification and Injection could be used to modify or create control traffic that could interfere with the process of a user requesting a level of service and/or the network's reply.

Reconnaissance could be used to characterize flows and perhaps target specific flows for attack via the Control plane as noted above.

6.1.18. Bounded Latency

DetNet provides the expectation of guaranteed bounded latency.

Delay attacks can cause packets to miss their agreed-upon latency boundaries.

Time Sync attacks can corrupt the system's time reference, resulting in missed latency deadlines (with respect to the "correct" time reference).

6.1.19. Low Latency

Applications may require "extremely low latency" however depending on the application these may mean very different latency values; for example "low latency" across a Utility grid network is on a different time scale than "low latency" in a motor control loop in a small machine. The intent is that the mechanisms for specifying desired latency include wide ranges, and that architecturally there is nothing to prevent arbitrarily low latencies from being implemented in a given network.

Attacks on the Control plane (as described in the Level of Service theme) and Delay and Time attacks (as described in the Bounded Latency theme) both apply here.

6.1.20. Bounded Jitter (Latency Variation)

DetNet is expected to provide bounded jitter (packet to packet latency variation).

Delay attacks can cause packets to vary in their arrival times, resulting in packet to packet latency variation, thereby violating the jitter specification.

6.1.21. Symmetrical Path Delays

Some applications would like to specify that the transit delay time values be equal for both the transmit and return paths.

Delay attacks can cause path delays to materially differ between paths.

Time Sync attacks can corrupt the system's time reference, resulting in path delays that may be perceived to be different (with respect to the "correct" time reference) even if they are not materially different.

6.1.22. Reliability and Availability

DetNet based systems are expected to be implemented with essentially arbitrarily high availability (for example 99.9999% up time, or even 12 nines). The intent is that the DetNet designs should not make any assumptions about the level of reliability and availability that may be required of a given system, and should define parameters for communicating these kinds of metrics within the network.

Any attack on the system, of any type, can affect its overall reliability and availability, thus in our table we have marked every

attack. Since every DetNet depends to a greater or lesser degree on reliability and availability, this essentially means that all networks have to mitigate all attacks, which to a greater or lesser degree defeats the purpose of associating attacks with use cases. It also underscores the difficulty of designing "extremely high reliability" networks.

6.1.23. Redundant Paths

DetNet based systems are expected to be implemented with essentially arbitrarily high reliability/availability. A strategy used by DetNet for providing such extraordinarily high levels of reliability is to provide redundant paths that can be seamlessly switched between, all the while maintaining the required performance of that system.

Replication-related attacks are by definition applicable here. Control plane attacks can also interfere with the configuration of redundant paths.

6.1.24. Security Measures

A DetNet network must be made secure against devices failures, attackers, misbehaving devices, and so on. Does the threat affect such security measures themselves, e.g. by attacking SW designed to protect against device failure?

This is TBD, thus there are no specific entries in our table, however that does not imply that there could be no relevant attacks.

6.2. Attack Types by Use Case Common Theme

The following table lists the attacks of [Section 3](#), assigning a number to each type of attack. That number is then used as a short form identifier for the attack in Figure 5.

Editor's note: Is this tabular summary of the above information useful or necessary in this draft? If we opt to maintain the tables then the WG needs to validate them for completeness and correctness after all other draft comments have been addressed.

End-to-end Delivery		+		+		+		+		+		+		+	
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+
Proprietary Deterministic Ethernet Networks				+			+	+	+	+	+				
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+
Replacement for Proprietary Fieldbuses				+			+	+	+	+	+				
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+
Deterministic vs. Best- Effort Traffic				+											
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+
Deterministic Flows			+	+		+	+		+						
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+
Unused Reserved Bandwidth			+	+					+	+					
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+
Interoperability															
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+
Cost Reductions															
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+
Insufficiently Secure Devices															
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+
DetNet Network Size		+					+	+						+	
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+
Multiple Hops		+	+				+	+						+	
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+
Level of Service									+	+	+	+			
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+
Bounded Latency		+												+	
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+
Low Latency		+							+	+	+	+	+	+	+
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+
Bounded Jitter		+													
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+
Symmetric Path Delays		+												+	
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+
Reliability and Availability		+	+	+	+	+	+	+	+	+	+	+	+	+	+
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+
Redundant Paths					+	+			+	+					
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+
Security Measures															
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+

Figure 5: Mapping Between Themes and Attacks

6.3. Security Considerations for OAM Traffic

This section considers DetNet-specific security considerations for packet traffic that is generated and transmitted over a DetNet as part of OAM (Operations, Administration and Maintenance). For purposes of this discussion, OAM traffic falls into one of two basic types:

- o OAM traffic generated by the network itself. The additional bandwidth required for such packets is added by the network administration, presumably transparent to the customer. Security considerations for such traffic are not DetNet-specific (apart from such traffic being subject to the same DetNet-specific security considerations as any other DetNet data flow) and are thus not covered in this document.
- o OAM traffic generated by the customer. From a DetNet security point of view, DetNet security considerations for such traffic are exactly the same as for any other customer data flows.

Thus OAM traffic presents no additional (i.e. OAM-specific) DetNet security considerations.

7. DetNet Technology-Specific Threats

[Section 3](#) described threats which are independent of a DetNet implementation. This section considers threats specifically related to the IP- and MPLS-specific aspects of DetNet implementations.

The primary security considerations for the data plane specifically are to maintain the integrity of the data and the delivery of the associated DetNet service traversing the DetNet network.

The primary relevant differences between IP and MPLS implementations are in flow identification and OAM methodologies.

As noted in [[RFC8655](#)], DetNet operates at the IP layer ([[I-D.ietf-detnet-ip](#)]) and delivers service over sub-layer technologies such as MPLS ([[I-D.ietf-detnet-mpls](#)]) and IEEE 802.1 Time-Sensitive Networking (TSN) ([[I-D.ietf-detnet-ip-over-tsn](#)]). Application flows can be protected through whatever means are provided by the layer and sub-layer technologies. For example, technology-specific encryption may be used, such as that provided by IPsec [[RFC4301](#)] for IP flows and/or by an underlying sub-net using MACSec [[IEEE802.1AE-2018](#)] for IP over Ethernet (Layer-2) flows.

However, if the DetNet nodes cannot decrypt IPsec traffic, IPsec may not be a valid option; this is because the DetNet IP data plane

identifies flows via a 6-tuple that consists of two IP addresses, the transport protocol ID, two transport protocol port numbers and the DSCP in the IP header. When IPsec is used, the transport header is encrypted and the next protocol ID is an IPsec protocol, usually ESP, and not a transport protocol (e.g., neither TCP nor UDP, etc.) leaving only three components of the 6-tuple, which are the two IP addresses and the DSCP, which are in general not sufficient to identify a DetNet flow.

Sections below discuss threats specific to IP and MPLS in more detail.

7.1. IP

The IP protocol has a long history of security considerations and architectural protection mechanisms. From a data plane perspective DetNet does not add or modify any IP header information, and its use as a DetNet Data Plane does not introduce any new security issues that were not there before, apart from those already described in the data-plane-independent threats section [Section 3](#).

Thus the security considerations for a DetNet based on an IP data plane are purely inherited from the rich IP Security literature and code/application base, and the data-plane-independent section of this document.

Maintaining security for IP segments of a DetNet may be more challenging than for the MPLS segments of the network, given that the IP segments of the network may reach the edges of the network, which are more likely to involve interaction with potentially malevolent outside actors. Conversely MPLS is inherently more secure than IP since it is internal to routers and it is well-known how to protect it from outside influence.

Another way to look at DetNet IP security is to consider it in the light of VPN security; as an industry we have a lot of experience with VPNs running through networks with other VPNs, it is well known how to secure the network for that. However for a DetNet we have the additional subtlety that any possible interaction of one packet with another can have a potentially deleterious effect on the time properties of the flows. So the network must provide sufficient isolation between flows, for example by protecting the forwarding bandwidth and related resources so that they are available to detnet traffic, by whatever means are appropriate for that network's data plane.

In a VPN, bandwidth is generally guaranteed over a period of time, whereas in DetNet it is not aggregated over time. This implies that

any VPN-type protection mechanism must also maintain the DetNet timing constraints.

7.2. MPLS

An MPLS network carrying DetNet traffic is expected to be a "well-managed" network. Given that this is the case, it is difficult for an attacker to pass a raw MPLS encoded packet into a network because operators have considerable experience at excluding such packets at the network boundaries, as well as excluding MPLS packets being inserted through the use of a tunnel.

MPLS security is discussed extensively in [[RFC5920](#)] ("Security Framework for MPLS and GMPLS Networks") to which the reader is referred.

[[RFC6941](#)] builds on [[RFC5920](#)] by providing additional security considerations that are applicable to the MPLS-TP extensions appropriate to the MPLS Transport Profile [[RFC5921](#)], and thus to the operation of DetNet over some types of MPLS network.

[[RFC5921](#)] introduces to MPLS new Operations, Administration, and Maintenance (OAM) capabilities, a transport-oriented path protection mechanism, and strong emphasis on static provisioning supported by network management systems.

The operation of DetNet over an MPLS network is modeled on the operation of multi-segment pseudowires (MS-PW). Thus for guidance on securing the DetNet elements of DetNet over MPLS the reader is referred to the MS-PW security mechanisms as defined in [[RFC4447](#)], [[RFC3931](#)], [[RFC3985](#)], [[RFC6073](#)], and [[RFC6478](#)].

Having attended to the conventional aspects of network security it is necessary to attend to the dynamic aspects. The closest experience that the IETF has with securing protocols that are sensitive to manipulation of delay are the two way time transfer protocols (TWTT), which are NTP [[RFC5905](#)] and Precision Time Protocol [[IEEE1588](#)]. The security requirements for these are described in [[RFC7384](#)].

One particular problem that has been observed in operational tests of TWTT protocols is the ability for two closely but not completely synchronized streams to beat and cause a sudden phase hit to one of the streams. This can be mitigated by the careful use of a scheduling system in the underlying packet transport.

Further consideration of protection against dynamic attacks is work in progress.

8. IANA Considerations

This memo includes no requests from IANA.

9. Security Considerations

The security considerations of DetNet networks are presented throughout this document.

10. Informative References

[ARINC664P7]

ARINC, "ARINC 664 Aircraft Data Network, Part 7, Avionics Full-Duplex Switched Ethernet Network", 2009.

[I-D.ietf-detnet-data-plane-framework]

Varga, B., Farkas, J., Berger, L., Fedyk, D., Malis, A., Bryant, S., and J. Korhonen, "DetNet Data Plane Framework", [draft-ietf-detnet-data-plane-framework-03](#) (work in progress), October 2019.

[I-D.ietf-detnet-ip]

Varga, B., Farkas, J., Berger, L., Fedyk, D., Malis, A., Bryant, S., and J. Korhonen, "DetNet Data Plane: IP", [draft-ietf-detnet-ip-04](#) (work in progress), November 2019.

[I-D.ietf-detnet-ip-over-tsn]

Varga, B., Farkas, J., Malis, A., and S. Bryant, "DetNet Data Plane: IP over IEEE 802.1 Time Sensitive Networking (TSN)", [draft-ietf-detnet-ip-over-tsn-01](#) (work in progress), October 2019.

[I-D.ietf-detnet-mpls]

Varga, B., Farkas, J., Berger, L., Fedyk, D., Malis, A., Bryant, S., and J. Korhonen, "DetNet Data Plane: MPLS", [draft-ietf-detnet-mpls-04](#) (work in progress), November 2019.

[I-D.varga-detnet-service-model]

Varga, B. and J. Farkas, "DetNet Service Model", [draft-varga-detnet-service-model-02](#) (work in progress), May 2017.

[IEEE1588]

IEEE, "IEEE 1588 Standard for a Precision Clock Synchronization Protocol for Networked Measurement and Control Systems Version 2", 2008.

[IEEE802.1AE-2018]

IEEE Standards Association, "IEEE Std 802.1AE-2018 MAC Security (MACsec)", 2018,
<<https://ieeexplore.ieee.org/document/8585421>>.

[IEEE802.1Qch-2017]

IEEE Standards Association, "IEEE Standard for Local and metropolitan area networks--Bridges and Bridged Networks-- Amendment 29: Cyclic Queuing and Forwarding", 2017,
<<https://ieeexplore.ieee.org/document/7961303>>.

[MIRAI]

krebsonsecurity.com, "<https://krebsonsecurity.com/2016/10/hacked-cameras-dvrs-powered-todays-massive-internet-outage/>", 2016.

[RFC2475]

Blake, S., Black, D., Carlson, M., Davies, E., Wang, Z., and W. Weiss, "An Architecture for Differentiated Services", [RFC 2475](#), DOI 10.17487/RFC2475, December 1998,
<<https://www.rfc-editor.org/info/rfc2475>>.

[RFC3552]

Rescorla, E. and B. Korver, "Guidelines for Writing RFC Text on Security Considerations", [BCP 72](#), [RFC 3552](#), DOI 10.17487/RFC3552, July 2003,
<<https://www.rfc-editor.org/info/rfc3552>>.

[RFC3931]

Lau, J., Ed., Townsley, M., Ed., and I. Goyret, Ed., "Layer Two Tunneling Protocol - Version 3 (L2TPv3)", [RFC 3931](#), DOI 10.17487/RFC3931, March 2005,
<<https://www.rfc-editor.org/info/rfc3931>>.

[RFC3985]

Bryant, S., Ed. and P. Pate, Ed., "Pseudo Wire Emulation Edge-to-Edge (PWE3) Architecture", [RFC 3985](#), DOI 10.17487/RFC3985, March 2005,
<<https://www.rfc-editor.org/info/rfc3985>>.

[RFC4301]

Kent, S. and K. Seo, "Security Architecture for the Internet Protocol", [RFC 4301](#), DOI 10.17487/RFC4301, December 2005, <<https://www.rfc-editor.org/info/rfc4301>>.

[RFC4447]

Martini, L., Ed., Rosen, E., El-Aawar, N., Smith, T., and G. Heron, "Pseudowire Setup and Maintenance Using the Label Distribution Protocol (LDP)", [RFC 4447](#), DOI 10.17487/RFC4447, April 2006,
<<https://www.rfc-editor.org/info/rfc4447>>.

- [RFC5905] Mills, D., Martin, J., Ed., Burbank, J., and W. Kasch, "Network Time Protocol Version 4: Protocol and Algorithms Specification", [RFC 5905](#), DOI 10.17487/RFC5905, June 2010, <<https://www.rfc-editor.org/info/rfc5905>>.
- [RFC5920] Fang, L., Ed., "Security Framework for MPLS and GMPLS Networks", [RFC 5920](#), DOI 10.17487/RFC5920, July 2010, <<https://www.rfc-editor.org/info/rfc5920>>.
- [RFC5921] Bocci, M., Ed., Bryant, S., Ed., Frost, D., Ed., Levrau, L., and L. Berger, "A Framework for MPLS in Transport Networks", [RFC 5921](#), DOI 10.17487/RFC5921, July 2010, <<https://www.rfc-editor.org/info/rfc5921>>.
- [RFC6073] Martini, L., Metz, C., Nadeau, T., Bocci, M., and M. Aissaoui, "Segmented Pseudowire", [RFC 6073](#), DOI 10.17487/RFC6073, January 2011, <<https://www.rfc-editor.org/info/rfc6073>>.
- [RFC6478] Martini, L., Swallow, G., Heron, G., and M. Bocci, "Pseudowire Status for Static Pseudowires", [RFC 6478](#), DOI 10.17487/RFC6478, May 2012, <<https://www.rfc-editor.org/info/rfc6478>>.
- [RFC6941] Fang, L., Ed., Niven-Jenkins, B., Ed., Mansfield, S., Ed., and R. Graveman, Ed., "MPLS Transport Profile (MPLS-TP) Security Framework", [RFC 6941](#), DOI 10.17487/RFC6941, April 2013, <<https://www.rfc-editor.org/info/rfc6941>>.
- [RFC7384] Mizrahi, T., "Security Requirements of Time Protocols in Packet Switched Networks", [RFC 7384](#), DOI 10.17487/RFC7384, October 2014, <<https://www.rfc-editor.org/info/rfc7384>>.
- [RFC8578] Grossman, E., Ed., "Deterministic Networking Use Cases", [RFC 8578](#), DOI 10.17487/RFC8578, May 2019, <<https://www.rfc-editor.org/info/rfc8578>>.
- [RFC8655] Finn, N., Thubert, P., Varga, B., and J. Farkas, "Deterministic Networking Architecture", [RFC 8655](#), DOI 10.17487/RFC8655, October 2019, <<https://www.rfc-editor.org/info/rfc8655>>.

Authors' Addresses

Tal Mizrahi
Huawei Network.IO Innovation Lab

Email: tal.mizrahi.phd@gmail.com

Ethan Grossman (editor)
Dolby Laboratories, Inc.
1275 Market Street
San Francisco, CA 94103
USA

Phone: +1 415 645 4726
Email: ethan.grossman@dolby.com
URI: <http://www.dolby.com>

Andrew J. Hacker
MistiQ Technologies, Inc

Harrisburg, PA
USA

Phone:
Email: ajhacker@mistiqttech.com
URI: <http://www.mistiqttech.com>

Subir Das
Applied Communication Sciences
150 Mount Airy Road, Basking Ridge
New Jersey, 07920
USA

Email: sdas@appcomsci.com

John Dowdell
Airbus Defence and Space
Celtic Springs
Newport NP10 8FZ
United Kingdom

Email: john.dowdell.ietf@gmail.com

Henrik Austad
SINTEF Digital
Klaebuveien 153
Trondheim 7037
Norway

Email: henrik@austad.us

Norman Finn
Huawei

Email: norman.finn@mail01.huawei.com