

INTERNET-DRAFT  
Dynamic Host Control Working Group  
Expires August 2001

D. Jones  
YAS Corporation  
R. Woundy  
Cisco  
February 2001

Addition of Device Class to Agent Options  
<[draft-ietf-dhc-agentoptions-device-class-01.txt](#)>

Status of this Memo

This document is an Internet-Draft and is in full conformance with all provisions of [Section 10 of RFC2026](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/lid-abstracts.txt>

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

Copyright Notice

Copyright (C) The Internet Society (2001). All Rights Reserved.

Abstract

This document proposes a new sub-option to the DHCP Relay Information Agent Option. This new sub-option is for use with DOCSIS cable modems and describes a "device class" to which the cable modem belongs. The cable modem signals its device class information to the Relay Agent using DOCSIS signalling, and the Relay Agent forwards the device class information to the DHCP Server which can then make a policy decision based on it.

---

Internet Draft Addition of Device Class to Agent Options February 2001

## 1. Introduction

DHCP Agent Options is described in [1] and includes several Relay Agent Information sub-options. This I-D proposes an additional sub-option for use with DOCSIS cable modems. This sub-option MAY be added by DHCP relay agents which terminate cable modems. The sub-option encodes an identifier of the device class to which the cable modem belongs. It is intended for use by DHCP servers to make policy decisions based on the device class of the host.

The motivation for using a Relay Agent Information sub-option, rather than a new or existing DHCP option, is the introduction of CPE Controlled Cable Modems (CCCMs) [2]. In an implementation of a CCCM, the modem firmware controls DOCSIS signalling, but the attached computer (CPE) manages other protocol activities -- particularly DHCP client message handling. The assumption of this document is that it is better to trust the operation of the CCCM firmware, than to trust the operation of CCCM software running on the attached computer (e.g. a standard PC).

## 2. Device Class Sub-option

The DOCSIS RFI specification [3] specifies the Device Class encoding within the payload of the Device Class Identification Request (DCI-REQ) message. The relay agent passes the Device Class value unchanged to the DHCP server. Possible uses of this field include:

- o host endpoint information
- o host hardware capabilities
- o host software capabilities
- o host options information

The Device Class sub-option is coded as follows:

SubOpt	Len	Device Class						
TBD	n	d1	d2	d3	d4	d5	d6	...

The DHCP server needs to understand the meaning of this sub-option in order to offer different policy options in its reply to the host. DHCP servers MAY use the Device Class for IP and other parameter assignment policies for cable modems.

### 3. Security Considerations

Operation of the DHCP Relay Agent Information Option relies on an implied trusted relationship between the DHCP relay agent and the DHCP server.

Operation of the Device Class sub-option also relies on an implied trusted relationship between the DHCP client (i.e. the cable modem) and the DHCP relay agent, through DOCSIS signalling. According to DOCSIS specifications, the cable modem firmware always controls DOCSIS signalling, but may not control DHCP client message handling (e.g. CCCMs). This document assumes that the cable modem firmware is trustworthy for DOCSIS signalling information.

This document introduces a new identifier, the Device Class sub-option, that is provided by the relay agent device and is assumed to be trusted. Cryptographic or other techniques to authenticate the Device Class are beyond the scope of this document.

### 4. References

- [1] Patrick, M., "DHCP Relay Agent Information Option", [RFC 3046](#), January 2001.
- [2] "Data-Over-Cable Service Interface Specifications: Cable Modem to Customer Premise Equipment Interface Specification SP-CMCI-I05-001215", DOCSIS, December 2000, <http://www.cablemodem.com>.
- [3] "Data-Over-Cable Service Interface Specifications: Cable Modem Radio Frequency Interface Specification SP-RFIV1.1-I06-001215", DOCSIS, December 2000, <http://www.cablemodem.com>.

## 5. Authors' Addresses

Doug Jones  
YAS Corporation  
300 Brickstone Square  
Andover, MA 01810  
Phone: (303) 661-3823  
EMail: doug@yas.com

Rich Woundy  
Cisco Systems

Doug Jones, Rich Woundy Expires August 2001

[Page 3]

---

Internet Draft Addition of Device Class to Agent Options February 2001

250 Apollo Drive  
Chelmsford, MA 01824  
Phone: (978) 244-8000  
EMail: rwoundy@cisco.com

## 6. Full Copyright Statement

Copyright (C) The Internet Society (2001). All Rights Reserved.

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this paragraph are included on all such copies and derivative works. However, this document itself may not be modified in any way, such as by removing the copyright notice or references to the Internet Society or other Internet organizations, except as needed for the purpose of developing Internet standards in which case the procedures for copyrights defined in the Internet Standards process must be followed, or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by the Internet Society or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING

BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION  
HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MER-  
CHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Doug Jones, Rich Woundy Expires August 2001

[Page 4]