

Network Working Group
Dynamic Host Configuration Working Group
Category: Standards Track
INTERNET-DRAFT

Michael Carney
Sun Microsystems, Inc
March 2000
Expires: September 2000

New Option Review Guidelines and Additional Option Namespace
<[draft-ietf-dhc-option-review-and-namespace-02.txt](#)>

Status of this memo

This document is an Internet-Draft and is in full conformance with all provisions of [Section 10 of RFC2026](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/lid-abstracts.txt>

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

Comments regarding this draft should be sent to dhcp-v4@bucknell.edu

Abstract

This document outlines deficiencies that have become evident since [RFC 2131](#) and [RFC 2132](#) were published regarding the allocation of new option codes, the review of drafts covering these new option codes, and the availability of option codes for new parameters. The document then presents proposals for correcting these deficiencies.

1. Introduction

The rapid and wide-spread adoption of DHCPv4 has lead to an increasing number of new DHCP option and message type drafts under DHC WG review. Experience with the current IANA option code allocation process and the DHC WG draft review process has

identified a number of deficiencies, namely:

- * We're rapidly going through the remaining option codes, and face the possibility of exhausting the remaining codes before the wide-spread adoption of IPv6 is achieved.
- * There are no guidelines to help the DHC WG and the DHCP community at large gauge the impact of the addition of new

Mar 10 13:59 2000 New Option Review and Option Namespace Carney Page 2

message types and options. Some message types and options that have been proposed require changes to the DHCP protocol itself and/or current implementations. Because the adoption of such message types or options has a greater impact on the DHCP community, these message types and options require more scrutiny by the DHC WG and IESG.

- * Because some options or message types could change the DHCP protocol itself, we need a method of explicitly communicating the change of DHCP versions among implementations. Today, we have no such method.
- * There is no provision to preserve compatibility with earlier versions of the protocol.

Interoperability testing at Connectathon (1997, 1998, and 1999) has shown a reduction in the level of interoperability between implementations. These interoperability problems were found to be due to confusion among implementors about how certain features of the protocol should be implemented. Improvement (tightening) of the general [RFC 2131](#) and [RFC 2132](#) drafts as well as the tightening of new option specifications (using the guidelines defined in this document) will help increase the level of interoperability.

[1.1](#) Conventions Used in the Document

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY" and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [5].

[1.2](#) Terminology

[RFC 2132](#)-form options The [RFC 2132](#) [2] option block form is currently in use by DHCPv4, and is documented in [RFC 2131](#) [1]. This option form is identified by the BOOTP magic cookie {99, 130, 83, 99}.

RFC TBD-form options A new option block form recommendation to alleviate option code exhaustion (described in [section 3.6](#) below). This option form will be identified by a TBD BOOTP magic cookie issued by IANA.

[2.](#) Review Guidelines

We tackle the message type and option code review problem by defining a set of categories based upon upon the impact the adoption of an option or new message type will have on the DHCP community. Option or new message drafts appropriately categorized aid reviewers by helping them evaluate the draft. Once the DHC WG and the draft author(s) agree on the category of the proposed option or message type, that category will be listed explicitly in the abstract of the option or message draft.

Mar 10 13:59 2000 New Option Review and Option Namespace Carney Page 3

[2.1.](#) Hints for selecting the correct review category

- A) This option has no relationship to other existing or proposed options. It would not require change of existing DHCP client, server, or BOOTP relay agent implementations. It would not change the version of the DHCP protocol. Its introduction would not invalidate previous version(s) of the DHCP protocol. Is this option better handled by the Service Location Protocol (SLP) [\[7\]](#)? If it provides data which is unrelated to network interface configuration, then the option proposer SHOULD consider the use of SLP for the delivery of this data, if SLP is deployed widely enough to meet her needs.
- B) This message type has no relationship to other existing or proposed message types. It would not require change of existing DHCP client, server, or BOOTP relay agent implementations. It would not change the version of the DHCP protocol. The message type is useful to the DHCP community at large.
- C) This option has no relationship to other existing or proposed options or message types. It would not require change of existing DHCP client, server, or BOOTP relay agent implementations. It would not change the version of the DHCP protocol. Its introduction would not invalidate previous version(s) of the DHCP protocol. It isn't a candidate for SLP. Is this option useful to the DHCP community at large (e.g. implementors) or is it specific to a particular

implementation? If it is the latter, then the proposer of the option should consider using the encapsulated vendor space available to your implementation to encode this information. Note that most DHCP implementations only support default option types for encapsulated options. (see [Section 3.6](#) below).

- D) This option has no relationship to other existing or proposed options or message types. It would not require change of existing DHCP client, server, or BOOTP relay agent implementations. It would not change the version of the DHCP protocol. Its introduction would not invalidate previous version(s) of the DHCP protocol. It is not a candidate for SLP or the vendor's option space. Can this option be effectively encoded in the default option type ([Section 3.6](#) below)? For example, can it be communicated as a single ASCII string? A list of IP addresses? If so, then one of the default formats should be used.
- E) This option would have a implicit or explicit relationship between it and other existing options or other proposed options, or the data it represents cannot be carried in a default option type ([Section 3.6](#) below). It MAY change the behavior of existing DHCP client, server, and/or BOOTP relay agent implementations. It would not change the DHCP protocol version. Its introduction would not invalidate previous

version(s) of the DHCP protocol.

Examples of implicit/explicit option relationships:

Option	Related Options
-----	-----
Vendor Class Identifier	Encapsulated vendor option(s)
User Class Identifier	Standard option's scope

- F) This message type would have a implicit or explicit relationship between it and other existing message types or options Its adoption MAY change the behavior of existing DHCP client, server, and/or BOOTP relay agent implementations. It would not change the DHCP protocol version. Its introduction would not invalidate previous version(s) of the DHCP protocol.
- G) The addition of this option would change Table 3, "Fields and options used by DHCP servers" and/or Table 5, "Fields and options used by DHCP clients" in [RFC 2131](#) [1], and thus

change the DHCP protocol. Pre-existing versions / implementations would continue to interoperate.

- H) The addition of this option or message type would invalidate previous versions of the DHCP protocol, preventing client, server, and/or BOOTP relay agents implementing the earlier version(s) from functioning.

Guidelines -----	Review Category -----
A	None. Use SLP to register and deliver your information.
B	Category One
C	None. Use your Vendor-specific option space for your option.
D	Category One
E	Category Two
F	Category Two
G	Category Three
H	Category Four

[2.2](#). Category One

Options in this category MUST NOT require changes to the DHCP protocol, server, client, or BOOTP relay agent implementations. They MAY be either [RFC 2132](#)-form or RFC TBD-form options. They MUST NOT be dependent on other options being present or absent. Earlier

Mar 10 13:59 2000 New Option Review and Option Namespace Carney Page 5

versions/implementations of the protocol continue to interoperate in the presence of these options. Administrative tools and DHCP protocol debugging tools which generically support the default option types MAY need to be reconfigured in order to permit management of the new option. Options of this type are "payload" options, and MUST be of one of the default option types for the option block form ([RFC 2132](#) or RFC TBD).

Acceptance criteria:

Working group/IETF community review: Yes.

IANA option number registration:	Yes.
Interoperability testing (2 or more implementations)	No.
DHCP protocol version change:	No.

2.3. Category Two

Options in this category MUST NOT require changes to the DHCP protocol. They MAY require changes to server, client, relay agent implementations, administrative tools, and DHCP protocol debugging tools. They MAY depend on the presence or absence of other options, as long as those other options are NOT in Table 3 or Table 5 of [RFC 2131](#) [1]. Any dependence on other options MUST be made explicit in the new options draft. Existing versions / implementations of the protocol continue to interoperate in the presence of messages containing category two options. Options of this type are "affect implementation" options.

An option MUST be designed in such a way as a reply/response from non-compliant implementations can be easily distinguished from those of compliant implementations. An option MUST NEVER change the interpretation of existing options. The option draft author MUST specify a compliant implementation's behavior if that implementation receives a reply/response from a non-compliant implementation.

Acceptance criteria:

Working group/IETF community review:	Yes.
IANA option number registration:	Yes.
Interoperability testing (2 or more implementations)	Yes.
DHCP protocol version change:	No.

2.4. Category Three

Options in this category EXPLICITLY change the DHCP protocol. They WILL require changes to server, client, and/or relay agent implementations. They MAY depend on the presence or absence of other options. Any dependence on other options MUST be made explicit in the new option draft. The addition of such options result in changes to Table 3, "Fields and options used by DHCP servers" and/or Table 5, "Fields and options used by DHCP clients" in [RFC 2131](#) [1]. Existing versions / implementations of the protocol continue to interoperate in the presence of traffic containing category three options. Administrative tools MUST be changed to support options of this type. DHCP protocol debugging

tools would need to be updated to recognize these options. Options of this type are known as "affect protocol" options. The acceptance

of a Category Three option results in incrementing the DHCP version option value.

An option MUST be designed in such a way as a reply/response from non-compliant implementations can be easily distinguished from those of compliant implementations. The option draft author MUST specify a compliant implementation's behavior if that implementation receives a reply/response from a non-compliant implementation. An option MUST NEVER change the interpretation of existing options. Category Three option implementations can easily detect a non-compliant implementation due to the absence of the DHCP version option or a lower than expected version number.

Acceptance criteria:

Working group/IETF community review:	Yes.
IANA option number registration:	Yes.
Interoperability testing (2 or more implementations)	Yes.
DHCP protocol version change:	Yes.

[2.5.](#) Category Four

Options in this category would EXPLICITLY change the DHCP protocol in a non-backward compatible manner. They would require changes to ALL DHCP client, server, and/or BOOTP relay agent implementations. They INVALIDATE one or more of the previous versions of the BOOTP/DHCP protocol.

Because category four options invalidate previous versions of the protocol, they are NOT candidates for acceptance. Changes to the the DHCP protocol MUST BE backward compatible.

[3.](#) New [RFC 2132](#)-form options for version, block-type, and parameter request list.

We define three new [RFC 2132](#)-form options. The first is used by a DHCP client to request a response in a certain option block form. The second option is used by both DHCP clients and servers to explicitly identify the version of protocol used in the messages generated. The final option is used by RFC TBD client implementations to request RFC TBD options from RFC TBD servers.

[3.1.](#) DHCP Option Block Request Option

This option is used by RFC TBD client implementations to request RFC TBD-form replies from RFC TBD server implementations. This option is included in [RFC 2132](#)-form DHCPDISCOVERs, INIT-REBOOT DHCPREQUESTs, and DHCPINFORMs to request RFC TBD-form replies.

This option MUST NOT be used by DHCP servers in their responses to DHCP clients.

The DHCP Option Block Request Option is of the [RFC 2132](#)-form, and

consists of a single 4 octet string holding the magic cookie of the desired option block form.

Code	Len	Magic cookie
X	4	...

[3.2.](#) DHCP Version Option

This option represents the DHCP version. DHCP messages without this option are [RFC 2131](#) [1]. The addition of Category Three option(s) (perhaps grouped together) result in a DHCP version change. All implementations supporting versions greater than [RFC 2131](#) MUST include the DHCP version option in all messages, generated by both client or server.

The DHCP Protocol Version Option is of the [RFC 2132](#)-form, and consists of an single unsigned 16bit integer. The first Category Three option accepted by the DHC WG will be assigned version zero (0).

Code	Len	Value
Y	2	(0-65535)

DHCP protocol versions MUST be backward compatible with earlier versions.

[3.3.](#) RFC TBD Parameter Request List Option

This option is used by a RFC TBD DHCP client to request values for the specified configuration parameters. The list of requested parameters is specified as a power of 2n octets, where each 16 bit field carries an unsigned 16bit number from 1-65534 representing valid DHCP option codes defined in [RFC 2132](#) [2] and in separate option specification drafts. Note that at most 128 options can be requested.

The client MAY list the options in order of preference. The DHCP server is not required to return the options in the requested order.

The RFC TBD parameter request list option is intended for use by RFC TBD DHCP clients and servers ONLY. While a RFC TBD client could include use either (or both) parameter request list options ([RFC 2132](#) code 55 or this option), such a client SHOULD make request its parameters using only the RFC TBD parameter request list option.

```

Code   Len   Option Codes
+-----+-----+-----+-----+-----+-----+-----+
|  Z   | 2n   |      s1   |      s2   |      ...

```

Mar 10 13:59 2000 New Option Review and Option Namespace Carney Page 8

```

+-----+-----+-----+-----+-----+-----+-----+

```

3.4 Allocation of options from [RFC 2132](#) or RFC TBD option name spaces

Allocation of new options from the RFC TBD name space can only occur if we have two (2) or more RFC TBD option name space implementations which have demonstrated interoperability. Such interoperability testing could occur at the next Connectathon event (held late February/early March every year).

The selection of which name space from which to allocate an option is left to the DHC WG and IESG, following the process outlined in Ralph Drom's "Procedure for Defining New DHCP Options" [[4](#)].

3.5. [RFC 2132](#) Option Block Form

For convenience, I have extracted the description of [RFC 2132](#)-form options from [RFC 2132](#) [[2](#)].

```

Code   Len   Value
+-----+-----+-----+
|      |      |      ...
+-----+-----+-----+

```

Options of this form consist of three single octet fields: code, len, and value.

The code value is a single octet (0-255). 0 (pad) and 255 (end) are the only codes that do not follow the code, len, value form. Len is a single octet (0-255) describing the length of the value field. Value contains the data payload.

3.6. [RFC 2132](#)-form Default Option Types

1) Single variable-length ASCII string.

- 2) Single variable-length OCTET string.
- 3) 1-X Multiple of NUMBERS (1, 2, 4, 8 octets each). May consist of a LIST where the list entries are defined as multiple NUMBERS.

Example: "A variable-length list of 2 32bit NUMBERS representing the offset and length of a block of data"

- 4) 1-X Multiple of IPv4 addresses. May consist of a LIST where the list entries consist of multiple IP addresses.

Example: "A list of static routes (destination, router), ..."

If an implementation encounters [RFC 2132](#)-form options which it does not understand, it will simply skip over the option (using that option's len field) and continue option processing. This behavior ensures that [RFC 2131](#) compliant implementations safely ignore new options (e.g. the DHCP version option). Current DHCP

implementations SHOULD ignore any non-RFC 2132-form option block.

[3.7.](#) Proposed RFC TBD Option Block Form

We propose the creation of the following option block form described below, which greatly increases the option space and size of individual options. We feel that the adoption of this option block form will resolve the approaching [RFC 2132](#) standard option code availability problem.

Code	Len	Data
uint16_t	uint16_t	...

Code value is a network-order double-octet unsigned value (0-65535). 0 (pad) and 65535 (end) are the only codes that do not follow the code, len, value form. Len is a network-order double-octet unsigned value (0-65535). Data contains Len octets.

The first 255 RFC TBD option codes are preassigned for mapping [RFC 2132](#) options into the RFC TBD option space. Because the size limit of options within the RFC TBD option space is much higher than that of options within the [RFC 2132](#) option space, RFC TBD server implementations MUST use care in responding to [RFC 2132](#) clients. If the data for a mapped [RFC 2132](#) option would exceed the

253 length restriction of [RFC 2132](#) clients, the RFC TBD implementation MUST drop the option from the reply, and SHOULD increment an error count or log a message regarding this event. Note that the creation of multiple instances of [RFC 2132](#) options in order to provide all of the data within the configured RFC TBD option is not workable, since by definition options within the [RFC 2132](#) (and RFC TBD) option space are position-independent, and thus deterministic ordering of data is not possible.

3.8. RFC TBD Default Option Types

All option types as listed in [Section 3.6](#), and:

- 1) UNICODE string.
- 2) IPv6 addresses(s). Multiple of 16 octets. Encoded within an implementation's configuration table using the text representation as defined by [Section 2.2 of RFC 2373](#) [6].
- 3) Encapsulated RFC TBD options. For example, New User class, Vendor class-style options. Encapsulated options follow same code, len, value form of RFC TBD options. Overall length specifies limit of encapsulation.
- 4) Mixed-type options. These options are made up of combinations of 3.6/3.8 typed fields. Variable-length typed fields are preceded by a two octet unsigned integer length field. Mixed type options are useful for encoding combinations of data (structures).

Example: The following option contains an NVT ASCII string followed by a boolean, followed by a 32bit unsigned integer.

Code	Len	Data
771	17	13 Hello, World! 1 4123782

- 5) BOOLEAN. A single octet value which is explicitly TRUE if non-zero, explicitly FALSE if zero (0). Len is always one.

4. Behavior of [RFC 2132](#) and RFC TBD Client and Server Implementations

4.1 Client Behavior

A DHCP client in the INIT state prefers DHCP replies matching the DHCP option block form ([RFC 2132](#) or RFC TBD) and DHCP protocol

version of its DHCPDISCOVER. Option block form is preferred over DHCP protocol version.

DHCP clients SHOULD always indicate the size of response they can accept using the DHCP MTU option.

4.1.1 INIT/INFORM states

A client in one of these states pauses to collect replies (DHCP of any type/version or BOOTP replies) for a tunable polling interval (default: 5 seconds). Retransmissions use the algorithm outlined in [Section 4.1 of RFC 2131](#) [1].

Existing [RFC 2132](#)-form clients require no change in their behavior as specified in [RFC 2131](#) [1].

[RFC 2132](#)-form clients who support a later version of the DHCP protocol include the DHCP version option identifying the version of DHCP protocol they support. They prefer replies matching their protocol version over older versions of DHCP and BOOTP replies. If a [RFC 2132](#)-form client selects a reply from a down-rev DHCP protocol server (or BOOTP server), then that client MAY update an error count or log this event.

A RFC TBD-form client in one of these states forms the appropriate [RFC 2132](#)-form message (DHCPDISCOVER, DHCPINFORM) and includes the DHCP Option Block Request Option (set to the RFC TBD magic cookie) and the DHCP version option if it supports a version greater than that specified in [RFC 2131](#), and sends this message in the manner appropriate for the message type. A RFC TBD-form client prefers RFC TBD-form responses over [RFC 2132](#)-form responses. Within responses of a certain option form, responses which match the client's DHCP protocol version are preferred over those responses that are down-rev. If no DHCP responses are received, the client MAY choose a BOOTP response if such a response is available. A RFC TBD-form client MAY use the RFC TBD parameter request option to request options in the RFC TBD option space ([section 3.3](#)).

In the case of an INIT state client, the DHCPREQUEST used to accept the DHCP OFFER is formed using the option block form and DHCP protocol version of the selected DHCP OFFER.

For the duration of the lease, the client MUST form request messages using the option block form and DHCP protocol version of the original DHCPACK (INIT/INFORM) states when verifying existing configuration (INIT-REBOOT DHCPREQUEST), requesting lease

extensions (DHCPREQUEST), declining an IP address (DHCPDECLINE), or releasing an IP address (DHCPRELEASE).

In summary, a RFC TBD-form DHCP client will prefer RFC TBD-form replies over [RFC 2132](#)-form replies. Within replies which match the selected option block form, a client will prefer replies which match its DHCP protocol version. All subsequent traffic is done using the option block form and DHCP protocol version of the accepted DHCP OFFER/DHCPACK.

[4.2](#) Server Behavior

[4.2.1](#) Option Block Format-independent Server Behavior

A server which receives a BOOTP magic cookie it does not understand SHOULD respond with a standard BOOTP reply ONLY if it is explicitly configured to do so. Note that RFC TBD-form requests will appear to [RFC 2131](#) servers as BOOTP requests with an unrecognized magic cookie. In such environments, the [RFC 2131](#) server's ability to respond to BOOTP clients SHOULD be restricted, and RFC TBD servers SHOULD be configured to respond to BOOTP clients.

If a DHCPDISCOVER/DHCPINFORM is received which contains a DHCP protocol version option, a server MUST:

- a) If the DHCP protocol version is down-rev of that supported by the server, the server will format all messages in that earlier version. If the DHCP server does not support the earlier version of the protocol, it MUST drop the request, and MAY update an error counter or log the event.
- b) If the DHCP protocol version is greater than that supported by the server, it MAY either drop the request or respond to the client using messages of the DHCP protocol version supported by the server. This behavior SHOULD be configurable by the administrator. The server SHOULD choose to delay responding to the up-rev client for a configurable number of seconds, in order to give potential higher-rev servers a chance to reply.
- c) If the DHCP protocol version matches that of the server, then the server responds immediately (if possible) to the client with the appropriately formatted reply.

[4.2.2](#) RFC TBD-form Server Behavior

A RFC TBD-form server can identify a RFC TBD-form client by the

presence of the DHCP Option Block Request Option with the RFC TBD magic cookie in the option value field in [RFC 2132](#)-form requests or RFC TBD-form requests identified by the RFC TBD-form magic cookie. For the following scenarios, assume a RFC TBD-form server has free resources available for allocation.

- a) If a RFC TBD-form response is requested, it MUST respond with a RFC TBD-form response if it chooses to respond at all. The server SHOULD endeavor to provide the information requested in any present [RFC 2132](#) code 55 (parameter request list option) and/or RFC TBD parameter request list option ([Section 3.3](#)).
- b) If a [RFC 2132](#)-form response is requested (no DHCP Option Block Request Option is present) and the RFC TBD-form server is explicitly configured to respond to [RFC 2132](#)-form clients, it MUST respond with a [RFC 2132](#)-form response if it chooses to respond at all.
- c) If a request is received which contains a DHCP Option Block Request Option with a value it does not recognize, the server MUST either drop the request or respond with a [RFC 2132](#)-form response. Its behavior in this situation SHOULD be an administrator-configured option.

A DHCP server MUST NOT use the DHCP Option Block Request Option in the messages it generates for DHCP clients.

[5](#). Security Considerations

Not Applicable.

[6](#). Acknowledgements

The author would like to gratefully acknowledge the active participation of the following DHCP future panel members: Ralph Droms, Kester Fong, Pratik Gupta, Barr Hibbs, Kim Kinnear, Ted Lemon, Nathan Lane, and Glenn Waters. The author would also like to thank Thomas Narten for his review comments.

[7](#). Copyright

Copyright (C) The Internet Society (1999). All Rights Reserved.

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this paragraph are included on all such copies and derivative works. However, this

document itself may not be modified in any way, such as by removing the copyright notice or references to the Internet Society or other Internet organizations, except as needed for the purpose of developing Internet standards in which case the procedures for copyrights defined in the Internet Standards process must be

Mar 10 13:59 2000 New Option Review and Option Namespace Carney Page 13

followed, or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by the Internet Society or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

8. References

[1] Droms, R. "Dynamic Host Configuration Protocol", [RFC 2131](#), Bucknell University, March 1997.
<<ftp://ds.internic.net/rfc/rfc2131.txt>>

[2] Alexander, S. and Droms, R., "DHCP Options and BOOTP Vendor Extension", [RFC 2132](#), March 1997.
<<ftp://ds.internic.net/rfc/rfc2132.txt>>

[3] Prindeville, P. "BOOTP Vendor Information Extensions", [RFC 1048](#), McGill University, February 1988.
<<ftp://ds.internic.net/rfc/rfc1048.txt>>

[4] Droms, R. "Procedure for Defining New DHCP Options", INTERNET-DRAFT, August 1998
<<ftp://www.ietf.org/internet-drafts/draft-ietf-dhc-new-options-02.txt>>

[5] Bradner, "Key words for use in RFCs to Indicate Requirement Levels", [RFC 2119](#), Harvard University, March 1997.
<<ftp://ds.internic.net/rfc/rfc2119.txt>>

[6] Hinden R. and Deering, S., "IP Version 6 Addressing Architecture", [RFC 2373](#), Nokia and Cisco Systems, July 1998.
<<ftp://ds.internic.net/rfc/rfc2373.txt>>

[7] Guttman E., Perkins C., Veizades J., and Day M., "Service Location Protocol, Version 2", April 1999.

<<ftp://www.ietf.org/internet-drafts/draft-ietf-svrloc-protocol-v2-16.txt>>

9. Author's Address

Michael Carney
Sun Microsystems, Inc.
901 San Antonio Road
Palo Alto, CA 94303-4900

Phone: (650) 786-4171
Fax: (650) 786-5896
Email: Michael.Carney@sun.com

10. Expiration

Mar 10 13:59 2000 New Option Review and Option Namespace Carney Page 14

This document will expire on September 30, 2000.