

Network Working Group  
INTERNET DRAFT

Obsoletes: [draft-ietf-dhc-options-1533update-00.txt](#)

S. Alexander  
Lachman Technology, Inc.

R. Droms  
Bucknell University  
September 1995  
Expires March 1996

DHCP Options and BOOTP Vendor Extensions  
<[draft-ietf-dhc-options-1533update-01.txt](#)>

#### Status of this memo

This document is an Internet-Draft. Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as ``work in progress.''

To learn the current status of any Internet-Draft, please check the ``1id-abstracts.txt' listing contained in the Internet-Drafts Shadow Directories on ftp.is.co.za (Africa), nic.nordu.net (Europe), munnari.oz.au (Pacific Rim), ds.internic.net (US East Coast), or ftp.isi.edu (US West Coast).

#### Abstract

The Dynamic Host Configuration Protocol (DHCP) [1] provides a framework for passing configuration information to hosts on a TCP/IP network. Configuration parameters and other control information are carried in tagged data items that are stored in the 'options' field of the DHCP message. The data items themselves are also called "options."

This document specifies the current set of DHCP options. This document will be periodically updated as new options are defined.

Each superseding document will include the entire current list of valid options. The current list of valid options is also available in <ftp://ftp.isi.edu/in-notes/iana/assignments> [22].

All of the vendor information extensions defined in [RFC 1497](#) [2] may be used as DHCP options. The definitions given in [RFC 1497](#) are included in this document, which supersedes [RFC 1497](#). All of the DHCP options defined in this document, except for those specific to

---

DRAFT                      DHCP Options and BOOTP Vendor Extensions    September 1995

DHCP as defined in [section 9](#), may be used as BOOTP vendor information extensions.

## Table of Contents

<a href="#">1.</a>	Introduction .....	<a href="#">2</a>
<a href="#">2.</a>	BOOTP Extension/DHCP Option Field Format .....	<a href="#">2</a>
<a href="#">3.</a>	<a href="#">RFC 1497</a> Vendor Extensions .....	<a href="#">3</a>
<a href="#">4.</a>	IP Layer Parameters per Host .....	<a href="#">10</a>
<a href="#">5.</a>	IP Layer Parameters per Interface .....	<a href="#">13</a>
<a href="#">6.</a>	Link Layer Parameters per Interface .....	<a href="#">16</a>
<a href="#">7.</a>	TCP Parameters .....	<a href="#">17</a>
<a href="#">8.</a>	Application and Service Parameters .....	<a href="#">18</a>
<a href="#">9.</a>	DHCP Extensions .....	<a href="#">26</a>
<a href="#">10.</a>	Extensions .....	<a href="#">33</a>
<a href="#">11.</a>	Acknowledgements .....	<a href="#">33</a>
<a href="#">12.</a>	References .....	<a href="#">33</a>
<a href="#">13.</a>	Security Considerations .....	<a href="#">35</a>
<a href="#">14.</a>	Authors' Addresses .....	<a href="#">35</a>
<a href="#">A.</a>	Changes to <a href="#">draft-ietf-dhc-options-1533update-00.txt</a> .....	<a href="#">36</a>

## [1.](#) Introduction

This document specifies options for use with both the Dynamic Host Configuration Protocol and the Bootstrap Protocol.

The full description of DHCP packet formats may be found in the DHCP specification document [[1](#)], and the full description of BOOTP packet formats may be found in the BOOTP specification document [[3](#)]. This document defines the format of information in the last field of DHCP packets ('options') and of BOOTP packets ('vend'). The remainder of this section defines a generalized use of this area for giving information useful to a wide class of machines, operating systems and configurations. Sites with a single DHCP or BOOTP server that is shared among heterogeneous clients may choose to define other, site-specific formats for the use of the 'options' field.

[Section 2](#) of this memo describes the formats of DHCP options and BOOTP vendor extensions. [Section 3](#) describes options defined in previous documents for use with BOOTP (all may also be used with DHCP). Sections [4-8](#) define new options intended for use with both DHCP and BOOTP. [Section 9](#) defines options used only in DHCP.

References further describing most of the options defined in sections 2-6 can be found in [section 12](#). The use of the options defined in [section 9](#) is described in the DHCP specification [1].

Information on registering new options is contained in [section 10](#).

## [2](#). BOOTP Extension/DHCP Option Field Format

DHCP options have the same format as the BOOTP 'vendor extensions' defined in [RFC 1497](#) [2]. Options may be fixed length or variable length. All options begin with a tag octet, which uniquely identifies the option. Fixed-length options without data consist of only a tag octet. Only options 0 and 255 are fixed length. All other options are variable-length with a length octet following the tag octet. The value of the length octet does not include the two octets specifying the tag and length. The length octet is followed by "length" octets of data. Options containing NVT ASCII data SHOULD NOT include a trailing NULL; however, the receiver of such options MUST be prepared to delete trailing nulls if they exist. The receiver MUST NOT require that a trailing null be included in the data. In the case of some variable-length options the length field is a constant but must still be specified.

Any options defined subsequent to this document should contain a length octet even if the length is fixed or zero.

All multi-octet quantities are in network byte-order.

When used with BOOTP, the first four octets of the vendor information field have been assigned to the "magic cookie" (as suggested in [RFC 951](#)). This field identifies the mode in which the succeeding data is to be interpreted. The value of the magic cookie is the 4 octet dotted decimal 99.130.83.99 (or hexadecimal number 63.82.53.63) in network byte order.

All of the "vendor extensions" defined in [RFC 1497](#) are also DHCP options.

Option codes 128 to 254 (decimal) are reserved for site-specific options.

Except for the options in [section 9](#), all options may be used with

either DHCP or BOOTP.

Many of these options have their default values specified in other documents. In particular, [RFC 1122](#) [4] specifies default values for most IP and TCP configuration parameters.

### 3. [RFC 1497](#) Vendor Extensions

This section lists the vendor extensions as defined in [RFC 1497](#). They are defined here for completeness.

#### [3.1.](#) Pad Option

The pad option can be used to cause subsequent fields to align on word boundaries.

The code for the pad option is 0, and its length is 1 octet.

```
Code
+-----+
|  0  |
+-----+
```

#### [3.2.](#) End Option

The end option marks the end of valid information in the vendor field. Subsequent octets should be filled with pad options.

The code for the end option is 255, and its length is 1 octet.

```
Code
+-----+
| 255 |
+-----+
```

#### [3.3.](#) Subnet Mask

The subnet mask option specifies the client's subnet mask as per [RFC 950](#) [5].

If both the subnet mask and the router option are specified in a DHCP reply, the subnet mask option MUST be first.

The code for the subnet mask option is 1, and its length is 4 octets.

Code	Len	Subnet Mask			
1	4	m1	m2	m3	m4

### [3.4.](#) Time Offset

The time offset field specifies the offset of the client's subnet in seconds from Coordinated Universal Time (UTC). The offset is expressed as a signed 32-bit integer.

The code for the time offset option is 2, and its length is 4 octets.

Code	Len	Time Offset			
2	4	n1	n2	n3	n4

### [3.5.](#) Router Option

The router option specifies a list of IP addresses for routers on the client's subnet. Routers SHOULD be listed in order of preference.

The code for the router option is 3. The minimum length for the router option is 4 octets, and the length MUST always be a multiple of 4.

Code	Len	Address 1				Address 2	
3	n	a1	a2	a3	a4	a1	a2   ...

### 3.6. Time Server Option

The time server option specifies a list of [RFC 868](#) [6] time servers available to the client. Servers SHOULD be listed in order of preference.

The code for the time server option is 4. The minimum length for this option is 4 octets, and the length MUST always be a multiple of 4.

Code	Len	Address 1				Address 2	
4	n	a1	a2	a3	a4	a1	a2   ...

### 3.7. Name Server Option

The name server option specifies a list of IEN 116 [7] name servers available to the client. Servers SHOULD be listed in order of preference.

The code for the name server option is 5. The minimum length for this option is 4 octets, and the length MUST always be a multiple of 4.

Code	Len	Address 1				Address 2	
5	n	a1	a2	a3	a4	a1	a2   ...

### 3.8. Domain Name Server Option

The domain name server option specifies a list of Domain Name System (STD 13, [RFC 1035](#) [8]) name servers available to the client. Servers SHOULD be listed in order of preference.

The code for the domain name server option is 6. The minimum length for this option is 4 octets, and the length MUST always be a multiple of 4.

Code	Len	Address 1				Address 2		
6	n	a1	a2	a3	a4	a1	a2	...

### 3.9. Log Server Option

The log server option specifies a list of MIT-LCS UDP log servers available to the client. Servers SHOULD be listed in order of preference.

The code for the log server option is 7. The minimum length for this option is 4 octets, and the length MUST always be a multiple of 4.

Code	Len	Address 1				Address 2		
7	n	a1	a2	a3	a4	a1	a2	...

### 3.10. Cookie Server Option

The cookie server option specifies a list of [RFC 865](#) [9] cookie servers available to the client. Servers SHOULD be listed in order of preference.

The code for the log server option is 8. The minimum length for this option is 4 octets, and the length MUST always be a multiple of 4.

Code	Len	Address 1				Address 2	
8	n	a1	a2	a3	a4	a1	a2   ...

### 3.11. LPR Server Option

The LPR server option specifies a list of [RFC 1179](#) [10] line printer servers available to the client. Servers SHOULD be listed in order of preference.

The code for the LPR server option is 9. The minimum length for this option is 4 octets, and the length MUST always be a multiple of 4.

Code	Len	Address 1				Address 2	
9	n	a1	a2	a3	a4	a1	a2   ...

### 3.12. Impress Server Option

The Impress server option specifies a list of Imagen Impress servers available to the client. Servers SHOULD be listed in order of preference.

The code for the Impress server option is 10. The minimum length for this option is 4 octets, and the length MUST always be a multiple of 4.

Code	Len	Address 1				Address 2	
10	n	a1	a2	a3	a4	a1	a2   ...

### 3.13. Resource Location Server Option



This option specifies a list of [RFC 887 \[11\]](#) Resource Location servers available to the client. Servers SHOULD be listed in order of preference.

The code for this option is 11. The minimum length for this option is 4 octets, and the length MUST always be a multiple of 4.

Code	Len	Address 1				Address 2	
11	n	a1	a2	a3	a4	a1	a2   ...

### [3.14.](#) Host Name Option

This option specifies the name of the client. The name may or may not be qualified with the local domain name (see [section 3.17](#) for the preferred way to retrieve the domain name). See [RFC 1035](#) for character set restrictions.

The code for this option is 12, and its minimum length is 1.

Code	Len	Host Name					
12	n	h1	h2	h3	h4	h5	h6   ...

### [3.15.](#) Boot File Size Option

This option specifies the length in 512-octet blocks of the default boot image for the client. The file length is specified as an unsigned 16-bit integer.

The code for this option is 13, and its length is 2.

Code	Len	File Size	
13	2	l1	l2

### 3.16. Merit Dump File

This option specifies the path-name of a file to which the client's core image should be dumped in the event the client crashes. The path is formatted as a character string consisting of characters from the NVT ASCII character set.

The code for this option is 14. Its minimum length is 1.

Code	Len	Dump File Pathname			
14	n	n1	n2	n3	n4   ...

### 3.17. Domain Name

This option specifies the domain name that client should use when resolving hostnames via the Domain Name System.

The code for this option is 15. Its minimum length is 1.

Code	Len	Domain Name			
15	n	d1	d2	d3	d4   ...

### 3.18. Swap Server

This specifies the IP address of the client's swap server.

The code for this option is 16 and its length is 4.

Code	Len	Swap Server Address			
16	n	a1	a2	a3	a4

---

DRAFT                      DHCP Options and BOOTP Vendor Extensions    September 1995

### [3.19.](#) Root Path

This option specifies the path-name that contains the client's root disk. The path is formatted as a character string consisting of characters from the NVT ASCII character set.

The code for this option is 17. Its minimum length is 1.

Code	Len	Root Disk Pathname			
17	n	n1	n2	n3	n4   ...

### [3.20.](#) Extensions Path

A string to specify a file, retrievable via TFTP, which contains information which can be interpreted in the same way as the 64-octet vendor-extension field within the BOOTP response, with the following exceptions:

- the length of the file is unconstrained;
- all references to Tag 18 (i.e., instances of the BOOTP Extensions Path field) within the file are ignored.

The code for this option is 18. Its minimum length is 1.

Code	Len	Extensions Pathname			
18	n	n1	n2	n3	n4   ...

## [4.](#) IP Layer Parameters per Host

This section details the options that affect the operation of the IP layer on a per-host basis.

### [4.1.](#) IP Forwarding Enable/Disable Option

This option specifies whether the client should configure its IP layer for packet forwarding. A value of 0 means disable IP forwarding, and a value of 1 means enable IP forwarding.

The code for this option is 19, and its length is 1.

Code	Len	Value
19	1	0/1

+-----+-----+-----+

#### [4.2.](#) Non-Local Source Routing Enable/Disable Option

This option specifies whether the client should configure its IP layer to allow forwarding of datagrams with non-local source routes (see Section 3.3.5 of [4] for a discussion of this topic). A value of 0 means disallow forwarding of such datagrams, and a value of 1 means allow forwarding.

The code for this option is 20, and its length is 1.

Code	Len	Value
20	1	0/1

#### [4.3.](#) Policy Filter Option


This option specifies policy filters for non-local source routing. The filters consist of a list of IP addresses and masks which specify destination/mask pairs with which to filter incoming source routes.

Any source routed datagram whose next-hop address does not match one of the filters should be discarded by the client.

See [4] for further information.

The code for this option is 21. The minimum length of this option is 8, and the length MUST be a multiple of 8.


Code	Len	Address 1	Mask 1
------	-----	-----------	--------



[4.4.](#) Maximum Datagram Reassembly Size

This option specifies the maximum size datagram that the client should be prepared to reassemble. The size is specified as a 16-bit unsigned integer. The minimum value legal value is 576.


The code for this option is 22, and its length is 2.



[4.5.](#) Default IP Time-to-live

This option specifies the default time-to-live that the client should use on outgoing datagrams. The TTL is specified as an octet with a value between 1 and 255.

The code for this option is 23, and its length is 1.



#### 4.6. Path MTU Aging Timeout Option

This option specifies the timeout (in seconds) to use when aging Path MTU values discovered by the mechanism defined in [RFC 1191](#) [12]. The timeout is specified as a 32-bit unsigned integer.

The code for this option is 24, and its length is 4.

Code	Len	Timeout			
24	4	t1	t2	t3	t4

#### 4.7. Path MTU Plateau Table Option

This option specifies a table of MTU sizes to use when performing Path MTU Discovery as defined in [RFC 1191](#). The table is formatted as a list of 16-bit unsigned integers, ordered from smallest to largest. The minimum MTU value cannot be smaller than 68.

The code for this option is 25. Its minimum length is 2, and the length MUST be a multiple of 2.

Code	Len	Size 1		Size 2	
25	n	s1	s2	s1	s2   ...

### 5. IP Layer Parameters per Interface

This section details the options that affect the operation of the IP

layer on a per-interface basis. It is expected that a client can issue multiple requests, one per interface, in order to configure interfaces with their specific parameters.

### 5.1. Interface MTU Option

This option specifies the MTU to use on this interface. The MTU is specified as a 16-bit unsigned integer. The minimum legal value for the MTU is 68.

The code for this option is 26, and its length is 2.

Code	Len	MTU
26	2	m1   m2

### 5.2. All Subnets are Local Option

This option specifies whether or not the client may assume that all subnets of the IP network to which the client is connected use the same MTU as the subnet of that network to which the client is directly connected. A value of 1 indicates that all subnets share the same MTU. A value of 0 means that the client should assume that some subnets of the directly connected network may have smaller MTUs.

The code for this option is 27, and its length is 1.

Code	Len	Value
27	1	0/1

### 5.3. Broadcast Address Option

This option specifies the broadcast address in use on the client's subnet. Legal values for broadcast addresses are specified in section 3.2.1.3 of [4].

The code for this option is 28, and its length is 4.

Code	Len	Broadcast Address
28	4	b1   b2   b3   b4

### 5.4. Perform Mask Discovery Option

This option specifies whether or not the client should perform subnet mask discovery using ICMP. A value of 0 indicates that the client should not perform mask discovery. A value of 1 means that the client should perform mask discovery.

The code for this option is 29, and its length is 1.

Code	Len	Value
29	1	0/1

### 5.5. Mask Supplier Option

This option specifies whether or not the client should respond to subnet mask requests using ICMP. A value of 0 indicates that the



client should not respond. A value of 1 means that the client should respond.

The code for this option is 30, and its length is 1.

Code	Len	Value
30	1	0/1

#### [5.6.](#) Perform Router Discovery Option

This option specifies whether or not the client should solicit routers using the Router Discovery mechanism defined in [RFC 1256](#) [13]. A value of 0 indicates that the client should not perform router discovery. A value of 1 means that the client should perform router discovery.

The code for this option is 31, and its length is 1.

Code	Len	Value
31	1	0/1

#### [5.7.](#) Router Solicitation Address Option

This option specifies the address to which the client should transmit router solicitation requests.

The code for this option is 32, and its length is 4.

Code	Len	Address			
32	4	a1	a2	a3	a4

### 5.8. Static Route Option

This option specifies a list of static routes that the client should install in its routing cache. If multiple routes to the same destination are specified, they are listed in descending order of priority.

The routes consist of a list of IP address pairs. The first address is the destination address, and the second address is the router for the destination.

The default route (0.0.0.0) is an illegal destination for a static route. See [section 3.5](#) for information about the router option.

The code for this option is 33. The minimum length of this option is 8, and the length MUST be a multiple of 8.

Code	Len	Destination 1				Router 1			
33	n	d1	d2	d3	d4	r1	r2	r3	r4
		Destination 2				Router 2			
		d1	d2	d3	d4	r1	r2	r3	r4   ...

## 6. Link Layer Parameters per Interface

This section lists the options that affect the operation of the data link layer on a per-interface basis.

### 6.1. Trailer Encapsulation Option

This option specifies whether or not the client should negotiate the use of trailers ([RFC 893](#) [[14](#)]) when using the ARP protocol. A value of 0 indicates that the client should not attempt to use trailers. A value of 1 means that the client should attempt to use trailers.

The code for this option is 34, and its length is 1.

Code	Len	Value
34	1	0/1

---

DRAFT                      DHCP Options and BOOTP Vendor Extensions    September 1995

### [6.2.](#) ARP Cache Timeout Option

This option specifies the timeout in seconds for ARP cache entries. The time is specified as a 32-bit unsigned integer.

The code for this option is 35, and its length is 4.

Code	Len	Time			
35	4	t1	t2	t3	t4

### [6.3.](#) Ethernet Encapsulation Option

This option specifies whether or not the client should use Ethernet Version 2 ([RFC 894](#) [[15](#)]) or IEEE 802.3 ([RFC 1042](#) [[16](#)]) encapsulation if the interface is an Ethernet. A value of 0 indicates that the client should use [RFC 894](#) encapsulation. A value of 1 means that the client should use [RFC 1042](#) encapsulation.

The code for this option is 36, and its length is 1.

Code	Len	Value
36	1	0/1

## [7.](#) TCP Parameters

This section lists the options that affect the operation of the TCP layer on a per-interface basis.

### [7.1.](#) TCP Default TTL Option

This option specifies the default TTL that the client should use when sending TCP segments. The value is represented as an 8-bit unsigned integer. The minimum value is 1.

The code for this option is 37, and its length is 1.

Code	Len	TTL
37	1	n

### 7.2. TCP Keepalive Interval Option

This option specifies the interval (in seconds) that the client TCP should wait before sending a keepalive message on a TCP connection. The time is specified as a 32-bit unsigned integer. A value of zero indicates that the client should not generate keepalive messages on connections unless specifically requested by an application.

The code for this option is 38, and its length is 4.

Code	Len	Time			
38	4	t1	t2	t3	t4

### 7.3. TCP Keepalive Garbage Option

This option specifies the whether or not the client should send TCP keepalive messages with a octet of garbage for compatibility with older implementations. A value of 0 indicates that a garbage octet should not be sent. A value of 1 indicates that a garbage octet should be sent.

The code for this option is 39, and its length is 1.

Code	Len	Value
39	1	0/1

## 8. Application and Service Parameters

This section details some miscellaneous options used to configure

miscellaneous applications and services.

### 8.1. Network Information Service Domain Option

This option specifies the name of the client's NIS [17] domain. The domain is formatted as a character string consisting of characters from the NVT ASCII character set.

The code for this option is 40. Its minimum length is 1.

Code	Len	NIS Domain Name				
40	n	n1	n2	n3	n4   ...	

### 8.2. Network Information Servers Option

This option specifies a list of IP addresses indicating NIS servers available to the client. Servers SHOULD be listed in order of preference.

The code for this option is 41. Its minimum length is 4, and the length MUST be a multiple of 4.

Code	Len	Address 1				Address 2	
41	n	a1	a2	a3	a4	a1	a2   ...

### 8.3. Network Time Protocol Servers Option

This option specifies a list of IP addresses indicating NTP [18] servers available to the client. Servers SHOULD be listed in order of preference.

The code for this option is 42. Its minimum length is 4, and the length MUST be a multiple of 4.

Code	Len	Address 1				Address 2	
42	n	a1	a2	a3	a4	a1	a2   ...



When encapsulated vendor-specific extensions are used, the information bytes 1-n have the following format:

Code	Len	Data item	Code	Len	Data item	Code
T1	n	d1   d2   ...	T2	n	D1   D2   ...	...

### 8.5. NetBIOS over TCP/IP Name Server Option

The NetBIOS name server (NBNS) option specifies a list of [RFC 1001/1002](#) [19] [20] NBNS name servers listed in order of preference.

The code for this option is 44. The minimum length of the option is 4 octets, and the length must always be a multiple of 4.

Code	Len	Address 1	Address 2
44	n	a1   a2   a3   a4	b1   b2   b3   b4   ...

### 8.6. NetBIOS over TCP/IP Datagram Distribution Server Option

The NetBIOS datagram distribution server (NBDD) option specifies a list of [RFC 1001/1002](#) NBDD servers listed in order of preference. The code for this option is 45. The minimum length of the option is 4 octets, and the length must always be a multiple of 4.

Code	Len	Address 1	Address 2
45	n	a1   a2   a3   a4	b1   b2   b3   b4   ...

### 8.7. NetBIOS over TCP/IP Node Type Option

The NetBIOS node type option allows NetBIOS over TCP/IP clients which are configurable to be configured as described in [RFC 1001/1002](#). The value is specified as a single octet which identifies the client type as follows:

Value	Node Type
-----	-----
0x1	B-node
0x2	P-node
0x4	M-node
0x8	H-node

In the above chart, the notation '0x' indicates a number in base-16 (hexadecimal).

The code for this option is 46. The length of this option is always 1.

Code	Len	Node Type
-----	-----	-----
46	1	see above
-----	-----	-----

### 8.8. NetBIOS over TCP/IP Scope Option

The NetBIOS scope option specifies the NetBIOS over TCP/IP scope parameter for the client as specified in [RFC 1001/1002](#). See [\[19\]](#), [\[20\]](#), and [\[8\]](#) for character-set restrictions.



The code for this option is 47. The minimum length of this option is 1.

Code	Len	NetBIOS Scope				
47	n	s1	s2	s3	s4	...

### 8.9. X Window System Font Server Option

This option specifies a list of X Window System [21] Font servers available to the client. Servers SHOULD be listed in order of preference.

The code for this option is 48. The minimum length of this option is 4 octets, and the length MUST be a multiple of 4.

Code	Len	Address 1				Address 2		
48	n	a1	a2	a3	a4	a1	a2	...

### 8.10. X Window System Display Manager Option

This option specifies a list of IP addresses of systems that are running the X Window System Display Manager and are available to the client.

Addresses SHOULD be listed in order of preference.

The code for the this option is 49. The minimum length of this option is 4, and the length MUST be a multiple of 4.

Code	Len	Address 1				Address 2		
49	n	a1	a2	a3	a4	a1	a2	...

### 8.11. Network Information Service+ Domain Option

This option specifies the name of the client's NIS+ [17] domain. The domain is formatted as a character string consisting of characters from the NVT ASCII character set.

The code for this option is 64. Its minimum length is 1.

Code	Len	NIS Client Domain Name				
64	n	n1	n2	n3	n4   ...	

### 8.12. Network Information Service+ Servers Option

This option specifies a list of IP addresses indicating NIS+ servers available to the client. Servers SHOULD be listed in order of preference.

The code for this option is 65. Its minimum length is 4, and the length MUST be a multiple of 4.

Code	Len	Address 1				Address 2	
65	n	a1	a2	a3	a4	a1	a2   ...

### 8.13. Mobile IP Home Agent option

This option specifies a list of IP addresses indicating mobile IP home agents available to the client. Agents SHOULD be listed in order of preference.

The code for this option is 68. Its minimum length is 0 (indicating no home agents are available) and the length MUST be a multiple of 4. It is expected that the usual length will be four octets, containing a single home agent's address.

Code	Len	Home Agent Addresses (zero or more)			
68	n	a1	a2	a3	a4   ...

---

DRAFT                      DHCP Options and BOOTP Vendor Extensions    September 1995

#### [8.14.](#) Simple Mail Transport Protocol (SMTP) Server Option

The SMTP server option specifies a list of SMTP servers available to the client. Servers SHOULD be listed in order of preference.

The code for the SMTP server option is 69. The minimum length for this option is 4 octets, and the length MUST always be a multiple of 4.

Code	Len	Address 1				Address 2		
69	n	a1	a2	a3	a4	a1	a2	...

#### [8.15.](#) Post Office Protocol (POP3) Server Option

The POP3 server option specifies a list of POP3 available to the client. Servers SHOULD be listed in order of preference.

The code for the POP3 server option is 70. The minimum length for this option is 4 octets, and the length MUST always be a multiple of 4.

Code	Len	Address 1				Address 2		
70	n	a1	a2	a3	a4	a1	a2	...

#### [8.16.](#) Network News Transport Protocol (NNTP) Server Option

The NNTP server option specifies a list of NNTP available to the client. Servers SHOULD be listed in order of preference.

The code for the NNTP server option is 71. The minimum length for this option is 4 octets, and the length MUST always be a multiple of 4.

Code	Len	Address 1				Address 2		
71	n	a1	a2	a3	a4	a1	a2	...

---

DRAFT                      DHCP Options and BOOTP Vendor Extensions    September 1995

### [8.17.](#) Default World Wide Web (WWW) Server Option

The WWW server option specifies a list of WWW available to the client. Servers SHOULD be listed in order of preference.

The code for the WWW server option is 72. The minimum length for this option is 4 octets, and the length MUST always be a multiple of 4.

Code	Len	Address 1				Address 2	
72	n	a1	a2	a3	a4	a1	a2   ...

### [8.18.](#) Default Finger Server Option

The Finger server option specifies a list of Finger available to the client. Servers SHOULD be listed in order of preference.

The code for the Finger server option is 73. The minimum length for this option is 4 octets, and the length MUST always be a multiple of 4.

Code	Len	Address 1				Address 2	
73	n	a1	a2	a3	a4	a1	a2   ...

### [8.19.](#) Default Internet Relay Chat (IRC) Server Option

The IRC server option specifies a list of IRC available to the client. Servers SHOULD be listed in order of preference.

The code for the IRC server option is 74. The minimum length for this option is 4 octets, and the length MUST always be a multiple of

4.

Code	Len	Address 1				Address 2		
74	n	a1	a2	a3	a4	a1	a2	...

#### [8.20](#). StreetTalk Server Option

The StreetTalk server option specifies a list of StreetTalk servers available to the client. Servers SHOULD be listed in order of preference.

The code for the StreetTalk server option is 75. The minimum length for this option is 4 octets, and the length MUST always be a multiple of 4.

Code	Len	Address 1				Address 2		
75	n	a1	a2	a3	a4	a1	a2	...

#### [8.21](#). StreetTalk Directory Assistance (STDA) Server Option

The StreetTalk Directory Assistance (STDA) server option specifies a list of STDA servers available to the client. Servers SHOULD be listed in order of preference.

The code for the StreetTalk Directory Assistance server option is 76. The minimum length for this option is 4 octets, and the length MUST always be a multiple of 4.

Code	Len	Address 1				Address 2		
76	n	a1	a2	a3	a4	a1	a2	...

+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----

## 9. DHCP Extensions

This section details the options that are specific to DHCP.

### 9.1. Requested IP Address

This option is used in a client request (DHCPDISCOVER) to allow the client to request that a particular IP address be assigned.

The code for this option is 50, and its length is 4.

Code	Len	Address			
50	4	a1	a2	a3	a4

### 9.2. IP Address Lease Time

This option is used in a client request (DHCPDISCOVER or DHCPREQUEST) to allow the client to request a lease time for the IP address. In a server reply (DHCPOFFER), a DHCP server uses this option to specify the lease time it is willing to offer.

The time is in units of seconds, and is specified as a 32-bit unsigned integer.

The code for this option is 51, and its length is 4.

Code	Len	Lease Time			
51	4	t1	t2	t3	t4

### 9.3. Option Overload

This option is used to indicate that the DHCP 'sname' or 'file' fields are being overloaded by using them to carry DHCP options. A

DHCP server inserts this option if the returned parameters will exceed the usual space allotted for options.

If this option is present, the client interprets the specified additional fields after it concludes interpretation of the standard option fields.

The code for this option is 52, and its length is 1. Legal values for this option are:

Value	Meaning
1	the 'file' field is used to hold options
2	the 'sname' field is used to hold options
3	both fields are used to hold options

Code	Len	Value
52	1	1/2/3

#### [9.4](#) TFTP server name

This option is used to identify a TFTP server when the 'sname' field in the DHCP header has been used for DHCP options.

The code for this option is 66, and its minimum length is 1.

Code	Len	TFTP server			
66	n	c1	c2	c3	...

#### [9.5](#) Bootfile name

This option is used to identify a bootfile when the 'file' field in the DHCP header has been used for DHCP options.

The code for this option is 67, and its minimum length is 1.

Code	Len	Bootfile name
-----	-----	-----

```

| 67 | n | c1 | c2 | c3 | ...
+-----+-----+-----+-----+-----+

```

## 9.6. DHCP Message Type

This option is used to convey the type of the DHCP message. The code for this option is 53, and its length is 1. Legal values for this option are:

Value	Message Type
-----	-----
1	DHCPDISCOVER
2	DHCPOFFER
3	DHCPREQUEST
4	DHCPDECLINE
5	DHCPACK
6	DHCPNAK
7	DHCPRELEASE
8	DHCPINFORM

```

Code  Len  Type
+-----+-----+-----+
| 53 | 1 | 1-9 |
+-----+-----+-----+

```

## 9.7. Server Identifier

This option is used in DHCPOFFER and DHCPREQUEST messages, and may optionally be included in the DHCPACK and DHCPNAK messages. DHCP servers include this option in the DHCPOFFER in order to allow the client to distinguish between lease offers. DHCP clients indicate which of several lease offers is being accepted by including this



option in a DHCPREQUEST message.

The identifier is the IP address of the selected server.

The code for this option is 54, and its length is 4.

Code	Len	Address			
54	4	a1	a2	a3	a4

### 9.8. Parameter Request List

This option is used by a DHCP client to request values for specified configuration parameters. The list of requested parameters is specified as *n* octets, where each octet is a valid DHCP option code as defined in this document.

The client MAY list the options in order of preference. The DHCP server is not required to return the options in the requested order, but MUST try to insert the requested options in the order requested by the client.

The code for this option is 55. Its minimum length is 1.

Code	Len	Option Codes		
55	n	c1	c2	...

### [9.9. Message](#)

This option is used by a DHCP server to provide an error message to a DHCP client in a DHCPNAK message in the event of a failure. A client may use this option in a DHCPDECLINE message to indicate the why the client declined the offered parameters. The message consists of n octets of NVT ASCII text, which the client may display on an available output device.

The code for this option is 56 and its minimum length is 1.

Code	Len	Text
56	n	c1   c2   ...

### [9.10. Maximum DHCP Message Size](#)

This option specifies the maximum length DHCP message that it is willing to accept. The length is specified as an unsigned 16-bit integer. A client may use the maximum DHCP message size option in DHCPDISCOVER or DHCPREQUEST messages, but should not use the option in DHCPDECLINE messages.

The code for this option is 57, and its length is 2. The minimum legal value is 576 octets.

Code	Len	Length
57	2	l1   l2

### [9.11. Renewal \(T1\) Time Value](#)

This option specifies the time interval from address assignment until the client transitions to the RENEWING state.

The value is in units of seconds, and is specified as a 32-bit unsigned integer.

The code for this option is 58, and its length is 4.

Code	Len	T1 Interval
58	4	t1   t2   t3   t4

---

DRAFT                      DHCP Options and BOOTP Vendor Extensions    September 1995

### [9.12.](#) Rebinding (T2) Time Value

This option specifies the time interval from address assignment until the client transitions to the REBINDING state.

The value is in units of seconds, and is specified as a 32-bit unsigned integer.

The code for this option is 59, and its length is 4.

Code	Len	T2 Interval			
59	4	t1	t2	t3	t4

### [9.13.](#) Vendor class identifier

This option is used by DHCP clients to optionally identify the vendor type and configuration of a DHCP client. The information is a string of *n* octets, interpreted by servers. Vendors may choose to define specific vendor class identifiers to convey particular configuration or other identification information about a client. For example, the identifier may encode the client's hardware configuration. Servers not equipped to interpret the class-specific information sent by a client **MUST** ignore it (although it may be reported). Servers that respond **SHOULD** only use option 43 to return the vendor-specific information to the client.

The code for this option is 60, and its minimum length is 1.

Code	Len	Vendor class Identifier		
60	<i>n</i>	i1	i2	...

---

DRAFT                      DHCP Options and BOOTP Vendor Extensions    September 1995

#### [9.14.](#) Client-identifier

This option is used by DHCP clients to specify their unique identifier. DHCP servers use this value to index their database of address bindings. This value is expected to be unique for all clients in an administrative domain.

Identifiers SHOULD be treated as opaque objects by DHCP servers.

The client identifier MAY consist of type-value pairs similar to the 'htype'/'chaddr' fields defined in [3]. For instance, it MAY consist of a hardware type and hardware address. In this case the type field SHOULD be one of the ARP hardware types defined in STD2 [22]. A hardware type of 0 (zero) should be used when the value field contains an identifier other than a hardware address (e.g. a fully qualified domain name).

The code for this option is 61, and its minimum length is 2.

```
Code   Len   Type   Client-Identifier
+-----+-----+-----+-----+-----+
| 61 | n | t1 | i1 | i2 | ...
+-----+-----+-----+-----+-----+
```

#### [9.15.](#) User Class Information

This option is used by a DHCP client to optionally identify the type or category of user or applications it represents. The information contained in this option is an NVT ASCII text object that represents the user class of which the client is a member.

DHCP administrators may define specific user class identifiers to convey information about a client's software configuration or about its user's preferences. For example, an identifier may specify that a particular DHCP client is a member of the class "accounting auditors", which have special service needs such as a particular

database server.

Servers not equipped to interpret any of user classes specified by a client MUST ignore it (although it may be reported). Otherwise, servers SHOULD respond with the set of options corresponding to the user class specified by the client. Further, if the server responds, it MUST return this option to the client.

Clients which do not receive information for the user class requested SHOULD make an attempt to operate without it, although they may do so (and may announce they are doing so) in a degraded mode.

The code for this option is 77. The minimum length for this option is two.

```
Code   Len   text1
+-----+-----+-----+-----+-----
| 77   |  N   |  c1  |  c2  |  ...
+-----+-----+-----+-----+-----
```

## 10. Extensions

Additional generic data fields may be registered by contacting:

Internet Assigned Numbers Authority (IANA)  
USC/Information Sciences Institute  
4676 Admiralty Way  
Marina del Rey, California 90292-6695

or by email as: [iana@isi.edu](mailto:iana@isi.edu)

Implementation specific use of undefined generic types (those in the range 61-127) may conflict with other implementations, and registration is required.

## 11. Acknowledgements

The authors would like to thank Philip Almquist for his feedback on this document. The comments of the DHCP Working Group are also gratefully acknowledged. In particular, Mike Carney and Jon Dreyer

from SunSelect suggested the current format of the Vendor-specific Information option.

[RFC 1497](#) is based on earlier work by Philip Prindeville, with help from Drew Perkins, Bill Croft, and Steve Deering.

## [12.](#) References

- [1] Droms, R., "Dynamic Host Configuration Protocol", [RFC 1531](#), Bucknell University, October 1993.
- [2] Reynolds, J., "BOOTP Vendor Information Extensions", [RFC 1497](#), USC/Information Sciences Institute, August 1993.
- [3] Croft, W., and J. Gilmore, "Bootstrap Protocol", [RFC 951](#), Stanford University and Sun Microsystems, September 1985.
- [4] Braden, R., Editor, "Requirements for Internet Hosts - Communication Layers", STD 3, [RFC 1122](#), USC/Information Sciences

Institute, October 1989.

- [5] Mogul, J., and J. Postel, "Internet Standard Subnetting Procedure", STD 5, [RFC 950](#), USC/Information Sciences Institute, August 1985.
- [6] Postel, J., and K. Harrenstien, "Time Protocol", STD 26, [RFC 868](#), USC/Information Sciences Institute, SRI, May 1983.
- [7] Postel, J., "Name Server", IEN 116, USC/Information Sciences Institute, August 1979.
- [8] Mockapetris, P., "Domain Names - Implementation and Specification", STD 13, [RFC 1035](#), USC/Information Sciences Institute, November 1987.
- [9] Postel, J., "Quote of the Day Protocol", STD 23, [RFC 865](#), USC/Information Sciences Institute, May 1983.
- [10] McLaughlin, L., "Line Printer Daemon Protocol", [RFC 1179](#), The Wollongong Group, August 1990.

- [11] Accetta, M., "Resource Location Protocol", [RFC 887](#), CMU, December 1983.
- [12] Mogul, J. and S. Deering, "Path MTU Discovery", [RFC 1191](#), DECWRL, Stanford University, November 1990.
- [13] Deering, S., "ICMP Router Discovery Messages", [RFC 1256](#), Xerox PARC, September 1991.
- [14] Leffler, S. and M. Karels, "Trailer Encapsulations", [RFC 893](#), U. C. Berkeley, April 1984.
- [15] Hornig, C., "Standard for the Transmission of IP Datagrams over Ethernet Networks", [RFC 894](#), Symbolics, April 1984.
- [16] Postel, J. and J. Reynolds, "Standard for the Transmission of IP Datagrams Over IEEE 802 Networks", [RFC 1042](#), USC/Information Sciences Institute, February 1988.
- [17] Sun Microsystems, "System and Network Administration", March 1990.
- [18] Mills, D., "Internet Time Synchronization: The Network Time Protocol", [RFC 1305](#), UDEL, March 1992.
- [19] NetBIOS Working Group, "Protocol Standard for a NetBIOS Service

---

DRAFT                      DHCP Options and BOOTP Vendor Extensions      September 1995

on a TCP/UDP transport: Concepts and Methods", STD 19, [RFC 1001](#), March 1987.

- [20] NetBIOS Working Group, "Protocol Standard for a NetBIOS Service on a TCP/UDP transport: Detailed Specifications", STD 19, [RFC 1002](#), March 1987.

- [21] Scheifler, R., "FYI On the X Window System", FYI 6, [RFC 1198](#), MIT Laboratory for Computer Science, January 1991.

- [22] Reynolds, J., and J. Postel, "Assigned Numbers", STD 2, [RFC 1700](#), USC/Information Sciences Institute, July 1992.

### 13. Security Considerations

Security issues are not discussed in this memo.

#### 14. Authors' Addresses

Steve Alexander  
Lachman Technology, Inc.  
1901 North Naper Boulevard  
Naperville, IL 60563-8895

Phone: (708) 505-9555 x256  
EMail: stevea@lachman.com

Ralph Droms  
Computer Science Department  
323 Dana Engineering  
Bucknell University  
Lewisburg, PA 17837

Phone: (717) 524-1145  
EMail: droms@bucknell.edu

#### A. Changes to [draft-ietf-dhc-options-1533update-00.txt](#):

- \* [Section 8.4](#) - changed to indicate vendor-specific information is interpreted based on vendor class identifier.
- \* [Section 9.13](#) - changed "Class-identifier" to "Vendor class identifier"



\* Added [section 9.15](#) describing "User class identifier"