

Dynamic Host Configuration (DHC)
Internet-Draft
Updates: [3633](#) (if approved)
Intended status: Standards Track
Expires: July 16, 2011

J. Korhonen, Ed.
Nokia Siemens Networks
T. Savolainen
Nokia
S. Krishnan
Ericsson
O. Troan
Cisco Systems, Inc
January 12, 2011

Prefix Exclude Option for DHCPv6-based Prefix Delegation
draft-ietf-dhc-pd-exclude-01.txt

Abstract

This specification defines an optional mechanism to allow exclusion of one specific prefix from a delegated prefix set when using DHCPv6-based prefix delegation.

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on July 16, 2011.

Copyright Notice

Copyright (c) 2011 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must

Internet-Draft

PD Exclude Option

January 2011

include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	3
2.	Requirements and Terminology	3
3.	Problem Background	3
4.	Solution	3
4.1.	Prefix Delegation with Excluded Prefixes	4
4.2.	Prefix Exclude Option	4
5.	Delegating Router Solicitation	5
5.1.	Requesting Router	6
5.2.	Delegating Router	6
6.	Requesting Router Initiated Prefix Delegation	6
6.1.	Requesting Router	7
6.2.	Delegating Router	7
7.	Security Considerations	7
8.	IANA Considerations	7
9.	Acknowledgements	8
10.	References	8
10.1.	Normative References	8
10.2.	Informative References	8
	Authors' Addresses	8

Internet-Draft

PD Exclude Option

January 2011

1. Introduction

This specification defines an optional mechanism and the related DHCPv6 option to allow exclusion of one specific prefix from a delegated prefix set when using DHCPv6-based prefix delegation.

The prefix exclusion mechanism is targeted to deployments where DHCPv6-based prefix delegation is used but a single aggregatable route/prefix has to represent one customer, instead of using one prefix for the link between the delegating router and the requesting router and another prefix for the customer network. The mechanism defined in this specification allows a delegating router to use a prefix out of the delegated prefix set on the link through which it exchanges DHCPv6 messages with the requesting router.

2. Requirements and Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

3. Problem Background

DHCPv6 Prefix Delegation (DHCPv6-PD) [[RFC3633](#)] has an explicit limitation described in [Section 12.1 of \[RFC3633\]](#) that a prefix delegated to a requesting router cannot be used by the delegating router. This restriction implies that the delegating router will have two (non aggregatable) routes towards a customer, one for the link between the requesting router and the delegating router, and one for the customer site behind the requesting router.

There are architectures and link models, where a host (e.g. a mobile router, also acting as a requesting router) always has a single (/64) prefix configured on its uplink interface and the delegating router

is also requesting router's first hop router. Furthermore, it may be required that the prefix configured on the uplink interface has to be aggregatable with the delegated prefixes. This introduces a problem in how to use DHCPv6-PD together with stateless [RFC4862] or stateful [RFC3315] address autoconfiguration on a link, where the /64 advertised on the link is also part of the prefix delegated (e.g /56) to the requesting router.

[4.](#) Solution


[4.1.](#) Prefix Delegation with Excluded Prefixes

This specification defines a new DHCPv6 option, OPTION_PD_EXCLUDE (TBD1), that is used to exclude exactly one prefix from a delegated prefix. The OPTION_PD_EXCLUDE is included in the OPTION_IAPREFIX IAprefix-options field. There can be at most one OPTION_PD_EXCLUDE option in one OPTION_IAPREFIX option. The OPTION_PD_EXCLUDE option allows prefix delegation where a requesting router is delegated a prefix (e.g. /56) and the delegating router uses one prefix (e.g. /64) on the link through which it exchanges DHCPv6 messages with the requesting router with a prefix out of the same delegated prefix set.

A requesting router includes an OPTION_ORO option with the OPTION_PD_EXCLUDE option code in a Solicit, Request, Renew, Rebind or Confirm message to inform the delegating router about the support for the prefix delegation functionality defined in this specification. A delegating router may include the OPTION_PD_EXCLUDE option code in an OPTION_ORO option in a Reconfigure message for indicating that the requesting router should request OPTION_PD_EXCLUDE from the delegating router.

The delegating router includes the prefix in the OPTION_PD_EXCLUDE option that is excluded from the delegated prefix set. The requesting router MUST NOT assign the excluded prefix to any of its downstream interfaces.

[4.2.](#) Prefix Exclude Option



Prefix Exclude Option

- o option-code: OPTION_PD_EXCLUDE (TBD1).
- o option-len: 1 + length of IPv6 subnet ID in octets. A valid option-len is between 2 and 17.
- o prefix-len: The length of the excluded prefix in bits. The prefix-len MUST be between 'OPTION_IAPREFIX prefix-length'+1 and 128.

- o IPv6 subnet ID: A variable length IPv6 subnet ID up to 128 bits. The subnet ID contains prefix-len minus 'OPTION_IAPREFIX prefix-length' bits extracted from the excluded prefix starting from the bit position 'OPTION_IAPREFIX prefix-length'. The extracted subnet ID MUST be left shifted to start from a full octet boundary, i.e. left shift of 'OPTION_IAPREFIX prefix-length' mod 8 bits. The subnet ID MUST be zero padded to the next full octet boundary.


The OPTION_PD_EXCLUDE option MUST only be included in the OPTION_IAPREFIX IAprefix-options [[RFC3633](#)] field. The OPTION_PD_EXCLUDE option MUST be located before the possible Status Code option in the IAprefix-options field.

Any prefix excluded from the delegated prefix MUST be contained in OPTION_PD_EXCLUDE options within the corresponding OPTION_IAPREFIX.

The prefix included in the OPTION_PD_EXCLUDE option share the same preferred-lifetime and valid-lifetime as the delegated prefix in the encapsulating OPTION_IAPREFIX option.

The prefix in the OPTION_PD_EXCLUDE option MUST be part of the

delegated prefix in the OPTION_IAPREFIX. For example, the requesting router has earlier been assigned a 2001:db8:dead:beef::/64 prefix by the delegating router, and the delegated prefix in the OPTION_IAPREFIX is 2001:db8:dead:bee0::/59. In this case, 2001:db8:dead:beef::/64 is a valid prefix to be used in the OPTION_PD_EXCLUDE option. The OPTION_PD_EXCLUDE option would be encoded as follows:



5. Delegating Router Solicitation

The requesting router locates and selects a delegating router in the same way as described in [Section 11 \[RFC3633\]](#). This specification

only describes the additional steps required by the use of OPTION_PD_EXCLUDE option.

5.1. Requesting Router

If the requesting router implements the solution described in [Section 4.1](#) then the requesting router SHOULD include the OPTION_PD_EXCLUDE option code in the OPTION_ORO option in the Solicit message.

Once receiving Advertise message, the requesting router uses the prefix(es) received in OPTION_PD_EXCLUDE in addition to the advertised prefixes to choose the delegating router to respond to. If Advertise message did not include OPTION_PD_EXCLUDE option, then the requesting router MUST fall back to normal [\[RFC3633\]](#) behavior.

[5.2.](#) Delegating Router

If the OPTION_ORO option in the Solicit message includes the OPTION_PD_EXCLUDE option code, then the delegating router knows that the requesting router supports the solution defined in this specification. If the Solicit message also contains an IA_PD option, the delegating router can delegate to the requesting router a prefix which includes the prefix already assigned to the requesting router's uplink interface. The delegating router includes the prefix originally or to be assigned to the requesting router in the OPTION_PD_EXCLUDE option within the OPTION_IAPREFIX IAprefix-option in the Advertise message.

If the OPTION_ORO option in the Solicit message does not include the OPTION_PD_EXCLUDE option code, then the delegating router MUST fall back to normal [[RFC3633](#)] behavior.

If the OPTION_ORO option in the Solicit message includes the OPTION_PD_EXCLUDE option code but the delegating router does not support the solution described in this specification, then the delegating router acts as specified in [[RFC3633](#)]. The requesting router MUST in this case also fall back to normal [[RFC3633](#)] behavior.

[6.](#) Requesting Router Initiated Prefix Delegation

The procedures described in the following sections are aligned with [Section 12 of \[RFC3633\]](#). In this specification we only describe the additional steps required by the use of OPTION_PD_EXCLUDE option.

[6.1.](#) Requesting Router

The requesting router behavior regarding the use of the OPTION_PD_EXCLUDE option is more or less identical to step described in [Section 5.1](#). The only difference really is different used DHCPv6 messages.

The requesting router uses a Release message to return the delegated

prefix(es) to a delegating router. The prefix(es) to be released MUST be included in the IA_PDs along with the excluded prefix included in the OPTION_PD_EXCLUDE option. The requesting router MUST NOT use the OPTION_PD_EXCLUDE option to introduce additional excluded prefix in the Release message that it originally got a valid binding for.

The requesting router must create sink routes for the delegated prefixes minus the excluded prefixes. This may be done by creating sink routes for delegated prefixes and more specific routes for the excluded prefixes.

[6.2.](#) Delegating Router

The delegating router behavior regarding the use of the OPTION_PD_EXCLUDE option is more or less identical to step described in [Section 5.2](#). The only difference really is DHCPv6 messages used to carry the OPTION_PD_EXCLUDE option.

The delegating router may mark any prefix(es) in IA_PD Prefix options in a Release message from a requesting router as 'available' excluding the prefix included in the OPTION_PD_EXCLUDE options. If the Release message contains 'new' excluded prefix in any OPTION_PD_EXCLUDE option, the delegating router MUST send a Reply message with Status Code set to NoBinding for that IA_PD option.

[7.](#) Security Considerations

Security considerations in DHCPv6 are described in [Section 23 of \[RFC3315\]](#), and for DHCPv6 Prefix Delegation in [Section 12 of \[RFC3633\]](#).

[8.](#) IANA Considerations

A new DHCPv6 Option Code is reserved from DHCPv6 registry for DHCP Option Codes.

OPTION_PD_EXCLUDE is set to TBD1

[9.](#) Acknowledgements

Authors would like to thank Ralph Droms, Frank Brockners, Ted Lemon, Julien Laganier, Fredrik Garneij, Sri Gundavelli, Mikael Abrahamsson, Behcet Sarikaya, Jyrki Soini and Deng Hui for their valuable comments and discussions.

10. References

10.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC3315] Droms, R., Bound, J., Volz, B., Lemon, T., Perkins, C., and M. Carney, "Dynamic Host Configuration Protocol for IPv6 (DHCPv6)", [RFC 3315](#), July 2003.
- [RFC3633] Troan, O. and R. Droms, "IPv6 Prefix Options for Dynamic Host Configuration Protocol (DHCP) version 6", [RFC 3633](#), December 2003.

10.2. Informative References

- [RFC4862] Thomson, S., Narten, T., and T. Jinmei, "IPv6 Stateless Address Autoconfiguration", [RFC 4862](#), September 2007.

Authors' Addresses

Jouni Korhonen (editor)
Nokia Siemens Networks
Linnoitustie 6
FI-02600 Espoo
Finland

Email: jouni.nospam@gmail.com

Teemu Savolainen
Nokia
Hermiankatu 12 D
FI-33720 Tampere
Finland

Email: teemu.savolainen@nokia.com

Internet-Draft

PD Exclude Option

January 2011

Suresh Krishnan
Ericsson
8400 Decarie Blvd.
Town of Mount Royal, QC
Canada

Email: suresh.krishnan@ericsson.com

Ole Troan
Cisco Systems, Inc
Oslo
Norway

Email: ot@cisco.com

