

Submitted to DHC Working Group
INTERNET DRAFT
<[draft-ietf-dhc-pv4-reconfigure-01.txt](#)>

Peter De Schrijver
Yves T'Joens
Christian Hublet
Alcatel

June 2000
Expires December 2000

Dynamic host configuration : DHCP reconfigure extension

Status of this memo

This document is an Internet-Draft and is in full conformance with all provisions of [Section 10 of RFC2026](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months. Internet-Drafts may be updated, replaced, or obsoleted by other documents at any time. It is not appropriate to use Internet-Drafts as reference material or to cite them other than as a ``working draft'' or ``work in progress.''

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/lid-abstracts.txt>

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

To view the entire list of current Internet-Drafts, please check the "lid-abstracts.txt" listing contained in the Internet-Drafts Shadow Directories on ftp.is.co.za (Africa), ftp.nordu.net (Northern Europe), ftp.nis.garr.it (Southern Europe), munnari.oz.au (Pacific Rim), ftp.ietf.org (US East Coast), or ftp.isi.edu (US West Coast).

Distribution of this memo is unlimited.

Abstract

This draft defines extensions to DHCP [[DHCP](#)] to allow dynamic reconfiguration of a single host triggered by the DHCP server (eg. a new IP address). This is achieved by introducing a unicast DHCP FORCERENEW message which forces the client to the RENEW state.

1. Introduction

The procedures as described within this draft allow the dynamic reconfiguration of individual hosts.

1.1 Conventions

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY" and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)].

2. DHCP force renew

This section describes the DHCP force renew extension.

2.1 Terminology

DHCP client : host to be reconfigured using DHCP.

DHCP server : server which configured the DHCP client.


2.2 Force renew procedures

The DHCP server sends a force renew message to the client. The client will change its state to the RENEW state. The client will then try to renew its lease according to normal DHCP procedures. If the server wants to assign a new IP address to the client, it will reply to the DHCP REQUEST with a DHCP NAK. The client will then go back to the init state and broadcast a DHCP DISCOVER message. The server can now assign a new IP address to the client by replying with a DHCP OFFER. If the force renew message is lost, the DHCP server will not receive a DHCP REQUEST from the client and it should retransmit the DHCP FORCERENEW message using an exponential backoff algorithm. Depending on the bandwidth of the network between server and client, the server should choose a delay. This delay grows exponentially as retransmissions fail. The amount of retransmissions should be limited.

2.3 Rationale

This approach has a number of advantages. It does not require new states to be added to the DHCP client implementation. This minimizes the amount of code to be changed. It also allows lease RENEWAL to be driven by the server, which can be used to optimize network usage or DHCP server load.

3. Extended DHCP state diagram



should only send a DHCPFORCERENEW when in "PARTNER DOWN", "COMMUNICATIONS INTERRUPTED" or "NORMAL" state, and only for DHCP clients of which the state is synchronised. (see [[DHCP-FAILOVER](#)])

6. IANA Considerations

The new value for DHCP option 53 (DHCP message type) to indicate a DHCPFORCERENEW message is TBD.

7. Security Considerations

As in some network environments DHCPFORCERENEW can be used to snoop and spoof traffic, the DHCPFORCERENEW message MUST be authenticated using a shared secret based mechanism as described in [[DHCP-AUTH](#)].

8. References

[DHCP] R.Droms, "Dynamic Host Configuration Protocol", [RFC 2131](#), March 1997.

[DHCP-AUTH] R. Droms, "Authentication for DHCP Messages", [draft-ietf-dhc-authentication-12](#), October 1999, Work in progress.

[DHCP-FAILOVER] R. Droms, K. Kinnear, M. Stapp, B. Volz, S. Gonczi, G. Rabil, M. Dooley, A. Kapur, "DHCP Failover Protocol", [draft-ietf-dhc-failover-06.txt](#), March 2000, Work in progress.

9. Contacts

Peter De Schrijver
Alcatel Network Strategy Group
Francis Wellesplein 1, 2018 Antwerp, Belgium
Phone : +32 3 240 8569
E-mail : peter.de_schrijver@alcatel.be

Yves T'joens
Alcatel Network Strategy Group
Francis Wellesplein 1, 2018 Antwerp, Belgium
Phone : +32 3 240 7890
E-mail : yves.tjoens@alcatel.be

Christian Hublet
Alcatel Carrier Internetworking Division
De Villermontstraat 28, 2550 Kontich, Belgium

Phone : +32 3 450 3322

E-mail : Christian.Hublet@alcatel.be