dnsop J. Appelbaum Internet-Draft

Intended status: Standards Track

Expires: March 12, 2016

The Tor Project, Inc A. Muffett Facebook September 9, 2015

The .onion Special-Use Domain Name draft-ietf-dnsop-onion-tld-01

Abstract

This document registers the ".onion" Special-Use Domain Name.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of \underline{BCP} 78 and \underline{BCP} 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at http://datatracker.ietf.org/drafts/current/.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on March 12, 2016.

Copyright Notice

Copyright (c) 2015 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (http://trustee.ietf.org/license-info) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

<u>1</u> .]	Introduction						2
1.1	${ t 1}$. Notational Conventions						3
<u>2</u> . 1	The ".onion" Special-Use Domain Name						3
<u>3</u> .]	IANA Considerations						4
<u>4</u> . 9	Security Considerations						4
<u>5</u> . F	References						5
<u>5.1</u>	$\underline{ t 1}$. Normative References						5
5.2	2. Informative References						6
<u>Apper</u>	<u>ndix A</u> . Acknowledgements						6
Autho	ors' Addresses		 				6

1. Introduction

The Tor network [Dingledine2004] has the ability to host network services using the ".onion" Special-Use Top-Level Domain. Such names can be used as other domain names would be (e.g., in URLs [RFC3986]), but instead of using the DNS infrastructure, .onion names functionally correspond to the identity of a given service, thereby combining location and authentication.

.onion names are used to provide access to end to end encrypted, secure, anonymized services; that is, the identity and location of the server is obscured from the client. The location of the client is obscured from the server. The identity of the client may or may not be disclosed through an optional cryptographic authentication process.

.onion names are self-authenticating, in that they are derived from the cryptographic keys used by the server in a client-verifiable manner during connection establishment. As a result, the cryptographic label component of a .onion name is not intended to be human-meaningful.

The Tor network is designed to not be subject to any central controlling authorities with regards to routing and service publication, so .onion names cannot be registered, assigned, transferred or revoked. "Ownership" of a .onion name is derived solely from control of a public/private key pair which corresponds to the algorithmic derivation of the name.

In this way, .onion names are "special" in the sense defined by [RFC6761] Section 3; they require hardware and software implementations to change their handling in order to achieve the desired properties of the name (see Section 4). These differences are listed in Section 2.

Like Top-Level Domain Names, .onion names can have an arbitrary number of subdomain components. This information is not meaningful to the Tor protocol, but can be used in application protocols like HTTP [RFC7230].

Note that .onion names are required conform to DNS name syntax (as defined in <u>Section 3.5 of [RFC1034]</u> and <u>Section 2.1 of [RFC1123]</u>), as they will still be exposed to DNS implementations.

See [tor-address] and [tor-rendezvous] for the details of the creation and use of .onion names.

1.1. Notational Conventions

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC2119].

2. The ".onion" Special-Use Domain Name

These properties have the following effects upon parties using or processing .onion names (as per [RFC6761]):

- Users: Human users are expected to recognize .onion names as
 having different security properties (see <u>Section 1</u>), and also as
 being only available through software that is aware of onion
 names.
- 2. Application Software: Applications (including proxies) that implement the Tor protocol MUST recognize .onion names as special by either accessing them directly, or using a proxy (e.g., SOCKS [RFC1928]) to do so. Applications that do not implement the Tor protocol SHOULD generate an error upon the use of .onion, and SHOULD NOT perform a DNS lookup.
- 3. Name Resolution APIs and Libraries: Resolvers MUST either respond to requests for .onion names by resolving them according to [tor-rendezvous] or by responding with NXDOMAIN.
- 4. Caching DNS Servers: Caching servers, where not explicitly adapted to interoperate with Tor, SHOULD NOT attempt to look up records for .onion names. They MUST generate NXDOMAIN for all such queries.
- 5. Authoritative DNS Servers: Authoritative servers MUST respond to queries for .onion with NXDOMAIN.

- 6. DNS Server Operators: Operators MUST NOT configure an authoritative DNS server to answer queries for .onion. If they do so, client software is likely to ignore any results (see above).
- 7. DNS Registries/Registrars: Registrars MUST NOT register .onion names; all such requests MUST be denied.

Note that the restriction upon the registration of .onion names does not prohibit IANA from inserting a record into the root zone database to reserve the name.

Likewise, it does not prevent non-DNS service providers (such as trust providers) from supporting .onion names in their applications.

3. IANA Considerations

This document registers "onion" in the registry of Special-Use Domain Names [RFC6761]. See Section 2 for the registration template.

4. Security Considerations

The security properties of .onion names can be compromised if, for example:

- o The server "leaks" its identity in another way (e.g., in an application-level message), or
- o The access protocol is implemented or deployed incorrectly, or
- o The access protocol itself is found to have a flaw.

Users must take special precautions to ensure that the .onion name they are communicating with is the intended one, as attackers may be able to find keys which produce service names that are visually or semantically similar to the desired service. This risk is magnified because .onion names are typically not human-meaningful. It can be mitigated by generating human meaningful .onion names (at considerable computing expense), or through users using bookmarks and other trusted stores when following links.

Also, users need to understand the difference between a .onion name used and accessed directly via Tor-capable software, versus .onion subdomains of other top-level domain names and providers (e.g., the difference between example.onion and example.onion.tld).

The cryptographic label for a .onion name is constructed by applying a function to the public key of the server, the output of which is

rendered as a string and concatenated with the string ".onion". Dependent upon the specifics of the function used, an attacker may be able to find a key that produces a collision with the same .onion name with substantially less work than a cryptographic attack on the full strength key. If this is possible the attacker may be able to impersonate the service on the network.

A legacy client may inadvertently attempt to resolve a ".onion" name through the DNS. This causes a disclosure that the client is attempting to use Tor to reach a specific service. Malicious resolvers could be engineered to capture and record such leaks, which might have very adverse consequences for the well-being of the Tor user. This issue is mitigated if the client's Tor software is updated to not leak such queries, or if the client's DNS software is updated to drop any request to the ".onion" TLD.

5. References

5.1. Normative References

[Dingledine2004]

Dingledine, R., Mathewson, N., and P. Syverson, "Tor: the second-generation onion router", 2004, https://spec.torproject.org/tor-spec>.

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate
 Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/
 RFC2119, March 1997,
 http://www.rfc-editor.org/info/rfc2119.

[tor-address]

Mathewson, N. and R. Dingledine, "Special Hostnames in Tor", September 2001, https://spec.torproject.org/ address-spec>.

[tor-rendezvous]

Mathewson, N. and R. Dingledine, "Tor Rendezvous Specification", April 2014, https://spec.torproject.org/rend-spec.

5.2. Informative References

- [RFC3986] Berners-Lee, T., Fielding, R., and L. Masinter, "Uniform
 Resource Identifier (URI): Generic Syntax", STD 66, RFC
 3986, DOI 10.17487/RFC3986, January 2005,
 http://www.rfc-editor.org/info/rfc3986.
- [RFC7230] Fielding, R., Ed. and J. Reschke, Ed., "Hypertext Transfer
 Protocol (HTTP/1.1): Message Syntax and Routing", RFC
 7230, DOI 10.17487/RFC7230, June 2014,
 http://www.rfc-editor.org/info/rfc7230.

<u>Appendix A</u>. Acknowledgements

Thanks to Roger Dingledine, Linus Nordberg, and Seth David Schoen for their input and review.

This specification builds upon previous work by Christian Grothoff, Matthias Wachs, Hellekin O. Wolf, Jacob Appelbaum, and Leif Ryge to register .onion in conjunction with other, similar Special-Use Top-Level Domain Names.

Authors' Addresses

Jacob Appelbaum
The Tor Project, Inc

Email: jacob@appelbaum.net

Alec Muffett Facebook

Email: alecm@fb.com