

Network Working Group
Internet-Draft
Intended status: BCP
Expires: January 15, 2009

P. Koch
DENIC eG
M. Larson
VeriSign, Inc.
July 14, 2008

Initializing a DNS Resolver with Priming Queries **draft-ietf-dnsop-resolver-priming-01**

Status of this Memo

By submitting this Internet-Draft, each author represents that any applicable patent or other IPR claims of which he or she is aware have been or will be disclosed, and any of which he or she becomes aware will be disclosed, in accordance with [Section 6 of BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/1id-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

This Internet-Draft will expire on January 15, 2009.

Abstract

This document describes the initial queries a DNS resolver is supposed to emit to initialize its cache with a current NS RRSet for the root zone as well as the necessary address information.

1. Introduction

Domain Name System (DNS) resolvers need a starting point to resolve queries. [\[RFC1034\]](#), [section 5.3.2](#), defines the SBELT structure in a full resolver as:

``a "safety belt" structure of the same form as SLIST, which is initialized from a configuration file, and lists servers which should be used when the resolver doesn't have any local information to guide name server selection. The match count will be -1 to indicate that no labels are known to match.''

[Section 5.3.3 of \[RFC1034\]](#) adds

``the usual choice is two of the root servers and two of the servers for the host's domain''

Today's practice generally separates serving and resolving functionality, so the servers ``for the host's domain'' might no longer be an appropriate choice, even if they were only intended to resolve ``local'' names, especially since the SBELT structure does not distinguish between local and global information. In addition, DNS server implementations have for a long time been seeded with not only two but an exhaustive list of the root servers' addresses. This list is either supplied as a configuration file (root "hints", an excerpt of the DNS root zone) or even compiled into the software.

The list of root name servers has been rather stable over the last ten years. After the last four servers had been added and moved to their final (network) destinations in 1997, there have been only four address changes affecting the L (twice), J, and B servers. Research is available for B [[Mann2006](#)] and J [[BLKT2004](#)], which shows that several months or even years after the change had become effective, traffic is still received on the old addresses. Therefore, it is important that resolvers be able to cope with change, even without relying upon configuration updates to be applied by their operator.

Work by the ICANN SSAC and RSSAC committees, [[SSAC016](#)] and [[SSAC017](#)], aiming at adding AAAA RRs for the root name servers' names, deals with priming queries and so does a draft on DNSSEC Trust Anchor maintenance [[I-D.ietf-dnsop-dnssec-trust-anchor](#)]. However, it turned out that despite having been practiced for a long time, priming queries have not yet been documented as an important resolver feature.

The following sections cover parameters of both the priming query and the response to be sent by a root name server.

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

2. Parameters of a Priming Query

This document only deals with QCLASS IN. A priming query SHOULD use a QNAME of "." and a QTYPE of NS. It SHOULD also use EDNS0 [[RFC2671](#)] and announce and handle a reassembly size of at least 1024 octets [[RFC3226](#)].

A priming query MUST be sent over UDP ([section 6.1.3.2 of \[RFC1123\]](#)). The RD bit MUST NOT be set in the query.

2.1. Target Selection

A resolver MUST select the target for a priming query randomly from the list of addresses available in its SBELT structure and it MUST ensure that all targets are selected with equal probability even upon startup. For resending the priming query to a different server the random selection SHOULD also be used.

2.2. DNSSEC with Priming Queries

The resolver MAY choose to use DNSSEC OK [[RFC4033](#)], in which case it MUST announce and handle a message size of at least 1220 octets.

Discussion: Delegations in referral responses are not signed, so following this model there would be no need to require a signed root NS RRSets and, equally important, signed A and AAAA RRSets for the root name servers' names. On the other hand, a poisoned priming response could drastically influence the resolver's operations. If the priming response should be secured by DNSSEC, then it should also be self contained, i.e., the whole validation chain should be present in the priming response. This might call for a different naming scheme (see section 6.1 of [[I-D.koch-dns-glue-clarifications](#)]).

2.3. Repeating Priming Queries

A resolver SHOULD NOT originate a priming query more often than once per day (or whenever it starts). It SHOULD adhere to the TTL values given in the priming response. To avoid amnesia, the resolver MAY proactively re-prime before the old root NS RRSets expires from the cache, but only after 75 percent of the NS RRSets' TTL (or the A/AAAA RRSets' TTL, whichever is lower) have passed.

3. Expected Properties of a Priming Response

The response can be expected to have an RCODE of NOERROR and the AA bit set. Also, there should be an NS RRSets in the answer section (since the NS RRSets originates from the root zone), an empty

authority section (since the NS RRSets already appears in the answer section) and an additional section with A and AAAA RRSets for the root name servers pointed at by the NS RRSets. Resolver software SHOULD NOT expect a fixed number of 13 NS RRs, since "internal" root server setups in split DNS configurations might use a lower number of servers. Resolver software SHOULD warn the operator about any change in the number or names of name servers compared to the SBELT information.

3.1. Use of the Priming Response

A resolver MAY use the priming response as it would use any other data fed to its cache. However, it SHOULD NOT use the SBELT information directly in any responses it hands out.

3.2. Completeness of the Response

For an EDNS response, a resolver SHOULD consider the address information found in the additional section complete for any particular server that appears at all. In other words: if the additional section only has an A RRSets for a server, the resolver SHOULD assume that no AAAA RRSets exists. To ensure equal availability the A and AAAA RRSets should have identical TTL values at the authoritative source. [[There might still be some degenerate cases of response sizes between 512 and 1024.]]

[[If the resolver did not announce a reassembly size larger than 512 octets, this assumption is invalid. How to acquire the remaining address RRSets is TBD. Simple re-issuing of the priming query does not help with those root name servers that respond with a fixed order of addresses in the additional section.]]

4. Root Name Server Requirements

The operational requirements for root name servers are described in [\[RFC2870\]](#).

All DNS root name servers need to be able to provide for all addresses of all root name servers. This can easily be achieved by making all root name servers authoritative for the zone containing the servers' names.

[[At the time of writing, all but one root name server were authoritative for ROOT-SERVERS.NET., even though only a subset received an official delegation.]]

If the response packet does not provide for more than 512 octets due

to lack of EDNS0 support, A RRSets SHOULD be given preference over AAAA RRSets when filling the additional section.

[[EDNS0 is used as an indication of AAAA understanding on the side of the client. What to do with small payload sizes indicated by EDNS0 is open to discussion. At the time of writing, some root name servers will fill the additional section with all available A RRSets, only adding some AAAA RRSets, when queried over IPv4 without EDNS0. Other servers will deliver more AAAA RRSets, therefore withholding some A RRSets completely [[RFC4472](#)].]]

[[Do the TTLs for the root NS RRSets and address RRSets in the root and the ROOT-SERVERS.NET. zones need to be aligned? In real life responses, the address RRSets' TTL values vary by implementation.]]

5. Security Considerations

This document deals with priming a DNS resolver's cache. The usual DNS caveats apply. Use of DNSSEC with priming queries is discussed in [section 2.2](#).

Spoofing a response to a priming query can be used to redirect all queries originating from a victim resolver, therefore any difference between the initial SBELT list and the priming response SHOULD be brought to the operators' attention. There is also a chance that the random target selection chooses the address of a retired root name server. Operational measures to prevent reuse of these addresses are out of the scope of this document.

[[This section needs more work.]]

6. IANA Considerations

This document does not propose any new IANA registry nor does it ask for any allocation from an existing IANA registry.

However, this document deals with requirements for the root zone and root server operations.

[[Any recommendation on the "." NS RRSets TTL or the TTLs of the respective A and/or AAAA RRSets would go here.]]

[[This section needs more work.]]

7. References

7.1. Normative References

- [RFC1034] Mockapetris, P., "Domain names - concepts and facilities", STD 13, [RFC 1034](#), November 1987.
- [RFC1123] Braden, R., "Requirements for Internet Hosts - Application and Support", STD 3, [RFC 1123](#), October 1989.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC2671] Vixie, P., "Extension Mechanisms for DNS (EDNS0)", [RFC 2671](#), August 1999.
- [RFC3226] Gudmundsson, O., "DNSSEC and IPv6 A6 aware server/resolver message size requirements", [RFC 3226](#), December 2001.
- [RFC4033] Arends, R., Austein, R., Larson, M., Massey, D., and S. Rose, "DNS Security Introduction and Requirements", [RFC 4033](#), March 2005.

7.2. Informative References

- [BLKT2004] Barber, P., Larson, M., Kisters, M., and P. Toscano, "Life and Times of J-Root", NANOG 32, October 2004.
- [I-D.ietf-dnsop-dnssec-trust-anchor] Larson, M. and O. Gudmundsson, "DNSSEC Trust Anchor Configuration and Maintenance", [draft-ietf-dnsop-dnssec-trust-anchor-01](#) (work in progress), February 2008.
- [I-D.koch-dns-glue-clarifications] Koch, P., "DNS Glue RR Survey and Terminology Clarification", [draft-koch-dns-glue-clarifications-03](#) (work in progress), November 2007.
- [Mann2006] Manning, B., "persistent queries and phantom nameservers", WIDE/CAIDA Workshop , October 2006.
- [RFC2870] Bush, R., Karrenberg, D., Kisters, M., and R. Plzak, "Root Name Server Operational Requirements", [BCP 40](#), [RFC 2870](#), June 2000.
- [RFC4472] Durand, A., Ihren, J., and P. Savola, "Operational Considerations and Issues with IPv6 DNS", [RFC 4472](#),

April 2006.

[SSAC016] ICANN Security and Stability Advisory Committee, "Testing Firewalls for IPv6 and EDNS0 Support", SSAC 016, January 2007.

[SSAC017] ICANN Security and Stability Advisory Committee, "Testing Recursive Name Servers for IPv6 and EDNS0 Support", SSAC 017, February 2007.

[Appendix A.](#) Document Revision History

This section is to be removed should the draft be published.

[A.1.](#) -01 WG Document

Revived with minor edits. Open issues marked [[]].

[A.2.](#) -00 WG Document

Reposted as WG document with minor edits.

Added re-priming proposal and A/AAAA TTL considerations.

[A.3.](#) Initial Document

First draft

Authors' Addresses

Peter Koch
DENIC eG
Kaiserstrasse 75-77
Frankfurt 60329
DE

Phone: +49 69 27235 0
Email: pk@DENIC.DE

Matt Larson
VeriSign, Inc.
21345 Ridgetop Circle
Dulles, VA 20166-6503
USA

Email: mlarson@verisign.com

Full Copyright Statement

Copyright (C) The IETF Trust (2008).

This document is subject to the rights, licenses and restrictions contained in [BCP 78](#), and except as set forth therein, the authors retain all their rights.

This document and the information contained herein are provided on an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY, THE IETF TRUST AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Intellectual Property

The IETF takes no position regarding the validity or scope of any Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; nor does it represent that it has made any independent effort to identify any such rights. Information on the procedures with respect to rights in RFC documents can be found in [BCP 78](#) and [BCP 79](#).

Copies of IPR disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF on-line IPR repository at <http://www.ietf.org/ipr>.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement this standard. Please address the information to the IETF at ietf-ipr@ietf.org.

