

Network Working Group
Internet-Draft
Intended status: Standards Track
Expires: May 27, 2016

A. Mayrhofer
nic.at GmbH
November 24, 2015

The EDNS(0) Padding Option
draft-ietf-dprive-edns0-padding-01

Abstract

This document specifies the EDNS(0) 'Padding' option, which allows DNS clients and servers to pad request and response messages by a variable number of octets.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on May 27, 2016.

Copyright Notice

Copyright (c) 2015 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	2
2.	Terminology	2
3.	The 'Padding' Option	3
4.	Usage Considerations	3
5.	IANA Considerations	4
6.	Security Considerations	4
7.	Acknowledgements	4
8.	Changes	4
8.1.	draft-ietf-dprive-edns0-padding-01	4
8.2.	draft-ietf-dprive-edns0-padding-00	5
8.3.	draft-mayrhofer-edns0-padding-01	5
8.4.	draft-mayrhofer-edns0-padding-00	5
9.	References	5
9.1.	Normative References	5
9.2.	Informative References	5
	Author's Address	5

[1.](#) Introduction

The Domain Name System (DNS) [[RFC1035](#)] was specified to transport DNS packets in clear text form. Since this can expose significant amounts of information about the internet activities of an end user, the IETF has undertaken work to provide confidentiality to DNS transactions (see the DPRIVE WG). Encrypting the DNS transport is considered as one of the options to improve the situation.

However, even if both DNS query and response packets were encrypted, meta data of these packets could be used to correlate such packets with well known unencrypted packets, hence jeopardizing some of the confidentiality gained by encryption. One such property is the message size.

This document specifies the Extensions Mechanisms for DNS (EDNS(0)) "Padding" Option, which allows to artificially increase the size of a DNS message by a variable number of bytes, significantly hampering size-based correlation of the encrypted packet.

[2.](#) Terminology

The terms "Requestor", "Responder" are to be interpreted as specified in [[RFC6891](#)].

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

3. The 'Padding' Option

The EDNS(0) [[RFC6891](#)] specifies a mechanism to include new options in DNS packets, contained in the RDATA of the OPT meta-RR. This document specifies the 'Padding' option in order to allow clients and servers pad DNS packets by a variable number of bytes. The 'Padding' option MUST occur at most once per OPT meta-RR.

The figure below specifies the structure of the option in the RDATA of the OPT RR:




Figure 1

The OPTION-CODE for the 'Padding' option is 12.

The OPTION-LENGTH for the 'Padding' option is the size (in octets) of the PADDING. The minimum number of padding octets is 0.

The PADDING octets SHOULD be set to 0x00. Application developers who are concerned about misguided lower layer compression MAY instead fill the PADDING octets with the output of a cryptographic random number generator. Responders MUST NOT reject messages containing non-0x00 PADDING octets.

4. Usage Considerations

This document does not specify the actual amount of padding to be used, since this depends on the situation in which the option is used. However, padded DNS messages MUST NOT exceed the number of octets specified in the Requestor's Payload Size field encoded in The RR Class Field (see [Section 6.2.3](#) and 6.2.4 of [[RFC6891](#)]).

Responders MUST pad DNS responses when the respective DNS query included the 'Padding' option, unless doing so would violate the maximum UDP payload size.

Responders MAY pad DNS responses when the respective DNS query indicated EDNS(0) support of the Requestor.

Responders MUST NOT pad DNS responses when the respective DNS query did not indicate EDNS(0).

5. IANA Considerations

IANA has assigned EDNS Option Code 12 for Padding.

IANA is requested to update the respective registration record by changing the Reference field to `[[THISRFC]]` and the Status field to 'Standard'.

6. Security Considerations

Padding DNS packets obviously increases their size, and will therefore lead to increased traffic, can lead to increased number of truncated packets when used over UDP-based transport.

The use of the EDNS(0) Padding provides only a benefit when DNS packets are not transported in clear text. Implementations therefore SHOULD avoid using this option if the DNS transport is not encrypted.

Padding length might be affected by lower-level compression. Therefore (as described in [Section 3.3 of \[RFC7525\]](#)), implementations and deployments SHOULD disable TLS-level compression.

The payload of the 'Padding' option could (like many other fields in the DNS protocol) be used as a covert channel.

7. Acknowledgements

This document was inspired by a discussion with Daniel Kahn Gillmor during IETF93, as an alternative to the proposed padding on the TLS layer. Allison Mankin and Christian Huitema suggested text for this document.

8. Changes

8.1. [draft-ietf-dprive-edns0-padding-01](#)

Fixed 'octects' typo. Changed 'covert channel' text to align with allowing non-0x00 padding. changed IANA considerations - assigned option code is 12. Changed field definitions to allow for non-0x00 padding, removed FORMERR requirement. referenced [rfc7525](#) in security considerations. added acknowledgements.

[8.2. draft-ietf-dprive-edns0-padding-00](#)

Adopted by WG. Changed text about message size limit based on feedback.

[8.3. draft-mayrhofer-edns0-padding-01](#)

Changed minimum padding size to 0, rewrote Usage Considerations section, extended Security considerations section

[8.4. draft-mayrhofer-edns0-padding-00](#)

Initial version

[9. References](#)

[9.1. Normative References](#)

- [RFC1035] Mockapetris, P., "Domain names - implementation and specification", STD 13, [RFC 1035](#), DOI 10.17487/RFC1035, November 1987, <<http://www.rfc-editor.org/info/rfc1035>>.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<http://www.rfc-editor.org/info/rfc2119>>.
- [RFC6891] Damas, J., Graff, M., and P. Vixie, "Extension Mechanisms for DNS (EDNS(0))", STD 75, [RFC 6891](#), DOI 10.17487/RFC6891, April 2013, <<http://www.rfc-editor.org/info/rfc6891>>.

[9.2. Informative References](#)

- [RFC7525] Sheffer, Y., Holz, R., and P. Saint-Andre, "Recommendations for Secure Use of Transport Layer Security (TLS) and Datagram Transport Layer Security (DTLS)", [BCP 195](#), [RFC 7525](#), DOI 10.17487/RFC7525, May 2015, <<http://www.rfc-editor.org/info/rfc7525>>.

Author's Address

Alexander Mayrhofer
nic.at GmbH
Karlsplatz 1/2/9
Vienna 1010
Austria

Email: alex.mayrhofer.ietf@gmail.com