

ECRIT
Internet-Draft
Intended status: Standards Track
Expires: January 30, 2014

B.R. Rosen
NeuStar
H. Tschofenig
Nokia Siemens Networks
R. Marshall
TeleCommunication Systems, Inc.
R. Gellens
Qualcomm Technologies, Inc.
J. Winterbottom
July 31, 2013

Additional Data related to an Emergency Call
draft-ietf-ecrit-additional-data-11.txt

Abstract

When an emergency call is sent to a Public Safety Answering Point (PSAP), the device that sends it, as well as any application service provider in the path of the call, or access network provider through which the call originated may have information about the call, the caller or the location which the PSAP may be able to use. This document describes data structures and a mechanism to convey such data to the PSAP. The mechanism uses a Uniform Resource Identifier (URI), which may point to either an external resource or an object in the body of the SIP message. The mechanism thus allows the data to be passed by reference (when the URI points to an external resource) or by value (when it points into the body of the message). This follows the tradition of prior emergency services standardization work where data can be conveyed by value within the call signaling (i.e., in body of the SIP message) and also by reference.

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on January 30, 2014.

Copyright Notice

Copyright (c) 2013 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the [Trust Legal Provisions](#) and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	3
2.	Terminology	5
3.	Data Structures	6
3.1.	Data Provider Information	6
3.1.1.	Data Provider String	7
3.1.2.	Data Provider ID	7
3.1.3.	Data Provider ID Series	7
3.1.4.	Type of Data Provider	8
3.1.5.	Data Provider Contact URI	8
3.1.6.	Data Provider Languages(s) Supported	9
3.1.7.	xCard of Data Provider	9
3.1.8.	Subcontractor Principal	10
3.1.9.	Subcontractor Priority	10
3.1.10.	emergencyCall.ProviderInfo Example	11
3.2.	Service Information	13
3.2.1.	Service Environment	13
3.2.2.	Service Delivered by Provider to End User	14
3.2.3.	Service Mobility Environment	16
3.2.4.	emergencyCall.SvcInfo Example	16
3.3.	Device Information	16
3.3.1.	Device Classification	17
3.3.2.	Device Manufacturer	18
3.3.3.	Device Model Number	19
3.3.4.	Unique Device Identifier	19
3.3.5.	Type of Device Identifier	19
3.3.6.	Device/Service Specific Additional Data Structure	20
3.3.7.	Device/Service Specific Additional Data Structure Type 21	
3.3.8.	Choosing between defining a new type of block or new type of device/service specific additional data	21
3.3.9.	emergencyCall.DevInfo Example	22
3.4.	Owner/Subscriber Information	22
3.4.1.	xCard for Subscriber's Data	22
3.4.2.	emergencyCall.SubInfo Example	23
3.5.	Comment	25
3.5.1.	Comment	26
3.5.2.	emergencyCall.Comment Example	26
4.	Transport	26

4.1.	Transmitting Blocks using the Call-Info Header	28
4.2.	Transmitting Blocks by Reference using the Provided-By Element	29
4.3.	Transmitting Blocks by Value using the Provided-By Element	29
4.4.	The Content-Disposition Parameter	30

5.	Examples	31
6.	XML Schemas	35
6.1.	emergencyCall.ProviderInfo XML Schema	35
6.2.	emergencyCall.SvcInfo XML Schema	36
6.3.	emergencyCall.DevInfo XML Schema	37
6.4.	emergencyCall.SubInfo XML Schema	38
6.5.	emergencyCall.Comment XML Schema	39
6.6.	Provided-By XML Schema	40
7.	Security Considerations	42
8.	Privacy Considerations	43
9.	IANA Considerations	45
9.1.	Registry creation	45
9.1.1.	Provider ID Series Registry	45
9.1.2.	Service Provider Type Registry	46
9.1.3.	Service Delivered Registry	46
9.1.4.	Device Classification Registry	47
9.1.5.	Device ID Type Type Registry	47
9.1.6.	Device/Service Data Type Registry	47
9.1.7.	Additional Data Blocks Registry	48
9.2.	'emergencyCallData' Purpose Parameter Value	48
9.3.	URN Sub-Namespace Registration for provided-by Registry Entr	49
9.4.	MIME Registrations	49
9.4.1.	MIME Content-type Registration for 'application/emergencyCall.ProviderInfo+xml'	49
9.4.2.	MIME Content-type Registration for 'application/emergencyCall.SvcInfo+xml'	50
9.4.3.	MIME Content-type Registration for 'application/emergencyCall.DevInfo+xml'	51
9.4.4.	MIME Content-type Registration for 'application/emergencyCall.SubInfo+xml'	52
9.4.5.	MIME Content-type Registration for 'application/emergencyCall.Comment+xml'	52
9.5.	URN Sub-Namespace Registration	53
9.5.1.	Registration for urn:ietf:params:xml:ns:emergencyCallAddlData	53
9.5.2.	Registration for urn:ietf:params:xml:ns:emergencyCallProviderInfo	54
9.5.3.	Registration for urn:ietf:params:xml:ns:emergencyCall.SvcInfo	55
9.5.4.	Registration for urn:ietf:params:xml:ns:emergencyCall.DevInfo	55
9.5.5.	Registration for urn:ietf:params:xml:ns:emergencyCall.SubInfo	56
9.5.6.	Registration for urn:ietf:params:xml:ns:emergencyCall.Comment	57
9.6.	Schema Registrations	57
9.7.	VCard Parameter Value Registration	58
10.	Acknowledgments	58
11.	References	59

11.1.	Normative References	59
11.2.	Informational References	60
Appendix A.	XML Schema for vCard/xCard	60
	Authors' Addresses	81

[1.](#) Introduction

When an IP-based emergency call is initiated a rich set of data from multiple data sources is conveyed to the Public Safety Answering Point (PSAP). This data includes information about the calling party identity, the multimedia capabilities of the device, the emergency service number, location information, and meta-data about the sources of the data. The device, the access network provider, and any service provider in the call path may have even more information useful for a PSAP. This document extends the basic set of data communicated with an IP-based emergency call, as described in [\[RFC6443\]](#) and [\[RFC6881\]](#), in order to carry additional data which may be useful to an entity or call taker handling the call. This data is "additional" to the basic information found in the emergency call signaling used.

In general, there are three categories of data communicated in an emergency call:

Data Associated with a Location: Location data is conveyed in the Presence Information Data Format Location Object (PIDF-LO) data structure originally defined in [RFC 4119](#) [\[RFC4119\]](#) and extended by [RFC 5139](#) [\[RFC5139\]](#) and [RFC 6848](#) [\[RFC6848\]](#) (for civic location information), [RFC 5491](#) [\[RFC5491\]](#) and [RFC 5962](#) [\[RFC5962\]](#) (for geodetic location information), and [I-D.ietf-geopriv-relative-location] (for relative location). There may be data that is specific to the location not available in the location data structure itself, such as floor plans, tenant and building owner contact data, heating, ventilation and air conditioning (HVAC) status, etc.

Data Associated with a Call: While information is carried in the call setup procedure itself (as part of the SIP headers as well as in the body of the SIP message), there is additional data known by the device making the call, and the service provider along the path of the call. This information may include the service provider contact information, subscriber identity and contact information, the type of service the service provider and the access network provider offer, what kind of device is being used, etc. Some data is device or service dependent data. For example, a car telematics system may have crash information. A medical monitoring device may have sensor data.

Data Associated with a Caller: This is personal data about a caller, such as medical information and emergency contact data.

This document only defines data structures relevant to data associated with the call but defines extension points for other data to be added via other specifications.

For interoperability, there needs to be a common way for the information conveyed to a PSAP to be encoded and identified. Identification allows emergency services authorities to know during call processing which types of data are present and to determine if they wish to access it. A common encoding allows the data to be accessed.

This document defines the data structures and a way to communicate the information in several ways. Although current standardization efforts around IP-based emergency services are focused on the Session Initiation Protocol (SIP) and HTTP the data structures in XML format described in this document are usable for other communication systems as well. In [Section 3](#) the data structures are defined and the SIP/HTTP transport components are defined in [Section 4](#) to offer a clear separation between the two.

More technically, the data structure described in this document is represented as one or more "blocks" of information. Each of the blocks is an XML structure with an associated Multipurpose Internet Mail Extensions (MIME) type for encapsulation, and an extensible set of these types constitute the data set. A registry is defined to list the block types that may be included.

2. Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)].

This document also uses terminology from [[RFC5012](#)]. We use the term service provider to refer to an Application Service Provider (ASP). A Voice Service Provider (VSP) is a special type of ASP. With the term "Access Network Provider" we refer to the Internet Access Provider (IAP) and the Internet Service Provider (ISP) without further distinguishing these two entities, since the difference between the two is not relevant for this document. Note that the roles of ASP and access network provider may be provided by a single company.

In the data block definitions, see [Section 3](#), the values for the "Use:" label are specified as one of:

'Required': means they must be present in the data structure.

'Conditional': means they must be present unless the specified condition is met, in which case they may be present.

'Optional': means they may be present.

vCard is a data format for representing and exchanging a variety of information about individuals and other entities. For applications that use XML the format defined in vCard is not immediately applicable. For this purpose an XML-based encoding of the information elements defined in the vCard specification has been defined and the name of that specification is xCard. Since the term vCard is more familiar to most readers we use the term xCard and vCard interchangeable but it would be accurate to use the term vCard only.

3. Data Structures

This section defines the following five data structures, each as a data block. For each block we define the MIME type, and the XML data structure. The five data structures are:

'Data Provider': This block supplies name and contact information for the entity that created the data. [Section 3.1](#) provides the details.

'Service Information': This block supplies information about the service. The description can be found in [Section 3.2](#).

'Device Information': This block supplies information about the device placing the call. Device information can be found in [Section 3.3](#).

'Owner/Subscriber': This block supplies information about the owner of the device or about the subscriber. Details can be found in [Section 3.4](#).

'Comment': This block provides a way to supply free form human readable text to the PSAP or emergency responders. This simple structure is defined in [Section 3.5](#).

Note that the xCard format is re-used in some of the data structures to provide contact information. In an xCard there is no way to specify a "main" telephone number. These numbers are useful to emergency responders who are called to a large enterprise. This document adds a new property value to the "tel" property of the TYPE parameter called "main". It can be used in any xCard in additional data.

3.1. Data Provider Information

This block is intended to be provided by any service provider in the path of the call or the access network provider. It includes identification and contact information. This block SHOULD be provided by every service provider in the call path, and by the

access network provider. Devices MAY use this block to provide identifying information. The MIME subtype is "application/

emergencyCall.ProviderInfo+xml".

3.1.1. Data Provider String

Data Element: Data Provider String

Use: Required

XML Element: <DataProviderString>

Description: This is a plain language string suitable for displaying the name of the service provider that created the additional data structure. If the device created the structure the value is identical to the contact header in the SIP INVITE.

Reason for Need: Inform the call taker of the identity of the entity providing the additional call data structure.

How Used by Call Taker: Allows the call taker to interpret the data in this structure. The source of the information often influences how the information is used, believed or verified.

3.1.2. Data Provider ID

Data Element: Data Provider ID

Use: Conditional. Must be provided if the service provider is located in a jurisdiction that maintains such ids. Devices are not required to provide it.

XML Element: <ProviderID>

Description: A jurisdiction specific code for the provider shown in the <DataProvidedBy> element that created the structure of the call. This data SHOULD be provided if the local jurisdiction maintains such an ID list. For example, in North America, this would be a "NENA Company ID". Devices SHOULD NOT use this element.

Reason for Need: Inform the call taker of the identity of the entity providing the additional call data structure.

How Used by Call Taker: Where jurisdictions have lists of providers the Data Provider ID can be useful.

3.1.3. Data Provider ID Series

Data Element: Data Provider ID Series

Use: Conditional. If Data Provider ID is provided, Data Provider ID

Series is required.

XML Element: <ProviderIDSeries>

Rosen, Tschofenig, MarshExpiresJanuaryW30, 2014

[Page 7]

Description: Identifies the issuer of the ProviderId. A registry will reflect the following valid entries:

- * NENA
- * EENA

Reason for Need: Identifies how to interpret the Data Provider ID.

How Used by Call Taker: Determines which provider ID registry to consult for more information

3.1.4. Type of Data Provider

Data Element: Type of Data Provider ID

Use: Conditional. If Data Provider ID is provided, Type of Data Provider ID is required.

XML Element: <TypeOfProviderID>

Description: Identifies the type of data provider id being supplied in the ProviderId data element. A registry with an initial set of values is shown in Figure 1.

Token	Description
Access Network Provider	Access network service provider
Service Provider	Calling or Origination telecom SP
Service Provider Subcontractor	A contractor to another kind of SP
Telematics Provider	A sensor based SP, especially vehicle based
Language Translation Provider	A spoken language translation SP
Expert Advice Provider	An SP giving expert advice
Emergency Modality Translation	An emergency call specific modality translation service e.g. for sign language
Relay Provider	A interpretation SP, for example, video relay for sign language interpreting
Other	Any other type of service provider

Reason for Need: Identifies what kind of data provider this is.

How Used by Call Taker: To decide who to contact when further information is needed

3.1.5. Data Provider Contact URI

Data Element: Data Provider Contact URI

Rosen, Tschofenig, MarshExpiresJanuaryW30, 2014

[Page 8]

Use: Required

XML Element: <ContactURI>

Description: For a service provider the contact SHOULD be a contact URI. This MUST be a SIP URI. If a telephone number is the contact address it should be provided in the form of sip:telephonenumber@serviceprovider:user=phone. If the call is from a device, this would reflect the contact information of the owner of the device. When provided by a service provider, this would be a URI to a 24/7 support organization tasked to provide PSAP support for this emergency call.

Reason for Need: Additional data providers may need to be contacted for error or other unusual circumstances.

How Used by Call Taker: To contact the supplier of the additional data for assistance in handling the call.

3.1.6. Data Provider Languages(s) Supported

Data Element: Data Provider Language(s) supported

Use: Conditional

XML Element: <Language>

Description: The language used by the entity at the Data Provider Contact URI as an alpha 2-character code as defined in ISO 639-1:2002 Codes for the representation of names of languages -- Part 1: Alpha-2 code Multiple instances of this element may occur. Order is significant; preferred language should appear first. This data is required if a Data Provider Contact URI is provided. The content must reflect the languages supported at the contact URI.

Reason for Need: Information needed to determine if emergency service authority can communicate with the service provider or if an interpreter will be needed.

How Used by Call Taker: If call taker cannot speak language(s) supported by the service provider, a translation service will need to be added to the conversation.

3.1.7. xCard of Data Provider

Data Element: xCard of Data Provider

Use: Optional

XML Element: <DataProviderContact>

Rosen, Tschofenig, MarshExpires1JanuaryW30, 2014

[Page 9]

Description: There are many fields in the xCard and the creator of the data structure is encouraged to provide as much information as they have available. N, ORG, ADR, TEL, EMAIL are suggested at a minimum. N should contain name of support group or device owner as appropriate. If more than one TEL property is provided, a parameter from the vCard Property Value registry MUST be specified on each TEL. For encoding of the xCard this specification uses the XML-based encoding specified in [[RFC6351](#)]. and is hereinafter referred to as "xCard"

Reason for Need: Information needed to determine additional contact information.

How Used by Call Taker: Assists call taker by providing additional contact information that may not be included in the SIP invite or the PIDF-LO.

[3.1.8.](#) Subcontractor Principal

Data Element: Subcontractor Principal

XML Element: <SubcontractorPrincipal>

Description: If the data provider is a subcontractor to another provider such as an access infrastructure provider or telematics provider, this element contains the DataProviderString of the service provider to indicate which provider the subcontractor is working for. This data is required if the Data Provider type is subcontractor.

Reason for Need: Identify the entity the subcontractor works for.

How Used by Call Taker: Allows the call taker to understand what the relationship between data providers and the service providers in the path of the call are.

[3.1.9.](#) Subcontractor Priority

Data Element: Subcontractor Priority

Use: Required

XML Element: <SubcontractorPriority>

Description: If the subcontractor should be contacted first, this element should have a "sub" value. If the access or origination service provider should be contacted first, this element should have a "main" value. This data is required if the Data Provider type is "subcontractor".

Reason for Need: Inform the call taker whether the network operator or the subcontractor should be contacted first if support is needed.

How Used by Call Taker: To decide which entity to contact first if assistance is needed.

3.1.10. emergencyCall.ProviderInfo Example


```
<?xml version="1.0" encoding="UTF-8"?>
<ad:emergencyCall.ProviderInfo
  xmlns:ad="urn:ietf:params:xml:ns:emergencyCall.ProviderInfo"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
  <ad:DataProviderString>Example VoIP Provider
</ad:DataProviderString>
  <ad:ProviderID>urn:nena:companyid:ID123</ad:ProviderID>
  <ad:ProviderIDSeries>NENA</ad:ProviderIDSeries>
  <ad:TypeOfProvider>Service Provider</ad:TypeOfProvider>
  <ad:ContactURI>sip:voip-provider@example.com</ad:ContactURI>
  <ad:Language>EN</ad:Language>
  <xc:DataProviderContact
    xmlns:xc="urn:ietf:params:xml:ns:vcard-4.0">
    <vcard>
      <fn><text>Hannes Tschofenig</text></fn>
      <n>
        <surname>Hannes</surname>
        <given>Tschofenig</given>
        <additional/>
        <prefix/>
        <suffix>Dipl. Ing.</suffix>
      </n>
      <bday><date>--0203</date></bday>
      <anniversary>
        <date-time>20090808T1430-0500</date-time>
      </anniversary>
      <gender><sex>M</sex></gender>
      <lang>
        <parameters><pref><integer>1</integer></pref>
        </parameters>
        <language-tag>de</language-tag>
      </lang>
      <lang>
        <parameters><pref><integer>2</integer></pref>
        </parameters>
        <language-tag>en</language-tag>
      </lang>
      <org>
        <parameters><type><text>work</text></type>
        </parameters>
        <text>Example VoIP Provider</text>
      </org>
      <adr>
        <parameters>
          <type><text>work</text></type>
          <label><text>Hannes Tschofenig
            Linnoitustie 6
```

Espoo , Finland
02600</text></label>
</parameters>
<pobox/>

```
<ext/>
<street>Linnoitustie 6</street>
<locality>Espoo</locality>
<region>Uusimaa</region>
<code>02600</code>
<country>Finland</country>
</adr>
<tel>
  <parameters>
    <type>
      <text>work</text>
      <text>voice</text>
    </type>
  </parameters>
  <uri>tel:+358 50 4871445</uri>
</tel>
<email>
  <parameters><type><text>work</text></type>
</parameters>
  <text>hannes.tschofenig@nsn.com</text>
</email>
<geo>
  <parameters><type><text>work</text></type>
</parameters>
  <uri>geo:60.210796,24.812924</uri>
</geo>
<key>
  <parameters><type><text>home</text></type>
</parameters>
  <uri>
http://www.tschofenig.priv.at/key.asc
  </uri>
</key>
<tz><text>Finland/Helsinki</text></tz>
<url>
  <parameters><type><text>home</text></type>
</parameters>
  <uri>http://www.tschofenig.priv.at</uri>
</url>
</vcard>
</xc:DataProviderContact>
</ad:emergencyCall.ProviderInfo>
```

3.2. Service Information

This block describes the service that the service provider provides to the caller. It SHOULD be included by all SPs in the path of the call. The mime subtype is "application/emergencyCall.SvcInfo+xml".

3.2.1. Service Environment

Data Element: Service Environment

Use: Required

Rosen, Tschofenig, MarshExpiresJanuary 30, 2014

[Page 13]

XML Element: <SvcEnvironment>

Description: This element defines whether a call is from a business or residence caller. Currently, the only valid entries are 'Business' or 'Residence'.

Reason for Need: To assist in determining equipment and manpower requirements.

How Used by Call Taker: Information may be used to assist in determining equipment and manpower requirements for emergency responders. As the information is not always available, and the registry is not all encompassing, this is at best advisory information, but since it mimics a similar capability in some current emergency calling systems, it is known to be valuable. The service provider uses its best information (such as a rate plan, facilities used to deliver service or service description) to determine the information and is not responsible for determining the actual characteristics of the location where the call originates from.

3.2.2. Service Delivered by Provider to End User

Data Element: Service Delivered by Provider to End User

Use: Required

XML Element: <SvcDelByProvider>

Description: This defines the type of service the end user has subscribed to. The implied mobility of this service cannot be relied upon. A registry with an initial set of values is defined in Figure 3.

Name	Description
Wrless	Wireless Telephone Service: Includes
	Satellite, CDMA, GSM, Wi-Fi, WiMAX,
	LTE (Long Term Evolution)
Coin	Fixed Public Pay/Coin telephones: Any
	coin or credit card operated device
1way	One way outbound service
Prison	Inmate call/service
Temp	Soft dialtone/quick service/warm
	disconnect/suspended
MLTS	Multi-line telephone system: Includes
	all PBX, Centrex, key systems,
	Shared Tenant Service
SenseU	Sensor, unattended: Includes devices
	that generate DATA ONLY. This is
	one-way information exchange and
	there will be no other form of
	communication
SenseA	Sensor, attended: Includes devices
	that are supported by a monitoring
	service provider or automatically
	open a two-way communication path
POTS	Wireline: Plain Old Telephone Service
VOIP	VoIP Telephone Service: A type of
	service that offers communication
	over internet protocol, such as Fixed
	Nomadic, Mobile, ...
Remote	Off premise extension
Relay	Relay Service: a type of service where
	there is a human 3rd party agent who
	provides some kind of additional
	assistance to the caller. Includes
	sign language relay and telematics
	services which provide a service
	assistant on the call.

More than one value MAY be returned. For example, a VoIP inmate telephone service is a reasonable combination.

Reason for Need: Knowing the type of service may assist the PSAP with the handling of the call.

How Used by Call Taker: Call takers often use this information to determine what kinds of questions to ask callers, and how much to rely on supportive information. An emergency call from a prison

is treated differently than a call from a sensor device. As the information is not always available, and the registry is not all encompassing, this is at best advisory information, but since it mimics a similar capability in some current emergency calling systems, it is known to be valuable.

3.2.3. Service Mobility Environment

Data Element: Service Mobility Environment

Use: Required

XML Element: <SvcMobility>

Description: This provides the service providers view of the mobility of the caller. As the service provider may not know the characteristics of the actual access network used, the value not be relied upon. A registry will reflect the following initial valid entries:

- * Mobile: the device should be able to move at any time
- * Fixed: the device is not expected to move unless the service is relocated
- * Nomadic: the device is not expected to change its point of attachment while on a call
- * Unknown: no information is known about the service mobility environment for the device

Reason for Need: Knowing the service provider's belief of mobility may assist the PSAP with the handling of the call.

How Used by Call Taker: To determine whether to assume the location of the caller might change.

3.2.4. emergencyCall.SvcInfo Example

```
<?xml version="1.0" encoding="UTF-8"?>
<svc:emergencyCall.SvcInfo
  xmlns:svc="urn:ietf:params:xml:ns:emergencyCall.SvcInfo"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
  <svc:SvcEnvironment>Business</svc:SvcEnvironment>
  <svc:SvcDelByProvider>MLTS</svc:SvcDelByProvider>
  <svc:SvcMobility>Fixed</svc:SvcMobility>
</svc:emergencyCall.SvcInfo>
```

3.3. Device Information

This block provides information about the device used to place the

call. It should be provided by any service provider that knows what device is being used, and by the device itself. The mime subtype is "application/emergencyCall.DevInfo+xml".

3.3.1. Device Classification

Data Element: Device Classification

Use: Optional

XML Element: <DeviceClassification>

Description: This data element defines the kind of device making the emergency call. If the device provides the data structure, the device information SHOULD be provided. If the service provider provides the structure and it knows what the device is, the service provider SHOULD provide the device information. Often the carrier does not know what the device is. It is possible to receive two Additional Data Associated with a Call data structures, one created by the device and one created by the service provider. This information describes the device, not how it is being used. This data element defines the kind of device making the emergency call. The registry with the initial set of values is shown in Figure 5.

Token	Description
Cordless	Cordless handset
Fixed	Fixed phone
Mobile	Mobile handset
ATA	analog terminal adapter
Satphone	Satellite phone
FSense	Stationary computing device (alarm system, data sensor)
Guard	Guardian devices
Desktop	Desktop PC
Laptop	Laptop computing device
Tablet	Tablet computing device
Alarm	Alarm system
MSense	Mobile Data sensor
Beacon	Personal beacons (spot)
Auto	Auto telematics
Truck	Truck telematics
Farm	Farm equipment telematics
Marine	Marine telematics
PDA	Personal digital assistant
PND	Personal navigation device)
SmrtPhn	Smart phone
Itab	Internet tablet
Game	Gaming console
Video	Video phone
Text	Other text device
NA	Not Available

Reason for Need: The device classification implies the capability of the calling device and assists in identifying the meaning of the emergency call location information that is being presented. For example, does the device require human intervention to initiate a call or is this call the result of programmed instructions? Does the calling device have the ability to update location or condition changes? Is this device interactive or a one-way reporting device?

How Used by Call Taker: May assist with location of caller. For example, a cordless handset may be outside or next door. May provide the calltaker some context about the caller, the capabilities of the device used for the call or the environment the device is being used in.

[3.3.2.](#) Device Manufacturer

Data Element: Device Manufacturer

Use: Optional

Rosen, Tschofenig, MarshExpiresJanuary 30, 2014

[Page 18]

XML Element: <DeviceMfgr>

Description: The plain language name of the manufacturer of the device.

Reason for Need: Used by PSAP management for post-mortem investigation/resolution.

How Used by Call Taker: Probably not used by the calltaker, but by PSAP management.

3.3.3. Device Model Number

Data Element: Device Model Number

Use: Optional

XML Element: <DeviceModelNr>

Description: Model number of the device.

Reason for Need: Used by PSAP management for after action investigation/resolution.

How Used by Call Taker: Probably not used by the calltaker, but by PSAP management.

3.3.4. Unique Device Identifier

Data Element: Unique Device Identifier

Use: Optional

XML Element: <UniqueDeviceID>

Description: String that identifies the specific device making the call or creating an event.

Reason for Need: Uniquely identifies the device as opposed to any signaling identifiers encountered in the call signaling stream.

How Used by Call Taker: Probably not used by the calltaker they would need to refer to management for investigation.

3.3.5. Type of Device Identifier

Data Element: Type of Device Identifier

Use: Conditional: must be provided if the DeviceID is provided

XML Element: <TypeOfDeviceID>

Description: Identifies the type of device identifier being generated in the unique device identifier data element. A registry with an initial set of values can be seen in Figure 6.

Token	Description
MEID	Mobile Equipment Identifier (CDMA)
ESN	Electronic Serial Number(GSM)
MAC	Media Access Control Address (IEEE)
WiMAX	Device Certificate Unique ID
IMEI	International Mobile Equipment ID (GSM)
UDI	Unique Device Identifier
RFID	Radio Frequency Identification
SN	Manufacturer Serial Number

Reason for Need: Identifies how to interpret the Unique Device Identifier.

How Used by Call Taker: Additional information that may be used to assist with call handling.

3.3.6. Device/Service Specific Additional Data Structure

Data Element: Device/service specific additional data structure

Use: Optional

XML Element: <DeviceSpecificData>

Description: A URI representing additional data whose schema is specific to the device or service which created it. An example is the VEDs structure for a vehicle telematics device. The URI, when dereferenced, MUST yield a data structure defined by the Device/service specific additional data type value. Different data may be created by each classification; e.g., telematics creates VEDS data set.

Reason for Need: Provides device/service specific data that may be used by the call taker and/or responders.

How Used by Call Taker: Provide information to guide call takers to select appropriate responders, give appropriate pre-arrival instructions to callers, and advise responders of what to be

prepared for. May be used by responders to guide assistance provided.

3.3.7. Device/Service Specific Additional Data Structure Type

Data Element: Type of Device/service specific additional data structure

Use: Conditional. MUST be provided when Device/service specific additional URI is provided

XML Element: <DeviceSpecificType>

Description: Value from a registry defined by this document to describe the type of data that can be retrieved from the Device/service specific additional data structure. Initial values are:

- * IEEE 1512 - USDOT Model for traffic incidents
- * VEDS

Reason for Need: This data element allows identification of externally defined schemas, which may have additional data that may assist in emergency response.

How Used by Call Taker: This data element allows the end user (calltaker or first responder) to know what type of additional data may be available to aid in providing the needed emergency services.

Note: Information which is specific to a location or a caller (person) should not be placed in this section.

3.3.8. Choosing between defining a new type of block or new type of device/service specific additional data

For devices that have device or service specific data, there are two choices to carry it. A new block can be defined, or the device/service specific additional data URL the DevInfo block can be used and a new type for it defined. The data passed would likely be the same in both cases. Considerations for choosing which mechanism to register under include:

Applicability: Information which will be carried by many kinds of devices or services are more appropriately defined as separate blocks.

Privacy: Information which may contain private data may be better sent in the DevInfo block, rather than a new block so that implementations are not tempted to send the data by value, and

thus having more exposure to the data than forcing the data to be retrieved via the URL in DevInfo.

Size: Information which may be very may be better sent in the DevInfo block, rather than a new block so that implementations are not tempted to send the data by value. Conversely, data which is small may best be sent in a separate block so that it can be sent by value

Availability of a server: Providing the data via the device block requires a server be made available to retrieve the data. Providing the data via new block allows it to be sent by value (CID).

3.3.9. emergencyCall.DevInfo Example

```
<?xml version="1.0" encoding="UTF-8"?>
<svc:emergencyCall.DevInfo
  xmlns:svc="urn:ietf:params:xml:ns:emergencyCall.DevInfo"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
  <svc:DeviceClassification>Fixed phone</svc:DeviceClassification>
  <svc:DeviceMfgr>Nokia</svc:DeviceMfgr>
  <svc:DeviceModelNr>Lumia 800</svc:DeviceModelNr>
  <svc:UniqueDeviceID>35788104</svc:UniqueDeviceID>
  <svc:TypeOfDeviceID>IMEI</svc:TypeOfDeviceID>
</svc:emergencyCall.DevInfo>
```

3.4. Owner/Subscriber Information

This block describes the owner of the device (if provided by the device) or the subscriber information, if provided by a service provider. The contact location is not necessarily the location of the caller or incident, but is rather the nominal contact address. The mime subtype is "application/emergencyCall.Subscriber+xml".

3.4.1. xCard for Subscriber's Data

Data Element: xCARD for Subscriber's Data

Use: Conditional: Some services (e.g., prepaid phones, initialized phones, etc.) may not have this information.

XML Element: <SubscriberData>

Description: Information known by the service provider or device about the subscriber; e.g., Name, Address, Individual Telephone Number, Main Telephone Number and any other data. N, ORG (if appropriate), ADR, TEL, EMAIL are suggested at a minimum. If more than one TEL property is provided, a parameter from the vCard

Property Value registry MUST be specified on each TEL.

Reason for Need: When the caller is unable to provide information,
this data may be used to obtain it

Rosen, Tschofenig, MarshExpiresJanuary 30, 2014

[Page 22]

How Used by Call Taker: Obtaining critical information about the caller and possibly the location when it is not able to be obtained otherwise.

3.4.2. emergencyCall.SubInfo Example


```
<?xml version="1.0" encoding="UTF-8"?>
<ad:emergencyCall.SubInfo
  xmlns:ad="urn:ietf:params:xml:ns:emergencyCall.SubInfo"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
  <xc:SubscriberData xmlns:xc="urn:ietf:params:xml:ns:vcard-4.0">
    <vcards xmlns="urn:ietf:params:xml:ns:vcard-4.0">
      <vcard>
        <fn><text>Simon Perreault</text></fn>
        <n>
          <surname>Perreault</surname>
          <given>Simon</given>
          <additional/>
          <prefix/>
          <suffix>ing. jr</suffix>
          <suffix>M.Sc.</suffix>
        </n>
        <bday><date>-0203</date></bday>
        <anniversary>
          <date-time>20090808T1430-0500</date-time>
        </anniversary>
        <gender><sex>M</sex></gender>
        <lang>
          <parameters><pref><integer>1</integer></pref>
          </parameters>
          <language-tag>fr</language-tag>
        </lang>
        <lang>
          <parameters><pref><integer>2</integer></pref>
          </parameters>
          <language-tag>en</language-tag>
        </lang>
        <org>
          <parameters><type><text>work</text></type>
          </parameters>
          <text>Viagenie</text>
        </org>
        <adr>
          <parameters>
            <type><text>work</text></type>
            <label><text>Simon Perreault
              2875 boul. Laurier, suite D2-630
              Quebec, QC, Canada
              G1V 2M2</text></label>
          </parameters>
          <pobox/>
          <ext/>
          <street>2875 boul. Laurier, suite D2-630</street>
```

<locality>Quebec</locality>
<region>QC</region>
<code>G1V 2M2</code>
<country>Canada</country>

Rosen, Tschofenig, MarshExpires1January 30, 2014

[Page 24]

```
</adr>
<tel>
  <parameters>
    <type>
      <text>work</text>
      <text>voice</text>
    </type>
  </parameters>
  <uri>tel:+1-418-656-9254;ext=102</uri>
</tel>
<tel>
  <parameters>
    <type>
      <text>work</text>
      <text>text</text>
      <text>voice</text>
      <text>cell</text>
      <text>video</text>
    </type>
  </parameters>
  <uri>tel:+1-418-262-6501</uri>
</tel>
<email>
  <parameters><type><text>work</text></type>
</parameters>
  <text>simon.perreault@viagenie.ca</text>
</email>
<geo>
  <parameters><type><text>work</text></type>
</parameters>
  <uri>geo:46.766336, -71.28955</uri>
</geo>
<key>
  <parameters><type><text>work</text></type>
</parameters>
  <uri>
http://www.viagenie.ca/simon.perreault/simon.asc
  </uri>
</key>
<tz><text>America/Montreal</text></tz>
<url>
  <parameters><type><text>home</text></type>
</parameters>
  <uri>http://nomis80.org</uri>
</url>
</vcard>
</vcards>
</xc:SubscriberData>
</ad:emergencyCall.SubInfo>
```

3.5. Comment

Rosen, Tschofenig, MarshExpiresJanuary 30, 2014

[Page 25]

This block provides a mechanism for the data provider to supply extra, human readable information to the PSAP. It is not intended for a general purpose extension mechanism. The mime subtype is "application/emergencyCall.Comment+xml"

3.5.1. Comment

Data Element: EmergencyCall.Comment

Use: Optional

XML Element: <Comment>

Description: Human readable text providing additional information to the PSAP staff.

Reason for Need: Explanatory information for values in the data structure

How Used by Call Taker: To interpret the data provided

3.5.2. emergencyCall.Comment Example

```
<?xml version="1.0" encoding="UTF-8"?>
<sub:emergencyCall.Comment
  xmlns:sub="urn:ietf:params:xml:ns:emergencyCall.Comment"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
  <sub:Comment xml:lang="en">This is an example text.</sub:Comment>
</sub:emergencyCall.Comment>
```

4. Transport

This section defines how to convey additional data to an emergency service provider. Two different means are specified: the first uses the call signaling; the second uses the <provided-by> element of a PIDF-LO [[RFC4119](#)].

1. First, the ability to embed a Uniform Resource Identifier (URI) in an existing SIP header field, the Call-Info header, is defined. The URI points to the additional data structure. The Call-Info header is specified in [Section 20.9 of \[RFC3261\]](#). This document adds a new compound token starting with the value 'emergencyCallData' for the Call-Info "purpose" parameter. If the "purpose" parameter is set to a value starting with 'emergencyCallData', then the Call-Info header contains either an HTTPS URL pointing to an external resource or a CID (content indirection) URI that allows the data structure to be placed in the body of the SIP message. The "purpose" parameter also indicates the kind of data (by its MIME type) that is available at the URI. As the data is conveyed using a URI in the SIP signaling, the data itself may reside on an external resource, or may be contained within the body of the SIP message. When the URI refers to data at an external resource, the data is said to be passed by reference. When the URI refers to data contained within the body of the SIP message, the data is said to be passed by value. A PSAP or emergency responder is able to examine the type of data provided and selectively inspect the data it is interested in, while forwarding all of it (the values or references) to downstream entities. To be conveyed in a SIP body, additional data about a call is defined as a series of MIME objects. Each block defined in this document is an XML data structure identified by its MIME type. (Blocks defined by others may be encoded in XML or not, as identified by their MIME registration.) As usual, whenever more than one MIME part is included in the body of a message, MIME-multipart (i.e., 'multipart/mixed') encloses them all. This document defines a set of XML schemas and MIME types used for each block defined here. When additional data is passed by value in the SIP signaling, each CID URL points to one block in the body. Multiple URIs are used within a Call-Info header field (or multiple Call-Info header fields) to point to multiple blocks. When additional data is provided by reference (in SIP signaling or Provided-By), each HTTPS URL references one block; the data is retrieved with an HTTPS GET operation, which returns one of the blocks as an object (the blocks defined here are returned as XML objects).

2. Second, the ability to embed additional data structures in the <provided-by> element of a PIDF-LO [[RFC4119](#)] is defined. Besides a service provider in the call path, the access network provider may also have similar information that may be valuable to the PSAP. The access network provider may provide location in the form of a PIDF-LO from a location server via a location configuration protocol. The data structures described in this document are not specific to the location itself, but rather provides descriptive information having to do with the immediate circumstances about the provision of the location (who the access network is, how to contact that entity, what kind of service the access network provides, subscriber information, etc.). This data is similar in nearly every respect to the data known by service providers in the path of the call. When the access network provider and service provider are separate entities, the access network does not participate in the application layer signaling (and hence cannot add a Call-Info header field to the SIP message), but may provide location information to assist in locating the caller's device. The <provided-by> element of the PIDF-LO is a mechanism for the access network provider to supply the information about the entity or organization that supplied this location information. For this reason, this document describes a namespace per [RFC 4119](#) for inclusion in the <provided-by> element of a PIDF-LO for adding information known to the access network provider.

One or more blocks of data registered in the Emergency Call Additional Data registry, as defined in [Section 9.1](#), may be included or referenced in the SIP signaling (using the Call-Info header field) or in the <provided-by> element of a PIDF-LO. Every block must be one of the types in the registry. Since the data of an emergency call may come from multiple sources, the data itself needs information describing the source. Consequently, each entity adding additional data MUST supply the "Data Provider" block. All other blocks are optional, but each entity SHOULD supply any blocks where it has at least some of the information in the block.

[4.1.1. Transmitting Blocks using the Call-Info Header](#)

A URI to a block MAY be inserted in a SIP request or response method (most often INVITE or MESSAGE) with a Call-Info header field containing a purpose value starting with 'emergencyCallData' and the type of data available at the URI. The type of data is denoted by including the root of the MIME type (not including the 'emergencyCall' prefix and any suffix such as '+xml') with a '.' separator. For example, when referencing a block with MIME type 'application/emergencyCall.ProviderInfo+xml', the 'purpose' parameter is set to 'emergencyCallData.ProviderInfo'. An example "Call-Info"

header field for this would be:

Call-Info: <https://www.example.com/23sedde3>;
purpose="emergencyCallData.ProviderInfo"

Rosen, Tschofenig, MarshExpires1January 30, 2014

[Page 28]

A Call-info header with a purpose value starting with 'emergencyCallData' MUST only be sent on an emergency call, which can be ascertained by the presence of an emergency service urn in a Route header of a SIP message.

If the data is provided by reference, an HTTPS URI MUST be included and consequently Transport Layer Security (TLS) protection is applied for protecting the retrieval of the information.

The data may also be supplied by value in a SIP message. In this case, Content Indirection (CID) [[RFC2392](#)] is used, with the CID URL referencing the MIME body part.

More than one Call-Info header with a purpose value starting with 'emergencyCallData' can be expected, but at least one MUST be provided. The device MUST provide one if it knows no service provider is in the path of the call. The device MAY insert one if it uses a service provider. Any service provider in the path of the call MUST insert its own. For example, a device, a telematics service provider in the call path, as well as the mobile carrier handling the call will each provide one. There may be circumstances where there is a service provider who is unaware that the call is an emergency call and cannot reasonably be expected to determine that it is an emergency call. In that case, that service provider is not expected to provide emergencyCallData.

[4.2.](#) Transmitting Blocks by Reference using the Provided-By Element

The 'emergencyCallDataReference' element is used to transmit an additional data block by reference within a 'Provided-By' element of a PIDF-LO. The 'emergencyCallDataReference' element has two attributes: 'ref' to specify the URL, and 'purpose' to indicate the type of data block referenced. The value of 'ref' is an HTTPS URL that resolves to a data structure with information about the call. The value of 'purpose' is the same as used in a 'Call-Info' header field (as specified in [Section 4.1](#)).

For example, to reference a block with MIME type 'application/emergencyCall.ProviderInfo+xml', the 'purpose' parameter is set to 'emergencyCallData.ProviderInfo'. An example 'emergencyCallDataReference' element for this would be:

```
<emergencyCallDataReference ref="https://www.example.com/23sedde3"
  purpose="emergencyCallData.ProviderInfo"/>
```

[4.3.](#) Transmitting Blocks by Value using the Provided-By Element

It is RECOMMENDED that access networks supply the data specified in this document by reference, but they MAY provide the data by value.

The 'emergencyCallDataValue' element is used to transmit an additional data block by value within a 'Provided-By' element of a PIDF-LO. The 'emergencyCallDataValue' element has one attribute: 'purpose' to indicate the type of data block contained. The value of 'purpose' is the same as used in a 'Call-Info' header field (as specified in [Section 4.1](#), and in [Section 4.1](#)). The same XML structure as would be contained in the corresponding MIME type body part is placed inside the 'emergencyCallDataValue' element.

For example:

```
<provided-by
  xmlns="urn:ietf:params:xml:ns:emergencyCallAddlData">
  <emergencyCallData>
    <byRef purpose="emergencyCallData.SvcInfo"
      ref="https://example.com/ref2"/>
    <sub:emergencyCall.Comment
      xmlns:sub="urn:ietf:params:xml:ns:emergencyCall.Comment">
      <sub:Comment xml:lang="en">This is an example text.
    </sub:Comment>
    </sub:emergencyCall.Comment>
  </emergencyCallData>
  <emergencyCallDataValue
    purpose="emergencyCallData.ProviderInfo">
    <ProviderID>Test</ProviderID>
    <ProviderIDSeries>NENA</ProviderIDSeries>
    <TypeOfProviderID>Access Infrastructure Provider
  </TypeOfProviderID>
    <ContactURI>sip:15555550987@burf.example.com;user=phone
    </ContactURI>
  </emergencyCallDataValue>
</provided-by>
```

[4.4.](#) The Content-Disposition Parameter

[RFC 5621](#) [[RFC5621](#)] discusses the handling of message bodies in SIP. It updates and clarifies handling originally defined in [RFC 3261](#) [[RFC3261](#)] based on implementation experience. While [RFC 3261](#) did not mandate support for 'multipart' message bodies 'multipart/mixed' MIME bodies are, however, used by many extensions (including additional data) today. For example, adding a PIDF-LO, SDP, and additional data in body of a SIP message requires a 'multipart' message body.

[RFC 3204](#) [[RFC3204](#)] and [RFC 3459](#) [[RFC3459](#)] define the 'handling' parameter for the Content-Disposition header field. These RFCs describe how a UAS reacts if it receives a message body whose content type or disposition type it does not understand. If the 'handling' parameter has the value "optional", the UAS ignores the message body. If the 'handling' parameter has the value "required", the UAS returns a 415 (Unsupported Media Type) response. The 'by-reference' disposition type allows a SIP message to contain a reference to the body part, and the SIP UA processes the body part according to the reference. This is the case for the Call-info header containing a Content Indirection (CID) URL.

As an example, a SIP message indicates the Content-Disposition parameter in the body of the SIP message as shown in Figure 11.

```
Content-Type: application/sdp

...Omit Content-Disposition here; defaults are ok
...SDP goes here

--boundary1

Content-Type: application/pidf+xml
Content-ID: <target123@atlanta.example.com>
Content-Disposition: by-reference;handling=optional

...PIDF-LO goes here

--boundary1--

Content-Type: application/emergencyCall.ProviderInfo+xml
Content-ID: <1234567890@atlanta.example.com>
Content-Disposition: by-reference;handling=optional

...Additional data goes here

--boundary1--
```

5. Examples

This section provides three examples of communicating additional data. In Figure 12 additional data is communicated in a SIP INVITE per value. In Figure 13 we illustrate how additional data is added by a SIP proxy per reference. Finally, an example for including additional data in the <Provided-By> element of a PIDF-LO is illustrated.


```
INVITE sip:bob@biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS pc33.atlanta.example.com;branch=z9hG4bK74bf9
Max-Forwards: 70
To: Bob <sip:bob@biloxi.example.com>
From: Alice <sip:alice@atlanta.example.com>;tag=9fxced76s1
Call-ID: 3848276298220188511@atlanta.example.com
Call-Info: <http://www.example.com/alice/photo.jpg> ;purpose=icon,
  <http://www.example.com/alice/> ;purpose=info,
  <cid:1234567890@atlanta.example.com>
  ;purpose=emergencyCallData.ProviderInfo
Geolocation: <cid:target123@atlanta.example.com>
Geolocation-Routing: no
Accept: application/sdp, application/pidf+xml,
  application/emergencyCallProviderinfo+xml
CSeq: 31862 INVITE
Contact: <sip:alice@atlanta.example.com>
Content-Type: multipart/mixed; boundary=boundary1

Content-Length: ...

--boundary1

Content-Type: application/sdp

...SDP goes here

--boundary1

Content-Type: application/pidf+xml
Content-ID: <target123@atlanta.example.com>
Content-Disposition: by-reference;handling=optional

...PIDF-LO goes here

--boundary1--

Content-Type: application/emergencyCall.ProviderInfo+xml
Content-ID: <1234567890@atlanta.example.com>
Content-Disposition: by-reference;handling=optional

...Additional data goes here

--boundary1--
```



```
INVITE sip:bob@biloxi.example.com SIP/2.0
Via: SIP/2.0/TLS pc33.atlanta.example.com;branch=z9hG4bK74bf9
Max-Forwards: 70
To: Bob <sip:bob@biloxi.example.com>
From: Alice <sip:alice@atlanta.example.com>;tag=9fxced76s1
Call-ID: 3848276298220188511@atlanta.example.com
Call-Info: <http://www.example.com/alice/photo.jpg> ;purpose=icon,
  <http://www.example.com/alice/> ;purpose=info,
  <https://www.example.com/abc123456/>
  ;purpose=emergencyCallData.ProviderInfo
Geolocation: <cid:target123@atlanta.example.com>
Geolocation-Routing: no
Accept: application/sdp, application/pidf+xml,
  application/emergencyCallProviderinfo+xml
CSeq: 31862 INVITE
Contact: <sip:alice@atlanta.example.com>
Content-Type: multipart/mixed; boundary=boundary1

Content-Length: ...

--boundary1

Content-Type: application/sdp

...SDP goes here

--boundary1

Content-Type: application/pidf+xml
Content-ID: <target123@atlanta.example.com>
Content-Disposition: by-reference;handling=optional

...PIDF-LO goes here

--boundary1--
```



```
<?xml version="1.0" encoding="UTF-8"?>
<presence xmlns="urn:ietf:params:xml:ns:pidf"
  xmlns:gp="urn:ietf:params:xml:ns:pidf:geopriv10"
  xmlns:gbp="urn:ietf:params:xml:ns:pidf:geopriv10:basicPolicy"
  xmlns:dm="urn:ietf:params:xml:ns:pidf:data-model"
  entity="pres:alice@atlanta.example.com">
  <dm:device id="target123-1">
    <gp:geopriv>
      <gp:location-info>
        <civicAddress
          xmlns="urn:ietf:params:xml:ns:pidf:geopriv10:civicAddr">
          <country>AU</country>
          <A1>NSW</A1>
          <A3>Wollongong</A3>
          <A4>North Wollongong</A4>
          <RD>Flinders</RD>
          <STS>Street</STS>
          <RDBR>Campbell Street</RDBR>
          <LMK>Gilligan's Island</LMK>
          <LOC>Corner</LOC>
          <NAM>Video Rental Store</NAM>
          <PC>2500</PC>
          <ROOM>Westerns and Classics</ROOM>
          <PLC>store</PLC>
          <POBOX>Private Box 15</POBOX>
        </civicAddress>
      </gp:location-info>
      <gp:usage-rules>
        <gbp:retransmission-allowed>true
      </gbp:retransmission-allowed>
        <gbp:retention-expiry>2013-07-10T20:00:00Z
      </gbp:retention-expiry>
      </gp:usage-rules>
      <gp:method>802.11</gp:method>
      <provided-by
        xmlns="urn:ietf:params:xml:ns:pidf:geopriv10:emergencyCallData">
        <emergencyCallDataReference purpose="emergencyCallData.SvcInfo"
          ref="https://example.com/ref2"/>
        <emergencyCallDataValue>
          <emergencyCall.ProviderInfo
            xmlns="urn:ietf:params:xml:ns:emergencyCall.ProviderInfo">
            <DataProviderString>University of California, Irvine
          </DataProviderString>
            <ProviderID>urn:nena:companyid:uci</ProviderID>
            <ProviderIDSeries>NENA</ProviderIDSeries>
          </emergencyCall.ProviderInfo>
        </emergencyCallDataValue>
      </provided-by>
    </dm:device>
  </presence>
```

```
<TypeOfProvider>Other</TypeOfProvider>  
<ContactURI>tel:+1 9498245222</ContactURI>  
<Language>EN</Language>  
</emergencyCall.ProviderInfo>
```

```
<emergencyCall.Comment
  xmlns="urn:ietf:params:xml:ns:emergencyCall.Comment">
  <Comment xml:lang="en">This is an example text.</Comment>
</emergencyCall.Comment>

</emergencyCallDataValue>
</provided-by>
</gp:geopriv>
<dm:deviceID>mac:1234567890ab</dm:deviceID>
<dm:timestamp>2013-07-09T20:57:29Z</dm:timestamp>
</dm:device>
</presence>
```

6. XML Schemas

This section defines the XML schemas of the five data blocks. Additionally, the Provided-By schema is specified.

6.1. emergencyCall.ProviderInfo XML Schema


```
<?xml version="1.0"?>
<xs:schema
  targetNamespace="urn:ietf:params:xml:ns:emergencyCall.ProviderInfo"
  xmlns:xs="http://www.w3.org/2001/XMLSchema"
  xmlns:pi="urn:ietf:params:xml:ns:emergencyCall.ProviderInfo"
  xmlns:xml="http://www.w3.org/XML/1998/namespace"
  xmlns:xc="urn:ietf:params:xml:ns:vcard-4.0"
  elementFormDefault="qualified"
  attributeFormDefault="unqualified">

  <xs:import namespace="http://www.w3.org/XML/1998/namespace"
    schemaLocation="http://www.w3.org/2001/xml.xsd"/>

  <xs:import namespace="urn:ietf:params:xml:ns:vcard-4.0">

    <xs:simpleType name="iso3166a2">
      <xs:restriction base="xs:token">
        <xs:pattern value="[A-Z]{2}"/>
      </xs:restriction>
    </xs:simpleType>

    <xs:element
      name="emergencyCall.ProviderInfo"
      type="pi:ProviderInfoType"/>

    <xs:complexType name="ProviderInfoType">
      <xs:sequence>
        <xs:element name="DataProviderString"
          type="xs:string" minOccurs="1" maxOccurs="1"/>
        <xs:element name="ProviderID"
          type="xs:string" minOccurs="0" maxOccurs="1"/>
        <xs:element name="ProviderIDSeries"
          type="xs:string" minOccurs="0" maxOccurs="1"/>
        <xs:element name="TypeOfProvider"
          type="xs:string" minOccurs="0" maxOccurs="1"/>
        <xs:element name="ContactURI" type="xs:anyURI"
          minOccurs="1" maxOccurs="1"/>
        <xs:element name="Language" type="pi:iso3166a2"
          minOccurs="0" maxOccurs="unbounded" />
        <xs:element name="DataProviderContact"
          type="xc:vcardType" minOccurs="0"
          maxOccurs="1"/>

        <xs:any namespace="##other" processContents="lax"
          minOccurs="0" maxOccurs="unbounded"/>
      </xs:sequence>
    </xs:complexType>
```

</xs:schema>

6.2. emergencyCall.SvcInfo XML Schema

Rosen, Tschofenig, MarshExpiresJanuary 30, 2014

[Page 36]

```
<?xml version="1.0"?>
<xs:schema
  targetNamespace="urn:ietf:params:xml:ns:emergencyCall.SvcInfo"
  xmlns:xs="http://www.w3.org/2001/XMLSchema"
  xmlns:svc="urn:ietf:params:xml:ns:emergencyCall.SvcInfo"
  xmlns:xml="http://www.w3.org/XML/1998/namespace"
  elementFormDefault="qualified" attributeFormDefault="unqualified">

  <xs:import namespace="http://www.w3.org/XML/1998/namespace"
    schemaLocation="http://www.w3.org/2001/xml.xsd"/>

  <xs:element name="emergencyCall.SvcInfo" type="svc:SvcInfoType"/>

  <xs:complexType name="SvcInfoType">
    <xs:sequence>
      <xs:element name="SvcEnvironment"
        type="xs:string" minOccurs="1" maxOccurs="1"/>
      <xs:element name="SvcDelByProvider"
        type="xs:string" minOccurs="1" maxOccurs="1"/>
      <xs:element name="SvcMobility"
        type="xs:string" minOccurs="1" maxOccurs="1"/>
      <xs:element name="Link"
        type="xs:string" minOccurs="0" maxOccurs="1"/>

      <xs:any namespace="##other" processContents="lax"
        minOccurs="0" maxOccurs="unbounded"/>
    </xs:sequence>
  </xs:complexType>
</xs:schema>
```

[6.3.](#) emergencyCall.DevInfo XML Schema


```
<?xml version="1.0"?>
<xs:schema
  targetNamespace="urn:ietf:params:xml:ns:emergencyCall.DevInfo"
  xmlns:xs="http://www.w3.org/2001/XMLSchema"
  xmlns:dev="urn:ietf:params:xml:ns:emergencyCall.DevInfo"
  xmlns:xml="http://www.w3.org/XML/1998/namespace"
  elementFormDefault="qualified" attributeFormDefault="unqualified">

  <xs:import namespace="http://www.w3.org/XML/1998/namespace"
    schemaLocation="http://www.w3.org/2001/xml.xsd"/>

  <xs:element name="emergencyCall.DevInfo" type="dev:DevInfoType"/>

  <xs:complexType name="DevInfoType">
    <xs:sequence>
      <xs:element name="DeviceClassification"
        type="xs:string" minOccurs="0" maxOccurs="1"/>
      <xs:element name="DeviceMfgr"
        type="xs:string" minOccurs="0" maxOccurs="1"/>
      <xs:element name="DeviceModelNr"
        type="xs:string" minOccurs="0" maxOccurs="1"/>
      <xs:element name="UniqueDeviceID"
        type="xs:string" minOccurs="0" maxOccurs="1"/>
      <xs:element name="TypeOfDeviceID"
        type="xs:string" minOccurs="0" maxOccurs="1"/>
      <xs:element name="DeviceSpecificData"
        type="xs:anyURI" minOccurs="0" maxOccurs="1"/>
      <xs:element name="DeviceSpecificType"
        type="xs:string" minOccurs="0" maxOccurs="1"/>

      <xs:any namespace="##other" processContents="lax"
        minOccurs="0" maxOccurs="unbounded"/>
    </xs:sequence>
  </xs:complexType>

</xs:schema>
```

[6.4.](#) emergencyCall.SubInfo XML Schema


```
<?xml version="1.0"?>
<xs:schema
  targetNamespace="urn:ietf:params:xml:ns:emergencyCall.SubInfo"
  xmlns:xs="http://www.w3.org/2001/XMLSchema"
  xmlns:sub="urn:ietf:params:xml:ns:emergencyCall.SubInfo"
  xmlns:xc="urn:ietf:params:xml:ns:vcard-4.0"
  xmlns:xml="http://www.w3.org/XML/1998/namespace"
  elementFormDefault="qualified" attributeFormDefault="unqualified">

  <xs:import namespace="http://www.w3.org/XML/1998/namespace"
    schemaLocation="http://www.w3.org/2001/xml.xsd"/>

  <xs:import namespace="urn:ietf:params:xml:ns:vcard-4.0"/>

  <xs:element name="emergencyCall.SubInfo" type="sub:SubInfoType"/>

  <xs:complexType name="SubInfoType">
    <xs:sequence>
      <xs:element name="SubscriberData" type="xc:vcardType"
        minOccurs="0" maxOccurs="1" />

      <xs:any namespace="##other" processContents="lax"
        minOccurs="0" maxOccurs="unbounded"/>
    </xs:sequence>
  </xs:complexType>

</xs:schema>
```

[6.5.](#) emergencyCall.Comment XML Schema


```
<?xml version="1.0"?>
<xs:schema
  targetNamespace="urn:ietf:params:xml:ns:emergencyCall.Comment"
  xmlns:xs="http://www.w3.org/2001/XMLSchema"
  xmlns:com="urn:ietf:params:xml:ns:emergencyCall.Comment"
  xmlns:xml="http://www.w3.org/XML/1998/namespace"
  elementFormDefault="qualified" attributeFormDefault="unqualified">

  <xs:import namespace="http://www.w3.org/XML/1998/namespace"
    schemaLocation="http://www.w3.org/2001/xml.xsd"/>

  <xs:element name="emergencyCall.Comment" type="com:CommentType"/>

  <xs:complexType name="CommentType">
    <xs:sequence>
      <xs:element name="Comment"
        type="com:CommentSubType" minOccurs="0"
        maxOccurs="unbounded"/>
      <xs:any namespace="##other" processContents="lax"
        minOccurs="0" maxOccurs="unbounded"/>
    </xs:sequence>
  </xs:complexType>

  <xs:complexType name="CommentSubType">
    <xs:simpleContent>
      <xs:extension base="xs:string">
        <xs:attribute ref="xml:lang"/>
      </xs:extension>
    </xs:simpleContent>
  </xs:complexType>

</xs:schema>
```

6.6. Provided-By XML Schema

This section defines the Provided-By schema.


```
<?xml version="1.0"?>
<xs:schema
  targetNamespace=
    "urn:ietf:params:xml:ns:pidf:geopriv10:emergencyCallData"
  xmlns:xs="http://www.w3.org/2001/XMLSchema"
  xmlns:ad="urn:ietf:params:xml:ns:pidf:geopriv10:emergencyCallData"
  xmlns:xml="http://www.w3.org/XML/1998/namespace"
  xmlns:pi="urn:ietf:params:xml:ns:emergencyCall.ProviderInfo"
  xmlns:svc="urn:ietf:params:xml:ns:emergencyCall.SvcInfo"
  xmlns:dev="urn:ietf:params:xml:ns:emergencyCall.DevInfo"
  xmlns:sub="urn:ietf:params:xml:ns:emergencyCall.SubInfo"
  xmlns:com="urn:ietf:params:xml:ns:emergencyCall.Comment"
  elementFormDefault="qualified" attributeFormDefault="unqualified">

  <xs:import namespace="urn:ietf:params:xml:ns:emergencyCall.Comment"/>
  <xs:import namespace="urn:ietf:params:xml:ns:emergencyCall.SubInfo"/>
  <xs:import namespace="urn:ietf:params:xml:ns:emergencyCall.DevInfo"/>
  <xs:import namespace="urn:ietf:params:xml:ns:emergencyCall.SvcInfo"/>
  <xs:import
namespace="urn:ietf:params:xml:ns:emergencyCall.ProviderInfo"/>

  <xs:element name="provided-by" type="ad:provided-by-Type"/>

  <xs:complexType name="provided-by-Type">
    <xs:sequence>

      <xs:element name="emergencyCallDataReference"
        type="ad:ByRefType"
        minOccurs="0" maxOccurs="unbounded"/>

      <xs:element name="emergencyCallDataValue"
        type="ad:emergencyCallDataValueType"
        minOccurs="0" maxOccurs="unbounded"/>

      <xs:any namespace="##other" processContents="lax"
        minOccurs="0" maxOccurs="unbounded"/>

    </xs:sequence>

  </xs:complexType>

  <!-- Additional Data By Reference -->

  <xs:complexType name="ByRefType">
    <xs:complexContent>
      <xs:restriction base="xs:anyType">
        <xs:sequence>
          <xs:any namespace="##other" minOccurs="0"
```

```
        maxOccurs="unbounded" processContents="lax"/>
</xs:sequence>
<xs:attribute name="purpose" type="xs:anyURI"
    use="required"/>
<xs:attribute name="ref" type="xs:anyURI"
```

```
        use="required"/>
      </xs:restriction>
    </xs:complexContent>
  </xs:complexType>

  <!-- Additional Data By Value -->

  <xs:complexType name="emergencyCallDataValueType">
    <xs:sequence>
      <xs:element name="emergencyCall.ProviderInfo"
        type="pi:ProviderInfoType"
        minOccurs="0" maxOccurs="unbounded"/>
      <xs:element name="emergencyCall.SvcInfo"
        type="svc:SvcInfoType"
        minOccurs="0" maxOccurs="unbounded"/>
      <xs:element name="emergencyCall.DevInfo"
        type="dev:DevInfoType"
        minOccurs="0" maxOccurs="unbounded"/>
      <xs:element name="emergencyCall.SubInfo"
        type="sub:SubInfoType"
        minOccurs="0" maxOccurs="unbounded"/>
      <xs:element name="emergencyCall.Comment"
        type="com:CommentType"
        minOccurs="0" maxOccurs="unbounded"/>

      <xs:any namespace="##other" processContents="lax"
        minOccurs="0" maxOccurs="unbounded"/>

    </xs:sequence>
  </xs:complexType>

</xs:schema>
```

7. Security Considerations

The information in this data structure will usually be considered private. HTTPS is specified to require the provider of the information to validate the credentials of the requester. While the creation of a PKI that has global scope may be difficult, the alternatives to creating devices and services that can provide critical information securely are more daunting. The provider may enforce any policy it wishes to use, but PSAPs and responder agencies should deploy a PKI so that providers of additional data can check the certificate of the client and decide the appropriate policy to enforce based on that certificate.

Ideally, the PSAP and emergency responders will be given credentials signed by an authority trusted by the data provider. In most circumstances, nationally recognized credentials would be sufficient, and if the emergency services arranges a PKI, data providers could be provisioned with the root CA public key for a given nation. Some nations are developing a PKI for this, and related, purposes. Since calls could be made from devices where the device and/or the service provider(s) are not local to the emergency authorities, globally recognized credentials are useful. This might be accomplished by extending the notion of the "forest guide" described in [\[RFC5222\]](#) to allow the forest guide to provide the credential of the PKI root for areas that it has coverage information for, but standards for such a mechanism are not yet available. In its absence, the data provider will need to obtain the root CA credentials for any areas it is willing to provide additional data by out of band means. With the credential of the root CA for a national emergency services PKI, the data provider server can validate the credentials of an entity requesting additional data by reference.

The data provider also needs a credential that can be verified by the emergency services to know that it is receiving data from the right server. The emergency authorities could provide credentials, distinguishable from credentials it provides to emergency responders and PSAPs, which could be used to validate data providers. Such credentials would have to be acceptable to any PSAP or responder that could receive a call with additional data supplied by that provider. This would be extensible to global credential validation using the forest guide as above. In the absence of such credentials, the emergency authorities could maintain a list of local data providers' credentials provided to it out of band. At a minimum, the emergency authorities could obtain a credential from the DNS entry of the domain in the Additional Data URI to at least validate that the server is known to the domain providing the URI.

Data provided by devices by reference have similar credential validation issues to service providers, and the solutions are the same.

8. Privacy Considerations

This document enables functionality for conveying additional information about the caller to the callee. Some of this information is personal data and therefore privacy concerns arise. There are a number of privacy concerns with regular real-time communication services that are also applicable to emergency calling. Data protection regulation world-wide has, however, decided to create exceptions for emergency services since the drawbacks of disclosing personal data in comparison to the benefit for the emergency caller

are often towards the latter. Hence, the data protection rights of individuals are often waived for emergency situations. There are, however, still various countries that offer some degree of anonymity for the caller towards PSAP call takers.

The functionality defined in this document, however, far exceeds the amount of information sharing found in the Plain old telephone system (POTS). For this reason there are additional privacy threats to consider, which are described in more detail in [I-D.iab-privacy-considerations].

Stored Data Compromise: First, there is an increased risk of stored data compromise since additional data is collected and stored in databases. Without adequate measures to secure stored data from unauthorized or inappropriate access at access network operators, service providers, end devices, as well as PSAPs individuals are exposed to potential financial, reputational, or physical harm.

Misattribution: If the personal data collected and conveyed is incorrect or inaccurate then this may lead to misattribution. Misattribution occurs when data or communications related to one individual are attributed to another.

Identification: By the nature of the additional data and its capability to provide much richer information about the caller, the call, and the location the calling party is identified in a much better way. Some users may feel uncomfortable with this degree of information sharing even in emergency services situations.

Secondary Use: Furthermore, there is the risk of secondary use. Secondary use is the use of collected information about an individual without the individual's consent for a purpose different from that for which the information was collected. The stated purpose of the additional data is for emergency services purposes but theoretically the same information could be used for any other call as well. Additionally, parties involved in the emergency call may retain the obtained information and may re-use it for other, non-emergency services purposes.

Disclosure: When the data defined in this document is not properly security (while in transit with traditional communication security techniques, and while at rest using access control mechanisms) there is the risk of disclosure, which is the revelation of information about an individual that affects the way others judge the individual.

To mitigate these privacy risks the following countermeasures can be taken.

In regions where callers can elect to suppress certain personally identifying information, the network or PSAP functionality can inspect privacy flags within the SIP headers to determine what information may be passed, stored, or displayed to comply with local policy or law. [RFC 3325](#) [RFC3325] defines the "id" priv-value token. The presence of this privacy type in a Privacy header field indicates that the user would like the network asserted identity to be kept private with respect to SIP entities outside the trust domain with which the user authenticated, including the PSAP.

This document defines various data structures that constitutes personal data. Local regulations may govern what data must be provided in emergency calls, but in general, the emergency call system is often aided by the kinds of information described in this document. There is a tradeoff between the privacy considerations and the utility of the data. For adequate protection this specification requires all data exchanges to be secured via communication security techniques (namely TLS) against eavesdropping and inception. Furthermore, security safeguards are required to prevent unauthorized access to data at rest. Various security incidents over the last 10 years have shown data breaches are not not uncommon and are often caused by lack of proper access control frameworks, software bugs (buffer overflows), or missing input parsing (SQL injection attacks). The risks of data breaches is increased with the obligation for emergency services to retain emergency call related data for extended periods, e.g., several years are the norm.

Finally, it is also worth to highlight the nature of the SIP communication architecture, which introduces additional complications for privacy. Some forms of data can be sent by value in the SIP signaling or by value (URL in SIP signaling). When data is sent by value, all intermediaries have access to the data. As such, these intermediaries may also introduce additional privacy risk. Therefore, in situations where the conveyed information raises privacy concerns and intermediaries are involved transmitting a reference is more appropriate (assuming proper access control policies are available for distinguishing the different entities dereferencing the reference). Without access control policies any party in possession of the reference is able to resolve the reference and to obtain the data, including intermediaries.

[9.](#) IANA Considerations

[9.1.](#) Registry creation

This document creates a new registry called 'Emergency Call Additional Data'. The following sub-registries are created in Emergency Call Additional Data:

9.1.1. Provider ID Series Registry

Rosen, Tschofenig, MarshExpiresJanuary 30, 2014

[Page 45]

This document creates a new sub-registry called 'Additional Call Data Provider ID Series'. As defined in [RFC5226], this registry operates under "Expert Review" rules. The expert should determine that the entity requesting a new value is a legitimate issuer of service provider IDs suitable for use in Additional Call Data.

The content of this registry includes:

Name: The identifier which will be used in the ProviderIDSeries element

Source: The full name of the organization issuing the identifiers

URL: A URL to the organization for further information

The initial set of values is listed in Figure 21.

Name	Source	URL
NENA	National Emergency Number Association	http://www.nena.org
EENA	European Emergency Number Association	http://www.eena.org

9.1.2. Service Provider Type Registry

This document creates a new sub-registry called 'Service Provider Type'. As defined in [RFC5226], this registry operates under "Expert Review". The expert should determine that the proposed new value is distinct from existing values and appropriate for use in the TypeOfServiceProvider element

The content of this registry includes:

Name: Value to be used in TypeOfServiceProvider.

Description: A short description of the type of service provider

The initial set of values is defined in Figure 1.

9.1.3. Service Delivered Registry

This document creates a new sub-registry called 'Service Delivered'. As defined in [RFC5226], this registry operates under "Expert Review" rules. The expert should consider whether the proposed service is unique from existing services and the definition of the service will be clear to implementors and PSAPS/responders.

The content of this registry includes:

Name: Enumeration token of the service.

Rosen, Tschofenig, MarshExpiresJanuary 30, 2014

[Page 46]

Description: Short description identifying the service.

The initial set of values are defined in Figure 3.

9.1.4. Device Classification Registry

This document creates a new sub-registry called 'Device Classification'. As defined in [[RFC5226](#)], this registry operates under "Expert Review" rules. The expert should consider whether the proposed class is unique from existing classes and the definition of the class will be clear to implementors and PSAPS/responders.

The content of this registry includes:

Name: Enumeration token of the device classification.

Description: Short description identifying the device type.

The initial set of values are defined in Figure 5.

9.1.5. Device ID Type Type Registry

This document creates a new sub-registry called 'Additional Call Data Device ID Type'. As defined in [[RFC5226](#)], this registry operates under "Expert Review" rules. The expert should ascertain that the proposed type is well understood, and provides the information useful to PSAPs and responders to uniquely identify a device.

The content of this registry includes:

Name: Enumeration token of the device id type.

Description: Short description identifying type of device id.

The initial set of values are defined in Figure 6.

9.1.6. Device/Service Data Type Registry

This document creates a new sub-registry called 'Device/Service Data Type Registry'. As defined in [[RFC5226](#)], this registry operates under "Expert Review" and "Specification Required" rules. The expert should ascertain that the proposed type is well understood, and provides information useful to PSAPs and responders. The specification must contain a complete description of the data, and a precise format specification suitable to allow interoperable implementations.

The content of this registry includes:

Name: Enumeration token of the data type.

Description: Short description identifying the the data.

Specification: Citation for the specification of the data.

The initial set of values are listed in Figure 22.

Token	Description	Specification
IEE1512	Common Incident Management Message Set	IEEE 1512-2006
VEDS	Vehicle Emergency Data Set	APCO/NENA VEDS

9.1.7. Additional Data Blocks Registry

This document creates a new sub-registry called 'Additional Data Blocks' in the purpose registry established by [RFC 3261](#) [[RFC3261](#)]. As defined in [[RFC5226](#)], this registry operates under "Expert Review" and "Specification Required" rules. The expert is responsible for verifying that the document contains a complete and clear specification and the proposed functionality does not obviously duplicate existing functionality.

The content of this registry includes:

Name: Element Name of enclosing block.

Reference: The document that describes the block

The initial set of values are listed in Figure 23.

Token	Reference
ProviderInfo	[This RFC]
SvcInfo	[This RFC]
DevInfo	[This RFC]
Subscriber	[This RFC]
Comment	[This RFC]

9.2. 'emergencyCallData' Purpose Parameter Value

This document defines the 'emergencyCall' value for the "purpose" parameter of the Call-Info header field. The Call-Info header and the corresponding registry for the 'purpose' parameter was established with [RFC 3261](#) [[RFC3261](#)].

Header Field	Parameter Name	New Value	Reference
-----	-----	-----	-----
Call-Info	purpose	emergencyCall	[This RFC]

9.3. URN Sub-Namespace Registration for provided-by Registry Entry

This section registers the namespace specified in [Section 9.5.1](#) in the provided-by registry established by [RFC 4119](#), for usage within the <provided-by> element of a PIDF-LO.

The schema for the provided-by schema used by this document is specified in [Section 6.6](#).

9.4. MIME Registrations

9.4.1. MIME Content-type Registration for 'application/emergencyCall.ProviderInfo+xml'

This specification requests the registration of a new MIME type according to the procedures of [RFC 4288](#) [[RFC4288](#)] and guidelines in [RFC 3023](#) [[RFC3023](#)].

MIME media type name: application

MIME subtype name: emergencyCall.ProviderInfo+xml

Mandatory parameters: none

Optional parameters: charset Indicates the character encoding of enclosed XML.

Encoding considerations: Uses XML, which can employ 8-bit characters, depending on the character encoding used. See [Section 3.2 of RFC 3023](#) [[RFC3023](#)].

Security considerations: This content type is designed to carry the data provider information, which is a sub-category of additional data about an emergency call. Since this data contains personal information appropriate precautions have to be taken to limit unauthorized access, inappropriate disclosure to third parties, and eavesdropping of this information. Please refer to [Section 7](#) and [Section 8](#) for more information.

Interoperability considerations: None

Published specification: [TBD: This specification]

Applications which use this media type: Emergency Services

Rosen, Tschofenig, MarshExpiresJanuary 30, 2014

[Page 49]

Additional information: Magic Number: None File Extension: .xml
Macintosh file type code: 'TEXT'

Person and email address for further information: Hannes
Tschofenig, Hannes.Tschofenig@gmx.net

Intended usage: LIMITED USE

Author: This specification is a work item of the IETF ECRIT
working group, with mailing list address <ecrit@ietf.org>.

Change controller: The IESG <ietf@ietf.org>

9.4.2. MIME Content-type Registration for 'application/ emergencyCall.SvcInfo+xml'

This specification requests the registration of a new MIME type
according to the procedures of [RFC 4288](#) [[RFC4288](#)] and guidelines in
[RFC 3023](#) [[RFC3023](#)].

MIME media type name: application

MIME subtype name: emergencyCall.SvcInfo+xml

Mandatory parameters: none

Optional parameters: charset Indicates the character encoding of
enclosed XML.

Encoding considerations: Uses XML, which can employ 8-bit
characters, depending on the character encoding used. See [Section
3.2 of RFC 3023](#) [[RFC3023](#)].

Security considerations: This content type is designed to carry
the service information, which is a sub-category of additional
data about an emergency call. Since this data contains personal
information appropriate precautions have to be taken to limit
unauthorized access, inappropriate disclosure to third parties,
and eavesdropping of this information. Please refer to [Section 7](#)
and [Section 8](#) for more information.

Interoperability considerations: None

Published specification: [TBD: This specification]

Applications which use this media type: Emergency Services

Additional information: Magic Number: None File Extension: .xml
Macintosh file type code: 'TEXT'

Person and email address for further information: Hannes
Tschofenig, Hannes.Tschofenig@gmx.net

Rosen, Tschofenig, MarshExpiresJanuary 30, 2014

[Page 50]

Intended usage: LIMITED USE

Author: This specification is a work item of the IETF ECRIT working group, with mailing list address <ecrit@ietf.org>.

Change controller: The IESG <ietf@ietf.org>

9.4.3. MIME Content-type Registration for 'application/emergencyCall.DevInfo+xml'

This specification requests the registration of a new MIME type according to the procedures of [RFC 4288](#) [[RFC4288](#)] and guidelines in [RFC 3023](#) [[RFC3023](#)].

MIME media type name: application

MIME subtype name: emergencyCall.DevInfo+xml

Mandatory parameters: none

Optional parameters: charset Indicates the character encoding of enclosed XML.

Encoding considerations: Uses XML, which can employ 8-bit characters, depending on the character encoding used. See [Section 3.2 of RFC 3023](#) [[RFC3023](#)].

Security considerations: This content type is designed to carry the device information information, which is a sub-category of additional data about an emergency call. Since this data contains personal information appropriate precautions have to be taken to limit unauthorized access, inappropriate disclosure to third parties, and eavesdropping of this information. Please refer to [Section 7](#) and [Section 8](#) for more information.

Interoperability considerations: None

Published specification: [TBD: This specification]

Applications which use this media type: Emergency Services

Additional information: Magic Number: None File Extension: .xml
Macintosh file type code: 'TEXT'

Person and email address for further information: Hannes
Tschofenig, Hannes.Tschofenig@gmx.net

Intended usage: LIMITED USE

Author: This specification is a work item of the IETF ECRIT working group, with mailing list address <ecrit@ietf.org>.

Change controller: The IESG <ietf@ietf.org>

Rosen, Tschofenig, MarshExpires1January 30, 2014

[Page 51]

9.4.4. MIME Content-type Registration for 'application/emergencyCall.SubInfo+xml'

This specification requests the registration of a new MIME type according to the procedures of [RFC 4288](#) [[RFC4288](#)] and guidelines in [RFC 3023](#) [[RFC3023](#)].

MIME media type name: application

MIME subtype name: emergencyCall.SubInfo+xml

Mandatory parameters: none

Optional parameters: charset Indicates the character encoding of enclosed XML.

Encoding considerations: Uses XML, which can employ 8-bit characters, depending on the character encoding used. See [Section 3.2 of RFC 3023](#) [[RFC3023](#)].

Security considerations: This content type is designed to carry owner/subscriber information, which is a sub-category of additional data about an emergency call. Since this data contains personal information appropriate precautions have to be taken to limit unauthorized access, inappropriate disclosure to third parties, and eavesdropping of this information. Please refer to [Section 7](#) and [Section 8](#) for more information.

Interoperability considerations: None

Published specification: [TBD: This specification]

Applications which use this media type: Emergency Services

Additional information: Magic Number: None File Extension: .xml
Macintosh file type code: 'TEXT'

Person and email address for further information: Hannes
Tschofenig, Hannes.Tschofenig@gmx.net

Intended usage: LIMITED USE

Author: This specification is a work item of the IETF ECRIT working group, with mailing list address <ecrit@ietf.org>.

Change controller: The IESG <ietf@ietf.org>

9.4.5. MIME Content-type Registration for 'application/emergencyCall.Comment+xml'

This specification requests the registration of a new MIME type according to the procedures of [RFC 4288](#) [[RFC4288](#)] and guidelines in [RFC 3023](#) [[RFC3023](#)].

MIME media type name: application

MIME subtype name: emergencyCall.Comment+xml

Mandatory parameters: none

Optional parameters: charset Indicates the character encoding of enclosed XML.

Encoding considerations: Uses XML, which can employ 8-bit characters, depending on the character encoding used. See [Section 3.2 of RFC 3023](#) [RFC3023].

Security considerations: This content type is designed to carry a comment, which is a sub-category of additional data about an emergency call. This data may contain personal information. Appropriate precautions may have to be taken to limit unauthorized access, inappropriate disclosure to third parties, and eavesdropping of this information. Please refer to [Section 7](#) and [Section 8](#) for more information.

Interoperability considerations: None

Published specification: [TBD: This specification]

Applications which use this media type: Emergency Services

Additional information: Magic Number: None File Extension: .xml
Macintosh file type code: 'TEXT'

Person and email address for further information: Hannes
Tschofenig, Hannes.Tschofenig@gmx.net

Intended usage: LIMITED USE

Author: This specification is a work item of the IETF ECRIT working group, with mailing list address <ecrit@ietf.org>.

Change controller: The IESG <ietf@ietf.org>

[9.5.](#) URN Sub-Namespace Registration

[9.5.1.](#) Registration for urn:ietf:params:xml:ns:emergencyCallAddlData

This section registers a new XML namespace, as per the guidelines in [RFC 3688](#) [RFC3688].

URI: urn:ietf:params:xml:ns:emergencyCallAddlData

Registrant Contact: IETF, ECRIT working group, <ecrit@ietf.org>, as delegated by the IESG <iesg@ietf.org>.

XML:

Rosen, Tschofenig, MarshExpires1January 30, 2014

[Page 53]

```
BEGIN
<?xml version="1.0"?>
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML Basic 1.0//EN"
  "http://www.w3.org/TR/xhtml1-basic/xhtml1-basic10.dtd">
<html xmlns="http://www.w3.org/1999/xhtml">
<head>
  <meta http-equiv="content-type"
    content="text/html; charset=iso-8859-1"/>
  <title>Namespace for Additional Emergency Call Data</title>
</head>
<body>
  <h1>Namespace for Additional Data related to an Emergency Call</h1>
<p>See [TBD: This document].</p>
</body>
</html>
END
```

9.5.2. Registration for urn:ietf:params:xml:ns:emergencyCallProviderInfo

This section registers a new XML namespace, as per the guidelines in [RFC 3688](#) [[RFC3688](#)].

URI: urn:ietf:params:xml:ns:emergencyCallProviderInfo

Registrant Contact: IETF, ECRIT working group, <ecrit@ietf.org>, as delegated by the IESG <iesg@ietf.org>.

XML:

```
BEGIN
<?xml version="1.0"?>
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML Basic 1.0//EN"
  "http://www.w3.org/TR/xhtml1-basic/xhtml1-basic10.dtd">
<html xmlns="http://www.w3.org/1999/xhtml">
<head>
  <meta http-equiv="content-type"
    content="text/html; charset=iso-8859-1"/>
  <title>Namespace for Additional Emergency Call Data:
    Data Provider Information</title>
</head>
<body>
  <h1>Namespace for Additional Data related to an Emergency Call</h1>
  <h2>Data Provider Information</h2>
<p>See [TBD: This document].</p>
</body>
```

</html>
END

Rosen, Tschofenig, MarshExpiresJanuary 30, 2014

[Page 54]

9.5.3. Registration for urn:ietf:params:xml:ns:emergencyCall.SvcInfo

This section registers a new XML namespace, as per the guidelines in [RFC 3688](#) [[RFC3688](#)].

URI: urn:ietf:params:xml:ns:emergencyCall.SvcInfo

Registrant Contact: IETF, ECRIT working group, <ecrit@ietf.org>, as delegated by the IESG <iesg@ietf.org>.

XML:

```
BEGIN
<?xml version="1.0"?>
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML Basic 1.0//EN"
    "http://www.w3.org/TR/xhtml1-basic/xhtml1-basic10.dtd">
<html xmlns="http://www.w3.org/1999/xhtml">
<head>
    <meta http-equiv="content-type"
        content="text/html; charset=iso-8859-1"/>
    <title>Namespace for Additional Emergency Call Data:
        Service Information</title>
</head>
<body>
    <h1>Namespace for Additional Data related to an Emergency Call</h1>
    <h2>Service Information</h2>
    <p>See [TBD: This document].</p>
</body>
</html>
END
```

9.5.4. Registration for urn:ietf:params:xml:ns:emergencyCall.DevInfo

This section registers a new XML namespace, as per the guidelines in [RFC 3688](#) [[RFC3688](#)].

URI: urn:ietf:params:xml:ns:emergencyCall.DevInfo

Registrant Contact: IETF, ECRIT working group, <ecrit@ietf.org>, as delegated by the IESG <iesg@ietf.org>.

XML:


```
BEGIN
<?xml version="1.0"?>
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML Basic 1.0//EN"
  "http://www.w3.org/TR/xhtml1-basic/xhtml1-basic10.dtd">
<html xmlns="http://www.w3.org/1999/xhtml">
<head>
  <meta http-equiv="content-type"
    content="text/html; charset=iso-8859-1"/>
  <title>Namespace for Additional Emergency Call Data:
    Device Information</title>
</head>
<body>
  <h1>Namespace for Additional Data related to an Emergency Call</h1>
  <h2>Device Information</h2>
<p>See [TBD: This document].</p>
</body>
</html>
END
```

9.5.5. Registration for urn:ietf:params:xml:ns:emergencyCall.SubInfo

This section registers a new XML namespace, as per the guidelines in [RFC 3688](#) [[RFC3688](#)].

URI: urn:ietf:params:xml:ns:emergencyCall.SubInfo

Registrant Contact: IETF, ECRIT working group, <ecrit@ietf.org>, as delegated by the IESG <iesg@ietf.org>.

XML:

```
BEGIN
<?xml version="1.0"?>
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML Basic 1.0//EN"
  "http://www.w3.org/TR/xhtml1-basic/xhtml1-basic10.dtd">
<html xmlns="http://www.w3.org/1999/xhtml">
<head>
  <meta http-equiv="content-type"
    content="text/html; charset=iso-8859-1"/>
  <title>Namespace for Additional Emergency Call Data:
    Owner/Subscriber Information</title>
</head>
<body>
  <h1>Namespace for Additional Data related to an Emergency Call</h1>
  <h2> Owner/Subscriber Information</h2>
<p>See [TBD: This document].</p>
```

```
</body>  
</html>  
END
```

9.5.6. Registration for urn:ietf:params:xml:ns:emergencyCall.Comment

This section registers a new XML namespace, as per the guidelines in [RFC 3688](#) [[RFC3688](#)].

URI: urn:ietf:params:xml:ns:emergencyCall.Comment

Registrant Contact: IETF, ECRIT working group, <ecrit@ietf.org>, as delegated by the IESG <iesg@ietf.org>.

XML:

```
BEGIN
<?xml version="1.0"?>
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML Basic 1.0//EN"
    "http://www.w3.org/TR/xhtml1-basic/xhtml1-basic10.dtd">
<html xmlns="http://www.w3.org/1999/xhtml">
<head>
    <meta http-equiv="content-type"
        content="text/html; charset=iso-8859-1"/>
    <title>Namespace for Additional Emergency Call Data:Comment</title>
</head>
<body>
    <h1>Namespace for Additional Data related to an Emergency Call</h1>
    <h2> Comment</h2>
    <p>See [TBD: This document].</p>
</body>
</html>
END
```

9.6. Schema Registrations

This specification registers five schemas, as per the guidelines in [RFC 3688](#) [[RFC3688](#)].

URI: urn:ietf:params:xml:schema:additional-
data:emergencyCallProviderInfo

Registrant Contact: IETF, ECRIT Working Group (ecrit@ietf.org), as delegated by the IESG (iesg@ietf.org).

XML: The XML schema can be found in Figure 15.

URI: urn:ietf:params:xml:schema:additional-data:addCallSvcInfo

Registrant Contact: IETF, ECRIT Working Group (ectit@ietf.org), as delegated by the IESG (iesg@ietf.org).

XML: The XML schema can be found in Figure 16.

URI: urn:ietf:params:xml:schema:additional-data:emergencyCallDevInfo

Registrant Contact: IETF, ECRIT Working Group (ecrit@ietf.org), as delegated by the IESG (iesg@ietf.org).

XML: The XML schema can be found in Figure 17.

URI: urn:ietf:params:xml:schema:additional-data:emergencyCall.SubInfo

Registrant Contact: IETF, ECRIT Working Group (ecrit@ietf.org), as delegated by the IESG (iesg@ietf.org).

XML: The XML schema can be found in [Section 6.4](#).

URI: urn:ietf:params:xml:schema:additional-data:emergencyCall.Comment

Registrant Contact: IETF, ECRIT Working Group (ecrit@ietf.org), as delegated by the IESG (iesg@ietf.org).

XML: The XML schema can be found in [Section 6.5](#).

[9.7.](#) VCard Parameter Value Registration

This document registers a new value in the vCARD Parameter Values registry as defined by [\[RFC6350\]](#) with the following template:

Value: main

Purpose: The main telephone number, typically of an enterprise, as opposed to a direct dial number of an individual employee

Conformance: This value can be used with the "TYPE" parameter applied on the "TEL" property.

Example(s): TEL;VALUE=uri;TYPE="main,voice";PREF=1:tel:+1-418-656-9000

0

[10.](#) Acknowledgments

This work was originally started in NENA and has benefitted from a large number of participants in NENA standardization efforts, originally in the Long Term Definition Working Group, the Data Technical Committee and most recently the Additional Data working group. The authors are grateful for the initial work and extended comments provided by many NENA participants, including Delaine Arnold, Marc Berryman, Guy Caron, Mark Fletcher, Brian Dupras, James

Leyerle, Kathy McMahon, Christian, Militeau, Ira Pyles, Matt Serra,
and Robert (Bob) Sherry.

Rosen, Tschofenig, MarshExpiresJanuary 30, 2014

[Page 58]

We would also like to thank Paul Kyzivat, Gunnar Hellstrom, Martin Thomson, Keith Drage, and Laura Liess for their review comments.

11. References

11.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC2392] Levinson, E., "Content-ID and Message-ID Uniform Resource Locators", [RFC 2392](#), August 1998.
- [RFC3023] Murata, M., St. Laurent, S. and D. Kohn, "XML Media Types", [RFC 3023](#), January 2001.
- [RFC3204] Zimmerer, E., Peterson, J., Vemuri, A., Ong, L., Audet, F., Watson, M. and M. Zonoun, "MIME media types for ISUP and QSIG Objects", [RFC 3204](#), December 2001.
- [RFC3261] Rosenberg, J., Schulzrinne, H., Camarillo, G., Johnston, A., Peterson, J., Sparks, R., Handley, M. and E. Schooler, "SIP: Session Initiation Protocol", [RFC 3261](#), June 2002.
- [RFC3325] Jennings, C., Peterson, J. and M. Watson, "Private Extensions to the Session Initiation Protocol (SIP) for Asserted Identity within Trusted Networks", [RFC 3325](#), November 2002.
- [RFC3459] Burger, E., "Critical Content Multi-purpose Internet Mail Extensions (MIME) Parameter", [RFC 3459](#), January 2003.
- [RFC3688] Mealling, M., "The IETF XML Registry", [BCP 81](#), [RFC 3688](#), January 2004.
- [RFC4119] Peterson, J., "A Presence-based GEOPRIV Location Object Format", [RFC 4119](#), December 2005.
- [RFC4288] Freed, N. and J. Klensin, "Media Type Specifications and Registration Procedures", [RFC 4288](#), December 2005.
- [RFC5226] Narten, T. and H. Alvestrand, "Guidelines for Writing an IANA Considerations Section in RFCs", [BCP 26](#), [RFC 5226](#), May 2008.
- [RFC5621] Camarillo, G., "Message Body Handling in the Session Initiation Protocol (SIP)", [RFC 5621](#), September 2009.
- [RFC6350] Perreault, S., "vCard Format Specification", [RFC 6350](#),

August 2011.

[RFC6351] Perreault, S., "xCard: vCard XML Representation", [RFC 6351](#), August 2011.

Rosen, Tschofenig, MarshExpires1January 30, 2014

[Page 59]

11.2. Informational References

- [I-D.iab-privacy-considerations]
Cooper, A., Tschofenig, H., Aboba, B., Peterson, J.,
Morris, J., Hansen, M. and R. Smith, "Privacy
Considerations for Internet Protocols", Internet-Draft
[draft-iab-privacy-considerations-03](#), July 2012.
- [I-D.ietf-geopriv-relative-location]
Thomson, M., Rosen, B., Stanley, D., Bajko, G. and A.
Thomson, "Relative Location Representation", Internet-
Draft [draft-ietf-geopriv-relative-location-06](#), July 2013.
- [RFC5012] Schulzrinne, H. and R. Marshall, "Requirements for
Emergency Context Resolution with Internet Technologies",
[RFC 5012](#), January 2008.
- [RFC5139] Thomson, M. and J. Winterbottom, "Revised Civic Location
Format for Presence Information Data Format Location
Object (PIDF-LO)", [RFC 5139](#), February 2008.
- [RFC5222] Hardie, T., Newton, A., Schulzrinne, H. and H. Tschofenig,
"LoST: A Location-to-Service Translation Protocol", [RFC
5222](#), August 2008.
- [RFC5491] Winterbottom, J., Thomson, M. and H. Tschofenig, "GEOPRIV
Presence Information Data Format Location Object (PIDF-LO)
Usage Clarification, Considerations, and Recommendations",
[RFC 5491](#), March 2009.
- [RFC5962] Schulzrinne, H., Singh, V., Tschofenig, H. and M. Thomson,
"Dynamic Extensions to the Presence Information Data
Format Location Object (PIDF-LO)", [RFC 5962](#), September
2010.
- [RFC5985] Barnes, M., "HTTP-Enabled Location Delivery (HELD)", [RFC
5985](#), September 2010.
- [RFC6443] Rosen, B., Schulzrinne, H., Polk, J. and A. Newton,
"Framework for Emergency Calling Using Internet
Multimedia", [RFC 6443](#), December 2011.
- [RFC6848] Winterbottom, J., Thomson, M., Barnes, R., Rosen, B. and
R. George, "Specifying Civic Address Extensions in the
Presence Information Data Format Location Object (PIDF-
LO)", [RFC 6848](#), January 2013.
- [RFC6881] Rosen, B. and J. Polk, "Best Current Practice for
Communications Services in Support of Emergency Calling",

[BCP 181](#), [RFC 6881](#), March 2013.

[Appendix A](#). XML Schema for vCard/xCard

Rosen, Tschofenig, MarshExpiresJanuary 30, 2014

[Page 60]

This section contains the vCard/xCard XML schema version of the Relax NG schema defined in [RFC 6351](#) [[RFC6351](#)] for simplified use with the XML schemas defined in this document. The schema in [RFC 6351](#) [[RFC6351](#)] is the normative source and this section is informative only.


```
<?xml version="1.0" encoding="UTF-8"?>
<xs:schema xmlns:xs="http://www.w3.org/2001/XMLSchema"
  elementFormDefault="qualified"
  targetNamespace="urn:ietf:params:xml:ns:vcard-4.0"
  xmlns:ns1="urn:ietf:params:xml:ns:vcard-4.0">
  <!--

    3.3
    iana-token = xs:string { pattern = "[a-zA-Z0-9-]+" }
    x-name = xs:string { pattern = "x-[a-zA-Z0-9-]+" }
  -->
  <xs:simpleType name="iana-token">
    <xs:annotation>
      <xs:documentation>vCard Format Specification
    </xs:documentation>
    </xs:annotation>
    <xs:restriction base="xs:string"/>
  </xs:simpleType>
  <xs:simpleType name="x-name">
    <xs:restriction base="xs:string"/>
  </xs:simpleType>
  <!--

    4.1
  -->
  <xs:element name="text" type="xs:string"/>
  <xs:group name="value-text-list">
    <xs:sequence>
      <xs:element maxOccurs="unbounded" ref="ns1:text"/>
    </xs:sequence>
  </xs:group>
  <!-- 4.2 -->
  <xs:element name="uri" type="xs:anyURI"/>
  <!-- 4.3.1 -->
  <xs:element name="date"
    substitutionGroup="ns1:value-date-and-or-time">
    <xs:simpleType>
      <xs:restriction base="xs:string">
        <xs:pattern value="\d{8}|\d{4}-\d\d|
          --\d\d(\d\d)?|---\d\d"/>
      </xs:restriction>
    </xs:simpleType>
  </xs:element>
  <!-- 4.3.2 -->
  <xs:element name="time"
    substitutionGroup="ns1:value-date-and-or-time">
    <xs:simpleType>
```

```
<xs:restriction base="xs:string">
  <xs:pattern value="(\d\d(\d\d(\d\d)?)?|-\d\d(\d\d?)|--\d\d)
  (Z|[\+\\-]\d\d(\d\d)?)" />
</xs:restriction>
</xs:simpleType>
```

```
</xs:element>
<!-- 4.3.3 -->
<xs:element name="date-time"
substitutionGroup="ns1:value-date-and-or-time">
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:pattern value=
        "(\d{8}|--\d{4}|---\d\d)T
        \d\d(\d\d(\d\d)?)(Z|[\+-]\d\d(\d\d)?)" />
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<!-- 4.3.4 -->
<xs:element name="value-date-and-or-time" abstract="true"/>
<!-- 4.3.5 -->
<xs:complexType name="value-timestamp">
  <xs:sequence>
    <xs:element ref="ns1:timestamp"/>
  </xs:sequence>
</xs:complexType>
<xs:element name="timestamp">
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:pattern value="\d{8}T\d{6}(Z|[\+-]\d\d(\d\d)?)" />
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<!-- 4.4 -->
<xs:element name="boolean" type="xs:boolean"/>
<!-- 4.5 -->
<xs:element name="integer" type="xs:integer"/>
<!-- 4.6 -->
<xs:element name="float" type="xs:float"/>
<!-- 4.7 -->
<xs:element name="utc-offset">
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:pattern value="[\+-]\d\d(\d\d)?" />
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<!-- 4.8 -->
<xs:element name="language-tag">
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:pattern
        value="([a-z]{2,3}((-[a-z]{3}){0,3})?|[a-z]{4,8})
        (-[a-z]{4})?(-([a-z]{2}|\d{3}))?(-([0-9a-z]{5,8}|
        \d[0-9a-z]{3}))*(-([0-9a-wyz](-[0-9a-z]{2,8})+))*" />
    </xs:restriction>
  </xs:simpleType>
</xs:element>
```

```
        (-x(-[0-9a-z]{1,8})+)?|x(-[0-9a-z]{1,8})+|[a-z]{1,3}  
        (-[0-9a-z]{2,8}){1,2}"/>  
    </xs:restriction>  
</xs:simpleType>  
</xs:element>
```

```
<!--  
  
    5.1  
-->  
<xs:group name="param-language">  
  <xs:annotation>  
    <xs:documentation>Section 5: Parameters</xs:documentation>  
  </xs:annotation>  
  <xs:sequence>  
    <xs:element minOccurs="0" ref="ns1:language"/>  
  </xs:sequence>  
</xs:group>  
<xs:element name="language">  
  <xs:complexType>  
    <xs:sequence>  
      <xs:element ref="ns1:language-tag"/>  
    </xs:sequence>  
  </xs:complexType>  
</xs:element>  
<!-- 5.2 -->  
<xs:group name="param-pref">  
  <xs:sequence>  
    <xs:element minOccurs="0" ref="ns1:pref"/>  
  </xs:sequence>  
</xs:group>  
<xs:element name="pref">  
  <xs:complexType>  
    <xs:sequence>  
      <xs:element name="integer">  
        <xs:simpleType>  
          <xs:restriction base="xs:integer">  
            <xs:minInclusive value="1"/>  
            <xs:maxInclusive value="100"/>  
          </xs:restriction>  
        </xs:simpleType>  
      </xs:element>  
    </xs:sequence>  
  </xs:complexType>  
</xs:element>  
<!-- 5.4 -->  
<xs:group name="param-altid">  
  <xs:sequence>  
    <xs:element minOccurs="0" ref="ns1:altid"/>  
  </xs:sequence>  
</xs:group>  
<xs:element name="altid">  
  <xs:complexType>  
    <xs:sequence>  
      <xs:element ref="ns1:text"/>  
    </xs:sequence>  
  </xs:complexType>  
</xs:element>
```

```
        </xs:sequence>
    </xs:complexType>
</xs:element>
<!-- 5.5 -->
<xs:group name="param-pid">
```

```
<xs:sequence>
  <xs:element minOccurs="0" ref="ns1:pid"/>
</xs:sequence>
</xs:group>
<xs:element name="pid">
  <xs:complexType>
    <xs:sequence>
      <xs:element maxOccurs="unbounded" name="text">
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:pattern value="\d+(\.\d+)?"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<!-- 5.6 -->
<xs:group name="param-type">
  <xs:sequence>
    <xs:element minOccurs="0" ref="ns1:type"/>
  </xs:sequence>
</xs:group>
<xs:element name="type">
  <xs:complexType>
    <xs:sequence>
      <xs:element maxOccurs="unbounded" name="text">
        <xs:simpleType>
          <xs:restriction base="xs:token">
            <xs:enumeration value="work"/>
            <xs:enumeration value="home"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<!-- 5.7 -->
<xs:group name="param-mediatype">
  <xs:sequence>
    <xs:element minOccurs="0" ref="ns1:mediatype"/>
  </xs:sequence>
</xs:group>
<xs:element name="mediatype">
  <xs:complexType>
    <xs:sequence>
      <xs:element ref="ns1:text"/>
    </xs:sequence>
  </xs:complexType>
```

```
</xs:element>
<!-- 5.8 -->
<xs:group name="param-calscale">
  <xs:sequence>
    <xs:element minOccurs="0" ref="ns1:calscale"/>
  </xs:sequence>
</xs:group>
```

```
</xs:sequence>
</xs:group>
<xs:element name="calscale">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="text">
        <xs:simpleType>
          <xs:restriction base="xs:token">
            <xs:enumeration value="gregorian"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<!-- 5.9 -->
<xs:group name="param-sort-as">
  <xs:sequence>
    <xs:element minOccurs="0" ref="ns1:sort-as"/>
  </xs:sequence>
</xs:group>
<xs:element name="sort-as">
  <xs:complexType>
    <xs:sequence>
      <xs:element maxOccurs="unbounded" ref="ns1:text"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<!-- 5.10 -->
<xs:group name="param-geo">
  <xs:sequence>
    <xs:element minOccurs="0" name="geo">
      <xs:complexType>
        <xs:sequence>
          <xs:element ref="ns1:uri"/>
        </xs:sequence>
      </xs:complexType>
    </xs:element>
  </xs:sequence>
</xs:group>
<!-- 5.11 -->
<xs:group name="param-tz">
  <xs:sequence>
    <xs:element minOccurs="0" name="tz">
      <xs:complexType>
        <xs:choice>
          <xs:element ref="ns1:text"/>
          <xs:element ref="ns1:uri"/>
        </xs:choice>
      </xs:complexType>
    </xs:element>
  </xs:sequence>
</xs:group>
```

```
        </xs:complexType>
      </xs:element>
    </xs:sequence>
  </xs:group>
<!--
```

```
6.1.3
-->
<xs:element name="source">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="parameters">
        <xs:complexType>
          <xs:sequence>
            <xs:group ref="ns1:param-altid"/>
            <xs:group ref="ns1:param-pid"/>
            <xs:group ref="ns1:param-pref"/>
            <xs:group ref="ns1:param-mediatype"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:element ref="ns1:uri"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<!-- 6.1.4 -->
<xs:element name="kind">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="unbounded" name="text">
        <xs:simpleType>
          <xs:union memberTypes="ns1:x-name ns1:iana-token">
            <xs:simpleType>
              <xs:restriction base="xs:token">
                <xs:enumeration value="individual"/>
              </xs:restriction>
            </xs:simpleType>
            <xs:simpleType>
              <xs:restriction base="xs:token">
                <xs:enumeration value="group"/>
              </xs:restriction>
            </xs:simpleType>
            <xs:simpleType>
              <xs:restriction base="xs:token">
                <xs:enumeration value="org"/>
              </xs:restriction>
            </xs:simpleType>
            <xs:simpleType>
              <xs:restriction base="xs:token">
                <xs:enumeration value="location"/>
              </xs:restriction>
            </xs:simpleType>
          </xs:union>
        </xs:simpleType>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

```
        </xs:element>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
<!-- 6.2.1 -->
```

```
<xs:element name="fn">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="parameters">
        <xs:complexType>
          <xs:sequence>
            <xs:group ref="ns1:param-language"/>
            <xs:group ref="ns1:param-altid"/>
            <xs:group ref="ns1:param-pid"/>
            <xs:group ref="ns1:param-pref"/>
            <xs:group ref="ns1:param-type"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:element ref="ns1:text"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<!-- 6.2.2 -->
<xs:element name="n">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="parameters">
        <xs:complexType>
          <xs:sequence>
            <xs:group ref="ns1:param-language"/>
            <xs:group ref="ns1:param-sort-as"/>
            <xs:group ref="ns1:param-altid"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:element maxOccurs="unbounded" ref="ns1:surname"/>
      <xs:element maxOccurs="unbounded" ref="ns1:given"/>
      <xs:element maxOccurs="unbounded" ref="ns1:additional"/>
      <xs:element maxOccurs="unbounded" ref="ns1:prefix"/>
      <xs:element maxOccurs="unbounded" ref="ns1:suffix"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="surname" type="xs:string"/>
<xs:element name="given" type="xs:string"/>
<xs:element name="additional" type="xs:string"/>
<xs:element name="prefix" type="xs:string"/>
<xs:element name="suffix" type="xs:string"/>
<!-- 6.2.3 -->
<xs:element name="nickname">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="parameters">
```

```
<xs:complexType>
  <xs:sequence>
    <xs:group ref="ns1:param-language"/>
    <xs:group ref="ns1:param-altid"/>
    <xs:group ref="ns1:param-pid"/>
```

```
        <xs:group ref="ns1:param-pref"/>
        <xs:group ref="ns1:param-type"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:group ref="ns1:value-text-list"/>
</xs:sequence>
</xs:complexType>
</xs:element>
<!-- 6.2.4 -->
<xs:element name="photo">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="parameters">
        <xs:complexType>
          <xs:sequence>
            <xs:group ref="ns1:param-altid"/>
            <xs:group ref="ns1:param-pid"/>
            <xs:group ref="ns1:param-pref"/>
            <xs:group ref="ns1:param-type"/>
            <xs:group ref="ns1:param-mediatype"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:element ref="ns1:uri"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<!-- 6.2.5 -->
<xs:element name="bday">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="parameters">
        <xs:complexType>
          <xs:sequence>
            <xs:group ref="ns1:param-altid"/>
            <xs:group ref="ns1:param-calscale"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:choice>
        <xs:element ref="ns1:value-date-and-or-time"/>
        <xs:element ref="ns1:text"/>
      </xs:choice>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<!-- 6.2.6 -->
<xs:element name="anniversary">
```

```
<xs:complexType>  
  <xs:sequence>  
    <xs:element minOccurs="0" name="parameters">  
      <xs:complexType>  
        <xs:sequence>
```

```
        <xs:group ref="ns1:param-altid"/>
        <xs:group ref="ns1:param-calscale"/>
    </xs:sequence>
</xs:complexType>
</xs:element>
<xs:choice>
    <xs:element ref="ns1:value-date-and-or-time"/>
    <xs:element ref="ns1:text"/>
</xs:choice>
</xs:sequence>
</xs:complexType>
</xs:element>
<!-- 6.2.7 -->
<xs:element name="gender">
    <xs:complexType>
        <xs:sequence>
            <xs:element ref="ns1:sex"/>
            <xs:element minOccurs="0" ref="ns1:identity"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="sex">
    <xs:simpleType>
        <xs:restriction base="xs:token">
            <xs:enumeration value=""/>
            <xs:enumeration value="M"/>
            <xs:enumeration value="F"/>
            <xs:enumeration value="0"/>
            <xs:enumeration value="N"/>
            <xs:enumeration value="U"/>
        </xs:restriction>
    </xs:simpleType>
</xs:element>
<xs:element name="identity" type="xs:string"/>
<!-- 6.3.1 -->
<xs:group name="param-label">
    <xs:sequence>
        <xs:element minOccurs="0" ref="ns1:label"/>
    </xs:sequence>
</xs:group>
<xs:element name="label">
    <xs:complexType>
        <xs:sequence>
            <xs:element ref="ns1:text"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="adr">
    <xs:complexType>
```

```
<xs:sequence>
  <xs:element minOccurs="0" name="parameters">
    <xs:complexType>
      <xs:sequence>
        <xs:group ref="ns1:param-language"/>

```



```
<xs:enumeration value="video"/>
<xs:enumeration value="pager"/>
<xs:enumeration value="textphone"/>
</xs:restriction>
</xs:simpleType>
```

```
        </xs:element>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:group ref="ns1:param-mediatype"/>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:choice>
  <xs:element ref="ns1:text"/>
  <xs:element ref="ns1:uri"/>
</xs:choice>
</xs:sequence>
</xs:complexType>
</xs:element>
<!-- 6.4.2 -->
<xs:element name="email">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="parameters">
        <xs:complexType>
          <xs:sequence>
            <xs:group ref="ns1:param-altid"/>
            <xs:group ref="ns1:param-pid"/>
            <xs:group ref="ns1:param-pref"/>
            <xs:group ref="ns1:param-type"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:element ref="ns1:text"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<!-- 6.4.3 -->
<xs:element name="impp">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="parameters">
        <xs:complexType>
          <xs:sequence>
            <xs:group ref="ns1:param-altid"/>
            <xs:group ref="ns1:param-pid"/>
            <xs:group ref="ns1:param-pref"/>
            <xs:group ref="ns1:param-type"/>
            <xs:group ref="ns1:param-mediatype"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:element ref="ns1:uri"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

```
        </xs:sequence>
      </xs:complexType>
    </xs:element>
    <!-- 6.4.4 -->
    <xs:element name="lang">
```

```
<xs:complexType>
  <xs:sequence>
    <xs:element minOccurs="0" name="parameters">
      <xs:complexType>
        <xs:sequence>
          <xs:group ref="ns1:param-altid"/>
          <xs:group ref="ns1:param-pid"/>
          <xs:group ref="ns1:param-pref"/>
          <xs:group ref="ns1:param-type"/>
        </xs:sequence>
      </xs:complexType>
    </xs:element>
    <xs:element ref="ns1:language-tag"/>
  </xs:sequence>
</xs:complexType>
</xs:element>
<!-- 6.5.1 -->
<xs:group name="property-tz">
  <xs:sequence>
    <xs:element name="tz">
      <xs:complexType>
        <xs:sequence>
          <xs:element minOccurs="0" name="parameters">
            <xs:complexType>
              <xs:sequence>
                <xs:group ref="ns1:param-altid"/>
                <xs:group ref="ns1:param-pid"/>
                <xs:group ref="ns1:param-pref"/>
                <xs:group ref="ns1:param-type"/>
                <xs:group ref="ns1:param-mediatype"/>
              </xs:sequence>
            </xs:complexType>
          </xs:element>
          <xs:choice>
            <xs:element ref="ns1:text"/>
            <xs:element ref="ns1:uri"/>
            <xs:element ref="ns1:utc-offset"/>
          </xs:choice>
        </xs:sequence>
      </xs:complexType>
    </xs:element>
  </xs:sequence>
</xs:group>
<!-- 6.5.2 -->
<xs:group name="property-geo">
  <xs:sequence>
    <xs:element name="geo">
      <xs:complexType>
        <xs:sequence>
```

```
<xs:element minOccurs="0" name="parameters">
  <xs:complexType>
    <xs:sequence>
      <xs:group ref="ns1:param-altid"/>
      <xs:group ref="ns1:param-pid"/>
    
```

```
        <xs:group ref="ns1:param-pref"/>
        <xs:group ref="ns1:param-type"/>
        <xs:group ref="ns1:param-mediatype"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:element ref="ns1:uri"/>
</xs:sequence>
</xs:complexType>
</xs:element>
</xs:sequence>
</xs:group>
<!-- 6.6.1 -->
<xs:element name="title">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="parameters">
        <xs:complexType>
          <xs:sequence>
            <xs:group ref="ns1:param-language"/>
            <xs:group ref="ns1:param-altid"/>
            <xs:group ref="ns1:param-pid"/>
            <xs:group ref="ns1:param-pref"/>
            <xs:group ref="ns1:param-type"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:element ref="ns1:text"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<!-- 6.6.2 -->
<xs:element name="role">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="parameters">
        <xs:complexType>
          <xs:sequence>
            <xs:group ref="ns1:param-language"/>
            <xs:group ref="ns1:param-altid"/>
            <xs:group ref="ns1:param-pid"/>
            <xs:group ref="ns1:param-pref"/>
            <xs:group ref="ns1:param-type"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:element ref="ns1:text"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
</xs:sequence>
</xs:complexType>
```

```
</xs:element>
<!-- 6.6.3 -->
<xs:element name="logo">
  <xs:complexType>
    <xs:sequence>
```

```
<xs:element minOccurs="0" name="parameters">
  <xs:complexType>
    <xs:sequence>
      <xs:group ref="ns1:param-language"/>
      <xs:group ref="ns1:param-altid"/>
      <xs:group ref="ns1:param-pid"/>
      <xs:group ref="ns1:param-pref"/>
      <xs:group ref="ns1:param-type"/>
      <xs:group ref="ns1:param-mediatype"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element ref="ns1:uri"/>
</xs:sequence>
</xs:complexType>
</xs:element>
<!-- 6.6.4 -->
<xs:element name="org">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="parameters">
        <xs:complexType>
          <xs:sequence>
            <xs:group ref="ns1:param-language"/>
            <xs:group ref="ns1:param-altid"/>
            <xs:group ref="ns1:param-pid"/>
            <xs:group ref="ns1:param-pref"/>
            <xs:group ref="ns1:param-type"/>
            <xs:group ref="ns1:param-sort-as"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:group ref="ns1:value-text-list"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<!-- 6.6.5 -->
<xs:element name="member">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="parameters">
        <xs:complexType>
          <xs:sequence>
            <xs:group ref="ns1:param-altid"/>
            <xs:group ref="ns1:param-pid"/>
            <xs:group ref="ns1:param-pref"/>
            <xs:group ref="ns1:param-mediatype"/>
          </xs:sequence>
        </xs:complexType>
      </xs:complexType>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

```
        </xs:element>
        <xs:element ref="ns1:uri"/>
    </xs:sequence>
</xs:complexType>
</xs:element>
```

```
<!-- 6.6.6 -->
<xs:element name="related">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="parameters">
        <xs:complexType>
          <xs:sequence>
            <xs:group ref="ns1:param-altid"/>
            <xs:group ref="ns1:param-pid"/>
            <xs:group ref="ns1:param-pref"/>
            <xs:element minOccurs="0" name="type">
              <xs:complexType>
                <xs:sequence>
                  <xs:element maxOccurs="unbounded" name="text">
                    <xs:simpleType>
                      <xs:restriction base="xs:token">
                        <xs:enumeration value="work"/>
                        <xs:enumeration value="home"/>
                        <xs:enumeration value="contact"/>
                        <xs:enumeration value="acquaintance"/>
                        <xs:enumeration value="friend"/>
                        <xs:enumeration value="met"/>
                        <xs:enumeration value="co-worker"/>
                        <xs:enumeration value="colleague"/>
                        <xs:enumeration value="co-resident"/>
                        <xs:enumeration value="neighbor"/>
                        <xs:enumeration value="child"/>
                        <xs:enumeration value="parent"/>
                        <xs:enumeration value="sibling"/>
                        <xs:enumeration value="spouse"/>
                        <xs:enumeration value="kin"/>
                        <xs:enumeration value="muse"/>
                        <xs:enumeration value="crush"/>
                        <xs:enumeration value="date"/>
                        <xs:enumeration value="sweetheart"/>
                        <xs:enumeration value="me"/>
                        <xs:enumeration value="agent"/>
                        <xs:enumeration value="emergency"/>
                      </xs:restriction>
                    </xs:simpleType>
                  </xs:element>
                </xs:sequence>
              </xs:complexType>
            </xs:element>
            <xs:group ref="ns1:param-mediatype"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
    </xs:choice>
```

```
        <xs:element ref="ns1:uri"/>
        <xs:element ref="ns1:text"/>
    </xs:choice>
</xs:sequence>
</xs:complexType>
```

```
</xs:element>
<!-- 6.7.1 -->
<xs:element name="categories">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="parameters">
        <xs:complexType>
          <xs:sequence>
            <xs:group ref="ns1:param-altid"/>
            <xs:group ref="ns1:param-pid"/>
            <xs:group ref="ns1:param-pref"/>
            <xs:group ref="ns1:param-type"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:group ref="ns1:value-text-list"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<!-- 6.7.2 -->
<xs:element name="note">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="parameters">
        <xs:complexType>
          <xs:sequence>
            <xs:group ref="ns1:param-language"/>
            <xs:group ref="ns1:param-altid"/>
            <xs:group ref="ns1:param-pid"/>
            <xs:group ref="ns1:param-pref"/>
            <xs:group ref="ns1:param-type"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:element ref="ns1:text"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<!-- 6.7.3 -->
<xs:element name="prodid">
  <xs:complexType>
    <xs:sequence>
      <xs:element ref="ns1:text"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<!-- 6.7.4 -->
<xs:element name="rev" type="ns1:value-timestamp"/>
<!-- 6.7.5 -->
```

```
<xs:element name="sound">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="parameters">
        <xs:complexType>
```

```
<xs:sequence>
  <xs:group ref="ns1:param-language"/>
  <xs:group ref="ns1:param-altid"/>
  <xs:group ref="ns1:param-pid"/>
  <xs:group ref="ns1:param-pref"/>
  <xs:group ref="ns1:param-type"/>
  <xs:group ref="ns1:param-mediatype"/>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element ref="ns1:uri"/>
</xs:sequence>
</xs:complexType>
</xs:element>
<!-- 6.7.6 -->
<xs:element name="uid">
  <xs:complexType>
    <xs:sequence>
      <xs:element ref="ns1:uri"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<!-- 6.7.7 -->
<xs:element name="clientpidmap">
  <xs:complexType>
    <xs:sequence>
      <xs:element ref="ns1:sourceid"/>
      <xs:element ref="ns1:uri"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="sourceid" type="xs:positiveInteger"/>
<!-- 6.7.8 -->
<xs:element name="url">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="parameters">
        <xs:complexType>
          <xs:sequence>
            <xs:group ref="ns1:param-altid"/>
            <xs:group ref="ns1:param-pid"/>
            <xs:group ref="ns1:param-pref"/>
            <xs:group ref="ns1:param-type"/>
            <xs:group ref="ns1:param-mediatype"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:element ref="ns1:uri"/>
    </xs:sequence>
```

```
    </xs:complexType>
</xs:element>
<!-- 6.8.1 -->
<xs:element name="key">
  <xs:complexType>
```

```
<xs:sequence>
  <xs:element minOccurs="0" name="parameters">
    <xs:complexType>
      <xs:sequence>
        <xs:group ref="ns1:param-altid"/>
        <xs:group ref="ns1:param-pid"/>
        <xs:group ref="ns1:param-pref"/>
        <xs:group ref="ns1:param-type"/>
        <xs:group ref="ns1:param-mediatype"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:choice>
    <xs:element ref="ns1:uri"/>
    <xs:element ref="ns1:text"/>
  </xs:choice>
</xs:sequence>
</xs:complexType>
</xs:element>
<!-- 6.9.1 -->
<xs:element name="fburl">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="parameters">
        <xs:complexType>
          <xs:sequence>
            <xs:group ref="ns1:param-altid"/>
            <xs:group ref="ns1:param-pid"/>
            <xs:group ref="ns1:param-pref"/>
            <xs:group ref="ns1:param-type"/>
            <xs:group ref="ns1:param-mediatype"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:element ref="ns1:uri"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<!-- 6.9.2 -->
<xs:element name="caladruri">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="parameters">
        <xs:complexType>
          <xs:sequence>
            <xs:group ref="ns1:param-altid"/>
            <xs:group ref="ns1:param-pid"/>
            <xs:group ref="ns1:param-pref"/>
            <xs:group ref="ns1:param-type"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

```
        <xs:group ref="ns1:param-mediatype"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:element ref="ns1:uri"/>
```

```
    </xs:sequence>
  </xs:complexType>
</xs:element>
<!-- 6.9.3 -->
<xs:element name="caluri">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="parameters">
        <xs:complexType>
          <xs:sequence>
            <xs:group ref="ns1:param-altid"/>
            <xs:group ref="ns1:param-pid"/>
            <xs:group ref="ns1:param-pref"/>
            <xs:group ref="ns1:param-type"/>
            <xs:group ref="ns1:param-mediatype"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:element ref="ns1:uri"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<!-- Top-level grammar -->
<xs:group name="property">
  <xs:choice>
    <xs:element ref="ns1:adr"/>
    <xs:element ref="ns1:anniversary"/>
    <xs:element ref="ns1:bday"/>
    <xs:element ref="ns1:caladruri"/>
    <xs:element ref="ns1:caluri"/>
    <xs:element ref="ns1:categories"/>
    <xs:element ref="ns1:clientpidmap"/>
    <xs:element ref="ns1:email"/>
    <xs:element ref="ns1:fburl"/>
    <xs:element ref="ns1:fn"/>
    <xs:group ref="ns1:property-geo"/>
    <xs:element ref="ns1:impp"/>
    <xs:element ref="ns1:key"/>
    <xs:element ref="ns1:kind"/>
    <xs:element ref="ns1:lang"/>
    <xs:element ref="ns1:logo"/>
    <xs:element ref="ns1:member"/>
    <xs:element ref="ns1:n"/>
    <xs:element ref="ns1:nickname"/>
    <xs:element ref="ns1:note"/>
    <xs:element ref="ns1:org"/>
    <xs:element ref="ns1:photo"/>
    <xs:element ref="ns1:prodid"/>
    <xs:element ref="ns1:related"/>
```

```
<xs:element ref="ns1:rev"/>
<xs:element ref="ns1:role"/>
<xs:element ref="ns1:gender"/>
<xs:element ref="ns1:sound"/>
<xs:element ref="ns1:source"/>
```

```
<xs:element ref="ns1:tel"/>
<xs:element ref="ns1:title"/>
<xs:group ref="ns1:property-tz"/>
<xs:element ref="ns1:uid"/>
<xs:element ref="ns1:url"/>
</xs:choice>
</xs:group>

<xs:element name="vcards">
  <xs:complexType>
    <xs:sequence>
      <xs:element maxOccurs="unbounded" ref="ns1:vcard"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>

<xs:complexType name="vcardType">
  <xs:complexContent>
    <xs:restriction base="xs:anyType">
      <xs:choice maxOccurs="unbounded">
        <xs:group ref="ns1:property"/>
        <xs:element ref="ns1:group"/>
      </xs:choice>
    </xs:restriction>
  </xs:complexContent>
</xs:complexType>

<xs:element name="vcard" type="ns1:vcardType"/>

<xs:element name="group">
  <xs:complexType>
    <xs:group minOccurs="0" maxOccurs="unbounded"
      ref="ns1:property"/>
    <xs:attribute name="name" use="required"/>
  </xs:complexType>
</xs:element>
</xs:schema>
```

Authors' Addresses

Brian Rosen
NeuStar
470 Conrad Dr.
Mars, PA 16046
US

Phone: +1 724 382 1051
Email: br@brianrosen.net

Hannes Tschofenig
Nokia Siemens Networks
Linnoitustie 6
Espoo, 02600
Finland

Phone: +358 (50) 4871445
Email: Hannes.Tschofenig@gmx.net
URI: <http://www.tschofenig.priv.at>

Roger Marshall
TeleCommunication Systems, Inc.
2401 Elliott Avenue
Seattle, WA 98121
US

Phone: +1 206 792 2424
Email: rmarshall@telecomsys.com
URI: <http://www.telecomsys.com>

Randall Gellens
Qualcomm Technologies, Inc.
5775 Morehouse Drive
San Diego, CA 92121
US

Email: rg+ietf@qti.qualcomm.com

James Winterbottom
AU

Email: a.james.winterbottom@gmail.com

