

ECRIT
Internet-Draft
Intended status: Standards Track
Expires: January 5, 2016

R. Gellens
Qualcomm Technologies, Inc.
B. Rosen
NeuStar
H. Tschofenig

R. Marshall
TeleCommunication Systems, Inc.
J. Winterbottom

July 4, 2015

Additional Data Related to an Emergency Call
draft-ietf-ecrit-additional-data-32.txt

Abstract

When an emergency call is sent to a Public Safety Answering Point (PSAP), the originating device, the access network provider to which the device is connected, and all service providers in the path of the call have information about the call, the caller or the location which is helpful for the PSAP to have in handling the emergency. This document describes data structures and mechanisms to convey such data to the PSAP. The intent is that every emergency call carry the information described here using the mechanisms described here.

The mechanisms permit the data to be conveyed by reference (as an external resource) or by value (within the body of a SIP message or a location object). This follows the tradition of prior emergency services standardization work where data can be conveyed by value within the call signaling (i.e., in the body of the SIP message) or by reference.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on January 5, 2016.

Copyright Notice

Copyright (c) 2015 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	4
2.	Terminology	6
3.	Document Scope	7
4.	Data Structures	7
4.1.	Data Provider Information	9
4.1.1.	Data Provider String	9
4.1.2.	Data Provider ID	9
4.1.3.	Data Provider ID Series	10
4.1.4.	Type of Data Provider	11
4.1.5.	Data Provider Contact URI	12
4.1.6.	Data Provider Languages(s) Supported	13
4.1.7.	xCard of Data Provider	13
4.1.8.	Subcontractor Principal	14
4.1.9.	Subcontractor Priority	15
4.1.10.	ProviderInfo Example	15
4.2.	Service Information	17
4.2.1.	Service Environment	17
4.2.2.	Service Type	18
4.2.3.	Service Mobility Environment	20
4.2.4.	EmergencyCallData.ServiceInfo Example	21
4.3.	Device Information	22
4.3.1.	Device Classification	22
4.3.2.	Device Manufacturer	23
4.3.3.	Device Model Number	24
4.3.4.	Unique Device Identifier	24
4.3.5.	Device/Service-Specific Additional Data Structure	25
4.3.6.	Device/Service Specific Additional Data Structure Type	25
4.3.7.	Issues with getting new types of data into use	26

4.3.8.	Choosing between defining a new type of block or new type of device/service specific additional data . . .	27
4.3.9.	EmergencyCallData.DeviceInfo Example	28
4.4.	Owner/Subscriber Information	28
4.4.1.	Subscriber Data Privacy Indicator	28
4.4.2.	xCard for Subscriber's Data	29
4.4.3.	EmergencyCallData.SubscriberInfo Example	29
4.5.	Comment	32
4.5.1.	Comment	32
4.5.2.	EmergencyCallData.Comment Example	32
5.	Data Transport Mechanisms	32
5.1.	Transmitting Blocks using the Call-Info Header	34
5.2.	Transmitting Blocks by Reference using the <provided-by> Element	35
5.3.	Transmitting Blocks by Value using the <provided-by> Element	36
5.4.	The Content-Disposition Parameter	38
6.	Examples	39
7.	XML Schemas	52
7.1.	EmergencyCallData.ProviderInfo XML Schema	52
7.2.	EmergencyCallData.ServiceInfo XML Schema	54
7.3.	EmergencyCallData.DeviceInfo XML Schema	55
7.4.	EmergencyCallData.SubscriberInfo XML Schema	57
7.5.	EmergencyCallData.Comment XML Schema	58
7.6.	provided-by XML Schema	59
8.	Security Considerations	61
9.	Privacy Considerations	63
10.	IANA Considerations	66
10.1.	Registry creation	66
10.1.1.	Provider ID Series Registry	66
10.1.2.	Service Environment Registry	66
10.1.3.	Service Type Registry	67
10.1.4.	Service Mobility Registry	67
10.1.5.	Service Provider Type Registry	68
10.1.6.	Device Classification Registry	68
10.1.7.	Device ID Type Type Registry	68
10.1.8.	Device/Service Data Type Registry	69
10.1.9.	Emergency Call Data Types Registry	69
10.2.	'EmergencyCallData' Purpose Parameter Value	70
10.3.	URN Sub-Namespace Registration for <provided-by> Registry Entry	71
10.4.	MIME Registrations	71
10.4.1.	MIME Content-type Registration for 'application/EmergencyCallData.ProviderInfo+xml' . .	71
10.4.2.	MIME Content-type Registration for 'application/EmergencyCallData.ServiceInfo+xml' . .	72
10.4.3.	MIME Content-type Registration for 'application/EmergencyCallData.DeviceInfo+xml' . . .	73

10.4.4.	MIME Content-type Registration for 'application/EmergencyCallData.SubscriberInfo+xml' .	74
10.4.5.	MIME Content-type Registration for 'application/EmergencyCallData.Comment+xml'	75
10.5.	URN Sub-Namespace Registration	76
10.5.1.	Registration for urn:ietf:params:xml:ns:EmergencyCallData	76
10.5.2.	Registration for urn:ietf:params:xml:ns:EmergencyCallData:ProviderInfo	77
10.5.3.	Registration for urn:ietf:params:xml:ns:EmergencyCallData:ServiceInfo .	78
10.5.4.	Registration for urn:ietf:params:xml:ns:EmergencyCallData:DeviceInfo .	79
10.5.5.	Registration for urn:ietf:params:xml:ns:EmergencyCallData:SubscriberInfo	80
10.5.6.	Registration for urn:ietf:params:xml:ns:EmergencyCallData:Comment . .	81
10.6.	Schema Registrations	82
10.7.	VCard Parameter Value Registration	83
11.	Acknowledgments	83
12.	References	84
12.1.	Normative References	84
12.2.	Informational References	85
12.3.	URIs	86
Appendix A.	XML Schema for vCard/xCard	87
Appendix B.	XML Validation	109
	Authors' Addresses	109

[1.](#) Introduction

When an IP-based emergency call is initiated, a rich set of data from multiple data sources is conveyed to the Public Safety Answering Point (PSAP). This data includes information about the calling party identity, the multimedia capabilities of the device, the request for emergency services, location information, and meta-data about the sources of the data. In addition, the device, the access network provider, and any service provider in the call path has even more information that is useful for a PSAP when handling an emergency.

This document extends the basic set of data communicated with an IP-based emergency call, as described in [\[RFC6443\]](#) and [\[RFC6881\]](#), in order to carry additional data which is useful to an entity or call taker handling the call. This data is "additional" to the basic information found in the emergency call signaling used. The intent is that every emergency call carry the information described here using the mechanisms described here.

This document defines three categories of this additional data that can be transmitted with an emergency call:

Data Associated with a Location: Primary location data is conveyed in the Presence Information Data Format Location Object (PIDF-LO) data structure as defined in [RFC 4119](#) [[RFC4119](#)] and extended by [RFC 5139](#) [[RFC5139](#)] and [RFC 6848](#) [[RFC6848](#)] (for civic location information), [RFC 5491](#) [[RFC5491](#)] and [RFC 5962](#) [[RFC5962](#)] (for geodetic location information), and [[RFC7035](#)] (for relative location). This primary location data identifies the location or estimated location of the caller. However, there may exist additional, secondary data which is specific to the location, such as floor plans, tenant and building owner contact data, heating, ventilation and air conditioning (HVAC) status, etc. Such secondary location data is not included in the location data structure but can be transmitted using the mechanisms defined in this document. Although this document does not define any structures for such data, future documents may do so following the procedures defined here.

Data Associated with a Call: While some information is carried in the call setup procedure itself (as part of the SIP headers as well as in the body of the SIP message), there is additional data known by the device making the call, the access network to which the device is connected, and service providers along the path of the call. This information includes service provider contact information, subscriber identity and contact information, the type of service the service provider and the access network provide, what type of device is being used, etc. Some data is broadly applicable, while other data is dependent on the type of device or service. For example, a medical monitoring device may have sensor data. The data structures defined in this document (Data Provider Information, Device Information, and Owner/Subscriber Information) all fall into the category of "Data Associated with a Call". Note that the Owner/Subscriber Information includes the subscriber's vCard, which may contain personal information such as birthday, anniversary, etc., but the data block itself is still considered to be about the call, not the caller.

Data Associated with a Caller: This is personal data about a caller, such as medical information and emergency contact data. Although this document does not define any structures within this category, future documents may do so following the procedures defined here.

While this document defines data structures only within the category of Data Associated with a Call, by establishing the overall framework of Additional Data, along with general mechanisms for transport of such data, extension points and procedures for future extensions, it

minimizes the work needed to carry data in the other categories. Other specifications may make use of the facilities provided here.

For interoperability, there needs to be a common way for the information conveyed to a PSAP to be encoded and identified. Identification allows emergency services authorities to know during call processing which types of data are present and to determine if they wish to access it. A common encoding allows the data to be successfully accessed.

This document defines an extensible set of data structures, and mechanisms to transmit this data either by value or by reference, either in the Session Initiation Protocol (SIP) call signaling or in the Presence Information Data Format Location Object (PIDF-LO). The data structures are usable by other communication systems and transports as well. The data structures are defined in [Section 4](#), and the transport mechanisms (using SIP and HTTPS) are defined in [Section 5](#).

Each data structure described in this document is encoded as a "block" of information. Each block is an XML structure with an associated Multipurpose Internet Mail Extensions (MIME) type for identification within transport such as SIP and HTTPS. The set of blocks is extensible. Registries are defined to identify the block types that may be used and to allow blocks to be included in emergency call signaling.

Much of the information supplied by service providers and devices is private and confidential; service providers and devices generally go to lengths to protect this information; disclosing it in the context of an emergency call is a trade-off to protect the greater interest of the customer in an emergency.

2. Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)].

This document also uses terminology from [[RFC5012](#)]. We use the term service provider to refer to an Application Service Provider (ASP). A Voice Service Provider (VSP) is a special type of ASP. With the term "Access Network Provider" we refer to the Internet Access Provider (IAP) and the Internet Service Provider (ISP) without further distinguishing these two entities, since the difference between the two is not relevant for this document. Note that the roles of ASP and access network provider may be provided by a single company. An Emergency Services Provider is an entity directly

involved in providing emergency services. This includes PSAPs, dispatch, police, fire, emergency medical, other responders, and other similar agencies.

Within each data block definition (see [Section 4](#)), the values for the "Use:" label are specified as one of the following:

'Required': means it MUST be present in the data structure.

'Conditional': means it MUST be present if the specified condition(s) is met. It MAY be present if the condition(s) is not met.

'Optional': means it MAY be present.

vCard [[RFC6350](#)] is a data format for representing and exchanging a variety of information about individuals and other entities. For applications that use XML, the format defined in vCard is not immediately applicable. For this reason, an XML-based encoding of the information elements defined in the vCard specification has been defined and the name of that specification is xCard [[RFC6351](#)]. Since the term vCard is more familiar to most readers, we use the terms xCard and vCard interchangeably.

3. Document Scope

The scope of this document is explicitly limited to emergency calls. The data structures defined here are not appropriate to be conveyed with non-emergency calls because they carry sensitive and private data. However, in certain private-use situations where the endpoints have a preexisting relationship and privacy issues are addressed within the relationship or do not apply because of it, the mechanisms and data structures defined here MAY be used.

4. Data Structures

This section defines the following five data structures, each as a data block. For each block we define the MIME type, and the XML encoding. The five data structures are:

'Data Provider': This block supplies name and contact information for the entity that created the data. [Section 4.1](#) provides the details.

'Service Information': This block supplies information about the service. The description can be found in [Section 4.2](#).

'Device Information': This block supplies information about the device placing the call. Device information can be found in [Section 4.3](#).

'Owner/Subscriber': This block supplies information about the owner of the device or about the subscriber. Details can be found in [Section 4.4](#).

'Comment': This block provides a way to supply free form human readable text to the PSAP or emergency responders. This simple structure is defined in [Section 4.5](#).

Each block contains a mandatory <DataProviderReference> element. The purpose of the <DataProviderReference> element is to associate all blocks added by the same data provider as a unit. The <DataProviderReference> element associates the data provider block to each of the other blocks added as a unit. Consequently, when a data provider adds additional data to an emergency call (such as device information) it MUST add information about itself (via the data provider block) and the blocks added contain the same value in the <DataProviderReference> element. All blocks added by a single entity at the same time MUST have the same <DataProviderReference> value. The value of the <DataProviderReference> element has the same syntax and properties (specifically, world-uniqueness) as the value of the "Message-ID" message body header field specified in [RFC 5322](#) [[RFC5322](#)] except that the <DataProviderReference> element is not enclosed in brackets (the "<" and ">" symbols are omitted). In other words, the value of a <DataProviderReference> element is syntactically a msg-id as specified in [RFC 5322](#) [[RFC5322](#)].

Each block is added to the Additional Data Blocks Registry created in [Section 10.1.9](#) and categorized as providing data about the caller. New blocks added to the registry in the future MUST also be categorized per the description of the three categories in [Section 1](#). See [Section 4.3.7](#) and [Section 4.3.8](#) for additional considerations when adding new blocks or types of data.

Note that the xCard format is re-used in some of the data structures to provide contact information. In an xCard there is no way to specify a "main" telephone number. These numbers are useful to emergency responders who are called to a large enterprise. This document adds a new property value to the "tel" property of the TYPE parameter called "main". It can be used in any xCard in additional data.

4.1. Data Provider Information

This block is intended to be supplied by any service provider in the path of the call, or the access network provider, and the device. It includes identification and contact information. This block **MUST** be supplied by any entity that provides any other block; it **SHOULD** be supplied by every service provider in the call path and by the access network provider if those entities do not add any other blocks. Devices **SHOULD** use this block to provide identifying information. The MIME subtype is "application/EmergencyCallData.ProviderInfo+xml". An access network provider **SHOULD** provide this block either by value or by reference in the <provided-by> element of a PIDF-LO

4.1.1. Data Provider String

Data Element: Data Provider String

Use: Conditional

XML Element: <DataProviderString>

Description: This is a plain text string suitable for displaying the name of the service provider that supplied the data structure. If the device creates the structure, it **SHOULD** use the value of the contact header in the SIP INVITE.

Reason for Need: Inform the call taker of the identity of the entity providing the data.

How Used by Call Taker: Allows the call taker to interpret the data in this structure. The source of the information often influences how the information is used, believed or verified.

4.1.2. Data Provider ID

Data Element: Data Provider ID

Use: Conditional. Optional for blocks supplied by the originating device, mandatory otherwise. This data **MUST** be provided by all entities other than the originating device in order to uniquely identify the service provider or access provider.

XML Element: <ProviderID>

Description: A jurisdiction-specific code for, or the fully-qualified domain name of, the access network provider or service provider shown in the <DataProvidedBy> element that created the structure. NOTE: The value **SHOULD** be assigned by an organization

appropriate for the jurisdiction. In the U.S., if the provider is registered with NENA, the provider's NENA Company ID MUST appear here. Additional information can be found at NENA Company Identifier Program [\[1\]](#) or NENA Company ID [\[2\]](#). The NENA Company ID MUST be in the form of a URI in the following format: urn:nena:companyid:<NENA Company ID>. If the organization does not have an identifier registered with a jurisdiction-specific emergency services registrar (such as NENA), then the value MAY be the fully-qualified domain name of the service provider or access provider. The device MAY use its IP address or fully-qualified domain name (and set the "Data Provider ID Series" element to "domain").

Reason for Need: Inform the call taker of the identity of the entity providing the data.

How Used by Call Taker: Where jurisdictions have lists of providers the Data Provider ID provides useful information about the data source. The Data Provider ID uniquely identifies the source of the data, which might be needed especially during unusual circumstances and for routine logging.

[4.1.3](#). Data Provider ID Series

Data Element: Data Provider ID Series

Use: Conditional. Optional for blocks supplied by the originating device, mandatory otherwise.

XML Element: <ProviderIDSeries>

Description: Identifies the issuer of the <ProviderID>. The Provider ID Series Registry created in [Section 10.1.1](#) initially contains the entries shown in Figure 1.

Reason for Need: Identifies how to interpret the Data Provider ID. The combination of ProviderIDSeries and ProviderID MUST be globally unique.

How Used by Call Taker: Determines which provider ID registry to consult for more information

+-----+-----+-----+			
Name		Source	URL
+-----+-----+-----+			
NENA		National Emergency	http://www.nena.org
		Number Association	
EENA		European Emergency	http://www.eena.org
		Number Association	
domain		(The ID is a fully-	(not applicable)
		qualified domain name)	
+-----+-----+-----+			

Figure 1: Provider ID Series Registry

4.1.4. Type of Data Provider

Data Element: Type of Data Provider

Use: Required.

XML Element: <TypeOfProvider>

Description: Identifies the type of data provider supplying the data. The registry containing all valid values is created in [Section 10.1.5](#) and the initial set of values is shown in Figure 2.

Reason for Need: Identifies the category of data provider.

How Used by Call Taker: This information may be helpful when deciding whom to contact when further information is needed.

Token	Description
Client	Originating client/device
Access Network Provider	Access network service provider
Telecom Provider	Telecom service provider (including over-the-top VoIP services)
Telematics Provider	A sensor-based service provider, especially vehicle-based
Language Translation Provider	A spoken language translation service
Emergency Service Provider	An emergency service provider conveying information to another emergency service provider.
Emergency Modality Translation	An emergency-call-specific modality translation service e.g., for sign language
Relay Provider	A interpretation service, e.g., video relay for sign language interpreting
Other	Any other type of service provider

Figure 2: Type of Data Provider Registry

4.1.5. Data Provider Contact URI

Data Element: Data Provider Contact URI

Use: Required

XML Element: <ContactURI>

Description: When provided by a service provider or an access network provider, this information MUST be a URI to a 24/7 support organization tasked to provide PSAP support for this emergency call. When provided by a device, this MUST be the contact information of the user or owner of the device. (Ideally, this is the contact information of the device user, but when the owner and user are separate (e.g., the device owner is an organization), this MAY be the contact information of the owner.) The Data Provider Contact URI SHOULD be a TEL URI [[RFC3966](#)] in E.164 format fully specified with country code. If a TEL URI is not available, it MAY be a generic SIP URI. Note that this contact information is not used by PSAPs for callbacks (a call from a PSAP directly related to a recently terminated emergency call, placed by the PSAP using a SIP Priority header field set to "psap-callback", as described in [[RFC7090](#)]).

Reason for Need: Additional data providers may need to be contacted in error cases or other unusual circumstances.

How Used by Call Taker: To contact the supplier of the additional data for assistance in handling the call.

4.1.6. Data Provider Language(s) Supported

Data Element: Data Provider Language(s) supported

Use: Required.

XML Element: <Language>

Description: This field encodes the language used by the entity at the Data Provider Contact URI. The content of this field consists of a single token from the language tags registry, which can be found at [[LanguageTagRegistry](#)], and is defined in [[RFC5646](#)]. Multiple instances of this element may occur but the order is significant and the preferred language should appear first. The content MUST reflect the languages supported at the contact URI.

(Note that this field informs the PSAP of the language(s) used by the data provider. If the PSAP needs to contact the data provider, it can be helpful to know in advance the language(s) used by the data provider. If the PSAP uses a communication protocol to reach the data provider, that protocol may have language facilities of its own (such as the 'language' media feature tag, defined in [RFC 3840](#) [[RFC3840](#)] and the more extensive language negotiation mechanism proposed with [[I-D.gellens-slim-negotiating-human-language](#)]), and if so, those are independent of this field.)

Reason for Need: This information indicates if the emergency service authority can directly communicate with the service provider or if an interpreter will be needed.

How Used by Call Taker: If the call taker cannot speak any language supported by the service provider, a translation service will need to be added to the conversation. Alternatively, other persons at the PSAP, besides the call taker, might be consulted for help (depending on the urgency and the type of interaction).

4.1.7. xCard of Data Provider

Data Element: xCard of Data Provider

Use: Optional

XML Element: <DataProviderContact>

Description: Per [[RFC6351](#)] the xCard structure is represented within a <vcard> element. Although multiple <vcard> elements may be contained in a structure only one <vcard> element SHOULD be provided. If more than one appears, the first SHOULD be used. There are many fields in the xCard and the creator of the data structure is encouraged to provide all available information. N, ORG, ADR, TEL, EMAIL are suggested at a minimum. N SHOULD contain the name of the support group or device owner as appropriate. If more than one TEL property is provided, a parameter from the vCard Property Value registry MUST be specified for each TEL. For encoding of the vCard this specification uses the XML-based encoding specified in [[RFC6351](#)], referred to in this document as "xCard".

Reason for Need: Information needed to determine additional contact information.

How Used by Call Taker: Assists the call taker by providing additional contact information aside from what may be included in the SIP INVITE or the PIDF-LO.

4.1.8. Subcontractor Principal

When the entity providing the data is a subcontractor, the Data Provider Type is set to that of the primary service provider and this entry is supplied to provide information regarding the subcontracting entity.

Data Element: Subcontractor Principal

Use: Conditional. This data is required if the entity providing the data is a subcontractor.

XML Element: <SubcontractorPrincipal>

Description: Some providers outsource their obligations to handle aspects of emergency services to specialized providers. If the data provider is a subcontractor to another provider this element contains the DataProviderString of the service provider to indicate which provider the subcontractor is working for.

Reason for Need: Identify the entity the subcontractor works for.

How Used by Call Taker: Allows the call taker to understand what the relationship between data providers and the service providers in the path of the call are.

4.1.9. Subcontractor Priority

Data Element: Subcontractor Priority

Use: Conditional. This data is required if the entity providing the data is a subcontractor.

XML Element: <SubcontractorPriority>

Description: If the subcontractor is supposed to be contacted first then this element MUST have the value "sub". If the provider the subcontractor is working for is supposed to be contacted first then this element MUST have the value "main".

Reason for Need: Inform the call taker whom to contact first, if support is needed.

How Used by Call Taker: To decide which entity to contact first if assistance is needed.

4.1.10. ProviderInfo Example

```
<?xml version="1.0" encoding="UTF-8"?>
<ad:EmergencyCallData.ProviderInfo
  xmlns:ad="urn:ietf:params:xml:ns:EmergencyCallData:ProviderInfo">
  <ad:DataProviderReference>string0987654321@example.org
</ad:DataProviderReference>
  <ad:DataProviderString>Example VoIP Provider
</ad:DataProviderString>
  <ad:ProviderID>urn:nena:companyid:ID123</ad:ProviderID>
  <ad:ProviderIDSeries>NENA</ad:ProviderIDSeries>
  <ad:TypeOfProvider>Telecom Provider</ad:TypeOfProvider>
  <ad:ContactURI>tel:+1-201-555-0123</ad:ContactURI>
  <ad:Language>en</ad:Language>
  <ad:DataProviderContact
    xmlns="urn:ietf:params:xml:ns:vcard-4.0">
    <vcard>
      <fn><text>Hannes Tschofenig</text></fn>
      <n>
        <surname>Hannes</surname>
        <given>Tschofenig</given>
        <additional/>
        <prefix/>
        <suffix>Dipl. Ing.</suffix>
      </n>
      <bday><date>--0203</date></bday>
      <anniversary>
```



```
<date-time>20090808T1430-0500</date-time>
</anniversary>
<gender><sex>M</sex></gender>
<lang>
  <parameters><pref><integer>1</integer></pref>
</parameters>
  <language-tag>de</language-tag>
</lang>
<lang>
  <parameters><pref><integer>2</integer></pref>
</parameters>
  <language-tag>en</language-tag>
</lang>
<org>
  <parameters><type><text>work</text></type>
</parameters>
  <text>Example VoIP Provider</text>
</org>
<adr>
  <parameters>
    <type><text>work</text></type>
    <label><text>Hannes Tschofenig
      Linnoitustie 6
      Espoo , Finland
      02600</text></label>
  </parameters>
  <pobox/>
  <ext/>
  <street>Linnoitustie 6</street>
  <locality>Espoo</locality>
  <region>Uusimaa</region>
  <code>02600</code>
  <country>Finland</country>
</adr>
<tel>
  <parameters>
    <type>
      <text>work</text>
      <text>voice</text>
    </type>
  </parameters>
  <uri>tel:+358 50 4871445</uri>
</tel>
<email>
  <parameters><type><text>work</text></type>
</parameters>
  <text>hannes.tschofenig@nsn.com</text>
</email>
```



```

    <geo>
      <parameters><type><text>work</text></type>
    </parameters>
    <uri>geo:60.210796,24.812924</uri>
  </geo>
  <key>
    <parameters><type><text>home</text></type>
  </parameters>
  <uri>
    http://www.tschofenig.priv.at/key.asc
  </uri>
</key>
<tz><text>Finland/Helsinki</text></tz>
<url>
  <parameters><type><text>home</text></type>
</parameters>
  <uri>http://www.tschofenig.priv.at</uri>
</url>
</vcard>
</ad:DataProviderContact>
</ad:EmergencyCallData.ProviderInfo>

```

Figure 3: EmergencyCallData.ProviderInfo Example.

4.2. Service Information

This block describes the service that the service provider provides to the caller. It SHOULD be included by all service providers in the path of the call. The mime subtype is "application/EmergencyCallData.ServiceInfo+xml".

4.2.1. Service Environment

Data Element: Service Environment

Use: Conditional: Required unless the 'ServiceType' value is 'wireless'.

XML Element: <ServiceEnvironment>

Description: This element indicates whether a call is from a business or residence. Currently, the only valid entries are 'Business', 'Residence', and 'unknown', as shown in Figure 4. New values can be defined via the registry created in [Section 10.1.2](#).

Reason for Need: To provide context and a hint when determining equipment and manpower requirements.

How Used by Call Taker: Information may be used to provide context and a hint to assist in determining equipment and manpower requirements for emergency responders. Because there are situations where the service provider does not know (such as anonymous pre-paid service), and because the type of service does not necessarily reflect the nature of the premises (for example, a business line installed in a residence, or wireless service), and the registry is not all-encompassing, this is at best advisory information, but since it mimics a similar capability in some current emergency calling systems (e.g., a field in the Automatic Location Information (ALI) information used with legacy North American wireline systems), it is known to be valuable. The service provider uses its best information (such as a rate plan, facilities used to deliver service or service description) to determine the information and is not responsible for determining the actual characteristics of the location from which the call originated. Because the usefulness is unknown (and less clear) for wireless, this element is OPTIONAL for wireless and REQUIRED otherwise.

+-----+-----+	
Token	Description
+-----+-----+	
Business	Business service
Residence	Residential service
unknown	Type of service unknown
	(e.g., anonymous pre-
	paid service)
+-----+-----+	

Figure 4: Service Environment Registry

4.2.2. Service Type

Data Element: Service Delivered by Provider to End User

Use: Required

XML Element: <ServiceType>

Description: This defines the type of service over which the call is placed (similar to the Class of Service delivered with legacy emergency calls in some some regions). The implied mobility of this service cannot be relied upon. A registry is created in [Section 10.1.3](#). The initial set of values is shown in Figure 5. More than one value MAY be returned. For example, a VoIP inmate telephone service is a reasonable combination.

Reason for Need: Knowing the type of service may assist the PSAP in handling of the call.

How Used by Call Taker: Call takers often use this information to determine what kinds of questions to ask callers, and how much to rely on supportive information. An emergency call from a prison is treated differently than a call from a sensor device. As the information is not always available, and the registry is not all-encompassing, this is at best advisory information, but since it mimics a similar capability in some legacy emergency calling systems, it is known to be valuable.

Name	Description
wireless	Wireless Telephone Service: Includes CDMA, GSM, Wi-Fi, WiMAX, LTE (but not satellite)
coin	Fixed public pay/coin telephones: Any coin or credit card operated device
one-way	One way outbound service
prison	Inmate call/service
temp	Soft dial tone/quick service/warm disconnect/suspended
MLTS-hosted	Hosted multi-line telephone system such as Centrex
MLTS-local	Local multi-line telephone system, includes all PBX, key systems, Shared Tenant Service
sensor-unattended	These are devices that generate DATA ONLY. This is a one-way information transmit without interactive media
sensor-attended	Devices that are supported by a monitoring service provider or that are capable of supporting interactive media
POTS	Wireline: Plain Old Telephone Service
VOIP	An over-the-top service that provides communication over arbitrary Internet access (fixed, nomadic, mobile)
remote	Off-premise extension
relay	A service where a human third-party agent provides additional assistance. This includes sign language relay/interpretation, telematics services that provide a human on the call, and similar services.

Figure 5: Service Delivered by Provider to End User Registry

4.2.3. Service Mobility Environment

Data Element: Service Mobility Environment

Use: Required

XML Element: <ServiceMobility>

Description: This provides the service provider's view of the mobility of the caller's device. As the service provider might not know the characteristics of the actual device or access network used, the value should be treated as advisory and not be relied upon. A registry is created in [Section 10.1.4](#) with the initial valid entries shown in Figure 6.

Reason for Need: Knowing the service provider's belief of mobility may assist the PSAP with the handling of the call.

How Used by Call Taker: To determine whether to assume the location of the caller might change.

Token	Description
Mobile	The device is able to move at any time
Fixed	The device is not expected to move unless the service is relocated
Nomadic	The device is not expected to change its point of attachment while on a call
Unknown	No information is known about the service mobility environment for the device

Figure 6: Service Environment Registry

4.2.4. EmergencyCallData.ServiceInfo Example

```
<?xml version="1.0" encoding="UTF-8"?>
<svc:EmergencyCallData.ServiceInfo
  xmlns:svc="urn:ietf:params:xml:ns:EmergencyCallData:ServiceInfo">
  <svc:DataProviderReference>2468.IBOC.MLTS.1359@example.org
</svc:DataProviderReference>
  <svc:ServiceEnvironment>Business</svc:ServiceEnvironment>
  <svc:ServiceType>MLTS-hosted</svc:ServiceType>
  <svc:ServiceMobility>Fixed</svc:ServiceMobility>
</svc:EmergencyCallData.ServiceInfo>
```

Figure 7: EmergencyCallData.ServiceInfo Example.

4.3. Device Information

This block provides information about the device used to place the call. It should be provided by any service provider that knows what device is being used, and by the device itself. The mime subtype is "application/EmergencyCallData.DeviceInfo+xml".

4.3.1. Device Classification

Data Element: Device Classification

Use: Optional

XML Element: <DeviceClassification>

Description: This data element defines the kind of device making the emergency call. If the device provides the data structure, the device information SHOULD be provided. If the service provider provides the structure and it knows what the device is, the service provider SHOULD provide the device information. Often the carrier does not know what the device is. It is possible to receive two Additional Data Associated with a Call data structures, one created by the device and one created by the service provider. This information describes the device, not how it is being used. This data element defines the kind of device making the emergency call. A registry is created in [Section 10.1.6](#) with the initial set of values as shown in Figure 8.

Reason for Need: The device classification implies the capability of the calling device and assists in identifying the meaning of the emergency call location information that is being presented. For example, does the device require human intervention to initiate a call or is this call the result of programmed instructions? Does the calling device have the ability to update location or condition changes? Is this device interactive or a one-way reporting device?

How Used by Call Taker: May provide the call taker context regarding the caller, the capabilities of the calling device or the environment in which the device is being used, and may assist in understanding the location information and capabilities of the calling device. For example, a cordless handset may be outside or next door.

Token	Description
cordless	Cordless handset
fixed	Fixed phone
satellite	Satellite phone
sensor-fixed	Fixed (non mobile) sensor/alarm device
desktop	Soft client on desktop PC
laptop	Soft client on laptop type device
tablet	Soft client on tablet type device
alarm-monitored	Alarm system
sensor-mobile	Mobile sensor device
aircraft	Aircraft telematics device
automobile	Automobile/cycle/off-road telematics
truck	Truck/construction telematics
farm	Farm equipment telematics
marine	Marine telematics
personal	Personal telematics device
feature-phone	Feature- (not smart-) cellular phone
smart-phone	Smart-phone cellular phone (native)
smart-phone-app	Soft client app on smart-phone
unknown-device	Soft client on unknown device type
game	Gaming console
text-only	Other text device
NA	Not Available

Figure 8: Device Classification Registry Initial Values

4.3.2. Device Manufacturer

Data Element: Device Manufacturer

Use: Optional

XML Element: <DeviceMfgr>

Description: The plain language name of the manufacturer of the device.

Reason for Need: Used by PSAP management for post-mortem investigation/resolution.

How Used by Call Taker: Probably not used by the calltaker, but by PSAP management.

4.3.3. Device Model Number

Data Element: Device Model Number

Use: Optional

XML Element: <DeviceModelNr>

Description: Model number of the device.

Reason for Need: Used by PSAP management for after-action investigation/resolution.

How Used by Call Taker: Probably not used by the calltaker, but by PSAP management.

4.3.4. Unique Device Identifier

Data Element: Unique Device Identifier

Use: Optional

XML Element: <UniqueDeviceID>

XML Attribute: <TypeOfDeviceID>

Description: A string that identifies the specific device (or the device's current SIM) making the call or creating an event. Note that more than one <UniqueDeviceID> may be present, to supply more than one of the identifying values.

The <TypeOfDeviceID> attribute identifies the type of device identifier. A registry is created in [Section 10.1.7](#) with an initial set of values shown in Figure 9.

Reason for Need: Uniquely identifies the device (or, in the case of IMSI, a SIM), independent of any signaling identifiers present in the call signaling stream.

How Used by Call Taker: Probably not used by the call taker; may be used by PSAP management during an investigation.

Example: <UniqueDeviceID TypeOfDeviceID="SN">12345</UniqueDeviceID>

+-----+-----+-----+-----+-----+		
Token	Description	
+-----+-----+-----+-----+-----+		
MEID	Mobile Equipment Identifier (CDMA)	
ESN	Electronic Serial Number (GSM)	
MAC	Media Access Control Address (IEEE)	
WiMAX	Device Certificate Unique ID	
IMEI	International Mobile Equipment ID (GSM)	
IMSI	International Mobile Subscriber ID (GSM)	
UDI	Unique Device Identifier	
RFID	Radio Frequency Identification	
SN	Manufacturer Serial Number	
+-----+-----+-----+-----+-----+		

Figure 9: Registry of Device Identifier Types

4.3.5. Device/Service-Specific Additional Data Structure

Data Element: Device/service-specific additional data structure

Use: Optional

XML Element: <DeviceSpecificData>

Description: A URI representing additional data whose schema is specific to the device or service which created it. (For example, a medical device or medical device monitoring service may have a defined set of medical data). The URI, when dereferenced, MUST yield a data structure defined by the Device/service specific additional data type value. Different data may be created by each classification; e.g., a medical device created data set.

Reason for Need: Provides device/service specific data that may be used by the call taker and/or responders.

How Used by Call Taker: Provide information to guide call takers to select appropriate responders, give appropriate pre-arrival instructions to callers, and advise responders of what to be prepared for. May be used by responders to guide assistance provided.

4.3.6. Device/Service Specific Additional Data Structure Type

Data Element: Type of device/service-specific additional data structure

Use: Conditional. MUST be provided when device/service specific-additional URI is provided

XML Element: <DeviceSpecificType>

Description: A value from the registry defined in [Section 10.1.8](#) to describe the type of data located at the device/service-specific additional data structure. The initial values shown in Figure 10 currently only include IEEE 1512, which is the USDoT model for traffic incidents.

Reason for Need: This data element allows identification of externally defined schemas, which may have additional data that may assist in emergency response.

How Used by Call Taker: This data element allows the end user (call taker or first responder) to know what type of additional data may be available to aid in providing the needed emergency services.

Note: Information which is specific to a location or a caller (person) should not be placed in this section.

Token	Description	Specification
IEEE1512	Common Incident Management Message Set (USDoT model for traffic incidents)	IEEE 1512-2006 https://standards.ieee.org/findstds/standard/1512-2006.html

Figure 10: Device/Service Data Type Registry

[4.3.7.](#) Issues with getting new types of data into use

This document describes two mechanisms that allow extension of the kind of data provided with an emergency call: define a new block or define a new service specific additional data URL for the DeviceInfo block. While defining new data types and getting a new device or application to send the new data may be easy, getting PSAPs and responders to actually retrieve the data and use it will be difficult. New mechanism providers should understand that acquiring and using new forms of data usually require software upgrades at the PSAP and/or responders, as well as training of call takers and responders in how to interpret and use the information. Legal and operational review may also be needed. Overwhelming a call taker or responder with too much information is highly discouraged. Thus, the barrier to supporting new data is quite high.

The mechanisms this document describes are meant to encourage development of widely supported, common data formats for classes of devices. If all manufacturers of a class of device use the same

format, and the data can be shown to improve outcomes, then PSAPs and responders may be encouraged to upgrade their systems and train their staff to use the data. Variations, however well intentioned, are unlikely to be supported.

Implementers should consider that data from sensor-based devices in some cases may not be useful to call takers or PSAPs (and privacy or other considerations may preclude the PSAP from touching the data), but may be of use to responders. Each data item provided with the call in conformance with this document can be accessed by responders or other entities in the emergency services, whether or not the data is accessed by the PSAP.

4.3.8. Choosing between defining a new type of block or new type of device/service specific additional data

For devices that have device or service specific data, there are two choices to carry it. A new block can be defined, or the device/service specific additional data URL the DeviceInfo block can be used and a new type for it defined. The data passed would likely be the same in both cases. Considerations for choosing which mechanism to register under include:

Applicability: Information which will be carried by many kinds of devices or services are more appropriately defined as separate blocks.

Privacy: Information which may contain private data may be better sent in the DeviceInfo block, rather than a new block so that implementations are not tempted to send the data by value, and thus having more exposure to the data than forcing the data to be retrieved via the URL in DeviceInfo.

Size: Information which may be very large may be better sent in the DeviceInfo block, rather than a new block so that implementations are not tempted to send the data by value. Conversely, data which is small may best be sent in a separate block so that it can be sent by value

Availability of a server: Providing the data via the device block requires a server be made available to retrieve the data. Providing the data via new block allows it to be sent by value (CID).

4.3.9. EmergencyCallData.DeviceInfo Example

```
<?xml version="1.0" encoding="UTF-8"?>
<dev:EmergencyCallData.DeviceInfo
  xmlns:dev="urn:ietf:params:xml:ns:EmergencyCallData:DeviceInfo">
  <dev:DataProviderReference>d4b3072df.201409182208075@example.org
  </dev:DataProviderReference>
  <dev:DeviceClassification>fixed</dev:DeviceClassification>
  <dev:DeviceMfgr>Nokia</dev:DeviceMfgr>
  <dev:DeviceModelNr>Lumia 800</dev:DeviceModelNr>
  <dev:UniqueDeviceID TypeOfDeviceID="IMEI">35788104
  </dev:UniqueDeviceID>
</dev:EmergencyCallData.DeviceInfo>
```

Figure 11: EmergencyCallData.DeviceInfo Example.

4.4. Owner/Subscriber Information

This block describes the owner of the device (if provided by the device) or the subscriber information (if provided by a service provider). The contact location is not necessarily the location of the caller or incident, but is rather the nominal contact address. The MIME type is "application/EmergencyCallData.SubscriberInfo+xml".

In some jurisdictions some or all parts of the subscriber-specific information are subject to privacy constraints. These constraints vary but dictate what information can be displayed and logged. A general privacy indicator expressing a desire for privacy by the subscriber is provided. The interpretation of how this is applied is left to the receiving jurisdiction as the custodians of the local regulatory requirements. This matches an equivalent privacy flag provided in some legacy emergency call systems.

4.4.1. Subscriber Data Privacy Indicator

Attribute: 'privacyRequested', Boolean.

Use: Conditional. This attribute MUST be provided if the owner/subscriber information block is not empty.

Description: The subscriber data privacy indicator specifically expresses the subscriber's desire for privacy. In some jurisdictions subscriber services can have a specific "Type of Service" which prohibits information, such as the name of the subscriber, from being displayed. This attribute is provided to explicitly indicate whether the subscriber service includes such constraints. The interpretation of this indicator is left to each

jurisdiction (in keeping with the semantics of the privacy indicator provided in some legacy emergency call systems).

Reason for Need: Some jurisdictions require subscriber privacy to be observed when processing emergency calls.

How Used by Call Taker: Where privacy is indicated the call taker may not have access to some aspects of the subscriber information.

4.4.2. xCard for Subscriber's Data

Data Element: xCARD for Subscriber's Data

Use: Conditional. Subscriber data MUST be provided unless it is not available. Some services, such as prepaid phones, non-initialized phones, etc., do not have information about the subscriber.

XML Element: <SubscriberData>

Description: Information known by the service provider or device about the subscriber; e.g., Name, Address, Individual Telephone Number, Main Telephone Number and any other data. <n>, <org> (if appropriate), <adr>, <tel>, <email> are suggested at a minimum. If more than one <tel> property is provided, a parameter from the vCard Property Value registry MUST be specified on each <tel>. While some data (such as <anniversary>) might not seem obviously relevant for emergency services, any data is potentially useful in some emergency circumstances.

Reason for Need: When the caller is unable to provide information, this data may be used to obtain it

How Used by Call Taker: Obtaining critical information about the caller and possibly the location when it is not able to be obtained otherwise. While the location here is not necessarily that of caller, in some circumstances it can be helpful in locating the caller when other means have failed.

4.4.3. EmergencyCallData.SubscriberInfo Example

```
<?xml version="1.0" encoding="UTF-8"?>
<sub:EmergencyCallData.SubscriberInfo
  xmlns:sub=
    "urn:ietf:params:xml:ns:EmergencyCallData:SubscriberInfo"
  privacyRequested="false">
  <sub:DataProviderReference>FEABFECD901@example.org
</sub:DataProviderReference>
```



```
<sub:SubscriberData xmlns="urn:ietf:params:xml:ns:vcard-4.0">
  <vcard>
    <fn><text>Simon Perreault</text></fn>
    <n>
      <surname>Perreault</surname>
      <given>Simon</given>
      <additional/>
      <prefix/>
      <suffix>ing. jr</suffix>
      <suffix>M.Sc.</suffix>
    </n>
    <bday><date>--0203</date></bday>
    <anniversary>
      <date-time>20090808T1430-0500</date-time>
    </anniversary>
    <gender><sex>M</sex></gender>
    <lang>
      <parameters><pref><integer>1</integer></pref>
      </parameters>
      <language-tag>fr</language-tag>
    </lang>
    <lang>
      <parameters><pref><integer>2</integer></pref>
      </parameters>
      <language-tag>en</language-tag>
    </lang>
    <org>
      <parameters><type><text>work</text></type>
      </parameters>
      <text>Viagenie</text>
    </org>
    <adr>
      <parameters>
        <type><text>work</text></type>
        <label><text>Simon Perreault
          2875 boul. Laurier, suite D2-630
          Quebec, QC, Canada
          G1V 2M2</text></label>
      </parameters>
      <pobox/>
      <ext/>
      <street>2875 boul. Laurier, suite D2-630</street>
      <locality>Quebec</locality>
      <region>QC</region>
      <code>G1V 2M2</code>
      <country>Canada</country>
    </adr>
    <tel>
```



```
<parameters>
  <type>
    <text>work</text>
    <text>voice</text>
  </type>
</parameters>
<uri>tel:+1-418-656-9254;ext=102</uri>
</tel>
<tel>
  <parameters>
    <type>
      <text>work</text>
      <text>text</text>
      <text>voice</text>
      <text>cell</text>
      <text>video</text>
    </type>
  </parameters>
  <uri>tel:+1-418-262-6501</uri>
</tel>
<email>
  <parameters><type><text>work</text></type>
</parameters>
  <text>simon.perreault@viagenie.ca</text>
</email>
<geo>
  <parameters><type><text>work</text></type>
</parameters>
  <uri>geo:46.766336, -71.28955</uri>
</geo>
<key>
  <parameters><type><text>work</text></type>
</parameters>
  <uri>
http://www.viagenie.ca/simon.perreault/simon.asc
  </uri>
</key>
<tz><text>America/Montreal</text></tz>
<url>
  <parameters><type><text>home</text></type>
</parameters>
  <uri>http://nomis80.org</uri>
</url>
</vcard>
</sub:SubscriberData>
</sub:EmergencyCallData.SubscriberInfo>
```

Figure 12: EmergencyCallData.SubscriberInfo Example.

4.5. Comment

This block provides a mechanism for the data provider to supply extra, human readable information to the PSAP. It is not intended for a general purpose extension mechanism nor does it aim to provide machine-readable content. The mime subtype is "application/EmergencyCallData.Comment+xml"

4.5.1. Comment

Data Element: EmergencyCallData.Comment

Use: Optional

XML Element: <Comment>

Description: Human readable text providing additional information to the PSAP staff.

Reason for Need: Explanatory information for values in the data structure.

How Used by Call Taker: To interpret the data provided.

4.5.2. EmergencyCallData.Comment Example

```
<?xml version="1.0" encoding="UTF-8"?>
<com:EmergencyCallData.Comment
  xmlns:com="urn:ietf:params:xml:ns:EmergencyCallData:Comment">
  <com:DataProviderReference>string0987654321@example.org
</com:DataProviderReference>
  <com:Comment xml:lang="en">This is an example text.</com:Comment>
</com:EmergencyCallData.Comment>
```

Figure 13: EmergencyCallData.Comment Example.

5. Data Transport Mechanisms

This section defines how to convey additional data to an emergency service provider. Two different means are specified: the first uses the call signaling; the second uses the <provided-by> element of a PIDF-LO [RFC4119].

1. First, the ability to embed a Uniform Resource Identifier (URI) in an existing SIP header field, the Call-Info header, is defined. The URI points to the additional data structure. The Call-Info header is specified in [Section 20.9 of \[RFC3261\]](#). This

document adds a new compound token starting with the value 'EmergencyCallData' for the Call-Info "purpose" parameter. If the "purpose" parameter is set to a value starting with 'EmergencyCallData', then the Call-Info header contains either an HTTPS URL pointing to an external resource or a CID (content indirection) URI that allows the data structure to be placed in the body of the SIP message. The "purpose" parameter also indicates the kind of data (by its MIME subtype) that is available at the URI. As the data is conveyed using a URI in the SIP signaling, the data itself may reside on an external resource, or may be contained within the body of the SIP message. When the URI refers to data at an external resource, the data is said to be passed by reference. When the URI refers to data contained within the body of the SIP message, the data is said to be passed by value. A PSAP or emergency responder is able to examine the type of data provided and selectively inspect the data it is interested in, while forwarding all of it (the values or references) to downstream entities. To be conveyed in a SIP body, additional data about a call is defined as a series of MIME objects. Each block defined in this document is an XML data structure identified by its MIME type. (Blocks defined by others may be encoded in XML or not, as identified by their MIME registration.) As usual, whenever more than one MIME part is included in the body of a message, MIME multipart (i.e., 'multipart/mixed') encloses them all. This document defines a set of XML schemas and MIME types used for each block defined here. When additional data is passed by value in the SIP signaling, each CID URL points to one block in the body. Multiple URIs are used within a Call-Info header field (or multiple Call-Info header fields) to point to multiple blocks. When additional data is provided by reference (in SIP signaling or the <provided-by> element of a PIDF-LO), each HTTPS URL references one block; the data is retrieved with an HTTPS GET operation, which returns the block as an object (the blocks defined here are returned as XML objects).

2. Second, the ability to embed additional data structures in the <provided-by> element of a PIDF-LO [[RFC4119](#)] is defined. In addition to service providers in the call path, the access network provider may also have similar information that can be valuable to the PSAP. When the access network provider supplies location information in the form of a PIDF-LO from a location server via a location configuration protocol, it has the ability to add the data structures defined in this document within the PIDF-LO. The data in these data structures is not specific to the location itself, but rather provides descriptive information having to do with the immediate circumstances about the provision of the location (e.g., the identity of the access network

provider, how to contact that entity, what kind of service the access network provides, subscriber information, etc.). This data is similar in nearly every respect to the data known by service providers in the path of the call. When the access network provider and service provider are separate entities, the access network does not participate in the application layer signaling (and hence cannot add a Call-Info header field to the SIP message), but can provide location information in a PIDF-LO. The <provided-by> element of the PIDF-LO is a mechanism for the access network provider to supply the information. For this reason, this document describes a namespace per [RFC4119] for inclusion in the <provided-by> element of a PIDF-LO for adding information known to the access network provider. The access network provider SHOULD provide additional data within a <provided-by> element of a PIDF-LO it returns for emergency use (e.g., if requested with a HELD "responseTime" attribute of "emergencyRouting" or "emergencyDispatch" [RFC5985]).

One or more blocks of data registered in the Emergency Call Additional Data registry, as defined in [Section 10.1.9](#), can be included or referenced in the SIP signaling (using the Call-Info header field) or in the <provided-by> element of a PIDF-LO. For interoperability, only blocks in the registry are permitted to be sent using the mechanisms specified in this document. Since multiple entities are expected to provide sets of data, the data itself needs information describing the source. Consequently, each entity adding additional data MUST supply a "Data Provider" block. All other blocks are optional, but each entity SHOULD supply all blocks where it has at least some of the information in the block.

5.1. Transmitting Blocks using the Call-Info Header

A URI to a block MAY be inserted in any SIP request or response method (most often INVITE or MESSAGE) with a Call-Info header field containing a purpose value starting with 'EmergencyCallData', a dot ("."), and the type of data available at the URI. The type of data is denoted by including the root of the MIME subtype (the 'EmergencyCallData' prefix is not repeated), omitting any suffix such as '+xml'). For example, when referencing a block with MIME type 'application/EmergencyCallData.ProviderInfo+xml', the 'purpose' parameter is set to 'EmergencyCallData.ProviderInfo'. An example "Call-Info" header field for this would be:

```
Call-Info: https://www.example.com/23sedde3;  
           purpose="EmergencyCallData.ProviderInfo"
```

A Call-info header with a purpose value starting with 'EmergencyCallData' only has meaning in the context of an emergency

call (as ascertained by the presence of an emergency service URN in a Request-URI header of a SIP message), test emergency calls (using an appropriate service URN), and some private-use calls where the endpoints have a preexisting relationship and privacy concerns do not apply because of the relationship; use in other contexts is undefined and is likely to unnecessarily expose confidential data.

If the data is provided by reference, an HTTPS URI **MUST** be included and consequently Transport Layer Security (TLS) protection is applied for protecting the retrieval of the information.

The data may also be supplied by value in any SIP request or response method that is permitted to contain a body (i.e., not a BYE request). In this case, Content Indirection (CID) [[RFC2392](#)] is used, with the CID URL referencing the MIME body part containing the data. Note that [[RFC3261](#)] forbids proxies from altering message bodies, so entities in the call path that add blocks by value need to do so using an appropriate SIP entity (e.g., a back-to-back user agent).

Transmitting data by value is especially useful in certain cases, such as when the data exists in or is generated by the originating device, but is not intended for very large data blocks. Additional security and privacy considerations apply to data transmitted by value, as discussed in [Section 8](#) and [Section 9](#).

More than one Call-Info header with a purpose value starting with 'EmergencyCallData' can be expected, but at least one **MUST** be provided. The device **MUST** provide one if it knows no service provider is in the path of the call. The device **MAY** insert one if it uses a service provider. Any service provider in the path of the call **MUST** insert its own. For example, a device, a telematics service provider in the call path, as well as the mobile carrier handling the call will each provide one. There may be circumstances where there is a service provider who is unaware that the call is an emergency call and cannot reasonably be expected to determine that it is an emergency call. In that case, that service provider is not expected to provide EmergencyCallData.

5.2. Transmitting Blocks by Reference using the <provided-by> Element

The <EmergencyCallDataReference> element is used to transmit an additional data block by reference within a <provided-by> element of a PIDF-LO. The <EmergencyCallDataReference> element has two attributes: 'ref' to specify the URL, and 'purpose' to indicate the type of data block referenced. The value of 'ref' is an HTTPS URL that resolves to a data structure with information about the call. The value of 'purpose' is the same as used in a 'Call-Info' header field (as specified in [Section 5.1](#)).

For example, to reference a block with MIME type 'application/EmergencyCallData.ProviderInfo+xml', the 'purpose' parameter is set to 'EmergencyCallData.ProviderInfo'. An example `<EmergencyCallDataReference>` element for this would be:

```
<EmergencyCallDataReference ref="https://www.example.com/23sedde3"
  purpose="EmergencyCallData.ProviderInfo"/>
```

The `<EmergencyCallDataReference>` element transmits one data block; multiple data blocks may be transmitted by using multiple `<EmergencyCallDataReference>` elements. Multiple `<EmergencyCallDataReference>` elements MAY be included as child elements inside the `<provided-by>` element.

The following is a simplified example:

```
<provided-by
  <EmergencyCallDataReference
    purpose="EmergencyCallData.ServiceInfo"
    ref="https://example.com/ref2" />

  <EmergencyCallDataReference
    purpose="EmergencyCallData.ProviderInfo"
    ref="https://example.com/ref3" />

  <EmergencyCallDataReference
    purpose="EmergencyCallData.Comment"
    ref="https://example.com/ref4" />
</provided-by>
```

Example `<provided-by>` by Reference

For an example in context, Figure 18 shows a PIDF-LO example with an `<EmergencyCallDataReference>` element pointing to an `EmergencyCallData.ServiceInfo` data block with the URL in the 'ref' attribute and the purpose attribute set to "EmergencyCallData.ServiceInfo".

5.3. Transmitting Blocks by Value using the `<provided-by>` Element

It is RECOMMENDED that access networks supply the data specified in this document by reference, but they MAY provide the data by value.

The `<EmergencyCallDataValue>` element is used to transmit one or more additional data blocks by value within a `<provided-by>` element of a PIDF-LO. Each block being transmitted is placed (as a child element)

inside the <EmergencyCallDataValue> element. (The same XML structure as would be contained in the corresponding MIME type body part is placed inside the <EmergencyCallDataValue> element.) Multiple <EmergencyCallDataValue> elements MAY be included as child elements in the <provided-by> element.

The following is a simplified example:

<provided-by

```
<EmergencyCallDataValue>

  <EmergencyCallData.ProviderInfo
    xmlns=
      "urn:ietf:params:xml:ns:EmergencyCallData:ProviderInfo">
    <DataProviderReference>flurbit735@es.example.com
      </DataProviderReference>
    <DataProviderString>Access Network Examples, Inc
      </DataProviderString>
    <ProviderID>urn:nena:companyid:Test</ProviderID>
    <ProviderIDSeries>NENA</ProviderIDSeries>
    <TypeOfProvider>Access Network Provider
      </TypeOfProvider>
    <ContactURI>tel:+1-555-555-0897</ContactURI>
    <Language>en</Language>
  </EmergencyCallData.ProviderInfo>

  <EmergencyCallData.Comment
    xmlns=
      "urn:ietf:params:xml:ns:EmergencyCallData:Comment">
    <DataProviderReference>flurbit735@es.example.com
      </DataProviderReference>
    <Comment xml:lang="en">This is an example text.
      </Comment>
  </EmergencyCallData.Comment>

</EmergencyCallDataValue>
```

</provided-by>

Example <provided-by> by Value

For an example in context, Figure 18 shows a PIDF-LO example that contains a <provided-by> element with the <EmergencyCallData.ProviderInfo> and the <EmergencyCallData.Comment> elements as child elements of an <EmergencyCallDataValue> element.

5.4. The Content-Disposition Parameter

[RFC 5621](#) [[RFC5621](#)] discusses the handling of message bodies in SIP. It updates and clarifies handling originally defined in [RFC 3261](#) [[RFC3261](#)] based on implementation experience. While [RFC 3261](#) did not mandate support for 'multipart' message bodies, 'multipart/mixed' MIME bodies are used by many extensions (including this document) today. For example, adding a PIDF-LO, SDP, and additional data in body of a SIP message requires a 'multipart' message body.

[RFC 3204](#) [[RFC3204](#)] and [RFC 3459](#) [[RFC3459](#)] define the 'handling' parameter for the Content-Disposition header field. These RFCs describe how a UAS reacts if it receives a message body whose content type or disposition type it does not understand. If the 'handling' parameter has the value "optional", the UAS ignores the message body. If the 'handling' parameter has the value "required", the UAS returns a 415 (Unsupported Media Type) response. The 'by-reference' disposition type allows a SIP message to contain a reference to the body part, and the SIP UA processes the body part according to the reference. This is the case for the Call-info header containing a Content Indirection (CID) URL.

As an example, a SIP message indicates the Content-Disposition parameter in the body of the SIP message as shown in Figure 14.


```
Content-Type: application/sdp

...Omit Content-Disposition here; defaults are ok
...SDP goes in here

--boundary1

Content-Type: application/pidf+xml
Content-ID: <target123@atlanta.example.com>
Content-Disposition: by-reference;handling=optional

...PIDF-LO goes in here

--boundary1--

Content-Type: application/EmergencyCallData.ProviderInfo+xml
Content-ID: <1234567890@atlanta.example.com>
Content-Disposition: by-reference; handling=optional

...Data provider information data goes in here

--boundary1--
```

Figure 14: Example for use of the Content-Disposition Parameter in SIP

6. Examples

This section illustrates a longer and more complex example, as shown in Figure 15. In this example additional data is added by the end device, included by the VoIP provider, and provided by the access network provider (via the PIDF-LO).


```

0  +-----+ [=====] [=====]
/|\ | UA | [ Access ] [ VoIP ]
| +-----+ [ Network ] [ Provider ]
/ \ [ Provider ] [ example.org ]
[ ] [ ]
(1) [ ] (2) [ ]
Emergency Call [ ] Emergency Call [ ]
----->
+Device Info [ ] +Device Info [ ]
+Data Prov. Info [ ^ ] +Data Provider Info [ | ]
+Location URI [=====] +Location URI [=====]
. |
. |
+Location . [=====] |
+Owner/Subscriber Info . [ ] (3) |
+Device Info . (4) [ <-----+
+Data Provider Info #3 .....> ] Emergency Call
[ ] +Device Info
[ PSAP ] +Data Prov. Info #2
[ ] +Location URI
[=====]

```

Legend:

```

--- Emergency Call Setup Procedure
... Location Retrieval/Response

```

Figure 15: Additional Data Example Flow

The example scenario starts with the end device itself adding device information, owner/subscriber information, a location URI, and data provider information to the outgoing emergency call setup message (see step #1 in Figure 15). The SIP INVITE example is shown in Figure 16.

```

INVITE urn:service:sos SIP/2.0
Via: SIP/2.0/TLS server.example.com;branch=z9hG4bK74bf9
Max-Forwards: 70
To: <urn:service:sos>
From: Hannes Tschofenig <sips:hannes@example.com>;tag=9fxced76s1
Call-ID: 3848276298220188511@example.com
Call-Info: <http://www.example.com/hannes/photo.jpg>
           ;purpose=icon,
           <http://www.example.com/hannes/> ;purpose=info,
           <cid:1234567890@atlanta.example.com>
           ;purpose=EmergencyCallData.ProviderInfo,

```



```
<cid:0123456789@atlanta.example.com>
  ;purpose=EmergencyCallData.DeviceInfo
Geolocation: <https://ls.example.net:9768/357yc6s64ceyoivy5ax3o>
Geolocation-Routing: yes
Accept: application/sdp, application/pidf+xml,
       application/EmergencyCallData.ProviderInfo+xml
CSeq: 31862 INVITE
Contact: <sips:hannes@example.com>
Content-Type: multipart/mixed; boundary=boundary1

Content-Length: ...

--boundary1

Content-Type: application/sdp

...SDP goes here

--boundary1--

Content-Type: application/EmergencyCallData.DeviceInfo+xml
Content-ID: <0123456789@atlanta.example.com>
Content-Disposition: by-reference;handling=optional
<?xml version="1.0" encoding="UTF-8"?>

<dev:EmergencyCallData.DeviceInfo
  xmlns:dev="urn:ietf:params:xml:ns:EmergencyCallData:DeviceInfo">
  <dev:DataProviderReference>d4b3072df09876543@[93.184.216.119]
  </dev:DataProviderReference>
  <dev:DeviceClassification>laptop</dev:DeviceClassification>
  <dev:UniqueDeviceID
    TypeOfDeviceID="MAC">00-0d-4b-30-72-df</dev:UniqueDeviceID>
  </dev:EmergencyCallData.DeviceInfo>

--boundary1--

Content-Type: application/EmergencyCallData.ProviderInfo+xml
Content-ID: <1234567890@atlanta.example.com>
Content-Disposition: by-reference;handling=optional
<?xml version="1.0" encoding="UTF-8"?>
<pi:EmergencyCallData.ProviderInfo
  xmlns:pi="urn:ietf:params:xml:ns:EmergencyCallData:ProviderInfo">
  <pi:DataProviderReference>d4b3072df09876543@[93.184.216.119]
  </pi:DataProviderReference>
  <pi:DataProviderString>Hannes Tschofenig
  </pi:DataProviderString>
  <pi:TypeOfProvider>Client</pi:TypeOfProvider>
```



```
<pi:ContactURI>tel:+1-555-555-0123</pi:ContactURI>
<pi:Language>en</pi:Language>
<pi:DataProviderContact
  xmlns="urn:ietf:params:xml:ns:vcard-4.0">
  <vcard>
    <fn><text>Hannes Tschofenig</text></fn>
    <n>
      <surname>Hannes</surname>
      <given>Tschofenig</given>
      <additional/>
      <prefix/>
      <suffix>Dipl. Ing.</suffix>
    </n>
    <bday><date>--0203</date></bday>
    <anniversary>
      <date-time>20090808T1430-0500</date-time>
    </anniversary>
    <gender><sex>M</sex></gender>
    <lang>
      <parameters><pref><integer>1</integer></pref>
      </parameters>
      <language-tag>de</language-tag>
    </lang>
    <lang>
      <parameters><pref><integer>2</integer></pref>
      </parameters>
      <language-tag>en</language-tag>
    </lang>
    <adr>
      <parameters>
        <type><text>work</text></type>
        <label><text>Hannes Tschofenig
          Linnoitustie 6
          Espoo, Finland
          02600</text></label>
      </parameters>
      <pobox/>
      <ext/>
      <street>Linnoitustie 6</street>
      <locality>Espoo</locality>
      <region>Uusimaa</region>
      <code>02600</code>
      <country>Finland</country>
    </adr>
    <adr>
      <parameters>
        <type><text>home</text></type>
        <label><text>Hannes Tschofenig
```



```
        c/o Hotel DuPont
        42 W 11th St
        Wilmington, DE 19801
        USA</text></label>
</parameters>
<pobox/>
<ext/>
<street>42 W 11th St</street>
<locality>Wilmington</locality>
<region>DE</region>
<code>19801</code>
<country>USA</country>
</adr>
<tel>
  <parameters>
    <type>
      <text>work</text>
      <text>voice</text>
    </type>
  </parameters>
  <uri>tel:+358 50 4871445</uri>
</tel>
<tel>
  <parameters>
    <type>
      <text>home</text>
      <text>voice</text>
    </type>
  </parameters>
  <uri>tel:+1 555 555 0123</uri>
</tel>
<email>
  <parameters><type><text>work</text></type>
</parameters>
  <text>hannes.tschofenig@nsn.com</text>
</email>
<geo>
  <parameters><type><text>work</text></type>
</parameters>
  <uri>geo:60.210796,24.812924</uri>
</geo>
<geo>
  <parameters><type><text>home</text></type>
</parameters>
  <uri>geo:39.746537,-75.548027</uri>
</geo>
<key>
  <parameters>
```



```

                <type><text>home</text></type>
            </parameters>
            <uri>https://www.example.com/key.asc
                </uri>
        </key>
        <tz><text>Finland/Helsinki</text></tz>
        <url>
            <parameters><type><text>home</text></type>
                </parameters>
            <uri>http://example.com/hannes.tschofenig
                </uri>
        </url>
    </vcard>
</pi:DataProviderContact>
</pi:EmergencyCallData.ProviderInfo>
--boundary1--

```

Figure 16: End Device sending SIP INVITE with Additional Data

In this example, information available to the access network provider is included in the call setup message only indirectly via the use of the location reference. The PSAP has to retrieve it via a separate look-up step. Since the access network provider and the VoIP service provider are two independent entities in this scenario, the access network provider is not involved in application layer exchanges; the SIP INVITE transits the access network transparently, as illustrated in steps #1 and #2 (the access network does not alter the SIP INVITE).

The VoIP service provider receives the message and determines, based on the Service URN, that the incoming request is an emergency call. It performs typical emergency services related tasks (such as location-based routing), and adds additional data, namely service and subscriber information as well as data provider information #2, to the outgoing message. For the example we assume a VoIP service provider that deploys a back-to-back user agent allowing additional data to be included in the body of the SIP message (rather than by reference), which allows us to illustrate the use of multiple data provider info blocks. The resulting message is shown in Figure 17. The SIP INVITE is sent to the PSAP in step #3.

```

INVITE sips:psap@example.org SIP/2.0
Via: SIP/2.0/TLS server.example.com;branch=z9hG4bK74bf9
Max-Forwards: 70
To: <urn:service:sos>
From: Hannes Tschofenig <sips:hannes@example.com>;tag=9fxced76sl
Call-ID: 3848276298220188511@example.com

```


Call-Info: <http://www.example.com/hannes/photo.jpg>
;purpose=icon,
<http://www.example.com/hannes/> ;purpose=info,
<cid:1234567890@atlanta.example.com>
;purpose=EmergencyCallData.ProviderInfo
<cid:0123456789@atlanta.example.com>
;purpose=EmergencyCallData.DeviceInfo
Call-Info: <cid:bloorpyhex@atlanta.example.com>
;purpose=EmergencyCallData.ServiceInfo
Call-Info: <cid:aaabbb@atlanta.example.com>
;purpose=EmergencyCallData.ProviderInfo
Geolocation: <<https://ls.example.net:9768/357yc6s64ceyoivy5ax3o>>
Geolocation-Routing: yes
Accept: application/sdp, application/pidf+xml,
application/EmergencyCallData.ProviderInfo+xml
CSeq: 31862 INVITE
Contact: <sips:hannes@example.com>
Content-Type: multipart/mixed; boundary=boundary1

Content-Length: ...

--boundary1

Content-Type: application/sdp

...SDP goes here

--boundary1--

Content-Type: application/EmergencyCallData.DeviceInfo+xml
Content-ID: <0123456789@atlanta.example.com>
Content-Disposition: by-reference;handling=optional
<?xml version="1.0" encoding="UTF-8"?>

<dev:EmergencyCallData.DeviceInfo
xmlns:dev="urn:iETF:params:xml:ns:EmergencyCallData:DeviceInfo">
<dev:DataProviderReference>d4b3072df09876543@[93.184.216.119]
</dev:DataProviderReference>
<dev:DeviceClassification>laptop</dev:DeviceClassification>
<dev:UniqueDeviceID
TypeOfDeviceID="MAC">00-0d-4b-30-72-df</dev:UniqueDeviceID>
</dev:EmergencyCallData.DeviceInfo>

--boundary1--

Content-Type: application/EmergencyCallData.ProviderInfo+xml
Content-ID: <1234567890@atlanta.example.com>

Content-Disposition: by-reference;handling=optional

<?xml version="1.0" encoding="UTF-8"?>

<pi:EmergencyCallData.ProviderInfo

xmlns:pi="urn:ietf:params:xml:ns:EmergencyCallData:ProviderInfo">

<pi:DataProviderReference>d4b3072df09876543@[93.184.216.119]

</pi:DataProviderReference>

<pi:DataProviderString>Hannes Tschofenig

</pi:DataProviderString>

<pi:TypeOfProvider>Client</pi:TypeOfProvider>

<pi:ContactURI>tel:+1-555-555-0123</pi:ContactURI>

<pi:Language>en</pi:Language>

<pi:DataProviderContact

xmlns="urn:ietf:params:xml:ns:vcard-4.0">

<vcard>

<fn><text>Hannes Tschofenig</text></fn>

<n>

<surname>Hannes</surname>

<given>Tschofenig</given>

<additional/>

<prefix/>

<suffix>Dipl. Ing.</suffix>

</n>

<bday><date>--0203</date></bday>

<anniversary>

<date-time>20090808T1430-0500</date-time>

</anniversary>

<gender><sex>M</sex></gender>

<lang>

<parameters><pref><integer>1</integer></pref>

</parameters>

<language-tag>de</language-tag>

</lang>

<lang>

<parameters><pref><integer>2</integer></pref>

</parameters>

<language-tag>en</language-tag>

</lang>

<adr>

<parameters>

<type><text>work</text></type>

<label><text>Hannes Tschofenig

Linnoitustie 6

Espoo, Finland

02600</text></label>

</parameters>

<pobox/>

<ext/>

<street>Linnoitustie 6</street>


```
<locality>Espoo</locality>
<region>Uusimaa</region>
<code>02600</code>
<country>Finland</country>
</adr>
<adr>
  <parameters>
    <type><text>home</text></type>
    <label><text>Hannes Tschofenig
      c/o Hotel DuPont
      42 W 11th St
      Wilmington, DE 19801
      USA</text></label>
  </parameters>
  <pobox/>
  <ext/>
  <street>42 W 11th St</street>
  <locality>Wilmington</locality>
  <region>DE</region>
  <code>19801</code>
  <country>USA</country>
</adr>
<tel>
  <parameters>
    <type>
      <text>work</text>
      <text>voice</text>
    </type>
  </parameters>
  <uri>tel:+358 50 4871445</uri>
</tel>
<tel>
  <parameters>
    <type>
      <text>home</text>
      <text>voice</text>
    </type>
  </parameters>
  <uri>tel:+1 555 555 0123</uri>
</tel>
<email>
  <parameters><type><text>work</text></type>
  </parameters>
  <text>hannes.tschofenig@nsn.com</text>
</email>
<geo>
  <parameters><type><text>work</text></type>
  </parameters>
```



```
<uri>geo:60.210796,24.812924</uri>
</geo>
<geo>
  <parameters><type><text>home</text></type>
</parameters>
  <uri>geo:39.746537,-75.548027</uri>
</geo>
<key>
  <parameters>
    <type><text>home</text></type>
  </parameters>
  <uri>https://www.example.com/key.asc
    </uri>
</key>
<tz><text>Finland/Helsinki</text></tz>
<url>
  <parameters><type><text>home</text></type>
  </parameters>
  <uri>http://example.com/hannes.tschofenig
    </uri>
</url>
</vcard>
</pi:DataProviderContact>
</pi:EmergencyCallData.ProviderInfo>

--boundary1--

Content-Type: application/EmergencyCallData.ServiceInfo+xml
Content-ID: <bloorpyhex@atlanta.example.com>
Content-Disposition: by-reference;handling=optional
<?xml version="1.0" encoding="UTF-8"?>
<svc:EmergencyCallData.ServiceInfo
  xmlns:svc="urn:ietf:params:xml:ns:EmergencyCallData:ServiceInfo">
  <svc:DataProviderReference>string0987654321@example.org
</svc:DataProviderReference>
  <svc:ServiceEnvironment>Residence</svc:ServiceEnvironment>
  <svc:ServiceType>VOIP</svc:ServiceType>
  <svc:ServiceMobility>Unknown</svc:ServiceMobility>
</svc:EmergencyCallData.ServiceInfo>

--boundary1--

Content-Type: application/EmergencyCallData.ProviderInfo+xml
Content-ID: <aaabbb@atlanta.example.com>
Content-Disposition: by-reference;handling=optional
<?xml version="1.0" encoding="UTF-8"?>
<pi:EmergencyCallData.ProviderInfo
  xmlns:pi="urn:ietf:params:xml:ns:EmergencyCallData:ProviderInfo">
```



```
<pi:DataProviderReference>string0987654321@example.org
</pi:DataProviderReference>
  <pi:DataProviderString>Exemplar VoIP Provider
  </pi:DataProviderString>
<pi:ProviderID>urn:nena:companyid:ID123</pi:ProviderID>
<pi:ProviderIDSeries>NENA</pi:ProviderIDSeries>
<pi:TypeOfProvider>Service Provider</pi:TypeOfProvider>
<pi:ContactURI>sip:voip-provider@example.com</pi:ContactURI>
<pi:Language>en</pi:Language>
<pi:DataProviderContact
  xmlns:xc="urn:ietf:params:xml:ns:vcard-4.0">
  <vcard>
    <fn><text>John Doe</text></fn>
    <n>
      <surname>John</surname>
      <given>Doe</given>
      <additional/>
      <prefix/>
      <suffix/>
    </n>
    <bday><date>-0203</date></bday>
    <anniversary>
      <date-time>20090808T1430-0500</date-time>
    </anniversary>
    <gender><sex>M</sex></gender>
    <lang>
      <parameters><pref><integer>1</integer></pref>
      </parameters>
      <language-tag>en</language-tag>
    </lang>
    <org>
      <parameters><type><text>work</text></type>
      </parameters>
      <text>Exemplar VoIP Provider</text>
    </org>
    <adr>
      <parameters>
        <type><text>work</text></type>
        <label><text>John Doe
          123 Middle Street
          The Sticks, IA 50055</text></label>
      </parameters>
      <pobox/>
      <ext/>
      <street>123 Middle Street</street>
      <locality>the Sticks</locality>
      <region>IA</region>
      <code>50055</code>
```



```

        <country>USA</country>
    </adr>
    <tel>
        <parameters>
            <type>
                <text>work</text>
                <text>voice</text>
            </type>
        </parameters>
        <uri>sips:john.doe@example.com</uri>
    </tel>
    <email>
        <parameters><type><text>work</text></type>
        </parameters>
        <text>john.doe@example.com</text>
    </email>
    <geo>
        <parameters><type><text>work</text></type>
        </parameters>
        <uri>geo:41.761838, -92.963268</uri>
    </geo>
    <tz><text>America/Chicago</text></tz>
    <url>
        <parameters><type><text>home</text></type>
        </parameters>
        <uri>http://www.example.com/john.doe</uri>
    </url>
</vcard>
</pi:DataProviderContact>
</pi:EmergencyCallData.ProviderInfo>

```

Figure 17: VoIP Provider sending SIP INVITE with Additional Data

Finally, the PSAP requests location information from the access network provider. The response is shown in Figure 18. Along with the location information, additional data is provided in the <provided-by> element of the PIDF-L0. This request and response is step #4.

```

<?xml version="1.0" encoding="UTF-8"?>
<presence xmlns="urn:ietf:params:xml:ns:pidf"
  xmlns:gp="urn:ietf:params:xml:ns:pidf:geopriv10"
  xmlns:gbp="urn:ietf:params:xml:ns:pidf:geopriv10:basicPolicy"
  xmlns:dm="urn:ietf:params:xml:ns:pidf:data-model"
  entity="pres:alice@atlanta.example.com">
  <dm:device id="target123-1">
    <gp:geopriv>

```



```
<gp:location-info>
  <civicAddress
    xmlns="urn:ietf:params:xml:ns:pidf:geopriv10:civicAddr">
    <country>US</country>
    <A1>DE</A1>
    <A3>Wilmington</A3>
    <PRD>W</PRD>
    <RD>11th</RD>
    <STS>Street</STS>
    <HNO>42</HNO>
    <NAM>The Hotel DuPont</NAM>
    <PC>19801</PC>
  </civicAddress>
</gp:location-info>
<gp:usage-rules>
  <gbp:retransmission-allowed>true
</gbp:retransmission-allowed>
  <gbp:retention-expiry>2013-12-10T20:00:00Z
</gbp:retention-expiry>
</gp:usage-rules>
<gp:method>802.11</gp:method>

  <gp:provided-by
    xmlns="urn:ietf:params:xml:ns:EmergencyCallData">

    <EmergencyCallDataReference
      purpose="EmergencyCallData.ServiceInfo"
      ref="https://example.com/ref2" />

    <EmergencyCallDataValue>
      <EmergencyCallData.ProviderInfo
        xmlns=
          "urn:ietf:params:xml:ns:EmergencyCallData:ProviderInfo">
        <DataProviderReference>88QV4FpfZ976T@example.com
        </DataProviderReference>
        <DataProviderString>Diamond State Exemplar
        </DataProviderString>
        <ProviderID>urn:nena:companyid:diamond</ProviderID>
        <ProviderIDSeries>NENA</ProviderIDSeries>
        <TypeOfProvider>Access Network Provider</TypeOfProvider>
        <ContactURI>tel:+1-302-555-0000</ContactURI>
        <Language>en</Language>
      </EmergencyCallData.ProviderInfo>

      <EmergencyCallData.Comment
        xmlns="urn:ietf:params:xml:ns:EmergencyCallData:Comment">
        <DataProviderReference>88QV4FpfZ976T@example.com
        </DataProviderReference>
```



```

        <Comment xml:lang="en">This is an example text.</Comment>
    </EmergencyCallData.Comment>

    </EmergencyCallDataValue>
</gp:provided-by>
</gp:geopriv>
<dm:deviceID>mac:00-0d-4b-30-72-df</dm:deviceID>
<dm:timestamp>2013-07-09T20:57:29Z</dm:timestamp>
</dm:device>
</presence>

```

Figure 18: Access Network Provider returning PIDF-LO with Additional Data

7. XML Schemas

This section defines the XML schemas of the five data blocks. Additionally, the provided-by schema is specified.

7.1. EmergencyCallData.ProviderInfo XML Schema

```

<?xml version="1.0"?>
<xs:schema
  targetNamespace=
    "urn:ietf:params:xml:ns:EmergencyCallData:ProviderInfo"
  xmlns:xs="http://www.w3.org/2001/XMLSchema"
  xmlns:pi="urn:ietf:params:xml:ns:EmergencyCallData:ProviderInfo"
  xmlns:xml="http://www.w3.org/XML/1998/namespace"
  xmlns:xc="urn:ietf:params:xml:ns:vcard-4.0"
  elementFormDefault="qualified"
  attributeFormDefault="unqualified">

  <xs:import namespace="http://www.w3.org/XML/1998/namespace"
    schemaLocation="http://www.w3.org/2009/01/xml.xsd"/>

  <xs:import namespace="urn:ietf:params:xml:ns:vcard-4.0"
    schemaLocation="vcard.xsd"/>

  <xs:element
    name="EmergencyCallData.ProviderInfo"
    type="pi:ProviderInfoType"/>

  <xs:simpleType name="SubcontractorPriorityType">
    <xs:restriction base="xs:string">
      <xs:enumeration value="sub"/>
      <xs:enumeration value="main"/>
    </xs:restriction>
  </xs:simpleType>

```



```
</xs:restriction>
</xs:simpleType>

<xs:complexType name="ProviderInfoType">
  <xs:sequence>
    <xs:element name="DataProviderReference"
      type="xs:token" minOccurs="1" maxOccurs="1"/>

    <xs:element name="DataProviderString"
      type="xs:string" minOccurs="1" maxOccurs="1"/>

    <xs:element name="ProviderID"
      type="xs:string" minOccurs="0" maxOccurs="1"/>

    <xs:element name="ProviderIDSeries"
      type="xs:string" minOccurs="0" maxOccurs="1"/>

    <xs:element name="TypeOfProvider"
      type="xs:string" minOccurs="1" maxOccurs="1"/>

    <xs:element name="ContactURI" type="xs:anyURI"
      minOccurs="1" maxOccurs="1"/>

<xs:element name="Language" minOccurs="1" maxOccurs="unbounded">
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:pattern
value="([a-z]{2,3}((-[a-z]{3}){0,3})?|[a-z]{4,8})
(-[a-z]{4})?(-([a-z]{2}|\d{3}))?(-([0-9a-z]{5,8}|
\d[0-9a-z]{3}))*(-[0-9a-wyz](-[0-9a-z]{2,8})+)*
(-x(-[0-9a-z]{1,8})+)?|x(-[0-9a-z]{1,8})+|[a-z]{1,3}
(-[0-9a-z]{2,8}){1,2}"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>

<xs:element name="DataProviderContact"
  minOccurs="0" maxOccurs="1">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0"
        maxOccurs="unbounded" ref="xc:vcard"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```



```
<xs:element name="SubcontractorPrincipal"
  type="xs:string" minOccurs="0" maxOccurs="1"/>

<xs:element name="SubcontractorPriority"
  type="pi:SubcontractorPriorityType"
  minOccurs="0" maxOccurs="1"/>

<xs:any namespace="##other" processContents="lax"
  minOccurs="0" maxOccurs="unbounded"/>
</xs:sequence>
</xs:complexType>

</xs:schema>
```

Figure 19: EmergencyCallData.ProviderInfo XML Schema.

7.2. EmergencyCallData.ServiceInfo XML Schema


```
<?xml version="1.0"?>
<xs:schema
  targetNamespace=
    "urn:ietf:params:xml:ns:EmergencyCallData:ServiceInfo"
  xmlns:xs="http://www.w3.org/2001/XMLSchema"
  xmlns:svc="urn:ietf:params:xml:ns:EmergencyCallData:ServiceInfo"
  xmlns:xml="http://www.w3.org/XML/1998/namespace"
  elementFormDefault="qualified"
  attributeFormDefault="unqualified">

  <xs:import namespace="http://www.w3.org/XML/1998/namespace"
    schemaLocation="http://www.w3.org/2001/xml.xsd"/>

  <xs:element name="EmergencyCallData.ServiceInfo"
    type="svc:ServiceInfoType"/>

  <xs:complexType name="ServiceInfoType">
    <xs:sequence>
      <xs:element name="DataProviderReference"
        type="xs:token" minOccurs="1" maxOccurs="1"/>

      <xs:element name="ServiceEnvironment"
        type="xs:string" minOccurs="0" maxOccurs="1"/>

      <xs:element name="ServiceType"
        type="xs:string" minOccurs="1"
        maxOccurs="unbounded"/>

      <xs:element name="ServiceMobility"
        type="xs:string" minOccurs="1" maxOccurs="1"/>

      <xs:any namespace="##other" processContents="lax"
        minOccurs="0" maxOccurs="unbounded"/>
    </xs:sequence>
  </xs:complexType>

</xs:schema>
```

Figure 20: EmergencyCallData.ServiceInfo XML Schema.

[7.3.](#) EmergencyCallData.DeviceInfo XML Schema

```
<?xml version="1.0"?>
<xs:schema
  targetNamespace=
    "urn:ietf:params:xml:ns:EmergencyCallData:DeviceInfo"
  xmlns:xs="http://www.w3.org/2001/XMLSchema"
```



```
xmlns:dev="urn:ietf:params:xml:ns:EmergencyCallData:DeviceInfo"
xmlns:xml="http://www.w3.org/XML/1998/namespace"
elementFormDefault="qualified"
attributeFormDefault="unqualified">

<xs:import namespace="http://www.w3.org/XML/1998/namespace"
           schemaLocation="http://www.w3.org/2001/xml.xsd"/>

<xs:element name="EmergencyCallData.DeviceInfo"
           type="dev:DeviceInfoType"/>

<xs:complexType name="DeviceInfoType">
  <xs:sequence>
    <xs:element name="DataProviderReference"
               type="xs:token" minOccurs="1" maxOccurs="1"/>

    <xs:element name="DeviceClassification"
               type="xs:string" minOccurs="0" maxOccurs="1"/>

    <xs:element name="DeviceMfgr"
               type="xs:string" minOccurs="0" maxOccurs="1"/>

    <xs:element name="DeviceModelNr"
               type="xs:string" minOccurs="0" maxOccurs="1"/>

    <xs:element name="UniqueDeviceID" minOccurs="0"
               maxOccurs="unbounded">
      <xs:complexType>
        <xs:simpleContent>
          <xs:extension base="xs:string">
            <xs:attribute name="TypeOfDeviceID"
                          type="xs:string"
                          use="required"/>
          </xs:extension>
        </xs:simpleContent>
      </xs:complexType>
    </xs:element>

    <xs:element name="DeviceSpecificData"
               type="xs:anyURI" minOccurs="0" maxOccurs="1"/>

    <xs:element name="DeviceSpecificType"
               type="xs:string" minOccurs="0" maxOccurs="1"/>

    <xs:any namespace="##other" processContents="lax"
           minOccurs="0" maxOccurs="unbounded"/>
  </xs:sequence>
</xs:complexType>
```



```
</xs:schema>
```

Figure 21: EmergencyCallData.DeviceInfo XML Schema.

7.4. EmergencyCallData.SubscriberInfo XML Schema

```
<?xml version="1.0"?>
<xs:schema
  targetNamespace=
    "urn:ietf:params:xml:ns:EmergencyCallData:SubscriberInfo"
  xmlns:xs="http://www.w3.org/2001/XMLSchema"
  xmlns:sub=
    "urn:ietf:params:xml:ns:EmergencyCallData:SubscriberInfo"
  xmlns:xc="urn:ietf:params:xml:ns:vcard-4.0"
  xmlns:xml="http://www.w3.org/XML/1998/namespace"
  elementFormDefault="qualified"
  attributeFormDefault="unqualified">

  <xs:import namespace="http://www.w3.org/XML/1998/namespace"
    schemaLocation="http://www.w3.org/2001/xml.xsd"/>

  <xs:import namespace="urn:ietf:params:xml:ns:vcard-4.0"
    schemaLocation="vcard.xsd"/>

  <xs:element name="EmergencyCallData.SubscriberInfo"
    type="sub:SubscriberInfoType"/>

  <xs:complexType name="SubscriberInfoType">
    <xs:complexContent>
      <xs:restriction base="xs:anyType">
        <xs:sequence>
          <xs:element name="DataProviderReference"
            type="xs:token" minOccurs="1" maxOccurs="1"/>

          <xs:element name="SubscriberData">
            <xs:complexType>
              <xs:sequence>
                <xs:element maxOccurs="unbounded"
                  ref="xc:vcard"/>
              </xs:sequence>
            </xs:complexType>
          </xs:element>

          <xs:any namespace="##other" processContents="lax"
            minOccurs="0" maxOccurs="unbounded"/>
        </xs:sequence>
```



```
        <xs:attribute name="privacyRequested" type="xs:boolean"
            use="required"/>
    </xs:restriction>
</xs:complexContent>
</xs:complexType>

</xs:schema>
```

Figure 22: EmergencyCallData.SubscriberInfo XML Schema.

[7.5.](#) EmergencyCallData.Comment XML Schema

```
<?xml version="1.0"?>
<xs:schema
  targetNamespace=
    "urn:ietf:params:xml:ns:EmergencyCallData:Comment"
  xmlns:xs="http://www.w3.org/2001/XMLSchema"
  xmlns:com="urn:ietf:params:xml:ns:EmergencyCallData:Comment"
  xmlns:xml="http://www.w3.org/XML/1998/namespace"
  elementFormDefault="qualified"
  attributeFormDefault="unqualified">

  <xs:import namespace="http://www.w3.org/XML/1998/namespace"
    schemaLocation="http://www.w3.org/2001/xml.xsd"/>

  <xs:element name="EmergencyCallData.Comment"
    type="com:CommentType"/>

  <xs:complexType name="CommentType">
    <xs:sequence>
      <xs:element name="DataProviderReference"
        type="xs:token" minOccurs="1" maxOccurs="1"/>

      <xs:element name="Comment"
        type="com:CommentSubType" minOccurs="0"
        maxOccurs="unbounded"/>

      <xs:any namespace="##other" processContents="lax"
        minOccurs="0" maxOccurs="unbounded"/>
    </xs:sequence>
  </xs:complexType>

  <xs:complexType name="CommentSubType">
    <xs:simpleContent>
      <xs:extension base="xs:string">
        <xs:attribute ref="xml:lang"/>
      </xs:extension>
    </xs:simpleContent>
  </xs:complexType>

</xs:schema>
```

Figure 23: EmergencyCallData.Comment XML Schema.

7.6. provided-by XML Schema

This section defines the provided-by schema.

```
<?xml version="1.0"?>
```



```
<xs:schema
  targetNamespace=
    "urn:ietf:params:xml:ns:EmergencyCallData"
  xmlns:xs="http://www.w3.org/2001/XMLSchema"
  xmlns:ad="urn:ietf:params:xml:ns:EmergencyCallData"
  xmlns:xml="http://www.w3.org/XML/1998/namespace"
  xmlns:pi="urn:ietf:params:xml:ns:EmergencyCallData:ProviderInfo"
  xmlns:svc="urn:ietf:params:xml:ns:EmergencyCallData:ServiceInfo"
  xmlns:dev="urn:ietf:params:xml:ns:EmergencyCallData:DeviceInfo"
  xmlns:sub=
    "urn:ietf:params:xml:ns:EmergencyCallData:SubscriberInfo"
  xmlns:com="urn:ietf:params:xml:ns:EmergencyCallData:Comment"
  elementFormDefault="qualified"
  attributeFormDefault="unqualified">

  <xs:import
    namespace="urn:ietf:params:xml:ns:EmergencyCallData:ProviderInfo"
    schemaLocation="ProviderInfo.xsd"/>
  <xs:import
    namespace="urn:ietf:params:xml:ns:EmergencyCallData:ServiceInfo"
    schemaLocation="ServiceInfo.xsd"/>
  <xs:import
    namespace="urn:ietf:params:xml:ns:EmergencyCallData:DeviceInfo"
    schemaLocation="DeviceInfo.xsd"/>
  <xs:import
    namespace="urn:ietf:params:xml:ns:EmergencyCallData:SubscriberInfo"
    schemaLocation="SubscriberInfo.xsd"/>
  <xs:import
    namespace="urn:ietf:params:xml:ns:EmergencyCallData:Comment"
    schemaLocation="Comment.xsd"/>

  <xs:element name="EmergencyCallDataReference"
    type="ad:ByRefType"/>

  <xs:element name="EmergencyCallDataValue"
    type="ad:EmergencyCallDataValueType"/>

  <!-- Additional Data By Reference -->

  <xs:complexType name="ByRefType">
    <xs:complexContent>
      <xs:restriction base="xs:anyType">
        <xs:sequence>
          <xs:any namespace="##other" minOccurs="0"
            maxOccurs="unbounded" processContents="lax"/>
        </xs:sequence>
        <xs:attribute name="purpose" type="xs:token"
          use="required"/>
      </xs:restriction>
    </xs:complexContent>
  </xs:complexType>
```



```

        <xs:attribute name="ref" type="xs:anyURI"
            use="required"/>
    </xs:restriction>
</xs:complexContent>
</xs:complexType>

<!-- Additional Data By Value -->

<xs:complexType name="EmergencyCallDataValueType">
    <xs:sequence>
        <xs:element name="EmergencyCallData.ProviderInfo"
            type="pi:ProviderInfoType"
            minOccurs="0" maxOccurs="unbounded"/>
        <xs:element name="EmergencyCallData.ServiceInfo"
            type="svc:ServiceInfoType"
            minOccurs="0" maxOccurs="unbounded"/>
        <xs:element name="EmergencyCallData.DeviceInfo"
            type="dev:DeviceInfoType"
            minOccurs="0" maxOccurs="unbounded"/>
        <xs:element name="EmergencyCallData.SubscriberInfo"
            type="sub:SubscriberInfoType"
            minOccurs="0" maxOccurs="unbounded"/>
        <xs:element name="EmergencyCallData.Comment"
            type="com:CommentType"
            minOccurs="0" maxOccurs="unbounded"/>

        <xs:any namespace="##other" processContents="lax"
            minOccurs="0" maxOccurs="unbounded"/>

    </xs:sequence>
</xs:complexType>

</xs:schema>

```

Figure 24: provided-by XML Schema

8. Security Considerations

The data structures described in this document contain information usually considered private. When information is provided by value, entities that are a party to the SIP signaling (such as proxy servers and back-to-back user agents) will have access to it and need to protect it against inappropriate disclosure. An entity that is able to eavesdrop on the SIP signaling will also have access. Some access types (such as in-the-clear Wi-Fi) are more vulnerable than others (such as 3G or 4G cellular data traffic) to eavesdropping. Mechanisms that protect against eavesdropping (such as Transport Layer Security (TLS)) SHOULD be preferentially used whenever

feasible. (This requirement is not a "MUST" because there is an existing deployed base of clear-text SIP, and also because, as an emergency call, it is more important for the call to go through than for it to be protected; e.g., the call MUST proceed even if the TLS negotiation or certificate verification fails for whatever reason.) When information is provided by reference, HTTPS is REQUIRED for dereferencing, and the provider of the information is REQUIRED to validate the credentials of the requester. While the creation of a public key infrastructure (PKI) that has global scope may be difficult, the alternatives to creating devices and services that can provide critical information securely are more daunting. The provider of the information MAY enforce any policy it wishes to use, but PSAPs and responder agencies SHOULD deploy a PKI so that providers of additional data can check the certificate of the client (the requester) and decide the appropriate policy to enforce based on that certificate.

Ideally, the PSAP and emergency responders will be given credentials signed by an authority trusted by the data provider. In most circumstances, nationally recognized credentials are sufficient; the emergency services community within a country can arrange a PKI, data providers can be provisioned with the root CA public key for the country. Some nations are developing a PKI for this, and related, purposes. Since calls could be made from devices where the device and/or the service provider(s) are not local to the emergency services authorities, globally recognized credentials are useful. This might be accomplished by extending the notion of the "forest guide" described in [[RFC5582](#)] to allow the forest guide to provide the credential of the PKI root for areas for which it has coverage information, but standards for such a mechanism are not yet available. In its absence, the data provider needs to obtain by out of band means the root CA credentials for any areas to which it is willing to provide additional data. With the credential of the root CA for a national emergency services PKI, the data provider server can validate the credentials of an entity requesting additional data by reference.

The data provider also needs a credential that can be verified by the emergency services to know that it is receiving data from an authorized server. The emergency services authorities could provide credentials, distinguishable from credentials provided to emergency responders and PSAPs, which could be used to validate data providers. Such credentials would have to be acceptable to any PSAP or responder that could receive a call with additional data supplied by that provider. This would be extensible to global credential validation using the forest guide as mentioned above. In the absence of such credentials, the emergency services authorities could maintain a list of local data providers' credentials as provided to them out of band.

At a minimum, the emergency services authorities could obtain a credential from the DNS entry of the domain in the Additional Data URI to at least validate that the server is known to the domain providing the URI.

Data provided by devices by reference have similar credential validation issues as for service providers, and while the solutions are the same, the challenges of doing so for every device are obviously more difficult, especially when considering root certificate updates, revocation lists, etc. However, in general, devices are not expected to provide data directly by reference, but rather, to either provide data by value, or upload the data to a server which can more reliably make it available and more easily enforce security policy. Devices which do provide data directly by reference, which might include fixed-location sensors, will need to be capable of handling this.

Much of the information supplied by service providers and devices is private and confidential; service providers and devices generally go to lengths to protect this information; disclosing it in the context of an emergency call is a trade-off to protect the greater interest of the customer in an emergency.

Neither service providers nor devices will supply private information unless the call is recognized as an emergency call. In cellular telephony systems (such as those using 3GPP IMS), there are different procedures for an originating device to place an emergency versus a normal call. If a call that is really an emergency call is initiated as a normal call and the cellular service provider recognizes this, 3GPP IMS permits the service provider to either accept the call anyway or reject it with a specific code that instructs the device to retry the call as an emergency call. Service providers ought to choose the latter, because otherwise the device will not have included the information specified in this document (since the device didn't recognize the call as being an emergency call).

9. Privacy Considerations

This document enables functionality for conveying additional information about the caller and the caller's device and service to the callee. Some of this information is personal data and therefore privacy concerns arise. An explicit privacy indicator for information directly relating to the caller's identity is defined and use is mandatory. However, observance of this request for privacy and which information it relates to is determined by the destination jurisdiction (which replicates functionality provided in some legacy emergency services systems).

There are a number of privacy concerns with non-emergency real-time communication services that are also applicable to emergency calling. Data protection regulation world-wide has, however, decided to create exceptions for emergency services since the drawbacks of disclosing personal data are outweighed by the benefit for the emergency caller. Hence, the data protection rights of individuals are commonly waived for emergency situations. There are, however, still various countries that offer some degree of anonymity for the caller towards PSAP call takers.

The functionality defined in this document far exceeds the amount of information sharing available in the legacy POTS system. For this reason there are additional privacy threats to consider, which are described in more detail in [[RFC6973](#)].

Stored Data Compromise: There is an increased risk of stored data compromise since additional data is collected and stored in databases. Without adequate measures to secure stored data from unauthorized or inappropriate access at access network providers, service providers, end devices, as well as PSAPs, individuals are exposed to potential financial, reputational, or physical harm.

Misattribution: If the personal data collected and conveyed is incorrect or inaccurate then this may lead to misattribution. Misattribution occurs when data or communications related to one individual are attributed to another.

Identification: By the nature of the additional data and its capability to provide much richer information about the caller, the call, and the location, the calling party is identified in a much better way. Some users may feel uncomfortable with this degree of information sharing even in emergency services situations.

Secondary Use: There is a risk of secondary use, which is the use of collected information about an individual without the individual's consent for a purpose different from that for which the information was collected. The stated purpose of the additional data is for emergency services purposes but theoretically the same information could be used for any other call as well. Additionally, parties involved in the emergency call may retain the obtained information and may re-use it for other, non-emergency services purposes.

Disclosure: When the data defined in this document is not properly protected (while in transit with traditional communication security techniques, and while stored using access control

mechanisms) there is the risk of disclosure, which is the revelation of private information about an individual.

To mitigate these privacy risks the following countermeasures can be taken:

In regions where callers can elect to suppress certain personally identifying information, network or PSAP functionality can inspect privacy flags within the SIP headers to determine what information may be passed, stored, or displayed to comply with local policy or law. [RFC 3325](#) [[RFC3325](#)] defines the "id" priv-value token. The presence of this privacy type in a Privacy header field indicates that the user would like the network asserted identity to be kept private with respect to SIP entities outside the trust domain with which the user authenticated, including the PSAP.

This document defines various data structures that contain privacy-sensitive data. For example, identifiers for the device (e.g., serial number, MAC address) or account/SIM (e.g., IMSI), contact information for the user, location of the caller. Local regulations may govern which data is provided in emergency calls, but in general, the emergency call system is aided by the information described in this document. There is a tradeoff between the privacy considerations and the utility of the data. For protection, this specification requires all retrieval of data passed by reference to be protected against eavesdropping and alteration via communication security techniques (namely TLS). Furthermore, security safeguards are required to prevent unauthorized access to stored data. Various security incidents over at least the past few decades have shown that data breaches are not uncommon and are often caused by lack of proper access control frameworks, software bugs (such as buffer overflows), or missing input parsing (such as SQL injection attacks). The risks of data breaches is increased with the obligation for emergency services to retain emergency call related data for extended periods (e.g., several years are the norm).

Finally, it is also worth highlighting the nature of the SIP communication architecture, which introduces additional complications for privacy. Some forms of data can be sent by value in the SIP signaling or by reference (a URL in the SIP signaling). When data is sent by value, all intermediaries have access to the data. As such, these intermediaries may also introduce additional privacy risk. Therefore, in situations where the conveyed information is privacy-sensitive and intermediaries are involved, transmitting by reference might be appropriate, assuming the source of the data can operate a sufficient dereferencing infrastructure and that proper access control policies are available for distinguishing the different entities dereferencing the reference. Without access control

policies any party in possession of the reference is able to resolve the reference and to obtain the data, including intermediaries.

10. IANA Considerations

10.1. Registry creation

This document creates a new registry called 'Emergency Call Additional Data'. The following sub-registries are created for this registry.

10.1.1. Provider ID Series Registry

This document creates a new sub-registry called "Additional Call Data Provider ID Series". As defined in [[RFC5226](#)], this registry operates under "Expert Review" rules. The expert should determine that the entity requesting a new value is a legitimate issuer of service provider IDs suitable for use in Additional Call Data.

Private entities issuing or using internally-generated IDs are encouraged to register here and to ensure that all IDs they issue or use are unique. This guarantees that IDs issued or used by the entity are globally unique and distinguishable from other IDs issued or used by the same or a different entity. (Some organizations, such as NENA, issue IDs that are unique among all IDs they issue, so an entity using a combination of its NENA ID and the fact that it is from NENA is globally unique. Other entities might not have an ID issued by an organization such as NENA, so they are permitted to use their domain name, but if so, it needs to be unique.)

The content of this registry includes:

Name: An identifier to be used in the 'ProviderIDSeries' element.

Source: The full name of the organization issuing the identifiers.

URL: A URL to the organization for further information.

The initial set of values is listed in Figure 1.

10.1.2. Service Environment Registry

This document creates a new sub-registry called 'Additional Call Service Environment'. As defined in [[RFC5226](#)], this registry operates under "Expert Review" rules. The expert should determine that the entity requesting a new value is relevant for this service element, and that the new value is distinct from existing values, and its use is unambiguous.

The content of this registry includes:

Token: The value to be used in the <ServiceEnvironment> element.

Description: A short description of the value.

The initial set of values is listed in Figure 4.

10.1.3. Service Type Registry

This document creates a new sub-registry called 'Additional Call Service Type'. As defined in [[RFC5226](#)], this registry operates under "Expert Review" rules. The expert should determine that the entity requesting a new value is relevant for this service element and that the requested value is clearly distinct from other values so that there is no ambiguity as to when the value is to be used or which value is to be used.

The content of this registry includes:

Name: The value to be used in the <ServiceType> element.

Description: A short description of the value.

The initial set of values is listed in Figure 5.

10.1.4. Service Mobility Registry

This document creates a new sub-registry called 'Additional Call Service Mobility'. As defined in [[RFC5226](#)], this registry operates under "Expert Review" rules. The expert should determine that the entity requesting a new value is relevant for this service element and that the requested value is clearly distinct from other values so that there is no ambiguity as to when the value is to be used or which value is to be used.

The content of this registry includes:

Token: The value used in the <ServiceMobility> element.

Description: A short description of the value.

The initial set of values is listed in Figure 6.

10.1.5. Service Provider Type Registry

This document creates a new sub-registry called 'Service Provider Type'. As defined in [[RFC5226](#)], this registry operates under "Expert Review". The expert should determine that the proposed new value is distinct from existing values and appropriate for use in the <TypeOfServiceProvider> element

The content of this registry includes:

Token: The value used in the <TypeOfProvider> element.

Description: A short description of the type of service provider.

The initial set of values is defined in Figure 2.

10.1.6. Device Classification Registry

This document creates a new sub-registry called 'Device Classification'. As defined in [[RFC5226](#)], this registry operates under "Expert Review" rules. The expert should consider whether the proposed class is unique from existing classes and the definition of the class will be clear to implementors and PSAPs/responders.

The content of this registry includes:

Token: Value used in the <DeviceClassification> element.

Description: Short description identifying the device type.

The initial set of values are defined in Figure 8.

10.1.7. Device ID Type Registry

This document creates a new sub-registry called 'Additional Call Data Device ID Type'. As defined in [[RFC5226](#)], this registry operates under "Expert Review" rules. The expert should ascertain that the proposed type is well understood, and provides information which PSAPs and responders are able to use to uniquely identify a device. (For example, a biometric fingerprint used to authenticate a device would not normally be useful by a PSAP or responder to identify a device.)

The content of this registry includes:

Token: The value to be placed in the <TypeOfDeviceID> element.

Description: Short description identifying the type of the device ID.

The initial set of values are defined in Figure 9.

10.1.8. Device/Service Data Type Registry

This document creates a new sub-registry called 'Device/Service Data Type Registry'. As defined in [\[RFC5226\]](#), this registry operates under "Specification Required" rules, which include an explicit expert review. The designated expert should ascertain that the proposed type is well understood, and provides information useful to PSAPs and responders. The specification must contain a complete description of the data, and a precise format specification suitable to allow interoperable implementations.

The content of this registry includes:

Token: The value to be placed in the <DeviceSpecificType> element.

Description: Short description identifying the the data.

Specification: Citation for the specification of the data.

The initial set of values are listed in Figure 10.

10.1.9. Emergency Call Data Types Registry

This document creates a new sub-registry called 'Emergency Call Data Types' in the 'purpose' registry established by [RFC 3261](#) [\[RFC3261\]](#). As defined in [\[RFC5226\]](#), this registry operates under "Specification Required" rules, which include an explicit expert review. The expert is responsible for verifying that the document contains a complete and clear specification and the proposed functionality does not obviously duplicate existing functionality. The expert is also responsible for verifying that the block is correctly categorized per the description of the categories in [Section 1](#).

The registry contains an entry for every data block that can be sent with an emergency call using the mechanisms as specified in this document. Each data block is identified by the "root" of its MIME subtype (which is the part after 'EmergencyCallData.'). If the MIME subtype does not start with 'EmergencyCallData.', then it cannot be registered here nor used in a Call-Info header as specified in this document. The subtype MAY exist under any MIME media type (although most commonly these are under 'Application/' this is NOT REQUIRED), however, to be added to the registry the "root" needs to be unique regardless of the MIME media type.

The content of this registry includes:

Token: The root of the data's MIME subtype (not including the 'EmergencyCallData' prefix and any suffix such as '+xml')

Data About: Indicates if the data describes the call, the caller, or the location (or is applicable to all), which helps PSAPs and other entities determine if they wish to process the block. The value **MUST** be either "The Call", "The Caller", "The Location", or "All". New values are created by extending this registry in a subsequent RFC.

Reference: The document that describes the data object

Note that the values from this registry are part of the 'EmergencyCallData' compound value; when used as a value of the 'purpose' parameter of the Call-Info header, the values listed in this registry are prefixed by 'EmergencyCallData.' per the the 'EmergencyCallData' registration [Section 10.2](#).

The initial set of values are listed in Figure 25.

Token	Data About	Reference
ProviderInfo	The Call	[This RFC]
ServiceInfo	The Call	[This RFC]
DeviceInfo	The Call	[This RFC]
SubscriberInfo	The Call	[This RFC]
Comment	The Call	[This RFC]

Figure 25: Additional Data Blocks Registry

[10.2](#). 'EmergencyCallData' Purpose Parameter Value

This document defines the 'EmergencyCallData' value for the "purpose" parameter of the Call-Info header field. The Call-Info header and the corresponding registry for the 'purpose' parameter was established with [RFC 3261](#) [[RFC3261](#)]. Note that 'EmergencyCallData' is a compound value; when used as a value of the 'purpose' parameter of the Call-Info header, 'EmergencyCallData' is immediately followed by a dot ('.') and a value from the 'Emergency Call Data Types' registry [Section 10.1.9](#).

Header Field	Parameter Name	New Value	Reference
-----	-----	-----	-----
Call-Info	purpose	EmergencyCallData	[This RFC]

10.3. URN Sub-Namespace Registration for <provided-by> Registry Entry

This section registers the namespace specified in [Section 10.5.1](#) in the provided-by registry established by [RFC 4119](#), for usage within the <provided-by> element of a PIDF-LO.

The schema for the <provided-by> element used by this document is specified in [Section 7.6](#).

10.4. MIME Registrations

10.4.1. MIME Content-type Registration for 'application/ EmergencyCallData.ProviderInfo+xml'

This specification requests the registration of a new MIME type according to the procedures of [RFC 6838](#) [[RFC6838](#)] and guidelines in [RFC 7303](#) [[RFC7303](#)].

MIME media type name: application

MIME subtype name: EmergencyCallData.ProviderInfo+xml

Mandatory parameters: none

Optional parameters: charset (indicates the character encoding of the contents)

Encoding considerations: Uses XML, which can contain 8-bit characters, depending on the character encoding. See [Section 3.2 of RFC 7303](#) [[RFC7303](#)].

Security considerations: This content type is designed to carry the data provider information, which is a sub-category of additional data about an emergency call. Since this data may contain personal information, appropriate precautions might be needed to limit unauthorized access, inappropriate disclosure, and eavesdropping of personal information. Please refer to [Section 8](#) and [Section 9](#) for more information.

Interoperability considerations: None

Published specification: [TBD: This specification]

Applications which use this media type: Emergency Services

Additional information:

Magic Number: None

File Extension: .xml

Macintosh file type code: 'TEXT'

Person and email address for further information: Hannes
Tschofenig, Hannes.Tschofenig@gmx.net

Intended usage: LIMITED USE

Author: This specification is a work item of the IETF ECRIT
working group, with mailing list address <ecrit@ietf.org>.

Change controller: The IESG <ietf@ietf.org>

10.4.2. MIME Content-type Registration for 'application/ EmergencyCallData.ServiceInfo+xml'

This specification requests the registration of a new MIME type according to the procedures of [RFC 6838](#) [[RFC6838](#)] and guidelines in [RFC 7303](#) [[RFC7303](#)].

MIME media type name: application

MIME subtype name: EmergencyCallData.ServiceInfo+xml

Mandatory parameters: none

Optional parameters: charset (indicates the character encoding of the contents)

Encoding considerations: Uses XML, which can contain 8-bit characters, depending on the character encoding. See [Section 3.2 of RFC 7303](#) [[RFC7303](#)].

Security considerations: This content type is designed to carry the service information, which is a sub-category of additional data about an emergency call. Since this data may contain personal information, appropriate precautions may be needed to limit unauthorized access, inappropriate disclosure, and

eavesdropping of personal information. Please refer to [Section 8](#) and [Section 9](#) for more information.

Interoperability considerations: None

Published specification: [TBD: This specification]

Applications which use this media type: Emergency Services

Additional information:

Magic Number: None

File Extension: .xml

Macintosh file type code: 'TEXT'

Person and email address for further information: Hannes
Tschofenig, Hannes.Tschofenig@gmx.net

Intended usage: LIMITED USE

Author: This specification is a work item of the IETF ECRIT
working group, with mailing list address <ecrit@ietf.org>.

Change controller: The IESG <ietf@ietf.org>

[10.4.3.](#) MIME Content-type Registration for 'application/ EmergencyCallData.DeviceInfo+xml'

This specification requests the registration of a new MIME type according to the procedures of [RFC 6838](#) [[RFC6838](#)] and guidelines in [RFC 7303](#) [[RFC7303](#)].

MIME media type name: application

MIME subtype name: EmergencyCallData.DeviceInfo+xml

Mandatory parameters: none

Optional parameters: charset (indicates the character encoding of the contents)

Encoding considerations: Uses XML, which can contain 8-bit characters, depending on the character encoding. See [Section 3.2 of RFC 7303](#) [[RFC7303](#)].

Security considerations: This content type is designed to carry device information, which is a sub-category of additional data about an emergency call. Since this data contains personal information, appropriate precautions need to be taken to limit unauthorized access, inappropriate disclosure to third parties, and eavesdropping of this information. Please refer to [Section 8](#) and [Section 9](#) for more information.

Interoperability considerations: None

Published specification: [TBD: This specification]

Applications which use this media type: Emergency Services

Additional information:

Magic Number: None

File Extension: .xml

Macintosh file type code: 'TEXT'

Person and email address for further information: Hannes
Tschofenig, Hannes.Tschofenig@gmx.net

Intended usage: LIMITED USE

Author: This specification is a work item of the IETF ECRIT working group, with mailing list address <ecrit@ietf.org>.

Change controller: The IESG <ietf@ietf.org>

10.4.4. MIME Content-type Registration for 'application/ EmergencyCallData.SubscriberInfo+xml'

This specification requests the registration of a new MIME type according to the procedures of [RFC 6838](#) [[RFC6838](#)] and guidelines in [RFC 7303](#) [[RFC7303](#)].

MIME media type name: application

MIME subtype name: EmergencyCallData.SubscriberInfo+xml

Mandatory parameters: none

Optional parameters: charset (indicates the character encoding of the contents)

Encoding considerations: Uses XML, which can contain 8-bit characters, depending on the character encoding. See [Section 3.2 of RFC 7303](#) [RFC7303].

Security considerations: This content type is designed to carry owner/subscriber information, which is a sub-category of additional data about an emergency call. Since this data contains personal information, appropriate precautions need to be taken to limit unauthorized access, inappropriate disclosure to third parties, and eavesdropping of this information. Please refer to [Section 8](#) and [Section 9](#) for more information.

Interoperability considerations: None

Published specification: [TBD: This specification]

Applications which use this media type: Emergency Services

Additional information:

Magic Number: None

File Extension: .xml

Macintosh file type code: 'TEXT'

Person and email address for further information: Hannes Tschofenig, Hannes.Tschofenig@gmx.net

Intended usage: LIMITED USE

Author: This specification is a work item of the IETF ECRIT working group, with mailing list address <ecrit@ietf.org>.

Change controller: The IESG <ietf@ietf.org>

[10.4.5.](#) MIME Content-type Registration for 'application/EmergencyCallData.Comment+xml'

This specification requests the registration of a new MIME type according to the procedures of [RFC 6838](#) [RFC6838] and guidelines in [RFC 7303](#) [RFC7303].

MIME media type name: application

MIME subtype name: EmergencyCallData.Comment+xml

Mandatory parameters: none

Optional parameters: charset (indicates the character encoding of the contents)

Encoding considerations: Uses XML, which can contain 8-bit characters, depending on the character encoding. See [Section 3.2 of RFC 7303](#) [RFC7303].

Security considerations: This content type is designed to carry a comment, which is a sub-category of additional data about an emergency call. This data may contain personal information. Appropriate precautions may be needed to limit unauthorized access, inappropriate disclosure to third parties, and eavesdropping of this information. Please refer to [Section 8](#) and [Section 9](#) for more information.

Interoperability considerations: None

Published specification: [TBD: This specification]

Applications which use this media type: Emergency Services

Additional information:

Magic Number: None

File Extension: .xml

Macintosh file type code: 'TEXT'

Person and email address for further information: Hannes Tschofenig, Hannes.Tschofenig@gmx.net

Intended usage: LIMITED USE

Author: This specification is a work item of the IETF ECRIT working group, with mailing list address <ecrit@ietf.org>.

Change controller: The IESG <ietf@ietf.org>

[10.5.](#) URN Sub-Namespace Registration

[10.5.1.](#) Registration for urn:ietf:params:xml:ns:EmergencyCallData

This section registers a new XML namespace, as per the guidelines in [RFC 3688](#) [RFC3688].

URI: urn:ietf:params:xml:ns:EmergencyCallData

Registrant Contact: IETF, ECRIT working group, <ecrit@ietf.org>, as delegated by the IESG <iesg@ietf.org>.

XML:

```
BEGIN
<?xml version="1.0"?>
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML Basic 1.0//EN"
  "http://www.w3.org/TR/xhtml1-basic/xhtml1-basic10.dtd">
<html xmlns="http://www.w3.org/1999/xhtml">
<head>
  <meta http-equiv="content-type"
    content="text/html; charset=iso-8859-1"/>
  <title>Namespace for Additional Emergency Call Data</title>
</head>
<body>
  <h1>Namespace for Additional Data related to an Emergency Call
    </h1>
<p>See [TBD: This document].</p>
</body>
</html>
END
```

10.5.2. Registration for urn:ietf:params:xml:ns:EmergencyCallData:ProviderInfo

This section registers a new XML namespace, as per the guidelines in [RFC 3688](#) [[RFC3688](#)].

URI: urn:ietf:params:xml:ns:EmergencyCallData:ProviderInfo

Registrant Contact: IETF, ECRIT working group, <ecrit@ietf.org>, as delegated by the IESG <iesg@ietf.org>.

XML:


```
BEGIN
<?xml version="1.0"?>
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML Basic 1.0//EN"
  "http://www.w3.org/TR/xhtml1-basic/xhtml1-basic10.dtd">
<html xmlns="http://www.w3.org/1999/xhtml">
<head>
  <meta http-equiv="content-type"
    content="text/html; charset=iso-8859-1"/>
  <title>Namespace for Additional Emergency Call Data:
    Data Provider Information</title>
</head>
<body>
  <h1>Namespace for Additional Data related to an Emergency Call
    </h1>
  <h2>Data Provider Information</h2>
  <p>See [TBD: This document].</p>
</body>
</html>
END
```

10.5.3. Registration for

urn:ietf:params:xml:ns:EmergencyCallData:ServiceInfo

This section registers a new XML namespace, as per the guidelines in [RFC 3688](#) [[RFC3688](#)].

URI: urn:ietf:params:xml:ns:EmergencyCallData:ServiceInfo

Registrant Contact: IETF, ECRIT working group, <ecrit@ietf.org>, as delegated by the IESG <iesg@ietf.org>.

XML:


```
BEGIN
<?xml version="1.0"?>
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML Basic 1.0//EN"
  "http://www.w3.org/TR/xhtml1-basic/xhtml1-basic10.dtd">
<html xmlns="http://www.w3.org/1999/xhtml">
<head>
  <meta http-equiv="content-type"
    content="text/html; charset=iso-8859-1"/>
  <title>Namespace for Additional Emergency Call Data:
    Service Information</title>
</head>
<body>
  <h1>Namespace for Additional Data related to an Emergency Call
    </h1>
  <h2>Service Information</h2>
  <p>See [TBD: This document].</p>
</body>
</html>
END
```

10.5.4. Registration for urn:ietf:params:xml:ns:EmergencyCallData:DeviceInfo

This section registers a new XML namespace, as per the guidelines in [RFC 3688](#) [[RFC3688](#)].

URI: urn:ietf:params:xml:ns:EmergencyCallData:DeviceInfo

Registrant Contact: IETF, ECRIT working group, <ecrit@ietf.org>, as delegated by the IESG <iesg@ietf.org>.

XML:


```
BEGIN
<?xml version="1.0"?>
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML Basic 1.0//EN"
  "http://www.w3.org/TR/xhtml1-basic/xhtml1-basic10.dtd">
<html xmlns="http://www.w3.org/1999/xhtml">
<head>
  <meta http-equiv="content-type"
    content="text/html; charset=iso-8859-1"/>
  <title>Namespace for Additional Emergency Call Data:
    Device Information</title>
</head>
<body>
  <h1>Namespace for Additional Data related to an Emergency Call
    </h1>
  <h2>Device Information</h2>
  <p>See [TBD: This document].</p>
</body>
</html>
END
```

10.5.5. Registration for

urn:ietf:params:xml:ns:EmergencyCallData:SubscriberInfo

This section registers a new XML namespace, as per the guidelines in [RFC 3688](#) [[RFC3688](#)].

URI: urn:ietf:params:xml:ns:EmergencyCallData:SubscriberInfo

Registrant Contact: IETF, ECRIT working group, <ecrit@ietf.org>, as delegated by the IESG <iesg@ietf.org>.

XML:


```
BEGIN
<?xml version="1.0"?>
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML Basic 1.0//EN"
  "http://www.w3.org/TR/xhtml1-basic/xhtml1-basic10.dtd">
<html xmlns="http://www.w3.org/1999/xhtml">
<head>
  <meta http-equiv="content-type"
    content="text/html; charset=iso-8859-1"/>
  <title>Namespace for Additional Emergency Call Data:
    Owner/Subscriber Information</title>
</head>
<body>
  <h1>Namespace for Additional Data related to an Emergency Call
    </h1>
  <h2> Owner/Subscriber Information</h2>
  <p>See [TBD: This document].</p>
</body>
</html>
END
```

10.5.6. Registration for urn:ietf:params:xml:ns:EmergencyCallData:Comment

This section registers a new XML namespace, as per the guidelines in [RFC 3688](#) [[RFC3688](#)].

URI: urn:ietf:params:xml:ns:EmergencyCallData:Comment

Registrant Contact: IETF, ECRIT working group, <ecrit@ietf.org>, as delegated by the IESG <iesg@ietf.org>.

XML:


```
BEGIN
<?xml version="1.0"?>
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML Basic 1.0//EN"
  "http://www.w3.org/TR/xhtml1-basic/xhtml1-basic10.dtd">
<html xmlns="http://www.w3.org/1999/xhtml">
<head>
  <meta http-equiv="content-type"
    content="text/html; charset=iso-8859-1"/>
  <title>Namespace for Additional Emergency Call Data:Comment
  </title>
</head>
<body>
  <h1>Namespace for Additional Data related to an Emergency Call
  </h1>
  <h2> Comment</h2>
<p>See [TBD: This document].</p>
</body>
</html>
END
```

10.6. Schema Registrations

This specification registers five schemas, as per the guidelines in [RFC 3688](#) [[RFC3688](#)].

URI: urn:ietf:params:xml:schema:emergencycalldata:ProviderInfo

Registrant Contact: IETF, ECRIT Working Group (ecrit@ietf.org), as delegated by the IESG (iesg@ietf.org).

XML: The XML schema can be found in Figure 19.

URI: urn:ietf:params:xml:schema:emergencycalldata:ServiceInfo

Registrant Contact: IETF, ECRIT Working Group (ectit@ietf.org), as delegated by the IESG (iesg@ietf.org).

XML: The XML schema can be found in Figure 20.

URI: urn:ietf:params:xml:schema:emergencycalldata:DeviceInfo

Registrant Contact: IETF, ECRIT Working Group (ecrit@ietf.org), as delegated by the IESG (iesg@ietf.org).

XML: The XML schema can be found in Figure 21.

URI: urn:ietf:params:xml:schema:emergencycalldata:SubscriberInfo

Registrant Contact: IETF, ECRIT Working Group (ecrit@ietf.org), as delegated by the IESG (iesg@ietf.org).

XML: The XML schema can be found in [Section 7.4](#).

URI: urn:ietf:params:xml:schema:emergencycalldata:comment

Registrant Contact: IETF, ECRIT Working Group (ecrit@ietf.org), as delegated by the IESG (iesg@ietf.org).

XML: The XML schema can be found in [Section 7.5](#).

[10.7](#). VCard Parameter Value Registration

This document registers a new value in the vCARD Parameter Values registry as defined by [[RFC6350](#)] with the following template:

Value: main

Purpose: The main telephone number, typically of an enterprise, as opposed to a direct dial number of an individual employee

Conformance: This value can be used with the "TYPE" parameter applied on the "TEL" property.

Example(s): TEL;VALUE=uri;TYPE="main,voice";PREF=1:tel:+1-418-656-9000

[11](#). Acknowledgments

This work was originally started in NENA and has benefitted from a large number of participants in NENA standardization efforts, originally in the Long Term Definition Working Group, the Data Technical Committee and most recently the Additional Data working group. The authors are grateful for the initial work and extended comments provided by many NENA participants, including Delaine Arnold, Marc Berryman, Guy Caron, Mark Fletcher, Brian Dupras, James Leyerle, Kathy McMahon, Christian, Militeau, Ira Pyles, Matt Serra, and Robert (Bob) Sherry. Amursana Khiyod, Robert Sherry, Frank Rahoi, Scott Ross, and Tom Klepetka provided valuable feedback regarding the vCard/xCard use in this specification.

We would also like to thank Paul Kyzivat, Gunnar Hellstrom, Martin Thomson, Keith Drage, Laura Liess, Chris Santer, Barbara Stark, Chris Santer, and Archie Cobbs for their review comments. Alissa Cooper and Guy Caron deserves special mention for their detailed and extensive review comments, which were very helpful and appreciated.

12. References

12.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC2392] Levinson, E., "Content-ID and Message-ID Uniform Resource Locators", [RFC 2392](#), August 1998.
- [RFC3204] Zimmerer, E., Peterson, J., Vemuri, A., Ong, L., Audet, F., Watson, M., and M. Zonoun, "MIME media types for ISUP and QSIG Objects", [RFC 3204](#), December 2001.
- [RFC3261] Rosenberg, J., Schulzrinne, H., Camarillo, G., Johnston, A., Peterson, J., Sparks, R., Handley, M., and E. Schooler, "SIP: Session Initiation Protocol", [RFC 3261](#), June 2002.
- [RFC3459] Burger, E., "Critical Content Multi-purpose Internet Mail Extensions (MIME) Parameter", [RFC 3459](#), January 2003.
- [RFC3688] Mealling, M., "The IETF XML Registry", [BCP 81](#), [RFC 3688](#), January 2004.
- [RFC3966] Schulzrinne, H., "The tel URI for Telephone Numbers", [RFC 3966](#), December 2004.
- [RFC4119] Peterson, J., "A Presence-based GEOPRIV Location Object Format", [RFC 4119](#), December 2005.
- [RFC5226] Narten, T. and H. Alvestrand, "Guidelines for Writing an IANA Considerations Section in RFCs", [BCP 26](#), [RFC 5226](#), May 2008.
- [RFC5322] Resnick, P., Ed., "Internet Message Format", [RFC 5322](#), October 2008.
- [RFC5621] Camarillo, G., "Message Body Handling in the Session Initiation Protocol (SIP)", [RFC 5621](#), September 2009.
- [RFC5646] Phillips, A. and M. Davis, "Tags for Identifying Languages", [BCP 47](#), [RFC 5646](#), September 2009.
- [RFC6350] Perreault, S., "vCard Format Specification", [RFC 6350](#), August 2011.

- [RFC6351] Perreault, S., "xCard: vCard XML Representation", [RFC 6351](#), August 2011.
- [RFC6838] Freed, N., Klensin, J., and T. Hansen, "Media Type Specifications and Registration Procedures", [BCP 13](#), [RFC 6838](#), January 2013.
- [RFC7303] Thompson, H. and C. Lilley, "XML Media Types", [RFC 7303](#), July 2014.

[12.2](#). Informational References

- [ECRIT-WG-wiki]
IETF, "ECRIT WG Wiki", July 2015,
<<http://tools.ietf.org/wg/ecrit/trac/attachment/wiki/WikiStart/additional-data-examples.zip>>.
- [I-D.gellens-slim-negotiating-human-language]
Gellens, R., "Negotiating Human Language in Real-Time Communications", [draft-gellens-slim-negotiating-human-language-01](#) (work in progress), April 2015.
- [IANA-XML-Schemas]
IANA, "IANA XML Schemas", July 2015,
<<http://www.iana.org/assignments/xml-registry/xml-registry.xhtml#schema>>.
- [LanguageTagRegistry]
IANA, "Language Subtag Registry", Feb 2015,
<<http://www.iana.org/assignments/language-subtag-registry/language-subtag-registry>>.
- [RFC3325] Jennings, C., Peterson, J., and M. Watson, "Private Extensions to the Session Initiation Protocol (SIP) for Asserted Identity within Trusted Networks", [RFC 3325](#), November 2002.
- [RFC3840] Rosenberg, J., Schulzrinne, H., and P. Kyzivat, "Indicating User Agent Capabilities in the Session Initiation Protocol (SIP)", [RFC 3840](#), August 2004.
- [RFC5012] Schulzrinne, H. and R. Marshall, "Requirements for Emergency Context Resolution with Internet Technologies", [RFC 5012](#), January 2008.
- [RFC5139] Thomson, M. and J. Winterbottom, "Revised Civic Location Format for Presence Information Data Format Location Object (PIDF-LO)", [RFC 5139](#), February 2008.

- [RFC5491] Winterbottom, J., Thomson, M., and H. Tschofenig, "GEOPRIV Presence Information Data Format Location Object (PIDF-LO) Usage Clarification, Considerations, and Recommendations", [RFC 5491](#), March 2009.
- [RFC5582] Schulzrinne, H., "Location-to-URL Mapping Architecture and Framework", [RFC 5582](#), September 2009.
- [RFC5962] Schulzrinne, H., Singh, V., Tschofenig, H., and M. Thomson, "Dynamic Extensions to the Presence Information Data Format Location Object (PIDF-LO)", [RFC 5962](#), September 2010.
- [RFC5985] Barnes, M., "HTTP-Enabled Location Delivery (HELD)", [RFC 5985](#), September 2010.
- [RFC6443] Rosen, B., Schulzrinne, H., Polk, J., and A. Newton, "Framework for Emergency Calling Using Internet Multimedia", [RFC 6443](#), December 2011.
- [RFC6848] Winterbottom, J., Thomson, M., Barnes, R., Rosen, B., and R. George, "Specifying Civic Address Extensions in the Presence Information Data Format Location Object (PIDF-LO)", [RFC 6848](#), January 2013.
- [RFC6881] Rosen, B. and J. Polk, "Best Current Practice for Communications Services in Support of Emergency Calling", [BCP 181](#), [RFC 6881](#), March 2013.
- [RFC6973] Cooper, A., Tschofenig, H., Aboba, B., Peterson, J., Morris, J., Hansen, M., and R. Smith, "Privacy Considerations for Internet Protocols", [RFC 6973](#), July 2013.
- [RFC7035] Thomson, M., Rosen, B., Stanley, D., Bajko, G., and A. Thomson, "Relative Location Representation", [RFC 7035](#), October 2013.
- [RFC7090] Schulzrinne, H., Tschofenig, H., Holmberg, C., and M. Patel, "Public Safety Answering Point (PSAP) Callback", [RFC 7090](#), April 2014.

12.3. URIs

- [1] <http://www.nena.org/?page=cid2014>
- [2] <http://www.nena.org/?page=CompanyID>

[Appendix A](#). XML Schema for vCard/xCard

This section contains the vCard/xCard XML schema version of the Relax NG schema defined in [RFC 6351](#) [[RFC6351](#)] for simplified use with the XML schemas defined in this document. The schema in [RFC 6351](#) [[RFC6351](#)] is the normative source and this section is informative only.

```
<?xml version="1.0" encoding="UTF-8"?>
<xs:schema xmlns:xs="http://www.w3.org/2001/XMLSchema"
  elementFormDefault="qualified"
  targetNamespace="urn:ietf:params:xml:ns:vcard-4.0"
  xmlns:ns1="urn:ietf:params:xml:ns:vcard-4.0">
  <!--

      3.3
      iana-token = xsd:string { pattern = "[a-zA-Z0-9-]+" }
      x-name = xsd:string { pattern = "x-[a-zA-Z0-9-]+" }
      -->
  <xs:simpleType name="iana-token">
    <xs:annotation>
      <xs:documentation>vCard Format Specification
    </xs:documentation>
    </xs:annotation>
    <xs:restriction base="xs:string"/>
  </xs:simpleType>
  <xs:simpleType name="x-name">
    <xs:restriction base="xs:string"/>
  </xs:simpleType>
  <!--

      4.1
      -->
  <xs:element name="text" type="xs:string"/>
  <xs:group name="value-text-list">
    <xs:sequence>
      <xs:element maxOccurs="unbounded" ref="ns1:text"/>
    </xs:sequence>
  </xs:group>
  <!-- 4.2 -->
  <xs:element name="uri" type="xs:anyURI"/>
  <!-- 4.3.1 -->
  <xs:element name="date"
    substitutionGroup="ns1:value-date-and-or-time">
    <xs:simpleType>
      <xs:restriction base="xs:string">
        <xs:pattern value=
```



```
"\d{8}|\d{4}-\d\d|--\d\d(\d\d)?|---\d\d"/>
  </xs:restriction>
</xs:simpleType>
</xs:element>
<!-- 4.3.2 -->
<xs:element name="time"
substitutionGroup="ns1:value-date-and-or-time">
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:pattern value=
"(\d\d(\d\d(\d\d)?)?|-\d\d(\d\d)?|--\d\d)(Z|[\+-]\d\d(\d\d)?)" />
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<!-- 4.3.3 -->
<xs:element name="date-time"
substitutionGroup="ns1:value-date-and-or-time">
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:pattern value=
"(\d{8}|--\d{4}|---\d\d)T\d\d(\d\d(\d\d)?)?(Z|[\+-]\d\d(\d\d)?)" />
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<!-- 4.3.4 -->
<xs:element name="value-date-and-or-time" abstract="true"/>
<!-- 4.3.5 -->
<xs:complexType name="value-timestamp">
  <xs:sequence>
    <xs:element ref="ns1:timestamp"/>
  </xs:sequence>
</xs:complexType>
<xs:element name="timestamp">
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:pattern value="\d{8}T\d{6}(Z|[\+-]\d\d(\d\d)?)" />
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<!-- 4.4 -->
<xs:element name="boolean" type="xs:boolean"/>
<!-- 4.5 -->
<xs:element name="integer" type="xs:integer"/>
<!-- 4.6 -->
<xs:element name="float" type="xs:float"/>
<!-- 4.7 -->
<xs:element name="utc-offset">
  <xs:simpleType>
```



```

        <xs:restriction base="xs:string">
            <xs:pattern value="[+\-]\d\d(\d\d)?"/>
        </xs:restriction>
    </xs:simpleType>
</xs:element>
<!-- 4.8 -->
<xs:element name="language-tag">
    <xs:simpleType>
        <xs:restriction base="xs:string">
            <xs:pattern
value="([a-z]{2,3}((-[a-z]{3}){0,3})?|[a-z]{4,8})
(-[a-z]{4})?(-([a-z]{2}|\d{3}))?(-([0-9a-z]{5,8}|
\d[0-9a-z]{3}))*(-[0-9a-wyz](-[0-9a-z]{2,8})+)*
(-x(-[0-9a-z]{1,8})+)?|x(-[0-9a-z]{1,8})+|[a-z]{1,3}
(-[0-9a-z]{2,8}){1,2}"/>
        </xs:restriction>
    </xs:simpleType>
</xs:element>
<!--

5.1
-->
<xs:group name="param-language">
    <xs:annotation>
        <xs:documentation>Section 5: Parameters</xs:documentation>
    </xs:annotation>
    <xs:sequence>
        <xs:element minOccurs="0" ref="ns1:language"/>
    </xs:sequence>
</xs:group>
<xs:element name="language">
    <xs:complexType>
        <xs:sequence>
            <xs:element ref="ns1:language-tag"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<!-- 5.2 -->
<xs:group name="param-pref">
    <xs:sequence>
        <xs:element minOccurs="0" ref="ns1:pref"/>
    </xs:sequence>
</xs:group>
<xs:element name="pref">
    <xs:complexType>
        <xs:sequence>
            <xs:element name="integer">
                <xs:simpleType>

```



```
        <xs:restriction base="xs:integer">
          <xs:minInclusive value="1"/>
          <xs:maxInclusive value="100"/>
        </xs:restriction>
      </xs:simpleType>
    </xs:element>
  </xs:sequence>
</xs:complexType>
</xs:element>
<!-- 5.4 -->
<xs:group name="param-altid">
  <xs:sequence>
    <xs:element minOccurs="0" ref="ns1:altid"/>
  </xs:sequence>
</xs:group>
<xs:element name="altid">
  <xs:complexType>
    <xs:sequence>
      <xs:element ref="ns1:text"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<!-- 5.5 -->
<xs:group name="param-pid">
  <xs:sequence>
    <xs:element minOccurs="0" ref="ns1:pid"/>
  </xs:sequence>
</xs:group>
<xs:element name="pid">
  <xs:complexType>
    <xs:sequence>
      <xs:element maxOccurs="unbounded" name="text">
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:pattern value="\d+(\.\d+)?"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<!-- 5.6 -->
<xs:group name="param-type">
  <xs:sequence>
    <xs:element minOccurs="0" ref="ns1:type"/>
  </xs:sequence>
</xs:group>
<xs:element name="type">
```



```
<xs:complexType>
  <xs:sequence>
    <xs:element maxOccurs="unbounded" name="text">
      <xs:simpleType>
        <xs:restriction base="xs:token">
          <xs:enumeration value="work"/>
          <xs:enumeration value="home"/>
        </xs:restriction>
      </xs:simpleType>
    </xs:element>
  </xs:sequence>
</xs:complexType>
</xs:element>
<!-- 5.7 -->
<xs:group name="param-mediatype">
  <xs:sequence>
    <xs:element minOccurs="0" ref="ns1:mediatype"/>
  </xs:sequence>
</xs:group>
<xs:element name="mediatype">
  <xs:complexType>
    <xs:sequence>
      <xs:element ref="ns1:text"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<!-- 5.8 -->
<xs:group name="param-calscale">
  <xs:sequence>
    <xs:element minOccurs="0" ref="ns1:calscale"/>
  </xs:sequence>
</xs:group>
<xs:element name="calscale">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="text">
        <xs:simpleType>
          <xs:restriction base="xs:token">
            <xs:enumeration value="gregorian"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<!-- 5.9 -->
<xs:group name="param-sort-as">
  <xs:sequence>
```



```
        <xs:element minOccurs="0" ref="ns1:sort-as"/>
      </xs:sequence>
    </xs:group>
    <xs:element name="sort-as">
      <xs:complexType>
        <xs:sequence>
          <xs:element maxOccurs="unbounded" ref="ns1:text"/>
        </xs:sequence>
      </xs:complexType>
    </xs:element>
    <!-- 5.10 -->
    <xs:group name="param-geo">
      <xs:sequence>
        <xs:element minOccurs="0" name="geo">
          <xs:complexType>
            <xs:sequence>
              <xs:element ref="ns1:uri"/>
            </xs:sequence>
          </xs:complexType>
        </xs:element>
      </xs:sequence>
    </xs:group>
    <!-- 5.11 -->
    <xs:group name="param-tz">
      <xs:sequence>
        <xs:element minOccurs="0" name="tz">
          <xs:complexType>
            <xs:choice>
              <xs:element ref="ns1:text"/>
              <xs:element ref="ns1:uri"/>
            </xs:choice>
          </xs:complexType>
        </xs:element>
      </xs:sequence>
    </xs:group>
    <!--
```

6.1.3

```
-->
<xs:element name="source">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="parameters">
        <xs:complexType>
          <xs:sequence>
            <xs:group ref="ns1:param-altid"/>
            <xs:group ref="ns1:param-pid"/>
            <xs:group ref="ns1:param-pref"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```



```
        <xs:group ref="ns1:param-mediatype"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:element ref="ns1:uri"/>
</xs:sequence>
</xs:complexType>
</xs:element>
<!-- 6.1.4 -->
<xs:element name="kind">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="unbounded" name="text">
        <xs:simpleType>
          <xs:union memberTypes="ns1:x-name ns1:iana-token">
            <xs:simpleType>
              <xs:restriction base="xs:token">
                <xs:enumeration value="individual"/>
              </xs:restriction>
            </xs:simpleType>
            <xs:simpleType>
              <xs:restriction base="xs:token">
                <xs:enumeration value="group"/>
              </xs:restriction>
            </xs:simpleType>
            <xs:simpleType>
              <xs:restriction base="xs:token">
                <xs:enumeration value="org"/>
              </xs:restriction>
            </xs:simpleType>
            <xs:simpleType>
              <xs:restriction base="xs:token">
                <xs:enumeration value="location"/>
              </xs:restriction>
            </xs:simpleType>
          </xs:union>
        </xs:simpleType>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<!-- 6.2.1 -->
<xs:element name="fn">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="parameters">
        <xs:complexType>
          <xs:sequence>
```



```
        <xs:group ref="ns1:param-language"/>
        <xs:group ref="ns1:param-altid"/>
        <xs:group ref="ns1:param-pid"/>
        <xs:group ref="ns1:param-pref"/>
        <xs:group ref="ns1:param-type"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:element ref="ns1:text"/>
</xs:sequence>
</xs:complexType>
</xs:element>
<!-- 6.2.2 -->
<xs:element name="n">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="parameters">
        <xs:complexType>
          <xs:sequence>
            <xs:group ref="ns1:param-language"/>
            <xs:group ref="ns1:param-sort-as"/>
            <xs:group ref="ns1:param-altid"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:element maxOccurs="unbounded" ref="ns1:surname"/>
      <xs:element maxOccurs="unbounded" ref="ns1:given"/>
      <xs:element maxOccurs="unbounded" ref="ns1:additional"/>
      <xs:element maxOccurs="unbounded" ref="ns1:prefix"/>
      <xs:element maxOccurs="unbounded" ref="ns1:suffix"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="surname" type="xs:string"/>
<xs:element name="given" type="xs:string"/>
<xs:element name="additional" type="xs:string"/>
<xs:element name="prefix" type="xs:string"/>
<xs:element name="suffix" type="xs:string"/>
<!-- 6.2.3 -->
<xs:element name="nickname">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="parameters">
        <xs:complexType>
          <xs:sequence>
            <xs:group ref="ns1:param-language"/>
            <xs:group ref="ns1:param-altid"/>
            <xs:group ref="ns1:param-pid"/>
```



```
        <xs:group ref="ns1:param-pref"/>
        <xs:group ref="ns1:param-type"/>
    </xs:sequence>
</xs:complexType>
</xs:element>
    <xs:group ref="ns1:value-text-list"/>
</xs:sequence>
</xs:complexType>
</xs:element>
<!-- 6.2.4 -->
<xs:element name="photo">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="parameters">
                <xs:complexType>
                    <xs:sequence>
                        <xs:group ref="ns1:param-altid"/>
                        <xs:group ref="ns1:param-pid"/>
                        <xs:group ref="ns1:param-pref"/>
                        <xs:group ref="ns1:param-type"/>
                        <xs:group ref="ns1:param-mediatype"/>
                    </xs:sequence>
                </xs:complexType>
            </xs:element>
            <xs:element ref="ns1:uri"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<!-- 6.2.5 -->
<xs:element name="bday">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="parameters">
                <xs:complexType>
                    <xs:sequence>
                        <xs:group ref="ns1:param-altid"/>
                        <xs:group ref="ns1:param-calscale"/>
                    </xs:sequence>
                </xs:complexType>
            </xs:element>
            <xs:choice>
                <xs:element ref="ns1:value-date-and-or-time"/>
                <xs:element ref="ns1:text"/>
            </xs:choice>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<!-- 6.2.6 -->
```



```
<xs:element name="anniversary">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="parameters">
        <xs:complexType>
          <xs:sequence>
            <xs:group ref="ns1:param-altid"/>
            <xs:group ref="ns1:param-calscale"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:choice>
        <xs:element ref="ns1:value-date-and-or-time"/>
        <xs:element ref="ns1:text"/>
      </xs:choice>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<!-- 6.2.7 -->
<xs:element name="gender">
  <xs:complexType>
    <xs:sequence>
      <xs:element ref="ns1:sex"/>
      <xs:element minOccurs="0" ref="ns1:identity"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="sex">
  <xs:simpleType>
    <xs:restriction base="xs:token">
      <xs:enumeration value=""/>
      <xs:enumeration value="M"/>
      <xs:enumeration value="F"/>
      <xs:enumeration value="0"/>
      <xs:enumeration value="N"/>
      <xs:enumeration value="U"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element name="identity" type="xs:string"/>
<!-- 6.3.1 -->
<xs:group name="param-label">
  <xs:sequence>
    <xs:element minOccurs="0" ref="ns1:label"/>
  </xs:sequence>
</xs:group>
<xs:element name="label">
  <xs:complexType>
```



```
<xs:sequence>
  <xs:element ref="ns1:text"/>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="adr">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="parameters">
        <xs:complexType>
          <xs:sequence>
            <xs:group ref="ns1:param-language"/>
            <xs:group ref="ns1:param-altid"/>
            <xs:group ref="ns1:param-pid"/>
            <xs:group ref="ns1:param-pref"/>
            <xs:group ref="ns1:param-type"/>
            <xs:group ref="ns1:param-geo"/>
            <xs:group ref="ns1:param-tz"/>
            <xs:group ref="ns1:param-label"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:element maxOccurs="unbounded" ref="ns1:pobox"/>
      <xs:element maxOccurs="unbounded" ref="ns1:ext"/>
      <xs:element maxOccurs="unbounded" ref="ns1:street"/>
      <xs:element maxOccurs="unbounded" ref="ns1:locality"/>
      <xs:element maxOccurs="unbounded" ref="ns1:region"/>
      <xs:element maxOccurs="unbounded" ref="ns1:code"/>
      <xs:element maxOccurs="unbounded" ref="ns1:country"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="pobox" type="xs:string"/>
<xs:element name="ext" type="xs:string"/>
<xs:element name="street" type="xs:string"/>
<xs:element name="locality" type="xs:string"/>
<xs:element name="region" type="xs:string"/>
<xs:element name="code" type="xs:string"/>
<xs:element name="country" type="xs:string"/>
<!-- 6.4.1 -->
<xs:element name="tel">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="parameters">
        <xs:complexType>
          <xs:sequence>
            <xs:group ref="ns1:param-altid"/>
            <xs:group ref="ns1:param-pid"/>
```



```
<xs:group ref="ns1:param-pref"/>
<xs:element minOccurs="0" name="type">
  <xs:complexType>
    <xs:sequence>
      <xs:element maxOccurs="unbounded" name="text">
        <xs:simpleType>
          <xs:restriction base="xs:token">
            <xs:enumeration value="work"/>
            <xs:enumeration value="home"/>
            <xs:enumeration value="text"/>
            <xs:enumeration value="voice"/>
            <xs:enumeration value="fax"/>
            <xs:enumeration value="cell"/>
            <xs:enumeration value="video"/>
            <xs:enumeration value="pager"/>
            <xs:enumeration value="textphone"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:group ref="ns1:param-mediatype"/>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:choice>
  <xs:element ref="ns1:text"/>
  <xs:element ref="ns1:uri"/>
</xs:choice>
</xs:sequence>
</xs:complexType>
</xs:element>
<!-- 6.4.2 -->
<xs:element name="email">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="parameters">
        <xs:complexType>
          <xs:sequence>
            <xs:group ref="ns1:param-altid"/>
            <xs:group ref="ns1:param-pid"/>
            <xs:group ref="ns1:param-pref"/>
            <xs:group ref="ns1:param-type"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:element ref="ns1:text"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```



```
        </xs:sequence>
      </xs:complexType>
    </xs:element>
    <!-- 6.4.3 -->
    <xs:element name="impp">
      <xs:complexType>
        <xs:sequence>
          <xs:element minOccurs="0" name="parameters">
            <xs:complexType>
              <xs:sequence>
                <xs:group ref="ns1:param-altid"/>
                <xs:group ref="ns1:param-pid"/>
                <xs:group ref="ns1:param-pref"/>
                <xs:group ref="ns1:param-type"/>
                <xs:group ref="ns1:param-mediatype"/>
              </xs:sequence>
            </xs:complexType>
          </xs:element>
          <xs:element ref="ns1:uri"/>
        </xs:sequence>
      </xs:complexType>
    </xs:element>
    <!-- 6.4.4 -->
    <xs:element name="lang">
      <xs:complexType>
        <xs:sequence>
          <xs:element minOccurs="0" name="parameters">
            <xs:complexType>
              <xs:sequence>
                <xs:group ref="ns1:param-altid"/>
                <xs:group ref="ns1:param-pid"/>
                <xs:group ref="ns1:param-pref"/>
                <xs:group ref="ns1:param-type"/>
              </xs:sequence>
            </xs:complexType>
          </xs:element>
          <xs:element ref="ns1:language-tag"/>
        </xs:sequence>
      </xs:complexType>
    </xs:element>
    <!-- 6.5.1 -->
    <xs:group name="property-tz">
      <xs:sequence>
        <xs:element name="tz">
          <xs:complexType>
            <xs:sequence>
              <xs:element minOccurs="0" name="parameters">
                <xs:complexType>
```



```
        <xs:sequence>
          <xs:group ref="ns1:param-altid"/>
          <xs:group ref="ns1:param-pid"/>
          <xs:group ref="ns1:param-pref"/>
          <xs:group ref="ns1:param-type"/>
          <xs:group ref="ns1:param-mediatype"/>
        </xs:sequence>
      </xs:complexType>
    </xs:element>
    <xs:choice>
      <xs:element ref="ns1:text"/>
      <xs:element ref="ns1:uri"/>
      <xs:element ref="ns1:utc-offset"/>
    </xs:choice>
  </xs:sequence>
</xs:complexType>
</xs:element>
</xs:sequence>
</xs:group>
<!-- 6.5.2 -->
<xs:group name="property-geo">
  <xs:sequence>
    <xs:element name="geo">
      <xs:complexType>
        <xs:sequence>
          <xs:element minOccurs="0" name="parameters">
            <xs:complexType>
              <xs:sequence>
                <xs:group ref="ns1:param-altid"/>
                <xs:group ref="ns1:param-pid"/>
                <xs:group ref="ns1:param-pref"/>
                <xs:group ref="ns1:param-type"/>
                <xs:group ref="ns1:param-mediatype"/>
              </xs:sequence>
            </xs:complexType>
          </xs:element>
          <xs:element ref="ns1:uri"/>
        </xs:sequence>
      </xs:complexType>
    </xs:element>
  </xs:sequence>
</xs:group>
<!-- 6.6.1 -->
<xs:element name="title">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="parameters">
        <xs:complexType>
```



```
<xs:sequence>
  <xs:group ref="ns1:param-language"/>
  <xs:group ref="ns1:param-altid"/>
  <xs:group ref="ns1:param-pid"/>
  <xs:group ref="ns1:param-pref"/>
  <xs:group ref="ns1:param-type"/>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element ref="ns1:text"/>
</xs:sequence>
</xs:complexType>
</xs:element>
<!-- 6.6.2 -->
<xs:element name="role">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="parameters">
        <xs:complexType>
          <xs:sequence>
            <xs:group ref="ns1:param-language"/>
            <xs:group ref="ns1:param-altid"/>
            <xs:group ref="ns1:param-pid"/>
            <xs:group ref="ns1:param-pref"/>
            <xs:group ref="ns1:param-type"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:element ref="ns1:text"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<!-- 6.6.3 -->
<xs:element name="logo">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="parameters">
        <xs:complexType>
          <xs:sequence>
            <xs:group ref="ns1:param-language"/>
            <xs:group ref="ns1:param-altid"/>
            <xs:group ref="ns1:param-pid"/>
            <xs:group ref="ns1:param-pref"/>
            <xs:group ref="ns1:param-type"/>
            <xs:group ref="ns1:param-mediatype"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```



```
        <xs:element ref="ns1:uri"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <!-- 6.6.4 -->
  <xs:element name="org">
    <xs:complexType>
      <xs:sequence>
        <xs:element minOccurs="0" name="parameters">
          <xs:complexType>
            <xs:sequence>
              <xs:group ref="ns1:param-language"/>
              <xs:group ref="ns1:param-altid"/>
              <xs:group ref="ns1:param-pid"/>
              <xs:group ref="ns1:param-pref"/>
              <xs:group ref="ns1:param-type"/>
              <xs:group ref="ns1:param-sort-as"/>
            </xs:sequence>
          </xs:complexType>
        </xs:element>
        <xs:group ref="ns1:value-text-list"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <!-- 6.6.5 -->
  <xs:element name="member">
    <xs:complexType>
      <xs:sequence>
        <xs:element minOccurs="0" name="parameters">
          <xs:complexType>
            <xs:sequence>
              <xs:group ref="ns1:param-altid"/>
              <xs:group ref="ns1:param-pid"/>
              <xs:group ref="ns1:param-pref"/>
              <xs:group ref="ns1:param-mediatype"/>
            </xs:sequence>
          </xs:complexType>
        </xs:element>
        <xs:element ref="ns1:uri"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <!-- 6.6.6 -->
  <xs:element name="related">
    <xs:complexType>
      <xs:sequence>
        <xs:element minOccurs="0" name="parameters">
          <xs:complexType>
```



```
<xs:sequence>
  <xs:group ref="ns1:param-altid"/>
  <xs:group ref="ns1:param-pid"/>
  <xs:group ref="ns1:param-pref"/>
  <xs:element minOccurs="0" name="type">
    <xs:complexType>
      <xs:sequence>
        <xs:element maxOccurs="unbounded" name="text">
          <xs:simpleType>
            <xs:restriction base="xs:token">
              <xs:enumeration value="work"/>
              <xs:enumeration value="home"/>
              <xs:enumeration value="contact"/>
              <xs:enumeration value="acquaintance"/>
              <xs:enumeration value="friend"/>
              <xs:enumeration value="met"/>
              <xs:enumeration value="co-worker"/>
              <xs:enumeration value="colleague"/>
              <xs:enumeration value="co-resident"/>
              <xs:enumeration value="neighbor"/>
              <xs:enumeration value="child"/>
              <xs:enumeration value="parent"/>
              <xs:enumeration value="sibling"/>
              <xs:enumeration value="spouse"/>
              <xs:enumeration value="kin"/>
              <xs:enumeration value="muse"/>
              <xs:enumeration value="crush"/>
              <xs:enumeration value="date"/>
              <xs:enumeration value="sweetheart"/>
              <xs:enumeration value="me"/>
              <xs:enumeration value="agent"/>
              <xs:enumeration value="emergency"/>
            </xs:restriction>
          </xs:simpleType>
        </xs:element>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:group ref="ns1:param-mediatype"/>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:choice>
  <xs:element ref="ns1:uri"/>
  <xs:element ref="ns1:text"/>
</xs:choice>
</xs:sequence>
</xs:complexType>
```



```
</xs:element>
<!-- 6.7.1 -->
<xs:element name="categories">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="parameters">
        <xs:complexType>
          <xs:sequence>
            <xs:group ref="ns1:param-altid"/>
            <xs:group ref="ns1:param-pid"/>
            <xs:group ref="ns1:param-pref"/>
            <xs:group ref="ns1:param-type"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:group ref="ns1:value-text-list"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<!-- 6.7.2 -->
<xs:element name="note">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="parameters">
        <xs:complexType>
          <xs:sequence>
            <xs:group ref="ns1:param-language"/>
            <xs:group ref="ns1:param-altid"/>
            <xs:group ref="ns1:param-pid"/>
            <xs:group ref="ns1:param-pref"/>
            <xs:group ref="ns1:param-type"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:element ref="ns1:text"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<!-- 6.7.3 -->
<xs:element name="prodid">
  <xs:complexType>
    <xs:sequence>
      <xs:element ref="ns1:text"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<!-- 6.7.4 -->
<xs:element name="rev" type="ns1:value-timestamp"/>
```



```
<!-- 6.7.5 -->
<xs:element name="sound">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="parameters">
        <xs:complexType>
          <xs:sequence>
            <xs:group ref="ns1:param-language"/>
            <xs:group ref="ns1:param-altid"/>
            <xs:group ref="ns1:param-pid"/>
            <xs:group ref="ns1:param-pref"/>
            <xs:group ref="ns1:param-type"/>
            <xs:group ref="ns1:param-mediatype"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:element ref="ns1:uri"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<!-- 6.7.6 -->
<xs:element name="uid">
  <xs:complexType>
    <xs:sequence>
      <xs:element ref="ns1:uri"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<!-- 6.7.7 -->
<xs:element name="clientpidmap">
  <xs:complexType>
    <xs:sequence>
      <xs:element ref="ns1:sourceid"/>
      <xs:element ref="ns1:uri"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="sourceid" type="xs:positiveInteger"/>
<!-- 6.7.8 -->
<xs:element name="url">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="parameters">
        <xs:complexType>
          <xs:sequence>
            <xs:group ref="ns1:param-altid"/>
            <xs:group ref="ns1:param-pid"/>
            <xs:group ref="ns1:param-pref"/>
```



```
        <xs:group ref="ns1:param-type"/>
        <xs:group ref="ns1:param-mediatype"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:element ref="ns1:uri"/>
</xs:sequence>
</xs:complexType>
</xs:element>
<!-- 6.8.1 -->
<xs:element name="key">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="parameters">
        <xs:complexType>
          <xs:sequence>
            <xs:group ref="ns1:param-altid"/>
            <xs:group ref="ns1:param-pid"/>
            <xs:group ref="ns1:param-pref"/>
            <xs:group ref="ns1:param-type"/>
            <xs:group ref="ns1:param-mediatype"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:choice>
        <xs:element ref="ns1:uri"/>
        <xs:element ref="ns1:text"/>
      </xs:choice>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<!-- 6.9.1 -->
<xs:element name="fburl">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="parameters">
        <xs:complexType>
          <xs:sequence>
            <xs:group ref="ns1:param-altid"/>
            <xs:group ref="ns1:param-pid"/>
            <xs:group ref="ns1:param-pref"/>
            <xs:group ref="ns1:param-type"/>
            <xs:group ref="ns1:param-mediatype"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:element ref="ns1:uri"/>
    </xs:sequence>
```



```
</xs:complexType>
</xs:element>
<!-- 6.9.2 -->
<xs:element name="caladruri">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="parameters">
        <xs:complexType>
          <xs:sequence>
            <xs:group ref="ns1:param-altid"/>
            <xs:group ref="ns1:param-pid"/>
            <xs:group ref="ns1:param-pref"/>
            <xs:group ref="ns1:param-type"/>
            <xs:group ref="ns1:param-mediatype"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:element ref="ns1:uri"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<!-- 6.9.3 -->
<xs:element name="caluri">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="parameters">
        <xs:complexType>
          <xs:sequence>
            <xs:group ref="ns1:param-altid"/>
            <xs:group ref="ns1:param-pid"/>
            <xs:group ref="ns1:param-pref"/>
            <xs:group ref="ns1:param-type"/>
            <xs:group ref="ns1:param-mediatype"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:element ref="ns1:uri"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<!-- Top-level grammar -->
<xs:group name="property">
  <xs:choice>
    <xs:element ref="ns1:adr"/>
    <xs:element ref="ns1:anniversary"/>
    <xs:element ref="ns1:bday"/>
    <xs:element ref="ns1:caladruri"/>
    <xs:element ref="ns1:caluri"/>
  </xs:choice>
</xs:group>
</xs:schema>
```



```
<xs:element ref="ns1:categories"/>
<xs:element ref="ns1:clientpidmap"/>
<xs:element ref="ns1:email"/>
<xs:element ref="ns1:fburl"/>
<xs:element ref="ns1:fn"/>
<xs:group ref="ns1:property-geo"/>
<xs:element ref="ns1:impp"/>
<xs:element ref="ns1:key"/>
<xs:element ref="ns1:kind"/>
<xs:element ref="ns1:lang"/>
<xs:element ref="ns1:logo"/>
<xs:element ref="ns1:member"/>
<xs:element ref="ns1:n"/>
<xs:element ref="ns1:nickname"/>
<xs:element ref="ns1:note"/>
<xs:element ref="ns1:org"/>
<xs:element ref="ns1:photo"/>
<xs:element ref="ns1:prodid"/>
<xs:element ref="ns1:related"/>
<xs:element ref="ns1:rev"/>
<xs:element ref="ns1:role"/>
<xs:element ref="ns1:gender"/>
<xs:element ref="ns1:sound"/>
<xs:element ref="ns1:source"/>
<xs:element ref="ns1:tel"/>
<xs:element ref="ns1:title"/>
<xs:group ref="ns1:property-tz"/>
<xs:element ref="ns1:uid"/>
<xs:element ref="ns1:url"/>
</xs:choice>
</xs:group>

<xs:element name="vcards">
  <xs:complexType>
    <xs:sequence>
      <xs:element maxOccurs="unbounded" ref="ns1:vcard"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>

<xs:complexType name="vcardType">
  <xs:complexContent>
    <xs:restriction base="xs:anyType">
      <xs:choice maxOccurs="unbounded">
        <xs:group ref="ns1:property"/>
        <xs:element ref="ns1:group"/>
      </xs:choice>
    </xs:restriction>
  </xs:complexContent>
</xs:complexType>
```



```
        </xs:restriction>
      </xs:complexContent>
    </xs:complexType>

    <xs:element name="vcard" type="ns1:vcardType"/>

    <xs:element name="group">
      <xs:complexType>
        <xs:group minOccurs="0" maxOccurs="unbounded"
          ref="ns1:property"/>
        <xs:attribute name="name" use="required"/>
      </xs:complexType>
    </xs:element>
  </xs:schema>
```

Appendix B. XML Validation

This document defines a number of XML schemas and contains various examples. Extracting the XML and validating the examples against the schemas can be challenging, especially due to the formatting limitations introduced by IETF RFCs. For those readers who copy the XML schemas and examples directly from this document, please consider that errors might be introduced due to line breaks and extra whitespaces in the regular expressions contained in the vcard schema in [Appendix A](#). To validate the PIDF-LO from Figure 18 it is also necessary to consult the referenced RFCs and copy the schemas necessary for successful validation.

The XML schemas found in this document include a 'SchemaLocation' attribute. Depending on the location of the downloaded schema files you may need to adjust this schema location or configure your XML editor to point to the location.

For convenience of readers, the schemas are available at <http://ip-emergency.net/additional-data.zip> and the XML examples are available at the IETF ECRIT Working Group wiki page [[ECRIT-WG-wiki](#)].

Note to RFC Editor: After IANA has published the schemas, the above link to the schemas should be replaced with [[IANA-XML-Schemas](#)].

Authors' Addresses

Randall Gellens
Qualcomm Technologies, Inc.
5775 Morehouse Drive
San Diego, CA 92121
US

Email: rg+ietf@qti.qualcomm.com

Brian Rosen
NeuStar
470 Conrad Dr.
Mars, PA 16046
US

Phone: +1 724 382 1051
Email: br@brianrosen.net

Hannes Tschofenig
Hall in Tirol 6060
Austria

Email: Hannes.tschofenig@gmx.net
URI: <http://www.tschofenig.priv.at>

Roger Marshall
TeleCommunication Systems, Inc.
2401 Elliott Avenue
Seattle, WA 98121
US

Phone: +1 206 792 2424
Email: rmarshall@telecomsys.com
URI: <http://www.telecomsys.com>

James Winterbottom
AU

Email: a.james.winterbottom@gmail.com

