

Entity MIB (Version 3)

[<draft-ietf-entmib-v3-07.txt>](mailto:draft-ietf-entmib-v3-07.txt)

Status of this Memo

By submitting this Internet-Draft, each author represents that any applicable patent or other IPR claims of which he or she is aware have been or will be disclosed, and any of which he or she becomes aware will be disclosed, in accordance with [Section 6 of RFC 3668](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/lid-abstracts.html>

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>

Copyright Notice

Copyright (C) The Internet Society (2005). All Rights Reserved.

Abstract

This memo defines a portion of the Management Information Base

(MIB) for use with network management protocols in the Internet community. In particular, it describes managed objects used for managing multiple logical and physical entities managed by a single SNMP agent. This document specifies version 3 of the Entity MIB, which obsoletes version 2 ([RFC 2737](#)).

Table of Contents

| | | |
|------------------------|--|--------------------|
| 1 | The SNMP Management Framework | 3 |
| 2 | Overview | 3 |
| 2.1 | Terms | 4 |
| 2.2 | Relationship to Community Strings | 6 |
| 2.3 | Relationship to SNMP Contexts | 6 |
| 2.4 | Relationship to Proxy Mechanisms | 6 |
| 2.5 | Relationship to a Chassis MIB | 7 |
| 2.6 | Relationship to the Interfaces MIB | 7 |
| 2.7 | Relationship to the Other MIBs | 7 |
| 2.8 | Relationship to Naming Scopes | 8 |
| 2.9 | Multiple Instances of the Entity MIB | 8 |
| 2.10 | Re-Configuration of Entities | 9 |
| 2.11 | Textual Convention Change | 9 |
| 2.12 | MIB Structure | 9 |
| 2.12.1 | entityPhysical Group | 10 |
| 2.12.2 | entityLogical Group | 12 |
| 2.12.3 | entityMapping Group | 12 |
| 2.12.4 | entityGeneral Group | 13 |
| 2.12.5 | entityNotifications Group | 13 |
| 2.13 | Multiple Agents | 13 |
| 2.14 | Changes Since RFC 2037 | 14 |
| 2.14.1 | Textual Conventions | 14 |
| 2.14.2 | New entPhysicalTable Objects | 14 |
| 2.14.3 | New entLogicalTable Objects | 14 |
| 2.14.4 | Bugfixes | 15 |
| 2.15 | Changes Since RFC 2737 | 15 |
| 2.15.1 | Textual Conventions | 15 |
| 2.15.2 | New Objects | 15 |
| 2.15.3 | Bugfixes | 15 |
| 3 | Definitions | 16 |
| 4 | Usage Examples | 48 |
| 4.1 | Router/Bridge | 48 |
| 4.2 | Repeaters | 55 |
| 5 | Security Considerations | 62 |
| 6 | IANA Considerations | 64 |
| 7 | Acknowledgements | 64 |
| 8 | References | 64 |

Expires July 2005

[Page 2]

| | |
|--|--------------------|
| 8.1 Normative References | 64 |
| 8.2 Informative References | 65 |

[1.](#) The SNMP Management Framework

For a detailed overview of the documents that describe the current Internet-Standard Management Framework, please refer to [section 7 of RFC 3410](#) [[RFC3410](#)].

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. MIB objects are generally accessed through the Simple Network Management Protocol (SNMP). Objects in the MIB are defined using the mechanisms defined in the Structure of Management Information (SMI). This memo specifies a MIB module that is compliant to the SMIV2, which is described in STD 58, [RFC 2578](#) [[RFC2578](#)], STD 58, [RFC 2579](#) [[RFC2579](#)] and STD 58, [RFC 2580](#) [[RFC2580](#)].

[2.](#) Overview

There is a need for a standardized way of representing a single agent which supports multiple instances of one MIB. This is presently true for at least 3 standard MIBs, and is likely to become true for more and more MIBs as time passes. For example:

- multiple instances of a bridge supported within a single device having a single agent;
- multiple repeaters supported by a single agent;
- multiple OSPF backbone areas, each one operating as part of its own Autonomous System, and each identified by the same area-id (e.g., 0.0.0.0), supported inside a single router with one agent.

The fact that it is a single agent in each of these cases implies there is some relationship which binds all of these entities together. Effectively, there is some "overall" physical entity which houses the sum of the things managed by that one agent, i.e., there are multiple "logical" entities within a single physical entity. Sometimes, the overall physical entity contains multiple (smaller) physical entities and each logical entity is associated with a particular physical entity. Sometimes, the overall physical

Expires July 2005

[Page 3]

entity is a "compound" of multiple physical entities (e.g., a stack of stackable hubs).

What is needed is a way to determine exactly what logical entities are managed by the agent (with some version of SNMP), and thereby to be able to communicate with the agent about a particular logical entity. When different logical entities are associated with different physical entities within the overall physical entity, it is also useful to be able to use this information to distinguish between logical entities.

In these situations, there is no need for varbinds for multiple logical entities to be referenced in the same SNMP message (although that might be useful in the future). Rather, it is sufficient, and in some situations preferable, to have the context/community in the message identify the logical entity to which the varbinds apply.

Version 2 of this MIB addresses new requirements that have emerged since the publication of the first Entity MIB ([RFC 2037](#) [[RFC2037](#)]). There is a need for a standardized way of providing non-volatile, administratively assigned identifiers for physical components represented with the Entity MIB. There is also a need to align the Entity MIB with the SNMPv3 administrative framework (STD 62, [RFC 3411](#) [[RFC3411](#)]). Implementation experience has shown that additional physical component attributes are also desirable.

Version 3 of this MIB addresses new requirements that have emerged since the publication of the second Entity MIB ([RFC 2737](#) [[RFC2737](#)]). There is a need for identifying physical entities which are central processing units (CPUs) and a need to provide a textual convention which identifies an entPhysicalIndex value or zero, where the value zero has application-specific semantics. Two new objects have been added to the entPhysicalTable to identify the manufacturing date and provide additional URIs for a particular physical entity.

[2.1.](#) Terms

Some new terms are used throughout this document:

- Naming Scope

A "naming scope" represents the set of information that may be

Expires July 2005

[Page 4]

potentially accessed through a single SNMP operation. All instances within the naming scope share the same unique identifier space. For SNMPv1, a naming scope is identified by the value of the associated 'entLogicalCommunity' instance. For SNMPv3, the term 'context' is used instead of 'naming scope'. The complete definition of an SNMP context can be found in section 3.3.1 of [RFC 3411](#) [[RFC3411](#)].

- Multi-Scoped Object

A MIB object, for which identical instance values identify different managed information in different naming scopes, is called a "multi-scoped" MIB object.

- Single-Scoped Object

A MIB object, for which identical instance values identify the same managed information in different naming scopes, is called a "single-scoped" MIB object.

- Logical Entity

A managed system contains one or more logical entities, each represented by at most one instantiation of each of a particular set of MIB objects. A set of management functions is associated with each logical entity. Examples of logical entities include routers, bridges, print-servers, etc.

- Physical Entity

A "physical entity" or "physical component" represents an identifiable physical resource within a managed system. Zero or more logical entities may utilize a physical resource at any given time. It is an implementation-specific manner as to which physical components are represented by an agent in the EntPhysicalTable. Typically, physical resources (e.g., communications ports, backplanes, sensors, daughter-cards, power supplies, the overall chassis) which can be managed via functions associated with one or more logical entities are included in the MIB.

- Containment Tree

Each physical component may be modeled as 'contained' within another physical component. A "containment-tree" is the conceptual sequence of entPhysicalIndex values which uniquely specifies the exact physical location of a physical component within the managed system. It is generated by 'following and recording' each

Expires July 2005

[Page 5]

'entPhysicalContainedIn' instance 'up the tree towards the root', until a value of zero indicating no further containment is found.

2.2. Relationship to Community Strings

For community-based SNMP, distinguishing between different logical entities is one (but not the only) purpose of the community string ([RFC 1157](#) [[RFC1157](#)]). This is accommodated by representing each community string as a logical entity.

Note that different logical entities may share the same naming scope (and therefore the same values of entLogicalCommunity). This is possible, providing they have no need for the same instance of a MIB object to represent different managed information.

2.3. Relationship to SNMP Contexts

Version 2 of the Entity MIB contains support for associating SNMPv3 contexts with logical entities. Two new MIB objects, defining an SnmpEngineID and ContextName pair, are used together to identify an SNMP context associated with a logical entity. This context can be used (in conjunction with the entLogicalIPAddress and entLogicalDomain MIB objects) to send SNMPv3 messages on behalf of a particular logical entity.

2.4. Relationship to Proxy Mechanisms

The Entity MIB is designed to allow functional component discovery. The administrative relationships between different logical entities are not visible in any Entity MIB tables. An NMS cannot determine whether MIB instances in different naming scopes are realized locally or remotely (e.g., via some proxy mechanism) by examining any particular Entity MIB objects.

The management of administrative framework functions is not an explicit goal of the Entity MIB WG at this time. This new area of functionality may be revisited after some operational experience with the Entity MIB is gained.

Note that for community-based versions of SNMP, a network administrator will likely be able to associate community strings with naming scopes with proprietary mechanisms, as a matter of

Expires July 2005

[Page 6]

configuration. There are no mechanisms for managing naming scopes defined in this MIB.

2.5. Relationship to a Chassis MIB

Some readers may recall that a previous IETF working group attempted to define a Chassis MIB. No consensus was reached by that working group, possibly because its scope was too broad. As such, it is not the purpose of this MIB to be a "Chassis MIB replacement", nor is it within the scope of this MIB to contain all the information which might be necessary to manage a "chassis". On the other hand, the entities represented by an implementation of this MIB might well be contained in a chassis.

2.6. Relationship to the Interfaces MIB

The Entity MIB contains a mapping table identifying physical components that have 'external values' (e.g., ifIndex) associated with them within a given naming scope. This table can be used to identify the physical location of each interface in the ifTable ([RFC 2863](#) [[RFC2863](#)]). Since ifIndex values in different contexts are not related to one another, the interface to physical component associations are relative to the same logical entity within the agent.

The Entity MIB also contains 'entPhysicalName' and 'entPhysicalAlias' objects, which approximate the semantics of the 'ifName' and 'ifAlias' objects (respectively) from the Interfaces MIB [[RFC2863](#)], for all types of physical components.

2.7. Relationship to the Other MIBs

The Entity MIB contains a mapping table identifying physical components that have identifiers from other standard MIBs associated with them. For example, this table can be used along with the physical mapping table to identify the physical location of each repeater port in the rpTrPortTable, or each interface in the ifTable.

Expires July 2005

[Page 7]

2.8. Relationship to Naming Scopes

There is some question as to which MIB objects may be returned within a given naming scope. MIB objects which are not multi-scoped within a managed system are likely to ignore context information in implementation. In such a case, it is likely such objects will be returned in all naming scopes (e.g., not just the 'default' naming scope or the SNMPv3 default context).

For example, a community string used to access the management information for logical device 'bridge2' may allow access to all the non-bridge related objects in the 'default' naming scope, as well as a second instance of the Bridge MIB ([RFC 1493](#) [[RFC1493](#)]).

It is an implementation-specific matter as to the isolation of single-scoped MIB objects by the agent. An agent may wish to limit the objects returned in a particular naming scope to just the multi-scoped objects in that naming scope (e.g., system group and the Bridge MIB). In this case, all single-scoped management information would belong to a common naming scope (e.g., 'default'), which itself may contain some multi-scoped objects (e.g., system group).

2.9. Multiple Instances of the Entity MIB

It is possible that more than one agent exists in a managed system, and in such cases, multiple instances of the Entity MIB (representing the same managed objects) may be available to an NMS.

In order to reduce complexity for agent implementation, multiple instances of the Entity MIB are not required to be equivalent or even consistent. An NMS may be able to 'align' instances returned by different agents by examining the columns of each table, but vendor-specific identifiers and (especially) index values are likely to be different. Each agent may be managing different subsets of the entire chassis as well.

When all of a physically-modular device is represented by a single agent, the entry for which `entPhysicalContainedIn` has the value zero would likely have 'chassis' as the value of its `entPhysicalClass`; alternatively, for an agent on a module where the agent represents only the physical entities on that module (not those on other modules), the entry for which `entPhysicalContainedIn` has the value zero would likely have 'module' as the value of its

Expires July 2005

[Page 8]

entPhysicalClass.

An agent implementation of the entLogicalTable is not required to contain information about logical entities managed primarily by other agents. That is, the entLogicalTAddress and entLogicalTDomain objects in the entLogicalTable are provided to support an historical multiplexing mechanism, not to identify other SNMP agents.

Note that the Entity MIB is a single-scoped MIB, in the event an agent represents the MIB in different naming scopes.

2.10. Re-Configuration of Entities

Most of the MIB objects defined in this MIB have at most a read-only MAX-ACCESS clause. This is a conscious decision by the working group to limit this MIB's scope. The second version of the Entity MIB allows a network administrator to configure some common attributes of physical components.

2.11. Textual Convention Change

Version 1 of the Entity MIB contains three MIB objects defined with the (now obsolete) DisplayString textual convention. In version 2 of the Entity MIB, the syntax for these objects has been updated to use the (now preferred) SnmpAdminString textual convention.

The working group realizes that this change is not strictly supported by SMIV2. In our judgment, the alternative of deprecating the old objects and defining new objects would have a more adverse impact on backward compatibility and interoperability, given the particular semantics of these objects.

2.12. MIB Structure

The Entity MIB contains five groups of MIB objects:

- entityPhysical group
Describes the physical entities managed by a single agent.

Expires July 2005

[Page 9]

- entityLogical group
Describes the logical entities managed by a single agent.
- entityMapping group
Describes the associations between the physical entities, logical entities, interfaces, and non-interface ports managed by a single agent.
- entityGeneral group
Describes general system attributes shared by potentially all types of entities managed by a single agent.
- entityNotifications group
Contains status indication notifications.

2.12.1. entityPhysical Group

This group contains a single table to identify physical system components, called the entPhysicalTable.

The entPhysicalTable contains one row per physical entity, and must always contain at least one row for an "overall" physical entity, which should have an entPhysicalClass value of 'stack(11)', 'chassis(3)' or 'module(9)'.

Each row is indexed by an arbitrary, small integer, and contains a description and type of the physical entity. It also optionally contains the index number of another entPhysicalEntry indicating a containment relationship between the two.

Version 2 of the Entity MIB provides additional MIB objects for each physical entity. Some common read-only attributes have been added, as well as three writable string objects.

- entPhysicalAlias
This string can be used by an NMS as a non-volatile identifier for the physical component. Maintaining a non-volatile string for every physical component represented in the entPhysicalTable can be costly and unnecessary. An agent may algorithmically generate 'entPhysicalAlias' strings for particular entries (e.g., based on the entPhysicalClass value).
- entPhysicalAssetID
This string is provided to store a user-specific asset identifier

Expires July 2005

[Page 10]

for removable physical components. In order to reduce the non-volatile storage needed by a particular agent, a network administrator should only assign asset identifiers to physical entities which are field-replaceable (i.e., not permanently contained within another physical entity).

- entPhysicalSerialNum

This string is provided to store a vendor-specific serial number string for physical components. This is a writable object in case an agent cannot identify the serial numbers of all installed physical entities, and a network administrator wishes to configure the non-volatile serial number strings manually (via an NMS application).

Version 3 of the Entity MIB provides two additional MIB objects for each physical entity:

- entPhysicalMfgDate

This object contains the date of manufacturing of the managed entity. If the manufacturing date is unknown or not supported the object is not instantiated. The special value '0000000000000000'H may also be returned in this case.

- entPhysicalUris

This object provides additional identification information about the physical entity.

The object contains one or more Uniform Resource Identifiers (URIs) and therefore the syntax of this object must conform to [RFC 2396](#) [[RFC2396](#) section 2]. Uniform Resource Names (URNs), [RFC 3406](#) [[RFC3406](#)], are resource identifiers with the specific requirements for enabling location independent identification of a resource, as well as longevity of reference. URNs are part of the larger URI family with the specific goal of providing persistent naming of resources. URI schemes and URN name spaces are registered by IANA (see <http://www.iana.org/assignments/uri-schemes> and <http://www.iana.org/assignments/urn-namespaces>).

The entPhysicalUris object may be used to encode for example a URI containing a Common Language Equipment Identifier (CLEI) URI for the managed physical entity. The URN name space for CLEIs is defined in [RFC CLEIURN], and the CLEI format is defined in [T1.213][T1.213a]. For example, an entPhysicalUris instance may have the value of

Expires July 2005

[Page 11]

URN:CLEI:D4CE18B7AA

[RFC2396] and [[RFCCLEIURN](#)] identify this as a URI in the CLEI URN name space, and the specific CLEI code, D4CE18B7AA is based on the example provided in [[T1.213a](#)].

Multiple URIs may be present and are separated by white space characters. Leading and trailing white space characters are ignored.

If no additional identification information is known or supported about the physical entity the object is not instantiated.

[2.12.2.](#) **entityLogical Group**

This group contains a single table to identify logical entities, called the entLogicalTable.

The entLogicalTable contains one row per logical entity. Each row is indexed by an arbitrary, small integer and contains a name, description, and type of the logical entity. It also contains information to allow access to the MIB information for the logical entity. This includes SNMP versions that use a community name (with some form of implied context representation) and SNMP versions that use the SNMP ARCH [[RFC3411](#)] method of context identification.

If a agent represents multiple logical entities with this MIB, then this group must be implemented for all logical entities known to the agent.

If an agent represents a single logical entity, or multiple logical entities within a single naming scope, then implementation of this group may be omitted by the agent.

[2.12.3.](#) **entityMapping Group**

This group contains three tables to identify associations between different system components.

The entLPMappingTable contains mappings between entLogicalIndex values (logical entities) and entPhysicalIndex values (the physical components supporting that entity). A logical entity can map to

Expires July 2005

[Page 12]

more than one physical component, and more than one logical entity can map to (share) the same physical component. If an agent represents a single logical entity, or multiple logical entities within a single naming scope, then implementation of this table may be omitted by the agent. Note that this table is deprecated in version 3 of the Entity MIB.

The entAliasMappingTable contains mappings between entLogicalIndex, entPhysicalIndex pairs and 'alias' object identifier values. This allows resources managed with other MIBs (e.g., repeater ports, bridge ports, physical and logical interfaces) to be identified in the physical entity hierarchy. Note that each alias identifier is only relevant in a particular naming scope. If an agent represents a single logical entity, or multiple logical entities within a single naming scope, then implementation of this table may be omitted by the agent.

The entPhysicalContainsTable contains simple mappings between 'entPhysicalContainedIn' values for each container/'containee' relationship in the managed system. The indexing of this table allows an NMS to quickly discover the 'entPhysicalIndex' values for all children of a given physical entity.

2.12.4. entityGeneral Group

This group contains general information relating to the other object groups.

At this time, the entGeneral group contains a single scalar object (entLastChangeTime), which represents the value of sysUptime when any part of the Entity MIB configuration last changed.

2.12.5. entityNotifications Group

This group contains notification definitions relating to the overall status of the Entity MIB instantiation.

2.13. Multiple Agents

Even though a primary motivation for this MIB is to represent the multiple logical entities supported by a single agent, it is also possible to use it to represent multiple logical entities supported

Expires July 2005

[Page 13]

by multiple agents (in the same "overall" physical entity). Indeed, it is implicit in the SNMP architecture, that the number of agents is transparent to a network management station.

However, there is no agreement at this time as to the degree of cooperation which should be expected for agent implementations. Therefore, multiple agents within the same managed system are free to implement the Entity MIB independently. (Refer the section on "Multiple Instances of the Entity MIB" for more details).

2.14. Changes Since [RFC 2037](#)

2.14.1. Textual Conventions

The PhysicalClass TC text has been clarified, and a new enumeration to support 'stackable' components has been added. The SnmpEngineIdOrNone TC has been added to support SNMPv3.

2.14.2. New entPhysicalTable Objects

The entPhysicalHardwareRev, entPhysicalFirmwareRev, and entPhysicalSoftwareRev objects have been added for revision identification.

The entPhysicalSerialNum, entPhysicalMfgName, entPhysicalModelName, and entPhysicalIsFru objects have been added for better vendor identification for physical components. The entPhysicalSerialNum object can be set by a management station in the event the agent cannot identify this information.

The entPhysicalAlias and entPhysicalAssetID objects have been added for better user component identification. These objects are intended to be set by a management station and preserved by the agent across restarts.

2.14.3. New entLogicalTable Objects

The entLogicalContextEngineID and entLogicalContextName objects have been added to provide an SNMP context for SNMPv3 access on behalf of a logical entity.

Expires July 2005

[Page 14]

2.14.4. Bugfixes

A bug was fixed in the entLogicalCommunity object. The subrange was incorrect (1..255) and is now (0..255). The description clause has also been clarified. This object is now deprecated.

The entLastChangeTime object description has been changed to generalize the events which cause an update to the last change timestamp.

The syntax was changed from DisplayString to SnmpAdminString for the entPhysicalDescr, entPhysicalName, and entLogicalDescr objects.

2.15. Changes Since RFC 2737

2.15.1. Textual Conventions

The PhysicalIndexOrZero TC has been added to allow objects to reference an entPhysicalIndex value or zero. The PhysicalClass TC has been extended to support a new enumeration for central processing units.

2.15.2. New Objects

The entPhysicalMfgDate object has been added to the entPhysicalTable to provide the date of manufacturing of the managed entity.

The entPhysicalUris object has been added to the entPhysicalTable to provide additional identification information about the physical entity, such as a Common Language Equipment Identifier (CLEI) URI.

2.15.3. Bugfixes

The syntax was changed from INTEGER to Integer32 for the entPhysicalParentRelPos, entLogicalIndex, and entAliasLogicalIndexOrZero objects, and from INTEGER to PhysicalIndexOrZero for the entPhysicalContainedIn object.

Expires July 2005

[Page 15]

3. Definitions

ENTITY-MIB DEFINITIONS ::= BEGIN

IMPORTS

MODULE-IDENTITY, OBJECT-TYPE, mib-2, NOTIFICATION-TYPE,
Integer32
FROM SNMPv2-SMI
TDomain, TAddress, TEXTUAL-CONVENTION,
AutonomousType, RowPointer, TimeStamp, TruthValue,
DateAndTime
FROM SNMPv2-TC
MODULE-COMPLIANCE, OBJECT-GROUP, NOTIFICATION-GROUP
FROM SNMPv2-CONF
SnmAdminString
FROM SNMP-FRAMEWORK-MIB;

entityMIB MODULE-IDENTITY

LAST-UPDATED "200501190000Z"
ORGANIZATION "IETF ENTMIB Working Group"
CONTACT-INFO
" WG E-mail: entmib@ietf.org
Mailing list subscription info:
<http://www.ietf.org/mailman/listinfo/entmib>

Andy Bierman
Cisco Systems Inc.
170 West Tasman Drive
San Jose, CA 95134
+1 408-527-3711
abierman@cisco.com

Keith McCloghrie
Cisco Systems Inc.
170 West Tasman Drive
San Jose, CA 95134
+1 408-526-5260
kzm@cisco.com"

DESCRIPTION

"The MIB module for representing multiple logical entities supported by a single SNMP agent."

Copyright (C) The Internet Society (2005). This version of this MIB module is part of RFC xxxx; see

Expires July 2005

[Page 16]

the RFC itself for full legal notices."

-- RFC Ed.: replace xxxx with actual RFC number & remove this notice

REVISION "200501190000Z"

DESCRIPTION

"Initial Version of Entity MIB (Version 3).

This revision obsoletes [RFC 2737](#).

Additions:

- cpu(12) enumeration added to PhysicalClass TC
- DISPLAY-HINT clause to PhysicalIndex TC
- PhysicalIndexOrZero TC
- entPhysicalMfgDate object
- entPhysicalUris object

Changes:

- entPhysicalContainedIn SYNTAX changed from
INTEGER to PhysicalIndexOrZero

This version published as RFC xxxx."

-- RFC Ed.: replace xxxx with actual RFC number & remove this notice

REVISION "199912070000Z"

DESCRIPTION

"Initial Version of Entity MIB (Version 2).

This revision obsoletes [RFC 2037](#).

This version published as [RFC 2737](#)."

REVISION "199610310000Z"

DESCRIPTION

"Initial version (version 1), published as
[RFC 2037](#)."

::= { mib-2 47 }

entityMIBObjects OBJECT IDENTIFIER ::= { entityMIB 1 }

-- MIB contains four groups

entityPhysical OBJECT IDENTIFIER ::= { entityMIBObjects 1 }

entityLogical OBJECT IDENTIFIER ::= { entityMIBObjects 2 }

entityMapping OBJECT IDENTIFIER ::= { entityMIBObjects 3 }

entityGeneral OBJECT IDENTIFIER ::= { entityMIBObjects 4 }

-- Textual Conventions

PhysicalIndex ::= TEXTUAL-CONVENTION

DISPLAY-HINT "d"

STATUS current

Expires July 2005

[Page 17]

DESCRIPTION

"An arbitrary value which uniquely identifies the physical entity. The value should be a small positive integer; index values for different physical entities are not necessarily contiguous."

SYNTAX Integer32 (1..2147483647)

PhysicalIndexOrZero ::= TEXTUAL-CONVENTION

DISPLAY-HINT "d"

STATUS current

DESCRIPTION

"This textual convention is an extension of the PhysicalIndex convention which defines a greater than zero value used to identify a physical entity. This extension permits the additional value of zero. The semantics of the value zero are object-specific and must therefore be defined as part of the description of any object which uses this syntax. Examples of the usage of this extension are situations where none or all physical entities need to be referenced."

SYNTAX Integer32 (0..2147483647)

PhysicalClass ::= TEXTUAL-CONVENTION

STATUS current

DESCRIPTION

"An enumerated value which provides an indication of the general hardware type of a particular physical entity. There are no restrictions as to the number of entPhysicalEntries of each entPhysicalClass, which must be instantiated by an agent.

The enumeration 'other' is applicable if the physical entity class is known, but does not match any of the supported values.

The enumeration 'unknown' is applicable if the physical entity class is unknown to the agent.

The enumeration 'chassis' is applicable if the physical entity class is an overall container for networking equipment. Any class of physical entity except a stack may be contained within a chassis, and a chassis may only be contained within a stack.

The enumeration 'backplane' is applicable if the physical

entity class is some sort of device for aggregating and forwarding networking traffic, such as a shared backplane in a modular ethernet switch. Note that an agent may model a backplane as a single physical entity, which is actually implemented as multiple discrete physical components (within a chassis or stack).

The enumeration 'container' is applicable if the physical entity class is capable of containing one or more removable physical entities, possibly of different types. For example, each (empty or full) slot in a chassis will be modeled as a container. Note that all removable physical entities should be modeled within a container entity, such as field-replaceable modules, fans, or power supplies. Note that all known containers should be modeled by the agent, including empty containers.

The enumeration 'powerSupply' is applicable if the physical entity class is a power-supplying component.

The enumeration 'fan' is applicable if the physical entity class is a fan or other heat-reduction component.

The enumeration 'sensor' is applicable if the physical entity class is some sort of sensor, such as a temperature sensor within a router chassis.

The enumeration 'module' is applicable if the physical entity class is some sort of self-contained sub-system. If it is removable, then it should be modeled within a container entity, otherwise it should be modeled directly within another physical entity (e.g., a chassis or another module).

The enumeration 'port' is applicable if the physical entity class is some sort of networking port, capable of receiving and/or transmitting networking traffic.

The enumeration 'stack' is applicable if the physical entity class is some sort of super-container (possibly virtual), intended to group together multiple chassis entities. A stack may be realized by a 'virtual' cable, a real interconnect cable, attached to multiple chassis, or may in fact be comprised of multiple interconnect cables. A stack should not be modeled within any other physical entities,

Expires July 2005

[Page 19]

but a stack may be contained within another stack. Only chassis entities should be contained within a stack.

The enumeration 'cpu' is applicable if the physical entity class is some sort of central processing unit."

```
SYNTAX      INTEGER {
    other(1),
    unknown(2),
    chassis(3),
    backplane(4),
    container(5),      -- e.g., chassis slot or daughter-card holder
    powerSupply(6),
    fan(7),
    sensor(8),
    module(9),         -- e.g., plug-in card or daughter-card
    port(10),
    stack(11),         -- e.g., stack of multiple chassis entities
    cpu(12)
}
```

SnmpEngineIdOrNone ::= TEXTUAL-CONVENTION

STATUS current

DESCRIPTION

"A specially formatted SnmpEngineID string for use with the Entity MIB.

If an instance of an object of SYNTAX SnmpEngineIdOrNone has a non-zero length, then the object encoding and semantics are defined by the SnmpEngineID textual convention (see STD 62, [RFC 3411](#) [[RFC3411](#)]).

If an instance of an object of SYNTAX SnmpEngineIdOrNone contains a zero-length string, then no appropriate SnmpEngineID is associated with the logical entity (i.e., SNMPv3 not supported)."

SYNTAX OCTET STRING (SIZE(0..32)) -- empty string or SnmpEngineID

-- The Physical Entity Table

entPhysicalTable OBJECT-TYPE

SYNTAX SEQUENCE OF EntPhysicalEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"This table contains one row per physical entity. There is

Expires July 2005

[Page 20]

always at least one row for an 'overall' physical entity."
 ::= { entityPhysical 1 }

entPhysicalEntry OBJECT-TYPE

SYNTAX EntPhysicalEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

 "Information about a particular physical entity.

 Each entry provides objects (entPhysicalDescr,
entPhysicalVendorType, and entPhysicalClass) to help an NMS
identify and characterize the entry, and objects
(entPhysicalContainedIn and entPhysicalParentRelPos) to help
an NMS relate the particular entry to other entries in this
table."

INDEX { entPhysicalIndex }

::= { entPhysicalTable 1 }

EntPhysicalEntry ::= SEQUENCE {

| | |
|-------------------------|----------------------|
| entPhysicalIndex | PhysicalIndex, |
| entPhysicalDescr | SnmpAdminString, |
| entPhysicalVendorType | AutonomousType, |
| entPhysicalContainedIn | PhysicalIndexOrZero, |
| entPhysicalClass | PhysicalClass, |
| entPhysicalParentRelPos | Integer32, |
| entPhysicalName | SnmpAdminString, |
| entPhysicalHardwareRev | SnmpAdminString, |
| entPhysicalFirmwareRev | SnmpAdminString, |
| entPhysicalSoftwareRev | SnmpAdminString, |
| entPhysicalSerialNum | SnmpAdminString, |
| entPhysicalMfgName | SnmpAdminString, |
| entPhysicalModelName | SnmpAdminString, |
| entPhysicalAlias | SnmpAdminString, |
| entPhysicalAssetID | SnmpAdminString, |
| entPhysicalIsFRU | TruthValue, |
| entPhysicalMfgDate | DateAndTime, |
| entPhysicalUris | OCTET STRING |

}

entPhysicalIndex OBJECT-TYPE

SYNTAX PhysicalIndex

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The index for this entry."
 ::= { entPhysicalEntry 1 }

entPhysicalDescr OBJECT-TYPE

SYNTAX SnmpAdminString

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A textual description of physical entity. This object should contain a string which identifies the manufacturer's name for the physical entity, and should be set to a distinct value for each version or model of the physical entity. "

::= { entPhysicalEntry 2 }

entPhysicalVendorType OBJECT-TYPE

SYNTAX AutonomousType

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"An indication of the vendor-specific hardware type of the physical entity. Note that this is different from the definition of MIB-II's sysObjectID.

An agent should set this object to a enterprise-specific registration identifier value indicating the specific equipment type in detail. The associated instance of entPhysicalClass is used to indicate the general type of hardware device.

If no vendor-specific registration identifier exists for this physical entity, or the value is unknown by this agent, then the value { 0 0 } is returned."

::= { entPhysicalEntry 3 }

entPhysicalContainedIn OBJECT-TYPE

SYNTAX PhysicalIndexOrZero

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The value of entPhysicalIndex for the physical entity which 'contains' this physical entity. A value of zero indicates this physical entity is not contained in any other physical entity. Note that the set of 'containment' relationships

Expires July 2005

[Page 22]

define a strict hierarchy; that is, recursion is not allowed.

In the event a physical entity is contained by more than one physical entity (e.g., double-wide modules), this object should identify the containing entity with the lowest value of entPhysicalIndex."

::= { entPhysicalEntry 4 }

entPhysicalClass OBJECT-TYPE

SYNTAX PhysicalClass

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"An indication of the general hardware type of the physical entity.

An agent should set this object to the standard enumeration value which most accurately indicates the general class of the physical entity, or the primary class if there is more than one.

If no appropriate standard registration identifier exists for this physical entity, then the value 'other(1)' is returned. If the value is unknown by this agent, then the value 'unknown(2)' is returned."

::= { entPhysicalEntry 5 }

entPhysicalParentRelPos OBJECT-TYPE

SYNTAX Integer32 (-1..2147483647)

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"An indication of the relative position of this 'child' component among all its 'sibling' components. Sibling components are defined as entPhysicalEntries which share the same instance values of each of the entPhysicalContainedIn and entPhysicalClass objects.

An NMS can use this object to identify the relative ordering for all sibling components of a particular parent (identified by the entPhysicalContainedIn instance in each sibling entry).

This value should match any external labeling of the

physical component if possible. For example, for a container (e.g., card slot) labeled as 'slot #3', entPhysicalParentRelPos should have the value '3'. Note that the entPhysicalEntry for the module plugged in slot 3 should have an entPhysicalParentRelPos value of '1'.

If the physical position of this component does not match any external numbering or clearly visible ordering, then user documentation or other external reference material should be used to determine the parent-relative position. If this is not possible, then the agent should assign a consistent (but possibly arbitrary) ordering to a given set of 'sibling' components, perhaps based on internal representation of the components.

If the agent cannot determine the parent-relative position for some reason, or if the associated value of entPhysicalContainedIn is '0', then the value '-1' is returned. Otherwise a non-negative integer is returned, indicating the parent-relative position of this physical entity.

Parent-relative ordering normally starts from '1' and continues to 'N', where 'N' represents the highest positioned child entity. However, if the physical entities (e.g., slots) are labeled from a starting position of zero, then the first sibling should be associated with a entPhysicalParentRelPos value of '0'. Note that this ordering may be sparse or dense, depending on agent implementation.

The actual values returned are not globally meaningful, as each 'parent' component may use different numbering algorithms. The ordering is only meaningful among siblings of the same parent component.

The agent should retain parent-relative position values across reboots, either through algorithmic assignment or use of non-volatile storage."

::= { entPhysicalEntry 6 }

entPhysicalName OBJECT-TYPE
SYNTAX SnmpAdminString
MAX-ACCESS read-only
STATUS current

Expires July 2005

[Page 24]

DESCRIPTION

"The textual name of the physical entity. The value of this object should be the name of the component as assigned by the local device and should be suitable for use in commands entered at the device's `console'. This might be a text name, such as `console' or a simple component number (e.g., port or module number), such as `1', depending on the physical component naming syntax of the device.

If there is no local name, or this object is otherwise not applicable, then this object contains a zero-length string.

Note that the value of entPhysicalName for two physical entities will be the same in the event that the console interface does not distinguish between them, e.g., slot-1 and the card in slot-1."

::= { entPhysicalEntry 7 }

entPhysicalHardwareRev OBJECT-TYPE

SYNTAX SnmpAdminString

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The vendor-specific hardware revision string for the physical entity. The preferred value is the hardware revision identifier actually printed on the component itself (if present).

Note that if revision information is stored internally in a non-printable (e.g., binary) format, then the agent must convert such information to a printable format, in an implementation-specific manner.

If no specific hardware revision string is associated with the physical component, or this information is unknown to the agent, then this object will contain a zero-length string."

::= { entPhysicalEntry 8 }

entPhysicalFirmwareRev OBJECT-TYPE

SYNTAX SnmpAdminString

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The vendor-specific firmware revision string for the

physical entity.

Note that if revision information is stored internally in a non-printable (e.g., binary) format, then the agent must convert such information to a printable format, in an implementation-specific manner.

If no specific firmware programs are associated with the physical component, or this information is unknown to the agent, then this object will contain a zero-length string."

::= { entPhysicalEntry 9 }

entPhysicalSoftwareRev OBJECT-TYPE

SYNTAX SnmpAdminString

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The vendor-specific software revision string for the physical entity.

Note that if revision information is stored internally in a non-printable (e.g., binary) format, then the agent must convert such information to a printable format, in an implementation-specific manner.

If no specific software programs are associated with the physical component, or this information is unknown to the agent, then this object will contain a zero-length string."

::= { entPhysicalEntry 10 }

entPhysicalSerialNum OBJECT-TYPE

SYNTAX SnmpAdminString (SIZE (0..32))

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"The vendor-specific serial number string for the physical entity. The preferred value is the serial number string actually printed on the component itself (if present).

On the first instantiation of an physical entity, the value of entPhysicalSerialNum associated with that entity is set to the correct vendor-assigned serial number, if this information is available to the agent. If a serial number is unknown or non-existent, the entPhysicalSerialNum will be set to a zero-length string instead.

Expires July 2005

[Page 26]

Note that implementations which can correctly identify the serial numbers of all installed physical entities do not need to provide write access to the entPhysicalSerialNum object. Agents which cannot provide non-volatile storage for the entPhysicalSerialNum strings are not required to implement write access for this object.

Not every physical component will have a serial number, or even need one. Physical entities for which the associated value of the entPhysicalIsFRU object is equal to 'false(2)' (e.g., the repeater ports within a repeater module), do not need their own unique serial number. An agent does not have to provide write access for such entities, and may return a zero-length string.

If write access is implemented for an instance of entPhysicalSerialNum, and a value is written into the instance, the agent must retain the supplied value in the entPhysicalSerialNum instance associated with the same physical entity for as long as that entity remains instantiated. This includes instantiations across all re-initializations/reboots of the network management system, including those which result in a change of the physical entity's entPhysicalIndex value."

```
::= { entPhysicalEntry 11 }
```

entPhysicalMfgName OBJECT-TYPE

SYNTAX SnmpAdminString

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The name of the manufacturer of this physical component.
The preferred value is the manufacturer name string actually
printed on the component itself (if present).

Note that comparisons between instances of the
entPhysicalModelName, entPhysicalFirmwareRev,
entPhysicalSoftwareRev, and the entPhysicalSerialNum
objects, are only meaningful amongst entPhysicalEntries with
the same value of entPhysicalMfgName.

If the manufacturer name string associated with the physical
component is unknown to the agent, then this object will
contain a zero-length string."

```
::= { entPhysicalEntry 12 }
```


entPhysicalModelName OBJECT-TYPE

SYNTAX SnmpAdminString

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The vendor-specific model name identifier string associated with this physical component. The preferred value is the customer-visible part number, which may be printed on the component itself.

If the model name string associated with the physical component is unknown to the agent, then this object will contain a zero-length string."

::= { entPhysicalEntry 13 }

entPhysicalAlias OBJECT-TYPE

SYNTAX SnmpAdminString (SIZE (0..32))

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"This object is an 'alias' name for the physical entity as specified by a network manager, and provides a non-volatile 'handle' for the physical entity.

On the first instantiation of an physical entity, the value of entPhysicalAlias associated with that entity is set to the zero-length string. However, agent may set the value to a locally unique default value, instead of a zero-length string.

If write access is implemented for an instance of entPhysicalAlias, and a value is written into the instance, the agent must retain the supplied value in the entPhysicalAlias instance associated with the same physical entity for as long as that entity remains instantiated. This includes instantiations across all re-initializations/reboots of the network management system, including those which result in a change of the physical entity's entPhysicalIndex value."

::= { entPhysicalEntry 14 }

entPhysicalAssetID OBJECT-TYPE

SYNTAX SnmpAdminString (SIZE (0..32))

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"This object is a user-assigned asset tracking identifier for the physical entity as specified by a network manager, and provides non-volatile storage of this information.

On the first instantiation of an physical entity, the value of entPhysicalAssetID associated with that entity is set to the zero-length string.

Not every physical component will have a asset tracking identifier, or even need one. Physical entities for which the associated value of the entPhysicalIsFRU object is equal to 'false(2)' (e.g., the repeater ports within a repeater module), do not need their own unique asset tracking identifier. An agent does not have to provide write access for such entities, and may instead return a zero-length string.

If write access is implemented for an instance of entPhysicalAssetID, and a value is written into the instance, the agent must retain the supplied value in the entPhysicalAssetID instance associated with the same physical entity for as long as that entity remains instantiated. This includes instantiations across all re-initializations/reboots of the network management system, including those which result in a change of the physical entity's entPhysicalIndex value.

If no asset tracking information is associated with the physical component, then this object will contain a zero-length string."

::= { entPhysicalEntry 15 }

entPhysicalIsFRU OBJECT-TYPE

SYNTAX TruthValue

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"This object indicates whether or not this physical entity is considered a 'field replaceable unit' by the vendor. If this object contains the value 'true(1)' then this entPhysicalEntry identifies a field replaceable unit. For all entPhysicalEntries which represent components that are permanently contained within a field replaceable unit, the value 'false(2)' should be returned for this object."

Expires July 2005

[Page 29]

```
::= { entPhysicalEntry 16 }
```

```
entPhysicalMfgDate OBJECT-TYPE
```

```
    SYNTAX      DateAndTime
```

```
    MAX-ACCESS  read-only
```

```
    STATUS      current
```

```
    DESCRIPTION
```

```
        "This object contains the date of manufacturing of the
        managed entity. If the manufacturing date is unknown or not
        supported the object is not instantiated. The special value
        '0000000000000000'H may also be returned in this case."
```

```
::= { entPhysicalEntry 17 }
```

```
entPhysicalUris OBJECT-TYPE
```

```
    SYNTAX      OCTET STRING
```

```
    MAX-ACCESS  read-write
```

```
    STATUS      current
```

```
    DESCRIPTION
```

```
        "This object contains additional identification information
        about the physical entity. The object contains URIs and
        therefore the syntax of this object must conform to RFC
        2396, section 2."
```

```
        Multiple URIs may be present and are separated by white
        space characters. Leading and trailing white space
        characters are ignored.
```

```
        If no additional identification information is known or
        supported about the physical entity the object is not
        instantiated. A zero length octet string may also be
        returned in this case."
```

```
    REFERENCE
```

```
        "RFC 2396, Uniform Resource Identifiers (URI): Generic
        Syntax, section 2, August 1998."
```

```
::= { entPhysicalEntry 18 }
```

```
--          The Logical Entity Table
```

```
entLogicalTable OBJECT-TYPE
```

```
    SYNTAX      SEQUENCE OF EntLogicalEntry
```

```
    MAX-ACCESS  not-accessible
```

```
    STATUS      current
```

```
    DESCRIPTION
```

```
        "This table contains one row per logical entity. For agents
```


which implement more than one naming scope, at least one entry must exist. Agents which instantiate all MIB objects within a single naming scope are not required to implement this table."

::= { entLogical 1 }

entLogicalEntry OBJECT-TYPE

SYNTAX EntLogicalEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"Information about a particular logical entity. Entities may be managed by this agent or other SNMP agents (possibly) in the same chassis."

INDEX { entLogicalIndex }

::= { entLogicalTable 1 }

EntLogicalEntry ::= SEQUENCE {

entLogicalIndex Integer32,
entLogicalDescr SnmpAdminString,
entLogicalType AutonomousType,
entLogicalCommunity OCTET STRING,
entLogicalTAddress TAddress,
entLogicalTDomain TDomain,
entLogicalContextEngineID SnmpEngineIdOrNone,
entLogicalContextName SnmpAdminString

}

entLogicalIndex OBJECT-TYPE

SYNTAX Integer32 (1..2147483647)

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The value of this object uniquely identifies the logical entity. The value should be a small positive integer; index values for different logical entities are not necessarily contiguous."

::= { entLogicalEntry 1 }

entLogicalDescr OBJECT-TYPE

SYNTAX SnmpAdminString

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A textual description of the logical entity. This object

should contain a string which identifies the manufacturer's name for the logical entity, and should be set to a distinct value for each version of the logical entity. "

::= { entLogicalEntry 2 }

entLogicalType OBJECT-TYPE

SYNTAX AutonomousType

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"An indication of the type of logical entity. This will typically be the OBJECT IDENTIFIER name of the node in the SMI's naming hierarchy which represents the major MIB module, or the majority of the MIB modules, supported by the logical entity. For example:

a logical entity of a regular host/router -> mib-2

a logical entity of a 802.1d bridge -> dot1dBridge

a logical entity of a 802.3 repeater -> snmpDot3RptrMgmt

If an appropriate node in the SMI's naming hierarchy cannot be identified, the value 'mib-2' should be used."

::= { entLogicalEntry 3 }

entLogicalCommunity OBJECT-TYPE

SYNTAX OCTET STRING (SIZE (0..255))

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"An SNMPv1 or SNMPv2C community-string which can be used to access detailed management information for this logical entity. The agent should allow read access with this community string (to an appropriate subset of all managed objects) and may also return a community string based on the privileges of the request used to read this object. Note that an agent may return a community string with read-only privileges, even if this object is accessed with a read-write community string. However, the agent must take care not to return a community string which allows more privileges than the community string used to access this object.

A compliant SNMP agent may wish to conserve naming scopes by representing multiple logical entities in a single 'default' naming scope. This is possible when the logical entities represented by the same value of entLogicalCommunity have no object instances in common. For example, 'bridge1' and

Expires July 2005

[Page 32]

'repeater1' may be part of the main naming scope, but at least one additional community string is needed to represent 'bridge2' and 'repeater2'.

Logical entities 'bridge1' and 'repeater1' would be represented by sysOREntries associated with the 'default' naming scope.

For agents not accessible via SNMPv1 or SNMPv2C, the value of this object is the empty string. This object may also contain an empty string if a community string has not yet been assigned by the agent, or no community string with suitable access rights can be returned for a particular SNMP request.

Note that this object is deprecated. Agents which implement SNMPv3 access should use the entLogicalContextEngineID and entLogicalContextName objects to identify the context associated with each logical entity. SNMPv3 agents may return a zero-length string for this object, or may continue to return a community string (e.g., tri-lingual agent support)."

::= { entLogicalEntry 4 }

entLogicalTAddress OBJECT-TYPE

SYNTAX TAddress

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The transport service address by which the logical entity receives network management traffic, formatted according to the corresponding value of entLogicalTDomain.

For snmpUDPDomain, a TAddress is 6 octets long, the initial 4 octets containing the IP-address in network-byte order and the last 2 containing the UDP port in network-byte order. Consult 'Transport Mappings for the Simple Network Management Protocol' (STD 62, [RFC 3417](#) [[RFC3417](#)]) for further information on snmpUDPDomain."

::= { entLogicalEntry 5 }

entLogicalTDomain OBJECT-TYPE

SYNTAX TDomain

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Indicates the kind of transport service by which the logical entity receives network management traffic. Possible values for this object are presently found in the Transport Mappings for Simple Network Management Protocol' (STD 62, [RFC 3417](#) [[RFC3417](#)])."

::= { entLogicalEntry 6 }

entLogicalContextEngineID OBJECT-TYPE

SYNTAX SnmpEngineIdOrNone

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The authoritative contextEngineID that can be used to send an SNMP message concerning information held by this logical entity, to the address specified by the associated 'entLogicalTAddress/entLogicalTDomain' pair.

This object, together with the associated entLogicalContextName object, defines the context associated with a particular logical entity, and allows access to SNMP engines identified by a contextEngineId and contextName pair.

If no value has been configured by the agent, a zero-length string is returned, or the agent may choose not to instantiate this object at all."

::= { entLogicalEntry 7 }

entLogicalContextName OBJECT-TYPE

SYNTAX SnmpAdminString

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The contextName that can be used to send an SNMP message concerning information held by this logical entity, to the address specified by the associated 'entLogicalTAddress/entLogicalTDomain' pair.

This object, together with the associated entLogicalContextEngineID object, defines the context associated with a particular logical entity, and allows access to SNMP engines identified by a contextEngineId and contextName pair.

If no value has been configured by the agent, a zero-length string is returned, or the agent may choose not to instantiate this object at all."

::= { entLogicalEntry 8 }

entLPMappingTable OBJECT-TYPE

SYNTAX SEQUENCE OF EntLPMappingEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"This table contains zero or more rows of logical entity to physical equipment associations. For each logical entity known by this agent, there are zero or more mappings to the physical resources which are used to realize that logical entity.

An agent should limit the number and nature of entries in this table such that only meaningful and non-redundant information is returned. For example, in a system which contains a single power supply, mappings between logical entities and the power supply are not useful and should not be included.

Also, only the most appropriate physical component which is closest to the root of a particular containment tree should be identified in an entLPMapping entry.

For example, suppose a bridge is realized on a particular module, and all ports on that module are ports on this bridge. A mapping between the bridge and the module would be useful, but additional mappings between the bridge and each of the ports on that module would be redundant (since the entPhysicalContainedIn hierarchy can provide the same information). If, on the other hand, more than one bridge was utilizing ports on this module, then mappings between each bridge and the ports it used would be appropriate.

Also, in the case of a single backplane repeater, a mapping for the backplane to the single repeater entity is not necessary."

::= { entityMapping 1 }

entLPMappingEntry OBJECT-TYPE

SYNTAX EntLPMappingEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"Information about a particular logical entity to physical equipment association. Note that the nature of the association is not specifically identified in this entry. It is expected that sufficient information exists in the MIBs used to manage a particular logical entity to infer how physical component information is utilized."

INDEX { entLogicalIndex, entLPPhysicalIndex }

::= { entLPMappingTable 1 }

EntLPMappingEntry ::= SEQUENCE {
 entLPPhysicalIndex PhysicalIndex
}

entLPPhysicalIndex OBJECT-TYPE

SYNTAX PhysicalIndex

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The value of this object identifies the index value of a particular entPhysicalEntry associated with the indicated entLogicalEntity."

::= { entLPMappingEntry 1 }

-- logical entity/component to alias table

entAliasMappingTable OBJECT-TYPE

SYNTAX SEQUENCE OF EntAliasMappingEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"This table contains zero or more rows, representing mappings of logical entity and physical component to external MIB identifiers. Each physical port in the system may be associated with a mapping to an external identifier, which itself is associated with a particular logical entity's naming scope. A 'wildcard' mechanism is provided to indicate that an identifier is associated with more than one logical entity."

::= { entityMapping 2 }

entAliasMappingEntry OBJECT-TYPE

SYNTAX EntAliasMappingEntry

MAX-ACCESS not-accessible

Expires July 2005

[Page 36]

STATUS current

DESCRIPTION

"Information about a particular physical equipment, logical entity to external identifier binding. Each logical entity/physical component pair may be associated with one alias mapping. The logical entity index may also be used as a 'wildcard' (refer to the entAliasLogicalIndexOrZero object DESCRIPTION clause for details.)

Note that only entPhysicalIndex values which represent physical ports (i.e. associated entPhysicalClass value is 'port(10)') are permitted to exist in this table."

INDEX { entPhysicalIndex, entAliasLogicalIndexOrZero }

::= { entAliasMappingTable 1 }

```
EntAliasMappingEntry ::= SEQUENCE {  
    entAliasLogicalIndexOrZero      Integer32,  
    entAliasMappingIdentifier       RowPointer  
}
```

entAliasLogicalIndexOrZero OBJECT-TYPE

SYNTAX Integer32 (0..2147483647)

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The value of this object identifies the logical entity which defines the naming scope for the associated instance of the 'entAliasMappingIdentifier' object.

If this object has a non-zero value, then it identifies the logical entity named by the same value of entLogicalIndex.

If this object has a value of zero, then the mapping between the physical component and the alias identifier for this entAliasMapping entry is associated with all unspecified logical entities. That is, a value of zero (the default mapping) identifies any logical entity which does not have an explicit entry in this table for a particular entPhysicalIndex/entAliasMappingIdentifier pair.

For example, to indicate that a particular interface (e.g., physical component 33) is identified by the same value of ifIndex for all logical entities, the following instance might exist:


```
entAliasMappingIdentifier.33.0 = ifIndex.5
```

In the event an entPhysicalEntry is associated differently for some logical entities, additional entAliasMapping entries may exist, e.g.:

```
entAliasMappingIdentifier.33.0 = ifIndex.6
entAliasMappingIdentifier.33.4 = ifIndex.1
entAliasMappingIdentifier.33.5 = ifIndex.1
entAliasMappingIdentifier.33.10 = ifIndex.12
```

Note that entries with non-zero entAliasLogicalIndexOrZero index values have precedence over any zero-indexed entry. In this example, all logical entities except 4, 5, and 10, associate physical entity 33 with ifIndex.6."

```
::= { entAliasMappingEntry 1 }
```

entAliasMappingIdentifier OBJECT-TYPE

SYNTAX RowPointer

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The value of this object identifies a particular conceptual row associated with the indicated entPhysicalIndex and entLogicalIndex pair.

Since only physical ports are modeled in this table, only entries which represent interfaces or ports are allowed. If an ifEntry exists on behalf of a particular physical port, then this object should identify the associated 'ifEntry'. For repeater ports, the appropriate row in the 'rptrPortGroupTable' should be identified instead.

For example, suppose a physical port was represented by entPhysicalEntry.3, entLogicalEntry.15 existed for a repeater, and entLogicalEntry.22 existed for a bridge. Then there might be two related instances of entAliasMappingIdentifier:

```
entAliasMappingIdentifier.3.15 == rptrPortGroupIndex.5.2
entAliasMappingIdentifier.3.22 == ifIndex.17
```

It is possible that other mappings (besides interfaces and repeater ports) may be defined in the future, as required.

Bridge ports are identified by examining the Bridge MIB and appropriate ifEntries associated with each 'dot1dBasePort',

and are thus not represented in this table."
 ::= { entAliasMappingEntry 2 }

-- physical mapping table

entPhysicalContainsTable OBJECT-TYPE

SYNTAX SEQUENCE OF EntPhysicalContainsEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"A table which exposes the container/'containeer'
relationships between physical entities. This table provides
all the information found by constructing the virtual
containment tree for a given entPhysicalTable, but in a more
direct format.

In the event a physical entity is contained by more than one
other physical entity (e.g., double-wide modules), this
table should include these additional mappings, which cannot
be represented in the entPhysicalTable virtual containment
tree."

::= { entityMapping 3 }

entPhysicalContainsEntry OBJECT-TYPE

SYNTAX EntPhysicalContainsEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"A single container/'containeer' relationship."

INDEX { entPhysicalIndex, entPhysicalChildIndex }

::= { entPhysicalContainsTable 1 }

EntPhysicalContainsEntry ::= SEQUENCE {
 entPhysicalChildIndex PhysicalIndex
 }

entPhysicalChildIndex OBJECT-TYPE

SYNTAX PhysicalIndex

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The value of entPhysicalIndex for the contained physical
entity."

::= { entPhysicalContainsEntry 1 }


```
-- last change time stamp for the whole MIB
entLastChangeTime OBJECT-TYPE
    SYNTAX      TimeStamp
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The value of sysUpTime at the time a conceptual row is
        created, modified, or deleted in any of these tables:
            - entPhysicalTable
            - entLogicalTable
            - entLPMappingTable
            - entAliasMappingTable
            - entPhysicalContainsTable
        "
    ::= { entityGeneral 1 }
```

```
-- Entity MIB Trap Definitions
entityMIBTraps      OBJECT IDENTIFIER ::= { entityMIB 2 }
entityMIBTrapPrefix OBJECT IDENTIFIER ::= { entityMIBTraps 0 }
```

```
entConfigChange NOTIFICATION-TYPE
    STATUS      current
    DESCRIPTION
        "An entConfigChange notification is generated when the value
        of entLastChangeTime changes. It can be utilized by an NMS
        to trigger logical/physical entity table maintenance polls.

        An agent should not generate more than one entConfigChange
        'notification-event' in a given time interval (five seconds
        is the suggested default). A 'notification-event' is the
        transmission of a single trap or inform PDU to a list of
        notification destinations.

        If additional configuration changes occur within the
        throttling period, then notification-events for these
        changes should be suppressed by the agent until the current
        throttling period expires. At the end of a throttling
        period, one notification-event should be generated if any
        configuration changes occurred since the start of the
        throttling period. In such a case, another throttling period
        is started right away.

        An NMS should periodically check the value of
        entLastChangeTime to detect any missed entConfigChange
```



```
        notification-events, e.g., due to throttling or transmission
        loss."
 ::= { entityMIBTrapPrefix 1 }

-- conformance information
entityConformance OBJECT IDENTIFIER ::= { entityMIB 3 }

entityCompliances OBJECT IDENTIFIER ::= { entityConformance 1 }
entityGroups      OBJECT IDENTIFIER ::= { entityConformance 2 }

-- compliance statements
entityCompliance MODULE-COMPLIANCE
    STATUS deprecated
    DESCRIPTION
        "The compliance statement for SNMP entities which implement
        version 1 of the Entity MIB."
    MODULE -- this module
        MANDATORY-GROUPS {
            entityPhysicalGroup,
            entityLogicalGroup,
            entityMappingGroup,
            entityGeneralGroup,
            entityNotificationsGroup
        }
    ::= { entityCompliances 1 }

entity2Compliance MODULE-COMPLIANCE
    STATUS deprecated
    DESCRIPTION
        "The compliance statement for SNMP entities which implement
        version 2 of the Entity MIB."
    MODULE -- this module
        MANDATORY-GROUPS {
            entityPhysicalGroup,
            entityPhysical2Group,
            entityGeneralGroup,
            entityNotificationsGroup
        }
    GROUP entityLogical2Group
    DESCRIPTION
        "Implementation of this group is not mandatory for agents
        which model all MIB object instances within a single naming
        scope."
```


GROUP entityMappingGroup

DESCRIPTION

"Implementation of the entPhysicalContainsTable is mandatory for all agents. Implementation of the entLPMappingTable and entAliasMappingTables are not mandatory for agents which model all MIB object instances within a single naming scope.

Note that the entAliasMappingTable may be useful for all agents, however implementation of the entityLogicalGroup or entityLogical2Group is required to support this table."

OBJECT entPhysicalSerialNum

MIN-ACCESS not-accessible

DESCRIPTION

"Read and write access is not required for agents which cannot identify serial number information for physical entities, and/or cannot provide non-volatile storage for NMS-assigned serial numbers.

Write access is not required for agents which can identify serial number information for physical entities, but cannot provide non-volatile storage for NMS-assigned serial numbers.

Write access is not required for physical entities for physical entities for which the associated value of the entPhysicalIsFRU object is equal to 'false(2)'."

OBJECT entPhysicalAlias

MIN-ACCESS read-only

DESCRIPTION

"Write access is required only if the associated entPhysicalClass value is equal to 'chassis(3)'."

OBJECT entPhysicalAssetID

MIN-ACCESS not-accessible

DESCRIPTION

"Read and write access is not required for agents which cannot provide non-volatile storage for NMS-assigned asset identifiers.

Write access is not required for physical entities for which the associated value of entPhysicalIsFRU is equal to 'false(2)'."

OBJECT entPhysicalClass

SYNTAX INTEGER {

other(1),
unknown(2),
chassis(3),
backplane(4),
container(5),
powerSupply(6),
fan(7),
sensor(8),
module(9),
port(10),
stack(11)

}

DESCRIPTION

"Implementation of the 'cpu(12)' enumeration is not required."

::= { entityCompliances 2 }

entity3Compliance MODULE-COMPLIANCE

STATUS current

DESCRIPTION

"The compliance statement for SNMP entities which implement version 3 of the Entity MIB."

MODULE -- this module

MANDATORY-GROUPS {

entityPhysicalGroup,
entityPhysical2Group,
entityPhysical3Group,
entityGeneralGroup,
entityNotificationsGroup

}

GROUP entityLogical2Group

DESCRIPTION

"Implementation of this group is not mandatory for agents which model all MIB object instances within a single naming scope."

GROUP entityMappingGroup

DESCRIPTION

"Implementation of the entPhysicalContainsTable is mandatory for all agents. Implementation of the entLPMappingTable and entAliasMappingTables are not mandatory for agents which

model all MIB object instances within a single naming scope.

Note that the entAliasMappingTable may be useful for all agents, however implementation of the entityLogicalGroup or entityLogical2Group is required to support this table."

OBJECT entPhysicalSerialNum
MIN-ACCESS not-accessible
DESCRIPTION

"Read and write access is not required for agents which cannot identify serial number information for physical entities, and/or cannot provide non-volatile storage for NMS-assigned serial numbers.

Write access is not required for agents which can identify serial number information for physical entities, but cannot provide non-volatile storage for NMS-assigned serial numbers.

Write access is not required for physical entities for physical entities for which the associated value of the entPhysicalIsFRU object is equal to 'false(2)'."

OBJECT entPhysicalAlias
MIN-ACCESS read-only
DESCRIPTION

"Write access is required only if the associated entPhysicalClass value is equal to 'chassis(3)'."

OBJECT entPhysicalAssetID
MIN-ACCESS not-accessible
DESCRIPTION

"Read and write access is not required for agents which cannot provide non-volatile storage for NMS-assigned asset identifiers.

Write access is not required for physical entities for which the associated value of entPhysicalIsFRU is equal to 'false(2)'."

::= { entityCompliances 3 }

-- MIB groupings
entityPhysicalGroup OBJECT-GROUP
 OBJECTS {

Expires July 2005

[Page 44]

```
        entPhysicalDescr,
        entPhysicalVendorType,
        entPhysicalContainedIn,
        entPhysicalClass,
        entPhysicalParentRelPos,
        entPhysicalName
    }
    STATUS current
    DESCRIPTION
        "The collection of objects which are used to represent
        physical system components, for which a single agent
        provides management information."
    ::= { entityGroups 1 }

entityLogicalGroup      OBJECT-GROUP
    OBJECTS {
        entLogicalDescr,
        entLogicalType,
        entLogicalCommunity,
        entLogicalTAddress,
        entLogicalTDomain
    }
    STATUS deprecated
    DESCRIPTION
        "The collection of objects which are used to represent the
        list of logical entities for which a single agent provides
        management information."
    ::= { entityGroups 2 }

entityMappingGroup      OBJECT-GROUP
    OBJECTS {
        entLPPhysicalIndex,
        entAliasMappingIdentifier,
        entPhysicalChildIndex
    }
    STATUS current
    DESCRIPTION
        "The collection of objects which are used to represent the
        associations between multiple logical entities, physical
        components, interfaces, and port identifiers for which a
        single agent provides management information."
    ::= { entityGroups 3 }

entityGeneralGroup      OBJECT-GROUP
    OBJECTS {
```


Expires July 2005

[Page 45]

```
        entLastChangeTime
    }
    STATUS    current
    DESCRIPTION
        "The collection of objects which are used to represent
        general entity information for which a single agent provides
        management information."
    ::= { entityGroups 4 }
```

```
entityNotificationsGroup NOTIFICATION-GROUP
    NOTIFICATIONS { entConfigChange }
    STATUS        current
    DESCRIPTION
        "The collection of notifications used to indicate Entity MIB
        data consistency and general status information."
    ::= { entityGroups 5 }
```

```
entityPhysical2Group      OBJECT-GROUP
    OBJECTS {
        entPhysicalHardwareRev,
        entPhysicalFirmwareRev,
        entPhysicalSoftwareRev,
        entPhysicalSerialNum,
        entPhysicalMfgName,
        entPhysicalModelName,
        entPhysicalAlias,
        entPhysicalAssetID,
        entPhysicalIsFRU
    }
    STATUS    current
    DESCRIPTION
        "The collection of objects which are used to represent
        physical system components, for which a single agent
        provides management information.  This group augments the
        objects contained in the entityPhysicalGroup."
    ::= { entityGroups 6 }
```

```
entityLogical2Group      OBJECT-GROUP
    OBJECTS {
        entLogicalDescr,
        entLogicalType,
        entLogicalTAddress,
        entLogicalTDomain,
        entLogicalContextEngineID,
        entLogicalContextName
    }
```

Expires July 2005

[Page 46]

```
    }
    STATUS current
    DESCRIPTION
        "The collection of objects which are used to represent the
        list of logical entities for which a single SNMP entity
        provides management information."
    ::= { entityGroups 7 }

entityPhysical3Group    OBJECT-GROUP
    OBJECTS {
        entPhysicalMfgDate,
        entPhysicalUris
    }
    STATUS current
    DESCRIPTION
        "The collection of objects which are used to represent
        physical system components, for which a single agent
        provides management information.  This group augments the
        objects contained in the entityPhysicalGroup."
    ::= { entityGroups 8 }
```

END

4. Usage Examples

The following sections iterate the instance values for two example networking devices. These examples are kept simple to make them more understandable. Auxiliary components, such as fans, sensors, empty slots, and sub-modules are not shown, but might be modeled in real implementations.

4.1. Router/Bridge

A router containing two slots. Each slot contains a 3 port router/bridge module. Each port is represented in the ifTable. There are two logical instances of OSPF running and two logical bridges:

Physical entities -- entPhysicalTable:

1 Field-replaceable physical chassis:

```
entPhysicalDescr.1 ==      'Acme Chassis Model 100'
entPhysicalVendorType.1 == acmeProducts.chassisTypes.1
entPhysicalContainedIn.1 == 0
entPhysicalClass.1 ==      chassis(3)
entPhysicalParentRelPos.1 == 0
entPhysicalName.1 ==       '100-A'
entPhysicalHardwareRev.1 == 'A(1.00.02)'
entPhysicalSoftwareRev.1 == ''
entPhysicalFirmwareRev.1 == ''
entPhysicalSerialNum.1 ==   'C100076544'
entPhysicalMfgName.1 ==     'Acme'
entPhysicalModelName.1 ==   '100'
entPhysicalAlias.1 ==       'cl-SJ17-3-006:rack1:rtr-U3'
entPhysicalAssetID.1 ==     '0007372293'
entPhysicalIsFRU.1 ==       true(1)
entPhysicalMfgDate.1 ==     '2002-5-26,13:30:30.0,-4:0'
entPhysicalUris.1 ==        'URN:CLEI:CNME120ARA'
```

2 slots within the chassis:

```
entPhysicalDescr.2 ==      'Acme Chassis Slot Type AA'
entPhysicalVendorType.2 == acmeProducts.slotTypes.1
entPhysicalContainedIn.2 == 1
entPhysicalClass.2 ==      container(5)
entPhysicalParentRelPos.2 == 1
entPhysicalName.2 ==       'S1'
entPhysicalHardwareRev.2 == 'B(1.00.01)'
entPhysicalSoftwareRev.2 == ''
entPhysicalFirmwareRev.2 == ''
entPhysicalSerialNum.2 ==   ''
```



```
entPhysicalMfgName.2 ==      'Acme'
entPhysicalModelName.2 ==    'AA'
entPhysicalAlias.2 ==        ''
entPhysicalAssetID.2 ==      ''
entPhysicalIsFRU.2 ==        false(2)
entPhysicalMfgDate.2 ==      '2002-7-26,12:22:12.0,-4:0'
entPhysicalUris.2 ==         'URN:CLEI:CNME123ARA'

entPhysicalDescr.3 ==        'Acme Chassis Slot Type AA'
entPhysicalVendorType.3 =    acmeProducts.slotTypes.1
entPhysicalContainedIn.3 ==   1
entPhysicalClass.3 ==        container(5)
entPhysicalParentRelPos.3 ==  2
entPhysicalName.3 ==         'S2'
entPhysicalHardwareRev.3 ==   '1.00.07'
entPhysicalSoftwareRev.3 ==   ''
entPhysicalFirmwareRev.3 ==   ''
entPhysicalSerialNum.3 ==     ''
entPhysicalMfgName.3 ==      'Acme'
entPhysicalModelName.3 ==     'AA'
entPhysicalAlias.3 ==        ''
entPhysicalAssetID.3 ==      ''
entPhysicalIsFRU.3 ==        false(2)
entPhysicalMfgDate.3 ==      '2002-7-26,12:12:12.0,-4:0'
entPhysicalUris.3 ==         'URN:CLEI:CNME123ARA'
```

2 Field-replaceable modules:

Slot 1 contains a module with 3 ports:

```
entPhysicalDescr.4 ==        'Acme Router-100'
entPhysicalVendorType.4 ==    acmeProducts.moduleTypes.14
entPhysicalContainedIn.4 ==    2
entPhysicalClass.4 ==        module(9)
entPhysicalParentRelPos.4 ==  1
entPhysicalName.4 ==         'M1'
entPhysicalHardwareRev.4 ==   '1.00.07'
entPhysicalSoftwareRev.4 ==   '1.4.1'
entPhysicalFirmwareRev.4 ==   'A(1.1)'
entPhysicalSerialNum.4 ==     'C100087363'
entPhysicalMfgName.4 ==      'Acme'
entPhysicalModelName.4 ==     'R100-FE'
entPhysicalAlias.4 ==        'rtr-U3:m1:SJ17-3-eng'
entPhysicalAssetID.4 ==      '0007372462'
entPhysicalIsFRU.4 ==        true(1)
entPhysicalMfgDate.4 ==      '2003-7-18,13:30:30.0,-4:0'
entPhysicalUris.4 ==         'URN:CLEI:CNRU123CAA'
```


Expires July 2005

[Page 49]

```
entPhysicalDescr.5 ==      'Acme Ethernet-100 Port'
entPhysicalVendorType.5 == acmeProducts.portTypes.2
entPhysicalContainedIn.5 == 4
entPhysicalClass.5 ==      port(10)
entPhysicalParentRelPos.5 == 1
entPhysicalName.5 ==        'P1'
entPhysicalHardwareRev.5 == 'G(1.02)'
entPhysicalSoftwareRev.5 == ''
entPhysicalFirmwareRev.5 == '1.1'
entPhysicalSerialNum.5 ==   ''
entPhysicalMfgName.5 ==     'Acme'
entPhysicalModelName.5 ==   'FE-100'
entPhysicalAlias.5 ==        ''
entPhysicalAssetID.5 ==      ''
entPhysicalIsFRU.5 ==        false(2)
entPhysicalMfgDate.5 ==      '2003-7-18,14:20:22.0,-4:0'
entPhysicalUris.5 ==         'URN:CLEI:CNMES23ARA'

entPhysicalDescr.6 ==      'Acme Ethernet-100 Port'
entPhysicalVendorType.6 == acmeProducts.portTypes.2
entPhysicalContainedIn.6 == 4
entPhysicalClass.6 ==      port(10)
entPhysicalParentRelPos.6 == 2
entPhysicalName.6 ==        'P2'
entPhysicalHardwareRev.6 == 'G(1.02)'
entPhysicalSoftwareRev.6 == ''
entPhysicalFirmwareRev.6 == '1.1'
entPhysicalSerialNum.6 ==   ''
entPhysicalMfgName.6 ==     'Acme'
entPhysicalModelName.6 ==   'FE-100'
entPhysicalAlias.6 ==        ''
entPhysicalAssetID.6 ==      ''
entPhysicalIsFRU.6 ==        false(2)
entPhysicalMfgDate.6 ==      '2003-7-19,10:15:15.0,-4:0'
entPhysicalUris.6 ==         'URN:CLEI:CNMES23ARA'

entPhysicalDescr.7 ==      'Acme Router-100 FDDI-Port'
entPhysicalVendorType.7 == acmeProducts.portTypes.3
entPhysicalContainedIn.7 == 4
entPhysicalClass.7 ==      port(10)
entPhysicalParentRelPos.7 == 3
entPhysicalName.7 ==        'P3'
entPhysicalHardwareRev.7 == 'B(1.03)'
entPhysicalSoftwareRev.7 == '2.5.1'
entPhysicalFirmwareRev.7 == '2.5F'
```

Expires July 2005

[Page 50]

```
entPhysicalSerialNum.7 ==      ''
entPhysicalMfgName.7 ==       'Acme'
entPhysicalModelName.7 ==     'FDDI-100'
entPhysicalAlias.7 ==         ''
entPhysicalAssetID.7 ==       ''
entPhysicalIsFRU.7 ==         false(2)
```

Slot 2 contains another 3-port module:

```
entPhysicalDescr.8 ==         'Acme Router-100 Comm Module'
entPhysicalVendorType.8 ==    acmeProducts.moduleTypes.15
entPhysicalContainedIn.8 ==    3
entPhysicalClass.8 ==         module(9)
entPhysicalParentRelPos.8 ==  1
entPhysicalName.8 ==          'M2'
entPhysicalHardwareRev.8 ==   '2.01.00'
entPhysicalSoftwareRev.8 ==   '3.0.7'
entPhysicalFirmwareRev.8 ==   'A(1.2)'
entPhysicalSerialNum.8 ==     'C100098732'
entPhysicalMfgName.8 ==       'Acme'
entPhysicalModelName.8 ==     'C100'
entPhysicalAlias.8 ==         'rtr-U3:m2:SJ17-2-eng'
entPhysicalAssetID.8 ==       '0007373982'
entPhysicalIsFRU.8 ==         true(1)
entPhysicalMfgDate.8 ==       '2002-5-26,13:30:15.0,-4:0'
entPhysicalUris.8 ==          'URN:CLEI:CNRT321MAA'
```

```
entPhysicalDescr.9 ==         'Acme Fddi-100 Port'
entPhysicalVendorType.9 ==    acmeProducts.portTypes.5
entPhysicalContainedIn.9 ==    8
entPhysicalClass.9 ==         port(10)
entPhysicalParentRelPos.9 ==  1
entPhysicalName.9 ==          'FDDI Primary'
entPhysicalHardwareRev.9 ==   'CC(1.07)'
entPhysicalSoftwareRev.9 ==   '2.0.34'
entPhysicalFirmwareRev.9 ==   '1.1'
entPhysicalSerialNum.9 ==     ''
entPhysicalMfgName.9 ==       'Acme'
entPhysicalModelName.9 ==     'FDDI-100'
entPhysicalAlias.9 ==         ''
entPhysicalAssetID.9 ==       ''
entPhysicalIsFRU.9 ==         false(2)
```

```
entPhysicalDescr.10 ==        'Acme Ethernet-100 Port'
entPhysicalVendorType.10 ==    acmeProducts.portTypes.2
entPhysicalContainedIn.10 ==    8
```

Expires July 2005

[Page 51]

```
entPhysicalClass.10 ==      port(10)
entPhysicalParentRelPos.10 == 2
entPhysicalName.10 ==      'Ethernet A'
entPhysicalHardwareRev.10 == 'G(1.04)'
entPhysicalSoftwareRev.10 == ''
entPhysicalFirmwareRev.10 == '1.3'
entPhysicalSerialNum.10 ==  ''
entPhysicalMfgName.10 ==    'Acme'
entPhysicalModelName.10 ==  'FE-100'
entPhysicalAlias.10 ==     ''
entPhysicalAssetID.10 ==   ''
entPhysicalIsFRU.10 ==     false(2)
entPhysicalMfgDate.10 ==   '2002-7-26,13:30:15.0,-4:0'
entPhysicalUris.10 ==      'URN:CLEI:CNMES23ARA'
```

```
entPhysicalDescr.11 ==      'Acme Ethernet-100 Port'
entPhysicalVendorType.11 ==  acmeProducts.portTypes.2
entPhysicalContainedIn.11 == 8
entPhysicalClass.11 ==      port(10)
entPhysicalParentRelPos.11 == 3
entPhysicalName.11 ==      'Ethernet B'
entPhysicalHardwareRev.11 == 'G(1.04)'
entPhysicalSoftwareRev.11 == ''
entPhysicalFirmwareRev.11 == '1.3'
entPhysicalSerialNum.11 ==  ''
entPhysicalMfgName.11 ==    'Acme'
entPhysicalModelName.11 ==  'FE-100'
entPhysicalAlias.11 ==     ''
entPhysicalAssetID.11 ==   ''
entPhysicalIsFRU.11 ==     false(2)
entPhysicalMfgDate.11 ==   '2002-8-16,15:35:15.0,-4:0'
entPhysicalUris.11 ==      'URN:CLEI:CNMES23ARA'
```

Logical entities -- entLogicalTable; no SNMPv3 support

2 OSPF instances:

```
entLogicalDescr.1 ==      'Acme OSPF v1.1'
entLogicalType.1 ==       ospf
entLogicalCommunity.1 ==  'public-ospf1'
entLogicalTAddress.1 ==   124.125.126.127:161
entLogicalTDomain.1 ==    snmpUDPDomain
entLogicalContextEngineID.1 == ''
entLogicalContextName.1 == ''

entLogicalDescr.2 ==      'Acme OSPF v1.1'
entLogicalType.2 ==       ospf
```

Expires July 2005

[Page 52]

```
entLogicalCommunity.2 ==      'public-ospf2'
entLogicalTAddress.2 ==      124.125.126.127:161
entLogicalTDomain.2 ==       snmpUDPDomain
entLogicalContextEngineID.2 == ''
entLogicalContextName.2 ==   ''
```

2 logical bridges:

```
entLogicalDescr.3 ==          'Acme Bridge v2.1.1'
entLogicalType.3 ==           dot1dBridge
entLogicalCommunity.3 ==      'public-bridge1'
entLogicalTAddress.3 ==      124.125.126.127:161
entLogicalTDomain.3 ==       snmpUDPDomain
entLogicalContextEngineID.3 == ''
entLogicalContextName.3 ==   ''
```

```
entLogicalDescr.4 ==          'Acme Bridge v2.1.1'
entLogicalType.4 ==           dot1dBridge
entLogicalCommunity.4 ==      'public-bridge2'
entLogicalTAddress.4 ==      124.125.126.127:161
entLogicalTDomain.4 ==       snmpUDPDomain
entLogicalContextEngineID.4 == ''
entLogicalContextName.4 ==   ''
```

Logical to Physical Mappings:

1st OSPF instance: uses module 1-port 1

```
entLPPhysicalIndex.1.5 ==      5
```

2nd OSPF instance: uses module 2-port 1

```
entLPPhysicalIndex.2.9 ==      9
```

1st bridge group: uses module 1, all ports

[ed. -- Note that these mappings are included in the table since another logical entity (1st OSPF) utilizes one of the ports. If this were not the case, then a single mapping to the module (e.g., entLPPhysicalIndex.3.4) would be present instead.]

```
entLPPhysicalIndex.3.5 ==      5
entLPPhysicalIndex.3.6 ==      6
entLPPhysicalIndex.3.7 ==      7
```

2nd bridge group: uses module 2, all ports

```
entLPPhysicalIndex.4.9 ==      9
entLPPhysicalIndex.4.10 ==     10
entLPPhysicalIndex.4.11 ==     11
```


Physical to Logical to MIB Alias Mappings -- entAliasMappingTable:

Example 1: ifIndex values are global to all logical entities

```
entAliasMappingIdentifier.5.0 == ifIndex.1
entAliasMappingIdentifier.6.0 == ifIndex.2
entAliasMappingIdentifier.7.0 == ifIndex.3
entAliasMappingIdentifier.9.0 == ifIndex.4
entAliasMappingIdentifier.10.0 == ifIndex.5
entAliasMappingIdentifier.11.0 == ifIndex.6
```

Example 2: ifIndex values are not shared by all logical entities

```
entAliasMappingIdentifier.5.0 == ifIndex.1
entAliasMappingIdentifier.5.3 == ifIndex.101
entAliasMappingIdentifier.6.0 == ifIndex.2
entAliasMappingIdentifier.6.3 == ifIndex.102
entAliasMappingIdentifier.7.0 == ifIndex.3
entAliasMappingIdentifier.7.3 == ifIndex.103
entAliasMappingIdentifier.9.0 == ifIndex.4
entAliasMappingIdentifier.9.3 == ifIndex.204
entAliasMappingIdentifier.10.0 == ifIndex.5
entAliasMappingIdentifier.10.3 == ifIndex.205
entAliasMappingIdentifier.11.0 == ifIndex.6
entAliasMappingIdentifier.11.3 == ifIndex.206
```

Physical Containment Tree -- entPhysicalContainsTable

chassis has two containers:

```
entPhysicalChildIndex.1.2 == 2
entPhysicalChildIndex.1.3 == 3
```

container 1 has a module:

```
entPhysicalChildIndex.2.4 == 4
```

container 2 has a module:

```
entPhysicalChildIndex.3.8 == 8
```

module 1 has 3 ports:

```
entPhysicalChildIndex.4.5 == 5
entPhysicalChildIndex.4.6 == 6
entPhysicalChildIndex.4.7 == 7
```

module 2 has 3 ports:

```
entPhysicalChildIndex.8.9 == 9
entPhysicalChildIndex.8.10 == 10
entPhysicalChildIndex.1.11 == 11
```


4.2. Repeaters

A 3-slot Hub with 2 backplane ethernet segments. Slot three is empty, and the remaining slots contain ethernet repeater modules.

Note that this example assumes an older Repeater MIB implementation, ([RFC 1516](#) [[RFC1516](#)]) rather than the new Repeater MIB ([RFC 2108](#) [[RFC2108](#)]). The new version contains an object called 'rpTrPortRpTrId', which should be used to identify repeater port groupings, rather than with community strings or contexts.

Physical entities -- entPhysicalTable:

1 Field-replaceable physical chassis:

```
entPhysicalDescr.1 ==      'Acme Chassis Model 110'
entPhysicalVendorType.1 == acmeProducts.chassisTypes.2
entPhysicalContainedIn.1 == 0
entPhysicalClass.1 ==      chassis(3)
entPhysicalParentRelPos.1 == 0
entPhysicalName.1 ==        '110-B'
entPhysicalHardwareRev.1 == 'A(1.02.00)'
entPhysicalSoftwareRev.1 == ''
entPhysicalFirmwareRev.1 == ''
entPhysicalSerialNum.1 ==   'C100079294'
entPhysicalMfgName.1 ==     'Acme'
entPhysicalModelName.1 ==   '110'
entPhysicalAlias.1 ==       'bldg09:floor1:rpTr18:0067eea0229f'
entPhysicalAssetID.1 ==     '0007386327'
entPhysicalIsFRU.1 ==       true(1)
```

2 Chassis Ethernet Backplanes:

```
entPhysicalDescr.2 ==      'Acme Ethernet Backplane Type A'
entPhysicalVendorType.2 == acmeProducts.backplaneTypes.1
entPhysicalContainedIn.2 == 1
entPhysicalClass.2 ==      backplane(4)
entPhysicalParentRelPos.2 == 1
entPhysicalName.2 ==        'B1'
entPhysicalHardwareRev.2 == 'A(2.04.01)'
entPhysicalSoftwareRev.2 == ''
entPhysicalFirmwareRev.2 == ''
entPhysicalSerialNum.2 ==   ''
entPhysicalMfgName.2 ==     'Acme'
entPhysicalModelName.2 ==   'BK-A'
entPhysicalAlias.2 ==       ''
entPhysicalAssetID.2 ==     ''
entPhysicalIsFRU.2 ==       false(2)
```



```
entPhysicalDescr.3 ==      'Acme Ethernet Backplane Type A'
entPhysicalVendorType.3 == acmeProducts.backplaneTypes.1
entPhysicalContainedIn.3 == 1
entPhysicalClass.3 ==      backplane(4)
entPhysicalParentRelPos.3 == 2
entPhysicalName.3 ==       'B2'
entPhysicalHardwareRev.3 == 'A(2.04.01)'
entPhysicalSoftwareRev.3 == ''
entPhysicalFirmwareRev.3 == ''
entPhysicalSerialNum.3 ==  ''
entPhysicalMfgName.3 ==    'Acme'
entPhysicalModelName.3 ==  'BK-A'
entPhysicalAlias.3 ==      ''
entPhysicalAssetID.3 ==    ''
entPhysicalIsFRU.3 ==      false(2)
```

3 slots within the chassis:

```
entPhysicalDescr.4 ==      'Acme Hub Slot Type RB'
entPhysicalVendorType.4 == acmeProducts.slotTypes.5
entPhysicalContainedIn.4 == 1
entPhysicalClass.4 ==      container(5)
entPhysicalParentRelPos.4 == 1
entPhysicalName.4 ==       'Slot 1'
entPhysicalHardwareRev.4 == 'B(1.00.03)'
entPhysicalSoftwareRev.4 == ''
entPhysicalFirmwareRev.4 == ''
entPhysicalSerialNum.4 ==  ''
entPhysicalMfgName.4 ==    'Acme'
entPhysicalModelName.4 ==  'RB'
entPhysicalAlias.4 ==      ''
entPhysicalAssetID.4 ==    ''
entPhysicalIsFRU.4 ==      false(2)
```

```
entPhysicalDescr.5 ==      'Acme Hub Slot Type RB'
entPhysicalVendorType.5 == acmeProducts.slotTypes.5
entPhysicalContainedIn.5 == 1
entPhysicalClass.5 ==      container(5)
entPhysicalParentRelPos.5 == 2
entPhysicalName.5 ==       'Slot 2'
entPhysicalHardwareRev.5 == 'B(1.00.03)'
entPhysicalSoftwareRev.5 == ''
entPhysicalFirmwareRev.5 == ''
entPhysicalSerialNum.5 ==  ''
entPhysicalMfgName.5 ==    'Acme'
entPhysicalModelName.5 ==  'RB'
```

Expires July 2005

[Page 56]

```
entPhysicalAlias.5 ==      ''
entPhysicalAssetID.5 ==    ''
entPhysicalIsFRU.5 ==      false(2)

entPhysicalDescr.6 ==      'Acme Hub Slot Type RB'
entPhysicalVendorType.6 ==  acmeProducts.slotTypes.5
entPhysicalContainedIn.6 == 1
entPhysicalClass.6 ==      container(5)
entPhysicalParentRelPos.6 == 3
entPhysicalName.6 ==        'Slot 3'
entPhysicalHardwareRev.6 == 'B(1.00.03)'
entPhysicalSoftwareRev.6 == ''
entPhysicalFirmwareRev.6 == ''
entPhysicalSerialNum.6 ==   ''
entPhysicalMfgName.6 ==      'Acme'
entPhysicalModelName.6 ==    'RB'
entPhysicalAlias.6 ==        ''
entPhysicalAssetID.6 ==      ''
entPhysicalIsFRU.6 ==        false(2)
```

Slot 1 contains a plug-in module with 4 10-BaseT ports:

```
entPhysicalDescr.7 ==      'Acme 10Base-T Module 114'
entPhysicalVendorType.7 ==  acmeProducts.moduleTypes.32
entPhysicalContainedIn.7 == 4
entPhysicalClass.7 ==      module(9)
entPhysicalParentRelPos.7 == 1
entPhysicalName.7 ==        'M1'
entPhysicalHardwareRev.7 == 'A(1.02.01)'
entPhysicalSoftwareRev.7 == '1.7.2'
entPhysicalFirmwareRev.7 == 'A(1.5)'
entPhysicalSerialNum.7 ==   'C100096244'
entPhysicalMfgName.7 ==      'Acme'
entPhysicalModelName.7 ==    '114'
entPhysicalAlias.7 ==        'bldg09:floor1:eng'
entPhysicalAssetID.7 ==      '0007962951'
entPhysicalIsFRU.7 ==        true(1)

entPhysicalDescr.8 ==      'Acme 10Base-T Port RB'
entPhysicalVendorType.8 ==  acmeProducts.portTypes.10
entPhysicalContainedIn.8 == 7
entPhysicalClass.8 ==      port(10)
entPhysicalParentRelPos.8 == 1
entPhysicalName.8 ==        'Ethernet-A'
entPhysicalHardwareRev.8 ==  'A(1.04F)'
entPhysicalSoftwareRev.8 ==  ''
```


Expires July 2005

[Page 57]

```
entPhysicalFirmwareRev.8 ==      '1.4'
entPhysicalSerialNum.8 ==        ''
entPhysicalMfgName.8 ==          'Acme'
entPhysicalModelName.8 ==        'RB'
entPhysicalAlias.8 ==            ''
entPhysicalAssetID.8 ==          ''
entPhysicalIsFRU.8 ==            false(2)

entPhysicalDescr.9 ==            'Acme 10Base-T Port RB'
entPhysicalVendorType.9 ==        acmeProducts.portTypes.10
entPhysicalContainedIn.9 ==        7
entPhysicalClass.9 ==            port(10)
entPhysicalParentRelPos.9 ==      2
entPhysicalName.9 ==              'Ethernet-B'
entPhysicalHardwareRev.9 ==        'A(1.04F)'
entPhysicalSoftwareRev.9 ==        ''
entPhysicalFirmwareRev.9 ==        '1.4'
entPhysicalSerialNum.9 ==          ''
entPhysicalMfgName.9 ==            'Acme'
entPhysicalModelName.9 ==          'RB'
entPhysicalAlias.9 ==              ''
entPhysicalAssetID.9 ==            ''
entPhysicalIsFRU.9 ==              false(2)

entPhysicalDescr.10 ==            'Acme 10Base-T Port RB'
entPhysicalVendorType.10 ==        acmeProducts.portTypes.10
entPhysicalContainedIn.10 ==        7
entPhysicalClass.10 ==            port(10)
entPhysicalParentRelPos.10 ==      3
entPhysicalName.10 ==              'Ethernet-C'
entPhysicalHardwareRev.10 ==        'B(1.02.07)'
entPhysicalSoftwareRev.10 ==        ''
entPhysicalFirmwareRev.10 ==        '1.4'
entPhysicalSerialNum.10 ==          ''
entPhysicalMfgName.10 ==            'Acme'
entPhysicalModelName.10 ==          'RB'
entPhysicalAlias.10 ==              ''
entPhysicalAssetID.10 ==            ''
entPhysicalIsFRU.10 ==              false(2)

entPhysicalDescr.11 ==            'Acme 10Base-T Port RB'
entPhysicalVendorType.11 ==        acmeProducts.portTypes.10
entPhysicalContainedIn.11 ==        7
entPhysicalClass.11 ==            port(10)
entPhysicalParentRelPos.11 ==      4
```

Expires July 2005

[Page 58]

```
entPhysicalName.11 ==      'Ethernet-D'
entPhysicalHardwareRev.11 == 'B(1.02.07)'
entPhysicalSoftwareRev.11 == ''
entPhysicalFirmwareRev.11 == '1.4'
entPhysicalSerialNum.11 == ''
entPhysicalMfgName.11 ==   'Acme'
entPhysicalModelName.11 == 'RB'
entPhysicalAlias.11 ==     ''
entPhysicalAssetID.11 ==   ''
entPhysicalIsFRU.11 ==     false(2)
```

Slot 2 contains another ethernet module with 2 ports.

```
entPhysicalDescr.12 ==     'Acme 10Base-T Module Model 4'
entPhysicalVendorType.12 == acmeProducts.moduleTypes.30
entPhysicalContainedIn.12 == 5
entPhysicalClass.12 ==     module(9)
entPhysicalParentRelPos.12 == 1
entPhysicalName.12 ==      'M2'
entPhysicalHardwareRev.12 == 'A(1.01.07)'
entPhysicalSoftwareRev.12 == '1.8.4'
entPhysicalFirmwareRev.12 == 'A(1.8)'
entPhysicalSerialNum.12 ==  'C100102384'
entPhysicalMfgName.12 ==    'Acme'
entPhysicalModelName.12 ==  '4'
entPhysicalAlias.12 ==      'bldg09:floor1:devtest'
entPhysicalAssetID.12 ==    '0007968462'
entPhysicalIsFRU.12 ==     true(1)
```

```
entPhysicalDescr.13 ==     'Acme 802.3 AUI Port'
entPhysicalVendorType.13 == acmeProducts.portTypes.11
entPhysicalContainedIn.13 == 12
entPhysicalClass.13 ==     port(10)
entPhysicalParentRelPos.13 == 1
entPhysicalName.13 ==      'AUI'
entPhysicalHardwareRev.13 == 'A(1.06F)'
entPhysicalSoftwareRev.13 == ''
entPhysicalFirmwareRev.13 == '1.5'
entPhysicalSerialNum.13 ==  ''
entPhysicalMfgName.13 ==    'Acme'
entPhysicalModelName.13 ==  ''
entPhysicalAlias.13 ==      ''
entPhysicalAssetID.13 ==    ''
entPhysicalIsFRU.13 ==     false(2)
```

```
entPhysicalDescr.14 ==     'Acme 10Base-T Port RD'
```

Expires July 2005

[Page 59]

```
entPhysicalVendorType.14 == acmeProducts.portTypes.14
entPhysicalContainedIn.14 == 12
entPhysicalClass.14 == port(10)
entPhysicalParentRelPos.14 == 2
entPhysicalName.14 == 'E2'
entPhysicalHardwareRev.14 == 'B(1.01.02)'
entPhysicalSoftwareRev.14 == ''
entPhysicalFirmwareRev.14 == '2.1'
entPhysicalSerialNum.14 == ''
entPhysicalMfgName.14 == 'Acme'
entPhysicalModelName.14 == ''
entPhysicalAlias.14 == ''
entPhysicalAssetID.14 == ''
entPhysicalIsFRU.14 == false(2)
```

Logical entities -- entLogicalTable; with SNMPv3 support

Repeater 1--comprised of any ports attached to backplane 1

```
entLogicalDescr.1 == 'Acme repeater v3.1'
entLogicalType.1 == snmpDot3RptrMgt
entLogicalCommunity.1 == 'public-repeater1'
entLogicalTAddress.1 == 124.125.126.127:161
entLogicalTDomain.1 == snmpUDPDomain
entLogicalContextEngineID.1 == '80000777017c7d7e7f'H
entLogicalContextName.1 == 'repeater1'
```

Repeater 2--comprised of any ports attached to backplane 2:

```
entLogicalDescr.2 == 'Acme repeater v3.1'
entLogicalType.2 == snmpDot3RptrMgt
entLogicalCommunity.2 == 'public-repeater2'
entLogicalTAddress.2 == 124.125.126.127:161
entLogicalTDomain.2 == snmpUDPDomain
entLogicalContextEngineID.2 == '80000777017c7d7e7f'H
entLogicalContextName.2 == 'repeater2'
```

Logical to Physical Mappings -- entLPMappingTable:

```
repeater1 uses backplane 1, slot 1-ports 1 & 2, slot 2-port 1
[ed. -- Note that a mapping to the module is not included,
since in this example represents a port-switchable hub.
Even though all ports on the module could belong to the
same repeater as a matter of configuration, the LP port
mappings should not be replaced dynamically with a single
mapping for the module (e.g., entLPPhysicalIndex.1.7).
If all ports on the module shared a single backplane connection,
then a single mapping for the module would be more appropriate. ]
```

Expires July 2005

[Page 60]

```
entLPPhysicalIndex.1.2 ==      2
entLPPhysicalIndex.1.8 ==      8
entLPPhysicalIndex.1.9 ==      9
entLPPhysicalIndex.1.13 ==     13
```

repeater2 uses backplane 2, slot 1-ports 3 & 4, slot 2-port 2

```
entLPPhysicalIndex.2.3 ==      3
entLPPhysicalIndex.2.10 ==     10
entLPPhysicalIndex.2.11 ==     11
entLPPhysicalIndex.2.14 ==     14
```

Physical to Logical to MIB Alias Mappings -- entAliasMappingTable:

Repeater Port Identifier values are shared by both repeaters:

```
entAliasMappingIdentifier.8.0 ==    rpPtrPortGroupIndex.1.1
entAliasMappingIdentifier.9.0 ==    rpPtrPortGroupIndex.1.2
entAliasMappingIdentifier.10.0 ==   rpPtrPortGroupIndex.1.3
entAliasMappingIdentifier.11.0 ==   rpPtrPortGroupIndex.1.4
entAliasMappingIdentifier.13.0 ==   rpPtrPortGroupIndex.2.1
entAliasMappingIdentifier.14.0 ==   rpPtrPortGroupIndex.2.2
```

Physical Containment Tree -- entPhysicalContainsTable

chassis has two backplanes and three containers:

```
entPhysicalChildIndex.1.2 ==      2
entPhysicalChildIndex.1.3 ==      3
entPhysicalChildIndex.1.4 ==      4
entPhysicalChildIndex.1.5 ==      5
entPhysicalChildIndex.1.6 ==      6
```

container 1 has a module:

```
entPhysicalChildIndex.4.7 ==      7
```

container 2 has a module

```
entPhysicalChildIndex.5.12 ==     12
```

[ed. - in this example, container 3 is empty.]

module 1 has 4 ports:

```
entPhysicalChildIndex.7.8 ==      8
entPhysicalChildIndex.7.9 ==      9
entPhysicalChildIndex.7.10 ==     10
entPhysicalChildIndex.7.11 ==     11
```

module 2 has 2 ports:

```
entPhysicalChildIndex.12.13 ==    13
entPhysicalChildIndex.12.14 ==    14
```


5. Security Considerations

There are a number of management objects defined in this MIB that have a MAX-ACCESS clause of read-write and/or read-create. Such objects may be considered sensitive or vulnerable in some network environments. The support for SET operations in a non-secure environment without proper protection can have a negative effect on network operations.

There are a number of managed objects in this MIB that may contain sensitive information. These are:

entPhysicalDescr
entPhysicalVendorType
entPhysicalHardwareRev
entPhysicalFirmwareRev
entPhysicalSoftwareRev
entPhysicalSerialNum
entPhysicalMfgName
entPhysicalModelName

These objects expose information about the physical entities within a managed system, which may be used to identify the vendor, model, and version information of each system component.

entPhysicalAssetID

This object can allow asset identifiers for various system components to be exposed, in the event this MIB object is actually configured by an NMS application.

entLogicalDescr
entLogicalType

These objects expose the type of logical entities present in the managed system.

entLogicalCommunity

This object exposes community names associated with particular logical entities within the system.

entLogicalTAddress
entLogicalTDomain

These objects expose network addresses that can be used to communicate with an SNMP agent on behalf of particular logical entities within the system.

entLogicalContextEngineID
entLogicalContextName

These objects identify the authoritative SNMP engine that contains information on behalf of particular logical entities within the system.

It is thus important to control even GET access to these objects and possibly to even encrypt the values of these object when sending them over the network via SNMP. Not all versions of SNMP provide features for such a secure environment.

SNMPv1 by itself is not a secure environment. Even if the network itself is secure (for example by using IPSec), even then, there is no control as to who on the secure network is allowed to access and GET/SET (read/change/create/delete) the objects in this MIB.

It is recommended that the implementers consider the security features as provided by the SNMPv3 framework. Specifically, the use of the User-based Security Model [RFC 2574](#) [[RFC2574](#)] and the View-based Access Control Model [RFC 2575](#) [[RFC2575](#)] is recommended.

It is then a customer/user responsibility to ensure that the SNMP entity giving access to an instance of this MIB, is properly configured to give access to the objects only to those principals (users) that have legitimate rights to indeed GET or SET (change/create/delete) them.

6. IANA Considerations

The MIB module in this document uses the following IANA-assigned OBJECT IDENTIFIER values recorded in the SMI Numbers registry:

| Descriptor ----- | OBJECT IDENTIFIER value ----- |
|---------------------|----------------------------------|
| entityMIB | { mib-2 47 } |

Editor's Note (to be removed prior to publication): this draft makes no additional requests of the IANA.

7. Acknowledgements

This memo has been produced by the IETF's Entity MIB working group.

8. References

8.1. Normative References

[RFC2026]

Bradner, S., "The Internet Standards Process -- Revision 3", [RFC 2026](#), October, 1996.

[RFC2396]

Berners-Lee, T., Fielding, R., and L. Masinter, "Uniform Resource Identifiers (URI): Generic Syntax", [RFC 2396](#), August 1998.

[RFC2578]

McCloghrie, K., Perkins, D., Schoenwaelder, J., Case, J., Rose, M., and S. Waldbusser, "Structure of Management Information Version 2 (SMIv2)", STD 58, [RFC 2578](#), April 1999.

[RFC2579]

McCloghrie, K., Perkins, D., Schoenwaelder, J., Case, J., Rose, M., and S. Waldbusser, "Textual Conventions for SMIv2", STD 58, [RFC 2579](#), April 1999.

[RFC2580]

McCloghrie, K., Perkins, D., Schoenwaelder, J., Case, J., Rose, M., and S. Waldbusser, "Conformance Statements for SMIv2", STD 58, RFC

Expires July 2005

[Page 64]

2580, April 1999.

[RFC3411]

Harrington, D., Presuhn, R., and B. Wijnen, "An Architecture for Describing Simple Network Management Protocol (SNMP) Management Frameworks", STD 62, [RFC 3411](#), December 2002.

[RFC3417]

R. Presuhn, Ed., "Transport Mappings for the Simple Network Management Protocol (SNMP)", STD 62, [RFC 3417](#), December 2002.

[8.2.](#) Informative References

[RFC1157]

Case, J., Fedor, M., Schoffstall, M., and J. Davin, "Simple Network Management Protocol", STD 15, [RFC 1157](#), May 1990.

[RFC1493]

Decker, E., Langille, P., Rijsinghani, A., and K. McCloghrie, "Definitions of Managed Objects for Bridges", [RFC 1493](#), July, 1993.

[RFC1516]

McMaster, D., and K. McCloghrie, "Definitions of Managed Objects for IEEE 802.3 Repeater Devices", [RFC 1516](#), September, 1993.

[RFC2037]

McCloghrie, K., and A. Bierman, "Entity MIB using SMIV2", [RFC 2037](#), October 1996.

[RFC2108]

de Graaf, K., Romascanu, D., McMaster, D., and K. McCloghrie, "Definitions of Managed Objects for IEEE 802.3 Repeater Devices using SMIV2", [RFC 2108](#), February, 1997.

[RFC2863]

McCloghrie, K., and F. Kastenholz, "The Interfaces Group MIB", [RFC 2863](#), June, 2000.

[RFC2737]

McCloghrie, K., and A. Bierman, "Entity MIB (Version 2)", [RFC 2737](#), December 1999.

[RFC3406]

Daigle, L., van Gulik, D., Iannella, R., and P. Faltstrom, "Uniform Resource Names (URN) Namespace Definition Mechanisms", [RFC 3406](#), October 2002.

[RFC3410]

Case, J., Mundy, R., Partain, D. and B. Stewart, "Introduction and Applicability Statements for Internet- Standard Management Framework", [RFC 3410](#), December 2002.

[RFCCLEIURN]

Tesink, K., and Robert H. Fox, "A Uniform Resource Name (URN) Namespace for the CLEI Code", Work in progress, November 7, 2004.

[T1.213]

ATIS T1.213-2001, "Coded Identification of Equipment Entities in the North American Telecommunications System for Information Exchange", 2001, www.ansi.org.

[T1.213a]

ATIS T1.213a, "Supplement to T1.213-2001, Coded Identification of Equipment Entities in the North American Telecommunications System for Information Exchange, to correct the representation of the Basic Code in Figure B.1", 2001, www.ansi.org.

Expires July 2005

[Page 66]

Authors' Addresses

Andy Bierman
Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA 95134 USA
Phone: +1 408-527-3711
Email: abierman@cisco.com

Keith McCloghrie
Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA 95134 USA
Phone: +1 408-526-5260
Email: kzm@cisco.com

Intellectual Property Statement

The IETF takes no position regarding the validity or scope of any Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; nor does it represent that it has made any independent effort to identify any such rights. Information on the procedures with respect to rights in RFC documents can be found in [BCP 78](#) and [BCP 79](#).

Copies of IPR disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF on-line IPR repository at <http://www.ietf.org/ipr>.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement this standard. Please address the information to the IETF at ietf-ipr@ietf.org.

Disclaimer of Validity

This document and the information contained herein are provided on

Expires July 2005

[Page 67]

an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Copyright Statement

Copyright (C) The Internet Society (2005). This document is subject to the rights, licenses and restrictions contained in [BCP 78](#), and except as set forth therein, the authors retain all their rights.

Acknowledgment

Funding for the RFC Editor function is currently provided by the Internet Society.