

EXTRA  
Internet-Draft  
Updates: [5232](#) (if approved)  
Intended status: Standards Track  
Expires: 8 September 2022

K. Murchison  
R. Signes  
N. Jenkins  
Fastmail  
7 March 2022

Sieve Email Filtering: Snooze Extension  
draft-ietf-extra-sieve-snooze-04

## Abstract

This document describes the "snooze" extension to the Sieve email filtering language. The "snooze" extension gives Sieve the ability to postpone the delivery of an incoming email message into a target mailbox until a later point in time.

## Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 8 September 2022.

## Copyright Notice

Copyright (c) 2022 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Revised BSD License text as described in Section 4.e of the [Trust Legal Provisions](#) and are provided without warranty as described in the Revised BSD License.

Internet-Draft

Sieve Snooze

March 2022

## Table of Contents

<a href="#">1.</a>	Introduction . . . . .	<a href="#">2</a>
<a href="#">2.</a>	Conventions Used in This Document . . . . .	<a href="#">2</a>
<a href="#">3.</a>	Capability Identifier . . . . .	<a href="#">3</a>
<a href="#">4.</a>	Snooze Action . . . . .	<a href="#">3</a>
<a href="#">4.1.</a>	Mailbox Argument . . . . .	<a href="#">4</a>
<a href="#">4.2.</a>	Weekdays Argument . . . . .	<a href="#">4</a>
<a href="#">4.3.</a>	Times and TZID Arguments . . . . .	<a href="#">4</a>
<a href="#">4.3.1.</a>	Awaken Times Examples . . . . .	<a href="#">5</a>
<a href="#">4.4.</a>	Interaction with Extensions to the Fileinto Action . . . . .	<a href="#">6</a>
<a href="#">4.4.1.</a>	Imap4flags Extension . . . . .	<a href="#">6</a>
<a href="#">4.4.2.</a>	Mailbox Extension . . . . .	<a href="#">7</a>
<a href="#">4.4.3.</a>	Special-Use Extension . . . . .	<a href="#">8</a>
<a href="#">4.4.4.</a>	MailboxID Extension . . . . .	<a href="#">8</a>
<a href="#">5.</a>	Implementation Status . . . . .	<a href="#">8</a>
<a href="#">6.</a>	Security Considerations . . . . .	<a href="#">9</a>
<a href="#">7.</a>	Privacy Considerations . . . . .	<a href="#">9</a>
<a href="#">8.</a>	IANA Considerations . . . . .	<a href="#">9</a>
<a href="#">8.1.</a>	Registration of Sieve Extension . . . . .	<a href="#">9</a>
<a href="#">8.2.</a>	Registration of Sieve Action . . . . .	<a href="#">10</a>
<a href="#">8.3.</a>	Registration of IMAP Mailbox Name Attribute . . . . .	<a href="#">11</a>
<a href="#">9.</a>	Acknowledgments . . . . .	<a href="#">11</a>
<a href="#">10.</a>	References . . . . .	<a href="#">11</a>
<a href="#">10.1.</a>	Normative References . . . . .	<a href="#">11</a>
<a href="#">10.2.</a>	Informative References . . . . .	<a href="#">12</a>
<a href="#">Appendix A.</a>	Change History (To be removed by RFC Editor before publication) . . . . .	<a href="#">13</a>
	Authors' Addresses . . . . .	<a href="#">14</a>

[1.](#) Introduction

Users are not always ready, willing, or able to read and respond to email messages at the time of their arrival. Sometimes it is desirable to have messages appear in a mailbox at a more convenient time for the user to act upon them.

This document defines an extension to the Sieve language [[RFC5228](#)] that enables scripts to postpone the delivery of a message into a target mailbox until a later point in time.

[2.](#) Conventions Used in This Document

Conventions for notations are as in [Section 1.1 of \[RFC5228\]](#), including use of the "Usage:" label for the definition of action and tagged arguments syntax.

Internet-Draft

Sieve Snooze

March 2022

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [BCP 14 \[RFC2119\]](#) [[RFC8174](#)] when, and only when, they appear in all capitals, as shown here.

### [3.](#) Capability Identifier

Sieve implementations that implement this extension have an identifier of "snooze" for use with the capability mechanism.

### [4.](#) Snooze Action

Usage: snooze \*AWAKEN-OPTIONS <times: string-list>

The AWAKEN-OPTIONS argument is defined here in ABNF [[RFC4234](#)] syntax so that it can be modified by other extensions.

```
AWAKEN-OPTIONS = MAILBOX / WEEKDAYS / TZID
                  ; each option MUST NOT appear more than once
                  ; however, per Section 2.6.2 of RFC 5228,
                  ; the tagged arguments in AWAKEN-OPTIONS
                  ; may appear in any order
```

```
MAILBOX  = ":mailbox" string
WEEKDAYS = ":weekdays" string-list
TZID     = ":tzid" string
```

The "snooze" action cancels the implicit keep and postpones delivery of the message into the specified mailbox at a later point in time.

The snooze action is semantically equivalent to a delayed fileinto action (see [Section 4.1 of \[RFC5228\]](#)). The arguments of the snooze action specify when, where, and how the awakened message will be filed.

A Sieve interpreter MUST implement the snooze action by delivering the message to a special "snoozed" mailbox within its mailstore. IMAP [[RFC3501](#)] and JMAP [[RFC8621](#)] servers MUST apply the "Snoozed" ([Section 8.3](#)) attribute to this mailbox. The message will reside in this special mailbox until the prescribed awaken time at which it will be moved into the specified target mailbox.

#### [4.1.](#) Mailbox Argument

The optional :mailbox argument is used to specify the target mailbox that the message will be filed into when it is awakened. It is equivalent to the mailbox argument of the fileinto action (see [Section 4.1 of \[RFC5228\]](#)).

If :mailbox is omitted, or if the specified mailbox doesn't exist at the time of awakening, the message will be filed into the user's main mailbox. For instance, in an implementation where an IMAP server is running scripts on behalf of the user at time of delivery, the user's "INBOX" would be the implicit target for awakening messages.

#### [4.2.](#) Weekdays Argument

The optional :weekdays argument specifies the set of days on which the specified set of awakening times apply. Each day of the week is expressed as an integer between "0" and "6". "0" is Sunday, "1" is Monday, etc. This syntax matches that of the "weekday" date-part argument to the date test extension (see [Section 4.2 of \[RFC5260\]](#)).

If :weekdays is omitted, the set of awakening times applies to every day of the week.

#### [4.3.](#) Times and TZID Arguments

The required times argument, along with the optional :tzid argument, are used to specify when a snoozed message will be awakened. Each time is specified in "hh:mm:ss" format and is interpreted as the

local time in the time zone specified by the :tzid argument.

The value of the :tzid argument MUST be a time zone identifier from the IANA Time Zone Database [[tzdb](#)]. If :tzid is omitted, the time zone of the Sieve interpreter is used.

The combination of the weekdays and times form a chronological list of awaken times. When a message is snoozed, it is assigned the next future awaken time in the list. If a message is snoozed on a day with no awaken times, or after the last awaken time on a given day, the first awaken time on the next available day is used.

If the local time in the specified time zone occurs more than once (daylight saving to standard time transition), the first occurrence of the specified time value is used. If the local time in the specified time zone does not occur (standard to daylight saving time transition), the specified time value is interpreted using the UTC offset prior to the transition.

#### [4.3.1.](#) Awaken Times Examples

The following examples show, given the specified snooze action and a set of message arrival times, the corresponding times at which the message would be awakened and filed.

The following example shows awaken times rolling into the next day or week. Note that 2020-07-30 falls on a Thursday.

```
require "snooze";
snooze :weekdays ["1", "3", "5", "2", "4"]
       :tzid "Australia/Melbourne" ["12:00:00",
                                     "08:00:00", "16:00:00"];
```

=====+	=====+	=====+
Arrival (UTC)	Arrival (Melbourne)	Awaken (Melbourne)
=====+	=====+	=====+
2020-07-30T00:00:00Z	--07-30T10:00:00+10	--07-30T12:00:00+10
-----+	-----+	-----+
2020-07-30T04:00:00Z	--07-30T14:00:00+10	--07-30T16:00:00+10
-----+	-----+	-----+
2020-07-30T08:00:00Z	--07-30T18:00:00+10	--07-31T08:00:00+10

2020-07-31T12:00:00Z	--07-31T22:00:00+10	--08-03T08:00:00+10	
2020-08-01T16:00:00Z	--08-02T02:00:00+10	--08-03T08:00:00+10	

Table 1

The following example shows awaken times falling before, during, and after a daylight saving to standard time transition. Note that the transition occurs at 2020-11-01T02:00:00-04.

```
require "snooze";
snooze :tzid "America/New_York" "01:30:00";
```

Arrival (UTC)	Arrival (New York)	Awaken (New York)	
2020-11-01T05:00:00Z	--11-01T01:00:00-04	--11-01T01:30:00-04	
2020-11-01T06:00:00Z	--11-01T01:00:00-05	--11-02T01:30:00-05	
2020-11-01T07:00:00Z	--11-01T02:00:00-05	--11-02T01:30:00-05	

Table 2

The following example shows awaken times falling before, during, and after a standard to daylight saving time transition. Note that the transition occurs at 2021-03-14T02:00:00-05.

```
require "snooze";
snooze :tzid "America/New_York" "02:30:00";
```

Arrival (UTC)	Arrival (New York)	Awaken (New York)	
2021-03-13T06:30:00Z	--03-13T01:30:00-05	--03-13T02:30:00-05	
2021-03-14T06:30:00Z	--03-14T01:30:00-05	--03-14T03:30:00-04	
2021-03-14T07:30:00Z	--03-14T03:30:00-04	--03-15T02:30:00-04	

Table 3

#### [4.4.](#) Interaction with Extensions to the Fileinto Action

Some tagged arguments defined in extensions to the fileinto action can be used together with the snooze action. The sections below describe these interactions. Tagged arguments in future extensions to the fileinto action need to describe their interaction with the snooze extension, if any.

When any fileinto extension arguments are used with the snooze extension, the corresponding extension **MUST** be enabled, and the arguments are defined to have the same syntax, semantics, and treatment as they do with the fileinto action.

##### [4.4.1.](#) Imap4flags Extension

When the "imap4flags" [[RFC5232](#)] extension is enabled in a script, two additional tagged arguments are added to "snooze" that allow manipulating the set of flags on a snoozed message.

AWAKEN-OPTIONS /= ADDFLAGS / REMOVEFLAGS

ADDFLAGS = ":addflags" string-list  
REMOVEFLAGS = ":removeflags" string-list

The optional :addflags and :removeflags arguments are used to specify which IMAP [[RFC3501](#)] flags should be added to and/or removed from the set of IMAP flags present on the snoozed message at the time of awakening. Note the set of IMAP flags present at the time of awakening may be the empty set.

If the "setflag" and/or "addflag" actions have been used to store IMAP flags in the imap4flags internal variable, the Sieve interpreter **MUST** use the current value of the internal variable as the set of flags to associate with the message when storing it into the "snoozed" mailbox.

This document doesn't dictate how the Sieve interpreter will set the IMAP flags. In particular, the Sieve interpreter may work as an IMAP

client or may have direct access to the mailstore.

The general requirements for flag handling specified in [Section 2 of \[RFC5232\]](#) MUST be followed.

#### [4.4.1.1.](#) Example

The following example leverages the Date [\[RFC5260\]](#), Relational [\[RFC5231\]](#), and Imap4flags [\[RFC5232\]](#) extensions to snooze messages received after business hours until the following work day. Note that the message is marked as important when it is snoozed, and will be marked as unread when it is awakened.

```
require ["snooze", "imap4flags", "date", "relational"];

if anyof(header :is "from" "boss@example.com",
         currentdate :is "weekday" "0",
         currentdate :is "weekday" "6",
         currentdate :value "ge" "hour" "17") {
    setflag "\\Important";
    snooze :removeflags "\\Seen"
           :weekdays ["1". "2", "3", "4", "5"]
           :tzid "American/New_York", "09:00";
}
```

#### [4.4.2.](#) Mailbox Extension

This document extends the definition of the ":create" [\[RFC5490\]](#) tagged argument so that it can be used with the snooze action.

AWAKEN-OPTIONS /= CREATE

CREATE = ":create"  
          ; MUST NOT be appear unless MAILBOX also appears

If the optional ":create" argument is specified with snooze, it instructs the Sieve interpreter to create the target mailbox, if needed, before attempting to file the awakened message into the target mailbox.

#### [4.4.3.](#) Special-Use Extension



This document extends the definition of the `":specialuse"` [\[RFC8579\]](#) tagged argument so that it can be used with the snooze action.

AWAKEN-OPTIONS /= SPECIAL-USE

SPECIAL-USE = `":specialuse"` string

If the optional `":specialuse"` argument is specified with snooze, it instructs the Sieve interpreter to check whether a mailbox exists with the specific special-use flag assigned to it. If such a mailbox exists, the awakened message is filed into the special-use mailbox. Otherwise, the awakened message is filed into the target mailbox.

If both the optional `":specialuse"` and `":create"` arguments are specified with snooze, the Sieve interpreter is instructed to create the target mailbox per [Section 4.1 of \[RFC8579\]](#), if needed.

#### [4.4.4.](#) MailboxID Extension

This document extends the definition of the `":mailboxid"` [\[RFC9042\]](#) tagged argument so that it can be used with the snooze action.

AWAKEN-OPTIONS /= MAILBOXID

MAILBOXID = `":mailboxid"` string

If the optional `":mailboxid"` argument is specified with snooze, it instructs the Sieve interpreter to check whether a mailbox exists in the user's personal namespace [\[RFC2342\]](#) with the specified MAILBOXID [\[RFC8474\]](#). If such a mailbox exists, the awakened message is filed into that mailbox. Otherwise, the awakened message is filed into the target mailbox.

It is an error to specify both `":mailboxid"` and `":specialuse"` in the same snooze action.

## [5.](#) Implementation Status

< RFC Editor: before publication please remove this section and the reference to [\[RFC7942\]](#) >

This section records the status of known implementations of the protocol defined by this specification at the time of posting of this Internet-Draft, and is based on a proposal described in [\[RFC7942\]](#). The description of implementations in this section is intended to assist the IETF in its decision processes in progressing drafts to

RFCs. Please note that the listing of any individual implementation here does not imply endorsement by the IETF. Furthermore, no effort has been spent to verify the information presented here that was supplied by IETF contributors. This is not intended as, and must not be construed to be, a catalog of available implementations or their features. Readers are advised to note that other implementations may exist.

According to [RFC7942], "this will allow reviewers and working groups to assign due consideration to documents that have the benefit of running code, which may serve as evidence of valuable experimentation and feedback that have made the implemented protocols more mature. It is up to the individual working groups to use this information as they see fit".

### [5.1.](#) Cyrus Server

The open source Cyrus Server (<http://www.cyrusimap.org/>) project is a highly scalable enterprise mail system which supports Sieve email filtering at the point of final delivery. This production level Sieve implementation supports all of the requirements described in this document. This implementation is freely distributable under a BSD style license from Computing Services at Carnegie Mellon University (<http://www.cmu.edu/computing/>).

## [6.](#) Security Considerations

Security considerations are discussed in [RFC5228], [RFC5232], [RFC8579], and [RFC9042].

It is believed that this extension doesn't introduce any additional security concerns.

## [7.](#) Privacy Considerations

It is believed that this extension doesn't introduce any privacy considerations beyond those in [RFC5228].

## [8.](#) IANA Considerations

### [8.1.](#) Registration of Sieve Extension

This document defines the following new Sieve extension to be added to the registry defined in [Section 6.2 of \[RFC5228\]](#) and located here: <https://www.iana.org/assignments/sieve-extensions/sieve-extensions.xhtml#sieve-extensions>

Internet-Draft

Sieve Snooze

March 2022

IANA are requested to add a capability to the Sieve Extensions registry:

To: [iana@iana.org](mailto:iana@iana.org)

Subject: Registration of new Sieve extension

Capability name: snooze

Description: Adds the "snooze" action command to postpone delivery of a message into a target mailbox until a later point in time.

RFC number: RFC XXXX

Contact address: The Sieve discussion list <[sieve@ietf.org](mailto:sieve@ietf.org)>

## [8.2.](#) Registration of Sieve Action

This document defines the following new Sieve action to be added to the registry defined in Section 3.1 of [\[I-D.ietf-extra-sieve-action-registry\]](#).

IANA are requested to add an action to the Sieve Action registry:

Name: snooze

Description: Postpone delivery of a message into a target mailbox until a later point in time.

References: RFC XXXX, [\[RFC5232\]](#), [\[RFC5490\]](#), [\[RFC8579\]](#), [\[RFC9042\]](#)

Capabilities: "snooze", "imap4flags", "mailbox", "special-use", "mailboxid".

Interactions: Is not compatible with the reject or ereject actions.

Cancels Implicit Keep?: Y

Use with IMAP Events?: Y

Comments: Requires a special "snoozed" mailbox in the mailstore.

Murchison, et al.

Expires 8 September 2022

[Page 10]

---

Internet-Draft

Sieve Snooze

March 2022

### [8.3.](#) Registration of IMAP Mailbox Name Attribute

This document defines the following new IMAP mailbox name attribute to be added to the registry defined in [Section 6.2 of \[RFC8457\]](#) and located here: <https://www.iana.org/assignments/imap-mailbox-name-attributes/imap-mailbox-name-attributes.xhtml#imap-mailbox-name-attributes>

IANA are requested to add an attribute to the IMAP Mailbox Name Attribute registry:

To: iana@iana.org

Subject: Registration of new IMAP Mailbox Name Attribute

Attribute name: Snoozed

Description: Messages that have been snoozed.

Reference: RFC XXXX

## [9.](#) Acknowledgments

The authors would like to thank the following individuals for contributing their ideas and support for writing this specification: Ned Freed, Barry Leiba, and Alexey Melnikov.

## [10.](#) References

### [10.1.](#) Normative References

[I-D.ietf-extra-sieve-action-registry]

Melnikov, A. and K. Murchison, "IANA registry for Sieve actions", Work in Progress, Internet-Draft, [draft-ietf-extra-sieve-action-registry-02](https://www.ietf.org/archive/id/draft-ietf-extra-sieve-action-registry-02), 7 March 2022, <<https://www.ietf.org/archive/id/draft-ietf-extra-sieve-action-registry-02.txt>>.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.

[RFC2342] Gahrns, M. and C. Newman, "IMAP4 Namespace", [RFC 2342](#), DOI 10.17487/RFC2342, May 1998, <<https://www.rfc-editor.org/info/rfc2342>>.

Murchison, et al.

Expires 8 September 2022

[Page 11]

---

Internet-Draft

Sieve Snooze

March 2022

[RFC3501] Crispin, M., "INTERNET MESSAGE ACCESS PROTOCOL – VERSION 4rev1", [RFC 3501](#), DOI 10.17487/RFC3501, March 2003, <<https://www.rfc-editor.org/info/rfc3501>>.

[RFC4234] Crocker, D., Ed. and P. Overell, "Augmented BNF for Syntax Specifications: ABNF", [RFC 4234](#), DOI 10.17487/RFC4234, October 2005, <<https://www.rfc-editor.org/info/rfc4234>>.

[RFC5228] Guenther, P., Ed. and T. Showalter, Ed., "Sieve: An Email Filtering Language", [RFC 5228](#), DOI 10.17487/RFC5228, January 2008, <<https://www.rfc-editor.org/info/rfc5228>>.

[RFC5232] Melnikov, A., "Sieve Email Filtering: Imap4flags Extension", [RFC 5232](#), DOI 10.17487/RFC5232, January 2008, <<https://www.rfc-editor.org/info/rfc5232>>.

[RFC5490] Melnikov, A., "The Sieve Mail-Filtering Language -- Extensions for Checking Mailbox Status and Accessing Mailbox Metadata", [RFC 5490](#), DOI 10.17487/RFC5490, March 2009, <<https://www.rfc-editor.org/info/rfc5490>>.

[RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in [RFC 2119](#) Key Words", [BCP 14](#), [RFC 8174](#), DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.

- [RFC8457] Leiba, B., Ed., "IMAP "\$Important" Keyword and "\Important" Special-Use Attribute", [RFC 8457](#), DOI 10.17487/RFC8457, September 2018, <<https://www.rfc-editor.org/info/rfc8457>>.
- [RFC8474] Gondwana, B., Ed., "IMAP Extension for Object Identifiers", [RFC 8474](#), DOI 10.17487/RFC8474, September 2018, <<https://www.rfc-editor.org/info/rfc8474>>.
- [RFC8579] Bosch, S., "Sieve Email Filtering: Delivering to Special-Use Mailboxes", [RFC 8579](#), DOI 10.17487/RFC8579, May 2019, <<https://www.rfc-editor.org/info/rfc8579>>.
- [RFC9042] Gondwana, B., Ed., "Sieve Email Filtering: Delivery by MAILBOXID", [RFC 9042](#), DOI 10.17487/RFC9042, June 2021, <<https://www.rfc-editor.org/info/rfc9042>>.
- [tzdb] Internet Assigned Numbers Authority, "Time Zone Database", <<https://www.iana.org/time-zones>>.

## [10.2.](#) Informative References

Murchison, et al. Expires 8 September 2022 [Page 12]

---

Internet-Draft Sieve Snooze March 2022

- [RFC5231] Segmuller, W. and B. Leiba, "Sieve Email Filtering: Relational Extension", [RFC 5231](#), DOI 10.17487/RFC5231, January 2008, <<https://www.rfc-editor.org/info/rfc5231>>.
- [RFC5260] Freed, N., "Sieve Email Filtering: Date and Index Extensions", [RFC 5260](#), DOI 10.17487/RFC5260, July 2008, <<https://www.rfc-editor.org/info/rfc5260>>.
- [RFC7942] Sheffer, Y. and A. Farrel, "Improving Awareness of Running Code: The Implementation Status Section", [BCP 205](#), [RFC 7942](#), DOI 10.17487/RFC7942, July 2016, <<https://www.rfc-editor.org/info/rfc7942>>.
- [RFC8621] Jenkins, N. and C. Newman, "The JSON Meta Application Protocol (JMAP) for Mail", [RFC 8621](#), DOI 10.17487/RFC8621, August 2019, <<https://www.rfc-editor.org/info/rfc8621>>.

[Appendix A.](#) Change History (To be removed by RFC Editor before

publication)

Changes since [draft-ietf-extra-sieve-snooze-03](#):

- \* Added "snooze" to the Sieve Actions Registry.

Changes since [draft-ietf-extra-sieve-snooze-02](#):

- \* Updated :mailboxid reference to [RFC9042](#).
- \* Added an informative reference to [RFC8621](#).
- \* Miscellaneous editorial changes.

Changes since [draft-ietf-extra-sieve-snooze-01](#):

- \* Miscellaneous editorial changes.

Changes since [draft-ietf-extra-sieve-snooze-00](#):

- \* Disallow both :mailboxid and :specialuse in the same snooze action.
- \* Updated :mailboxid reference to [draft-ietf-extra-sieve-mailboxid](#)
- \* Specified that snooze cancels implicit keep.
- \* Specified that implementations MUST use a "snoozed" mailbox.
- \* Added registration of \Snoozed Special-Use Attribute.

Murchison, et al.

Expires 8 September 2022

[Page 13]

---

Internet-Draft

Sieve Snooze

March 2022

- \* Added example of manipulating IMAP flags at both snooze time and awaken time.
- \* Miscellaneous editorial changes.

Authors' Addresses

Kenneth Murchison  
Fastmail US LLC  
1429 Walnut Street - Suite 1201  
Philadelphia, PA 19102

United States of America  
Email: [murch@fastmailteam.com](mailto:murch@fastmailteam.com)

Ricardo Signes  
Fastmail US LLC  
1429 Walnut Street - Suite 1201  
Philadelphia, PA 19102  
United States of America  
Email: [rjbs@fastmailteam.com](mailto:rjbs@fastmailteam.com)

Neil Jenkins  
Fastmail Pty Ltd  
Level 2, 114 William Street  
Melbourne VIC 3000  
Australia  
Email: [neilj@fastmailteam.com](mailto:neilj@fastmailteam.com)