

GeoJSON
Internet-Draft
Intended status: Standards Track
Expires: November 14, 2016

H. Butler
Hobu Inc.
M. Daly
Cadcorp
A. Doyle

S. Gillies
Mapbox
S. Hagen

T. Schaub
Planet Labs
May 13, 2016

The GeoJSON Format
draft-ietf-geojson-03

Abstract

GeoJSON is a geospatial data interchange format based on JavaScript Object Notation (JSON). It defines several types of JSON objects and the manner in which they are combined to represent data about geographic features, their properties, and their spatial extents. This document recommends a single coordinate reference system based on WGS 84. Other coordinate reference systems are not recommended.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on November 14, 2016.

Copyright Notice

Copyright (c) 2016 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	3
1.1.	Requirements Language	4
1.2.	Conventions Used in This Document	4
1.3.	Specification of GeoJSON	4
1.4.	Definitions	5
1.5.	Example	5
2.	GeoJSON Text	7
3.	GeoJSON Object	7
3.1.	Geometry Object	7
3.1.1.	Position	7
3.1.2.	Point	8
3.1.3.	MultiPoint	9
3.1.4.	LineString	9
3.1.5.	MultiLineString	9
3.1.6.	Polygon	9
3.1.7.	MultiPolygon	10
3.1.8.	Geometry Collection	10
3.1.9.	Antimeridian Cutting	10
3.1.10.	Uncertainty and Confidence	11
3.2.	Feature Object	12
3.3.	Feature Collection Object	12
4.	Coordinate Reference System	12
5.	Bounding Box	13
5.1.	The Connecting Lines	14
5.2.	The Antimeridian	14
5.3.	The Poles	15
6.	Extending GeoJSON	15
6.1.	Foreign Members	15
7.	GeoJSON Types are not Extensible	16
7.1.	Semantics of GeoJSON Members and Types are not Changeable	16
8.	Versioning	17

9.	Mapping 'geo' URIs	17
10.	Security Considerations	18
11.	Interoperability Considerations	18
11.1.	I-JSON	18
11.2.	Coordinate Precision	18
12.	IANA Considerations	18
13.	Acknowledgements	19
14.	References	20
14.1.	Normative References	20
14.2.	Informative References	20
Appendix A.	Geometry Examples	21
A.1.	Points	21
A.2.	LineStrings	21
A.3.	Polygons	21
A.4.	MultiPoints	22
A.5.	MultiLineStrings	23
A.6.	MultiPolygons	23
A.7.	GeometryCollections	24
Appendix B.	Changes from pre-IETF Specification	25
B.1.	Normative Changes	25
B.2.	Informative Changes	26
Appendix C.	GeoJSON Text Sequences	26
Authors' Addresses		26

[1.](#) Introduction

GeoJSON is a format for encoding a variety of geographic data structures using JavaScript Object Notation (JSON) [[RFC7159](#)]. A GeoJSON object may represent a region of space (a Geometry), a spatially-bounded entity (a Feature), or a list of features (a Feature Collection). GeoJSON supports the following geometry types: Point, LineString, Polygon, MultiPoint, MultiLineString, MultiPolygon, and GeometryCollection. Features in GeoJSON contain a geometry object and additional properties, and a Feature Collection contains a list of features.

The format is concerned with geographic data in the broadest sense; any thing with qualities that are bounded in geographical space might be a feature whether it is a physical structure or not. The concepts in GeoJSON are not new; they are derived from pre-existing open geographic information system standards and have been streamlined to better suit web application development using JSON.

GeoJSON comprises the seven concrete geometry types defined in the OpenGIS Simple Features Implementation Specification for SQL [[SFSQL](#)]: 0-dimensional Point and MultiPoint; 1-dimensional curve LineString and MultiLineString; 2-dimensional surface Polygon and MultiPolygon; and the heterogeneous GeometryCollection. GeoJSON representations of

instances of these geometry types are analogous to the well-known binary (WKB) and text (WKT) representations described in that same specification.

GeoJSON also comprises the types `Feature` and `FeatureCollection`. `Feature` objects in GeoJSON contain a geometry object with one of the above geometry types and additional members. A `FeatureCollection` object contains an array of feature objects. This structure is analogous to that of the Web Feature Service (WFS) response to `GetFeatures` requests specified in [WFSv1] or to a KML Folder of Placemarks [KMLv2.2]. Some implementations of the WFS specification also provide GeoJSON formatted responses to `GetFeature` requests, but there is no particular service model or feature type ontology implied in the GeoJSON format specification.

Since its initial publication in 2008 [GJ2008], the GeoJSON format specification has steadily grown in popularity. It is widely used in JavaScript web mapping libraries, JSON-based document databases, and web APIs.

1.1. Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC2119].

1.2. Conventions Used in This Document

The ordering of the members of any JSON object defined in this document MUST be considered irrelevant, as specified by [RFC7159].

Some examples use the combination of a JavaScript single line comment (//) followed by an ellipsis (...) as placeholder notation for content deemed irrelevant by the authors. These placeholders must of course be deleted or otherwise replaced, before attempting to validate the corresponding JSON code example.

Whitespace is used in the examples inside this document to help illustrate the data structures, but is not required. Unquoted whitespace is not significant in JSON.

1.3. Specification of GeoJSON

This document updates the original GeoJSON format specification [GJ2008].

1.4. Definitions

- o JavaScript Object Notation (JSON), and the terms object, member, name, value, array, number, true, false, and null are to be interpreted as defined in [[RFC7159](#)].
- o Inside this document the term "geometry type" refers to the seven case-sensitive strings: "Point", "MultiPoint", "LineString", "MultiLineString", "Polygon", "MultiPolygon", and "GeometryCollection".
- o As another shorthand notation, the term "GeoJSON types" refers to the nine case-sensitive strings "Feature", "FeatureCollection" and the geometry types listed above.
- o The word "Collection" in "FeatureCollection" and "GeometryCollection" does not have any significance for the semantics of array members. The "features" and "geometries" members, respectively, of these objects are standard ordered JSON arrays, not unordered sets.

1.5. Example

A GeoJSON feature collection:


```
{
  "type": "FeatureCollection",
  "features": [{
    "type": "Feature",
    "geometry": {
      "type": "Point",
      "coordinates": [102.0, 0.5]
    },
    "properties": {
      "prop0": "value0"
    }
  }, {
    "type": "Feature",
    "geometry": {
      "type": "LineString",
      "coordinates": [
        [102.0, 0.0],
        [103.0, 1.0],
        [104.0, 0.0],
        [105.0, 1.0]
      ]
    },
    "properties": {
      "prop0": "value0",
      "prop1": 0.0
    }
  }, {
    "type": "Feature",
    "geometry": {
      "type": "Polygon",
      "coordinates": [
        [
          [100.0, 0.0],
          [101.0, 0.0],
          [101.0, 1.0],
          [100.0, 1.0],
          [100.0, 0.0]
        ]
      ]
    },
    "properties": {
      "prop0": "value0",
      "prop1": {
        "this": "that"
      }
    }
  }
}]
}
```


2. GeoJSON Text

A GeoJSON text is a JSON text and consists of a single GeoJSON object.

3. GeoJSON Object

A GeoJSON object represents a geometry, feature, or collection of features.

- o A GeoJSON object is a JSON object.
- o A GeoJSON object MUST have a member with the name "type". The value of the member MUST be one of the GeoJSON types.
- o A GeoJSON object MAY have a "bbox" member, the value of which MUST be a bounding box array (see [Section 5](#)).
- o A GeoJSON object MAY have any number of other members (see [Section 6](#)).

3.1. Geometry Object

A Geometry object represents points, curves, and surfaces in coordinate space.

- o The value of a geometry object's "type" member MUST be one of the seven geometry types (see [Section 1.4](#)).
- o A GeoJSON geometry object of any type other than "GeometryCollection" MUST have a member with the name "coordinates". The value of the coordinates member is always an array. The structure of the elements in this array is determined by the type of geometry. GeoJSON processors MAY interpret geometry objects with empty coordinates arrays as null objects.

3.1.1. Position

A position is the fundamental geometry construct. The "coordinates" member of a geometry object is composed of either:

- o one position in the case of a Point geometry,
- o an array of positions in the case of a LineString or MultiPoint geometry,
- o an array of LineString or linear ring (see [Section 3.1.6](#)) coordinates in the case of a Polygon or MultiLineString geometry,

- o or an array of Polygon coordinates in the case of a MultiPolygon geometry.

A position is an array of numbers. There MUST be two or more elements. The first two elements are longitude and latitude, or easting and northing, precisely in that order and using decimal numbers. Altitude or elevation MAY be included as an optional third element.

Implementations SHOULD NOT extend positions beyond 3 elements because the semantics of extra elements are unspecified and ambiguous. Historically, some implementations have used a 4th element to carry a linear referencing measure (sometimes denoted as "M") or a numerical timestamp, but in most situations a parser will not be able to properly interpret these values. The interpretation and meaning of additional elements is beyond the scope of this specification and additional elements MAY be ignored by parsers.

A line between two positions is a straight Cartesian line, the shortest line between those two points in the Coordinate Reference System (see [Section 4](#)).

In other words, every point on a line that does not cross the antimeridian between a point (lon0, lat0) and (lon1, lat1) can be calculated as

$$F(\text{lon}, \text{lat}) = (\text{lon0} + (\text{lon1} - \text{lon0}) * t, \text{lat0} + (\text{lat1} - \text{lat0}) * t)$$

with t a real number greater or equal to 0 and smaller or equal to 1. Note that this line may markedly differ from the geodesic path along the curved surface of the reference ellipsoid.

The same applies to the optional height element with the proviso that the direction of the height is as specified in the Coordinate Reference System.

Note that, again, this does not mean that a surface with equal height follows, for example, the curvature of a body of water. Nor is a surface of equal height perpendicular to a plumb line.

Examples of positions and geometries are provided in "Appendix A. Geometry Examples".

[3.1.2](#). Point

For type "Point", the "coordinates" member MUST be a single position.

3.1.3. MultiPoint

For type "MultiPoint", the "coordinates" member MUST be an array of positions.

3.1.4. LineString

For type "LineString", the "coordinates" member MUST be an array of two or more positions.

3.1.5. MultiLineString

For type "MultiLineString", the "coordinates" member MUST be an array of LineString coordinate arrays.

3.1.6. Polygon

To specify a constraint specific to polygons, it is useful to introduce the concept of a linear ring:

- o A linear ring is a closed LineString with 4 or more positions.
- o The first and last positions are equivalent, they MUST contain identical values; their representation SHOULD also be identical.
- o A linear ring is the boundary of a surface or the boundary of a hole in a surface.
- o A linear ring SHOULD follow the right-hand rule with respect to the area it bounds (i.e., exterior rings are counter-clockwise, holes are clockwise)

Though a linear ring is not explicitly represented as a GeoJSON geometry type, it leads to a canonical formulation of the Polygon geometry type definition as follows:

- o For type "Polygon", the "coordinates" member MUST be an array of linear ring coordinate arrays.
- o For Polygons with more than one of these rings, the first MUST be the exterior ring and any others MUST be interior rings. The exterior ring bounds the surface, and the interior rings (if present) bound holes within the surface.

3.1.7. MultiPolygon

For type "MultiPolygon", the "coordinates" member MUST be an array of Polygon coordinate arrays.

3.1.8. Geometry Collection

A GeoJSON object with type "GeometryCollection" is a geometry object. A geometry collection MUST have a member with the name "geometries". The value of "geometries" is an array. Each element of this array is a GeoJSON geometry object. It is possible for this array to be empty.

Unlike the other geometry types described above, a geometry collection can be a heterogeneous composition of smaller geometry objects. For example, a geometry object in the shape of a lowercase roman "i" can be composed of one point and one line string.

Geometry collections have a different syntax from single type geometry objects (Point, LineString, and Polygon) and homogeneously typed multipart geometry objects (MultiPoint, MultiLineString, and MultiPolygon) but have no different semantics. Although a geometry collection object has no "coordinates" member, it does have coordinates: the coordinates of all its parts belong to the collection. The "geometries" member of a geometry collection describes the parts of this composition. Implementations SHOULD NOT apply any additional semantics to the "geometries" array.

To maximize interoperability implementations SHOULD avoid nested geometry collections. Furthermore, geometry collections composed of a single part or a number of parts of a single type SHOULD be avoided when that single part or a single object of multi-part type (MultiPoint, MultiLineString, or MultiPolygon) could be used instead.

3.1.9. Antimeridian Cutting

In representing features that cross the antimeridian, interoperability is improved by modifying their geometry. Any geometry that crosses the antimeridian SHOULD be represented by cutting it in two such that neither part's representation crosses the antimeridian.

For example, a line extending from 45 degrees N, 170 degrees E across the antimeridian to 45 degrees N, 170 degrees W should be cut in two and represented as a MultiLineString.


```
{
  "type": "MultiLineString",
  "coordinates": [
    [
      [170.0, 45.0], [180.0, 45.0]
    ], [
      [-180.0, 45.0], [-170.0, 45.0]
    ]
  ]
}
```

A rectangle extending from 40 degrees N, 170 degrees E across the antimeridian to 50 degrees N, 170 degrees W should be cut in two and represented as a MultiPolygon.

```
{
  "type": "MultiPolygon",
  "coordinates": [
    [
      [
        [180.0, 40.0], [180.0, 50.0], [170.0, 50.0],
        [170.0, 40.0], [180.0, 40.0]
      ]
    ],
    [
      [
        [-170.0, 40.0], [-170.0, 50.0], [-180.0, 50.0],
        [-180.0, 40.0], [-170.0, 40.0]
      ]
    ]
  ]
}
```

3.1.10. Uncertainty and Confidence

As per [\[RFC7459\]](#) no measure of location uncertainty or confidence can be known for "Point", "MultiPoint", "LineString", or "MultiLineString" geometry types.

Applications such as PIDF-LO that are sensitive to location uncertainty and confidence might treat a geometry object of type "Polygon", "MultiPolygon", and "GeometryCollection" as a representation of a 95% confidence surface. In probabilistic terms: 95 percent of the location's point set is contained within the GeoJSON geometry.

As in [[RFC5870](#)] the number of digits of the values in coordinate positions MUST NOT be interpreted as an indication to the level of uncertainty.

3.2. Feature Object

A Feature object represents a spatially-bounded thing.

- o A feature object MUST have a "type" member with the value "Feature".
- o A feature object MUST have a member with the name "geometry". The value of the geometry member SHALL be either a geometry object as defined above or, in the the case that the feature is unlocated, a JSON null value.
- o A feature object MUST have a member with the name "properties". The value of the properties member is an object (any JSON object or a JSON null value).
- o If a feature has a commonly used identifier, that identifier SHOULD be included as a member of the feature object with the name "id", and the value of this member is either a JSON string or number.

3.3. Feature Collection Object

A GeoJSON object with the type "FeatureCollection" is a feature collection object. A feature collection object MUST have a member with the name "features". The value of "features" is a JSON array. Each element of the array is a feature object as defined above. It is possible for this array to be empty.

4. Coordinate Reference System

The coordinate reference system for all GeoJSON coordinates is a geographic coordinate reference system, using the WGS 84 [[WGS84](#)] datum, and with longitude and latitude units of decimal degrees. This coordinate reference system is equivalent to the OGC's "http://www.opengis.net/def/crs/OGC/1.3/CRS84" [[OGCURL](#)]. An OPTIONAL third position element SHALL be the height in meters above or below the WGS 84 reference ellipsoid. In the absence of elevation values, applications sensitive to height or depth SHOULD interpret positions as being at local ground or sea level.

Note: the use of alternative coordinate reference systems was specified in [[GJ2008](#)], but has been removed from this version of the specification because the use of different coordinate reference

systems -- especially in the manner specified in [[GJ2008](#)] -- has proven to have interoperability issues. In general, GeoJSON processing software is not expected to have access to coordinate reference systems databases or to have network access to coordinate reference system transformation parameters. However, where all involved parties have a prior arrangement, alternative coordinate reference systems can be used without risk of data being misinterpreted.

5. Bounding Box

A GeoJSON object MAY have a member named "bbox" to include information on the coordinate range for its geometries, features, or feature collections. The value of the bbox member MUST be an array of length $2 \times n$ where n is the number of dimensions represented in the contained geometries, with all axes of the most south-westerly point followed by all axes of the more north-easterly point. The axes order of a bbox follows the axes order of geometries.

The "bbox" values define shapes with edges that follow lines of constant longitude, latitude, and elevation.

Example of a 2D bbox member on a feature:

```
{
  "type": "Feature",
  "bbox": [-10.0, -10.0, 10.0, 10.0],
  "geometry": {
    "type": "Polygon",
    "coordinates": [
      [
        [-10.0, -10.0],
        [10.0, -10.0],
        [10.0, 10.0],
        [-10.0, 10.0]
      ]
    ]
  }
  //...
}
```

Example of a 2D bbox member on a feature collection:


```
{
  "type": "FeatureCollection",
  "bbox": [100.0, 0.0, 105.0, 1.0],
  "features": [
    //...
  ]
}
```

Example of a 3D bbox member with a depth of 100 meters:

```
{
  "type": "FeatureCollection",
  "bbox": [100.0, 0.0, -100.0, 105.0, 1.0, 0.0],
  "features": [
    //...
  ]
}
```

[5.1.](#) The Connecting Lines

The 4 lines of the bounding box are defined fully within the coordinate reference system; i.e. every point on the northernmost line can be expressed as

$$(\text{lon}, \text{lat}) = (\% \text{minlon}\% + (\% \text{maxlon}\% - \% \text{minlon}\%) * t, \% \text{maxlat}\%)$$

with $0 \leq t \leq 1$.

[5.2.](#) The Antimeridian

Consider a set of point features within the Fiji archipelago, straddling the antimeridian between 16 degrees S and 20 degrees S. The southwest corner of the box containing these features is at 20 degrees S and 177 degrees E, the northwest corner is at 16 degrees S and 178 degrees W. The antimeridian-spanning GeoJSON bounding box for this feature collection is

```
"bbox": [177.0, -20.0, -178.0, -16.0]
```

and covers 5 degrees of longitude.

The complementary bounding box for the same latitude band, not crossing the antimeridian, is

```
"bbox": [-178.0, -20.0, 177.0, -16.0]
```

and covers 355 degrees of longitude.

The latitude of the northeast corner is always greater than the latitude of the southwest corner, but bounding boxes that cross the antimeridian have a northeast corner longitude that is less than the longitude of the southwest corner.

5.3. The Poles

A bounding box that contains the North Pole extends from a southwest corner of %minlat% degrees N, 180 degrees W to a northeast corner of 90 degrees N, 180 degrees E. Viewed on a globe, this bounding box approximates a spherical cap.

```
"bbox": [-180.0, %minlat%, 180.0, 90.0]
```

A bounding box that contains the South Pole extends from a southwest corner of 90 degrees S, 180 degrees W to a northeast corner of %maxlat% degrees S, 180 degrees E.

```
"bbox": [-180.0, -90.0, 180.0, %maxlat%]
```

A bounding box that just touches the North Pole and forms a slice of an approximate spherical cap when viewed on a globe has as its northeast corner coordinates the easternmost longitude value and 90 degrees N.

```
"bbox": [%westlon%, %minlat%, %eastlon%, 90.0]
```

A bounding box that just touches the South Pole and forms a slice of an approximate spherical cap when viewed on a globe has as its southwest corner coordinates the westernmost longitude value and 90 degrees S.

```
"bbox": [%westlon%, -90.0, %eastlon%, %maxlat%]
```

Implementers **MUST NOT** use latitude values greater than 90 or less than -90 to imply an extent that is not a spherical cap.

6. Extending GeoJSON

6.1. Foreign Members

Members not described in this specification ("foreign members") MAY be used in a GeoJSON document. Note that support for foreign members can vary across implementations and no normative processing model for foreign members is defined. Accordingly, implementations that rely too heavily on the use of foreign members might experience reduced interoperability with other implementations.

For example, in the (abridged) feature object shown below

```
{
  "type": "Feature",
  "id": "f1",
  "geometry": {...},
  "properties": {...},
  "title": "Example Feature"
}
```

the name/value pair of "title": "Example Feature" is a foreign member. When the value of a foreign member is an object, all the descendant members of that object are themselves foreign members.

GeoJSON semantics do not apply to foreign members and their descendants, regardless of their names and values. For example, in the (abridged) feature object below

```
{
  "type": "Feature",
  "id": "f2",
  "geometry": {...},
  "properties": {...},
  "centerline": {
    "type": "LineString",
    "coordinates": [
      [-170, 10],
      [170, 11]
    ]
  }
}
```

the "centerline" member is not a GeoJSON geometry object.

7. GeoJSON Types are not Extensible

Implementations MUST NOT extend the fixed set of GeoJSON types: FeatureCollection, Feature, Point, LineString, MultiPoint, Polygon, MultiLineString, MultiPolygon, and GeometryCollection.

7.1. Semantics of GeoJSON Members and Types are not Changeable

Implementations MUST NOT change the the semantics of GeoJSON members and types.

The GeoJSON "coordinates" and "geometries" members define Geometry objects. FeatureCollection and Feature objects, respectively, MUST NOT contain a "coordinates" or "geometries" member.

The GeoJSON "geometry" and "properties" members define a Feature object. FeatureCollection and Geometry objects, respectively, MUST NOT contain a "geometry" or "properties" member.

The GeoJSON "features" member defines a FeatureCollection object. Feature and Geometry objects, respectively, MUST NOT contain a "features" member.

8. Versioning

The GeoJSON format can be extended as defined here, but no explicit versioning scheme is defined. A specification that alters the semantics of GeoJSON members or otherwise modifies the format does not create a new version of this format; instead, it defines an entirely new format that MUST NOT be identified as GeoJSON.

9. Mapping 'geo' URIs

'geo' URIs [[RFC5870](#)] identify geographic locations and precise (not uncertain) locations can be mapped to GeoJSON geometry objects.

For this section, as in [[RFC5870](#)], "%lat%", "%lon%", "%alt%", and "%unc%" are placeholders for 'geo' URI latitude, longitude, altitude, and uncertainty values, respectively.

A 'geo' URI with two coordinates and an uncertainty ('u') parameter that is absent or zero, and a GeoJSON Point geometry may be mapped to each other. A GeoJSON point is always converted to a 'geo' URI that has no uncertainty parameter.

'geo' URI:

geo:%lat%,%lon%

GeoJSON:

```
{"type": "Point", "coordinates": [%lon%, %lat%]}
```

The mapping between 'geo' URIs and GeoJSON points that specify elevation is shown below.

'geo' URI:

geo:%lat%,%lon%,%alt%

GeoJSON:

```
{"type": "Point", "coordinates": [%lon%, %lat%, %alt%]}
```


GeoJSON has no concept of uncertainty; imprecise or uncertain 'geo' URIs thus can not be mapped to GeoJSON geometries.

10. Security Considerations

GeoJSON shares security issues common to all JSON content types. See [\[RFC7159\] Section 12](#) for additional information. GeoJSON does not provide executable content.

As with other geographic data formats, e.g., [\[KMLv2.2\]](#), providing details about the locations of sensitive persons, animals, habitats, and facilities can expose them to unauthorized tracking or injury. GeoJSON does not provide privacy or integrity services; if sensitive data requires privacy or integrity protection the service must be provided externally.

11. Interoperability Considerations

11.1. I-JSON

GeoJSON texts should follow the constraints of I-JSON [\[RFC7493\]](#) for maximum interoperability.

11.2. Coordinate Precision

The size of a GeoJSON text in bytes is a major interoperability consideration and precision of coordinate values has a large impact on the size of texts. A GeoJSON text containing many detailed polygons can be inflated almost by a factor of two by increasing coordinate precision from 6 to 15 decimal places. For geographic coordinates with units of degrees, 6 decimal places (a default common in, e.g., `sprintf`) amounts to about 10 centimeters, a precision well within that of current GPS systems. Implementations should consider the cost of using a greater precision than necessary.

Furthermore the WGS 84 [\[WGS84\]](#) datum is a relatively coarse approximation of the geoid; with the height varying by up to 5m (but generally between 2 and 3 meters) higher or lower relative to a surface parallel to Earth's mean sea level.

12. IANA Considerations

The media type for GeoJSON text is "application/geo+json" and is registered in the "Media Types" registry described in [\[RFC6838\]](#). The entry for "application/vnd.geo+json" in the same registry should have its status changed to be Obsolete with a pointer to the media type "application/geo+json" and a reference added to this RFC.

Type name: application

Subtype name: geo+json

Required parameters: n/a

Optional parameters: n/a

Encoding considerations: binary

Security considerations: See [section 9](#) above

Interoperability considerations: See [section 10](#) above

Published specification: [[This document]]

Applications that use this media type: various

Additional information:

 Magic number(s): n/a

 File extension(s): .json, .geojson

 Macintosh file type code: n/a

 Object Identifiers: n/a

 Windows clipboard name: GeoJSON

 Macintosh uniform type identifier: public.geojson conforms to
 public.json

Person to contact for further information: Sean Gillies
(sean.gillies@gmail.com)

Intended usage: COMMON

Restrictions on usage: none

[13.](#) Acknowledgements

The GeoJSON format is the product of discussion on the GeoJSON mailing list, <http://lists.geojson.org/listinfo.cgi/geojson-geojson.org>, before October 2015 and the IETF's GeoJSON WG after October 2015.

Material in this document was adapted with changes from <http://geojson.org/geojson-spec.html> [GJ2008] which is licensed under <http://creativecommons.org/licenses/by/3.0/us/>.

14. References

14.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC6838] Freed, N., Klensin, J., and T. Hansen, "Media Type Specifications and Registration Procedures", [BCP 13](#), [RFC 6838](#), DOI 10.17487/RFC6838, January 2013, <<http://www.rfc-editor.org/info/rfc6838>>.
- [RFC7159] Bray, T., Ed., "The JavaScript Object Notation (JSON) Data Interchange Format", [RFC 7159](#), DOI 10.17487/RFC7159, March 2014, <<http://www.rfc-editor.org/info/rfc7159>>.
- [RFC7493] Bray, T., Ed., "The I-JSON Message Format", [RFC 7493](#), DOI 10.17487/RFC7493, March 2015, <<http://www.rfc-editor.org/info/rfc7493>>.
- [WGS84] National Imagery and Mapping Agency, "Department of Defense World Geodetic System 1984, Third Edition", 1984.

14.2. Informative References

- [GJ2008] Butler, H., Daly, M., Doyle, A., Gillies, S., Schaub, T., and C. Schmidt, "The GeoJSON Format Specification", June 2008.
- [KMLv2.2] Wilson, T., "OGC KML", OGC 07-147r2, April 2008.
- [OGCURL] Cox, S., "OGC-NA Name type specification - definitions: Part 1 - basic name", OGC 09-048r3, March 2010.
- [RFC7459] Thomson, M. and J. Winterbottom, "Representation of Uncertainty and Confidence in the Presence Information Data Format Location Object (PIDF-LO)", [RFC 7459](#), DOI 10.17487/RFC7459, February 2015, <<http://www.rfc-editor.org/info/rfc7459>>.
- [RFC7464] Williams, N., "JavaScript Object Notation (JSON) Text Sequences", [RFC 7464](#), DOI 10.17487/RFC7464, February 2015, <<http://www.rfc-editor.org/info/rfc7464>>.

- [SFSQL] OpenGIS Consortium, Inc., "OpenGIS Simple Features Specification For SQL Revision 1.1", OGC 99-049, May 1999.
- [WFSv1] Vretanos, P., "Web Feature Service Implementation Specification", OGC 02-058, May 2002.

[Appendix A.](#) Geometry Examples

Each of the examples below represents a valid and complete GeoJSON object.

[A.1.](#) Points

Point coordinates are in x, y order (easting, northing for projected coordinates, longitude, latitude for geographic coordinates):

```
{
  "type": "Point",
  "coordinates": [100.0, 0.0]
}
```

[A.2.](#) LineStrings

Coordinates of LineString are an array of positions (see [Section 3.1.1](#)):

```
{
  "type": "LineString",
  "coordinates": [
    [100.0, 0.0],
    [101.0, 1.0]
  ]
}
```

[A.3.](#) Polygons

Coordinates of a Polygon are an array of LinearRing (see [Section 3.1.6](#)) coordinate arrays. The first element in the array represents the exterior ring. Any subsequent elements represent interior rings (or holes).

No holes:


```
{
  "type": "Polygon",
  "coordinates": [
    [
      [100.0, 0.0],
      [100.0, 1.0],
      [101.0, 1.0],
      [101.0, 0.0],
      [100.0, 0.0]
    ]
  ]
}
```

With holes:

```
{
  "type": "Polygon",
  "coordinates": [
    [
      [100.0, 0.0],
      [100.0, 1.0],
      [101.0, 1.0],
      [101.0, 0.0],
      [100.0, 0.0]
    ],
    [
      [100.8, 0.8],
      [100.2, 0.8],
      [100.2, 0.2],
      [100.8, 0.2],
      [100.8, 0.8]
    ]
  ]
}
```

[A.4.](#) MultiPoints

Coordinates of a MultiPoint are an array of positions::

```
{
  "type": "MultiPoint",
  "coordinates": [
    [100.0, 0.0],
    [101.0, 1.0]
  ]
}
```


[A.5.](#) **MultiLineStrings**

Coordinates of a MultiLineString are an array of LineString coordinate arrays:

```
{
  "type": "MultiLineString",
  "coordinates": [
    [
      [100.0, 0.0],
      [101.0, 1.0]
    ],
    [
      [102.0, 2.0],
      [103.0, 3.0]
    ]
  ]
}
```

[A.6.](#) **MultiPolygons**

Coordinates of a MultiPolygon are an array of Polygon coordinate arrays:


```
{
  "type": "MultiPolygon",
  "coordinates": [
    [
      [
        [102.0, 2.0],
        [102.0, 3.0],
        [103.0, 3.0],
        [103.0, 2.0],
        [102.0, 2.0]
      ]
    ],
    [
      [
        [100.0, 0.0],
        [100.0, 1.0],
        [101.0, 1.0],
        [101.0, 0.0],
        [100.0, 0.0]
      ],
      [
        [100.2, 0.2],
        [100.8, 0.2],
        [100.8, 0.8],
        [100.2, 0.8],
        [100.2, 0.2]
      ]
    ]
  ]
}
```

[A.7.](#) GeometryCollections

Each element in the geometries array of a GeometryCollection is one of the geometry objects described above:


```
{
  "type": "GeometryCollection",
  "geometries": [{
    "type": "Point",
    "coordinates": [100.0, 0.0]
  }, {
    "type": "LineString",
    "coordinates": [
      [101.0, 0.0],
      [102.0, 1.0]
    ]
  }]
}
```

Appendix B. Changes from pre-IETF Specification

This appendix briefly summarizes non-editorial changes from the 2008 specification [[GJ2008](#)].

B.1. Normative Changes

- o Specification of coordinate reference systems has been removed, i.e., the "crs" member of [[GJ2008](#)] is no longer used.
- o In the absence of elevation values, applications sensitive to height or depth SHOULD interpret positions as being at local ground or sea level (see [Section 4](#)).
- o Implementations SHOULD NOT extend position arrays beyond 3 elements (see [Section 3.1.1](#)).
- o A line between two positions is a straight Cartesian line (see [Section 3.1.1](#)).
- o The values of a "bbox" array are "[%west%, %south%, %east%, %north%]", not "[%minx%, %miny%, %maxx%, %maxy%]" (see [Section 5](#)).
- o A Feature object's "id" member is a string or number (see [Section 3.2](#)).
- o Extensions MAY be used, but MUST NOT change the semantics of GeoJSON members and types (see [Section 6](#)).
- o GeoJSON objects MUST NOT contain the defining members of other types (see [Section 7.1](#)).
- o The media type for GeoJSON is application/geo+json.

B.2. Informative Changes

- o The definition of a GeoJSON text has been added.
- o Rules for mapping 'geo' URIs have been added.
- o A recommendation of the I-JSON [[RFC7493](#)] constraints has been added.
- o Implementers are cautioned about the effect of excessive coordinate precision on interoperability.
- o Right-hand rule orientation of polygon rings (counter-clockwise external rings, clockwise internal rings) is recommended to improve interoperability.
- o Interoperability concerns of geometry collections are noted. These objects should be used sparingly (see [Section 3.1.8](#)).

Appendix C. GeoJSON Text Sequences

All GeoJSON objects defined in this specification - FeatureCollection, Feature, and Geometry - consist of exactly one JSON object. However, there may be circumstances in which applications need to represent sets or sequences of these objects (over and above the grouping of Feature objects in a FeatureCollection), e.g. in order to efficiently "stream" large numbers of Feature objects. The definition of such sets or sequences is outside the scope of this specification.

If such a representation is needed, a new media type is required that has the ability to represent these sets or sequences. When defining such a media type, it may be useful to base it on "JSON Text Sequences" [[RFC7464](#)], leaving the foundations of how to represent multiple JSON objects to that specification, and only defining how it applies to GeoJSON objects.

Authors' Addresses

H. Butler
Hobu Inc.

Email: howard@hobu.co

M. Daly
Cadcorp

Email: martin.daly@cadcorp.com

A. Doyle

Email: adoyle@intl-interfaces.com

S. Gillies
Mapbox

Email: sean.gillies@gmail.com

URI: <http://sgillies.net>

S. Hagen
Rheinaustr. 62
Bonn 53225
DE

Email: stefan@hagen.link

URI: <http://stefan-hagen.website/>

T. Schaub
Planet Labs

Email: tim.schaub@gmail.com

