

Internet Engineering Task Force  
Internet Draft  
Expiration: June 8th, 2004  
File: [draft-ietf-geopriv-dhcp-lci-option-03.txt](#)

J. Polk  
J. Schnizlein  
M. Linsner  
Cisco Systems

Dynamic Host Configuration Protocol Option for  
Coordinate-based Location Configuration Information

December 8th, 2003

Status of this Memo

This document is an Internet-Draft and is in full conformance with all provisions of [Section 10 of RFC2026](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/lid-abstracts.txt>

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

Abstract

This document specifies a Dynamic Host Configuration Protocol Option for the coordinate-based geographic location of the client. The Location Configuration Information (LCI) includes latitude, longitude, and altitude, with resolution indicators for each. The reference datum for these values is also included.

Table of Contents

- [1.](#) Introduction . . . . . [2](#)
- [1.1](#) Conventions . . . . . [3](#)
- [1.2](#) Motivation . . . . . [3](#)
- [1.3](#) Rationale . . . . . [4](#)
- [2.](#) Location Configuration Information (LCI) Elements . . . . . [4](#)
- [2.1](#) Elements of the Location Configuration Information . . . . . [5](#)
- [3.](#) Security Considerations . . . . . [8](#)
- [4.](#) IANA Considerations . . . . . [8](#)
- [5.](#) Acknowledgements . . . . . [9](#)
- [Appendix](#) Calculations of Imprecision possible with the DHC LCI . 9
- [A.1](#) LCI of "White House" (Example 1) . . . . . [9](#)
- [A.2](#) LCI of "Sears Tower" (Example 2) . . . . . [12](#)
- [6.](#) Normative References . . . . . [12](#)
- [7.](#) Informational References . . . . . [13](#)
- [8.](#) Author Information . . . . . [13](#)

[1.](#) Introduction

This document specifies a Dynamic Host Configuration Protocol [[1](#)] Option for coordinate-based geographic location of the client, to be provided by the server.

The DHCP server is assumed to have determined the location from the Circuit-ID Relay Agent Information Option (RAIO) defined (as SubOpt 1) in [[2](#)]. In order to translate the circuit (switch port identifier) into a location, the DHCP server is assumed to have access to a service that maps from circuit-ID to the location at which the circuit connected to that port terminates in the building; for example, the location of the wall jack.

An important feature of this specification is that after the relevant DHC exchanges have taken place, the location information is stored on the end device rather than somewhere else, where retrieving it might be difficult in practice.

Another important feature of this LCI is its inclusion of a resolution parameter for each of the dimensions of location. Because this resolution parameter need not apply to all dimensions equally, a resolution value is included for each of the 3 location

elements.

This resolution method provides a natural ability for the device to hide from the center point of the bounding area as this resolution method is determined via the inherent effects of binary representation; or, this resolution mechanism could be used to define a geographic area. This would be useful when a group of clients would want to be known as the same geo-location, possibly all users in a room of a building would use the same LCI value.

Then the using application could use that value as a key for lookup in another data source. This is similar to one of the mechanisms utilized in the North American E911 systems today.

Resolution does not define how Geographic Privacy policy should relate to precision.

The resulting location information using this resolution method is a small fixed length Configuration Information that can be easily carried in protocols, such as DHCP, which have limited packet size because this LCI is only 18 bytes long.

Finally, the appendix this document provides some arithmetic examples of the implication of different resolution values on the La/Lo/Alt.

## [1.1](#) Conventions used in this document

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [\[3\]](#).

## [1.2](#) Motivation

As applications such as IP Telephony are replacing conventional telephony, users are expecting the same (or greater) level of services with the new technology. One service offered by conventional telephony that is missing, in any standardized fashion, within IP Telephony is for a user to be automatically located by emergency responders, in a timely fashion, when the user summons help (by dialing 911 in North America, for example). Unless strict administrative rules are followed, the mobility of a wired Ethernet

device within a campus negates any opportunity for an emergency responder to locate the device with any degree of expediency. Users do not want to give up the mobility IP Telephony offers. Informing the host device of its geo-location at host configuration time will allow the device to utilize this geo-location information to inform others of it's current geo-location, if the user and/or application so desires.

The goal of this option is to enable a wired Ethernet host to obtain its location, which it could provide to an emergency responder, as one example.

Wireless hosts can utilize this option to gain knowledge of the location of the radio access point used during host configuration, but would need some more exotic mechanisms, maybe GPS, or maybe a future DHCP option, which includes a list of geo-locations like that defined here, containing the locations of the radio access points

that are close to the client.

### 1.3 Rationale

Within the LCI described here, Latitude and Longitude are represented in fixed-point 2s-complement binary degrees, for the economy of a smaller option size compared to a string encoding of digits in [7]. The integer parts of these fields are 9 bits long to accommodate +/- 180 degrees. The fractional part is 25 bits long, better than the precision of 7 decimal digits. Each parameter is 40 bits total, in length.

Altitude is determined by the Altitude Type (AT) indicated by the AT field, which is 4 bits long. Two Altitude Types are defined here, meters (code=1) and floors (code=2), both of which are 2s-complement fixed-point with 8 bits of fraction. Additional Altitude Types MAY be assigned by IANA. The "floors" Altitude Type is provided because altitude in meters may not be known within a building, and a floor indication may be more useful.

GPS systems today can use WGS84 for horizontal and vertical datums, [6] defines WGS84 as a three-dimensional datum. For other datum values that do not include a vertical component, both the horizontal and vertical datum of reference will be specified in the IANA record.


Each of these 3 elements is preceded by an accuracy sub-field of 6 bits, indicating the number of bits of resolution. This resolution sub-field accommodates the desire by some to easily adjust the precision of a reported location. Contents beyond the claimed resolution MAY be randomized to obscure greater precision that might be available.

## 2. DHC Location Configuration Information Elements

DHCP is a binary Protocol; using protocols of LCI are likely to be text based. Since most coordinate systems translate fairly easily between binary-based and text-based location output (even emergency services within the US), translation/conversion is a non-issue with DHCP's binary format.

This binary format provides a fortunate benefit in a mechanism for making a true/correct location coordinate imprecise. It further provides the capability to have this binary representation be deterministically imprecise.

The LCI format is as follows:



## [2.1](#) Elements of the Location Configuration Information

Code TBD: The code for this DHCP option.

16: The length of this option is 16 bytes.

LaRes: Latitude resolution. 6 bits indicating the number of valid bits in the fixed-point value of Latitude.

This value is the number of high-order Latitude bits that should be considered valid. Any bits entered to the right of this limit should not be considered valid and might be purposely false, or zeroed by the sending.

The examples below in [section 4.0](#), are to illustrate that a smaller value in the resolution field increases the area within which the device is located).

LaRes does not define how Geographic Privacy policy should relate to precision.

Values of resolution above decimal 34 are Undefined and reserved because that is the largest number of bits in the Latitude field.

Latitude: a 34 bit fixed point value consisting of 9 bits of integer and 25 bits of fraction. Latitude SHOULD be normalized to within +/- 90 degrees. Positive numbers are north of the equator and negative numbers are south of the equator.

A value of 2 in the LaRes field indicates a precision of no greater than 1/6th that of the globe (detailed in the first example in [section 4.0](#)). A value of 34 in the LaRes field indicates a precision of about 3.11 mm in Latitude at the equator.

LoRes: Longitude resolution. 6 bits indicating the number of valid bits in the fixed-point value of Longitude.

This value is the number of high-order Longitude bits that should be considered valid. Any bits entered to the right of this limit should not be considered valid and might be purposely false, or zeroed by the sending.

LoRes does not define how Geographic Privacy policy should relate to

precision.

Values above decimal 34 are undefined and reserved.

Longitude: a 34 bit fixed point value consisting of 9 bits of integer and 25 bits of fraction. Longitude SHOULD be normalized to within +/- 180 degrees. Positive values are East of the prime meridian and negative (2s complement) numbers are West of the prime meridian.

A value of 2 in the LoRes field indicates precision of no greater than 1/6th that of the globe (see first example in [section 4.0](#)). A value of 34 in the LoRes field indicates a precision of about 2.42 mm in longitude (at the equator). Because lines of longitude converge at the poles, the distance is smaller (better precision) for locations away from the equator.

Altitude: A 30 bit value defined by the AT field

AltRes: Altitude resolution. 6 bits indicating the number of valid bits in the altitude. Values above 30 (decimal) are undefined and reserved.

AltRes does not define how Geographic Privacy policy should relate to precision.

AT: Altitude Type for altitude. Codes defined are:

1: Meters - in 2s-complement fixed-point 22-bit integer part with 8-bit fraction

If AT = 1, an AltRes value 0.0 would indicate unknown altitude. The most precise Altitude would have an AltRes value of 30. Many values of AltRes would obscure any variation due to vertical datum differences.

2: Floors - in 2s-complement fixed-point 22-bit integer part with 8-bit fraction

AT = 2 for Floors enables representing altitude in a form more relevant in buildings which have different floor-to-floor

dimensions. An altitude coded as AT=2, AltRes = 30, and Altitude = 0.0 is meaningful even outside a building, and represents ground

level at the given latitude and longitude. Inside a building, 0.0 represents the floor level associated with ground level at the main entrance. This document defines a number; one must arrive at the number by counting floors from the floor defined to be 0.0.

The values represented by this AT will be of local significance. Since buildings and floors can vary due to lack of common control, the values chosen to represent the characteristics of an individual building will be derived and agreed upon by the operator of the building and the intended users of the data. Attempting to standardize this type of function is beyond the scope this document.

Sub-floors can be represented by non-integer values. Example: a mezzanine between floor 1 and floor 2 could be represented as a value=1.1. Example: (2) mezzanines between floor 4 and floor 5 could be represented as values=4.1 and 4.2 respectively.

Floors located below ground level could be represented by negative values.

Larger values represent floors that are above (higher in altitude) floors with lower values.

The AltRes field SHOULD be set to maximum precision when AT = 2 (floors) when a floor value is included in the DHCP Reply, or the AT = 0 to denote the floor isn't known.

Any additional LCI Altitude Types(s) to be defined for use via this DHC Option MUST be done through a Standards Track RFC.

Datum: The Map Datum used for the coordinates given in this Option

The datum must include both a horizontal and a vertical reference. Since the WGS 84 reference datum is three-dimensional, it includes both. For any additional datum parameters, the datum codepoint must specify both horizontal datum and vertical datum references.

The Datum byte has 256 possibilities, of which 3 are to be registered with IANA by this document (all derived from specification in [\[5\]](#)):

- 1: WGS 84 (Geographical 3D) - World Geodesic System 1984, CRS Code 4327, Prime Meridian Name: Greenwich
- 2: NAD83 - North American Datum 1983, CRS Code 4269, Prime Meridian Name: Greenwich; The associated vertical datum is the North American Vertical Datum of 1988 (NAVD88)

Internet Draft

DHCP Option for Coordinate LCI

Dec 8th, 2003

This datum pair to be used when referencing locations on land, not near tidal water (which would use Datum = 3 below)

- 3: NAD83 - North American Datum 1983, CRS Code 4269, Prime Meridian Name: Greenwich; The associated vertical datum is Mean Lower Low Water (MLLW)

This datum pair to be used when referencing locations on water/sea/ocean

Any additional LCI datum(s) to be defined for use via this DHC Option MUST be done through a Standards Track RFC.

### 3. Security Considerations

Where critical decisions might be based on the value of this GeoLoc option, DHCP authentication in [\[4\]](#) SHOULD be used to protect the integrity of the DHCP options.

Since there is no privacy protection for DHCP messages, an eavesdropper who can monitor the link between the DHCP server and requesting client can discover this LCI.

To minimize the unintended exposure of location information, the LCI option SHOULD be returned by DHCP servers only when the DHCP client has included this option in its 'parameter request list' ([section 3.5 \[1\]](#)).

When implementing a DHC server that will serve clients across an uncontrolled network, one should consider the potential security risks.

### 4. IANA Considerations

IANA has assigned a DHCP option code of TBD for the GeoLoc option defined in this document.

The GeoLoc Option defines two fields for which IANA is to maintain a registry: The Altitude (AT) field (see [Section 2](#)) and the Datum field (see [Section 2](#)). The datum indicator MUST include

specification of both horizontal and vertical datum. New values for the Altitude (AT) field are assigned through "Standards Action" [[RFC 2434](#)]. The initial values of the Altitude registry are as follows:

AT = 1 meters of Altitude defined by the vertical datum specified.

AT = 2 building Floors of Altitude.

Datum = 1 denotes the vertical datum WGS 84 as defined by the EPSG as their CRS Code 4327; CRS Code 4327 also specifies WGS 84 as the vertical datum

Datum = 2 denotes the vertical datum NAD83 as defined by the EPSG as their CRS Code 4269; North American Vertical Datum of 1988 (NAVD88) is the associated vertical datum for NAD83

Datum = 3 denotes the vertical datum NAD83 as defined by the EPSG as their CRS Code 4269; Mean Lower Low Water (MLLW) is the associated vertical datum for NAD83

Any additional LCI datum(s) to be defined for use via this DHC Option MUST be done through a Standards Track RFC.

## 5. Acknowledgements

The authors would like to thank Patrik Falstrom, Ralph Droms, Ted Hardie, Jon Peterson and Nadine Abbott for their inputs and constructive comments regarding this document. Additionally, the authors would like to thank Greg Troxel for the education on vertical datums, and to Carl Reed.

## Appendix: Calculations of Imprecision possible with the DHC LCI

The following examples for two different locations demonstrate how the Resolution values for Latitude, Longitude and Altitude can be used. In both examples the geo-location values were derived from maps using the WGS84 map datum, therefore in these examples, the datum field would have a value = 1 (00000001, or 0x01).



Pole. This would cover an area of about one-sixth of the globe, approximately 20 million square nautical miles (nm).

If: LaRes is expressed as value 3 (0x03 or 000011) and LoRes is expressed as value 3, (0x03 or 000011) then it would describe a geo-location area that is north from the equator to 63 degrees north, and -65 degrees to -128 degrees longitude. This area includes south of a line from Anchorage, AL to eastern Nunavut, CN. and from the Amazons of northern Brazil to approximately 4400km south-southwest of Los Angeles, CA. This area would include North America, Central America, and parts of Venezuela and Columbia, except portions of Alaska and northern and eastern Canada, approximately 10 million square nm.

If: LaRes is expressed as value 5 (0x05 or 000101) and LoRes is expressed as value 5 (0x05 or 000101), then it would describe a geo-location area that is latitude 32 north of the equator to latitude 48 and extends from -64 degrees to -80 degrees longitude. This is approximately an east-west boundary of a time zone, an area of approximately 700,000 square nm.

If: LaRes is expressed as value 9 (0x09 or 001001) and LoRes is expressed as value 9 (0x09 or 001001), which includes all the

integer bits, then it would describe a geo-location area that is latitude 38 north of the equator to latitude 39 and extends from -77 degrees to -78 degrees longitude. This is an area of approximately 9600 square km (111.3km x 86.5km).

If: LaRes is expressed as value 18 (0x12 or 010010) and LoRes is expressed as value 18 (0x12 or 010010), then it would describe a geo-location area that is latitude 38.8984375 north to latitude 38.9003906 and extends from -77.0390625 degrees to -77.0371094 degrees longitude. This is an area of approximately 36,600 square meters (169m x 217m).

If: LaRes is expressed as value 22 (0x16 or 010110) and LoRes is expressed as value 22 (0x16 or 010110), then it would describe a geo-location area that is latitude 38.896816 north to latitude 38.8985596 and extends from -77.0372314 degrees to -77.0371094 degrees longitude. This is an area of approximately 143 square meters (10.5m x 13.6m).

If: LaRes is expressed as value 28 (0x1c or 011100) and LoRes is

expressed as value 28 (0x1c or 011100), then it would describe a geo-location area that is latitude 38.8986797 north to latitude 38.8986816 and extends from -77.0372314 degrees to -77.0372296 degrees longitude. This is an area of approximately 339 square centimeters (20.9cm x 16.23cm).

If: LaRes is expressed as value 30 (0x1e or 011110) and LoRes is expressed as value 30 (0x1e or 011110), then it would describe a geo-location area that is latitude 38.8986797 north to latitude 38.8986802 and extends from -77.0372300 degrees to -77.0372296 degrees longitude. This is an area of approximately 19.5 square centimeters (50mm x 39mm).

If: LaRes is expressed as value 34 (0x22 or 100010) and LoRes is expressed as value 34 (0x22 or 100010), then it would describe a geo-location area that is latitude 38.8986800 north to latitude 38.8986802 and extends from -77.0372300 degrees to -77.0372296 degrees longitude. This is an area of approximately 7.5 square millimeters (3.11mm x 2.42mm).

In the (White House) example, the requirement of emergency responders in North America via their NENA Model Legislation [8], could be met by a LaRes value of 21 and a LoRes value of 20. This would yield a geo-location that is latitude 38.8984375 north to latitude 38.8988616 north and longitude -77.0371094 to longitude -77.0375977. This is an area of approximately 89 feet by 75 feet or 6669 square feet, which is very close to the 7000 square feet asked for by NENA. In this example a service provider could enforce that a device send a Location Configuration Information with this minimum amount of resolution for this particular location when calling emergency services.

## [A.2](#) Location Configuration Information of "Sears Tower" (Example 2)

Postal Address:  
Sears Tower  
103rd Floor  
233 S. Wacker Dr.  
Chicago, IL 60606

Viewing the Chicago area from the Observation Deck of the Sears Tower.

Latitude 41.87884 degrees North (or +41.87884 degrees)  
Using 2s complement, 34 bit fixed point, 25 bit fraction  
Latitude = 0x053c1f751,  
Latitude = 0001010011110000011111011101010001

Longitude 87.63602 degrees West (or -87.63602 degrees)  
Using 2s complement, 34 bit fixed point, 25 bit fraction  
Longitude = 0xf50ba5b97,  
Longitude = 1101010000101110100101101110010111

Altitude 103

In this example we are inside a structure, therefore we will assume an altitude value of 103 to indicate the floor we are on. The Altitude Type value is 2 indicating floors. The AltRes field would indicate that all bits in the Altitude field are true, as we want to accurately represent the floor of the structure where we are located.

AltRes = 30, 0x1e, 011110  
AT = 2, 0x02, 000010  
Altitude = 103, 0x00006700, 0000000000000000110011100000000

For the accuracy of the latitude and longitude, the best information available to us was supplied by a generic mapping service that shows a single geo-loc for all of the Sears Tower. Therefore we are going to show LaRes as value 18 (0x12 or 010010) and LoRes as value 18 (0x12 or 010010). This would be describing a geo-location area that is latitude 41.8769531 to latitude 41.8789062 and extends from -87.6367188 degrees to -87.6347657 degrees longitude. This is an area of approximately 373412 square feet (713.3 ft. x 523.5 ft.).

## 6. Normative References

- [1] Droms R., "Dynamic Host Configuration Protocol", [RFC 2131](#), March 1997

- [2] Patrick M., "DHCP Relay Agent Information Option", [RFC 3046](#), January 2001

- [3] Bradner S., "Key words for use in RFCs to Indicate Requirement

Levels", [RFC 2119](#), March 1997

- [4] Droms R., "Authentication for DHCP Messages", [RFC 3118](#), June 2001
- [5] European Petroleum Survey Group, <http://www.epsg.org/> and <http://www.ihsenergy.com/epsg/geodetic2.html>
- [6] World Geodetic System 1984 (WGS 84), MIL-STD-2401, <http://164.214.2.59/publications/specs/printed/WGS84/wgs84.html> and <http://www.wgs84.com/>

## 7. Informational References

- [7] Farrell C., Schulze M., Pleitner S. and Baldoni D., "DNS Encoding of Geographical Location", [RFC 1712](#), November 1994.
- [8] National Emergency Number Association (NENA) [www.nena.org](http://www.nena.org)  
NENA Technical Information Document on Model Legislation  
Enhanced 911 for Multi-Line Telephone Systems  
([http://www.nena.org/9%2D1%2D1techstandards/TechInfoDocs/MLTS\\_ModLeg\\_Nov200.PDF](http://www.nena.org/9%2D1%2D1techstandards/TechInfoDocs/MLTS_ModLeg_Nov200.PDF))

## 8. Author Information

James M. Polk  
Cisco Systems  
2200 East President George Bush Turnpike  
Richardson, Texas 75082 USA [jmpolk@cisco.com](mailto:jmpolk@cisco.com)

John Schnizlein  
Cisco Systems  
9123 Loughran Road  
Fort Washington, MD 20744 USA [john.schnizlein@cisco.com](mailto:john.schnizlein@cisco.com)

Marc Linsner  
Cisco Systems  
Marco Island, FL 34145 USA [marc.linsner@cisco.com](mailto:marc.linsner@cisco.com)

## Intellectual Property Statement

The IETF takes no position regarding the validity or scope of any intellectual property or other rights that might be claimed to pertain to the implementation or use of the technology described in

this document or the extent to which any license under such rights might or might not be available; neither does it represent that it has made any effort to identify any such rights. Information on the IETF's procedures with respect to rights in standards-track and standards-related documentation can be found in [BCP-11](#). Copies of claims of rights made available for publication and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF Secretariat.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights which may cover technology that may be required to practice this standard. Please address the information to the IETF Executive Director.

#### Full Copyright Statement

"Copyright (C) The Internet Society (February 23rd, 2001).  
All Rights Reserved.

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this paragraph are included on all such copies and derivative works. However, this document itself may not be modified in any way, such as by removing the copyright notice or references to the Internet Society or other Internet organizations, except as needed for the purpose of developing Internet standards in which case the procedures for copyrights defined in the Internet Standards process must be followed, or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by the Internet Society or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE."

The Expiration date for this Internet Draft is:

June 8th, 2004

Polk & Schnizlein & Linsner

[Page 14]