HTTP M. Nottingham Internet-Draft Fastly

Intended status: Standards Track

Expires: February 12, 2021

The Cache-Status HTTP Response Header Field draft-ietf-httpbis-cache-header-05

Abstract

To aid debugging, HTTP caches often append header fields to a response explaining how they handled the request. This specification codifies that practice and updates it to align with HTTP's current caching model.

Note to Readers

RFC EDITOR: please remove this section before publication

Discussion of this draft takes place on the HTTP working group mailing list (ietf-http-wg@w3.org), which is archived at https://lists.w3.org/Archives/Public/ietf-http-wg/ [1].

Working Group information can be found at https://httpwg.org/ [2]; source code and issues list for this draft can be found at https://github.com/httpwg/http-extensions/labels/cache-header [3].

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at https://datatracker.ietf.org/drafts/current/.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on February 12, 2021.

August 11, 2020

Copyright Notice

Copyright (c) 2020 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to <u>BCP 78</u> and the IETF Trust's Legal Provisions Relating to IETF Documents

(https://trustee.jetf.org/license-info) in effect on the date

(https://trustee.ietf.org/license-info) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

\underline{L} . Introduction	2
<u>1.1</u> . Notational Conventions	3
2. The Cache-Status HTTP Response Header Field	3
${2.1 \over 2.1}$. The hit parameter	4
<u>2.2</u> . The fwd parameter	4
2.3. The fwd-status parameter	5
2.4. The ttl parameter	5
$\underline{2.5}$. The stored parameter	5
2.6. The collapsed parameter	5
<u>2.7</u> . The key parameter	<u>5</u>
2.8. The detail parameter	<u>5</u>
<u>3</u> . Examples	6
4. Defining New Proxy-Status Parameters	7
$\underline{5}$. IANA Considerations	7
$\underline{6}$. Security Considerations	7
<u>7</u> . References	8
<u>7.1</u> . Normative References	8
7.2. Informative References	9
<u>7.3</u> . URIs	9
Author's Address	9

1. Introduction

To aid debugging, HTTP caches often append header fields to a response explaining how they handled the request. Unfortunately, the semantics of these headers are often unclear, and both the semantics and syntax used vary greatly between implementations.

This specification defines a single, new HTTP response header field, "Cache-Status" for this purpose.

1.1. Notational Conventions

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in BCP 14 [RFC2119] [RFC8174] when, and only when, they appear in all capitals, as shown here.

This document uses ABNF as defined in [RFC5234], along with the "%s" extension for case sensitivity defined in [RFC7405].

2. The Cache-Status HTTP Response Header Field

The Cache-Status HTTP response header indicates caches' handling of the request corresponding to the response it occurs within.

Its value is a List [I-D.ietf-httpbis-header-structure]:

Cache-Status = sf-list

Each member of the list represents a cache that has handled the request. The first member of the list represents the cache closest to the origin server, and the last member of the list represents the cache closest to the client (possibly including the user agent's cache itself, if it chooses to append a value).

Caches determine when it is appropriate to add the Cache-Status header field to a response. Some might add it to all responses, whereas others might only do so when specifically configured to, or when the request contains a header that activates a debugging mode.

When adding a value to the Cache-Status header field, caches SHOULD preserve the existing contents of the header field, to allow debugging of the entire chain of caches handling the request.

Each list member identifies the cache that inserted that value, and MUST be a String or Token. Depending on the deployment, this might be a product or service name (e.g., ExampleCache or "Example CDN"), a hostname ("cache-3.example.com"), and IP address, or a generated string.

Each member of the list can also have parameters that describe that cache's handling of the request. While all of these parameters are OPTIONAL, caches are encouraged to provide as much information as possible.

This specification defines these parameters:

hit = sf-boolean

fwd = sf-token

fwd-status = sf-integer

ttl = sf-integer

stored = sf-boolean

collapsed = sf-boolean

key = sf-string

detail = sf-token / sf-string

2.1. The hit parameter

"hit", when true, indicates that the request was satisfied by the cache; i.e., it did not go forward, and the response was obtained from the cache. A response that originally was produced by the origin but was modified by the cache (for example, a 304 or 206 status code) is still considered a hit.

"hit" and "fwd" are exclusive; only one of them should appear on each list member.

2.2. The fwd parameter

"fwd" indicates that the request went forward towards the origin, and why.

The following values are defined to explain why the request went forward:

- o uri-miss The cache did not contain any responses that matched the request URI
- o vary-miss The cache contained a response that matched the request URI, but could not select a response based upon this request's headers and stored Vary headers.
- o miss The cache did not contain any responses that could be used to satisfy this request (to be used when an implementation cannot distinguish between uri-miss and vary-miss)
- o stale The cache was able to select a response for the request, but it was stale
- o request The cache was able to select a fresh response for the request, but client request headers (e.g., Cache-Control request directives) did not allow its use
- o bypass The cache was configured to not handle this request

2.3. The fwd-status parameter

"fwd-status" indicates what status code the next hop server returned in response to the request. Only meaningful when "fwd" is present; if "fwd-status" is not present but "fwd" is, it defaults to the status code sent in the response.

This parameter is useful to distinguish cases when the next hop server sends a 304 Not Modified response to a conditional request, or a 206 Partial Response because of a range request.

2.4. The ttl parameter

"ttl" indicates the response's remaining freshness lifetime as calculated by the cache, as an integer number of seconds, measured when the response is sent by the cache. This includes freshness assigned by the cache; e.g., through heuristics, local configuration, or other factors. May be negative, to indicate staleness.

2.5. The stored parameter

"stored" indicates whether the cache stored the response; a true value indicates that it did. Only meaningful when fwd is present.

2.6. The collapsed parameter

"collapsed" indicates whether this request was collapsed together with one or more other forward requests; if true, the response was successfully reused; if not, a new request had to be made. If not present, the request was not collapsed with others. Only meaningful when fwd is present.

2.7. The key parameter

"key" conveys a representation of the cache key used for the response. Note that this may be implementation-specific.

2.8. The detail parameter

"detail" allows implementations to convey additional information not captured in other parameters; for example, implementation-specific states, or other caching-related metrics.

For example:

Cache-Status: ExampleCache; hit; detail=MEMORY

The semantics of a detail parameter are always specific to the cache that sent it; even if a member of details from another cache shares the same name, it might not mean the same thing.

This parameter is intentionally limited. If an implementation needs to convey additional information, they are encouraged to register extension parameters (see <u>Section 4</u>) or define another header field.

3. Examples

The most minimal cache hit: Cache-Status: ExampleCache; hit ... but a polite cache will give some more information, e.g.: Cache-Status: ExampleCache; hit; ttl=376 A stale hit just has negative freshness: Cache-Status: ExampleCache; hit; ttl=-412 Whereas a complete miss is: Cache-Status: ExampleCache; fwd=uri-miss A miss that successfully validated on the back-end server: Cache-Status: ExampleCache; fwd=stale; fwd-status=304 A miss that was collapsed with another request: Cache-Status: ExampleCache; fwd=uri-miss; collapsed A miss that the cache attempted to collapse, but couldn't: Cache-Status: ExampleCache; fwd=uri-miss; collapsed=?0 Going through two layers of caching, both of which were hits, and the second collapsed with other requests: Cache-Status: OriginCache; hit; ttl=1100; collapsed, "CDN Company Here"; hit; ttl=545

4. Defining New Proxy-Status Parameters

New Cache-Status Parameters can be defined by registering them in the HTTP Cache-Status Parameters registry.

Registration requests are reviewed and approved by a Designated Expert, as per [RFC8126], Section 4.5. A specification document is appreciated, but not required.

The Expert(s) should consider the following factors when evaluating requests:

- o Community feedback
- o If the value is sufficiently well-defined
- o Generic parameters are preferred over vendor-specific, application-specific or deployment-specific values. If a generic value cannot be agreed upon in the community, the parameter's name should be correspondingly specific (e.g., with a prefix that identifies the vendor, application or deployment).

Registration requests should use the following template:

- o Name: [a name for the Cache-Status Parameter that matches key]
- o Description: [a description of the parameter semantics and value]
- o Reference: [to a specification defining this parameter]

See the registry at https://iana.org/assignments/http-cache-status [4] for details on where to send registration requests.

5. IANA Considerations

Upon publication, please create the HTTP Cache-Status Parameters registry at https://iana.org/assignments/http-cache-status [5] and populate it with the types defined in Section 2; see Section 4 for its associated procedures.

6. Security Considerations

Attackers can use the information in Cache-Status to probe the behaviour of the cache (and other components), and infer the activity of those using the cache. The Cache-Status header field may not create these risks on its own, but can assist attackers in exploiting them.

For example, knowing if a cache has stored a response can help an attacker execute a timing attack on sensitive data. Exposing the cache key can help an attacker understand modifications to the cache key, which may assist cache poisoning attacks. See [ENTANGLE] for details.

The underlying risks can be mitigated with a variety of techniques (e.g., use of encryption and authentication; avoiding the inclusion of attacker-controlled data in the cache key), depending on their exact nature.

To avoid assisting such attacks, the Cache-Status header field can be omitted, only sent when the client is authorized to receive it, or only send sensitive information (e.g., the key parameter) when the client is authorized.

7. References

7.1. Normative References

- [I-D.ietf-httpbis-header-structure]
 Nottingham, M. and P. Kamp, "Structured Field Values for
 HTTP", draft-ietf-httpbis-header-structure-19 (work in
 progress), June 2020.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate
 Requirement Levels", BCP 14, RFC 2119,
 DOI 10.17487/RFC2119, March 1997,
 https://www.rfc-editor.org/info/rfc2119.

- [RFC8126] Cotton, M., Leiba, B., and T. Narten, "Guidelines for Writing an IANA Considerations Section in RFCs", BCP 26, RFC 8126, DOI 10.17487/RFC8126, June 2017, https://www.rfc-editor.org/info/rfc8126.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in RFC
 2119 Key Words", BCP 14, RFC 8174, DOI 10.17487/RFC8174,
 May 2017, https://www.rfc-editor.org/info/rfc8174.

7.2. Informative References

[ENTANGLE]

Kettle, J., "Web Cache Entanglement: Novel Pathways to Poisoning", n.d., https://i.blackhat.com/USA-20/Wednesday/us-20-Kettle-Web-Cache-Entanglement-Novel-Pathways-To-Poisoning-wp.pdf>.

7.3. URIS

- [1] https://lists.w3.org/Archives/Public/ietf-http-wg/
- [2] https://httpwg.org/
- [3] https://github.com/httpwg/http-extensions/labels/cache-header
- [4] https://iana.org/assignments/http-cache-status
- [5] https://iana.org/assignments/http-cache-status

Author's Address

Mark Nottingham
Fastly
made in
Prahran, VIC
Australia

Email: mnot@mnot.net

URI: https://www.mnot.net/