

HTTP Working Group
Internet-Draft
Intended status: Experimental
Expires: September 30, 2017

K. Oku
DeNA Co., Ltd.
March 29, 2017

An HTTP Status Code for Indicating Hints
draft-ietf-httpbis-early-hints-01

Abstract

This memo introduces an informational status code for HTTP that can be used for indicating hints to help a client start making preparations for processing the final response.

Note to Readers

Discussion of this draft takes place on the HTTP working group mailing list (ietf-http-wg@w3.org), which is archived at <https://lists.w3.org/Archives/Public/ietf-http-wg/> .

Working Group information can be found at <https://httpwg.github.io/> ; source code and issues list for this draft can be found at <https://github.com/httpwg/http-extensions/labels/early-hints> .

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on September 30, 2017.

Copyright Notice

Copyright (c) 2017 IETF Trust and the persons identified as the document authors. All rights reserved.

Internet-Draft

Early Hints

March 2017

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	2
1.1.	Notational Conventions	3
2.	103 Early Hints	3
3.	Security Considerations	4
4.	IANA Considerations	4
5.	Acknowledgements	4
6.	Changes	4
6.1.	Since draft-ietf-httpbis-early-hints-00	4
7.	References	5
7.1.	Normative References	5
7.2.	Informative References	5
	Author's Address	5

[1.](#) Introduction

Most if not all of the web pages processed by a web browser contain links to external resources that need to be fetched prior to rendering the documents. Therefore, it is beneficial to send such links as early as possible in order to minimize the time spent until the browser becomes possible to render the document. Link header of type "preload" ([\[Preload\]](#)) can be used to indicate such links within the response headers of an HTTP response.

However, it is not always possible for an origin server to send a response immediately after receiving a request. In fact, it is often the contrary. There are many deployments in which an origin server needs to query a database before generating a response. It is also not unusual for an origin server to delegate a request to an upstream HTTP server running at a distant location.

The dilemma here is that even though it is preferable for an origin

server to send some headers as soon as it receives a request, it cannot do so until the status code and the headers of the final HTTP response is determined.

HTTP/2 ([[RFC7540](#)]) push can be used as a solution to the issue, but has its own limitations. The resources that can be pushed using HTTP/2 are limited to those belonging to the same origin. Also, it is impossible to send only the links of the resources using HTTP/2 push. Sending HTTP responses for every resource is an inefficient way of using bandwidth, especially when a caching server exists as an intermediary.

This memo defines a status code for sending an informational response ([[RFC7231](#)], [section 6.2](#)) that contains headers that are likely to be included in the final response. A server can send the informational response containing some of the headers to help the client start making preparations for processing the final response, and then run time-consuming operations to generate the final response. The informational response can also be used by an origin server to trigger HTTP/2 push at an caching intermediary.

[1.1](#). Notational Conventions

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

[2](#). 103 Early Hints

This informational status code indicates the client that the server is likely to send a final response with the headers included in the informational response.

A server MUST NOT include Content-Length, Transfer-Encoding, or any hop-by-hop headers ([[RFC7230](#)], [section 6.1](#)) in the informational response using the status code.

A client MAY speculatively evaluate the headers included in the informational response while waiting for the final response. For example, a client may recognize the link header of type preload and

start fetching the resource. However, the evaluation MUST NOT affect how the final response is processed; the client must behave as if it had not seen the informational response. A client MUST NOT process the headers included in the response as if they belonged to the informational response.

An intermediary MAY drop the informational response. It MAY send HTTP/2 ([RFC7540]) push responses using the information found in the informational response.

3. Security Considerations

Clients may have issues handling Early Hints, since informational response is rarely used for requests not including an Expect header ([RFC7231], section 5.1.1).

An HTTP/1.1 client that mishandles the informational response as a final response is likely to consider all the responses to the succeeding requests sent over the same connection to be part of the final response. Such behavior may constitute a cross-origin information disclosure vulnerability in case the client multiplexes requests to different origins onto a single persistent connection.

Therefore, a server might refrain from sending Early Hints over HTTP/1.1 unless when the client is known to handle informational responses correctly.

HTTP/2 clients are less likely to suffer from incorrect framing since handling of the response headers does not affect how the end of the response body is determined.

4. IANA Considerations

If Early Hints is standardized, the HTTP Status Codes Registry should be updated with the following entries:

- o Code: 103
- o Description: Early Hints

- o Specification: this document

5. Acknowledgements

Thanks to Tatsuhiro Tsujikawa for coming up with the idea of sending the link headers using an informational response.

6. Changes

6.1. Since [draft-ietf-httpbis-early-hints-00](#)

- o Forbid processing the headers of a 103 response as part of the informational response.

Oku

Expires September 30, 2017

[Page 4]

Internet-Draft

Early Hints

March 2017

7. References

7.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<http://www.rfc-editor.org/info/rfc2119>>.
- [RFC7230] Fielding, R., Ed. and J. Reschke, Ed., "Hypertext Transfer Protocol (HTTP/1.1): Message Syntax and Routing", [RFC 7230](#), DOI 10.17487/RFC7230, June 2014, <<http://www.rfc-editor.org/info/rfc7230>>.
- [RFC7231] Fielding, R., Ed. and J. Reschke, Ed., "Hypertext Transfer Protocol (HTTP/1.1): Semantics and Content", [RFC 7231](#), DOI 10.17487/RFC7231, June 2014, <<http://www.rfc-editor.org/info/rfc7231>>.
- [RFC7540] Belshe, M., Peon, R., and M. Thomson, Ed., "Hypertext Transfer Protocol Version 2 (HTTP/2)", [RFC 7540](#), DOI 10.17487/RFC7540, May 2015,

<<http://www.rfc-editor.org/info/rfc7540>>.

7.2. Informative References

[Preload] Grigorik, I., "Preload", September 2016,
<<https://w3c.github.io/preload/>>.

Author's Address

Kazuho Oku
DeNA Co., Ltd.

Email: kazuhooku@gmail.com