

HTTPbis Working Group  
Internet-Draft  
Obsoletes: [2616](#) (if approved)  
Intended status: Standards Track  
Expires: October 20, 2011

R. Fielding, Ed.  
Adobe  
J. Gettys  
Alcatel-Lucent  
J. Mogul  
HP  
H. Frystyk  
Microsoft  
L. Masinter  
Adobe  
P. Leach  
Microsoft  
T. Berners-Lee  
W3C/MIT  
Y. Lafon, Ed.  
W3C  
J. Reschke, Ed.  
greenbytes  
April 18, 2011

HTTP/1.1, part 5: Range Requests and Partial Responses  
draft-ietf-httpbis-p5-range-14

Abstract

The Hypertext Transfer Protocol (HTTP) is an application-level protocol for distributed, collaborative, hypermedia information systems. HTTP has been in use by the World Wide Web global information initiative since 1990. This document is Part 5 of the seven-part specification that defines the protocol referred to as "HTTP/1.1" and, taken together, obsoletes [RFC 2616](#). Part 5 defines range-specific requests and the rules for constructing and combining responses to those requests.

Editorial Note (To be removed by RFC Editor)

Discussion of this draft should take place on the HTTPBIS working group mailing list ([ietf-http-wg@w3.org](mailto:ietf-http-wg@w3.org)), which is archived at <http://lists.w3.org/Archives/Public/ietf-http-wg/>.

The current issues list is at <http://tools.ietf.org/wg/httpbis/trac/report/3> and related documents (including fancy diffs) can be found at <http://tools.ietf.org/wg/httpbis/>.

The changes in this draft are summarized in [Appendix D.15](#).

Internet-Draft

HTTP/1.1, Part 5

April 2011

## Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on October 20, 2011.

## Copyright Notice

Copyright (c) 2011 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

This document may contain material from IETF Documents or IETF Contributions published or made publicly available before November 10, 2008. The person(s) controlling the copyright in some of this material may not have granted the IETF Trust the right to allow modifications of such material outside the IETF Standards Process. Without obtaining an adequate license from the person(s) controlling the copyright in such materials, this document may not be modified outside the IETF Standards Process, and derivative works of it may not be created outside the IETF Standards Process, except to format it for publication as an RFC or to translate it into languages other than English.

## Table of Contents

<a href="#">1.</a>	Introduction . . . . .	<a href="#">4</a>
<a href="#">1.1.</a>	Requirements . . . . .	<a href="#">4</a>

Fielding, et al.

Expires October 20, 2011

[Page 2]

---

Internet-Draft

HTTP/1.1, Part 5

April 2011

<a href="#">1.2.</a>	Syntax Notation . . . . .	<a href="#">4</a>
<a href="#">1.2.1.</a>	Core Rules . . . . .	<a href="#">5</a>
<a href="#">1.2.2.</a>	ABNF Rules defined in other Parts of the Specification . . . . .	<a href="#">5</a>
<a href="#">2.</a>	Range Units . . . . .	<a href="#">5</a>
<a href="#">2.1.</a>	Range Specifier Registry . . . . .	<a href="#">5</a>
<a href="#">3.</a>	Status Code Definitions . . . . .	<a href="#">6</a>
<a href="#">3.1.</a>	206 Partial Content . . . . .	<a href="#">6</a>
<a href="#">3.2.</a>	416 Requested Range Not Satisfiable . . . . .	<a href="#">7</a>
<a href="#">4.</a>	Combining Ranges . . . . .	<a href="#">7</a>
<a href="#">5.</a>	Header Field Definitions . . . . .	<a href="#">7</a>
<a href="#">5.1.</a>	Accept-Ranges . . . . .	<a href="#">8</a>
<a href="#">5.2.</a>	Content-Range . . . . .	<a href="#">8</a>
<a href="#">5.3.</a>	If-Range . . . . .	<a href="#">10</a>
<a href="#">5.4.</a>	Range . . . . .	<a href="#">11</a>
<a href="#">5.4.1.</a>	Byte Ranges . . . . .	<a href="#">11</a>
<a href="#">5.4.2.</a>	Range Retrieval Requests . . . . .	<a href="#">13</a>
<a href="#">6.</a>	IANA Considerations . . . . .	<a href="#">14</a>
<a href="#">6.1.</a>	Status Code Registration . . . . .	<a href="#">14</a>
<a href="#">6.2.</a>	Header Field Registration . . . . .	<a href="#">14</a>
<a href="#">6.3.</a>	Range Specifier Registration . . . . .	<a href="#">15</a>
<a href="#">7.</a>	Security Considerations . . . . .	<a href="#">15</a>
<a href="#">8.</a>	Acknowledgments . . . . .	<a href="#">15</a>
<a href="#">9.</a>	References . . . . .	<a href="#">16</a>
<a href="#">9.1.</a>	Normative References . . . . .	<a href="#">16</a>
<a href="#">9.2.</a>	Informative References . . . . .	<a href="#">16</a>
<a href="#">Appendix A.</a>	Internet Media Type multipart/byteranges . . . . .	<a href="#">16</a>
<a href="#">Appendix B.</a>	Compatibility with Previous Versions . . . . .	<a href="#">19</a>
<a href="#">B.1.</a>	Changes from <a href="#">RFC 2616</a> . . . . .	<a href="#">19</a>
<a href="#">Appendix C.</a>	Collected ABNF . . . . .	<a href="#">19</a>
<a href="#">Appendix D.</a>	Change Log (to be removed by RFC Editor before publication) . . . . .	<a href="#">21</a>
<a href="#">D.1.</a>	Since <a href="#">RFC 2616</a> . . . . .	<a href="#">21</a>
<a href="#">D.2.</a>	Since <a href="#">draft-ietf-httpbis-p5-range-00</a> . . . . .	<a href="#">21</a>
<a href="#">D.3.</a>	Since <a href="#">draft-ietf-httpbis-p5-range-01</a> . . . . .	<a href="#">21</a>
<a href="#">D.4.</a>	Since <a href="#">draft-ietf-httpbis-p5-range-02</a> . . . . .	<a href="#">21</a>

<a href="#">D.5.</a>	Since <a href="#">draft-ietf-httpbis-p5-range-03</a>	22
<a href="#">D.6.</a>	Since <a href="#">draft-ietf-httpbis-p5-range-04</a>	22
<a href="#">D.7.</a>	Since <a href="#">draft-ietf-httpbis-p5-range-05</a>	22
<a href="#">D.8.</a>	Since <a href="#">draft-ietf-httpbis-p5-range-06</a>	22
<a href="#">D.9.</a>	Since <a href="#">draft-ietf-httpbis-p5-range-07</a>	23
<a href="#">D.10.</a>	Since <a href="#">draft-ietf-httpbis-p5-range-08</a>	23
<a href="#">D.11.</a>	Since <a href="#">draft-ietf-httpbis-p5-range-09</a>	23
<a href="#">D.12.</a>	Since <a href="#">draft-ietf-httpbis-p5-range-10</a>	23
<a href="#">D.13.</a>	Since <a href="#">draft-ietf-httpbis-p5-range-11</a>	23
<a href="#">D.14.</a>	Since <a href="#">draft-ietf-httpbis-p5-range-12</a>	24
<a href="#">D.15.</a>	Since <a href="#">draft-ietf-httpbis-p5-range-13</a>	24
Index		24

## [1.](#) Introduction

HTTP clients often encounter interrupted data transfers as a result of cancelled requests or dropped connections. When a cache has stored a partial representation, it is desirable to request the remainder of that representation in a subsequent request rather than transfer the entire representation. There are also a number of Web applications that benefit from being able to request only a subset of a larger representation, such as a single page of a very large document or only part of an image to be rendered by a device with limited local storage.

This document defines HTTP/1.1 range requests, partial responses, and the multipart/byteranges media type. The protocol for range requests is an OPTIONAL feature of HTTP, designed so resources or recipients that do not implement this feature can respond as if it is a normal GET request without impacting interoperability. Partial responses are indicated by a distinct status code to not be mistaken for full responses by intermediate caches that might not implement the feature.

Although the HTTP range request mechanism is designed to allow for extensible range types, this specification only defines requests for byte ranges.

### [1.1.](#) Requirements

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this

document are to be interpreted as described in [[RFC2119](#)].

An implementation is not compliant if it fails to satisfy one or more of the "MUST" or "REQUIRED" level requirements for the protocols it implements. An implementation that satisfies all the "MUST" or "REQUIRED" level and all the "SHOULD" level requirements for its protocols is said to be "unconditionally compliant"; one that satisfies all the "MUST" level requirements but not all the "SHOULD" level requirements for its protocols is said to be "conditionally compliant".

## [1.2.](#) Syntax Notation

This specification uses the ABNF syntax defined in Section 1.2 of [[Part1](#)] (which extends the syntax defined in [[RFC5234](#)] with a list rule). [Appendix C](#) shows the collected ABNF, with the list rule expanded.

The following core rules are included by reference, as defined in

Fielding, et al.

Expires October 20, 2011

[Page 4]

---

Internet-Draft

HTTP/1.1, Part 5

April 2011

[\[RFC5234\]](#), [Appendix B.1](#): ALPHA (letters), CR (carriage return), CRLF (CR LF), CTL (controls), DIGIT (decimal 0-9), DQUOTE (double quote), HEXDIG (hexadecimal 0-9/A-F/a-f), LF (line feed), OCTET (any 8-bit sequence of data), SP (space), VCHAR (any visible USASCII character), and WSP (whitespace).

### [1.2.1.](#) Core Rules

The core rules below are defined in Section 1.2.2 of [[Part1](#)]:

token = <token, defined in [[Part1](#)], Section 1.2.2>  
OWS = <OWS, defined in [[Part1](#)], Section 1.2.2>

### [1.2.2.](#) ABNF Rules defined in other Parts of the Specification

The ABNF rules below are defined in other parts:

HTTP-date = <HTTP-date, defined in [[Part1](#)], Section 6.1>

entity-tag = <entity-tag, defined in [[Part4](#)], Section 2.2>

## [2.](#) Range Units

HTTP/1.1 allows a client to request that only part (a range) of the representation be included within the response. HTTP/1.1 uses range units in the Range ([Section 5.4](#)) and Content-Range ([Section 5.2](#)) header fields. A representation can be broken down into subranges according to various structural units.

```
range-unit      = bytes-unit / other-range-unit
bytes-unit      = "bytes"
other-range-unit = token
```

HTTP/1.1 has been designed to allow implementations of applications that do not depend on knowledge of ranges. The only range unit defined by HTTP/1.1 is "bytes". Additional specifiers can be defined as described in [Section 2.1](#).

If a range unit is not understood in a request, a server MUST ignore the whole Range header field ([Section 5.4](#)). If a range unit is not understood in a response, an intermediary SHOULD pass the response to the client; a client MUST fail.

### [2.1.](#) Range Specifier Registry

The HTTP Range Specifier Registry defines the name space for the range specifier names.

Registrations MUST include the following fields:

- o Name
- o Description
- o Pointer to specification text

Values to be added to this name space are subject to IETF review ([\[RFC5226\]](#), [Section 4.1](#)).

The registry itself is maintained at <http://www.iana.org/assignments/http-range-specifiers>.

## [3.](#) Status Code Definitions

### [3.1.](#) 206 Partial Content

The server has fulfilled the partial GET request for the resource. The request **MUST** have included a Range header field ([Section 5.4](#)) indicating the desired range, and **MAY** have included an If-Range header field ([Section 5.3](#)) to make the request conditional.

The response **MUST** include the following header fields:

- o Either a Content-Range header field ([Section 5.2](#)) indicating the range included with this response, or a multipart/byteranges Content-Type including Content-Range fields for each part. If a Content-Length header field is present in the response, its value **MUST** match the actual number of octets transmitted in the message-body.
- o Date
- o Cache-Control, ETag, Expires, Content-Location, Last-Modified, and/or Vary, if the header field would have been sent in a 200 response to the same request

If the 206 response is the result of an If-Range request, the response **SHOULD NOT** include other representation header fields. Otherwise, the response **MUST** include all of the representation header fields that would have been returned with a 200 (OK) response to the same request.

A cache **MUST NOT** combine a 206 response with other previously cached content if the ETag or Last-Modified header fields do not match exactly, see [Section 4](#).

A cache that does not support the Range and Content-Range header fields **MUST NOT** cache 206 (Partial Content) responses. Furthermore, if a response uses a range unit that is not understood by the cache, then it **MUST NOT** be cached either.

### [3.2.](#) 416 Requested Range Not Satisfiable

A server **SHOULD** return a response with this status code if a request

included a Range header field ([Section 5.4](#)), and none of the ranges-specifier values in this field overlap the current extent of the selected resource, and the request did not include an If-Range header field ([Section 5.3](#)). (For byte-ranges, this means that the first-byte-pos of all of the byte-range-spec values were greater than the current length of the selected resource.)

When this status code is returned for a byte-range request, the response SHOULD include a Content-Range header field specifying the current length of the representation (see [Section 5.2](#)). This response MUST NOT use the multipart/byteranges content-type.

#### [4.](#) Combining Ranges

A response might transfer only a subrange of a representation, either because the request included one or more Range specifications, or because a connection closed prematurely. After several such transfers, a cache might have received several ranges of the same representation.

If a cache has a stored non-empty set of subranges for a representation, and an incoming response transfers another subrange, the cache MAY combine the new subrange with the existing set if both the following conditions are met:

- o Both the incoming response and the cache entry have a cache validator.
- o The two cache validators match using the strong comparison function (see Section 2.2.2 of [\[Part4\]](#)).

If either requirement is not met, the cache MUST use only the most recent partial response (based on the Date values transmitted with every response, and using the incoming response if these values are equal or missing), and MUST discard the other partial information.

#### [5.](#) Header Field Definitions

This section defines the syntax and semantics of HTTP/1.1 header fields related to range requests and partial responses.

##### [5.1.](#) Accept-Ranges



The "Accept-Ranges" header field allows a resource to indicate its acceptance of range requests.

```
Accept-Ranges      = acceptable-ranges
acceptable-ranges = 1#range-unit / "none"
```

Origin servers that accept byte-range requests MAY send

```
Accept-Ranges: bytes
```

but are not required to do so. Clients MAY generate range requests without having received this header field for the resource involved. Range units are defined in [Section 2](#).

Servers that do not accept any kind of range request for a resource MAY send

```
Accept-Ranges: none
```

to advise the client not to attempt a range request.

## [5.2](#). Content-Range

The "Content-Range" header field is sent with a partial representation to specify where in the full representation the payload body is intended to be applied.

Range units are defined in [Section 2](#).

```
Content-Range = content-range-spec
```

```
content-range-spec      = byte-content-range-spec
                        / other-content-range-spec
```

```
byte-content-range-spec = bytes-unit SP
                        byte-range-resp-spec "/"
                        ( instance-length / "*" )
```

```
byte-range-resp-spec    = (first-byte-pos "-" last-byte-pos)
                        / "*"
```

```
instance-length         = 1*DIGIT
```

```
other-content-range-spec = other-range-unit SP
                        other-range-resp-spec
```

```
other-range-resp-spec   = *CHAR
```

The header field SHOULD indicate the total length of the full representation, unless this length is unknown or difficult to determine. The asterisk "\*" character means that the instance-length is unknown at the time when the response was generated.

Unlike byte-ranges-specifier values (see [Section 5.4.1](#)), a byte-range-resp-spec MUST only specify one range, and MUST contain absolute byte positions for both the first and last byte of the range.

A byte-content-range-spec with a byte-range-resp-spec whose last-byte-pos value is less than its first-byte-pos value, or whose instance-length value is less than or equal to its last-byte-pos value, is invalid. The recipient of an invalid byte-content-range-spec MUST ignore it and any content transferred along with it.

In the case of a byte range request: A server sending a response with status code 416 (Requested range not satisfiable) SHOULD include a Content-Range field with a byte-range-resp-spec of "\*". The instance-length specifies the current length of the selected resource. A response with status code 206 (Partial Content) MUST NOT include a Content-Range field with a byte-range-resp-spec of "\*".

Examples of byte-content-range-spec values, assuming that the representation contains a total of 1234 bytes:

- o The first 500 bytes:

bytes 0-499/1234

- o The second 500 bytes:

bytes 500-999/1234

- o All except for the first 500 bytes:

bytes 500-1233/1234

- o The last 500 bytes:

bytes 734-1233/1234

When an HTTP message includes the content of a single range (for example, a response to a request for a single range, or to a request for a set of ranges that overlap without any holes), this content is transmitted with a Content-Range header field, and a Content-Length

header field showing the number of bytes actually transferred. For example,

HTTP/1.1 206 Partial Content

Date: Wed, 15 Nov 1995 06:25:24 GMT

Last-Modified: Wed, 15 Nov 1995 04:58:08 GMT

Content-Range: bytes 21010-47021/47022

Content-Length: 26012

Content-Type: image/gif

When an HTTP message includes the content of multiple ranges (for example, a response to a request for multiple non-overlapping ranges), these are transmitted as a multipart message. The multipart media type used for this purpose is "multipart/byteranges" as defined in [Appendix A](#).

A response to a request for a single range MUST NOT be sent using the multipart/byteranges media type. A response to a request for multiple ranges, whose result is a single range, MAY be sent as a multipart/byteranges media type with one part. A client that cannot decode a multipart/byteranges message MUST NOT ask for multiple ranges in a single request.

When a client requests multiple ranges in one request, the server SHOULD return them in the order that they appeared in the request.

If the server ignores a byte-range-spec because it is syntactically invalid, the server SHOULD treat the request as if the invalid Range header field did not exist. (Normally, this means return a 200 response containing the full representation).

If the server receives a request (other than one including an If-Range header field) with an unsatisfiable Range header field (that is, all of whose byte-range-spec values have a first-byte-pos value greater than the current length of the selected resource), it SHOULD return a response code of 416 (Requested range not satisfiable) ([Section 3.2](#)).

Note: Clients cannot depend on servers to send a 416 (Requested range not satisfiable) response instead of a 200 (OK) response for an unsatisfiable Range header field, since not all servers implement this header field.

### [5.3.](#) If-Range

If a client has a partial copy of a representation in its cache, and wishes to have an up-to-date copy of the entire representation in its cache, it could use the Range header field with a conditional GET (using either or both of If-Unmodified-Since and If-Match.) However, if the condition fails because the representation has been modified, the client would then have to make a second request to obtain the

entire current representation.

The "If-Range" header field allows a client to "short-circuit" the second request. Informally, its meaning is "if the representation is unchanged, send me the part(s) that I am missing; otherwise, send me the entire new representation".

If-Range = entity-tag / HTTP-date

Only a strong validator (Section 2.2.2 of [\[Part4\]](#)) is usable for range retrieval, since otherwise the client might end up with an internally inconsistent representation. Clients MUST NOT use weak validators in range requests. A cache or origin server receiving a conditional range request MUST use the strong comparison function to evaluate the condition.

If the client has no entity-tag for a representation, but does have a Last-Modified date, it MAY use that date in an If-Range header field. (The server can distinguish between a valid HTTP-date and any form of entity-tag by examining no more than two characters.) The If-Range header field SHOULD only be used together with a Range header field, and MUST be ignored if the request does not include a Range header field, or if the server does not support the sub-range operation.

If a client wishes to perform a sub-range retrieval on a value for which it has only a Last-Modified time and no opaque validator, it MAY do this only if the Last-Modified time is strong in the sense described in Section 2.1.2 of [\[Part4\]](#).

If the entity-tag given in the If-Range header field matches the current cache validator for the representation, then the server SHOULD provide the specified sub-range of the representation using a

206 (Partial Content) response. If the cache validator does not match, then the server SHOULD return the entire representation using a 200 (OK) response.

## [5.4.](#) Range

### [5.4.1.](#) Byte Ranges

Since all HTTP representations are transferred as sequences of bytes, the concept of a byte range is meaningful for any HTTP representation. (However, not all clients and servers need to support byte-range operations.)

Byte range specifications in HTTP apply to the sequence of bytes in the representation body (not necessarily the same as the message-body).

A byte range operation MAY specify a single range of bytes, or a set of ranges within a single representation.

```
byte-ranges-specifier = bytes-unit "=" byte-range-set
byte-range-set       = 1#( byte-range-spec / suffix-byte-range-spec )
byte-range-spec      = first-byte-pos "-" [ last-byte-pos ]
first-byte-pos       = 1*DIGIT
last-byte-pos        = 1*DIGIT
```

The first-byte-pos value in a byte-range-spec gives the byte-offset of the first byte in a range. The last-byte-pos value gives the byte-offset of the last byte in the range; that is, the byte positions specified are inclusive. Byte offsets start at zero.

If the last-byte-pos value is present, it MUST be greater than or equal to the first-byte-pos in that byte-range-spec, or the byte-range-spec is syntactically invalid. The recipient of a byte-range-set that includes one or more syntactically invalid byte-range-spec values MUST ignore the header field that includes that byte-range-set.

If the last-byte-pos value is absent, or if the value is greater than or equal to the current length of the representation body, last-byte-pos is taken to be equal to one less than the current length of the representation in bytes.

By its choice of last-byte-pos, a client can limit the number of bytes retrieved without knowing the size of the representation.

```
suffix-byte-range-spec = "-" suffix-length
suffix-length = 1*DIGIT
```

A suffix-byte-range-spec is used to specify the suffix of the representation body, of a length given by the suffix-length value. (That is, this form specifies the last N bytes of a representation.) If the representation is shorter than the specified suffix-length, the entire representation is used.

If a syntactically valid byte-range-set includes at least one byte-range-spec whose first-byte-pos is less than the current length of the representation, or at least one suffix-byte-range-spec with a non-zero suffix-length, then the byte-range-set is satisfiable. Otherwise, the byte-range-set is unsatisfiable. If the byte-range-set is unsatisfiable, the server SHOULD return a response with a 416 (Requested range not satisfiable) status code. Otherwise, the server SHOULD return a response with a 206 (Partial Content) status code containing the satisfiable ranges of the representation.

Examples of byte-ranges-specifier values (assuming a representation of length 10000):

- o The first 500 bytes (byte offsets 0-499, inclusive):

```
bytes=0-499
```

- o The second 500 bytes (byte offsets 500-999, inclusive):

```
bytes=500-999
```

- o The final 500 bytes (byte offsets 9500-9999, inclusive):

```
bytes=-500
```

Or:

```
bytes=9500-
```

- o The first and last bytes only (bytes 0 and 9999):

bytes=0-0,-1

- o Several legal but not canonical specifications of the second 500 bytes (byte offsets 500-999, inclusive):

bytes=500-600,601-999

bytes=500-700,601-999

#### [5.4.2.](#) Range Retrieval Requests

The "Range" header field defines the GET method (conditional or not) to request one or more sub-ranges of the response representation body, instead of the entire representation body.

Range = byte-ranges-specifier / other-ranges-specifier  
other-ranges-specifier = other-range-unit "=" other-range-set  
other-range-set = 1\*CHAR

A server MAY ignore the Range header field. However, HTTP/1.1 origin servers and intermediate caches ought to support byte ranges when possible, since Range supports efficient recovery from partially failed transfers, and supports efficient partial retrieval of large representations.

If the server supports the Range header field and the specified range or ranges are appropriate for the representation:

- o The presence of a Range header field in an unconditional GET modifies what is returned if the GET is otherwise successful. In other words, the response carries a status code of 206 (Partial Content) instead of 200 (OK).
- o The presence of a Range header field in a conditional GET (a request using one or both of If-Modified-Since and If-None-Match, or one or both of If-Unmodified-Since and If-Match) modifies what is returned if the GET is otherwise successful and the condition is true. It does not affect the 304 (Not Modified) response returned if the conditional is false.

In some cases, it might be more appropriate to use the If-Range header field (see [Section 5.3](#)) in addition to the Range header field.

If a proxy that supports ranges receives a Range request, forwards the request to an inbound server, and receives an entire representation in reply, it MAY only return the requested range to its client.

## 6. IANA Considerations

### 6.1. Status Code Registration

The HTTP Status Code Registry located at <http://www.iana.org/assignments/http-status-codes> shall be updated with the registrations below:

Value	Description	Reference
206	Partial Content	<a href="#">Section 3.1</a>
416	Requested Range Not Satisfiable	<a href="#">Section 3.2</a>

### 6.2. Header Field Registration

The Message Header Field Registry located at <http://www.iana.org/assignments/message-headers/message-header-index.html> shall be updated with the permanent registrations below (see [RFC3864]):

Header Field Name	Protocol	Status	Reference
Accept-Ranges	http	standard	<a href="#">Section 5.1</a>



Content-Range	http	standard	<a href="#">Section 5.2</a>	
If-Range	http	standard	<a href="#">Section 5.3</a>	
Range	http	standard	<a href="#">Section 5.4</a>	
+-----+-----+-----+-----+				

The change controller is: "IETF (iesg@ietf.org) - Internet Engineering Task Force".

### [6.3.](#) Range Specifier Registration

The registration procedure for HTTP Range Specifiers is defined by [Section 2.1](#) of this document.

The HTTP Range Specifier Registry shall be created at <http://www.iana.org/assignments/http-range-specifiers> and be populated with the registrations below:

Range Specifier Name	Description	Reference	
bytes	a range of octets	(this specification)	
+-----+-----+-----+			

The change controller is: "IETF (iesg@ietf.org) - Internet Engineering Task Force".

## [7.](#) Security Considerations

No additional security considerations have been identified beyond those applicable to HTTP in general [[Part1](#)].

## [8.](#) Acknowledgments

Most of the specification of ranges is based on work originally done by Ari Luotonen and John Franks, with additional input from Steve Zilles, Daniel W. Connolly, Roy T. Fielding, Jim Gettys, Martin Hamilton, Koen Holtman, Shel Kaplan, Paul Leach, Alex Lopez-Ortiz, Larry Masinter, Jeff Mogul, Lou Montulli, David W. Morris, Luigi Rizzo, and Bill Weihl.

## [9.](#) References

## 9.1. Normative References

- [Part1] Fielding, R., Ed., Gettys, J., Mogul, J., Frystyk, H., Masinter, L., Leach, P., Berners-Lee, T., Lafon, Y., Ed., and J. Reschke, Ed., "HTTP/1.1, part 1: URIs, Connections, and Message Parsing", [draft-ietf-httpbis-p1-messaging-14](#) (work in progress), April 2011.
- [Part4] Fielding, R., Ed., Gettys, J., Mogul, J., Frystyk, H., Masinter, L., Leach, P., Berners-Lee, T., Lafon, Y., Ed., and J. Reschke, Ed., "HTTP/1.1, part 4: Conditional Requests", [draft-ietf-httpbis-p4-conditional-14](#) (work in progress), April 2011.
- [RFC2046] Freed, N. and N. Borenstein, "Multipurpose Internet Mail Extensions (MIME) Part Two: Media Types", [RFC 2046](#), November 1996.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC5234] Crocker, D., Ed. and P. Overell, "Augmented BNF for Syntax Specifications: ABNF", STD 68, [RFC 5234](#), January 2008.

## 9.2. Informative References

- [RFC2616] Fielding, R., Gettys, J., Mogul, J., Frystyk, H., Masinter, L., Leach, P., and T. Berners-Lee, "Hypertext Transfer Protocol -- HTTP/1.1", [RFC 2616](#), June 1999.
- [RFC3864] Klyne, G., Nottingham, M., and J. Mogul, "Registration Procedures for Message Header Fields", [BCP 90](#), [RFC 3864](#), September 2004.
- [RFC4288] Freed, N. and J. Klensin, "Media Type Specifications and Registration Procedures", [BCP 13](#), [RFC 4288](#), December 2005.
- [RFC5226] Narten, T. and H. Alvestrand, "Guidelines for Writing an IANA Considerations Section in RFCs", [BCP 26](#), [RFC 5226](#), May 2008.

## Appendix A. Internet Media Type multipart/byteranges

When an HTTP 206 (Partial Content) response message includes the content of multiple ranges (a response to a request for multiple non-overlapping ranges), these are transmitted as a multipart message-body ([\[RFC2046\]](#), [Section 5.1](#)). The media type for this purpose is

called "multipart/byteranges". The following is to be registered

with IANA [[RFC4288](#)].

Note: Despite the name "multipart/byteranges" is not limited to the byte ranges only.

The multipart/byteranges media type includes one or more parts, each with its own Content-Type and Content-Range fields. The required boundary parameter specifies the boundary string used to separate each body-part.

Type name: multipart

Subtype name: byteranges

Required parameters: boundary

Optional parameters: none

Encoding considerations: only "7bit", "8bit", or "binary" are permitted

Security considerations: none

Interoperability considerations: none

Published specification: This specification (see [Appendix A](#)).

Applications that use this media type:

Additional information:

Magic number(s): none

File extension(s): none

Macintosh file type code(s): none

Person and email address to contact for further information: See Authors Section.

Intended usage: COMMON

Restrictions on usage: none

Author/Change controller: IESG

Fielding, et al.

Expires October 20, 2011

[Page 17]

---

Internet-Draft

HTTP/1.1, Part 5

April 2011

For example:

```
HTTP/1.1 206 Partial Content
Date: Wed, 15 Nov 1995 06:25:24 GMT
Last-Modified: Wed, 15 Nov 1995 04:58:08 GMT
Content-type: multipart/byteranges; boundary=THIS_STRING_SEPARATES
```

```
--THIS_STRING_SEPARATES
Content-type: application/pdf
Content-range: bytes 500-999/8000
```

```
...the first range...
--THIS_STRING_SEPARATES
Content-type: application/pdf
Content-range: bytes 7000-7999/8000
```

```
...the second range
--THIS_STRING_SEPARATES--
```

Other example:

```
HTTP/1.1 206 Partial Content
Date: Tue, 14 Nov 1995 06:25:24 GMT
Last-Modified: Tue, 14 July 04:58:08 GMT
Content-type: multipart/byteranges; boundary=THIS_STRING_SEPARATES
```

```
--THIS_STRING_SEPARATES
Content-type: video/example
Content-range: exampleunit 1.2-4.3/25
```

```
...the first range...
--THIS_STRING_SEPARATES
Content-type: video/example
```

Content-range: exampleunit 11.2-14.3/25

...the second range  
--THIS\_STRING\_SEPARATES--

Notes:

1. Additional CRLFs MAY precede the first boundary string in the body.
2. Although [[RFC2046](#)] permits the boundary string to be quoted, some existing implementations handle a quoted boundary string incorrectly.

Fielding, et al.

Expires October 20, 2011

[Page 18]

---

Internet-Draft

HTTP/1.1, Part 5

April 2011

3. A number of browsers and servers were coded to an early draft of the byteranges specification to use a media type of multipart/x-byteranges, which is almost, but not quite compatible with the version documented in HTTP/1.1.

## [Appendix B](#). Compatibility with Previous Versions

### [B.1](#). Changes from [RFC 2616](#)

Clarify that it is not ok to use a weak cache validator in a 206 response. ([Section 3.1](#))

Change ABNF productions for header fields to only define the field value. ([Section 5](#))

Clarify that multipart/byteranges can consist of a single part. (Appendix A)

### [Appendix C](#). Collected ABNF

Accept-Ranges = acceptable-ranges

Content-Range = content-range-spec

HTTP-date = <HTTP-date, defined in [\[Part1\]](#), Section 6.1>

If-Range = entity-tag / HTTP-date

OWS = <OWS, defined in [\[Part1\]](#), Section 1.2.2>

Range = byte-ranges-specifier / other-ranges-specifier

acceptable-ranges = ( \*( "," OWS ) range-unit \*( OWS "," [ OWS range-unit ] ) ) / "none"

byte-content-range-spec = bytes-unit SP byte-range-resp-spec "/" ( instance-length / "\*" )

byte-range-resp-spec = ( first-byte-pos "-" last-byte-pos ) / "\*"

byte-range-set = ( \*( "," OWS ) byte-range-spec ) / (

```

    suffix-byte-range-spec *( OWS "," [ ( OWS byte-range-spec ) /
    suffix-byte-range-spec ] ) )
byte-range-spec = first-byte-pos "-" [ last-byte-pos ]
byte-ranges-specifier = bytes-unit "=" byte-range-set
bytes-unit = "bytes"

content-range-spec = byte-content-range-spec /
    other-content-range-spec

entity-tag = <entity-tag, defined in [Part4], Section 2.2>

first-byte-pos = 1*DIGIT

instance-length = 1*DIGIT

last-byte-pos = 1*DIGIT

other-content-range-spec = other-range-unit SP other-range-resp-spec
other-range-resp-spec = *CHAR
other-range-set = 1*CHAR
other-range-unit = token
other-ranges-specifier = other-range-unit "=" other-range-set

range-unit = bytes-unit / other-range-unit

suffix-byte-range-spec = "-" suffix-length
suffix-length = 1*DIGIT

token = <token, defined in [Part1], Section 1.2.2>

```

ABNF diagnostics:

```

; Accept-Ranges defined but not used
; Content-Range defined but not used
; If-Range defined but not used
; Range defined but not used

```

[Appendix D](#). Change Log (to be removed by RFC Editor before publication)

[D.1](#). Since [RFC 2616](#)

Extracted relevant partitions from [\[RFC2616\]](#).

D.2. Since [draft-ietf-httpbis-p5-range-00](#)

Closed issues:

- o <<http://tools.ietf.org/wg/httpbis/trac/ticket/18>>: "Cache validators in 206 responses" (<http://purl.org/NET/http-errata#ifrange206>>)
- o <<http://tools.ietf.org/wg/httpbis/trac/ticket/35>>: "Normative and Informative references"
- o <<http://tools.ietf.org/wg/httpbis/trac/ticket/86>>: "Normative up-to-date references"

D.3. Since [draft-ietf-httpbis-p5-range-01](#)

Closed issues:

- o <<http://tools.ietf.org/wg/httpbis/trac/ticket/55>>: "Updating to [RFC4288](#)"

Ongoing work on ABNF conversion

(<<http://tools.ietf.org/wg/httpbis/trac/ticket/36>>):

- o Add explicit references to BNF syntax and rules imported from other parts of the specification.

D.4. Since [draft-ietf-httpbis-p5-range-02](#)

Ongoing work on IANA Message Header Field Registration

(<<http://tools.ietf.org/wg/httpbis/trac/ticket/40>>):

- o Reference [RFC 3984](#), and update header field registrations for headers defined in this document.

D.5. Since [draft-ietf-httpbis-p5-range-03](#)

None.

D.6. Since [draft-ietf-httpbis-p5-range-04](#)



Closed issues:

- o <<http://tools.ietf.org/wg/httpbis/trac/ticket/133>>: "multipart/byteranges minimum number of parts"

Ongoing work on ABNF conversion

(<<http://tools.ietf.org/wg/httpbis/trac/ticket/36>>):

- o Use "/" instead of "|" for alternatives.
- o Introduce new ABNF rules for "bad" whitespace ("BWS"), optional whitespace ("OWS") and required whitespace ("RWS").
- o Rewrite ABNFs to spell out whitespace rules, factor out header field value format definitions.

D.7. Since [draft-ietf-httpbis-p5-range-05](#)

Closed issues:

- o <<http://tools.ietf.org/wg/httpbis/trac/ticket/142>>: "State base for \*-byte-pos and suffix-length"

Ongoing work on Custom Ranges

(<<http://tools.ietf.org/wg/httpbis/trac/ticket/85>>):

- o Remove bias in favor of byte ranges; allow custom ranges in ABNF.

Final work on ABNF conversion

(<<http://tools.ietf.org/wg/httpbis/trac/ticket/36>>):

- o Add appendix containing collected and expanded ABNF, reorganize ABNF introduction.

D.8. Since [draft-ietf-httpbis-p5-range-06](#)

Closed issues:

- o <<http://tools.ietf.org/wg/httpbis/trac/ticket/161>>: "base for numeric protocol elements"

D.9. Since [draft-ietf-httpbis-p5-range-07](#)

Closed issues:

- o Fixed discrepancy in the If-Range definition about allowed validators.
- o <<http://tools.ietf.org/wg/httpbis/trac/ticket/150>>: "multipart/byteranges for custom range units"
- o <<http://tools.ietf.org/wg/httpbis/trac/ticket/151>>: "range unit missing from other-ranges-specifier in Range header"
- o <<http://tools.ietf.org/wg/httpbis/trac/ticket/198>>: "move IANA registrations for optional status codes"

D.10. Since [draft-ietf-httpbis-p5-range-08](#)

No significant changes.

D.11. Since [draft-ietf-httpbis-p5-range-09](#)

No significant changes.

D.12. Since [draft-ietf-httpbis-p5-range-10](#)

Closed issues:

- o <<http://tools.ietf.org/wg/httpbis/trac/ticket/69>>: "Clarify 'Requested Variant'"
- o <<http://tools.ietf.org/wg/httpbis/trac/ticket/109>>: "Clarify entity / representation / variant terminology"
- o <<http://tools.ietf.org/wg/httpbis/trac/ticket/220>>: "consider removing the 'changes from 2068' sections"

Ongoing work on Custom Ranges

(<<http://tools.ietf.org/wg/httpbis/trac/ticket/85>>):

- o Add IANA registry.

D.13. Since [draft-ietf-httpbis-p5-range-11](#)

Closed issues:

- o <<http://tools.ietf.org/wg/httpbis/trac/ticket/217>>: "Caches can't be required to serve ranges"

Internet-Draft

HTTP/1.1, Part 5

April 2011

[D.14.](#) Since [draft-ietf-httpbis-p5-range-12](#)

Closed issues:

- o <http://tools.ietf.org/wg/httpbis/trac/ticket/224>: "Header Classification"

[D.15.](#) Since [draft-ietf-httpbis-p5-range-13](#)

Closed issues:

- o <http://tools.ietf.org/wg/httpbis/trac/ticket/276>: "untangle ABNFs for header fields"

## Index

2		
206	Partial Content (status code)	6
4		
416	Requested Range Not Satisfiable (status code)	7
A		
	Accept-Ranges header field	8
C		
	Content-Range header field	8
G		
	Grammar	
	Accept-Ranges	8
	acceptable-ranges	8
	byte-content-range-spec	8
	byte-range-resp-spec	8
	byte-range-set	12
	byte-range-spec	12
	byte-ranges-specifier	12
	bytes-unit	5
	Content-Range	8
	content-range-spec	8
	first-byte-pos	12
	If-Range	11

instance-length 8  
last-byte-pos 12  
other-range-unit 5  
Range 13  
range-unit 5  
ranges-specifier 12

suffix-byte-range-spec 12  
suffix-length 12

## H

### Header Fields

Accept-Ranges 8  
Content-Range 8  
If-Range 10  
Range 11

## I

If-Range header field 10

## M

### Media Type

multipart/byteranges 16  
multipart/x-byteranges 19  
multipart/byteranges Media Type 16  
multipart/x-byteranges Media Type 19

## R

Range header field 11

## S

### Status Codes

206 Partial Content 6  
416 Requested Range Not Satisfiable 7

## Authors' Addresses

Roy T. Fielding (editor)  
Adobe Systems Incorporated  
345 Park Ave  
San Jose, CA 95110  
USA

E-Mail: [fielding@gbiv.com](mailto:fielding@gbiv.com)  
URI: <http://roy.gbiv.com/>

Fielding, et al.

Expires October 20, 2011

[Page 25]

---

Internet-Draft

HTTP/1.1, Part 5

April 2011

Jim Gettys  
Alcatel-Lucent Bell Labs  
21 Oak Knoll Road  
Carlisle, MA 01741  
USA

E-Mail: [jg@freedesktop.org](mailto:jg@freedesktop.org)  
URI: <http://gettys.wordpress.com/>

Jeffrey C. Mogul  
Hewlett-Packard Company  
HP Labs, Large Scale Systems Group  
1501 Page Mill Road, MS 1177  
Palo Alto, CA 94304  
USA

E-Mail: [JeffMogul@acm.org](mailto:JeffMogul@acm.org)

Henrik Frystyk Nielsen  
Microsoft Corporation  
1 Microsoft Way  
Redmond, WA 98052  
USA

E-Mail: [henrikn@microsoft.com](mailto:henrikn@microsoft.com)

Larry Masinter  
Adobe Systems Incorporated  
345 Park Ave  
San Jose, CA 95110  
USA

E-Mail: [LMM@acm.org](mailto:LMM@acm.org)  
URI: <http://larry.masinter.net/>

Paul J. Leach  
Microsoft Corporation  
1 Microsoft Way  
Redmond, WA 98052

E-Mail: [paulle@microsoft.com](mailto:paulle@microsoft.com)

Fielding, et al.

Expires October 20, 2011

[Page 26]

---

Internet-Draft

HTTP/1.1, Part 5

April 2011

Tim Berners-Lee  
World Wide Web Consortium  
MIT Computer Science and Artificial Intelligence Laboratory  
The Stata Center, Building 32  
32 Vassar Street  
Cambridge, MA 02139  
USA

E-Mail: [timbl@w3.org](mailto:timbl@w3.org)  
URI: <http://www.w3.org/People/Berners-Lee/>

Yves Lafon (editor)  
World Wide Web Consortium  
W3C / ERCIM  
2004, rte des Lucioles  
Sophia-Antipolis, AM 06902  
France

E-Mail: [ylafon@w3.org](mailto:ylafon@w3.org)  
URI: <http://www.raubacapeu.net/people/yves/>

Julian F. Reschke (editor)  
greenbytes GmbH  
Hafenweg 16  
Muenster, NW 48155  
Germany

Phone: +49 251 2807760  
Fax: +49 251 2807761  
EMail: [julian.reschke@greenbytes.de](mailto:julian.reschke@greenbytes.de)  
URI: <http://greenbytes.de/tech/webdav/>