

HTTPbis Working Group  
Internet-Draft  
Obsoletes: [2616](#) (if approved)  
Updates: [2617](#) (if approved)  
Intended status: Standards Track  
Expires: April 29, 2010

R. Fielding, Ed.  
Day Software  
J. Gettys  
One Laptop per Child  
J. Mogul  
HP  
H. Frystyk  
Microsoft  
L. Masinter  
Adobe Systems  
P. Leach  
Microsoft  
T. Berners-Lee  
W3C/MIT  
Y. Lafon, Ed.  
W3C  
J. Reschke, Ed.  
greenbytes  
October 26, 2009

HTTP/1.1, part 7: Authentication  
draft-ietf-httpbis-p7-auth-08

Status of this Memo

This Internet-Draft is submitted to IETF in full conformance with the provisions of [BCP 78](#) and [BCP 79](#). This document may contain material from IETF Documents or IETF Contributions published or made publicly available before November 10, 2008. The person(s) controlling the copyright in some of this material may not have granted the IETF Trust the right to allow modifications of such material outside the IETF Standards Process. Without obtaining an adequate license from the person(s) controlling the copyright in such materials, this document may not be modified outside the IETF Standards Process, and derivative works of it may not be created outside the IETF Standards Process, except to format it for publication as an RFC or to translate it into languages other than English.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

Internet-Draft

HTTP/1.1, Part 7

October 2009

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/lid-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

This Internet-Draft will expire on April 29, 2010.

#### Copyright Notice

Copyright (c) 2009 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents in effect on the date of publication of this document (<http://trustee.ietf.org/license-info>). Please review these documents carefully, as they describe your rights and restrictions with respect to this document.

#### Abstract

The Hypertext Transfer Protocol (HTTP) is an application-level protocol for distributed, collaborative, hypermedia information systems. HTTP has been in use by the World Wide Web global information initiative since 1990. This document is Part 7 of the seven-part specification that defines the protocol referred to as "HTTP/1.1" and, taken together, obsoletes [RFC 2616](#). Part 7 defines HTTP Authentication.

#### Editorial Note (To be removed by RFC Editor)

Discussion of this draft should take place on the HTTPBIS working group mailing list ([ietf-http-wg@w3.org](mailto:ietf-http-wg@w3.org)). The current issues list is at <http://tools.ietf.org/wg/httpbis/trac/report/11> and related documents (including fancy diffs) can be found at <http://tools.ietf.org/wg/httpbis/>.

The changes in this draft are summarized in [Appendix C.9](#).

Internet-Draft

HTTP/1.1, Part 7

October 2009

## Table of Contents

<a href="#">1.</a>	Introduction . . . . .	<a href="#">4</a>
<a href="#">1.1.</a>	Requirements . . . . .	<a href="#">4</a>
<a href="#">1.2.</a>	Syntax Notation . . . . .	<a href="#">4</a>
<a href="#">1.2.1.</a>	Core Rules . . . . .	<a href="#">5</a>
1.2.2.	ABNF Rules defined in other Parts of the Specification . . . . .	<a href="#">5</a>
<a href="#">2.</a>	Status Code Definitions . . . . .	<a href="#">5</a>
<a href="#">2.1.</a>	401 Unauthorized . . . . .	<a href="#">5</a>
<a href="#">2.2.</a>	407 Proxy Authentication Required . . . . .	<a href="#">5</a>
<a href="#">3.</a>	Header Field Definitions . . . . .	<a href="#">5</a>
<a href="#">3.1.</a>	Authorization . . . . .	<a href="#">6</a>
<a href="#">3.2.</a>	Proxy-Authenticate . . . . .	<a href="#">6</a>
<a href="#">3.3.</a>	Proxy-Authorization . . . . .	<a href="#">7</a>
<a href="#">3.4.</a>	WWW-Authenticate . . . . .	<a href="#">7</a>
<a href="#">4.</a>	IANA Considerations . . . . .	<a href="#">8</a>
<a href="#">4.1.</a>	Status Code Registration . . . . .	<a href="#">8</a>
<a href="#">4.2.</a>	Message Header Registration . . . . .	<a href="#">8</a>
<a href="#">5.</a>	Security Considerations . . . . .	<a href="#">8</a>
<a href="#">5.1.</a>	Authentication Credentials and Idle Clients . . . . .	<a href="#">9</a>
<a href="#">6.</a>	Acknowledgments . . . . .	<a href="#">9</a>
<a href="#">7.</a>	References . . . . .	<a href="#">9</a>
<a href="#">7.1.</a>	Normative References . . . . .	<a href="#">9</a>
<a href="#">7.2.</a>	Informative References . . . . .	<a href="#">10</a>
<a href="#">Appendix A.</a>	Compatibility with Previous Versions . . . . .	<a href="#">10</a>
<a href="#">A.1.</a>	Changes from <a href="#">RFC 2616</a> . . . . .	<a href="#">10</a>
<a href="#">Appendix B.</a>	Collected ABNF . . . . .	<a href="#">11</a>
<a href="#">Appendix C.</a>	Change Log (to be removed by RFC Editor before publication) . . . . .	<a href="#">11</a>
<a href="#">C.1.</a>	Since <a href="#">RFC2616</a> . . . . .	<a href="#">11</a>
<a href="#">C.2.</a>	Since <a href="#">draft-ietf-httpbis-p7-auth-00</a> . . . . .	<a href="#">11</a>
<a href="#">C.3.</a>	Since <a href="#">draft-ietf-httpbis-p7-auth-01</a> . . . . .	<a href="#">11</a>
<a href="#">C.4.</a>	Since <a href="#">draft-ietf-httpbis-p7-auth-02</a> . . . . .	<a href="#">12</a>
<a href="#">C.5.</a>	Since <a href="#">draft-ietf-httpbis-p7-auth-03</a> . . . . .	<a href="#">12</a>
<a href="#">C.6.</a>	Since <a href="#">draft-ietf-httpbis-p7-auth-04</a> . . . . .	<a href="#">12</a>

<a href="#">C.7.</a>	Since <a href="#">draft-ietf-httpbis-p7-auth-05</a>	. . . . .	<a href="#">12</a>
<a href="#">C.8.</a>	Since <a href="#">draft-ietf-httpbis-p7-auth-06</a>	. . . . .	<a href="#">12</a>
<a href="#">C.9.</a>	Since <a href="#">draft-ietf-httpbis-p7-auth-07</a>	. . . . .	<a href="#">12</a>
Index	. . . . .	. . . . .	<a href="#">13</a>
Authors' Addresses	. . . . .	. . . . .	<a href="#">13</a>

## [1.](#) Introduction

This document defines HTTP/1.1 access control and authentication. Right now it includes the extracted relevant sections of [RFC 2616](#) with only minor changes. The intention is to move the general framework for HTTP authentication here, as currently specified in [[RFC2617](#)], and allow the individual authentication mechanisms to be defined elsewhere. This introduction will be rewritten when that occurs.

HTTP provides several OPTIONAL challenge-response authentication mechanisms which can be used by a server to challenge a client request and by a client to provide authentication information. The general framework for access authentication, and the specification of "basic" and "digest" authentication, are specified in "HTTP Authentication: Basic and Digest Access Authentication" [[RFC2617](#)]. This specification adopts the definitions of "challenge" and "credentials" from that specification.

### [1.1.](#) Requirements

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

An implementation is not compliant if it fails to satisfy one or more of the MUST or REQUIRED level requirements for the protocols it implements. An implementation that satisfies all the MUST or REQUIRED level and all the SHOULD level requirements for its

protocols is said to be "unconditionally compliant"; one that satisfies all the MUST level requirements but not all the SHOULD level requirements for its protocols is said to be "conditionally compliant."

## 1.2. Syntax Notation

This specification uses the ABNF syntax defined in Section 1.2 of [\[Part1\]](#) (which extends the syntax defined in [\[RFC5234\]](#) with a list rule). [Appendix B](#) shows the collected ABNF, with the list rule expanded.

The following core rules are included by reference, as defined in [\[RFC5234\]](#), [Appendix B.1](#): ALPHA (letters), CR (carriage return), CRLF (CR LF), CTL (controls), DIGIT (decimal 0-9), DQUOTE (double quote), HEXDIG (hexadecimal 0-9/A-F/a-f), LF (line feed), OCTET (any 8-bit sequence of data), SP (space), VCHAR (any visible USASCII character), and WSP (whitespace).

### 1.2.1. Core Rules

The core rules below are defined in Section 1.2.2 of [\[Part1\]](#):

OWS = <OWS, defined in [\[Part1\]](#), Section 1.2.2>

### 1.2.2. ABNF Rules defined in other Parts of the Specification

The ABNF rules below are defined in other specifications:

challenge = <challenge, defined in [\[RFC2617\]](#), [Section 1.2](#)>  
credentials = <credentials, defined in [\[RFC2617\]](#), [Section 1.2](#)>

## 2. Status Code Definitions

### 2.1. 401 Unauthorized

The request requires user authentication. The response MUST include a WWW-Authenticate header field ([Section 3.4](#)) containing a challenge applicable to the requested resource. The client MAY repeat the request with a suitable Authorization header field ([Section 3.1](#)). If

the request already included Authorization credentials, then the 401 response indicates that authorization has been refused for those credentials. If the 401 response contains the same challenge as the prior response, and the user agent has already attempted authentication at least once, then the user SHOULD be presented the entity that was given in the response, since that entity might include relevant diagnostic information. HTTP access authentication is explained in "HTTP Authentication: Basic and Digest Access Authentication" [[RFC2617](#)].

## [2.2.](#) 407 Proxy Authentication Required

This code is similar to 401 (Unauthorized), but indicates that the client must first authenticate itself with the proxy. The proxy MUST return a Proxy-Authenticate header field ([Section 3.2](#)) containing a challenge applicable to the proxy for the requested resource. The client MAY repeat the request with a suitable Proxy-Authorization header field ([Section 3.3](#)). HTTP access authentication is explained in "HTTP Authentication: Basic and Digest Access Authentication" [[RFC2617](#)].

## [3.](#) Header Field Definitions

This section defines the syntax and semantics of HTTP/1.1 header fields related to authentication.

### [3.1.](#) Authorization

The "Authorization" request-header field allows a user agent to authenticate itself with a server -- usually, but not necessary, after receiving a 401 (Unauthorized) response. Its value consists of credentials containing information of the user agent for the realm of the resource being requested.

```
Authorization = "Authorization" ":" OWS Authorization-v  
Authorization-v = credentials
```

HTTP access authentication is described in "HTTP Authentication: Basic and Digest Access Authentication" [[RFC2617](#)]. If a request is authenticated and a realm specified, the same credentials SHOULD be valid for all other requests within this realm (assuming that the

authentication scheme itself does not require otherwise, such as credentials that vary according to a challenge value or using synchronized clocks).

When a shared cache (see Section 1.2 of [\[Part6\]](#)) receives a request containing an Authorization field, it MUST NOT return the corresponding response as a reply to any other request, unless one of the following specific exceptions holds:

1. If the response includes the "s-maxage" cache-control directive, the cache MAY use that response in replying to a subsequent request. But (if the specified maximum age has passed) a proxy cache MUST first revalidate it with the origin server, using the request-headers from the new request to allow the origin server to authenticate the new request. (This is the defined behavior for s-maxage.) If the response includes "s-maxage=0", the proxy MUST always revalidate it before re-using it.
2. If the response includes the "must-revalidate" cache-control directive, the cache MAY use that response in replying to a subsequent request. But if the response is stale, all caches MUST first revalidate it with the origin server, using the request-headers from the new request to allow the origin server to authenticate the new request.
3. If the response includes the "public" cache-control directive, it MAY be returned in reply to any subsequent request.

### [3.2.](#) Proxy-Authenticate

The "Proxy-Authenticate" response-header field consists of a challenge that indicates the authentication scheme and parameters applicable to the proxy for this request-target. It MUST be included

as part of a 407 (Proxy Authentication Required) response.

```
Proxy-Authenticate = "Proxy-Authenticate" ":" OWS
                   Proxy-Authenticate-v
Proxy-Authenticate-v = 1#challenge
```

The HTTP access authentication process is described in "HTTP Authentication: Basic and Digest Access Authentication" [\[RFC2617\]](#).

Unlike WWW-Authenticate, the Proxy-Authenticate header field applies only to the current connection and SHOULD NOT be passed on to downstream clients. However, an intermediate proxy might need to obtain its own credentials by requesting them from the downstream client, which in some circumstances will appear as if the proxy is forwarding the Proxy-Authenticate header field.

### 3.3. Proxy-Authorization

The "Proxy-Authorization" request-header field allows the client to identify itself (or its user) to a proxy which requires authentication. Its value consists of credentials containing the authentication information of the user agent for the proxy and/or realm of the resource being requested.

```
Proxy-Authorization = "Proxy-Authorization" ":" OWS
                    Proxy-Authorization-v
Proxy-Authorization-v = credentials
```

The HTTP access authentication process is described in "HTTP Authentication: Basic and Digest Access Authentication" [[RFC2617](#)]. Unlike Authorization, the Proxy-Authorization header field applies only to the next outbound proxy that demanded authentication using the Proxy-Authenticate field. When multiple proxies are used in a chain, the Proxy-Authorization header field is consumed by the first outbound proxy that was expecting to receive credentials. A proxy MAY relay the credentials from the client request to the next proxy if that is the mechanism by which the proxies cooperatively authenticate a given request.

### 3.4. WWW-Authenticate

The "WWW-Authenticate" response-header field consists of at least one challenge that indicates the authentication scheme(s) and parameters applicable to the request-target. It MUST be included in 401 (Unauthorized) response messages.

```
WWW-Authenticate = "WWW-Authenticate" ":" OWS WWW-Authenticate-v
WWW-Authenticate-v = 1#challenge
```



Authentication: Basic and Digest Access Authentication" [[RFC2617](#)]. User agents are advised to take special care in parsing the WWW-Authenticate field value as it might contain more than one challenge, or if more than one WWW-Authenticate header field is provided, the contents of a challenge itself can contain a comma-separated list of authentication parameters.

## 4. IANA Considerations

### 4.1. Status Code Registration

The HTTP Status Code Registry located at <http://www.iana.org/assignments/http-status-codes> should be updated with the registrations below:

Value	Description	Reference
401	Unauthorized	<a href="#">Section 2.1</a>
407	Proxy Authentication Required	<a href="#">Section 2.2</a>

### 4.2. Message Header Registration

The Message Header Registry located at <http://www.iana.org/assignments/message-headers/message-header-index.html> should be updated with the permanent registrations below (see [[RFC3864](#)]):

Header Field Name	Protocol	Status	Reference
Authorization	http	standard	<a href="#">Section 3.1</a>
Proxy-Authenticate	http	standard	<a href="#">Section 3.2</a>
Proxy-Authorization	http	standard	<a href="#">Section 3.3</a>
WWW-Authenticate	http	standard	<a href="#">Section 3.4</a>

The change controller is: "IETF (iesg@ietf.org) - Internet Engineering Task Force".

## 5. Security Considerations

This section is meant to inform application developers, information providers, and users of the security limitations in HTTP/1.1 as described by this document. The discussion does not include

definitive solutions to the problems revealed, though it does make some suggestions for reducing security risks.

### 5.1. Authentication Credentials and Idle Clients

Existing HTTP clients and user agents typically retain authentication information indefinitely. HTTP/1.1 does not provide a method for a server to direct clients to discard these cached credentials. This is a significant defect that requires further extensions to HTTP. Circumstances under which credential caching can interfere with the application's security model include but are not limited to:

- o Clients which have been idle for an extended period following which the server might wish to cause the client to reprompt the user for credentials.
- o Applications which include a session termination indication (such as a `logout' or `commit' button on a page) after which the server side of the application `knows' that there is no further reason for the client to retain the credentials.

This is currently under separate study. There are a number of work-arounds to parts of this problem, and we encourage the use of password protection in screen savers, idle time-outs, and other methods which mitigate the security problems inherent in this problem. In particular, user agents which cache credentials are encouraged to provide a readily accessible mechanism for discarding cached credentials under user control.

## 6. Acknowledgments

[[anchor2: TBD.]]

## 7. References

### 7.1. Normative References

- [Part1] Fielding, R., Ed., Gettys, J., Mogul, J., Frystyk, H., Masinter, L., Leach, P., Berners-Lee, T., Lafon, Y., Ed., and J. Reschke, Ed., "HTTP/1.1, part 1: URIs, Connections, and Message Parsing", [draft-ietf-httpbis-p1-messaging-08](#) (work in progress), October 2009.
- [Part6] Fielding, R., Ed., Gettys, J., Mogul, J., Frystyk, H.,

6: Caching", [draft-ietf-httpbis-p6-cache-08](#) (work in progress), October 2009.

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC2617] Franks, J., Hallam-Baker, P., Hostetler, J., Lawrence, S., Leach, P., Luotonen, A., and L. Stewart, "HTTP Authentication: Basic and Digest Access Authentication", [RFC 2617](#), June 1999.
- [RFC5234] Crocker, D., Ed. and P. Overell, "Augmented BNF for Syntax Specifications: ABNF", STD 68, [RFC 5234](#), January 2008.

## [7.2.](#) Informative References

- [RFC2616] Fielding, R., Gettys, J., Mogul, J., Frystyk, H., Masinter, L., Leach, P., and T. Berners-Lee, "Hypertext Transfer Protocol -- HTTP/1.1", [RFC 2616](#), June 1999.
- [RFC3864] Klyne, G., Nottingham, M., and J. Mogul, "Registration Procedures for Message Header Fields", [BCP 90](#), [RFC 3864](#), September 2004.

## [Appendix A.](#) Compatibility with Previous Versions

### [A.1.](#) Changes from [RFC 2616](#)

## [Appendix B](#). Collected ABNF

```
Authorization = "Authorization:" OWS Authorization-v
Authorization-v = credentials
```

```
OWS = <OWS, defined in \[Part1\], Section 1.2.2>
```

```
Proxy-Authenticate = "Proxy-Authenticate:" OWS Proxy-Authenticate-v
Proxy-Authenticate-v = *( "," OWS ) challenge *( OWS "," [ OWS
  challenge ] )
```

```
Proxy-Authorization = "Proxy-Authorization:" OWS
  Proxy-Authorization-v
Proxy-Authorization-v = credentials
```

```
WWW-Authenticate = "WWW-Authenticate:" OWS WWW-Authenticate-v
WWW-Authenticate-v = *( "," OWS ) challenge *( OWS "," [ OWS
  challenge ] )
```

```
challenge = <challenge, defined in \[RFC2617\], Section 1.2>
credentials = <credentials, defined in \[RFC2617\], Section 1.2>
```

ABNF diagnostics:

```
; Authorization defined but not used
; Proxy-Authenticate defined but not used
; Proxy-Authorization defined but not used
; WWW-Authenticate defined but not used
```

## [Appendix C](#). Change Log (to be removed by RFC Editor before publication)

### [C.1](#). Since [RFC2616](#)

Extracted relevant partitions from [[RFC2616](#)].

[C.2.](#) Since [draft-ietf-httpbis-p7-auth-00](#)

Closed issues:

- o <http://tools.ietf.org/wg/httpbis/trac/ticket/35>: "Normative and Informative references"

[C.3.](#) Since [draft-ietf-httpbis-p7-auth-01](#)

Ongoing work on ABNF conversion

(<http://tools.ietf.org/wg/httpbis/trac/ticket/36>):

Fielding, et al.

Expires April 29, 2010

[Page 11]

---

Internet-Draft

HTTP/1.1, Part 7

October 2009

- o Explicitly import BNF rules for "challenge" and "credentials" from [RFC2617](#).
- o Add explicit references to BNF syntax and rules imported from other parts of the specification.

[C.4.](#) Since [draft-ietf-httpbis-p7-auth-02](#)

Ongoing work on IANA Message Header Registration

(<http://tools.ietf.org/wg/httpbis/trac/ticket/40>):

- o Reference [RFC 3984](#), and update header registrations for headers defined in this document.

[C.5.](#) Since [draft-ietf-httpbis-p7-auth-03](#)

[C.6.](#) Since [draft-ietf-httpbis-p7-auth-04](#)

Ongoing work on ABNF conversion

(<http://tools.ietf.org/wg/httpbis/trac/ticket/36>):

- o Use "/" instead of "|" for alternatives.
- o Introduce new ABNF rules for "bad" whitespace ("BWS"), optional whitespace ("OWS") and required whitespace ("RWS").

- o Rewrite ABNFs to spell out whitespace rules, factor out header value format definitions.

C.7. Since [draft-ietf-httpbis-p7-auth-05](#)

Final work on ABNF conversion

(<<http://tools.ietf.org/wg/httpbis/trac/ticket/36>>):

- o Add appendix containing collected and expanded ABNF, reorganize ABNF introduction.

C.8. Since [draft-ietf-httpbis-p7-auth-06](#)

None.

C.9. Since [draft-ietf-httpbis-p7-auth-07](#)

Closed issues:

- o <<http://tools.ietf.org/wg/httpbis/trac/ticket/198>>: "move IANA registrations for optional status codes"

Index

4

401 Unauthorized (status code) 5

407 Proxy Authentication Required (status code) 5

A

Authorization header 6

G

Grammar

Authorization 6

Authorization-v 6

challenge 5

credentials 5

Proxy-Authenticate 7

Proxy-Authenticate-v 7

Proxy-Authorization 7

Proxy-Authorization-v 7  
WWW-Authenticate 7  
WWW-Authenticate-v 7

## H

### Headers

Authorization 6  
Proxy-Authenticate 6  
Proxy-Authorization 7  
WWW-Authenticate 7

## P

Proxy-Authenticate header 6  
Proxy-Authorization header 7

## S

### Status Codes

401 Unauthorized 5  
407 Proxy Authentication Required 5

## W

WWW-Authenticate header 7

## Authors' Addresses

Roy T. Fielding (editor)  
Day Software  
23 Corporate Plaza DR, Suite 280  
Newport Beach, CA 92660  
USA

Phone: +1-949-706-5300  
Fax: +1-949-706-5305  
Email: fielding@gbiv.com

URI: <http://roy.gbiv.com/>

Jim Gettys  
One Laptop per Child  
21 Oak Knoll Road  
Carlisle, MA 01741  
USA

Email: [jg@laptop.org](mailto:jg@laptop.org)  
URI: <http://www.laptop.org/>

Jeffrey C. Mogul  
Hewlett-Packard Company  
HP Labs, Large Scale Systems Group  
1501 Page Mill Road, MS 1177  
Palo Alto, CA 94304  
USA

Email: [JeffMogul@acm.org](mailto:JeffMogul@acm.org)

Henrik Frystyk Nielsen  
Microsoft Corporation  
1 Microsoft Way  
Redmond, WA 98052  
USA

Email: [henrikn@microsoft.com](mailto:henrikn@microsoft.com)

Larry Masinter  
Adobe Systems, Incorporated  
345 Park Ave  
San Jose, CA 95110



USA

Email: LMM@acm.org

URI: <http://larry.masinter.net/>

Paul J. Leach  
Microsoft Corporation  
1 Microsoft Way  
Redmond, WA 98052

Email: paulle@microsoft.com

Tim Berners-Lee  
World Wide Web Consortium  
MIT Computer Science and Artificial Intelligence Laboratory  
The Stata Center, Building 32  
32 Vassar Street  
Cambridge, MA 02139  
USA

Email: timbl@w3.org

URI: <http://www.w3.org/People/Berners-Lee/>

Yves Lafon (editor)  
World Wide Web Consortium  
W3C / ERCIM  
2004, rte des Lucioles  
Sophia-Antipolis, AM 06902  
France

Email: ylafon@w3.org

URI: <http://www.raubacapeu.net/people/yves/>

Julian F. Reschke (editor)  
greenbytes GmbH  
Hafenweg 16  
Muenster, NW 48155  
Germany

Phone: +49 251 2807760

Fax: +49 251 2807761

Email: [julian.reschke@greenbytes.de](mailto:julian.reschke@greenbytes.de)

URI: <http://greenbytes.de/tech/webdav/>

