

Workgroup: I2NSF Working Group

Internet-Draft:

draft-ietf-i2nsf-nsf-facing-interface-dm-21

Published: 11 February 2022

Intended Status: Standards Track

Expires: 15 August 2022

Authors: J. Kim, Ed.

J. Jeong, Ed.

Sungkyunkwan University

Sungkyunkwan University

J. Park S. Hares Q. Lin

ETRI Huawei Huawei

## **I2NSF Network Security Function-Facing Interface YANG Data Model**

### **Abstract**

This document defines a YANG data model for configuring security policy rules on Network Security Functions (NSF) in the Interface to Network Security Functions (I2NSF) framework. The YANG data model in this document corresponds to the information model for NSF-Facing Interface in the I2NSF framework.

### **Status of This Memo**

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 15 August 2022.

### **Copyright Notice**

Copyright (c) 2022 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Revised BSD License text as described in

Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Revised BSD License.

## Table of Contents

- [1. Introduction](#)
- [2. Terminology](#)
- [3. YANG Tree Diagram](#)
  - [3.1. General I2NSF Security Policy Rule](#)
  - [3.2. Event Clause](#)
  - [3.3. Condition Clause](#)
  - [3.4. Action Clause](#)
- [4. YANG Data Model of NSF-Facing Interface](#)
  - [4.1. YANG Module of NSF-Facing Interface](#)
- [5. XML Configuration Examples of Low-Level Security Policy Rules](#)
  - [5.1. Example Security Requirement 1: Block Social Networking Service \(SNS\) Access during Business Hours](#)
  - [5.2. Example Security Requirement 2: Block Malicious VoIP/VoCN Packets Coming to a Company](#)
  - [5.3. Example Security Requirement 3: Mitigate HTTP and HTTPS Flood Attacks on a Company Web Server](#)
- [6. IANA Considerations](#)
- [7. Security Considerations](#)
- [8. Acknowledgments](#)
- [9. Contributors](#)
- [10. References](#)
  - [10.1. Normative References](#)
  - [10.2. Informative References](#)
- [Authors' Addresses](#)

## 1. Introduction

This document defines a YANG [[RFC6020](#)][[RFC7950](#)] data model for security policy rule configuration of Network Security Functions (NSF). The YANG data model in this document is based on the information and data model in [[I-D.ietf-i2nsf-capability-data-model](#)] for the NSF-Facing Interface in the Interface to Network Security Functions (I2NSF) architecture [[RFC8329](#)]. The YANG data model in this document focuses on security policy configuration for the NSFs discussed in [[I-D.ietf-i2nsf-capability-data-model](#)], i.e., generic NSF (operate on packet header for layer 2, layer3, and layer 4) and advanced NSF (Intrusion Prevention System, URL-Filtering, anti-DDoS, Antivirus, and VoIP/VoCN Filter). Note: VoIP is an abbreviation for Voice over Internet Protocol and VoCN is an abbreviation for Voice over Cellular Network, such as Voice over LTE or 5G.

This YANG data model uses an "Event-Condition-Action" (ECA) policy model that is used as the basis for the design of I2NSF Policy described in [[RFC8329](#)] and [[I-D.ietf-i2nsf-capability-data-model](#)].

The "ietf-i2nsf-policy-rule-for-nsf" YANG module defined in this document provides the configuration of the following features.

\*A security policy rule of a network security function.

\*An event clause of a generic network security function.

\*A condition clause of a generic network security function.

\*An action clause of a generic network security function.

## **2. Terminology**

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in BCP 14 [[RFC2119](#)] [[RFC8174](#)] when, and only when, they appear in all capitals, as shown here.

This document uses the terminology described in [[RFC8329](#)].

This document follows the guidelines of [[RFC8407](#)], uses the common YANG types defined in [[RFC6991](#)], and adopts the Network Management Datastore Architecture (NMDA) [[RFC8342](#)]. The meaning of the symbols in tree diagrams is defined in [[RFC8340](#)].

## **3. YANG Tree Diagram**

This section shows a YANG tree diagram of policy for network security functions. [[I-D.ietf-i2nsf-capability-data-model](#)].

### **3.1. General I2NSF Security Policy Rule**

This section shows a YANG tree diagram for a general I2NSF security policy rule for generic network security functions.

```

module: ietf-i2nsf-policy-rule-for-nsf
+--rw i2nsf-security-policy* [name]
  +--rw name          string
  +--rw priority-usage?      identityref
  +--rw resolution-strategy? identityref
  +--rw default-action?      identityref
  +--rw rules* [name]
    | +--rw name          string
    | +--rw description?   string
    | +--rw priority?      uint8
    | +--rw enable?        boolean
    | +--rw session-aging-time? uint16
    | +--rw long-connection
    | | +--rw enable?      boolean
    | | +--rw duration?    uint16
    | +--rw event
    | | ...
    | +--rw condition
    | | ...
    | +--rw action
    | | ...
  +--rw rule-group
    +--rw groups* [group-name]
      +--rw group-name      string
      +--rw rule-name*      -> ../../../../rules/name
      +--rw enable?         boolean
      +--rw description?    string

```

Figure 1: YANG Tree Diagram for Network Security Policy

A security policy is used by one virtual instance of an NSF/device as a set of security rules to protect assets from major risk factors that threaten the system. There can be multiple security policies in a single NSF to provide the necessary protection. The security policy includes its name, priority usage, resolution strategy, default action, and rules.

A resolution strategy is used to decide how to resolve conflicts that occur between the actions of the same or different policy rules that are matched and contained in a particular NSF. The resolution strategy is defined as First Matching Rule (FMR), Last Matching Rule (LMR), Prioritized Matching Rule (PMR) with Errors (PMRE), and Prioritized Matching Rule with No Errors (PMRN). The resolution strategy can be extended according to specific vendor action features. The resolution strategy is described in detail in [[I-D.ietf-i2nsf-capability-data-model](#)].

A default action is used to execute I2NSF policy rule when no rule matches a packet. The default action is defined as pass, drop,

reject, rate-limit, and mirror. The default action can be extended according to specific vendor action features. The default action is described in detail in [[I-D.ietf-i2nsf-capability-data-model](#)].

The rules include rule name, rule description, rule priority, rule enable, event, condition, and action.

### **3.2. Event Clause**

This section shows a YANG tree diagram for an event clause for a general I2NSF security policy rule for generic network security functions.

```

module: ietf-i2nsf-policy-rule-for-nsf
+--rw i2nsf-security-policy* [name]
...
+--rw rules* [name]
| ...
| +--rw event
| | +--rw description?    string
| | +--rw time
| | | +--rw start-date-time?  yang:date-and-time
| | | +--rw end-date-time?    yang:date-and-time
| | | +--rw period
| | | | +--rw start-time?    time
| | | | +--rw end-time?      time
| | | | +--rw day*           day
| | | | +--rw date*          int8
| | | | +--rw month*         string
| | | +--rw frequency?       enumeration
| | +--rw event-clauses
| |   +--rw system-event*    identityref
| |   +--rw system-alarm*    identityref
| +--rw condition
| ...
| +--rw action
|   ...
+--rw rule-group
...

```

```

module: ietf-i2nsf-policy-rule-for-nsf
+--rw i2nsf-security-policy* [name]
...
+--rw rules* [name]
| ...
| +--rw event
| | +--rw description?    string
| | +--rw time
| | | +--rw start-date-time?  yang:date-and-time
| | | +--rw end-date-time?    yang:date-and-time
| | | +--rw period
| | | | +--rw start-time?    time
| | | | +--rw end-time?      time
| | | | +--rw day*           day
| | | | +--rw date*          int8
| | | | +--rw month*         string
| | | +--rw frequency?       enumeration
| | +--rw event-clauses
| |   +--rw system-event*    identityref
| |   +--rw system-alarm*    identityref
| +--rw condition
| | ...

```

```
|  +--rw action
|      ...
+--rw rule-group
    ...
```

Figure 2: YANG Tree Diagram for an Event Clause

An event clause is any important occurrence at a specific time of a change in the system being managed, and/or in the environment of the system being managed. An event clause is used to trigger the evaluation of the condition clause of the I2NSF Policy Rule. The event clause is defined as a system event, system alarm [[I-D.ietf-i2nsf-nsf-monitoring-data-model](#)] and time. The event clause can be extended according to specific vendor event features. The event clause is described in detail in [[I-D.ietf-i2nsf-capability-data-model](#)].

### 3.3. Condition Clause

This section shows a YANG tree diagram for a condition clause for a general I2NSF security policy rule for generic network security functions.



```

module: ietf-i2nsf-policy-rule-for-nsf
+--rw i2nsf-security-policy* [name]
    ...
+--rw rules* [name]
    |   ...
    |   +--rw event
    |   |   ...
    |   +--rw condition
    |   |   +--rw description?      string
    |   |   +--rw ethernet
    |   |   |   +--rw description?      string
    |   |   |   +--rw destination-mac-address?  yang:mac-address
    |   |   |   +--rw destination-mac-address-mask? yang:mac-address
    |   |   |   +--rw source-mac-address?  yang:mac-address
    |   |   |   +--rw source-mac-address-mask? yang:mac-address
    |   |   |   +--rw ethertype?          eth:ethertype
    |   |   +--rw ipv4
    |   |   |   +--rw description?      string
    |   |   |   +--rw dscp?              inet:dscp
    |   |   |   +--rw ecn?              uint8
    |   |   |   +--rw length?           uint16
    |   |   |   +--rw ttl?              uint8
    |   |   |   +--rw protocol?         uint8
    |   |   |   +--rw ihl?              uint8
    |   |   |   +--rw flags?            bits
    |   |   |   +--rw offset?           uint16
    |   |   |   +--rw identification?    uint16
    |   |   |   +--rw (destination-network)?
    |   |   |   |   +--:(destination-ipv4-network)
    |   |   |   |   |   +--rw destination-ipv4-network?  inet:ipv4-prefix
    |   |   |   |   |   +--:(destination-ipv4-range)
    |   |   |   |   |   +--rw destination-ipv4-range* [start end]
    |   |   |   |   |   |   +--rw start      inet:ipv4-address-no-zone
    |   |   |   |   |   |   +--rw end        inet:ipv4-address-no-zone
    |   |   |   +--rw (source-network)?
    |   |   |   |   +--:(source-ipv4-network)
    |   |   |   |   |   +--rw source-ipv4-network?      inet:ipv4-prefix
    |   |   |   |   +--:(source-ipv4-range)
    |   |   |   |   |   +--rw source-ipv4-range* [start end]
    |   |   |   |   |   |   +--rw start      inet:ipv4-address-no-zone
    |   |   |   |   |   |   +--rw end        inet:ipv4-address-no-zone
    |   |   +--rw ipv6
    |   |   |   +--rw description?      string
    |   |   |   +--rw dscp?              inet:dscp
    |   |   |   +--rw ecn?              uint8
    |   |   |   +--rw length?           uint16
    |   |   |   +--rw ttl?              uint8
    |   |   |   +--rw protocol?         uint8
    |   |   |   +--rw (destination-network)?

```

```

| | | | +--:(destination-ipv6-network)
| | | | | +--rw destination-ipv6-network? inet:ipv6-prefix
| | | | +--:(destination-ipv6-range)
| | | | | +--rw destination-ipv6-range* [start end]
| | | | | +--rw start inet:ipv6-address-no-zone
| | | | | +--rw end inet:ipv6-address-no-zone
| | | +--rw (source-network)?
| | | | +--:(source-ipv6-network)
| | | | | +--rw source-ipv6-network? inet:ipv6-prefix
| | | | +--:(source-ipv6-range)
| | | | | +--rw source-ipv6-range* [start end]
| | | | | +--rw start inet:ipv6-address-no-zone
| | | | | +--rw end inet:ipv6-address-no-zone
| | | +--rw flow-label? inet:ipv6-flow-label
| | +--rw tcp
| | | +--rw description? string
| | | +--rw source-port-number
| | | | +--rw (source-port)?
| | | | | +--:(range-or-operator)
| | | | | | +--rw (port-range-or-operator)?
| | | | | | | +--:(range)
| | | | | | | | +--rw lower-port inet:port-number
| | | | | | | | +--rw upper-port inet:port-number
| | | | | | | +--:(operator)
| | | | | | | +--rw operator? operator
| | | | | | | +--rw port inet:port-number
| | | | | +--:(port-list)
| | | | | +--rw port-numbers* [start end]
| | | | | +--rw start inet:port-number
| | | | | +--rw end inet:port-number
| | | +--rw destination-port-number
| | | | +--rw (destination-port)?
| | | | | +--:(range-or-operator)
| | | | | | +--rw (port-range-or-operator)?
| | | | | | | +--:(range)
| | | | | | | | +--rw lower-port inet:port-number
| | | | | | | | +--rw upper-port inet:port-number
| | | | | | | +--:(operator)
| | | | | | | +--rw operator? operator
| | | | | | | +--rw port inet:port-number
| | | | | +--:(port-list)
| | | | | +--rw port-numbers* [start end]
| | | | | +--rw start inet:port-number
| | | | | +--rw end inet:port-number
| | | +--rw sequence-number? uint32
| | | +--rw acknowledgement-number? uint32
| | | +--rw data-offset? uint8
| | | +--rw reserved? uint8
| | | +--rw flags? bits

```

			+++rw window-size?	uint16
			+++rw urgent-pointer?	uint16
			+++rw options?	binary
			+++rw udp	
			+++rw description?	string
			+++rw source-port-number	
			+++rw (source-port)?	
			+++:(range-or-operator)	
			+++rw (port-range-or-operator)?	
			+++:(range)	
			+++rw lower-port	inet:port-number
			+++rw upper-port	inet:port-number
			+++:(operator)	
			+++rw operator?	operator
			+++rw port	inet:port-number
			+++:(port-list)	
			+++rw port-numbers* [start end]	
			+++rw start	inet:port-number
			+++rw end	inet:port-number
			+++rw destination-port-number	
			+++rw (destination-port)?	
			+++:(range-or-operator)	
			+++rw (port-range-or-operator)?	
			+++:(range)	
			+++rw lower-port	inet:port-number
			+++rw upper-port	inet:port-number
			+++:(operator)	
			+++rw operator?	operator
			+++rw port	inet:port-number
			+++:(port-list)	
			+++rw port-numbers* [start end]	
			+++rw start	inet:port-number
			+++rw end	inet:port-number
			+++rw length?	uint16
			+++rw sctp	
			+++rw description?	string
			+++rw source-port-number	
			+++rw (source-port)?	
			+++:(range-or-operator)	
			+++rw (port-range-or-operator)?	
			+++:(range)	
			+++rw lower-port	inet:port-number
			+++rw upper-port	inet:port-number
			+++:(operator)	
			+++rw operator?	operator
			+++rw port	inet:port-number
			+++:(port-list)	
			+++rw port-numbers* [start end]	
			+++rw start	inet:port-number

```

| | | | +--rw end inet:port-number
| | | +--rw destination-port-number
| | | | +--rw (destination-port)?
| | | | +--:(range-or-operator)
| | | | | +--rw (port-range-or-operator)?
| | | | | +--:(range)
| | | | | | +--rw lower-port inet:port-number
| | | | | | +--rw upper-port inet:port-number
| | | | | +--:(operator)
| | | | | +--rw operator? operator
| | | | | +--rw port inet:port-number
| | | | +--:(port-list)
| | | | +--rw port-numbers* [start end]
| | | | +--rw start inet:port-number
| | | | +--rw end inet:port-number
| | | +--rw chunk-type* uint8
| | | +--rw chunk-length? uint16
| | +--rw dccp
| | | +--rw description? string
| | | +--rw source-port-number
| | | | +--rw (source-port)?
| | | | +--:(range-or-operator)
| | | | | +--rw (port-range-or-operator)?
| | | | | +--:(range)
| | | | | | +--rw lower-port inet:port-number
| | | | | | +--rw upper-port inet:port-number
| | | | | +--:(operator)
| | | | | +--rw operator? operator
| | | | | +--rw port inet:port-number
| | | | +--:(port-list)
| | | | +--rw port-numbers* [start end]
| | | | +--rw start inet:port-number
| | | | +--rw end inet:port-number
| | | +--rw destination-port-number
| | | | +--rw (destination-port)?
| | | | +--:(range-or-operator)
| | | | | +--rw (port-range-or-operator)?
| | | | | +--:(range)
| | | | | | +--rw lower-port inet:port-number
| | | | | | +--rw upper-port inet:port-number
| | | | | +--:(operator)
| | | | | +--rw operator? operator
| | | | | +--rw port inet:port-number
| | | | +--:(port-list)
| | | | +--rw port-numbers* [start end]
| | | | +--rw start inet:port-number
| | | | +--rw end inet:port-number
| | | +--rw service-code* uint32
| | | +--rw type* uint8

```

```

| | | +--rw data-offset?          uint8
| | +--rw icmp* [version]
| | | +--rw description?         string
| | | +--rw version              enumeration
| | | +--rw type?                uint8
| | | +--rw code?                uint8
| | | +--rw rest-of-header?      binary
| | +--rw url-category
| | | +--rw description?         string
| | | +--rw pre-defined*        string
| | | +--rw user-defined*       string
| | +--rw voice
| | | +--rw description?         string
| | | +--rw source-voice-id*     string
| | | +--rw destination-voice-id* string
| | | +--rw user-agent*         string
| | +--rw ddos
| | | +--rw description?         string
| | | +--rw alert-packet-rate?   uint32
| | | +--rw alert-flow-rate?     uint32
| | | +--rw alert-byte-rate?     uint32
| | +--rw anti-virus
| | | +--rw profile*            string
| | | +--rw exception-files*    string
| | +--rw payload
| | | +--rw description?         string
| | | +--rw content*            string
| | +--rw context
| | | +--rw description?         string
| | | +--rw application
| | | | +--rw description?       string
| | | | +--rw protocol*         identityref
| | | +--rw device-type
| | | | +--rw description?       string
| | | | +--rw device*           identityref
| | | +--rw users
| | | | +--rw description?       string
| | | | +--rw user* [id]
| | | | | +--rw id              uint32
| | | | | +--rw name?          string
| | | | | +--rw group* [id]
| | | | | | +--rw id            uint32
| | | | | | +--rw name?        string
| | | | | +--rw security-group? string
| | | +--rw geographic-location
| | | | +--rw description?       string
| | | | +--rw source*           string
| | | | +--rw destination*      string
| | +--rw action

```

```
| ...  
+--rw rule-group  
    ...
```

Figure 3: YANG Tree Diagram for a Condition Clause

A condition clause is defined as a set of attributes, features, and/or values that are to be compared with a set of known attributes, features, and/or values in order to determine whether the set of actions in that (imperative) I2NSF policy rule can be executed or not. A condition clause is classified as a condition of generic network security functions, advanced network security functions, or context. A condition clause of generic network security functions is defined as IPv4 condition, IPv6 condition, TCP condition, UDP condition, SCTP condition, DCCP condition, or ICMP (ICMPv4 and ICMPv6) condition.

Note that the data model in this document does not focus on only IP addresses, but focuses on all the fields of IPv4 and IPv6 headers. The IPv4 and IPv6 headers have similarity with some different fields. In this case, it is better to handle separately the IPv4 and IPv6 headers such that the different fields can be used to handle IPv4 and IPv6 packets.

A condition clause of advanced network security functions is defined as url category condition, voice condition, DDoS condition, or payload condition. A condition clause of context is defined as application condition, target condition, users condition, and geography condition.

Note that this document deals only with conditions of several advanced network security functions such as url filter (i.e., web filter), VoIP/VoCN security, and DDoS-attack mitigator. A condition clause of other advanced network security functions such as Intrusion Prevention System (IPS) and Data Loss Prevention (DLP) can be defined as an extension in future. A condition clause can be extended according to specific vendor condition features. A condition clause is described in detail in [[I-D.ietf-i2nsf-capability-data-model](#)].

### 3.4. Action Clause

This section shows a YANG tree diagram for an action clause for a general I2NSF security policy rule for generic network security functions.

```

module: ietf-i2nsf-policy-rule-for-nsf
+--rw i2nsf-security-policy* [name]
    ...
+--rw rules* [name]
    |   ...
    |   +--rw event
    |   |   ...
    |   +--rw condition
    |   |   ...
    |   +--rw action
    |       +--rw description?          string
    |       +--rw packet-action
    |           |   +--rw ingress-action?  identityref
    |           |   +--rw egress-action?   identityref
    |           |   +--rw log-action?      identityref
    |       +--rw flow-action
    |           |   +--rw ingress-action?  identityref
    |           |   +--rw egress-action?   identityref
    |           |   +--rw log-action?      identityref
    |       +--rw advanced-action
    |           +--rw content-security-control*  identityref
    |           +--rw attack-mitigation-control* identityref
+--rw rule-group
    ...

```

Figure 4: YANG Tree Diagram for an Action Clause

An action is used to control and monitor aspects of flow-based NSFs when the policy rule event and condition clauses are satisfied. NSFs provide security services by executing various actions. The action clause is defined as ingress action, egress action, or log action for packet action, flow action, and advanced action for additional inspection. The packet action is an action for an individual packet such as an IP datagram as a stateless process that uses the packet's header and payload. The flow action is an action of a traffic flow such as the packets of a TCP session (e.g., an HTTP/HTTPS session) as a stateful process that uses the traffic flow information such as 5-tuple information, packet counts, and byte counts. The advanced action is an action for an advanced security service (e.g., url filter, DDoS-attack mitigator, and VoIP/VoCN filter) for either a packet or a traffic flow according to the intention of such an advanced security service. The action clause can be extended according to specific vendor action features. The action clause is described in detail in [[I-D.ietf-i2nsf-capability-data-model](#)].

#### 4. YANG Data Model of NSF-Facing Interface

The main objective of this data model is to provide both an information model and the corresponding YANG data model of I2NSF



NSF-Facing Interface. This interface can be used to deliver control and management messages between Security Controller and NSFs for the I2NSF low-level security policies.

This data model is designed to support the I2NSF framework that can be extended according to the security needs. In other words, the model design is independent of the content and meaning of specific policies as well as the implementation approach.

With the YANG data model of I2NSF NSF-Facing Interface, this document suggests use cases for security policy rules such as time-based firewall, web filter, VoIP/VoCN security service, and DDoS-attack mitigation in [Section 5](#).

#### 4.1. YANG Module of NSF-Facing Interface

This section describes a YANG module of NSF-Facing Interface. This document provides identities in the data model for the configuration of an NSF. The identity has the same concept with the corresponding identity in [[I-D.ietf-i2nsf-consumer-facing-interface-dm](#)]. This YANG module imports from [[RFC6991](#)] and [[RFC8519](#)]. It makes references to [[RFC0768](#)] [[RFC0791](#)] [[RFC0792](#)] [[RFC0854](#)] [[RFC0959](#)] [[RFC1939](#)] [[RFC2595](#)] [[RFC3261](#)] [[RFC4250](#)] [[RFC4340](#)] [[RFC4443](#)] [[RFC4732](#)] [[RFC4987](#)] [[RFC5321](#)] [[RFC5595](#)] [[RFC6335](#)] [[RFC8075](#)] [[RFC8200](#)] [[RFC8329](#)] [[RFC8335](#)] [[RFC9051](#)] [[IEEE-802.3](#)] [[ISO-3166](#)] [[I-D.ietf-httpbis-http2bis](#)] [[I-D.ietf-httpbis-messaging](#)] [[I-D.ietf-httpbis-semantics](#)] [[I-D.ietf-netmod-geo-location](#)]. [[I-D.ietf-i2nsf-capability-data-model](#)] [[I-D.ietf-i2nsf-nsf-monitoring-data-model](#)] [[I-D.ietf-tcpm-rfc793bis](#)] [[I-D.ietf-tsvwg-rfc4960-bis](#)]

<CODE BEGINS> file "ietf-i2nsf-policy-rule-for-nsf@2022-02-11.yang"

```
module ietf-i2nsf-policy-rule-for-nsf {
  yang-version 1.1;
  namespace
    "urn:ietf:params:xml:ns:yang:ietf-i2nsf-policy-rule-for-nsf";
  prefix
    nsfintf;

  import ietf-inet-types{
    prefix inet;
    reference
      "Section 4 of RFC 6991";
  }
  import ietf-yang-types {
    prefix yang;
    reference
      "Section 3 of RFC 6991";
  }
  import ietf-packet-fields {
    prefix packet-fields;
    reference
      "Section 4.2 of RFC 8519";
  }

  organization
    "IETF I2NSF (Interface to Network Security Functions)
    Working Group";

  contact
    "WG Web: <https://datatracker.ietf.org/wg/i2nsf>
    WG List: <mailto:i2nsf@ietf.org>

    Editor: Jinyong Tim Kim
    <mailto:timkim@skku.edu>

    Editor: Jaehoon Paul Jeong
    <mailto:pauljeong@skku.edu>";

  description
    "This module is a YANG module for Network Security Functions
    (NSF)-Facing Interface.

    The key words 'MUST', 'MUST NOT', 'REQUIRED', 'SHALL',
    'SHALL NOT', 'SHOULD', 'SHOULD NOT', 'RECOMMENDED',
    'NOT RECOMMENDED', 'MAY', and 'OPTIONAL' in this
    document are to be interpreted as described in BCP 14
    (RFC 2119) (RFC 8174) when, and only when, they appear
    in all capitals, as shown here.
```

Copyright (c) 2022 IETF Trust and the persons identified as authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, is permitted pursuant to, and subject to the license terms contained in, the Simplified BSD License set forth in Section 4.c of the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>).

This version of this YANG module is part of RFC XXXX (<https://www.rfc-editor.org/info/rfcXXXX>); see the RFC itself for full legal notices.";

```
revision "2022-02-11"{
  description "The latest revision.";
  reference
    "RFC XXXX: I2NSF Network Security Function-Facing Interface
    YANG Data Model";
}

/*
 * Identities
 */

identity priority-usage {
  description
    "Base identity for priority usage type to define the type of
    priority to be implemented in a security policy rule, such
    as priority by order and priority by number.";
}

identity priority-by-order {
  base priority-usage;
  description
    "Identity for priority by order. This indicates the
    priority of a security policy rule follows the order of the
    configuration. The earlier the configuration is, the higher
    the priority is.";
}

identity priority-by-number {
  base priority-usage;
  description
    "Identity for priority by number. This indicates the priority
    of a security policy rule follows the number or value of the
    configuration. The higher the value is, the higher the
    priority is.";
}
```

```

identity event {
    description
        "Base identity for policy events.";
    reference
        "draft-ietf-i2nsf-nsf-monitoring-data-model-14: I2NSF NSF
        Monitoring Interface YANG Data Model - Event";
}

identity system-event {
    base event;
    description
        "Base Identity for system events. System event (also called
        alert) is defined as a warning about any changes of
        configuration, any access violation, the information of
        sessions and traffic flows.";
    reference
        "draft-ietf-i2nsf-nsf-monitoring-data-model-14: I2NSF NSF
        Monitoring Interface YANG Data Model - System event";
}

identity system-alarm {
    base event;
    description
        "Base identity for system alarms. System alarm is defined as a
        warning related to service degradation in system hardware.";
    reference
        "draft-ietf-i2nsf-nsf-monitoring-data-model-14: I2NSF NSF
        Monitoring Interface YANG Data Model - System alarm";
}

identity access-violation {
    base system-event;
    description
        "Identity for access-violation. Access-violation system
        event is an event when a user tries to access (read, write,
        create, or delete) any information or execute commands
        above their privilege (i.e., not-conformant with the
        access profile).";
    reference
        "draft-ietf-i2nsf-nsf-monitoring-data-model-14: I2NSF NSF
        Monitoring Interface YANG Data Model - System event for access
        violation";
}

identity configuration-change {
    base system-event;
    description
        "Identity for configuration change. Configuration change is
        a system event when a new configuration is added or an

```

```

        existing configuration is modified.";
reference
    "draft-ietf-i2nsf-nsf-monitoring-data-model-14: I2NSF NSF
    Monitoring Interface YANG Data Model - System event for
    configuration change";
}

identity memory-alarm {
    base system-alarm;
    description
        "Identity for memory alarm. Memory is the hardware to store
        information temporarily or for a short period, i.e., Random
        Access Memory (RAM). A memory-alarm is emitted when the memory
        usage is exceeding the threshold.";
    reference
        "draft-ietf-i2nsf-nsf-monitoring-data-model-14: I2NSF NSF
        Monitoring Interface YANG Data Model - System alarm for
        memory";
}

identity cpu-alarm {
    base system-alarm;
    description
        "Identity for CPU alarm. CPU is the Central Processing Unit
        that executes basic operations of the system. A cpu-alarm
        is emitted when the CPU usage is exceeding a threshold.";
    reference
        "draft-ietf-i2nsf-nsf-monitoring-data-model-14: I2NSF NSF
        Monitoring Interface YANG Data Model - System alarm for CPU";
}

identity disk-alarm {
    base system-alarm;
    description
        "Identity for disk alarm. Disk is the hardware to store
        information for a long period, i.e., Hard Disk and Solid-State
        Drive. A disk-alarm is emitted when the disk usage is
        exceeding a threshold.";
    reference
        "draft-ietf-i2nsf-nsf-monitoring-data-model-14: I2NSF NSF
        Monitoring Interface YANG Data Model - System alarm for disk";
}

identity hardware-alarm {
    base system-alarm;
    description
        "Identity for hardware alarm. A hardware alarm is emitted
        when a problem of hardware (e.g., CPU, memory, disk, or
        interface) is detected.";

```

```

    reference
      "draft-ietf-i2nsf-nsf-monitoring-data-model-14: I2NSF NSF
        Monitoring Interface YANG Data Model - System alarm for
        hardware";
  }

  identity interface-alarm {
    base system-alarm;
    description
      "Identity for interface alarm. Interface is the network
        interface for connecting a device with the network. The
        interface-alarm is emitted when the state of the interface
        is changed.";
    reference
      "draft-ietf-i2nsf-nsf-monitoring-data-model-14: I2NSF NSF
        Monitoring Interface YANG Data Model - System alarm for
        interface";
  }

  identity device-type {
    description
      "Base identity for types of device. This identity is used for
        type of the device for the source or destination of a packet
        or traffic flow.";
    reference
      "draft-ietf-i2nsf-capability-data-model-26:
        I2NSF Capability YANG Data Model";
  }

  identity computer {
    base device-type;
    description
      "Identity for computer such as personal computer (PC)
        and server.";
  }

  identity mobile-phone {
    base device-type;
    description
      "Identity for mobile-phone such as smartphone and
        cellphone";
  }

  identity voip-vocn-phone {
    base device-type;
    description
      "Identity for VoIP (Voice over Internet Protocol) or VoCN
        (Voice over Cellular Network, such as Voice over LTE or 5G)
        phone";
  }

```

```

}

identity tablet {
    base device-type;
    description
        "Identity for tablet devices";
}

identity network-infrastructure-device {
    base device-type;
    description
        "Identity for network infrastructure devices
        such as switch, router, and access point";
}

identity iot-device {
    base device-type;
    description
        "Identity for Internet of Things (IoT) devices
        such as sensors, actuators, and low-power
        low-capacity computing devices";
}

identity ot {
    base device-type;
    description
        "Identity for Operational Technology (OT) devices (also
        known as industrial control systems) that interact
        with the physical environment and detect or cause direct
        change through the monitoring and control of devices,
        processes, and events such as programmable logic
        controllers (PLCs), digital oscilloscopes, building
        management systems (BMS), and fire control systems";
}

identity vehicle {
    base device-type;
    description
        "Identity for transportation vehicles that connect to and
        share data through the Internet over Vehicle-to-Everything
        (V2X) communications.";
}

identity advanced-nsf {
    description
        "Base identity for advanced Network Security Function (NSF)
        capability. This can be used for advanced NSFs such as
        Anti-DDoS Attack, IPS, URL-Filtering, Antivirus,
        and VoIP/VoCN Filter.";
}

```

```

    reference
      "draft-ietf-i2nsf-capability-data-model-26:
        I2NSF Capability YANG Data Model";
  }

  identity content-security-control {
    base advanced-nsf;
    description
      "Base identity for content security control. Content security
        control is an NSF that evaluates the payload of a packet,
        such as Intrusion Prevention System (IPS), URL Filter,
        Antivirus, and VoIP/VoCN Filter.";
    reference
      "draft-ietf-i2nsf-capability-data-model-26:
        I2NSF Capability YANG Data Model";
  }

  identity ips {
    base content-security-control;
    description
      "Identity for IPS (Intrusion Prevention System)
        that prevents malicious activity within a network";
  }

  identity url-filtering {
    base content-security-control;
    description
      "Identity for url filtering that limits access by comparing the
        web traffic's URL with the URLs for web filtering in a
        database";
  }

  identity anti-virus {
    base content-security-control;
    description
      "Identity for antivirus to protect the network by detecting and
        removing viruses or malwares.";
  }

  identity voip-vocn-filtering {
    base content-security-control;
    description
      "Identity for VoIP (Voice over Internet Protocol) and
        VoCN (Voice over Cellular Network, such as Voice over LTE or
        5G) security service that filters out the packets or flows
        of malicious users with a deny-list of malicious users in
        a database";
  }

```



```
identity attack-mitigation-control {
    base advanced-nsf;
    description
        "Base identity for attack mitigation control. Attack mitigation
        control is an NSF that mitigates an attack such as
        anti-DDoS (i.e., DDoS-mitigator).";
    reference
        "draft-ietf-i2nsf-capability-data-model-26:
        I2NSF Capability YANG Data Model";
}
```

```
identity anti-ddos {
    base attack-mitigation-control;
    description
        "Identity for advanced NSF Anti-DDoS or DDoS Mitigator to
        protect a server or network from a DDoS attack. The mitigation
        approach is up to the implementation.";
    reference
        "RFC 4732: Internet Denial-of-Service Considerations - DoS
        Mitigation Strategies
        RFC 4987: TCP SYN Flooding Attacks and Common Mitigations -
        Common Defenses";
}
```

```
identity action {
    description
        "Base identity for action.";
}
```

```
identity ingress-action {
    base action;
    description
        "Base identity for ingress action. The action to handle the
        network traffic that is entering the secured network.";
    reference
        "draft-ietf-i2nsf-capability-data-model-26:
        I2NSF Capability YANG Data Model - Ingress Action";
}
```

```
identity egress-action {
    base action;
    description
        "Base identity for egress action. The action to handle the
        network traffic that is exiting the secured network.";
    reference
        "draft-ietf-i2nsf-capability-data-model-26:
        I2NSF Capability YANG Data Model - Egress Action";
}
```

```

identity default-action {
    base action;
    description
        "Base identity for default action. The default action of the
        NSF when no rule matches the packet or flow.";
    reference
        "draft-ietf-i2nsf-capability-data-model-26:
        I2NSF Capability YANG Data Model - Default Action";
}

identity pass {
    base ingress-action;
    base egress-action;
    base default-action;
    description
        "Identity for pass. The pass action allows traffic that matches
        the rule to proceed through the NSF to reach the
        destination.";
    reference
        "draft-ietf-i2nsf-capability-data-model-26:
        I2NSF Capability YANG Data Model - Actions and
        Default Action";
}

identity drop {
    base ingress-action;
    base egress-action;
    base default-action;
    description
        "Identity for drop. The drop action denies the traffic that
        matches the rule. The drop action should do a silent drop,
        which does not give any response to the source.";
    reference
        "draft-ietf-i2nsf-capability-data-model-26:
        I2NSF Capability YANG Data Model - Actions and
        Default Action";
}

identity reject {
    base ingress-action;
    base egress-action;
    base default-action;
    description
        "Identity for reject action capability. The reject action
        denies a packet to go through the NSF entering or exiting the
        internal network and sends a response back to the source.
        The response depends on the packet and implementation.
        For example, a TCP packet is rejected with TCP RST response
        or a UDP packet may be rejected with an ICMP response message

```

```

        with Type 3 Code 3, i.e., Destination Unreachable: Destination
        port unreachable.";
    }

    identity mirror {
        base ingress-action;
        base egress-action;
        base default-action;
        description
            "Identity for mirror. The mirror action copies a packet and
            sends the packet's copy to the monitoring entity while still
            allowing the packet or flow to go through the NSF.";
        reference
            "draft-ietf-i2nsf-capability-data-model-26:
            I2NSF Capability YANG Data Model - Actions and
            Default Action";
    }

    identity rate-limit {
        base ingress-action;
        base egress-action;
        base default-action;
        description
            "Identity for rate limiting action. The rate limit action
            limits the number of packets or flows that can go through the
            NSF by dropping packets or flows (randomly or
            systematically). The drop mechanism, e.g., silent drop and
            unreachable drop (i.e., reject), is up to the implementation";
        reference
            "draft-ietf-i2nsf-capability-data-model-26:
            I2NSF Capability YANG Data Model - Actions and
            Default Action";
    }

    identity log-action {
        base action;
        description
            "Base identity for log action";
    }

    identity rule-log {
        base log-action;
        description
            "Identity for rule log. Log the received packet or flow based
            on the rule.";
    }

    identity session-log {
        base log-action;
    }

```

```

    description
        "Identity for session log. Log the tasks that is performed
        during a session.";
}

identity invoke-signaling {
    base egress-action;
    description
        "Identity for invoke signaling. The invoke-signaling action
        is used to convey information of the event triggering this
        action to a monitoring entity.";
}

identity tunnel-encapsulation {
    base egress-action;
    description
        "Identity for tunnel encapsulation. The tunnel encapsulation
        action is used to encapsulate the packet to be tunneled across
        the network to enable a secure connection.";
}

identity forwarding {
    base egress-action;
    description
        "Identity for forwarding. The forwarding action is used to
        relay the packet from one network segment to another node
        in the network.";
}

identity transformation {
    base egress-action;
    description
        "Identity for transformation. The transformation action is used
        to transform the packet by modifying its protocol header such
        as HTTP-to-CoAP translation.";
    reference
        "RFC 8075: Guidelines for Mapping Implementations: HTTP to the
        Constrained Application Protocol (CoAP) - Translation between
        HTTP and CoAP.";
}

identity redirection {
    base egress-action;
    description
        "Identity for redirection. This action redirects the packet to
        another destination.";
}

identity resolution-strategy {

```

```

    description
        "Base identity for resolution strategy";
    reference
        "draft-ietf-i2nsf-capability-data-model-26:
        I2NSF Capability YANG Data Model - Resolution Strategy";
}

identity fmr {
    base resolution-strategy;
    description
        "Identity for First Matching Rule (FMR)";
    reference
        "draft-ietf-i2nsf-capability-data-model-26:
        I2NSF Capability YANG Data Model - Resolution Strategy";
}

identity lmr {
    base resolution-strategy;
    description
        "Identity for Last Matching Rule (LMR)";
    reference
        "draft-ietf-i2nsf-capability-data-model-26:
        I2NSF Capability YANG Data Model - Resolution Strategy";
}

identity pmre {
    base resolution-strategy;
    description
        "Identity for Prioritized Matching Rule with Errors (PMRE)";
    reference
        "draft-ietf-i2nsf-capability-data-model-26:
        I2NSF Capability YANG Data Model - Resolution Strategy";
}

identity pmrn {
    base resolution-strategy;
    description
        "Identity for Prioritized Matching Rule with No Errors (PMRN)";
    reference
        "draft-ietf-i2nsf-capability-data-model-26:
        I2NSF Capability YANG Data Model - Resolution Strategy";
}

identity application-protocol {
    description
        "Base identity for Application protocol";
}

identity http {

```

```

base application-protocol;
description
    "The identity for Hypertext Transfer Protocol version 1.X
    (HTTP/1.X).";
reference
    "draft-ietf-httpbis-semantics-19: HTTP Semantics
    draft-ietf-httpbis-messaging-19: HTTP/1.1";
}

identity https {
    base application-protocol;
    description
        "The identity for Hypertext Transfer Protocol version 1.X
        (HTTP/1.X) over TLS.";
    reference
        "draft-ietf-httpbis-semantics-19: HTTP Semantics
        draft-ietf-httpbis-messaging-19: HTTP/1.1";
}

identity http-2 {
    base application-protocol;
    description
        "The identity for Hypertext Transfer Protocol version 2
        (HTTP/2).";
    reference
        "draft-ietf-httpbis-http2bis-07: HTTP/2";
}

identity https-2 {
    base application-protocol;
    description
        "The identity for Hypertext Transfer Protocol version 2
        (HTTP/2) over TLS.";
    reference
        "draft-ietf-httpbis-http2bis-07: HTTP/2";
}

identity ftp {
    base application-protocol;
    description
        "The identity for File Transfer Protocol.";
    reference
        "RFC 959: File Transfer Protocol (FTP)";
}

identity ssh {
    base application-protocol;
    description
        "The identity for Secure Shell (SSH) protocol.";
}

```

```

    reference
      "RFC 4250: The Secure Shell (SSH) Protocol";
  }

  identity telnet {
    base application-protocol;
    description
      "The identity for telnet.";
    reference
      "RFC 854: Telnet Protocol";
  }

  identity smtp {
    base application-protocol;
    description
      "The identity for Simple Mail Transfer Protocol.";
    reference
      "RFC 5321: Simple Mail Transfer Protocol (SMTP)";
  }

  identity pop3 {
    base application-protocol;
    description
      "The identity for Post Office Protocol 3 (POP3).";
    reference
      "RFC 1939: Post Office Protocol - Version 3 (POP3)";
  }

  identity pop3s {
    base application-protocol;
    description
      "The identity for Post Office Protocol 3 (POP3) over TLS";
    reference
      "RFC 1939: Post Office Protocol - Version 3 (POP3)
      RFC 2595: Using TLS with IMAP, POP3 and ACAP";
  }

  identity imap {
    base application-protocol;
    description
      "The identity for Internet Message Access Protocol (IMAP).";
    reference
      "RFC 9051: Internet Message Access Protocol (IMAP) - Version
      4rev2";
  }

  identity imaps {
    base application-protocol;
    description

```

```

    "The identity for Internet Message Access Protocol (IMAP) over
    TLS";
reference
    "RFC 9051: Internet Message Access Protocol (IMAP) - Version
    4rev2
    RFC 2595: Using TLS with IMAP, POP3 and ACAP";
}

/*
 * Typedefs
 */

typedef time {
    type string {
        pattern '(0[0-9]|1[0-9]|2[0-3]):[0-5][0-9]:[0-5][0-9](\\.\\d+)?'
        + '(Z|\\+\\-)((1[0-3]|0[0-9]):([0-5][0-9])|14:00))?';
    }
    description
        "The time type represents an instance of time of zero-duration
        that recurs every day.";
}

typedef day {
    type enumeration {
        enum monday {
            description
                "This represents Monday.";
        }
        enum tuesday {
            description
                "This represents Tuesday.";
        }
        enum wednesday {
            description
                "This represents Wednesday";
        }
        enum thursday {
            description
                "This represents Thursday.";
        }
        enum friday {
            description
                "This represents Friday.";
        }
        enum saturday {
            description
                "This represents Saturday.";
        }
        enum sunday {

```



```

        description
            "This represents Sunday.";
    }
}
description
    "The type for representing the day of the week.";
}

/*
 * Groupings
 */

grouping port-range {
    leaf start {
        type inet:port-number;
        description
            "A start port number for a range match.";
    }
    leaf end {
        type inet:port-number;
        must '. >= ../start' {
            error-message
                "An end port number MUST be equal to or greater than a
                start port number.";
        }
        description
            "An end port number for a range match.";
    }
    description
        "A range match for port numbers. If only one value is needed,
        then set both start and end to the same value.";
    reference
        "draft-ietf-tcpm-rfc793bis-25: Transmission Control Protocol
        (TCP) Specification - Port Number
        RFC 768: User Datagram Protocol - Port Number
        draft-ietf-tsvwg-rfc4960-bis-18: Stream Control Transmission
        Protocol - Port Number
        RFC 4340: Datagram Congestion Control Protocol (DCCP)
        - Port Number";
}

grouping ipv4-range {
    description
        "A range match for IPv4 addresses. If only one value is
        needed, then set both start and end to the same value.
        The end IPv4 address MUST be equal to or greater than the
        start IPv4 address.";
    leaf start {
        type inet:ipv4-address-no-zone;

```

```

        description
            "A start IPv4 address for a range match.";
    }
    leaf end {
        type inet:ipv4-address-no-zone;
        description
            "An end IPv4 address for a range match.";
    }
    reference
        "RFC 791: Internet Protocol - IPv4 address";
}

grouping ipv6-range {
    description
        "A range match for IPv6 addresses.  If only one value is
        needed, then set both start and end to the same value.
        The end IPv6 address MUST be equal to or greater than the
        start IPv6 address.";
    leaf start {
        type inet:ipv6-address-no-zone;
        description
            "A start IPv6 address for a range match.";
    }

    leaf end {
        type inet:ipv6-address-no-zone;
        description
            "An end IPv6 address for a range match.";
    }
    reference
        "RFC 8200: Internet Protocol, Version 6 (IPv6)
        Specification - IPv6 address";
}

/*
 * Data nodes
 */

list i2nsf-security-policy {

    key "name";

    description
        "Container for security policy
        including a set of security rules according to certain logic,
        i.e., their similarity or mutual relations, etc. The network
        security policy can be applied to both the unidirectional
        and bidirectional traffic across the NSF.
        The I2NSF security policies use the Event-Condition-Action

```

(ECA) policy model ";

reference

"RFC 8329: Framework for Interface to Network Security  
Functions - I2NSF Flow Security Policy Structure  
draft-ietf-i2nsf-capability-data-model-26:  
I2NSF Capability YANG Data Model - Design Principles and  
ECA Policy Model Overview";

leaf name {  
 type string;  
 description  
 "The name of the security policy.  
 This must be unique.";  
}

leaf priority-usage {  
 type identityref {  
 base priority-usage;  
 }  
 default priority-by-order;  
 description  
 "Priority usage type for security policy rule:  
 priority by order and priority by number";  
}

leaf resolution-strategy {  
 type identityref {  
 base resolution-strategy;  
 }  
 default fmr;  
 description  
 "The resolution strategies that can be used to  
 specify how to resolve conflicts that occur between  
 actions of the same or different policy rules that  
 are matched and contained in this particular NSF";

reference

"draft-ietf-i2nsf-capability-data-model-26:  
I2NSF Capability YANG Data Model - Resolution strategy";

leaf default-action {  
 type identityref {  
 base default-action;  
 }  
 default mirror;  
 description  
 "This default action can be used to specify a predefined

```

        action when no other alternative action was matched
        by the currently executing I2NSF Policy Rule. An analogy
        is the use of a default statement in a C switch statement.";
reference
    "draft-ietf-i2nsf-capability-data-model-26:
    I2NSF Capability YANG Data Model - Default Action";
}

list rules {
    key "name";
    description
        "This is a rule for network security functions.";

    leaf name {
        type string;
        description
            "The name of the rule.";
    }

    leaf description {
        type string;
        description
            "This description gives more information about
            rules.";
    }

    leaf priority {
        type uint8 {
            range "1..255";
        }
        description
            "The priority for the rule comes with a mandatory
            numeric value which can range from 1 up to 255.
            Note that a higher number means a higher priority";
    }

    leaf enable {
        type boolean;
        description
            "If true, the rule is enabled and enforced.
            If false, the rule is configured but disabled and not
            enforced.";
    }

    leaf session-aging-time {
        type uint16;
        units "second";
        description
            "This is session aging time.";
    }

```

```

}

container long-connection {
  description
    "A container for long connection. A long connection is a
    connection that is maintained after the socket connection
    is established, regardless of whether it is used for data
    traffic or not.";

  leaf enable {
    type boolean;
    description
      "If true, the rule is enabled and enforced.
      If false, the rule is configured but disabled
      and not enforced.";
  }

  leaf duration {
    type uint16;
    units "second";
    description
      "This is the duration of the long-connection.";
  }
}

container event {
  description
    "An event is defined as any important
    occurrence in time of a change in the system being
    managed, and/or in the environment of the system being
    managed. When used in the context of policy rules for
    a flow-based NSF, it is used to determine whether the
    Condition clause of the Policy Rule can be evaluated
    or not. Examples of an I2NSF event include time and
    user actions (e.g., logon, logoff, and actions that
    violate any ACL.).";

  reference
    "RFC 8329: Framework for Interface to Network Security
    Functions - I2NSF Flow Security Policy Structure
    draft-ietf-i2nsf-capability-data-model-26:
    I2NSF Capability YANG Data Model - Design Principles and
    ECA Policy Model Overview
    draft-ietf-i2nsf-nsf-monitoring-data-model-14: I2NSF
    NSF Monitoring Interface YANG Data Model - Alarms,
    Events, Logs, and Counters";

  leaf description {
    type string;
  }
}

```

```

    description
        "Description for an event clause";
}

container time {
    description
        "Time to determine when the policy should be applied";
    leaf start-date-time {
        type yang:date-and-time;
        description
            "This is the start date and time for a security policy
            rule.";
    }

    leaf end-date-time {
        type yang:date-and-time;
        description
            "This is the end date and time for a policy rule. The
            policy rule will stop working after the specified
            end-date-time.";
    }
}

container period {
    when
        "../frequency!='only-once'";
    description
        "This represents the repetition time. In the case
        where the frequency is weekly, the days can be set.";
    leaf start-time {
        type time;
        description
            "This is a period's start time for an event.";
    }
    leaf end-time {
        type time;
        description
            "This is a period's end time for an event.";
    }
}

leaf-list day {
    when
        "../..frequency='weekly'";
    type day;
    min-elements 1;
    description
        "This represents the repeated day of every week
        (e.g., Monday and Tuesday). More than one day can
        be specified.";
}

leaf-list date {

```

```

when
    "...../frequency='monthly'";
type int8 {
    range "1..31";
}
min-elements 1;
description
    "This represents the repeated date of every month.
    More than one date can be specified.";
}
leaf-list month {
    when
        "...../frequency='yearly'";
    type string{
        pattern '\d{2}-\d{2}';
    }
    min-elements 1;
    description
        "This represents the repeated date and month of every
        year. More than one can be specified. A pattern
        used here is Month and Date (MM-DD).";
}
}

leaf frequency {
    type enumeration {
        enum only-once {
            description
                "This represents that the rule is immediately
                enforced only once and not repeated. The policy
                will continuously be active from the start-time
                to the end-time.";
        }
        enum daily {
            description
                "This represents that the rule is enforced on a
                daily basis. The policy will be repeated
                daily until the end-date.";
        }
        enum weekly {
            description
                "This represents that the rule is enforced on a
                weekly basis. The policy will be repeated weekly
                until the end-date. The repeated days can be
                specified.";
        }
        enum monthly {
            description
                "This represents that the rule is enforced on a

```

```

        monthly basis. The policy will be repeated monthly
        until the end-date.";
    }
    enum yearly {
        description
            "This represents that the rule is enforced on
            a yearly basis. The policy will be repeated
            yearly until the end-date.";
    }
}
default only-once;
description
    "This represents how frequently the rule
    should be enforced.";
}
}

container event-clauses {
    description
        "Event Clause - either a system event or system alarm";
    reference
        "RFC 8329: Framework for Interface to Network Security
        Functions - I2NSF Flow Security Policy Structure
        draft-ietf-i2nsf-capability-data-model-26:
        I2NSF Capability YANG Data Model - Design Principles and
        ECA Policy Model Overview
        draft-ietf-i2nsf-nsf-monitoring-data-model-14: I2NSF
        NSF Monitoring Interface YANG Data Model - Alarms,
        Events, Logs, and Counters";

    leaf-list system-event {
        type identityref {
            base system-event;
        }
        description
            "The security policy rule according to
            system events.";
    }

    leaf-list system-alarm {
        type identityref {
            base system-alarm;
        }
        description
            "The security policy rule according to
            system alarms.";
    }
}
}
}

```



```

container condition {
  description
    "A condition is defined as a set
    of attributes, features, and/or values that are to be
    compared with a set of known attributes, features,
    and/or values in order to determine whether the
    set of Actions in that (imperative) I2NSF Policy Rule
    can be executed or not. Examples of I2NSF Conditions
    include matching attributes of a packet or flow, and
    comparing the internal state of an NSF to a desired
    state.";
  reference
    "RFC 8329: Framework for Interface to Network Security
    Functions - I2NSF Flow Security Policy Structure
    draft-ietf-i2nsf-capability-data-model-26:
    I2NSF Capability YANG Data Model - Design Principles and
    ECA Policy Model Overview";

  leaf description {
    type string;
    description
      "Description for a condition clause.";
  }
}

container ethernet {
  description
    "The purpose of this container is to represent layer 2
    packet header information to determine the set of policy
    actions in this ECA policy rule should be executed or
    not.";
  reference
    "IEEE 802.3: IEEE Standard for Ethernet";

  leaf description {
    type string;
    description
      "The ethernet condition description";
  }

  uses packet-fields:acl-eth-header-fields;
}

container ipv4 {
  description
    "The purpose of this container is to represent IPv4
    packet header information to determine if the set
    of policy actions in this ECA policy rule should be
    executed or not.";
}

```

```

reference
  "RFC 791: Internet Protocol";

leaf description {
  type string;
  description
    "This is description for IPv4 condition.";
}

uses packet-fields:acl-ip-header-fields;
uses packet-fields:acl-ipv4-header-fields {
  augment destination-network {
    case destination-ipv4-range {
      list destination-ipv4-range {
        key "start end";
        uses ipv4-range;
        description
          "The list of IPv4 addresses specified with a
          start IPv4 address and an end IPv4 address.
          If only one value is needed, then set both
          start and end to the same value.
          Note that the 'end' IPv4 address MUST be equal
          to or greater than the 'start' IPv4 address.";
      }
    }
    description
      "IPv4 destination network denoted as IPv4 addresses";
  }
  augment source-network {
    case source-ipv4-range {
      list source-ipv4-range {
        key "start end";
        uses ipv4-range;
        description
          "The list of IPv4 addresses specified with a
          start IPv4 address and an end IPv4 address.
          If only one value is needed, then set both
          start and end to the same value.
          Note that the 'end' IPv4 address MUST be equal
          or greater than the 'start' IPv4 address.";
      }
    }
    description
      "IPv4 source network denoted as IPv4 addresses";
  }
}
}

container ipv6 {

```

```

description
    "The purpose of this container is to represent IPv6
    packet header information to determine if the set
    of policy actions in this ECA policy rule should be
    executed or not.";

reference
    "RFC 8200: Internet Protocol, Version 6 (IPv6)
    Specification";

leaf description {
    type string;
    description
        "This is description for IPv6 condition.";
}

uses packet-fields:acl-ip-header-fields;
uses packet-fields:acl-ipv6-header-fields {
    augment destination-network {
        case destination-ipv6-range {
            list destination-ipv6-range {
                key "start end";
                uses ipv6-range;
                description
                    "The list of IPv6 addresses specified with a
                    start IPv6 address and an end IPv6 address.
                    If only one value is needed, then set both
                    start and end to the same value.
                    Note that the 'end' IPv6 address MUST be equal
                    to or greater than the 'start' IPv6 address.";
            }
        }
        description
            "IPv6 destination network denoted as IPv6 addresses";
    }
    augment source-network {
        case source-ipv6-range {
            list source-ipv6-range {
                key "start end";
                uses ipv6-range;
                description
                    "The list of IPv6 addresses specified with a
                    start IPv6 address and an end IPv6 address.
                    If only one value is needed, then set both
                    start and end to the same value.
                    Note that the 'end' IPv6 address MUST be equal
                    to or greater than the 'start' IPv6 address.";
            }
        }
    }
}

```

```

        description
            "IPv6 source network denoted as IPv6 addresses";
    }
}
}

container tcp {
    description
        "The purpose of this container is to represent
        TCP packet header information to determine
        if the set of policy actions in this ECA policy
        rule should be executed or not.";
    reference
        "draft-ietf-tcpm-rfc793bis-25: Transmission Control
        Protocol (TCP) Specification";

    leaf description {
        type string;
        description
            "This is description for tcp condition.";
    }

    container source-port-number {
        choice source-port {
            case range-or-operator {
                uses packet-fields:port-range-or-operator;
                description
                    "Source port definition from range or operator.
                    Can be used when a single port range to be
                    specified.";
            }
            case port-list {
                list port-numbers {
                    key "start end";
                    uses port-range;
                    description
                        "List of source port numbers.";
                }
                description
                    "Source port definition from list of port numbers.
                    In the case of multiple port ranges needed to be
                    specified.";
            }
        }
        description
            "The choice of source port definition using
            range/operator or a choice to use list of port
            numbers.";
    }
}

```

```

description
    "The security policy rule according to
    tcp source port number.";
reference
    "draft-ietf-tcpm-rfc793bis-25: Transmission Control
    Protocol (TCP) Specification - Port Number";
}

container destination-port-number {
    choice destination-port {
        case range-or-operator {
            uses packet-fields:port-range-or-operator;
            description
                "Destination port definition from range or
                operator.
                Can be used when a single port range to be
                specified.";
        }
        case port-list {
            list port-numbers {
                key "start end";
                uses port-range;
                description
                    "List of destination port numbers.";
            }
            description
                "Destination port definition from list of port
                numbers.
                In the case of multiple port ranges needed to be
                specified.";
        }
        description
            "The choice of destination port definition using
            range/operator or a choice to use list of port
            numbers.";
    }
    description
        "The security policy rule according to
        tcp destination port number.";
    reference
        "draft-ietf-tcpm-rfc793bis-25: Transmission Control
        Protocol (TCP) Specification - Port Number";
}

uses packet-fields:acl-tcp-header-fields;

}

container udp {

```

```

description
    "The purpose of this container is to represent
    UDP packet header information to determine
    if the set of policy actions in this ECA policy
    rule should be executed or not.";
reference
    "RFC 768: User Datagram Protocol";

leaf description {
    type string;
    description
        "This is description for udp condition.";
}

container source-port-number {
    choice source-port {
        case range-or-operator {
            uses packet-fields:port-range-or-operator;
            description
                "Source port definition from range or operator.
                Can be used when a single port range to be
                specified.";
        }
        case port-list {
            list port-numbers {
                key "start end";
                uses port-range;
                description
                    "List of source port numbers.";
            }
            description
                "Source port definition from list of port numbers.
                In the case of multiple port ranges needed to be
                specified.";
        }
    }
    description
        "The choice of source port definition using
        range/operator or a choice to use list of port
        numbers.";
}
description
    "The security policy rule according to
    udp source port number.";
reference
    "RFC 768: User Datagram Protocol - Port Number";
}

container destination-port-number {
    choice destination-port {

```

```

    case range-or-operator {
        uses packet-fields:port-range-or-operator;
        description
            "Destination port definition from range or
            operator.
            Can be used when a single port range to be
            specified.";
    }
    case port-list {
        list port-numbers {
            key "start end";
            uses port-range;
            description
                "List of destination port numbers.";
        }
        description
            "Destination port definition from list of port
            numbers.
            In the case of multiple port ranges needed to be
            specified.";
    }
    description
        "The choice of destination port definition using
        range/operator or a choice to use list of port
        numbers.";
}
description
    "The security policy rule according to
    udp destination port number.";
reference
    "RFC 768: User Datagram Protocol - Port Number";
}

uses packet-fields:acl-udp-header-fields;
}

container sctp {
    description
        "The purpose of this container is to represent
        SCTP packet header information to determine
        if the set of policy actions in this ECA policy
        rule should be executed or not.";

    leaf description {
        type string;
        description
            "This is description for sctp condition.";
    }
}

```

```

container source-port-number {
  choice source-port {
    case range-or-operator {
      uses packet-fields:port-range-or-operator;
      description
        "Source port definition from range or operator.
        Can be used when a single port range to be
        specified.";
    }
    case port-list {
      list port-numbers {
        key "start end";
        uses port-range;
        description
          "List of source port numbers.";
      }
      description
        "Source port definition from list of port numbers.
        In the case of multiple port ranges needed to be
        specified.";
    }
  }
  description
    "The choice of source port definition using
    range/operator or a choice to use list of port
    numbers.";
}
description
  "The security policy rule according to
  sctp source port number.";
reference
  "draft-ietf-tsvwg-rfc4960-bis-18: Stream Control
  Transmission Protocol - Port number";
}

```

```

container destination-port-number {
  choice destination-port {
    case range-or-operator {
      uses packet-fields:port-range-or-operator;
      description
        "Destination port definition from range or
        operator.
        Can be used when a single port range to be
        specified.";
    }
  }
  case port-list {
    list port-numbers {
      key "start end";
      uses port-range;
      description

```



```

        "List of destination port numbers.";
    }
    description
        "Destination port definition from list of port
        numbers.
        In the case of multiple port ranges needed to be
        specified.";
    }
    description
        "The choice of destination port definition using
        range/operator or a choice to use list of port
        numbers.";
    }
    description
        "The security policy rule according to
        sctp destination port number.";
    reference
        "draft-ietf-tsvwg-rfc4960-bis-18: Stream Control
        Transmission Protocol - Port Number";
    }

leaf-list chunk-type {
    type uint8;
    description
        "The security policy rule according to
        sctp chunk type ID Value.";
    reference
        "draft-ietf-tsvwg-rfc4960-bis-18: Stream Control
        Transmission Protocol - Chunk Type";
    }

leaf chunk-length {
    type uint16 {
        range "4..max";
    }
    description
        "The security policy rule according to the length of
        the chunk in sctp. This value represents the size of
        the chunk in bytes, including the Chunk Type,
        Chunk Flags, Chunk Length, and Chunk Value fields.";
    reference
        "draft-ietf-tsvwg-rfc4960-bis-18: Stream Control
        Transmission Protocol - Chunk Length";
    }
}

container dccp {
    description
        "The purpose of this container is to represent

```

```

    DCCP packet header information to determine
    if the set of policy actions in this ECA policy
    rule should be executed or not.";
leaf description {
    type string;
    description
        "This is description for dccp condition.";
}

container source-port-number {
    choice source-port {
        case range-or-operator {
            uses packet-fields:port-range-or-operator;
            description
                "Source port definition from range or operator.
                Can be used when a single port range to be
                specified.";
        }
        case port-list {
            list port-numbers {
                key "start end";
                uses port-range;
                description
                    "List of source port numbers.";
            }
            description
                "Source port definition from list of port numbers.
                In the case of multiple port ranges needed to be
                specified.";
        }
    }
    description
        "The choice of source port definition using
        range/operator or a choice to use list of port
        numbers.";
}
description
    "The security policy rule according to
    dccp source port number.";
reference
    "RFC 4340: Datagram Congestion Control Protocol (DCCP)
    - Port number";
}

container destination-port-number {
    choice destination-port {
        case range-or-operator {
            uses packet-fields:port-range-or-operator;
            description
                "Destination port definition from range or

```

```

        operator.
        Can be used when a single port range to be
        specified.";
    }
    case port-list {
        list port-numbers {
            key "start end";
            uses port-range;
            description
                "List of destination port numbers.";
        }
        description
            "Destination port definition from list of port
            numbers.
            In the case of multiple port ranges needed to be
            specified.";
    }
    description
        "The choice of destination port definition using
        range/operator or a choice to use list of port
        numbers.";
}
description
    "The security policy rule according to
    dccp destination port number.";
reference
    "RFC 4340: Datagram Congestion Control Protocol (DCCP)
    - Port number";
}

leaf-list service-code {
    type uint32;
    description
        "The security policy rule according to
        dccp service code.";
    reference
        "RFC 4340: Datagram Congestion Control Protocol (DCCP)
        - Service Codes
        RFC 5595: The Datagram Congestion Control Protocol
        (DCCP) Service Codes
        RFC 6335: Internet Assigned Numbers Authority (IANA)
        Procedures for the Management of the Service
        Name and Transport Protocol Port Number
        Registry - Service Code";
}

leaf-list type {
    type uint8 {
        range "0..15";
    }
}

```

```

    }
    description
        "The security policy rule according to the 4 bits of
        dccp type header field for dccp packet types such as
        DCCP-Request, DCCP-Response, DCCP-Data, DCCP-Ack, and
        DCCP-DataAck.";
    reference
        "RFC 4340: Datagram Congestion Control Protocol (DCCP)
        - Packet Types";
}

leaf data-offset {
    type uint8;
    description
        "The security policy rule according to the offset from
        the start of the packet's DCCP header to the start
        of its application data area, in 32-bit word.";
    reference
        "RFC 4340: Datagram Congestion Control Protocol (DCCP)
        - Data Offset";
}
}

list icmp {
    key "version";
    description
        "The purpose of this container is to represent
        ICMP packet header information to determine
        if the set of policy actions in this ECA policy
        rule should be executed or not.";
    reference
        "RFC 792: Internet Control Message Protocol
        RFC 8335: PROBE: A Utility for Probing Interfaces";

    leaf description {
        type string;
        description
            "This is description for icmp condition.";
    }

    leaf version {
        type enumeration {
            enum icmpv4 {
                value "1";
                description
                    "The ICMPv4 Protocol as defined in RFC 792";
            }
            enum icmpv6 {
                value "2";
            }
        }
    }
}

```

```

        description
            "The ICMPv6 Protocol as defined in RFC 4443";
    }
}
description
    "The ICMP version to be matched. This value
    affected the type and code values.";
reference
    "RFC 792: Internet Control Message Protocol
    RFC 4443: Internet Control Message Protocol (ICMPv6)
    for the Internet Protocol Version 6 (IPv6)
    Specification";
}

uses packet-fields:acl-icmp-header-fields;
}

container url-category {
    description
        "Condition for url category";
    leaf description {
        type string;
        description
            "This is description for the condition of a URL's
            category such as SNS sites, game sites, ecommerce
            sites, company sites, and university sites.";
    }

    leaf-list pre-defined {
        type string;
        description
            "This is pre-defined-category. To specify the name of
            URL database.";
    }

    leaf-list user-defined {
        type string;
        description
            "This user-defined-category. To allow a users manual
            addition of URLs for URL filtering.";
    }
}

container voice {
    description
        "For the VoIP/VoCN security system, a VoIP/
        VoCN security system can monitor each
        VoIP/VoCN flow and manage VoIP/VoCN
        security rules controlled by a centralized
        server for VoIP/VoCN security service

```

```

        (called VoIP IPS). The VoIP/VoCN security
        system controls each switch for the
        VoIP/VoCN call flow management by
        manipulating the rules that can be added,
        deleted, or modified dynamically.";
reference
    "RFC 3261: SIP: Session Initiation Protocol";

leaf description {
    type string;
    description
        "This is description for voice condition.";
}

leaf-list source-voice-id {
    type string;
    description
        "The security policy rule according to
        a source voice ID for VoIP and VoCN.";
}

leaf-list destination-voice-id {
    type string;
    description
        "The security policy rule according to
        a destination voice ID for VoIP and VoCN.";
}

leaf-list user-agent {
    type string;
    description
        "The security policy rule according to
        a user agent for VoIP and VoCN.";
}
}

container ddos {
    description
        "Condition for DDoS attack.";

    leaf description {
        type string;
        description
            "This is description for ddos condition.";
    }

    leaf alert-packet-rate {
        type uint32;
        units "pps";
    }
}

```

```

        description
            "The alert rate of flood detection for
            packets per second (PPS) of an IP address.
            If the PPS of an IP address exceeds
            the alert rate threshold, an alert
            will be generated.";
    }

    leaf alert-flow-rate {
        type uint32;
        description
            "The alert rate of flood detection for
            flows per second of an IP address.
            If the flows per second of an IP address
            exceeds the alert rate threshold, an alert
            will be generated.";
    }

    leaf alert-byte-rate {
        type uint32;
        units "Bps";
        description
            "The alert rate of flood detection for
            bytes per second (Bps) of an IP address.
            If the bytes per second of an IP address
            exceeds the alert rate threshold, an alert
            will be generated.";
    }
}

container anti-virus {
    description
        "Condition for antivirus";

    leaf-list profile {
        type string;
        description
            "The security profile for antivirus. This is used to
            update the security profile for improving the
            security. The security profile is used to scan
            the viruses.";
    }

    leaf-list exception-files {
        type string;
        description
            "The type or name of the files to be excluded by the
            antivirus. This can be used to keep the known
            harmless files.";
    }
}

```

```

    }
}

container payload {
    description
        "Condition for packet payload";
    leaf description {
        type string;
        description
            "This is description for payload condition.";
    }
    leaf-list content {
        type string;
        description
            "This is a condition for packet payload content.";
    }
}

container context {
    description
        "Condition for context";
    leaf description {
        type string;
        description
            "This is description for context condition.";
    }
}

container application {
    description
        "Condition for application";
    leaf description {
        type string;
        description
            "This is description for application condition.";
    }
    leaf-list protocol {
        type identityref {
            base application-protocol;
        }
        description
            "The condition based on the application layer
            protocol";
    }
}

container device-type {
    description
        "Condition for type of the destination device";
    leaf description {

```



```

    type string;
    description
        "This is description for destination device type
        condition. Vendors can write instructions for the
        condition that vendor made";
}

leaf-list device {
    type identityref {
        base device-type;
    }
    description
        "The device attribute that can identify a device,
        including the device type (i.e., router, switch,
        pc, ios, or android) and the device's owner as
        well.";
}
}

container users {
    description
        "Condition for users";
    leaf description {
        type string;
        description
            "This is the description for users' condition.";
    }
    list user {
        key "id";
        description
            "The user with which the traffic flow is associated
            can be identified by either a user ID or username.
            The user-to-IP address mapping is assumed to be
            provided by the unified user management system via
            network.";
        leaf id {
            type uint32;
            description
                "The ID of the user.";
        }
        leaf name {
            type string;
            description
                "The name of the user.";
        }
    }
}
list group {
    key "id";
    description

```

```

        "The user group with which the traffic flow is
        associated can be identified by either a group ID
        or group name. The group-to-IP address and
        user-to-group mappings are assumed to be provided by
        the unified user management system via network.";
    leaf id {
        type uint32;
        description
            "The ID of the group.";
    }
    leaf name {
        type string;
        description
            "The name of the group.";
    }
}

leaf security-group {
    type string;
    description
        "security-group.";
}
}

container geographic-location {
    description
        "The location which network traffic flow is associated
        with. The region can be the geographic location such
        as country, province, and city, as well as the logical
        network location such as IP address, network section,
        and network domain.";
    reference
        "draft-ietf-netmod-geo-location-11: A YANG Grouping for
        Geographic Locations";

    leaf description {
        type string;
        description
            "This is the description for the geographic location
            condition. It is used to describe the conditions and
            instructions that should be implemented.";
    }

    leaf-list source {
        type string;
        description
            "The source is a geographic location mapped into an
            IP address. It matches the mapped IP address to the
            source IP address of the traffic flow.";
    }
}

```

```

        reference
        "ISO 3166: Codes for the representation of
        names of countries and their subdivisions
        draft-ietf-netmod-geo-location-11: A YANG Grouping
        for Geographic Locations";
    }

    leaf-list destination {
        type string;
        description
            "The destination is a geographic location mapped into
            an IP address. It matches the mapped IP address to
            the destination IP address of the traffic flow.";
        reference
            "ISO 3166: Codes for the representation of
            names of countries and their subdivisions
            draft-ietf-netmod-geo-location-11: A YANG Grouping
            for Geographic Locations";
    }
}

}

}

}

container action {
    description
        "An action is used to control and monitor aspects of
        flow-based NSFs when the event and condition clauses
        are satisfied. NSFs provide security functions by
        executing various Actions. Examples of I2NSF Actions
        include providing intrusion detection and/or protection,
        web and flow filtering, and deep packet inspection
        for packets and flows.";
    reference
        "RFC 8329: Framework for Interface to Network Security
        Functions - I2NSF Flow Security Policy Structure
        draft-ietf-i2nsf-capability-data-model-26:
        I2NSF Capability YANG Data Model - Design Principles and
        ECA Policy Model Overview";

    leaf description {
        type string;
        description
            "Description for an action clause.";
    }

    container packet-action {
        description
            "Action for packets";
        reference

```

"RFC 8329: Framework for Interface to Network Security  
Functions - I2NSF Flow Security Policy Structure  
draft-ietf-i2nsf-capability-data-model-26:  
I2NSF Capability YANG Data Model - Design Principles and  
ECA Policy Model Overview";

```
leaf ingress-action {  
  type identityref {  
    base ingress-action;  
  }  
  description  
    "Ingress Action: pass, drop, reject, rate-limit, and  
    mirror.";  
}
```

```
leaf egress-action {  
  type identityref {  
    base egress-action;  
  }  
  description  
    "Egress action: pass, drop, reject, rate-limit, mirror,  
    invoke-signaling, tunnel-encapsulation, forwarding,  
    and redirection.";  
}
```

```
leaf log-action {  
  type identityref {  
    base log-action;  
  }  
  description  
    "Log action: rule log and session log";  
}
```

```
}
```

```
container flow-action {  
  description  
    "Action for flows";  
  reference  
    "RFC 8329: Framework for Interface to Network Security  
    Functions - I2NSF Flow Security Policy Structure  
    draft-ietf-i2nsf-capability-data-model-26:  
    I2NSF Capability YANG Data Model - Design Principles and  
    ECA Policy Model Overview";
```

```
leaf ingress-action {  
  type identityref {  
    base ingress-action;  
  }  
}
```

```

    description
        "Action: pass, drop, reject, rate-limit, and mirror.";
}

leaf egress-action {
    type identityref {
        base egress-action;
    }
    description
        "Egress action: pass, drop, reject, rate-limit, mirror,
        invoke-signaling, tunnel-encapsulation, forwarding,
        and redirection.";
}

leaf log-action {
    type identityref {
        base log-action;
    }
    description
        "Log action: rule log and session log";
}
}

container advanced-action {
    description
        "If the packet needs to be additionally inspected,
        the packet is passed to advanced network
        security functions according to the profile.
        The profile means the types of NSFs where the packet
        will be forwarded in order to additionally
        inspect the packet.
        The advanced action activates Service Function
        Chaining (SFC) for further inspection of a packet.";
    reference
        "draft-ietf-i2nsf-capability-data-model-26:
        I2NSF Capability YANG Data Model - YANG Tree
        Diagram";

    leaf-list content-security-control {
        type identityref {
            base content-security-control;
        }
        description
            "Content-security-control is the NSFs that
            inspect the payload of the packet.
            The profile for the types of NSFs for mitigation is
            divided into content security control and
            attack-mitigation-control.
            Content security control: ips, url filtering,

```

```

        antivirus, and voip-vocn-filter. This can be
        extended according to the provided NSFs.";
    reference
        "draft-ietf-i2nsf-capability-data-model-26:
        I2NSF Capability YANG Data Model - YANG Tree Diagram";
}

leaf-list attack-mitigation-control {
    type identityref {
        base attack-mitigation-control;
    }
    description
        "Attack-mitigation-control is the NSFs that weaken
        the attacks related to a denial-of-service (DoS)
        and reconnaissance.
        The profile for the types of NSFs for mitigation is
        divided into content security control and
        attack-mitigation-control.
        Attack mitigation control: Anti-DDoS or DDoS
        mitigator. This can be extended according to the
        provided NSFs such as mitigators for ip sweep,
        port scanning, ping of death, teardrop, oversized
        icmp, and tracert.";
    reference
        "draft-ietf-i2nsf-capability-data-model-26:
        I2NSF Capability YANG Data Model - YANG Tree Diagram";
}
}
}
}
container rule-group {
    description
        "This is rule group";

    list groups {
        key "group-name";
        description
            "This is a group for rules";

        leaf group-name {
            type string;
            description
                "This is the name of the group for rules";
        }

        leaf-list rule-name {
            type leafref {
                path
                    "../.../rules/name";
            }
        }
    }
}

```



```

<i2nsf-security-policy
xmlns="urn:ietf:params:xml:ns:yang:ietf-i2nsf-policy-rule-for-nsf">
  <name>sns_access</name>
  <rules>
    <name>block_sns_access_during_operation_time</name>
    <event>
      <time>
        <start-date-time>2021-03-11T09:00:00.00Z</start-date-time>
        <end-date-time>2021-12-31T18:00:00.00Z</end-date-time>
        <period>
          <start-time>09:00:00Z</start-time>
          <end-time>18:00:00Z</end-time>
          <day>monday</day>
          <day>tuesday</day>
          <day>wednesday</day>
          <day>thursday</day>
          <day>friday</day>
        </period>
        <frequency>weekly</frequency>
      </time>
    </event>
    <condition>
      <ipv4>
        <source-ipv4-network>192.0.2.0/24</source-ipv4-network>
      </ipv4>
    </condition>
    <action>
      <advanced-action>
        <content-security-control>
          url-filtering
        </content-security-control>
      </advanced-action>
    </action>
  </rules>
</i2nsf-security-policy>

```

Figure 6: Configuration XML for Time-based Firewall to Block SNS Access during Business Hours in IPv4 Networks



```

<i2nsf-security-policy
xmlns="urn:ietf:params:xml:ns:yang:ietf-i2nsf-policy-rule-for-nsf">
  <name>sns_access</name>
  <rules>
    <name>block_sns_access_during_operation_time</name>
    <event>
      <time>
        <start-date-time>2021-03-11T09:00:00.00Z</start-date-time>
        <end-date-time>2021-12-31T18:00:00.00Z</end-date-time>
        <period>
          <start-time>09:00:00Z</start-time>
          <end-time>18:00:00Z</end-time>
          <day>monday</day>
          <day>tuesday</day>
          <day>wednesday</day>
          <day>thursday</day>
          <day>friday</day>
        </period>
        <frequency>weekly</frequency>
      </time>
    </event>
    <condition>
      <ipv6>
        <source-ipv6-network>2001:db8:0:1::0/120</source-ipv6-network>
      </ipv6>
    </condition>
    <action>
      <advanced-action>
        <content-security-control>
          url-filtering
        </content-security-control>
      </advanced-action>
    </action>
  </rules>
</i2nsf-security-policy>

```

Figure 7: Configuration XML for Time-based Firewall to Block SNS Access during Business Hours in IPv6 Networks

```

<i2nsf-security-policy
xmlns="urn:ietf:params:xml:ns:yang:ietf-i2nsf-policy-rule-for-nsf">
  <name>sns_access</name>
  <rules>
    <name>block_sns_access_during_operation_time</name>
    <condition>
      <url-category>
        <user-defined>SNS_1</user-defined>
        <user-defined>SNS_2</user-defined>
      </url-category>
    </condition>
    <action>
      <packet-action>
        <egress-action>drop</egress-action>
      </packet-action>
    </action>
  </rules>
</i2nsf-security-policy>

```

Figure 8: Configuration XML for Web Filter to Block SNS Access during Business Hours

[Figure 6](#) (or [Figure 7](#)) and [Figure 8](#) show the configuration XML documents for time-based firewall and web filter to block SNS access during business hours in IPv4 networks (or IPv6 networks). For the security requirement, two NSFs (i.e., a time-based firewall and a web filter) were used because one NSF cannot meet the security requirement. The instances of XML documents for the time-based firewall and the web filter are as follows: Note that a detailed data model for the configuration of the advanced network security function (i.e., web filter) can be defined as an extension in future.

Time-based Firewall is as follows:

1. The name of the security policy is sns\_access.
2. The name of the rule is block\_sns\_access\_during\_operation\_time.
3. The rule is started from 2021-03-11 at 9 a.m. to 2021-12-31 at 6 p.m.
4. The rule is operated weekly every weekday (i.e., Monday, Tuesday, Wednesday, Thursday, and Friday) during the business hours (i.e., from 9 a.m. to 6 p.m.) .
5. The rule inspects a source IPv4 address (i.e., 192.0.2.0/24). For the case of IPv6 networks, the rule inspects a source IPv6 address (i.e., from 2001:db8:0:1::0/120).

6. If the outgoing packets match the rules above, the time-based firewall sends the packets to url filtering for additional inspection because the time-based firewall can not inspect contents of the packets for the SNS URL.

Web Filter is as follows:

1. The name of the security policy is sns\_access.
2. The name of the rule is block\_SNS\_1\_and\_SNS\_2.
3. The rule inspects URL address to block the access packets to the SNS\_1 or the SNS\_2.
4. If the outgoing packets match the rules above, the packets are blocked.

## **5.2. Example Security Requirement 2: Block Malicious VoIP/VoCN Packets Coming to a Company**

This section shows a configuration example for blocking malicious VoIP/VoCN packets coming to a company.

```
<i2nsf-security-policy
xmlns="urn:ietf:params:xml:ns:yang:ietf-i2nsf-policy-rule-for-nsf">
  <name>voip_vocn_inspection</name>
  <rules>
    <name>block_malicious_voice_id</name>
    <condition>
      <ipv4>
        <destination-ipv4-network>192.0.2.0/24</destination-ipv4-network>
      </ipv4>
      <tcp>
        <destination-port-number>
          <lower-port>5060</lower-port>
          <upper-port>5061</upper-port>
        </destination-port-number>
      </tcp>
    </condition>
    <action>
      <advanced-action>
        <content-security-control>
          voip-vocn-filter
        </content-security-control>
      </advanced-action>
    </action>
  </rules>
</i2nsf-security-policy>
```

Figure 9: Configuration XML for General Firewall to Block Malicious VoIP/VoCN Packets Coming to a Company

```
<i2nsf-security-policy
xmlns="urn:ietf:params:xml:ns:yang:ietf-i2nsf-policy-rule-for-nsf">
  <name>voip_vocn_inspection</name>
  <rules>
    <name>block_malicious_voice_id</name>
    <condition>
      <voice>
        <source-voice-id>
          user1@voip.malicious.example.com
        </source-voice-id>
        <source-voice-id>
          user2@voip.malicious.example.com
        </source-voice-id>
      </voice>
    </condition>
    <action>
      <flow-action>
        <ingress-action>drop</ingress-action>
      </flow-action>
    </action>
  </rules>
</i2nsf-security-policy>
```

Figure 10: Configuration XML for VoIP/VoCN Filter to Block Malicious VoIP/VoCN Packets Coming to a Company

[Figure 9](#) and [Figure 10](#) show the configuration XML documents for general firewall and VoIP/VoCN filter to block malicious VoIP/VoCN packets coming to a company. For the security requirement, two NSFs (i.e., a general firewall and a VoIP/VoCN filter) were used because one NSF can not meet the security requirement. The instances of XML documents for the general firewall and the VoIP/VoCN filter are as follows: Note that a detailed data model for the configuration of the advanced network security function (i.e., VoIP/VoCN filter) can be described as an extension in future.

General Firewall is as follows:

1. The name of the security policy is voip\_vocn\_inspection.
2. The name of the rule is block\_malicious\_voice\_id.
3. The rule inspects a destination IPv4 address (i.e., from 192.0.2.0/24).
4. The rule inspects a port number (i.e., 5060 and 5061) to inspect VoIP/VoCN packet.

5. If the incoming packets match the rules above, the general firewall sends the packets to VoIP/VoCN filter for additional inspection because the general firewall can not inspect contents of the VoIP/VoCN packets.

VoIP/VoCN Filter is as follows:

1. The name of the security policy is malicious\_voice\_id.
2. The name of the rule is block\_malicious\_voice\_id.
3. The rule inspects the voice ID of the VoIP/VoCN packets to block the malicious VoIP/VoCN packets (i.e., user1@voip.malicious.example.com and user2@voip.malicious.example.com).
4. If the incoming packets match the rules above, the packets are blocked.

### **5.3. Example Security Requirement 3: Mitigate HTTP and HTTPS Flood Attacks on a Company Web Server**

This section shows a configuration example for mitigating http and https flood attacks on a company web server.

```

<i2nsf-security-policy
xmlns="urn:ietf:params:xml:ns:yang:ietf-i2nsf-policy-rule-for-nsf">
  <name>flood_attack_mitigation</name>
  <rules>
    <name>mitigate_http_and_https_flood_attack</name>
    <condition>
      <ipv4>
        <destination-ipv4-network>192.0.2.0/24</destination-ipv4-network>
      </ipv4>
      <tcp>
        <destination-port-number>
          <port-numbers>
            <start>80</start>
            <end>80</end>
          </port-numbers>
          <port-numbers>
            <start>443</start>
            <end>443</end>
          </port-numbers>
        </destination-port-number>
      </tcp>
    </condition>
    <action>
      <advanced-action>
        <attack-mitigation-control>
          anti-ddos
        </attack-mitigation-control>
      </advanced-action>
    </action>
  </rules>
</i2nsf-security-policy>

```

Figure 11: Configuration XML for General Firewall to Mitigate HTTP and HTTPS Flood Attacks on a Company Web Server

```

<i2nsf-security-policy
xmlns="urn:ietf:params:xml:ns:yang:ietf-i2nsf-policy-rule-for-nsf">
  <name>flood_attack_mitigation</name>
  <rules>
    <name>mitigate_http_and_https_flood_attack</name>
    <condition>
      <ddos>
        <alert-packet-rate>1000</alert-packet-rate>
      </ddos>
    </condition>
    <action>
      <flow-action>
        <ingress-action>drop</ingress-action>
      </flow-action>
    </action>
  </rules>
</i2nsf-security-policy>

```

Figure 12: Configuration XML for Anti-DDoS to Mitigate HTTP and HTTPS Flood Attacks on a Company Web Server

[Figure 11](#) and [Figure 12](#) show the configuration XML documents for general firewall and http and https flood attack mitigation to mitigate http and https flood attacks on a company web server. For the security requirement, two NSFs (i.e., a general firewall and a http and https flood attack mitigation) were used because one NSF can not meet the security requirement. The instances of XML documents for the general firewall and http and https flood attack mitigation are as follows: Note that a detailed data model for the configuration of the advanced network security function (i.e., http and https flood attack mitigation) can be defined as an extension in future.

General Firewall is as follows:

1. The name of the security policy is flood\_attack\_mitigation.
2. The name of the rule is mitigate\_http\_and\_https\_flood\_attack.
3. The rule inspects a destination IPv4 address (i.e., 192.0.2.0/24) to inspect the access packets coming into the company web server.
4. The rule inspects a port number (i.e., 80 and 443) to inspect http and https packet.
5. If the packets match the rules above, the general firewall sends the packets to anti-DDoS for additional inspection because the general firewall can not control the amount of packets for http and https packets.

Anti DDoS for HTTP and HTTPS Flood Attack Mitigation is as follows:

1. The name of the security policy is flood\_attack\_mitigation.
2. The name of the rule is mitigate\_http\_and\_https\_flood\_attack.
3. The rule controls the http and https packets according to the amount of incoming packets (1000 packets per second).
4. If the incoming packets match the rules above, the packets are blocked.

## 6. IANA Considerations

This document requests IANA to register the following URI in the "IETF XML Registry" [[RFC3688](#)]:

URI: urn:ietf:params:xml:ns:yang:ietf-i2nsf-policy-rule-for-nsf

Registrant Contact: The IESG.

XML: N/A; the requested URI is an XML namespace.

This document requests IANA to register the following YANG module in the "YANG Module Names" registry [[RFC7950](#)][[RFC8525](#)]:

name: ietf-i2nsf-policy-rule-for-nsf

namespace: urn:ietf:params:xml:ns:yang:ietf-i2nsf-policy-rule-for-nsf

prefix: nsfintf

reference: RFC XXXX

## 7. Security Considerations

The YANG module specified in this document defines a data schema designed to be accessed through network management protocols such as NETCONF [[RFC6241](#)] or RESTCONF [[RFC8040](#)]. The lowest NETCONF layer is the secure transport layer, and the required secure transport is Secure Shell (SSH) [[RFC6242](#)]. The lowest RESTCONF layer is HTTPS, and the required secure transport is TLS [[RFC8446](#)].

The NETCONF access control model [[RFC8341](#)] provides a means of restricting access to specific NETCONF or RESTCONF users to a preconfigured subset of all available NETCONF or RESTCONF protocol operations and content.

There are a number of data nodes defined in this YANG module that are writable/creatable/deletable (i.e., config true, which is the default). These data nodes may be considered sensitive or vulnerable in some network environments. Write operations (e.g., edit-config) to these data nodes without proper protection can have a negative



effect on network operations. These are the subtrees and data nodes and their sensitivity/vulnerability:

\*ietf-i2nsf-policy-rule-for-nsf: Writing to almost any element of this YANG module would directly impact on the configuration of NSFs, e.g., completely turning off security monitoring and mitigation capabilities; altering the scope of this monitoring and mitigation; creating an overwhelming logging volume to overwhelm downstream analytics or storage capacity; creating logging patterns which are confusing; or rendering useless trained statistics or artificial intelligence models.

Some of the readable data nodes in this YANG module may be considered sensitive or vulnerable in some network environments. It is thus important to control read access (e.g., via get, get-config, or notification) to these data nodes. These are the subtrees and data nodes and their sensitivity/vulnerability:

\*ietf-i2nsf-policy-rule-for-nsf: The attacker may gather the security policy information of any target NSFs and misuse the security policy information for subsequent attacks.

Policy rules identifying the specified users and user groups can be specified with "rules/condition/context/users". As with other data in this YANG module, this user information is provided by the Security Controller to the NSFs and is protected via the transport and access control mechanisms described above.

## **8. Acknowledgments**

This document is a product by the I2NSF Working Group (WG) including WG Chairs (i.e., Linda Dunbar and Yoav Nir) and Diego Lopez. This document took advantage of the review and comments from the following people: Roman Danyliw, Acee Lindem, Dan Romascanu (GenART), Yoshifumi Nishida (TSVART), Kyle Rose (SecDir), Joe Clarke (OpsDir), and Tom Petch. The authors sincerely appreciate their sincere efforts and kind help.

This work was supported by Institute of Information & Communications Technology Planning & Evaluation (IITP) grant funded by the Korea MSIT (Ministry of Science and ICT) (R-20160222-002755, Cloud based Security Intelligence Technology Development for the Customized Security Service Provisioning). This work was supported in part by the IITP (2020-0-00395, Standard Development of Blockchain based Network Management Automation Technology).

## **9. Contributors**

The following are co-authors of this document:

Patrick Lingga - Department of Electrical and Computer Engineering, Sungkyunkwan University, 2066 Seobu-ro Jangan-gu, Suwon, Gyeonggi-do 16419, Republic of Korea, EMail: patricklink@skku.edu

Hyoungshick Kim - Department of Computer Science and Engineering, Sungkyunkwan University, 2066 Seobu-ro Jangan-gu, Suwon, Gyeonggi-do 16419, Republic of Korea, EMail: hyoung@skku.edu

Daeyoung Hyun - Department of Computer Science and Engineering, Sungkyunkwan University, 2066 Seobu-ro Jangan-gu, Suwon, Gyeonggi-do 16419, Republic of Korea, EMail: dyhyun@skku.edu

Dongjin Hong - Department of Electronic, Electrical and Computer Engineering, Sungkyunkwan University, 2066 Seobu-ro Jangan-gu, Suwon, Gyeonggi-do 16419, Republic of Korea, EMail: dong.jin@skku.edu

Liang Xia - Huawei, 101 Software Avenue, Nanjing, Jiangsu 210012, China, EMail: Frank.Xialiang@huawei.com

Tae-Jin Ahn - Korea Telecom, 70 Yuseong-Ro, Yuseong-Gu, Daejeon, 305-811, Republic of Korea, EMail: taejin.ahn@kt.com

Se-Hui Lee - Korea Telecom, 70 Yuseong-Ro, Yuseong-Gu, Daejeon, 305-811, Republic of Korea, EMail: sehuilee@kt.com

## **10. References**

### **10.1. Normative References**

[RFC0768] Postel, J., "User Datagram Protocol", STD 6, RFC 768, DOI 10.17487/RFC0768, August 1980, <<https://www.rfc-editor.org/info/rfc768>>.

[RFC0791] Postel, J., "Internet Protocol", STD 5, RFC 791, DOI 10.17487/RFC0791, September 1981, <<https://www.rfc-editor.org/info/rfc791>>.

[RFC0792] Postel, J., "Internet Control Message Protocol", STD 5, RFC 792, DOI 10.17487/RFC0792, September 1981, <<https://www.rfc-editor.org/info/rfc792>>.

[RFC0854] Postel, J. and J. Reynolds, "Telnet Protocol Specification", STD 8, RFC 854, DOI 10.17487/RFC0854, May 1983, <<https://www.rfc-editor.org/info/rfc854>>.

[RFC0959] Postel, J. and J. Reynolds, "File Transfer Protocol", STD 9, RFC 959, DOI 10.17487/RFC0959, October 1985, <<https://www.rfc-editor.org/info/rfc959>>.

**[RFC1939]**

Myers, J. and M. Rose, "Post Office Protocol - Version 3", STD 53, RFC 1939, DOI 10.17487/RFC1939, May 1996, <<https://www.rfc-editor.org/info/rfc1939>>.

**[RFC2119]**

Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.

**[RFC2595]**

Newman, C., "Using TLS with IMAP, POP3 and ACAP", RFC 2595, DOI 10.17487/RFC2595, June 1999, <<https://www.rfc-editor.org/info/rfc2595>>.

**[RFC3261]**

Rosenberg, J., Schulzrinne, H., Camarillo, G., Johnston, A., Peterson, J., Sparks, R., Handley, M., and E. Schooler, "SIP: Session Initiation Protocol", RFC 3261, DOI 10.17487/RFC3261, June 2002, <<https://www.rfc-editor.org/info/rfc3261>>.

**[RFC3688]**

Mealling, M., "The IETF XML Registry", BCP 81, RFC 3688, DOI 10.17487/RFC3688, January 2004, <<https://www.rfc-editor.org/info/rfc3688>>.

**[RFC4250]**

Lehtinen, S. and C. Lonvick, Ed., "The Secure Shell (SSH) Protocol Assigned Numbers", RFC 4250, DOI 10.17487/RFC4250, January 2006, <<https://www.rfc-editor.org/info/rfc4250>>.

**[RFC4340]**

Kohler, E., Handley, M., and S. Floyd, "Datagram Congestion Control Protocol (DCCP)", RFC 4340, DOI 10.17487/RFC4340, March 2006, <<https://www.rfc-editor.org/info/rfc4340>>.

**[RFC4443]**

Conta, A., Deering, S., and M. Gupta, Ed., "Internet Control Message Protocol (ICMPv6) for the Internet Protocol Version 6 (IPv6) Specification", STD 89, RFC 4443, DOI 10.17487/RFC4443, March 2006, <<https://www.rfc-editor.org/info/rfc4443>>.

**[RFC5321]**

Klensin, J., "Simple Mail Transfer Protocol", RFC 5321, DOI 10.17487/RFC5321, October 2008, <<https://www.rfc-editor.org/info/rfc5321>>.

**[RFC5595]**

Fairhurst, G., "The Datagram Congestion Control Protocol (DCCP) Service Codes", RFC 5595, DOI 10.17487/RFC5595, September 2009, <<https://www.rfc-editor.org/info/rfc5595>>.

**[RFC6020]**

Bjorklund, M., Ed., "YANG - A Data Modeling Language for the Network Configuration Protocol (NETCONF)", RFC 6020, DOI 10.17487/RFC6020, October 2010, <<https://www.rfc-editor.org/info/rfc6020>>.

**[RFC6241]**

Enns, R., Ed., Bjorklund, M., Ed., Schoenwaelder, J., Ed., and A. Bierman, Ed., "Network Configuration Protocol (NETCONF)", RFC 6241, DOI 10.17487/RFC6241, June 2011, <<https://www.rfc-editor.org/info/rfc6241>>.

**[RFC6242]**

Wasserman, M., "Using the NETCONF Protocol over Secure Shell (SSH)", RFC 6242, DOI 10.17487/RFC6242, June 2011, <<https://www.rfc-editor.org/info/rfc6242>>.

**[RFC6335]**

Cotton, M., Eggert, L., Touch, J., Westerlund, M., and S. Cheshire, "Internet Assigned Numbers Authority (IANA) Procedures for the Management of the Service Name and Transport Protocol Port Number Registry", BCP 165, RFC 6335, DOI 10.17487/RFC6335, August 2011, <<https://www.rfc-editor.org/info/rfc6335>>.

**[RFC6991]**

Schoenwaelder, J., Ed., "Common YANG Data Types", RFC 6991, DOI 10.17487/RFC6991, July 2013, <<https://www.rfc-editor.org/info/rfc6991>>.

**[RFC7950]**

Bjorklund, M., Ed., "The YANG 1.1 Data Modeling Language", RFC 7950, DOI 10.17487/RFC7950, August 2016, <<https://www.rfc-editor.org/info/rfc7950>>.

**[RFC8040]**

Bierman, A., Bjorklund, M., and K. Watsen, "RESTCONF Protocol", RFC 8040, DOI 10.17487/RFC8040, January 2017, <<https://www.rfc-editor.org/info/rfc8040>>.

**[RFC8075]**

Castellani, A., Loreto, S., Rahman, A., Fossati, T., and E. Dijk, "Guidelines for Mapping Implementations: HTTP to the Constrained Application Protocol (CoAP)", RFC 8075, DOI 10.17487/RFC8075, February 2017, <<https://www.rfc-editor.org/info/rfc8075>>.

**[RFC8174]**

Leiba, B., "Ambiguity of Uppercase vs Lowercase in RFC 2119 Key Words", BCP 14, RFC 8174, DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.

**[RFC8200]**

Deering, S. and R. Hinden, "Internet Protocol, Version 6 (IPv6) Specification", STD 86, RFC 8200, DOI 10.17487/

RFC8200, July 2017, <<https://www.rfc-editor.org/info/rfc8200>>.

- [RFC8329] Lopez, D., Lopez, E., Dunbar, L., Strassner, J., and R. Kumar, "Framework for Interface to Network Security Functions", RFC 8329, DOI 10.17487/RFC8329, February 2018, <<https://www.rfc-editor.org/info/rfc8329>>.
- [RFC8335] Bonica, R., Thomas, R., Linkova, J., Lenart, C., and M. Boucadair, "PROBE: A Utility for Probing Interfaces", RFC 8335, DOI 10.17487/RFC8335, February 2018, <<https://www.rfc-editor.org/info/rfc8335>>.
- [RFC8340] Bjorklund, M. and L. Berger, Ed., "YANG Tree Diagrams", BCP 215, RFC 8340, DOI 10.17487/RFC8340, March 2018, <<https://www.rfc-editor.org/info/rfc8340>>.
- [RFC8341] Bierman, A. and M. Bjorklund, "Network Configuration Access Control Model", STD 91, RFC 8341, DOI 10.17487/RFC8341, March 2018, <<https://www.rfc-editor.org/info/rfc8341>>.
- [RFC8342] Bjorklund, M., Schoenwaelder, J., Shafer, P., Watsen, K., and R. Wilton, "Network Management Datastore Architecture (NMDA)", RFC 8342, DOI 10.17487/RFC8342, March 2018, <<https://www.rfc-editor.org/info/rfc8342>>.
- [RFC8407] Bierman, A., "Guidelines for Authors and Reviewers of Documents Containing YANG Data Models", BCP 216, RFC 8407, DOI 10.17487/RFC8407, October 2018, <<https://www.rfc-editor.org/info/rfc8407>>.
- [RFC8446] Rescorla, E., "The Transport Layer Security (TLS) Protocol Version 1.3", RFC 8446, DOI 10.17487/RFC8446, August 2018, <<https://www.rfc-editor.org/info/rfc8446>>.
- [RFC8519] Jethanandani, M., Agarwal, S., Huang, L., and D. Blair, "YANG Data Model for Network Access Control Lists (ACLs)", RFC 8519, DOI 10.17487/RFC8519, March 2019, <<https://www.rfc-editor.org/info/rfc8519>>.
- [RFC8525] Bierman, A., Bjorklund, M., Schoenwaelder, J., Watsen, K., and R. Wilton, "YANG Library", RFC 8525, DOI 10.17487/RFC8525, March 2019, <<https://www.rfc-editor.org/info/rfc8525>>.
- [RFC9051] Melnikov, A., Ed. and B. Leiba, Ed., "Internet Message Access Protocol (IMAP) - Version 4rev2", RFC 9051, DOI 10.17487/RFC9051, August 2021, <<https://www.rfc-editor.org/info/rfc9051>>.

**[I-D.ietf-httpbis-http2bis]**

Thomson, M. and C. Benfield, "HTTP/2", Work in Progress, Internet-Draft, draft-ietf-httpbis-http2bis-07, 24 January 2022, <<https://www.ietf.org/archive/id/draft-ietf-httpbis-http2bis-07.txt>>.

**[I-D.ietf-httpbis-messaging]**

Fielding, R. T., Nottingham, M., and J. Reschke, "HTTP/1.1", Work in Progress, Internet-Draft, draft-ietf-httpbis-messaging-19, 12 September 2021, <<https://www.ietf.org/archive/id/draft-ietf-httpbis-messaging-19.txt>>.

**[I-D.ietf-httpbis-semantic]**

Fielding, R. T., Nottingham, M., and J. Reschke, "HTTP Semantics", Work in Progress, Internet-Draft, draft-ietf-httpbis-semantic-19, 12 September 2021, <<https://www.ietf.org/archive/id/draft-ietf-httpbis-semantic-19.txt>>.

**[I-D.ietf-i2nsf-capability-data-model]**

Hares, S., Jeong, J. (., Kim, J. (., Moskowitz, R., and Q. Lin, "I2NSF Capability YANG Data Model", Work in Progress, Internet-Draft, draft-ietf-i2nsf-capability-data-model-26, 10 February 2022, <<https://www.ietf.org/archive/id/draft-ietf-i2nsf-capability-data-model-26.txt>>.

**[I-D.ietf-i2nsf-nsf-monitoring-data-model]**

Jeong, J. (., Lingga, P., Hares, S., Xia, L. (., and H. Birkholz, "I2NSF NSF Monitoring Interface YANG Data Model", Work in Progress, Internet-Draft, draft-ietf-i2nsf-nsf-monitoring-data-model-14, 28 January 2022, <<https://www.ietf.org/archive/id/draft-ietf-i2nsf-nsf-monitoring-data-model-14.txt>>.

**[I-D.ietf-tcpm-rfc793bis]**

Eddy, W. M., "Transmission Control Protocol (TCP) Specification", Work in Progress, Internet-Draft, draft-ietf-tcpm-rfc793bis-26, 8 February 2022, <<https://www.ietf.org/archive/id/draft-ietf-tcpm-rfc793bis-26.txt>>.

**[I-D.ietf-tsvwg-rfc4960-bis]**

Stewart, R. R., Tüxen, M., and K. E. E. Nielsen, "Stream Control Transmission Protocol", Work in Progress, Internet-Draft, draft-ietf-tsvwg-rfc4960-bis-18, 16 January 2022, <<https://www.ietf.org/archive/id/draft-ietf-tsvwg-rfc4960-bis-18.txt>>.

## 10.2. Informative References

[RFC4732]

Handley, M., Ed., Rescorla, E., Ed., and IAB, "Internet Denial-of-Service Considerations", RFC 4732, DOI 10.17487/RFC4732, December 2006, <<https://www.rfc-editor.org/info/rfc4732>>.

[RFC4987] Eddy, W., "TCP SYN Flooding Attacks and Common Mitigations", RFC 4987, DOI 10.17487/RFC4987, August 2007, <<https://www.rfc-editor.org/info/rfc4987>>.

**[I-D.ietf-i2nsf-consumer-facing-interface-dm]**

Jeong, J. (., Chung, C., Ahn, T., Kumar, R., and S. Hares, "I2NSF Consumer-Facing Interface YANG Data Model", Work in Progress, Internet-Draft, draft-ietf-i2nsf-consumer-facing-interface-dm-16, 28 January 2022, <<https://www.ietf.org/archive/id/draft-ietf-i2nsf-consumer-facing-interface-dm-16.txt>>.

**[I-D.ietf-netmod-geo-location]**

Hopps, C., "A YANG Grouping for Geographic Locations", Work in Progress, Internet-Draft, draft-ietf-netmod-geo-location-11, 24 October 2021, <<https://www.ietf.org/archive/id/draft-ietf-netmod-geo-location-11.txt>>.

[ISO-3166] "Codes for the representation of names of countries and their subdivisions", ISO 3166, September 2018, <<https://www.iso.org/iso-3166-country-codes.html>>.

[IEEE-802.3] Institute of Electrical and Electronics Engineers, "IEEE Standard for Ethernet", 2018, <<https://ieeexplore.ieee.org/document/8457469/>>.

**Authors' Addresses**

Jinyong (Tim) Kim (editor)  
Department of Electronic, Electrical and Computer Engineering  
Sungkyunkwan University  
2066 Seobu-Ro, Jangan-Gu  
Suwon  
Gyeonggi-Do  
16419  
Republic of Korea

Phone: [+82 10 8273 0930](tel:+82_10_8273_0930)  
Email: [timkim@skku.edu](mailto:timkim@skku.edu)

Jaehoon (Paul) Jeong (editor)  
Department of Computer Science and Engineering  
Sungkyunkwan University  
2066 Seobu-Ro, Jangan-Gu  
Suwon

Gyeonggi-Do  
16419  
Republic of Korea

Phone: [+82 31 299 4957](tel:+82-31-299-4957)  
Email: [pauljeong@skku.edu](mailto:pauljeong@skku.edu)  
URI: <http://iotlab.skku.edu/people-jaehoon-jeong.php>

Jung-Soo Park  
Electronics and Telecommunications Research Institute  
218 Gajeong-Ro, Yuseong-Gu  
Daejeon  
34129  
Republic of Korea

Phone: [+82 42 860 6514](tel:+82-42-860-6514)  
Email: [pjs@etri.re.kr](mailto:pjs@etri.re.kr)

Susan Hares  
Huawei  
7453 Hickory Hill  
Saline, MI 48176  
United States of America

Phone: [+1-734-604-0332](tel:+1-734-604-0332)  
Email: [shares@ndzh.com](mailto:shares@ndzh.com)

Qiushi Lin  
Huawei  
Huawei Industrial Base  
Shenzhen  
Guangdong 518129,  
China

Email: [linqiushi@huawei.com](mailto:linqiushi@huawei.com)