

IDMR Working Group  
INTERNET-DRAFT  
Expires January 2001

Keith McCloghrie  
Dino Farinacci  
cisco Systems  
Dave Thaler  
Microsoft  
Bill Fenner  
AT&T Labs  
10 July 2000

**Protocol Independent Multicast MIB for IPv4**  
**<[draft-ietf-idmr-pim-mib-11.txt](#)>**

Status of this Memo

This document is an Internet-Draft and is in full conformance with all provisions of [Section 10 of RFC2026](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at  
<http://www.ietf.org/ietf/1id-abstracts.txt>

The list of Internet-Draft Shadow Directories can be accessed at  
<http://www.ietf.org/shadow.html>.

Copyright Notice

Copyright (C) The Internet Society (2000). All Rights Reserved.

## **1. Abstract**

This memo defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. In particular, it describes managed objects used for managing the Protocol Independent Multicast (PIM) protocol for IPv4.

## **2. Introduction**

This memo defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. In particular, it describes managed objects used for managing the Protocol Independent Multicast (PIM) protocol [[16](#),[17](#),[18](#),[19](#)]. This MIB module is applicable to IPv4 multicast routers which implement PIM. This MIB does not support management of PIM for other address families, including IPv6. Such management may be supported by other MIBs.

## **3. The SNMP Network Management Framework**

The SNMP Management Framework presently consists of five major components:

- o An overall architecture, described in [RFC 2271](#) [[1](#)].
- o Mechanisms for describing and naming objects and events for the purpose of management. The first version of this Structure of Management Information (SMI) is called SMIV1 and described in [RFC 1155](#) [[2](#)], [RFC 1212](#) [[3](#)] and [RFC 1215](#) [[4](#)]. The second version, called SMIV2, is described in [RFC 2578](#) [[5](#)], [RFC 2579](#) [[6](#)] and [RFC 2580](#) [[7](#)].
- o Message protocols for transferring management information. The first version of the SNMP message protocol is called SNMPv1 and described in [RFC 1157](#) [[8](#)]. A second version of the SNMP message protocol, which is not an Internet standards track protocol, is called SNMPv2c and described in [RFC 1901](#) [[9](#)] and [RFC 1906](#) [[10](#)]. The third version of the message protocol is called SNMPv3 and described in [RFC 1906](#) [[10](#)], [RFC 2572](#) [[11](#)] and [RFC 2574](#) [[12](#)].
- o Protocol operations for accessing management information. The first set of protocol operations and associated PDU formats is described in [RFC 1157](#) [[8](#)]. A second set of protocol operations and associated PDU formats is described in [RFC 1905](#) [[13](#)].

Expires January 2001

[Page 2]

- o A set of fundamental applications described in [RFC 2573](#) [[14](#)] and the view-based access control mechanism described in [RFC 2575](#) [[15](#)].

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. Objects in the MIB are defined using the mechanisms defined in the SMI.

This memo specifies a MIB module that is compliant to the SMIV2. A MIB conforming to the SMIV1 can be produced through the appropriate translations. The resulting translated MIB must be semantically equivalent, except where objects or events are omitted because no translation is possible (use of Counter64). Some machine readable information in SMIV2 will be converted into textual descriptions in SMIV1 during the translation process. However, this loss of machine readable information is not considered to change the semantics of the MIB.

#### [4.](#) Overview

This MIB module contains one scalar and eight tables. Some of the objects in these tables are deprecated. This MIB contains deprecated objects since they are necessary for managing PIMv1 routers, but PIMv1 itself is obsoleted by PIMv2 [[18](#),[19](#)].

The tables contained in this MIB are:

- (1) The PIM Interface Table contains one row for each of the router's PIM interfaces.
- (2) The PIM Neighbor Table contains one row for each of the router's PIM neighbors.
- (3) The PIM IP Multicast Route Table contains one row for each multicast routing entry whose incoming interface is running PIM.
- (4) The PIM Next Hop Table which contains one row for each outgoing interface list entry in the multicast routing table whose interface is running PIM, and whose state is pruned.
- (5) The (deprecated) PIM RP Table contains the PIM (version 1) information for IP multicast groups which is common to all RPs of a group.

Expires January 2001

[Page 3]

- (6) The PIM RP-Set Table contains the PIM (version 2) information for sets of candidate Rendezvous Points (RPs) for IP multicast group addresses with particular address prefixes.
- (7) The PIM Candidate-RP Table contains the IP multicast groups for which the local router is to advertise itself as a Candidate-RP. If this table is empty, then the local router advertises itself as a Candidate-RP for all groups.
- (8) The PIM Component Table contains one row for each of the PIM domains to which the router is connected.

## 5. Definitions

PIM-MIB DEFINITIONS ::= BEGIN

### IMPORTS

```
MODULE-IDENTITY, OBJECT-TYPE, experimental,
NOTIFICATION-TYPE,
Integer32, IPAddress, TimeTicks FROM SNMPv2-SMI
RowStatus, TruthValue FROM SNMPv2-TC
MODULE-COMPLIANCE, OBJECT-GROUP,
NOTIFICATION-GROUP FROM SNMPv2-CONF
ipMRouteGroup, ipMRouteSource,
ipMRouteSourceMask, ipMRouteNextHopGroup,
ipMRouteNextHopSource, ipMRouteNextHopSourceMask,
ipMRouteNextHopIfIndex,
ipMRouteNextHopAddress FROM IPMROUTE-STD-MIB
InterfaceIndex FROM IF-MIB;
```

### pimMIB MODULE-IDENTITY

LAST-UPDATED "200007101200Z" -- July 10, 2000

ORGANIZATION "IETF IDMR Working Group."

#### CONTACT-INFO

" Dave Thaler  
Microsoft Corporation  
One Microsoft Way  
Redmond, WA 98052-6399  
US

Phone: +1 425 703 8835

Email: dthaler@dthaler.microsoft.com"

#### DESCRIPTION

"The MIB module for management of PIM routers."

REVISION "200007071200Z" -- July 10, 2000

#### DESCRIPTION

"Initial version, published as RFC xxxx (to be filled in by  
RFC-Editor)."

::= { experimental 61 }

pimMIBObjects OBJECT IDENTIFIER ::= { pimMIB 1 }

pimTraps OBJECT IDENTIFIER ::= { pimMIBObjects 0 }

pim OBJECT IDENTIFIER ::= { pimMIBObjects 1 }

pimJoinPruneInterval OBJECT-TYPE

Expires January 2001

[Page 5]



SYNTAX       Integer32  
UNITS         "seconds"  
MAX-ACCESS   read-write  
STATUS        current  
DESCRIPTION  
              "The default interval at which periodic PIM-SM Join/Prune  
              messages are to be sent."  
 ::= { pim 1 }

-- The PIM Interface Table

pimInterfaceTable OBJECT-TYPE

SYNTAX SEQUENCE OF PimInterfaceEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The (conceptual) table listing the router's PIM interfaces.  
IGMP and PIM are enabled on all interfaces listed in this  
table."

::= { pim 2 }

pimInterfaceEntry OBJECT-TYPE

SYNTAX PimInterfaceEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"An entry (conceptual row) in the pimInterfaceTable."

INDEX { pimInterfaceIfIndex }

::= { pimInterfaceTable 1 }

PimInterfaceEntry ::= SEQUENCE {

pimInterfaceIfIndex InterfaceIndex,

pimInterfaceAddress IpAddress,

pimInterfaceNetMask IpAddress,

pimInterfaceMode INTEGER,

pimInterfaceDR IpAddress,

pimInterfaceHelloInterval Integer32,

pimInterfaceStatus RowStatus,

pimInterfaceJoinPruneInterval Integer32,

pimInterfaceCBSRPreference Integer32

}

pimInterfaceIfIndex OBJECT-TYPE

SYNTAX InterfaceIndex

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The ifIndex value of this PIM interface."

::= { pimInterfaceEntry 1 }

pimInterfaceAddress OBJECT-TYPE

SYNTAX IpAddress

MAX-ACCESS read-only

STATUS current

Expires January 2001

[Page 7]

## DESCRIPTION

"The IP address of the PIM interface."

::= { pimInterfaceEntry 2 }

## pimInterfaceNetMask OBJECT-TYPE

SYNTAX       IpAddress

MAX-ACCESS read-only

STATUS       current

## DESCRIPTION

"The network mask for the IP address of the PIM interface."

::= { pimInterfaceEntry 3 }

## pimInterfaceMode OBJECT-TYPE

SYNTAX       INTEGER { dense(1), sparse(2), sparseDense(3) }

MAX-ACCESS read-create

STATUS       current

## DESCRIPTION

"The configured mode of this PIM interface. A value of sparseDense is only valid for PIMv1."

DEFVAL       { dense }

::= { pimInterfaceEntry 4 }

## pimInterfaceDR OBJECT-TYPE

SYNTAX       IpAddress

MAX-ACCESS read-only

STATUS       current

## DESCRIPTION

"The Designated Router on this PIM interface. For point-to-point interfaces, this object has the value 0.0.0.0."

::= { pimInterfaceEntry 5 }

## pimInterfaceHelloInterval OBJECT-TYPE

SYNTAX       Integer32

UNITS        "seconds"

MAX-ACCESS read-create

STATUS       current

## DESCRIPTION

"The frequency at which PIM Hello messages are transmitted on this interface."

DEFVAL       { 30 }

::= { pimInterfaceEntry 6 }

## pimInterfaceStatus OBJECT-TYPE

SYNTAX       RowStatus

MAX-ACCESS read-create

Expires January 2001

[Page 8]

```
STATUS      current
DESCRIPTION
    "The status of this entry.  Creating the entry enables PIM
    on the interface; destroying the entry disables PIM on the
    interface."
::= { pimInterfaceEntry 7 }
```

pimInterfaceJoinPruneInterval OBJECT-TYPE

```
SYNTAX      Integer32
UNITS       "seconds"
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
    "The frequency at which PIM Join/Prune messages are
    transmitted on this PIM interface.  The default value of
    this object is the pimJoinPruneInterval."
::= { pimInterfaceEntry 8 }
```

pimInterfaceCBSRPreference OBJECT-TYPE

```
SYNTAX      Integer32 (-1..255)
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
    "The preference value for the local interface as a candidate
    bootstrap router.  The value of -1 is used to indicate that
    the local interface is not a candidate BSR interface."
DEFVAL      { 0 }
::= { pimInterfaceEntry 9 }
```

-- The PIM Neighbor Table

pimNeighborTable OBJECT-TYPE

```
SYNTAX      SEQUENCE OF PimNeighborEntry
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
    "The (conceptual) table listing the router's PIM neighbors."
::= { pim 3 }
```

pimNeighborEntry OBJECT-TYPE

```
SYNTAX      PimNeighborEntry
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
```

Expires January 2001

[Page 9]

"An entry (conceptual row) in the pimNeighborTable."  
INDEX { pimNeighborAddress }  
::= { pimNeighborTable 1 }

PimNeighborEntry ::= SEQUENCE {  
 pimNeighborAddress IPAddress,  
 pimNeighborIfIndex InterfaceIndex,  
 pimNeighborUpTime TimeTicks,  
 pimNeighborExpiryTime TimeTicks,  
 pimNeighborMode INTEGER  
}

pimNeighborAddress OBJECT-TYPE  
 SYNTAX IPAddress  
 MAX-ACCESS not-accessible  
 STATUS current  
 DESCRIPTION  
 "The IP address of the PIM neighbor for which this entry  
 contains information."  
 ::= { pimNeighborEntry 1 }

pimNeighborIfIndex OBJECT-TYPE  
 SYNTAX InterfaceIndex  
 MAX-ACCESS read-only  
 STATUS current  
 DESCRIPTION  
 "The value of ifIndex for the interface used to reach this  
 PIM neighbor."  
 ::= { pimNeighborEntry 2 }

pimNeighborUpTime OBJECT-TYPE  
 SYNTAX TimeTicks  
 MAX-ACCESS read-only  
 STATUS current  
 DESCRIPTION  
 "The time since this PIM neighbor (last) became a neighbor  
 of the local router."  
 ::= { pimNeighborEntry 3 }

pimNeighborExpiryTime OBJECT-TYPE  
 SYNTAX TimeTicks  
 MAX-ACCESS read-only  
 STATUS current  
 DESCRIPTION  
 "The minimum time remaining before this PIM neighbor will be



Expires January 2001

[Page 10]

```

        aged out."
 ::= { pimNeighborEntry 4 }

pimNeighborMode OBJECT-TYPE
    SYNTAX      INTEGER { dense(1), sparse(2) }
    MAX-ACCESS  read-only
    STATUS      deprecated
    DESCRIPTION
        "The active PIM mode of this neighbor.  This object is
        deprecated for PIMv2 routers since all neighbors on the
        interface must be either dense or sparse as determined by
        the protocol running on the interface."
 ::= { pimNeighborEntry 5 }

--
-- The PIM IP Multicast Route Table
--

pimIpMRouteTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF PimIpMRouteEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The (conceptual) table listing PIM-specific information on
        a subset of the rows of the ipMRouteTable defined in the IP
        Multicast MIB."
 ::= { pim 4 }

pimIpMRouteEntry OBJECT-TYPE
    SYNTAX      PimIpMRouteEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "An entry (conceptual row) in the pimIpMRouteTable.  There
        is one entry per entry in the ipMRouteTable whose incoming
        interface is running PIM."
    INDEX       { ipMRouteGroup, ipMRouteSource, ipMRouteSourceMask }
 ::= { pimIpMRouteTable 1 }

PimIpMRouteEntry ::= SEQUENCE {
    pimIpMRouteUpstreamAssertTimer  TimeTicks,
    pimIpMRouteAssertMetric         Integer32,
    pimIpMRouteAssertMetricPref     Integer32,
    pimIpMRouteAssertRPTBit         TruthValue,
    pimIpMRouteFlags                BITS

```

Expires January 2001

[Page 11]

```
}
```

```
pimIpMRouteUpstreamAssertTimer OBJECT-TYPE
```

```
    SYNTAX      TimeTicks
```

```
    MAX-ACCESS  read-only
```

```
    STATUS      current
```

```
    DESCRIPTION
```

```
        "The time remaining before the router changes its upstream
        neighbor back to its RPF neighbor.  This timer is called the
        Assert timer in the PIM Sparse and Dense mode specification.
        A value of 0 indicates that no Assert has changed the
        upstream neighbor away from the RPF neighbor."
```

```
    ::= { pimIpMRouteEntry 1 }
```

```
pimIpMRouteAssertMetric OBJECT-TYPE
```

```
    SYNTAX      Integer32
```

```
    MAX-ACCESS  read-only
```

```
    STATUS      current
```

```
    DESCRIPTION
```

```
        "The metric advertised by the assert winner on the upstream
        interface, or 0 if no such assert is in received."
```

```
    ::= { pimIpMRouteEntry 2 }
```

```
pimIpMRouteAssertMetricPref OBJECT-TYPE
```

```
    SYNTAX      Integer32
```

```
    MAX-ACCESS  read-only
```

```
    STATUS      current
```

```
    DESCRIPTION
```

```
        "The preference advertised by the assert winner on the
        upstream interface, or 0 if no such assert is in effect."
```

```
    ::= { pimIpMRouteEntry 3 }
```

```
pimIpMRouteAssertRPTBit OBJECT-TYPE
```

```
    SYNTAX      TruthValue
```

```
    MAX-ACCESS  read-only
```

```
    STATUS      current
```

```
    DESCRIPTION
```

```
        "The value of the RPT-bit advertised by the assert winner on
        the upstream interface, or false if no such assert is in
        effect."
```

```
    ::= { pimIpMRouteEntry 4 }
```

```
pimIpMRouteFlags OBJECT-TYPE
```

```
    SYNTAX      BITS {
        rpt(0),
```

Expires January 2001

[Page 12]

```

        spt(1)
    }
    MAX-ACCESS read-only
    STATUS      current
    DESCRIPTION
        "This object describes PIM-specific flags related to a
        multicast state entry.  See the PIM Sparse Mode
        specification for the meaning of the RPT and SPT bits."
    ::= { pimIpMRouteEntry 5 }

```

```

--
-- The PIM Next Hop Table
--

```

```

pimIpMRouteNextHopTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF PimIpMRouteNextHopEntry
    MAX-ACCESS not-accessible
    STATUS      current
    DESCRIPTION
        "The (conceptual) table listing PIM-specific information on
        a subset of the rows of the ipMRouteNextHopTable defined in
        the IP Multicast MIB."
    ::= { pim 7 }

```

```

pimIpMRouteNextHopEntry OBJECT-TYPE
    SYNTAX      PimIpMRouteNextHopEntry
    MAX-ACCESS not-accessible
    STATUS      current
    DESCRIPTION
        "An entry (conceptual row) in the pimIpMRouteNextHopTable.
        There is one entry per entry in the ipMRouteNextHopTable
        whose interface is running PIM and whose
        ipMRouteNextHopState is pruned(1)."
    INDEX       { ipMRouteNextHopGroup, ipMRouteNextHopSource,
                  ipMRouteNextHopSourceMask, ipMRouteNextHopIfIndex,
                  ipMRouteNextHopAddress }
    ::= { pimIpMRouteNextHopTable 1 }

```

```

PimIpMRouteNextHopEntry ::= SEQUENCE {
    pimIpMRouteNextHopPruneReason      INTEGER
}

```

```

pimIpMRouteNextHopPruneReason OBJECT-TYPE
    SYNTAX      INTEGER {
        other (1),

```

Expires January 2001

[Page 13]

```
        prune (2),
        assert (3)
    }
MAX-ACCESS read-only
STATUS      current
DESCRIPTION
    "This object indicates why the downstream interface was
    pruned, whether in response to a PIM prune message or due to
    PIM Assert processing."
 ::= { pimIpMRouteNextHopEntry 2 }
```

-- The PIM RP Table

```
pimRPTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF PimRPEntry
    MAX-ACCESS  not-accessible
    STATUS      deprecated
    DESCRIPTION
        "The (conceptual) table listing PIM version 1 information
        for the Rendezvous Points (RPs) for IP multicast groups.
        This table is deprecated since its function is replaced by
        the pimRPSetTable for PIM version 2."
    ::= { pim 5 }
```

```
pimRPEntry OBJECT-TYPE
    SYNTAX      PimRPEntry
    MAX-ACCESS  not-accessible
    STATUS      deprecated
    DESCRIPTION
        "An entry (conceptual row) in the pimRPTable. There is one
        entry per RP address for each IP multicast group."
    INDEX       { pimRPGroupAddress, pimRPAddress }
    ::= { pimRPTable 1 }
```



Expires January 2001

[Page 14]

```
PimRPEntry ::= SEQUENCE {
```

```
    pimRPGroupAddress  IpAddress,
    pimRPAddress        IpAddress,
    pimRPState          INTEGER,
    pimRPStateTimer     TimeTicks,
    pimRPLastChange     TimeTicks,
    pimRPRowStatus      RowStatus
```

```
}
```

```
pimRPGroupAddress OBJECT-TYPE
```

```
    SYNTAX      IpAddress
    MAX-ACCESS  not-accessible
    STATUS      deprecated
    DESCRIPTION
```

```
        "The IP multicast group address for which this entry
        contains information about an RP."
```

```
    ::= { pimRPEntry 1 }
```

```
pimRPAddress OBJECT-TYPE
```

```
    SYNTAX      IpAddress
    MAX-ACCESS  not-accessible
    STATUS      deprecated
    DESCRIPTION
```

```
        "The unicast address of the RP."
```

```
    ::= { pimRPEntry 2 }
```

```
pimRPState OBJECT-TYPE
```

```
    SYNTAX      INTEGER { up(1), down(2) }
    MAX-ACCESS  read-only
    STATUS      deprecated
    DESCRIPTION
```

```
        "The state of the RP."
```

```
    ::= { pimRPEntry 3 }
```

```
pimRPStateTimer OBJECT-TYPE
```

```
    SYNTAX      TimeTicks
    MAX-ACCESS  read-only
    STATUS      deprecated
    DESCRIPTION
```

```
        "The minimum time remaining before the next state change.
        When pimRPState is up, this is the minimum time which must
        expire until it can be declared down.  When pimRPState is
        down, this is the time until it will be declared up (in
        order to retry)."
```

```
    ::= { pimRPEntry 4 }
```

Expires January 2001

[Page 15]

pimRPLastChange OBJECT-TYPE

SYNTAX TimeTicks

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"The value of sysUpTime at the time when the corresponding instance of pimRPState last changed its value."

::= { pimRPEntry 5 }

pimRPRowStatus OBJECT-TYPE

SYNTAX RowStatus

MAX-ACCESS read-create

STATUS deprecated

DESCRIPTION

"The status of this row, by which new entries may be created, or old entries deleted from this table."

::= { pimRPEntry 6 }

-- The PIM RP-Set Table

pimRPSetTable OBJECT-TYPE

SYNTAX SEQUENCE OF PimRPSetEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The (conceptual) table listing PIM information for candidate Rendezvous Points (RPs) for IP multicast groups. When the local router is the BSR, this information is obtained from received Candidate-RP-Advertisements. When the local router is not the BSR, this information is obtained from received RP-Set messages."

::= { pim 6 }

pimRPSetEntry OBJECT-TYPE

SYNTAX PimRPSetEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"An entry (conceptual row) in the pimRPSetTable."

INDEX { pimRPSetComponent, pimRPSetGroupAddress,  
pimRPSetGroupMask, pimRPSetAddress }

::= { pimRPSetTable 1 }

PimRPSetEntry ::= SEQUENCE {

Expires January 2001

[Page 16]

```
pimRPSetGroupAddress  IpAddress,
pimRPSetGroupMask     IpAddress,
pimRPSetAddress       IpAddress,
pimRPSetHoldTime      Integer32,
pimRPSetExpiryTime    TimeTicks,
pimRPSetComponent     Integer32
}
```

pimRPSetGroupAddress OBJECT-TYPE

```
SYNTAX      IpAddress
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
    "The IP multicast group address which, when combined with
    pimRPSetGroupMask, gives the group prefix for which this
    entry contains information about the Candidate-RP."
 ::= { pimRPSetEntry 1 }
```

pimRPSetGroupMask OBJECT-TYPE

```
SYNTAX      IpAddress
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
    "The multicast group address mask which, when combined with
    pimRPSetGroupAddress, gives the group prefix for which this
    entry contains information about the Candidate-RP."
 ::= { pimRPSetEntry 2 }
```

pimRPSetAddress OBJECT-TYPE

```
SYNTAX      IpAddress
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
    "The IP address of the Candidate-RP."
 ::= { pimRPSetEntry 3 }
```

pimRPSetHoldTime OBJECT-TYPE

```
SYNTAX      Integer32 (0..255)
UNITS       "seconds"
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The holdtime of a Candidate-RP.  If the local router is not
    the BSR, this value is 0."
 ::= { pimRPSetEntry 4 }
```

Expires January 2001

[Page 17]

pimRPSetExpiryTime OBJECT-TYPE

SYNTAX TimeTicks

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The minimum time remaining before the Candidate-RP will be declared down. If the local router is not the BSR, this value is 0."

::= { pimRPSetEntry 5 }

pimRPSetComponent OBJECT-TYPE

SYNTAX Integer32 (1..255)

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

" A number uniquely identifying the component. Each protocol instance connected to a separate domain should have a different index value."

::= { pimRPSetEntry 6 }

--

-- Note: { pim 8 } through { pim 10 } were used in older versions  
-- of this MIB. Since some earlier versions of this MIB have been  
-- widely-deployed, these values must not be used in the future,  
-- as long the MIB is rooted under { experimental 61 }.

--



Expires January 2001

[Page 18]

-- The PIM Candidate-RP Table

pimCandidateRPTable OBJECT-TYPE

SYNTAX SEQUENCE OF PimCandidateRPEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The (conceptual) table listing the IP multicast groups for which the local router is to advertise itself as a Candidate-RP when the value of pimComponentCRPHoldTime is non-zero. If this table is empty, then the local router will advertise itself as a Candidate-RP for all groups (providing the value of pimComponentCRPHoldTime is non-zero)."

::= { pim 11 }

pimCandidateRPEntry OBJECT-TYPE

SYNTAX PimCandidateRPEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"An entry (conceptual row) in the pimCandidateRPTable."

INDEX { pimCandidateRPGroupAddress,  
pimCandidateRPGroupMask }

::= { pimCandidateRPTable 1 }

PimCandidateRPEntry ::= SEQUENCE {

pimCandidateRPGroupAddress IpAddress,

pimCandidateRPGroupMask IpAddress,

pimCandidateRPAddress IpAddress,

pimCandidateRPRowStatus RowStatus

}

pimCandidateRPGroupAddress OBJECT-TYPE

SYNTAX IpAddress

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The IP multicast group address which, when combined with pimCandidateRPGroupMask, identifies a group prefix for which the local router will advertise itself as a Candidate-RP."

::= { pimCandidateRPEntry 1 }

pimCandidateRPGroupMask OBJECT-TYPE

SYNTAX IpAddress

Expires January 2001

[Page 19]

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The multicast group address mask which, when combined with  
pimCandidateRPGroupMask, identifies a group prefix for which  
the local router will advertise itself as a Candidate-RP."

::= { pimCandidateRPEntry 2 }

pimCandidateRPAAddress OBJECT-TYPE

SYNTAX IpAddress

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The (unicast) address of the interface which will be  
advertised as a Candidate-RP."

::= { pimCandidateRPEntry 3 }

pimCandidateRPRowStatus OBJECT-TYPE

SYNTAX RowStatus

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The status of this row, by which new entries may be  
created, or old entries deleted from this table."

::= { pimCandidateRPEntry 4 }

-- The PIM Component Table

pimComponentTable OBJECT-TYPE

SYNTAX SEQUENCE OF PimComponentEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The (conceptual) table containing objects specific to a PIM  
domain. One row exists for each domain to which the router  
is connected. A PIM-SM domain is defined as an area of the  
network over which Bootstrap messages are forwarded.  
Typically, a PIM-SM router will be a member of exactly one  
domain. This table also supports, however, routers which  
may form a border between two PIM-SM domains and do not  
forward Bootstrap messages between them."

::= { pim 12 }

pimComponentEntry OBJECT-TYPE

SYNTAX PimComponentEntry

Expires January 2001

[Page 20]

MAX-ACCESS not-accessible  
STATUS current  
DESCRIPTION  
    "An entry (conceptual row) in the pimComponentTable."  
INDEX { pimComponentIndex }  
::= { pimComponentTable 1 }

PimComponentEntry ::= SEQUENCE {  
    pimComponentIndex Integer32,  
    pimComponentBSRAddress IpAddress,  
    pimComponentBSRExpiryTime TimeTicks,  
    pimComponentCRPHoldTime Integer32,  
    pimComponentStatus RowStatus  
}

pimComponentIndex OBJECT-TYPE  
SYNTAX Integer32 (1..255)  
MAX-ACCESS not-accessible  
STATUS current  
DESCRIPTION  
    "A number uniquely identifying the component. Each protocol  
    instance connected to a separate domain should have a  
    different index value. Routers that only support membership  
    in a single PIM-SM domain should use a pimComponentIndex  
    value of 1."  
::= { pimComponentEntry 1 }

pimComponentBSRAddress OBJECT-TYPE  
SYNTAX IpAddress  
MAX-ACCESS read-only  
STATUS current  
DESCRIPTION  
    "The IP address of the bootstrap router (BSR) for the local  
    PIM region."  
::= { pimComponentEntry 2 }

pimComponentBSRExpiryTime OBJECT-TYPE  
SYNTAX TimeTicks  
MAX-ACCESS read-only  
STATUS current  
DESCRIPTION  
    "The minimum time remaining before the bootstrap router in  
    the local domain will be declared down. For candidate BSRs,  
    this is the time until the component sends an RP-Set  
    message. For other routers, this is the time until it may

Expires January 2001

[Page 21]

```
        accept an RP-Set message from a lower candidate BSR."
 ::= { pimComponentEntry 3 }
```

pimComponentCRPHoldTime OBJECT-TYPE

```
SYNTAX      Integer32 (0..255)
UNITS       "seconds"
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
    "The holdtime of the component when it is a candidate RP in
    the local domain. The value of 0 is used to indicate that
    the local system is not a Candidate-RP."
DEFVAL      { 0 }
 ::= { pimComponentEntry 4 }
```

pimComponentStatus OBJECT-TYPE

```
SYNTAX      RowStatus
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
    "The status of this entry. Creating the entry creates
    another protocol instance; destroying the entry disables a
    protocol instance."
 ::= { pimComponentEntry 5 }
```

-- PIM Traps

pimNeighborLoss NOTIFICATION-TYPE

```
OBJECTS {
    pimNeighborIfIndex
}
STATUS      current
DESCRIPTION
    "A pimNeighborLoss trap signifies the loss of an adjacency
    with a neighbor. This trap should be generated when the
    neighbor timer expires, and the router has no other
    neighbors on the same interface with a lower IP address than
    itself."
 ::= { pimTraps 1 }
```



Expires January 2001

[Page 22]

```
-- conformance information
```

```
pimMIBConformance OBJECT IDENTIFIER ::= { pimMIB 2 }
pimMIBCompliances OBJECT IDENTIFIER ::= { pimMIBConformance 1 }
pimMIBGroups      OBJECT IDENTIFIER ::= { pimMIBConformance 2 }
```

```
-- compliance statements
```

```
pimV1MIBCompliance MODULE-COMPLIANCE
```

```
    STATUS deprecated
```

```
    DESCRIPTION
```

```
        "The compliance statement for routers running PIMv1 and
        implementing the PIM MIB."
```

```
    MODULE -- this module
```

```
        MANDATORY-GROUPS { pimV1MIBGroup }
```

```
    ::= { pimMIBCompliances 1 }
```

```
pimSparseV2MIBCompliance MODULE-COMPLIANCE
```

```
    STATUS current
```

```
    DESCRIPTION
```

```
        "The compliance statement for routers running PIM Sparse
        Mode and implementing the PIM MIB."
```

```
    MODULE -- this module
```

```
        MANDATORY-GROUPS { pimV2MIBGroup }
```

```
    GROUP      pimV2CandidateRPMIBGroup
```

```
    DESCRIPTION
```

```
        "This group is mandatory if the router is capable of being a
        Candidate RP."
```

```
    OBJECT      pimInterfaceStatus
```

```
    MIN-ACCESS read-only
```

```
    DESCRIPTION
```

```
        "Write access is not required."
```

```
    ::= { pimMIBCompliances 2 }
```

```
pimDenseV2MIBCompliance MODULE-COMPLIANCE
```

```
    STATUS current
```

```
    DESCRIPTION
```

```
        "The compliance statement for routers running PIM Dense Mode
        and implementing the PIM MIB."
```

```
    MODULE -- this module
```

Expires January 2001

[Page 23]

```
MANDATORY-GROUPS { pimDenseV2MIBGroup }

OBJECT      pimInterfaceStatus
MIN-ACCESS  read-only
DESCRIPTION
    "Write access is not required."

 ::= { pimMIBCompliances 3 }

-- units of conformance

pimNotificationGroup NOTIFICATION-GROUP
    NOTIFICATIONS { pimNeighborLoss }
    STATUS current
    DESCRIPTION
        "A collection of notifications for signaling important PIM
        events."
    ::= { pimMIBGroups 1 }

pimV2MIBGroup OBJECT-GROUP
    OBJECTS { pimJoinPruneInterval, pimNeighborIfIndex,
        pimNeighborUpTime, pimNeighborExpiryTime,
        pimInterfaceAddress, pimInterfaceNetMask,
        pimInterfaceDR, pimInterfaceHelloInterval,
        pimInterfaceStatus, pimInterfaceJoinPruneInterval,
        pimInterfaceCBSRPreference, pimInterfaceMode,
        pimRPSetHoldTime, pimRPSetExpiryTime,
        pimComponentBSRAddress, pimComponentBSRExpiryTime,
        pimComponentCRPHoldTime, pimComponentStatus,
        pimIpMRouteFlags, pimIpMRouteUpstreamAssertTimer
    }
    STATUS current
    DESCRIPTION
        "A collection of objects to support management of PIM Sparse
        Mode (version 2) routers."
    ::= { pimMIBGroups 2 }

pimDenseV2MIBGroup OBJECT-GROUP
    OBJECTS { pimNeighborIfIndex,
        pimNeighborUpTime, pimNeighborExpiryTime,
        pimInterfaceAddress, pimInterfaceNetMask,
        pimInterfaceDR, pimInterfaceHelloInterval,
        pimInterfaceStatus, pimInterfaceMode
    }
```

Expires January 2001

[Page 24]

STATUS current

DESCRIPTION

"A collection of objects to support management of PIM Dense Mode (version 2) routers."

::= { pimMIBGroups 5 }

pimV2CandidateRPMIBGroup OBJECT-GROUP

OBJECTS { pimCandidateRPAddress,  
pimCandidateRPRowStatus  
}

STATUS current

DESCRIPTION

"A collection of objects to support configuration of which groups a router is to advertise itself as a Candidate-RP."

::= { pimMIBGroups 3 }

pimV1MIBGroup OBJECT-GROUP

OBJECTS { pimJoinPruneInterval, pimNeighborIfIndex,  
pimNeighborUpTime, pimNeighborExpiryTime,  
pimNeighborMode,  
pimInterfaceAddress, pimInterfaceNetMask,  
pimInterfaceJoinPruneInterval, pimInterfaceStatus,  
pimInterfaceMode, pimInterfaceDR,  
pimInterfaceHelloInterval,  
pimRPState, pimRPStateTimer,  
pimRPLastChange, pimRPRowStatus  
}

STATUS deprecated

DESCRIPTION

"A collection of objects to support management of PIM (version 1) routers."

::= { pimMIBGroups 4 }

pimNextHopGroup OBJECT-GROUP

OBJECTS { pimIpMRouteNextHopPruneReason }

STATUS current

DESCRIPTION

"A collection of optional objects to provide per-next hop information for diagnostic purposes. Supporting this group may add a large number of instances to a tree walk, but the information in this group can be extremely useful in tracking down multicast connectivity problems."

::= { pimMIBGroups 6 }

pimAssertGroup OBJECT-GROUP

Expires January 2001

[Page 25]

```
OBJECTS { pimIpMRouteAssertMetric, pimIpMRouteAssertMetricPref,
           pimIpMRouteAssertRPTBit }
STATUS   current
DESCRIPTION
    "A collection of optional objects to provide extra
    information about the assert election process.  There is no
    protocol reason to keep such information, but some
    implementations may already keep this information and make
    it available.  These objects can also be very useful in
    debugging connectivity or duplicate packet problems,
    especially if the assert winner does not support the PIM and
    IP Multicast MIBs."
 ::= { pimMIBGroups 7 }
```

END



## **6. Security Considerations**

This MIB contains readable objects whose values provide information related to multicast routing, including information on the network topology. There are also a number of objects that have a MAX-ACCESS clause of read-write and/or read-create, which allow an administrator to configure PIM in the router.

While unauthorized access to the readable objects is relatively innocuous, unauthorized access to the write-able objects could cause a denial of service. Hence, the support for SET operations in a non-secure environment without proper protection can have a negative effect on network operations.

SNMPv1 by itself is such an insecure environment. Even if the network itself is secure (for example by using IPSec), even then, there is no control as to who on the secure network is allowed to access and SET (change/create/delete) the objects in this MIB.

It is recommended that the implementers consider the security features as provided by the SNMPv3 framework. Specifically, the use of the User-based Security Model [RFC 2274](#) [12] and the View-based Access Control Model [RFC 2275](#) [15] is recommended.

It is then a customer/user responsibility to ensure that the SNMP entity giving access to this MIB, is properly configured to give access to those objects only to those principals (users) that have legitimate rights to access them.

## **7. Intellectual Property Notice**

The IETF takes no position regarding the validity or scope of any intellectual property or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; neither does it represent that it has made any effort to identify any such rights. Information on the IETF's procedures with respect to rights in standards-track and standards-related documentation can be found in [BCP-11](#). Copies of claims of rights made available for publication and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the

Expires January 2001

[Page 27]

IETF Secretariat.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights which may cover technology that may be required to practice this standard. Please address the information to the IETF Executive Director.

## **8. Acknowledgements**

This MIB module has been updated based on feedback from the IETF's Inter-Domain Multicast Routing (IDMR) Working Group.

## **9. Authors' Addresses**

Keith McCloghrie  
cisco Systems, Inc.  
170 West Tasman Drive  
San Jose, CA 95134-1706  
Phone: +1 408 526 5260  
EMail: kzm@cisco.com

Dino Farinacci  
cisco Systems, Inc.  
170 West Tasman Drive  
San Jose, CA 95134-1706  
Phone: +1 408 526 4696  
EMail: dino@cisco.com

Dave Thaler  
Microsoft Corporation  
One Microsoft Way  
Redmond, WA 98052-6399  
Phone: +1 425 703 8835  
EMail: dthaler@microsoft.com

Bill Fenner  
AT&T Labs - Research  
75 Willow Rd.  
Menlo Park, CA 94025  
Phone: +1 650 330 7893

Expires January 2001

[Page 28]

Email: fenner@research.att.com

## **10. References**

- [1] Wijnen, B., Harrington, D., and R. Presuhn, "An Architecture for Describing SNMP Management Frameworks", [RFC 2571](#), Cabletron Systems, Inc., BMC Software, Inc., IBM T. J. Watson Research, April 1999.
- [2] Rose, M., and K. McCloghrie, "Structure and Identification of Management Information for TCP/IP-based Internets", [RFC 1155](#), STD 16, Performance Systems International, Hughes LAN Systems, May 1990.
- [3] Rose, M., and K. McCloghrie, "Concise MIB Definitions", [RFC 1212](#), STD 16, Performance Systems International, Hughes LAN Systems, March 1991.
- [4] M. Rose, "A Convention for Defining Traps for use with the SNMP", [RFC 1215](#), Performance Systems International, March 1991.
- [5] McCloghrie, K., Perkins, D., Schoenwaelder, J., Case, J., Rose, M., and S. Waldbusser, "Structure of Management Information Version 2 (SMIv2)", [RFC 2578](#), STD 58, Cisco Systems, SNMPinfo, TU Braunschweig, SNMP Research, First Virtual Holdings, International Network Services, April 1999.
- [6] McCloghrie, K., Perkins, D., Schoenwaelder, J., Case, J., Rose, M., and S. Waldbusser, "Textual Conventions for SMIv2", [RFC 2579](#), STD 58, Cisco Systems, SNMPinfo, TU Braunschweig, SNMP Research, First Virtual Holdings, International Network Services, April 1999.
- [7] McCloghrie, K., Perkins, D., Schoenwaelder, J., Case, J., Rose, M., and S. Waldbusser, "Conformance Statements for SMIv2", [RFC 2580](#), STD 58, Cisco Systems, SNMPinfo, TU Braunschweig, SNMP Research, First Virtual Holdings, International Network Services, April 1999.
- [8] Case, J., Fedor, M., Schoffstall, M., and J. Davin, "Simple Network Management Protocol", [RFC 1157](#), STD 15, SNMP Research, Performance Systems International, Performance Systems International, MIT Laboratory for Computer Science, May 1990.

Expires January 2001

[Page 29]

- [9] Case, J., McCloghrie, K., Rose, M., and S. Waldbusser, "Introduction to Community-based SNMPv2", [RFC 1901](#), SNMP Research, Inc., Cisco Systems, Inc., Dover Beach Consulting, Inc., International Network Services, January 1996.
- [10] Case, J., McCloghrie, K., Rose, M., and S. Waldbusser, "Transport Mappings for Version 2 of the Simple Network Management Protocol (SNMPv2)", [RFC 1906](#), SNMP Research, Inc., Cisco Systems, Inc., Dover Beach Consulting, Inc., International Network Services, January 1996.
- [11] Case, J., Harrington D., Presuhn R., and B. Wijnen, "Message Processing and Dispatching for the Simple Network Management Protocol (SNMP)", [RFC 2572](#), SNMP Research, Inc., Cabletron Systems, Inc., BMC Software, Inc., IBM T. J. Watson Research, April 1999.
- [12] Blumenthal, U., and B. Wijnen, "User-based Security Model (USM) for version 3 of the Simple Network Management Protocol (SNMPv3)", [RFC 2574](#), IBM T. J. Watson Research, April 1999.
- [13] Case, J., McCloghrie, K., Rose, M., and S. Waldbusser, "Protocol Operations for Version 2 of the Simple Network Management Protocol (SNMPv2)", [RFC 1905](#), SNMP Research, Inc., Cisco Systems, Inc., Dover Beach Consulting, Inc., International Network Services, January 1996.
- [14] Levi, D., Meyer, P., and B. Stewart, "SNMPv3 Applications", [RFC 2573](#), SNMP Research, Inc., Secure Computing Corporation, Cisco Systems, April 1999.
- [15] Wijnen, B., Presuhn, R., and K. McCloghrie, "View-based Access Control Model (VACM) for the Simple Network Management Protocol (SNMP)", [RFC 2575](#), IBM T. J. Watson Research, BMC Software, Inc., Cisco Systems, Inc., April 1999.
- [16] Deering, S., Estrin, D., Farinacci, D., Jacobson, V., Liu, G., and L. Wei, "Protocol Independent Multicast (PIM): Motivation and Architecture", January 1995.
- [17] Deering, S., Estrin, D., Farinacci, D., Jacobson, V., Liu, G., and L. Wei, "Protocol Independent Multicast (PIM): Protocol Specification", January 1995.
- [18] Estrin, D., Farinacci, D., Helmy, A., Thaler, D., Deering, S., Handley, M., Jacobson, V., Liu, C., Sharma, P., and L. Wei,

Expires January 2001

[Page 30]



"Protocol Independent Multicast - Sparse Mode (PIM-SM): Protocol Specification", [RFC 2362](#), June 1998.

- [19] Deering, S., Estrin, D., Farinacci, D., Jacobson, V., Helmy, A., and L. Wei, "Protocol Independent Multicast Version 2, Dense Mode Specification". Work in Progress, May 1997.

## **11. Full Copyright Statement**

Copyright (C) The Internet Society (2000). All Rights Reserved.

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this paragraph are included on all such copies and derivative works. However, this document itself may not be modified in any way, such as by removing the copyright notice or references to the Internet Society or other Internet organizations, except as needed for the purpose of developing Internet standards in which case the procedures for copyrights defined in the Internet Standards process must be followed, or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by the Internet Society or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

## Table of Contents

<a href="#">1</a> Abstract .....	<a href="#">2</a>
<a href="#">2</a> Introduction .....	<a href="#">2</a>
<a href="#">3</a> The SNMP Network Management Framework .....	<a href="#">2</a>
<a href="#">4</a> Overview .....	<a href="#">3</a>
<a href="#">5</a> Definitions .....	<a href="#">5</a>
<a href="#">6</a> Security Considerations .....	<a href="#">27</a>

Expires January 2001

[Page 31]

<a href="#">7</a>	Intellectual Property Notice .....	<a href="#">27</a>
<a href="#">8</a>	Acknowledgements .....	<a href="#">28</a>
<a href="#">9</a>	Authors' Addresses .....	<a href="#">28</a>
<a href="#">10</a>	References .....	<a href="#">29</a>
<a href="#">11</a>	Full Copyright Statement .....	<a href="#">31</a>