

INTERNET-DRAFT
[draft-ietf-idr-bgp-analysis-04.txt](#)
Category
Expires: March 2004

D. Meyer
K. Patel
Informational
September 2003

BGP-4 Protocol Analysis
<[draft-ietf-idr-bgp-analysis-04.txt](#)>

Status of this Document

This document is an Internet-Draft and is in full conformance with all provisions of [Section 10 of RFC2026](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/lid-abstracts.txt>

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

This document is a product of the IDR Working Group. Comments should be addressed to the authors, or the mailing list at idr@ietf.org.

Copyright Notice

Copyright (C) The Internet Society (2003). All Rights Reserved.

INTERNET-DRAFT

Expires: March 2004

September 2003

Abstract

The purpose of this report is to document how the requirements for advancing a routing protocol from Draft Standard to full Standard have been satisfied by Border Gateway Protocol version 4 (BGP-4).

This report satisfies the requirement for "the second report", as described in [Section 6.0 of RFC 1264](#) [[RFC1264](#)]. In order to fulfill the requirement, this report augments [RFC 1774](#) [[RFC1774](#)] and summarizes the key features of BGP protocol, and analyzes the protocol with respect to scaling and performance.

INTERNET-DRAFT

Expires: March 2004

September 2003

Table of Contents

1.	Introduction	4
2.	Key Features and algorithms of the BGP protocol.	4
2.1.	Key Features.	4
2.2.	BGP Algorithms.	5
2.3.	BGP Finite State Machine (FSM).	6
3.	BGP Capabilities	8
4.	BGP Persistent Peer Oscillations	8
5.	Implementation Guidelines.	8
6.	BGP Performance characteristics and Scalability.	9
6.1.	Link bandwidth and CPU utilization.	9
6.1.1.	CPU utilization.	10
6.1.2.	Memory requirements.	11
7.	BGP Policy Expressiveness and its Implications	12
7.1.	Existence of Unique Stable Routings	13
7.2.	Existence of Stable Routings.	15
8.	Applicability.	16
9.	Intellectual Property.	17
10.	Acknowledgments	17
11.	Security Considerations	18
12.	IANA Considerations	18
13.	References.	18
13.1.	Informative References	18
14.	Author's Addresses.	19
15.	Full Copyright Statement.	19

INTERNET-DRAFT

Expires: March 2004

September 2003

1. Introduction

BGP-4 is an inter-autonomous system routing protocol designed for TCP/IP internets. Version 1 of the BGP protocol was published in [RFC 1105](#) [RFC1105]. Since then BGP versions 2, 3, and 4 have been developed. Version 2 was documented in [RFC 1163](#) [RFC1163]. Version 3 is documented in [RFC 1267](#) [RFC1267]. Version 4 is documented in the [BGP4] (version 4 of BGP will hereafter be referred to as BGP). The changes between versions are explained in [Appendix A](#) of [BGP4]. Possible applications of BGP in the Internet are documented in [RFC 1772](#) [RFC1772].

BGP introduced support for Classless InterDomain Routing [CIDR]. Since earlier versions of BGP lacked the support for CIDR, they are considered obsolete and unusable in today's Internet.

2. Key Features and algorithms of the BGP protocol

This section summarizes the key features and algorithms of the BGP protocol. BGP is an inter-autonomous system routing protocol; it is designed to be used between multiple autonomous systems. BGP assumes that routing within an autonomous system is done by an intra-autonomous system routing protocol. BGP also assumes that data packets are routed from source towards destination independent of the source. BGP does not make any assumptions about intra-autonomous

system routing protocols deployed within the various autonomous systems. Specifically, BGP does not require all autonomous systems to run the same intra-autonomous system routing protocol (i.e., interior gateway protocol or IGP).

Finally, note that BGP is a real inter-autonomous system routing protocol, and as such it imposes no constraints on the underlying Internet topology. The information exchanged via BGP is sufficient to construct a graph of autonomous systems connectivity from which routing loops may be pruned and many routing policy decisions at the autonomous system level may be enforced.

[2.1.](#) Key Features

The key features of the protocol are the notion of path attributes and aggregation of network layer reachability information (NLRI).

Path attributes provide BGP with flexibility and extensibility. Path attributes are partitioned into well-known and optional. The provision for optional attributes allows experimentation that may involve a group of BGP routers without affecting the rest of the Internet. New optional attributes can be added to the protocol in much the same way that new options are added to, say, the Telnet protocol [[RFC854](#)].

One of the most important path attributes is the Autonomous System Path, or AS_PATH. AS reachability information traverses the Internet, this information is augmented by the list of autonomous systems that have been traversed thus far, forming the AS_PATH. The AS_PATH allows straightforward suppression of the looping of routing information. In addition, the AS_PATH serves as a powerful and versatile mechanism for policy-based routing.

BGP enhances the AS_PATH attribute to include sets of autonomous systems as well as lists via the AS_SET attribute. This extended format allows generated aggregate routes to carry path information from the more specific routes used to generate the aggregate. It should be noted however, that as of this writing, AS_SETs are rarely used in the Internet [[ROUTEVIEWS](#)].

[2.2.](#) BGP Algorithms

BGP uses an algorithm that is neither a pure distance vector algorithm or a pure link state algorithm. It is instead a modified distance vector algorithm referred to as a "Path Vector" algorithm that uses path information to avoid traditional distance vector problems. Each route within BGP pairs destination with path information to that destination. Path information (also known as AS_PATH information) is stored within the AS_PATH attribute in BGP. This allows BGP to reconstruct large portions of overall topology whenever required.

BGP uses an incremental update strategy in order to conserve bandwidth and processing power. That is, after initial exchange of complete routing information, a pair of BGP routers exchanges only changes to that information. Such an incremental update design requires reliable transport between a pair of BGP routers to function correctly. BGP solves this problem by using TCP for reliable transport.

In addition to incremental updates, BGP has added the concept of route aggregation so that information about groups of networks may be

aggregated and sent as a single Network Layer Reachability (NLRI).

Finally, note that BGP is a self-contained protocol. That is, BGP specifies how routing information is exchanged both between BGP speakers in different autonomous systems, and between BGP speakers within a single autonomous system.

[2.3.](#) BGP Finite State Machine (FSM)

The BGP FSM is a set of rules that are applied to a BGP speaker's set of configured peers for the BGP operation. A BGP implementation requires that a BGP speaker must connect to and listen on TCP port

179 for accepting any new BGP connections from its peers. The BGP Finite State Machine, or FSM, must be initiated and maintained for each new incoming and outgoing peer connections. However, in steady state operation, there will be only one BGP FSM per connection per peer.

There may exist a temporary period where in a BGP peer may have separate incoming and outgoing connections resulting into two different BGP FSMs for a peer (instead of one). This can be resolved following BGP connection collision rules defined in the [[BGP4](#)].

Following are different states of BGP FSM for its peers:

IDLE: State when BGP peer refuses any incoming connections.

CONNECT: State in which BGP peer is waiting for its TCP connection to be completed.

ACTIVE: State in which BGP peer is trying to acquire a peer by listening and accepting TCP connection.

OPENSENT: BGP peer is waiting for OPEN message from its peer.

OPENCONFIRM: BGP peer is waiting for KEEPALIVE or NOTIFICATION message from its peer.

ESTABLISHED: BGP peer connection is established and exchanges UPDATE, NOTIFICATION, and KEEPALIVE messages with its peer.

There are different BGP events that operate on above mentioned states

of BGP FSM for its peers. These BGP events are used for initiating and terminating peer connections. They also assist BGP in identifying any persistent peer connection oscillations and provide a mechanism for controlling them.

Following are different BGP events:

Manual Start: Manually start the peer connection.

Manual Stop: Manually stop the peer connection.

Automatic Start: Local system automatically starts the peer connection.

Manual start with passive TCP flag: Local system administrator manually starts the peer connection with peer in passive mode.

Automatic start with passive TCP flag: Local system administrator automatically starts the peer connection with peer in passive mode.

Automatic start with bgp_stop_flap option set: Local system administrator automatically starts the peer connection with peer oscillation damping enabled.

Automatic start with bgp_stop_flap option set and passive TCP establishment option set: Local system administrator automatically starts the peer connection with peer oscillation damping enabled and with peer in passive mode.

Automatic stop: Local system automatically stops the BGP connection.

Both, Manual Start and Manual Stop are mandatory BGP events. All other events are optional.

The BGP Capability mechanism [[RFC2842](#)] provides an easy and flexible way to introduce new features within the protocol. In particular, the BGP capability mechanism allows peers to negotiate various optional features during startup. This allows the base BGP protocol to contain only essential functionality, while at the same time providing a flexible mechanism for signaling protocol extensions.

4. BGP Persistent Peer Oscillations

Ideally, whenever a BGP speaker detects an error in any peer connection, it shuts down the peer and changes its FSM state to IDLE. BGP speaker requires a Start event to re-initiate its idle peer connection. If the error remains persistent and BGP speaker generates Start event automatically then it may result in persistent peer flapping. However, although peer oscillation is found to be wide-spread in BGP implementations, methods for preventing persistent peer oscillations are outside the scope of base BGP protocol specification.

5. Implementation Guidelines

A robust BGP implementation is work conserving. This means that if the number of prefixes is bound, arbitrarily high levels of route change can be tolerated with bounded impact on route convergence for occasionally changes in generally stable routes.

A BGP implementation under high load conditions should empty as much inbound routing updates from its input streams, processing only the most recent route if the route for a given NLRI changes multiple times. TCP also provides blocking on the writes on the sender side. A BGP implementation under load should expect blocks on write calls and send only the most recent routes when sockets unblock rather than sending entire history.

A robust implementation of BGP should have the following characteristics:

1. It is able to operate in almost arbitrarily high levels of route flap without losing peerings (failing to send keepalives) or losing other protocol adjacencies as a

result of BGP load.

2. Instability of a subset of routes should not affect the route advertisements or forwarding associated with the set of stable routes.
3. High levels of instability and peers of different CPU speed or load resulting in faster or slower processing of routes should not cause instability and should have a bounded impact on the convergence time for generally stable routes.

Numerous robust BGP implementations exist. Producing a robust implementation is not a trivial matter but clearly achievable.

6. BGP Performance characteristics and Scalability

In this section, we provide "order of magnitude" answers to the questions of how much link bandwidth, router memory and router CPU cycles the BGP protocol will consume under normal conditions. In particular, we will address the scalability of BGP and its limitations.

6.1. Link bandwidth and CPU utilization

Immediately after the initial BGP connection setup, BGP peers exchange complete set of routing information. If we denote the total number of routes in the Internet by N , the mean AS distance of the Internet by M (distance at the level of an autonomous system, expressed in terms of the number of autonomous systems), the total number of unique AS paths by A , and assume that the networks are uniformly distributed among the autonomous systems, then the worst case amount of bandwidth consumed during the initial exchange between a pair of BGP speakers is

$$BW = O(N + (M * A))$$

The following table illustrates the typical amount of bandwidth consumed during the initial exchange between a pair of BGP speakers based on the above assumptions (ignoring bandwidth consumed by the

BGP Header). For purposes of the estimates here, we will calculate $BW = 4 * (N + (M * A))$.

INTERNET-DRAFT

Expires: March 2004

September 2003

# NLRI	Mean AS Distance	# AS's	Bandwidth (MR)
-----	-----	-----	-----
40,000	15	400	184,000 bytes
100,000	10	10,000	800,000 bytes
120,000	10	15,000	1,080,000 bytes
140,000	15	20,000	1,760,000 bytes

[note that most of this bandwidth is consumed by the NLRI exchange]

BGP was created specifically to reduce the size of the set of NLRI entries which have to be carried and exchanged by border routers. The aggregation scheme, defined in [RFC 1519](#) [[RFC1519](#)], describes the provider-based aggregation scheme in use in today's Internet.

Due to the advantages of advertising a few large aggregate blocks instead of many smaller class-based individual networks, it is difficult to estimate the actual reduction in bandwidth and processing that BGP has provided over BGP-3. If we simply enumerate all aggregate blocks into their individual class-based networks, we would not take into account "dead" space that has been reserved for future expansion. The best metric for determining the success of BGP's aggregation is to sample the number NLRI entries in the globally connected Internet today and compare it to projected growth rates before BGP was deployed.

At the time of this writing, the full set of exterior routes carried by BGP is approximately 120,000 network entries [[ROUTEVIEWS](#)].

[6.1.1](#). CPU utilization

An important and fundamental feature of BGP is that BGP's CPU utilization depends only on the stability of the Internet. If the Internet is stable, then the only link bandwidth and router CPU cycles consumed by BGP are due to the exchange of the BGP KEEPALIVE messages. The KEEPALIVE messages are exchanged only between peers.

The suggested frequency of the exchange is 30 seconds. The KEEPALIVE messages are quite short (19 octets), and require virtually no processing. As a result, the bandwidth consumed by the KEEPALIVE messages is about 5 bits/sec. Operational experience confirms that the overhead (in terms of bandwidth and CPU) associated with the KEEPALIVE messages should be viewed as negligible.

During periods of Internet instability, changes to the reachability information are passed between routers in UPDATE messages. The

greatest overhead per UPDATE message occurs when each UPDATE message contains only a single network. It should be pointed out that in practice routing changes exhibit strong locality with respect to the AS path. That is, routes that change are likely to have common AS path. In this case, multiple networks can be grouped into a single UPDATE message, thus significantly reducing the amount of bandwidth required (see also [Appendix F.1](#) of [[BGP4](#)]).

Since in the steady state the link bandwidth and router CPU cycles consumed by the BGP protocol are dependent only on the stability of the Internet, it follows that BGP should have no scaling problems in the areas of link bandwidth and router CPU utilization. This assumes that as the Internet grows, the overall stability of the inter-AS connectivity of the Internet can be controlled. In particular, while the size of the IPv4 Internet routing table is bounded by $O(232 * M)$, (where M is a slow-moving function describing the AS interconnectivity of the network), no such bound can be formulated for the dynamic properties (i.e., stability) of BGP. Although, the dynamic properties of the network cannot be quantitatively bounded, they can be controlled within BGP. Beyond certain changes in the network, BGP can start to suppress such changes using BGP Route Flap Damping [[RFC2439](#)], pacing of its route updates, or BGP would be unable to keep up with the changes and force suppression of multiple changes over very short periods by causing the BGP peer socket to block on the sender.

[6.1.2](#). Memory requirements

To quantify the worst case memory requirements for BGP, we denote the

total number of networks in the Internet by N, the mean AS distance of the Internet by M (distance at the level of an autonomous system, expressed in terms of the number of autonomous systems), the total number of unique AS paths as A. Then the worst case memory requirements (MR) can be expressed as

$$MR = O(N + (M * A))$$

Since a mean AS distance M is a slow moving function of the interconnectivity ("meshiness") of the Internet, for all practical purposes the worst case router memory requirements are on the order of the total number of networks in the Internet times the number of peers the local system is peering with. We expect that the total number of networks in the Internet will grow much faster than the

average number of peers per router. As a result, BGP's memory scaling properties are linearly related to the total number of networks in the Internet.

The following table illustrates typical memory requirements of a router running BGP. We denote average number of routes advertised by each peer as N, the total number of unique AS paths as A, the mean AS distance of the Internet as M (distance at the level of an autonomous system, expressed in terms of the number of autonomous systems), number of bytes required to store a route as R, and number of bytes required to store one AS in an AS path as P. It is assumed that each network is encoded as four bytes, each AS is encoded as two bytes, and each networks is reachable via some fraction of all of the peers (# BGP peers/per net). For purposes of the estimates here, we will calculate $MR = ((N * R) + (M * A) * P)$

# Networks	Mean AS Distance	# AS's	# BGP peers/per net	Memory Req (MR)
100,000	20	3,000	20	1,040,000
100,000	20	15,000	20	1,040,000
120,000	10	15,000	100	75,000,000
140,000	15	20,000	100	116,000,000

In analyzing BGP's memory requirements, we focus on the size of the forwarding table (and ignoring implementation details). In particular, we derive upper bounds for the size of the forwarding table. For example, at the time of this writing, the forwarding tables of a typical backbone router carry on the order of 120,000 entries. Given this number, one might ask whether it would be possible to have a functional router with a table that will have 1,000,000 entries. Clearly the answer to this question is more related to how BGP is implemented. A robust BGP implementation with a reasonable CPU and memory should not have issues scaling to such limits.

7. BGP Policy Expressiveness and its Implications

BGP is unique among deployed IP routing protocols in that routing is determined using semantically rich routing policies. Although routing policies are usually the first thing that comes to a network operator's mind concerning BGP, it is important to note that the languages and techniques for specifying BGP routing policies are not actually a part of the protocol specification (see [RFC 2622](#) [[RFC2622](#)]

for an example of such a policy language). In addition, the BGP specification contains few restrictions, either explicitly or implicitly, on routing policy languages. These languages have typically been developed by vendors and have evolved through interactions with network engineers in an environment lacking vendor-independent standards.

The complexity of typical BGP configurations, at least in provider networks, has been steadily increasing. Router vendors typically provided hundreds of special commands for use in the configuration of BGP, and this command set is continually expanding. For example, BGP communities [[RFC1997](#)] allow policy writers to selectively attach tags to routes and use these to signal policy information to other BGP-speaking routers. Many providers allow customers, and sometimes peers, to send communities that determine the scope and preference of their routes. These developments have more and more given the task of writing BGP configurations aspects associated with open-ended programming. This has allowed network operators to encode complex


policies in order to address many unforeseen situations, and has opened the door for a great deal of creativity and experimentation in routing policies. This policy flexibility is one of the main reasons why BGP is so well suited to the commercial environment of the current Internet.

However, this rich policy expressiveness has come with a cost that is often not recognized. In particular, it is possible to construct locally defined routing policies that can lead to unexpected global routing anomalies such as (unintended) nondeterminism and to protocol divergence. If the interacting policies causing such anomalies are defined in different autonomous systems, then these problems can be very difficult to debug and correct. In the following sections, we describe two such cases relating to the existence (or lack thereof) of stable routings.

7.1. Existence of Unique Stable Routings


One can easily construct sets of policies for which BGP can not guarantee that stable routings are unique. This can be illustrated by the following simple example. Consider the example of four Autonomous Systems, AS1, AS2, AS3, and AS4. AS1 and AS2 are peers, and they provide transit for AS3 and AS4 respectively, Suppose further that AS3 provides transit for AS4 (in this case AS3 is a customer of AS1, and AS4 is a multihomed customer of both AS3 and AS2). AS4 may want to use the link to AS3 as a "backup" link, and sends AS3 a community value that AS3 has configured to lower the

preference of AS4's routes to a level below that of its upstream provider, AS1. The intended "backup routing" to AS4 is illustrated here:



That is, the AS3-AS4 link is intended to be used only when the AS2-AS4 link is down (for outbound traffic, AS4 simply gives routes from AS2 a higher local preference). This is a common scenario in today's Internet. But note that this configuration has another

stable solution:



In this case, AS3 does not translate the "depref my route" community received from AS4 into a "depref my route" community for AS1, and so if AS1 hears the route to AS4 that transits AS3 it will prefer that route (since AS3 is a customer). This state could be reached, for example, by starting in the "correct" backup routing shown first, bringing down the AS2-AS4 BGP session, and then bringing it back up. In general, BGP has no way to prefer the "intended" solution over the anomalous one, and which is picked will depend on the unpredictable order of BGP messages.

While this example is relatively simple, many operators may fail to recognize that the true source of the problem is that the BGP policies of ASes can interact in unexpected ways, and that these interactions can result in multiple stable routings. One can imagine that the interactions could be much more complex in the real Internet. We suspect that such anomalies will only become more common as BGP continues to evolve with richer policy expressiveness. For example, extended communities provide an even more flexible means of signaling information within and between autonomous systems than is possible with [RFC 1997](#) communities. At the same time, applications of communities by network operators are evolving to address complex issues of inter-domain traffic engineering.

[7.2.](#) Existence of Stable Routings

One can also construct a set of policies for which BGP can not guarantee that a stable routing exists (or worse, that a stable routing will ever be found). For example, [RFC 3345](#) [[RFC3345](#)] documents several scenarios that lead to route oscillations associated with the use of the Multi-Exit Discriminator or MED,

attribute. Route oscillation will happen in BGP when a set of policies has no solution. That is, when there is no stable routing that satisfies the constraints imposed by policy, then BGP has no choice but to keep trying. In addition, BGP configurations can have a stable routing, yet the protocol may not be able to find it; BGP can "get trapped" down a blind alley that has no solution.

Protocol divergence is not, however, a problem associated solely with use of the MED attribute. This potential exists in BGP even without the use of the MED attribute. Hence, like the unintended nondeterminism described in the previous section, this type of protocol divergence is an unintended consequence of the unconstrained nature of BGP policy languages.

8. Applicability

In this section we answer the question of which environments is BGP well suited, and for which environments it is not suitable. This question is partially answered in [Section 2](#) of BGP [[BGP4](#)], which states:

"To characterize the set of policy decisions that can be enforced using BGP, one must focus on the rule that an AS advertises to its neighbor ASs only those routes that it itself uses. This rule reflects the "hop-by-hop" routing paradigm generally used throughout the current Internet. Note that some policies cannot be supported by the "hop-by-hop" routing paradigm and thus require techniques such as source routing to enforce. For example, BGP does not enable one AS to send traffic to a neighbor AS intending that the traffic take a different route from that taken by traffic originating in the neighbor AS. On the other hand, BGP can support any policy conforming to the "hop-by-hop" routing paradigm. Since the current Internet uses only the "hop-by-hop" routing paradigm and since BGP can support any policy that conforms to that paradigm, BGP is highly applicable as an inter-AS routing protocol for the current Internet."

One of the important points here is that the BGP protocol contains only the functionality that is essential, while at the same time providing a flexible mechanism within the protocol that allow us to extend its functionality. For example, BGP capabilities provide an easy and flexible way to introduce new features within the protocol. Finally, since BGP was designed with flexibility and extensibility in

mind, new and/or evolving requirements can be addressed via existing

INTERNET-DRAFT

Expires: March 2004

September 2003

mechanisms.

To summarize, BGP is well suitable as an inter-autonomous system routing protocol for the IPv4 Internet that is based on IP [[RFC791](#)] as the Internet Protocol and "hop-by-hop" routing paradigm.

[9](#). Intellectual Property

The IETF takes no position regarding the validity or scope of any intellectual property or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; neither does it represent that it has made any effort to identify any such rights. Information on the IETF's procedures with respect to rights in standards-track and standards-related documentation can be found in [BCP-11](#). Copies of claims of rights made available for publication and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementors or users of this specification can be obtained from the IETF Secretariat.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights which may cover technology that may be required to practice this standard. Please address the information to the IETF Executive Director.

[10](#). Acknowledgments

We would like to thank Paul Traina for authoring previous versions of this document. Tim Griffin, Randy Presuhn, Curtis Villamizar and Atanu Ghosh also provided many insightful comments on earlier versions of this document.

INTERNET-DRAFT

Expires: March 2004

September 2003

[11.](#) Security Considerations

This document presents an analysis of the BGP protocol and as such presents no new security implications for BGP.

[12.](#) IANA Considerations

This document presents an analysis of the BGP protocol and hence presents no new IANA considerations.

[13.](#) References

[13.1.](#) Informative References

- [BGP4] Rekhter, Y., T. Li., and S. Hares, Editors, "A Border Gateway Protocol 4 (BGP-4)", [draft-ietf-idr-bgp4-20.txt](#). Work in progress.
- [RFC791] "INTERNET PROTOCOL", DARPA INTERNET PROGRAM PROTOCOL SPECIFICATION, [RFC 791](#), September, 1981.
- [RFC854] Postel, J. and J. Reynolds, "TELNET PROTOCOL SPECIFICATION", [RFC 854](#), May, 1983.
- [RFC1105] Lougheed, K., and Y. Rekhter, "Border Gateway

Protocol BGP", [RFC 1105](#), June 1989.

[RFC1163] Lougheed, K., and Rekhter, Y, "Border Gateway Protocol BGP", [RFC 1105](#), June 1990.

[RFC1264] Hinden, R., "Internet Routing Protocol Standardization Criteria", [RFC 1264](#), October 1991.

[RFC1267] Lougheed, K., and Rekhter, Y, "Border Gateway Protocol 3 (BGP-3)", [RFC 1105](#), October 1991.

[RFC1519] Fuller, V., Li. T., Yu J., and K. Varadhan, "Classless Inter-Domain Routing (CIDR): an Address Assignment and Aggregation Strategy", [RFC 1519](#), September 1993.

Meyer and Patel

[Section 13.1](#). [Page 18]

INTERNET-DRAFT

Expires: March 2004

September 2003

[RFC1771] Rekhter, Y., and T. Li, "A Border Gateway Protocol 4 (BGP-4)", [RFC 1771](#), March 1995.

[RFC1772] Rekhter, Y., and P. Gross, Editors, "Application of the Border Gateway Protocol in the Internet", [RFC 1772](#), March 1995.

[RFC1997] Chandra. R, and T. Li, "BGP Communities Attribute", [RFC 1997](#), August, 1996.

[RFC2439] Villamizar, C., Chandra, R., and R. Govindan, "BGP Route Flap Damping", [RFC 2439](#), November 1998.

[RFC2622] Alaettinoglu, C., et. al., "Routing Policy Specification Language (RPSL)" [RFC 2622](#), May, 1998.

[RFC2842] Chandra, R. and J. Scudder, "Capabilities Advertisement with BGP-4", [RFC 2842](#), May 2000.

[RFC3345] McPherson, D., Gill, V., Walton, D., and A. Retana, "Border Gateway Protocol (BGP) Persistent Route Oscillation Condition", [RFC 3345](#), August, 2002.

[ROUTEVIEWS] Meyer, D., "The Route Views Project",
<http://www.routeviews.org>

14. Author's Addresses

David Meyer
Email: dmm@1-4-5.net

Keyur Patel
Cisco Systems
Email: keyupate@cisco.com

15. Full Copyright Statement

Copyright (C) The Internet Society (2003). All Rights Reserved.

Meyer and Patel

[Section 15.](#) [Page 19]

INTERNET-DRAFT

Expires: March 2004

September 2003

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this paragraph are included on all such copies and derivative works. However, this document itself may not be modified in any way, such as by removing the copyright notice or references to the Internet Society or other Internet organizations, except as needed for the purpose of developing Internet standards in which case the procedures for copyrights defined in the Internet Standards process must be followed, or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by the Internet Society or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and THE INTERNET SOCIETY AND THE INTERNET ENGINEERING

TASK FORCE DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.