

Interdomain Routing
Internet-Draft
Intended status: Standards Track
Expires: September 26, 2019

M. Jethanandani
VMware
K. Patel
Arrcus
S. Hares
Huawei
March 25, 2019

BGP YANG Model for Service Provider Networks
draft-ietf-idr-bgp-model-05

Abstract

This document defines a YANG data model for configuring and managing BGP, including protocol, policy, and operational aspects, such as RIB, based on data center, carrier and content provider operational requirements.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on September 26, 2019.

Copyright Notice

Copyright (c) 2019 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in [Section 4](#).e of

the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	2
1.1.	Goals and approach	3
1.2.	Note to RFC Editor	4
1.3.	Abbreviations	4
2.	Model overview	5
2.1.	BGP protocol configuration	6
2.2.	Policy configuration overview	9
2.3.	BGP RIB overview	10
2.3.1.	Local Routing	12
2.3.2.	Pre updates per-neighbor	12
2.3.3.	Post updates per-neighbor	12
2.3.4.	Pre route advertisements per-neighbor	12
2.3.5.	Post route advertisements per-neighbor	12
3.	Relation to other YANG data models	13
4.	Security Considerations	13
5.	IANA Considerations	13
5.1.	URI Registration	13
5.2.	YANG Module Name Registration	14
6.	YANG modules	14
7.	Structure of the YANG modules	15
7.1.	Main module and submodules for base items	15
7.2.	BGP types	55
7.3.	BGP policy data	66
7.4.	RIB modules	77
8.	Examples	126
8.1.	Creating BGP Instance	126
8.2.	Neighbor Address Family Configuration	127
9.	Contributors	129
10.	Acknowledgements	129
11.	References	129
11.1.	Normative references	129
11.2.	Informative references	131
	Authors' Addresses	131

[1.](#) Introduction

This document describes a YANG [\[RFC7950\]](#) data model for the BGP [\[RFC4271\]](#) protocol, including various protocol extensions, policy configuration, as well as defining key operational state data, including Routing Information Base (RIB). The model is intended to be vendor-neutral, in order to allow operators to manage BGP configuration in heterogeneous environments with routers supplied by multiple vendors. The model is also intended to be readily mapped to

existing implementations to facilitate support from as large a set of routing hardware and software vendors as possible.

1.1. Goals and approach

The model covers the base BGP features that are deployed across major implementations and the common BGP configurations in use across a number of operator network deployments. In particular, this model attempts to cover BGP features defined in BGP [[RFC4271](#)], BGP Communities Attribute [[RFC1997](#)], BGP Route Reflection [[RFC4456](#)], Multiprotocol Extensions for BGP-4 [[RFC4760](#)], Autonomous System Confederations for BGP [[RFC5065](#)], BGP Route Flap Damping [[RFC2439](#)], Graceful Restart Mechanism for BGP [[RFC4724](#)], and BGP Prefix Origin Validation [[RFC6811](#)].

Along with configuration of base BGP features, this model also addresses policy configuration, by providing "hooks" for applying policies, and also defining BGP-specific policy features. The BGP policy features are intended to be used with the general routing policy model defined in A YANG Data Model for Routing Policy Management [[I-D.ietf-rtgwg-policy-model](#)]. The model conforms to the NMDA [[RFC8342](#)] architecture and has support for configuring Bidirectional Forward Detection (BFD) [[RFC5880](#)] for fast next hop liveness check.

For the base BGP features, the focus of the model described in this document is on providing configuration and operational state information relating to:

- o The global BGP instance, and neighbors whose configuration is specified individually, or templated with the use of peer-groups.
- o The address families that are supported by peers, and the global configuration which relates to them.
- o The policy configuration "hooks" and BGP-specific policy features that relate to a neighbor - controlling the import and export of NLRIs.
- o RIB contents.

As mentioned earlier, any configuration items that are deemed to be widely available in existing major BGP implementations are included in the model. Additional, more esoteric, configuration items that are not commonly used, or only available from a single implementation, are omitted from the model with an expectation that they will be available in companion modules that augment or extend

the current model. This allows clarity in identifying data that is part of the vendor-neutral base model.

Where possible, naming in the model follows conventions used in available standards documents, and otherwise tries to be self-explanatory with sufficient descriptions of the intended behavior. Similarly, configuration data value constraints and default values, where used, are based on recommendations in current standards documentation, or those commonly used in multiple implementations. Since implementations can vary widely in this respect, this version of the model specifies only a limited set of defaults and ranges with the expectation of being more prescriptive in future versions based on actual operator use.

1.2. Note to RFC Editor

This document uses several placeholder values throughout the document. Please replace them as follows and remove this note before publication.

RFC XXXX, where XXXX is the number assigned to this document at the time of publication.

2019-03-21 with the actual date of the publication of this document.

RFC ZZZZ, where ZZZZ is the number assigned to A YANG Data Model for Routing Policy Management [[I-D.ietf-rtgwg-policy-model](#)].

RFC AAAA, where AAAA is the number assigned to BGP Monitoring Protocol [[I-D.ietf-grow-bmp](#)].

RFC BBBB, where BBBB is the number assigned to YANG Data Model for Bidirectional Forward Detection [[I-D.ietf-bfd-yang](#)].

1.3. Abbreviations

+-----+-----+	
Abbreviation	
+-----+-----+	
AFI	Address Family Identifier
BFD	Bidirectional Forward Detection
NLRI	Network Layer Reachability Information
NMDA	Network Management Datastore Architecture
RIB	Routing Information Base
SAFI	Subsequent Address Family Identifier
+-----+-----+	

2. Model overview

The BGP model is defined across several YANG modules and submodules, but at a high level is organized into six elements:

- o base protocol configuration -- configuration affecting BGP protocol-related operations, defined at various levels of hierarchy.
- o multiprotocol configuration -- configuration affecting individual address-families within BGP Multiprotocol Extensions for BGP-4 [[RFC4760](#)].
- o neighbor configuration -- configuration affecting an individual neighbor within BGP.
- o neighbor multiprotocol configuration -- configuration affecting individual address-families for a neighbor within BGP.
- o policy configuration -- hooks for application of the policies defined in A YANG Data Model for Routing Policy Management [[I-D.ietf-rtgwg-policy-model](#)] that act on routes sent (received) to (from) peers or other routing protocols and BGP-specific policy features.
- o operational state -- variables used for monitoring and management of BGP operations.

These modules also make use of standard Internet types, such as IP addresses and prefixes, autonomous system numbers, etc., defined in Common YANG Data Types [[RFC6991](#)].

2.1. BGP protocol configuration

The BGP protocol configuration model is organized hierarchically, much like the majority of router implementations. That is, configuration items can be specified at multiple levels, as shown below.

```
module: ietf-bgp
  augment /rt:routing/rt:control-plane-protocols
    /rt:control-plane-protocol:
      +--rw bgp
        +--rw global!
          |  +--rw as                               inet:as-number
          |  +--rw router-id?                       yang:dotted-quad
          |  +--ro total-paths?                     uint32
          |  +--ro total-prefixes?                  uint32
          |  +--rw default-route-distance
          |  |    ...
          |  +--rw confederation
          |  |    ...
          |  +--rw graceful-restart
          |  |    ...
          |  +--rw use-multiple-paths
          |  |    ...
          |  +--rw route-selection-options
          |  |    ...
          |  +--rw afi-safis
          |  |    ...
          |  +--rw apply-policy
          |  |    ...
          |  ...
        +--rw neighbors
          |  +--rw neighbor* [neighbor-address]
          |  |    ...
          |  ...
        +--rw peer-groups
          |  +--rw peer-group* [peer-group-name]
          |  |    ...
          |  ...
        +--rw interfaces
          |  +--rw interface* [name]
          |  |    ...
          |  ...
        +--ro rib
          +--ro attr-sets
          |  ...
          +--ro communities
          |  ...
          +--ro ext-communities
          |  ...
          +--ro afi-safis
          |  ...
          ...
```

Users may specify configuration at a higher level and have it apply to all lower-level items, or provide overriding configuration at a lower level of the hierarchy. Overriding configuration items are optional, with neighbor specific configuration being the most specific or lowest level, followed by peer-group, and finally global.

Global configuration options reflect a subset of the peer-group or neighbor specific configuration options which are relevant to the entire BGP instance.

The model makes the simplifying assumption that most of the configuration items are available at all levels of the hierarchy. That is, very little configuration is specific to a particular level in the hierarchy, other than obvious items such as "group-name" only being available for the peer group-level config. A notable exception is for sub-address family configuration where some items are only applicable for a given AFI-SAFI combination.

In order to allow common configuration to be applied to a set of neighbors, all neighbor configuration options are available within a peer-group. A neighbor is associated to a particular peer-group through the use of a peer-group leaf (which provides a reference to a configured item in the peer-group list).

Address-family configuration is made available in multiple points within the model - primarily within the global container, where instance-wide configuration can be set (for example, global protocol parameters, the BGP best path route selection options, or global policies relating to the address-family); and on a per-neighbor or per-peer-group basis, where address-families can be enabled or disabled, and policy associated with the parent entity applied. Within the afi-safi container, generic configuration that applies to all address-families (e.g., whether the AFI-SAFI is enabled) is presented at the top-level, with address-family specific containers made available for options relating to only that AFI-SAFI. Within the current revision of the model a generic set of address-families, and common configuration and state options are included - further work is expected to add additional parameters to this area of the model.

The following address-families are currently supported by the model:


```

+--rw bgp
  +--rw global!
    +--rw afi-safis
      +--rw afi-safi* [afi-safi-name]
        +--rw afi-safi-name          identityref
        |
        +--rw ipv4-unicast
        |   ...
        +--rw ipv6-unicast
        |   ...
        +--rw ipv4-labeled-unicast
        |   ...
        +--rw ipv6-labeled-unicast
        |   ...
        +--rw l3vpn-ipv4-unicast
        |   ...
        +--rw l3vpn-ipv6-unicast
        |   ...
        +--rw l3vpn-ipv4-multicast
        |   ...
        +--rw l3vpn-ipv6-multicast
        |   ...
        +--rw l2vpn-vpls
        |   ...
        +--rw l2vpn-evpn
        |   ...

```

2.2. Policy configuration overview

The BGP policy configuration model augments the generic YANG routing policy model described in A YANG Data Model for Routing Policy Management [[I-D.ietf-rtgwg-policy-model](#)], which represents a condition-action policy framework for routing. This model adds BGP-specific conditions (e.g., matching on the community attribute), and actions (e.g., setting local preference) to the generic policy framework.

Policies that are defined in the routing-policy model are referenced in multiple places within the model:

- o within the global instance, where a policy applies to all address-families for all peers.
- o on a global AFI-SAFI basis, where policies apply to all peers for a particular address-family.

- o on a per-peer-group or per-neighbor basis - where the policy applies to all address-families for the particular group or neighbor.
- o on a per-afi-safi basis within a neighbor or peer-group context, where the policy is specific to the AFI-SAFI for a a specific neighbor or group.

```

module: ietf-bgp-policy
  augment /rpol:routing-policy/rpol:defined-sets:
    +--rw bgp-defined-sets
    ...
  augment /rpol:routing-policy/rpol:policy-definitions
    /rpol:policy-definition/rpol:statements/rpol:statement
    /rpol:conditions:
    +--rw bgp-conditions
    ...
  augment /rpol:routing-policy/rpol:policy-definitions
    /rpol:policy-definition/rpol:statements/rpol:statement
    /rpol:actions:
    +--rw bgp-actions
    ...

```

2.3. BGP RIB overview

The RIB data model represents the BGP RIB contents. The model supports five logical RIBs per address family.

A abridged version of the tree shows the RIB portion of the tree diagram.

```

module: ietf-bgp
  augment /rt:routing/rt:control-plane-protocols
    /rt:control-plane-protocol:
    +--rw bgp
      +--ro rib
        +--ro afi-safis
          +--ro afi-safi* [afi-safi-name]
            +--ro afi-safi-name      identityref
            +--ro ipv4-unicast
              | +--ro loc-rib
              | | +--ro routes
              | |   +--ro route* [prefix origin path-id]
              | |   ...
              | +--ro neighbors
              |   +--ro neighbor* [neighbor-address]

```



```

|         +--ro neighbor-address    inet:ip-address
|         +--ro adj-rib-in-pre
|         |     ...
|         +--ro adj-rib-in-post
|         |     ...
|         +--ro adj-rib-out-pre
|         |     ...
|         +--ro adj-rib-out-post
|         |     ...
+--ro ipv6-unicast
|   +--ro loc-rib
|   |   +--ro routes
|   |   |   +--ro route* [prefix origin path-id]
|   |   |   |   ...
|   +--ro neighbors
|   |   +--ro neighbor* [neighbor-address]
|   |   |   +--ro neighbor-address    inet:ip-address
|   |   |   +--ro adj-rib-in-pre
|   |   |   |   ...
|   |   |   +--ro adj-rib-in-post
|   |   |   |   ...
|   |   |   +--ro adj-rib-out-pre
|   |   |   |   ...
|   |   |   +--ro adj-rib-out-post
|   |   |   |   ...
+--ro ipv4-srte-policy
|   +--ro loc-rib
|   |   +--ro routes
|   |   |   +--ro route* [path-id endpoint color]
|   |   |   |   ...
|   +--ro neighbors
|   |   +--ro neighbor* [neighbor-address]
|   |   |   +--ro neighbor-address    inet:ip-address
|   |   |   +--ro adj-rib-in-pre
|   |   |   |   ...
|   |   |   +--ro adj-rib-in-post
|   |   |   |   ...
|   |   |   +--ro adj-rib-out-pre
|   |   |   |   ...
|   |   |   +--ro adj-rib-out-post
|   |   |   |   ...
+--ro ipv6-srte-policy
|   +--ro loc-rib
|   |   +--ro routes
|   |   |   +--ro route* [path-id endpoint color]
|   |   |   |   ...
|   +--ro neighbors
|   |   +--ro neighbor* [neighbor-address]

```



```
+--ro neighbor-address    inet:ip-address
+--ro adj-rib-in-pre
|   ...
+--ro adj-rib-in-post
|   ...
+--ro adj-rib-out-pre
|   ...
+--ro adj-rib-out-post
    ...
```

2.3.1. Local Routing

The loc-rib is the main BGP routing table for the local routing instance, containing best-path selections for each prefix. The loc-rib table may contain multiple routes for a given prefix, with an attribute to indicate which was selected as the best path. Note that multiple paths may be used or advertised even if only one path is marked as best, e.g., when using BGP add-paths. An implementation may choose to mark multiple paths in the RIB as best path by setting the flag to true for multiple entries.

2.3.2. Pre updates per-neighbor

The adj-rib-in-pre table is a per-neighbor table containing the NLRI updates received from the neighbor before any local input policy rules or filters have been applied. This can be considered the 'raw' updates from a given neighbor.

2.3.3. Post updates per-neighbor

The adj-rib-in-post table is a per-neighbor table containing the routes received from the neighbor that are eligible for best-path selection after local input policy rules have been applied.

2.3.4. Pre route advertisements per-neighbor

The adj-rib-out-pre table is a per-neighbor table containing routes eligible for sending (advertising) to the neighbor before output policy rules have been applied.

2.3.5. Post route advertisements per-neighbor

The adj-rib-out-post table is a per-neighbor table containing routes eligible for sending (advertising) to the neighbor after output policy rules have been applied

3. Relation to other YANG data models

The BGP model augments the Routing Management model A YANG Data Model for Routing Management [[RFC8349](#)] which defines the notion of routing, routing protocols, routing instances, or VRFs, and RIBs.

4. Security Considerations

The YANG module specified in this document defines a schema for data that is designed to be accessed via network management protocols such as NETCONF [[RFC6241](#)] or RESTCONF [[RFC8040](#)]. The lowest NETCONF layer is the secure transport layer, and the mandatory-to-implement secure transport is Secure Shell (SSH) [[RFC6242](#)]. The lowest RESTCONF layer is HTTPS, and the mandatory-to-implement secure transport is TLS [[RFC8446](#)]. The NETCONF Access Control Model (NACM) [[RFC8341](#)] provides the means to restrict access for particular NETCONF or RESTCONF users to a preconfigured subset of all available NETCONF or RESTCONF protocol operations and content.

There are a number of data nodes defined in this YANG module that are writable/creatable/deletable (i.e., config true, which is the default). These data nodes may be considered sensitive or vulnerable in some network environments. Write operations (e.g., edit-config) to these data nodes without proper protection can have a negative effect on network operations. These are the subtrees and data nodes and their sensitivity/vulnerability:

Some of the readable data nodes in this YANG module may be considered sensitive or vulnerable in some network environments. It is thus important to control read access (e.g., via get, get-config, or notification) to these data nodes. These are the subtrees and data nodes and their sensitivity/vulnerability:

Some of the RPC operations in this YANG module may be considered sensitive or vulnerable in some network environments. It is thus important to control access to these operations. These are the operations and their sensitivity/vulnerability:

5. IANA Considerations

This document registers three URIs and three YANG modules.

5.1. URI Registration

in the IETF XML registry [[RFC3688](#)] [[RFC3688](#)]. Following the format in [RFC 3688](#), the following registration is requested to be made:

URI: urn:ietf:params:xml:ns:yang:ietf-bgp
URI: urn:ietf:params:xml:ns:yang:ietf-bgp-policy
URI: urn:ietf:params:xml:ns:yang:ietf-bgp-types

Registrant Contact: The IESG. XML: N/A, the requested URI is an XML namespace.

5.2. YANG Module Name Registration

This document registers three YANG module in the YANG Module Names registry YANG [[RFC6020](#)].

name: ietf-bgp
namespace: urn:ietf:params:xml:ns:yang:ietf-bgp
prefix: bgp
reference: RFC XXXX

name: ietf-bgp-policy
namespace: urn:ietf:params:xml:ns:yang:ietf-bgp-policy
prefix: bp
reference: RFC XXXX

name: ietf-bgp-types
namespace: urn:ietf:params:xml:ns:yang:ietf-bgp-types
prefix: bt
reference: RFC XXXX

6. YANG modules

The modules comprising the BGP configuration and operational model are described by the YANG modules and submodules in the sections below.

The main module, `ietf-bgp.yang`, includes the following submodules:

- o `ietf-bgp-common` - defines the groupings that are common across more than one context (where contexts are neighbor, group, global)
- o `ietf-bgp-common-multiprotocol` - defines the groupings that are common across more than one context, and relate to multiprotocol BGP
- o `ietf-bgp-common-structure` - defines groupings that are shared by multiple contexts, but are used only to create structural elements, i.e., containers (leaf nodes are defined in separate groupings)

- o ietf-bgp-global - groupings with data specific to the global context
- o ietf-bgp-peer-group - groupings with data specific to the peer group context
- o ietf-bgp-neighbor - groupings with data specific to the neighbor context
- o ietf-bgp-rib - grouping for representing BGP RIB.

Additionally, modules include:

- o ietf-bgp-types - common type and identity definitions for BGP, including BGP policy
- o ietf-bgp-policy - BGP-specific policy data definitions for use with [[I-D.ietf-rtgwg-policy-model](#)] (described in more detail [Section 2.2](#))

7. Structure of the YANG modules

The YANG model can be subdivided between the main module for base items, types, policy data, and the RIB module.

7.1. Main module and submodules for base items

```
<CODE BEGINS> file "ietf-bgp@2019-03-21.yang"
module ietf-bgp {
  yang-version "1.1";
  namespace "urn:ietf:params:xml:ns:yang:ietf-bgp";
  prefix "bgp";

  /*
   * Import and Include
   */
  import ietf-routing {
    prefix "rt";
    reference
      "RFC 8349, A YANG Data Model for Routing Management
      (NMDA Version)";
  }

  import ietf-routing-policy {
    prefix rpol;
    reference
      "RFC ZZZZ, A YANG Data Model for Routing Policy Management";
  }
}
```



```
import ietf-interfaces {
  prefix if;
  reference
    "RFC 8343, A YANG Data Model for Interface Management.";
}

import ietf-bgp-types {
  prefix bt;
  reference
    "RFC XXXX, BGP YANG Model for Service Provider Network.";
}

import ietf-bfd-types {
  prefix bfd;
  reference
    "RFC BBBB, YANG Data Model for Bidirectional Forward Detection.";
}

include ietf-bgp-common;
include ietf-bgp-common-multiprotocol;
include ietf-bgp-common-structure;
include ietf-bgp-neighbor;
include ietf-bgp-global;
include ietf-bgp-peer-group;
include ietf-bgp-rib-types;
include ietf-bgp-rib;
include ietf-bgp-rib-ext;
include ietf-bgp-rib-shared-attributes;
include ietf-bgp-rib-attributes;
include ietf-bgp-rib-table-attributes;
include ietf-bgp-rib-tables;

organization
  "IETF IDR Working Group";

contact
  "WG Web:  <http://tools.ietf.org/wg/idr>
  WG List:  <idr@ietf.org>

  Authors: Mahesh Jethanandani (mjethanandani at gmail.com),
           Keyur Patel (keyur at arrcus.com),
           Susan Hares (shares at ndzh.com");

description
  "This module describes a YANG model for BGP protocol
  configuration. It is a limited subset of all of the configuration
  parameters available in the variety of vendor implementations,
  hence it is expected that it would be augmented with vendor-
```


specific configuration data as needed. Additional modules or submodules to handle other aspects of BGP configuration, including policy, VRFs, VPNs, and additional address families are also expected.

This model supports the following BGP configuration level hierarchy:

```
BGP
|
+--> [ global BGP configuration ]
    +--> AFI / SAFI global
    +--> peer group
        +--> [ peer group config ]
        +--> AFI / SAFI [ per-AFI overrides ]
    +--> neighbor
        +--> [ neighbor config ]
        +--> [ optional pointer to peer-group ]
        +--> AFI / SAFI [ per-AFI overrides ]";

revision "2019-03-21" {
  description
    "Initial Version";
  reference
    "RFC XXXX, BGP Model for Service Provider Network ";
}

/*
 * Identity
 */
identity bgp {
  base "rt:routing-protocol";
  description
    "BGP protocol.";
}

/*
 * Containers
 */
augment "/rt:routing/rt:control-plane-protocols/" +
  "rt:control-plane-protocol" {
  when "derived-from-or-self(rt:type, 'bgp')" {
    description
      "This augmentation is valid for a routing protocol
      instance of BGP.";
  }
  description
    "BGP protocol augmentation of ietf-routing module
```



```
    control-plane-protocol.";

container bgp {
  description
    "Top-level configuration for the BGP router";

  container global {
    presence "Enables global configuration of BGP";
    description
      "Global configuration for the BGP router";
    uses bgp-global-base;
    uses rpol:apply-policy-group;
  }

  container neighbors {
    description
      "Configuration for BGP neighbors";
    uses bgp-neighbor-list;
  }

  container peer-groups {
    description
      "Configuration for BGP peer-groups";
    uses bgp-peer-group-list;
  }

  container interfaces {
    list interface {
      key "name";

      leaf name {
        type if:interface-ref;
        description
          "Reference to the interface within the routing instance.";
      }

      container bfd {
        if-feature bt:bfd;
        uses bfd:client-cfg-parms;
        description
          "BFD client configuration.";
        reference
          "RFC BBBB - YANG Data Model for Bidirectional Forwarding
          Detection.";
      }
      description
        "List of interfaces within the routing instance.";
    }
  }
}
```



```
        description
            "Interface specific parameters.";
    }
    uses rib;
}
}
}
<CODE ENDS>
```

```
<CODE BEGINS> file "ietf-bgp-common@2019-03-21.yang"
submodule ietf-bgp-common {
    yang-version "1.1";
    belongs-to ietf-bgp {
        prefix "bgp";
    }

    import ietf-bgp-types {
        prefix bt;
    }
    import ietf-inet-types {
        prefix inet;
    }

    organization
        "IETF IDR Working Group";

    contact
        "WG Web:  <http://tools.ietf.org/wg/idr>
        WG List:  <idr@ietf.org>

        Authors: Mahesh Jethanandani (mjethanandani at gmail.com),
                 Keyur Patel (keyur at arrcus.com),
                 Susan Hares (shares at ndzh.com";

    description
        "This sub-module contains common groupings that are common across
        multiple contexts within the BGP module. That is to say that
        they may be application to a subset of global, peer-group or
        neighbor contexts.";

    revision "2019-03-21" {
        description
            "Initial Version";
        reference
            "RFC XXXX, BGP Model for Service Provider Network.";
    }
}
```



```
grouping neighbor-group-timers-config {
  description
    "Config parameters related to timers associated with the BGP
    peer";

  leaf connect-retry {
    type decimal64 {
      fraction-digits 2;
    }
    default 30;
    description
      "Time interval in seconds between attempts to establish a
      session with the peer.";
  }

  leaf hold-time {
    type decimal64 {
      fraction-digits 2;
    }
    default 90;
    description
      "Time interval in seconds that a BGP session will be
      considered active in the absence of keepalive or other
      messages from the peer. The hold-time is typically set to
      3x the keepalive-interval.";
    reference
      "RFC 4271 - A Border Gateway Protocol 4, Sec. 10";
  }

  leaf keepalive-interval {
    type decimal64 {
      fraction-digits 2;
    }
    default 30;
    description
      "Time interval in seconds between transmission of keepalive
      messages to the neighbor. Typically set to 1/3 the
      hold-time.";
  }

  leaf minimum-advertisement-interval {
    type decimal64 {
      fraction-digits 2;
    }
    default 30;
    description
      "Minimum time which must elapse between subsequent UPDATE
      messages relating to a common set of NLRI being transmitted
```



```
        to a peer. This timer is referred to as
        MinRouteAdvertisementIntervalTimer by RFC 4721 and serves to
        reduce the number of UPDATE messages transmitted when a
        particular set of NLRI exhibit instability.";
    reference
        "RFC 4271 - A Border Gateway Protocol 4, Sec 9.2.1.1";
}
}

grouping neighbor-group-config {
    description
        "Neighbor level configuration items.";

    leaf peer-as {
        type inet:as-number;
        description
            "AS number of the peer.";
    }

    leaf local-as {
        type inet:as-number;
        description
            "The local autonomous system number that is to be used when
            establishing sessions with the remote peer or peer group, if
            this differs from the global BGP router autonomous system
            number.";
    }

    leaf peer-type {
        type bt:peer-type;
        description
            "Explicitly designate the peer or peer group as internal
            (iBGP) or external (eBGP).";
    }

    leaf auth-password {
        type string;
        description
            "Configures an MD5 authentication password for use with
            neighboring devices.";
    }

    leaf remove-private-as {
        // could also make this a container with a flag to enable
        // remove-private and separate option. here, option implies
        // remove-private is enabled.
        type bt:remove-private-as-option;
        description

```



```
    "Remove private AS numbers from updates sent to peers - when
    this leaf is not specified, the AS_PATH attribute should be
    sent to the peer unchanged";
}

leaf route-flap-damping {
    type boolean;
    default false;
    description
        "Enable route flap damping.";
}

leaf send-community {
    type bt:community-type;
    default "NONE";
    description
        "Specify which types of community should be sent to the
        neighbor or group. The default is to not send the community
        attribute";
}

leaf description {
    type string;
    description
        "An optional textual description (intended primarily for use
        with a peer or group";
}
}

grouping neighbor-group-transport-config {
    description
        "Configuration parameters relating to the transport protocol
        used by the BGP session to the peer";

    leaf tcp-mss {
        type uint16;
        description
            "Sets the max segment size for BGP TCP sessions.";
    }

    leaf mtu-discovery {
        type boolean;
        default false;
        description
            "Turns path mtu discovery for BGP TCP sessions on (true) or
            off (false)";
    }
}
```



```
leaf passive-mode {
  type boolean;
  default false;
  description
    "Wait for peers to issue requests to open a BGP session,
    rather than initiating sessions from the local router.";
}

leaf local-address {
  type union {
    type inet:ip-address;
    type leafref {
      path "../../../../../interfaces/interface/name";
    }
  }
  description
    "Set the local IP (either IPv4 or IPv6) address to use for
    the session when sending BGP update messages. This may be
    expressed as either an IP address or reference to the name
    of an interface.";
}

grouping neighbor-group-error-handling-config {
  description
    "Configuration parameters relating to enhanced error handling
    behaviors for BGP";

  leaf treat-as-withdraw {
    type boolean;
    default "false";
    description
      "Specify whether erroneous UPDATE messages for which the NLRI
      can be extracted are treated as though the NLRI is withdrawn
      - avoiding session reset";
    reference "draft-ietf-idr-error-handling-16";
  }
}

grouping graceful-restart-config {
  description
    "Configuration parameters relating to BGP graceful restart.";

  leaf enabled {
    type boolean;
    description
      "Enable or disable the graceful-restart capability.";
  }
}
```



```
leaf restart-time {
  type uint16 {
    range 0..4096;
  }
  description
    "Estimated time (in seconds) for the local BGP speaker to
    restart a session. This value is advertise in the graceful
    restart BGP capability. This is a 12-bit value, referred to
    as Restart Time in RFC4724. Per RFC4724, the suggested
    default value is <= the hold-time value.";
}

leaf stale-routes-time {
  type decimal64 {
    fraction-digits 2;
  }
  description
    "An upper-bound on the time that stale routes will be
    retained by a router after a session is restarted. If an
    End-of-RIB (EOR) marker is received prior to this timer
    expiring stale-routes will be flushed upon its receipt - if
    no EOR is received, then when this timer expires stale paths
    will be purged. This timer is referred to as the
    Selection_Deferral_Timer in RFC4724";
}

leaf helper-only {
  type boolean;
  description
    "Enable graceful-restart in helper mode only. When this leaf
    is set, the local system does not retain forwarding its own
    state during a restart, but supports procedures for the
    receiving speaker, as defined in RFC4724.";
}
}

grouping use-multiple-paths-config {
  description
    "Generic configuration options relating to use of multiple
    paths for a referenced AFI-SAFI, group or neighbor";

  leaf enabled {
    type boolean;
    default false;
    description
      "Whether the use of multiple paths for the same NLRI is
      enabled for the neighbor. This value is overridden by any
      more specific configuration value.";
  }
}
```



```
    }
  }

  grouping use-multiple-paths-ebgp-as-options-config {
    description
      "Configuration parameters specific to eBGP multi-path applicable
      to all contexts";

    leaf allow-multiple-as {
      type boolean;
      default "false";
      description
        "Allow multi-path to use paths from different neighboring ASes.
        The default is to only consider multiple paths from the same
        neighboring AS.";
    }
  }

  grouping global-group-use-multiple-paths {
    description
      "Common grouping used for both global and groups which provides
      configuration and state parameters relating to use of multiple
      paths";

    container use-multiple-paths {
      description
        "Parameters related to the use of multiple paths for the
        same NLRI";

      uses use-multiple-paths-config;

      container ebgp {
        description
          "Multi-Path parameters for eBGP";

        leaf allow-multiple-as {
          type boolean;
          default "false";
          description
            "Allow multi-path to use paths from different neighboring
            ASes. The default is to only consider multiple paths
            from the same neighboring AS.";
        }

        leaf maximum-paths {
          type uint32;
          default 1;
          description
```



```
        "Maximum number of parallel paths to consider when using
        BGP multi-path. The default is use a single path.";
    }
}

container ibgp {
    description
        "Multi-Path parameters for iBGP";

    leaf maximum-paths {
        type uint32;
        default 1;
        description
            "Maximum number of parallel paths to consider when using
            iBGP multi-path. The default is to use a single path";
    }
}

grouping route-selection-options {
    description
        "Configuration and state relating to route selection options";

    container route-selection-options {
        description
            "Parameters relating to options for route selection";

        leaf always-compare-med {
            type boolean;
            default "false";
            description
                "Compare multi-exit discriminator (MED) value from
                different ASes when selecting the best route. The default
                behavior is to only compare MEDs for paths received from
                the same AS.";
        }

        leaf ignore-as-path-length {
            type boolean;
            default "false";
            description
                "Ignore the AS path length when selecting the best path.
                The default is to use the AS path length and prefer paths
                with shorter length.";
        }

        leaf external-compare-router-id {
```



```
    type boolean;
    default "true";
    description
      "When comparing similar routes received from external BGP
       peers, use the router-id as a criterion to select the
       active path.";
  }

  leaf advertise-inactive-routes {
    type boolean;
    default "false";
    description
      "Advertise inactive routes to external peers. The default
       is to only advertise active routes.";
  }

  leaf enable-aigp {
    type boolean;
    default false;
    description
      "Flag to enable sending / receiving accumulated IGP
       attribute in routing updates";
  }

  leaf ignore-next-hop-igp-metric {
    type boolean;
    default "false";
    description
      "Ignore the IGP metric to the next-hop when calculating BGP
       best-path. The default is to select the route for which
       the metric to the next-hop is lowest";
  }
}

grouping state {
  description
    "Grouping containing common counters relating to prefixes and
     paths";

  leaf total-paths {
    type uint32;
    config false;
    description
      "Total number of BGP paths within the context";
  }

  leaf total-prefixes {
```



```
        type uint32;
        config false;
        description
            "Total number of BGP prefixes received within the context";
    }
}
}
<CODE ENDS>
```

```
<CODE BEGINS> file "ietf-bgp-common-multiprotocol@2019-03-21.yang"
submodule ietf-bgp-common-multiprotocol {
    yang-version "1.1";
    belongs-to ietf-bgp {
        prefix "bgp";
    }

    import ietf-bgp-types {
        prefix bt;
    }
    import ietf-routing-policy {
        prefix rpol;
    }

    include ietf-bgp-common;

    // meta
    organization
        "IETF IDR Working Group";

    contact
        "WG Web:   <http://tools.ietf.org/wg/idr>
        WG List:  <idr@ietf.org>

        Authors: Mahesh Jethanandani (mjethanandani at gmail.com),
                Keyur Patel (keyur at arrcus.com),
                Susan Hares (shares at ndzh.com";

    description
        "This sub-module contains groupings that are related to support
        for multiple protocols in BGP. The groupings are common across
        multiple contexts.";

    revision "2019-03-21" {
        description
            "Initial Version";
        reference
            "RFC XXX, BGP Model for Service Provider Network.";
```



```
}

grouping mp-afi-safi-graceful-restart-config {
  description
    "BGP graceful restart parameters that apply on a per-AFI-SAFI
    basis";

  leaf enabled {
    type boolean;
    default false;
    description
      "This leaf indicates whether graceful-restart is enabled for
      this AFI-SAFI";
  }
}

grouping mp-afi-safi-config {
  description
    "Configuration parameters used for all BGP AFI-SAFIs";

  leaf afi-safi-name {
    type identityref {
      base "bt:afi-safi-type";
    }
    description "AFI,SAFI";
  }

  leaf enabled {
    type boolean;
    default false;
    description
      "This leaf indicates whether the IPv4 Unicast AFI,SAFI is
      enabled for the neighbour or group";
  }
}

grouping mp-all-afi-safi-list-contents {
  description
    "A common grouping used for contents of the list that is used
    for AFI-SAFI entries";

  // import and export policy included for the afi/safi
  uses rpol:apply-policy-group;

  container ipv4-unicast {
    when "../afi-safi-name = 'bt:IPv4_UNICAST'" {
      description
        "Include this container for IPv4 Unicast specific
```



```
        configuration";
    }

    description
        "IPv4 unicast configuration options";

    // include common IPv[46] unicast options
    uses mp-ipv4-ipv6-unicast-common;

    // placeholder for IPv4 unicast specific configuration
}

container ipv6-unicast {
    when "../afi-safi-name = 'bt:IPV6_UNICAST'" {
        description
            "Include this container for IPv6 Unicast specific
            configuration";
    }

    description
        "IPv6 unicast configuration options";

    // include common IPv[46] unicast options
    uses mp-ipv4-ipv6-unicast-common;

    // placeholder for IPv6 unicast specific configuration
    // options
}

container ipv4-labeled-unicast {
    when "../afi-safi-name = 'bt:IPV4_LABELED_UNICAST'" {
        description
            "Include this container for IPv4 Labeled Unicast specific
            configuration";
    }

    description
        "IPv4 Labeled Unicast configuration options";

    uses mp-all-afi-safi-common;

    // placeholder for IPv4 Labeled Unicast specific config
    // options
}

container ipv6-labeled-unicast {
    when "../afi-safi-name = 'bt:IPV6_LABELED_UNICAST'" {
        description
```



```
        "Include this container for IPv6 Labeled Unicast specific
          configuration";
      }

      description
        "IPv6 Labeled Unicast configuration options";

      uses mp-all-afi-safi-common;

      // placeholder for IPv6 Labeled Unicast specific config
      // options.
    }

    container l3vpn-ipv4-unicast {
      when "../afi-safi-name = 'bt:L3VPN_IPV4_UNICAST'" {
        description
          "Include this container for IPv4 Unicast L3VPN specific
            configuration";
      }

      description
        "Unicast IPv4 L3VPN configuration options";

      // include common L3VPN configuration options
      uses mp-l3vpn-ipv4-ipv6-unicast-common;

      // placeholder for IPv4 Unicast L3VPN specific config options.
    }

    container l3vpn-ipv6-unicast {
      when "../afi-safi-name = 'bt:L3VPN_IPV6_UNICAST'" {
        description
          "Include this container for unicast IPv6 L3VPN specific
            configuration";
      }

      description
        "Unicast IPv6 L3VPN configuration options";

      // include common L3VPN configuration options
      uses mp-l3vpn-ipv4-ipv6-unicast-common;

      // placeholder for IPv6 Unicast L3VPN specific configuration
      // options
    }

    container l3vpn-ipv4-multicast {
      when "../afi-safi-name = 'bt:L3VPN_IPV4_MULTICAST'" {
```



```
    description
      "Include this container for multicast IPv6 L3VPN specific
      configuration";
  }

  description
    "Multicast IPv4 L3VPN configuration options";

  // include common L3VPN multicast options
  uses mp-l3vpn-ipv4-ipv6-multicast-common;

  // placeholder for IPv4 Multicast L3VPN specific configuration
  // options
}

container l3vpn-ipv6-multicast {
  when "../afi-safi-name = 'bt:L3VPN_IPV6_MULTICAST'" {
    description
      "Include this container for multicast IPv6 L3VPN specific
      configuration";
  }
  description
    "Multicast IPv6 L3VPN configuration options";

  // include common L3VPN multicast options
  uses mp-l3vpn-ipv4-ipv6-multicast-common;

  // placeholder for IPv6 Multicast L3VPN specific configuration
  // options
}

container l2vpn-vpls {
  when "../afi-safi-name = 'bt:L2VPN_VPLS'" {
    description
      "Include this container for BGP-signalled VPLS specific
      configuration";
  }
}

description
  "BGP-signalled VPLS configuration options";

  // include common L2VPN options
  uses mp-l2vpn-common;

  // placeholder for BGP-signalled VPLS specific configuration
  // options
}
```



```
container l2vpn-evpn {
  when "../afi-safi-name = 'bt:L2VPN_EVPN'" {
    description
      "Include this container for BGP EVPN specific
        configuration";
  }

  description
    "BGP EVPN configuration options";

  // include common L2VPN options
  uses mp-l2vpn-common;

  // placeholder for BGP EVPN specific configuration options
}
}

// Common groupings across multiple AFI,SAFIs
grouping mp-all-afi-safi-common {
  description
    "Grouping for configuration common to all AFI,SAFI";

  container prefix-limit {
    description
      "Parameters relating to the prefix limit for the AFI-SAFI";
    leaf max-prefixes {
      type uint32;
      description
        "Maximum number of prefixes that will be accepted from the
          neighbour";
    }
    leaf shutdown-threshold-pct {
      type bt:percentage;
      description
        "Threshold on number of prefixes that can be received from
          a neighbour before generation of warning messages or log
          entries. Expressed as a percentage of max-prefixes";
    }
  }

  leaf restart-timer {
    type decimal64 {
      fraction-digits 2;
    }
    units "seconds";
    description
      "Time interval in seconds after which the BGP session is
        re-established after being torn down due to exceeding the
        max-prefix limit.";
```



```
    }
  }
}

grouping mp-ipv4-ipv6-unicast-common {
  description
    "Common configuration that is applicable for IPv4 and IPv6
    unicast";

  // include common afi-safi options.
  uses mp-all-afi-safi-common;

  // configuration options that are specific to IPv[46] unicast
  leaf send-default-route {
    type boolean;
    default "false";
    description
      "If set to true, send the default-route to the neighbour(s)";
  }
}

grouping mp-l3vpn-ipv4-ipv6-unicast-common {
  description
    "Common configuration applied across L3VPN for IPv4
    and IPv6";

  // placeholder -- specific configuration options that are generic
  // across IPv[46] unicast address families.
  uses mp-all-afi-safi-common;
}

grouping mp-l3vpn-ipv4-ipv6-multicast-common {
  description
    "Common configuration applied across L3VPN for IPv4
    and IPv6";

  // placeholder -- specific configuration options that are
  // generic across IPv[46] multicast address families.
  uses mp-all-afi-safi-common;
}

grouping mp-l2vpn-common {
  description
    "Common configuration applied across L2VPN address
    families";

  // placeholder -- specific configuration options that are
  // generic across L2VPN address families
```



```
    uses mp-all-afi-safi-common;
  }

  // Config groupings for common groups
  grouping mp-all-afi-safi-common-prefix-limit-config {
    description
      "Configuration parameters relating to prefix-limits for an
      AFI-SAFI";

  }
}
<CODE ENDS>
```

```
<CODE BEGINS> file "ietf-bgp-common-structure@2019-03-21.yang"
submodule ietf-bgp-common-structure {
  yang-version "1.1";
  belongs-to ietf-bgp {
    prefix "bgp";
  }

  import ietf-bgp-types { prefix bt; }
  import ietf-routing-policy { prefix rpol; }
  include ietf-bgp-common-multiprotocol;
  include ietf-bgp-common;

  // meta
  organization
    "IETF IDR Working Group";

  contact
    "WG Web:  <http://tools.ietf.org/wg/idr>
    WG List:  <idr@ietf.org>

    Authors: Mahesh Jethanandani (mjethanandani at gmail.com),
             Keyur Patel (keyur at arccus.com),
             Susan Hares (shares at ndzh.com";

  description
    "This sub-module contains groupings that are common across
    multiple BGP contexts and provide structure around other
    primitive groupings.";

  revision "2019-03-21" {
    description
      "Initial Version";
    reference
```



```
    "RFC XXX, BGP Model for Service Provider Network.";
}

grouping structure-neighbor-group-logging-options {
  description
    "Structural grouping used to include error handling
    configuration and state for both BGP neighbors and groups";

  container logging-options {
    description
      "Logging options for events related to the BGP neighbor or
      group";

    leaf log-neighbor-state-changes {
      type boolean;
      default "true";
      description
        "Configure logging of peer state changes. Default is to
        enable logging of peer state changes.";
    }
  }
}

grouping structure-neighbor-group-ebgp-multihop {
  description
    "Structural grouping used to include eBGP multi-hop
    configuration and state for both BGP neighbors and peer
    groups";

  container ebgp-multihop {
    description
      "eBGP multi-hop parameters for the BGPgroup";

    leaf enabled {
      type boolean;
      default "false";
      description
        "When enabled the referenced group or neighbors are
        permitted to be indirectly connected - including cases
        where the TTL can be decremented between the BGP peers";
    }

    leaf multihop-ttl {
      type uint8;
      description
        "Time-to-live value to use when packets are sent to the
        referenced group or neighbors and ebgp-multihop is
        enabled";
    }
  }
}
```



```
    }
  }

  grouping structure-neighbor-group-route-reflector {
    description
      "Structural grouping used to include route reflector
      configuration and state for both BGP neighbors and peer
      groups";

    container route-reflector {
      description
        "Route reflector parameters for the BGPgroup";

      leaf route-reflector-cluster-id {
        type bt:rr-cluster-id-type;
        description
          "route-reflector cluster id to use when local router is
          configured as a route reflector. Commonly set at the
          group level, but allows a different cluster id to be set
          for each neighbor.";
      }

      leaf route-reflector-client {
        type boolean;
        default "false";
        description
          "Configure the neighbor as a route reflector client.";
      }
    }
  }

  grouping structure-neighbor-group-as-path-options {
    description
      "Structural grouping used to include AS_PATH manipulation
      configuration and state for both BGP neighbors and peer
      groups";

    container as-path-options {
      description
        "AS_PATH manipulation parameters for the BGP neighbor or
        group";

      leaf allow-own-as {
        type uint8;
        default 0;
        description
          "Specify the number of occurrences of the local BGP
          speaker's AS that can occur within the AS_PATH before it
          is rejected.";
      }
    }
  }
}
```



```
    }

    leaf replace-peer-as {
      type boolean;
      default "false";
      description
        "Replace occurrences of the peer's AS in the AS_PATH with
         the local autonomous system number";
    }
  }
}

grouping structure-neighbor-group-add-paths {
  description
    "Structural grouping used to include ADD-PATHs configuration
     and state for both BGP neighbors and peer groups";

  container add-paths {
    description
      "Parameters relating to the advertisement and receipt of
       multiple paths for a single NLRI (add-paths)";

    leaf receive {
      type boolean;
      default false;
      description
        "Enable ability to receive multiple path advertisements for
         an NLRI from the neighbor or group";
    }

    leaf send-max {
      type uint8;
      description
        "The maximum number of paths to advertise to neighbors for
         a single NLRI";
    }

    leaf eligible-prefix-policy {
      type leafref {
        path "/rpol:routing-policy/rpol:policy-definitions/" +
          "rpol:policy-definition/rpol:name";
      }
      description
        "A reference to a routing policy which can be used to
         restrict the prefixes for which add-paths is enabled";
    }
  }
}
}
```


<CODE ENDS>

```
<CODE BEGINS> file "ietf-bgp-peer-group@2019-03-21.yang"
submodule ietf-bgp-peer-group {
  yang-version "1.1";
  belongs-to ietf-bgp {
    prefix "bgp";
  }

  import ietf-routing-policy {
    prefix rpol;
  }

  // Include the common submodule
  include ietf-bgp-common;
  include ietf-bgp-common-multiprotocol;
  include ietf-bgp-common-structure;

  // meta
  organization
    "IETF IDR Working Group";

  contact
    "WG Web:  <http://tools.ietf.org/wg/idr>
    WG List:  <idr@ietf.org>

    Authors: Mahesh Jethanandani (mjethanandani at gmail.com),
             Keyur Patel (keyur at arccus.com),
             Susan Hares (shares at ndzh.com);

  description
    "This sub-module contains groupings that are specific to the
    peer-group context of the OpenConfig BGP module.";

  revision "2019-03-21" {
    description
      "Initial Version";
    reference
      "RFC XXX, BGP Model for Service Provider Network.";
  }

  grouping bgp-peer-group-config {
    description
      "Configuration parameters relating to a base BGP peer group
      that are not also applicable to any other context (e.g.,
      neighbor)";
```



```
    leaf peer-group-name {
      type string;
      description
        "Name of the BGP peer-group";
    }
  }

  grouping bgp-peer-group-afi-safi-list {
    description
      "List of address-families associated with the BGP peer-group";

    list afi-safi {
      key "afi-safi-name";

      description
        "AFI,SAFI configuration available for the
        neighbour or group";

      uses mp-afi-safi-config;

      container graceful-restart {
        description
          "Parameters relating to BGP graceful-restart";

        uses mp-afi-safi-graceful-restart-config;
      }

      uses route-selection-options;
      uses global-group-use-multiple-paths;
      uses mp-all-afi-safi-list-contents;
    }
  }

  grouping bgp-peer-group-base {
    description
      "Parameters related to a BGP group";

    uses bgp-peer-group-config;
    uses neighbor-group-config;
    uses state;

    container timers {
      description
        "Timers related to a BGP peer-group";

      uses neighbor-group-timers-config;
    }
  }
```



```
    container transport {
      description
        "Transport session parameters for the BGP peer-group";

      uses neighbor-group-transport-config;
    }

    container error-handling {
      description
        "Error handling parameters used for the BGP peer-group";

      uses neighbor-group-error-handling-config;
    }

    container graceful-restart {
      description
        "Parameters relating the graceful restart mechanism for BGP";

      uses graceful-restart-config;
    }

    uses structure-neighbor-group-logging-options;
    uses structure-neighbor-group-ebgp-multihop;
    uses structure-neighbor-group-route-reflector;
    uses structure-neighbor-group-as-path-options;
    uses structure-neighbor-group-add-paths;
    uses global-group-use-multiple-paths;
    uses rpol:apply-policy-group;

    container afi-safis {
      description
        "Per-address-family configuration parameters associated with
        thegroup";
      uses bgp-peer-group-afi-safi-list;
    }
  }

  grouping bgp-peer-group-list {
    description
      "The list of BGP peer groups";

    list peer-group {
      key "peer-group-name";
      description
        "List of BGP peer-groups configured on the local system -
        uniquely identified by peer-group name";

      uses bgp-peer-group-base;
```



```
    }  
  }  
}  
<CODE ENDS>
```

```
<CODE BEGINS> file "ietf-bgp-neighbor@2019-03-21.yang"  
submodule ietf-bgp-neighbor {  
  yang-version "1.1";  
  belongs-to ietf-bgp {  
    prefix "bgp";  
  }  
  
  import ietf-routing-policy {  
    prefix rpol;  
  }  
  import ietf-bgp-types {  
    prefix bt;  
  }  
  import ietf-inet-types {  
    prefix inet;  
  }  
  import ietf-yang-types {  
    prefix yang;  
  }  
  
  // Include the common submodule  
  include ietf-bgp-common;  
  include ietf-bgp-common-multiprotocol;  
  include ietf-bgp-peer-group;  
  include ietf-bgp-common-structure;  
  
  // meta  
  organization  
    "IETF IDR Working Group";  
  
  contact  
    "WG Web:  <http://tools.ietf.org/wg/idr>  
    WG List:  <idr@ietf.org>  
  
    Authors: Mahesh Jethanandani (mjethanandani at gmail.com),  
             Keyur Patel (keyur at arrcus.com),  
             Susan Hares (shares at ndzh.com);  
  
  description  
    "This sub-module contains groupings that are specific to the  
    neighbor context of the OpenConfig BGP module.";
```



```
revision "2019-03-21" {
  description
    "Initial Version";
  reference
    "RFC XXX, BGP Model for Service Provider Network.";
}

grouping bgp-neighbor-use-multiple-paths {
  description
    "Multi-path configuration and state applicable to a BGP
    neighbor";

  container use-multiple-paths {
    description
      "Parameters related to the use of multiple-paths for the same
      NLRI when they are received only from this neighbor";

    uses use-multiple-paths-config;

    container ebgp {
      description
        "Multi-path configuration for eBGP";
      uses use-multiple-paths-ebgp-as-options-config;
    }
  }
}

grouping bgp-neighbor-counters-message-types-state {
  description
    "Grouping of BGP message types, included for re-use across
    counters";

  leaf UPDATE {
    type uint64;
    description
      "Number of BGP UPDATE messages announcing, withdrawing or
      modifying paths exchanged.";
  }

  leaf NOTIFICATION {
    type uint64;
    description
      "Number of BGP NOTIFICATION messages indicating an error
      condition has occurred exchanged.";
  }
}

grouping bgp-neighbor-afi-safi-list {
```



```
description
  "List of address-families associated with the BGP neighbor";

list afi-safi {
  key "afi-safi-name";

  description
    "AFI,SAFI configuration available for the neighbour or
    group";

  uses mp-afi-safi-config;

  leaf active {
    type boolean;
    config false;
    description
      "This value indicates whether a particular AFI-SAFI has
      been successfully negotiated with the peer. An AFI-SAFI may
      be enabled in the current running configuration, but a
      session restart may be required in order to negotiate the
      new capability.";
  }

  container prefixes {
    config false;
    description "Prefix counters for the BGP session";
    leaf received {
      type uint32;
      description
        "The number of prefixes received from the neighbor";
    }

    leaf sent {
      type uint32;
      description
        "The number of prefixes advertised to the neighbor";
    }

    leaf installed {
      type uint32;
      description
        "The number of advertised prefixes installed in the
        Loc-RIB";
    }
  }
}

container graceful-restart {
  description
```



```
    "Parameters relating to BGP graceful-restart";

    uses mp-afi-safi-graceful-restart-config;

    leaf received {
        type boolean;
        config false;
        description
            "This leaf indicates whether the neighbor advertised the
             ability to support graceful-restart for this AFI-SAFI";
    }

    leaf advertised {
        type boolean;
        config false;
        description
            "This leaf indicates whether the ability to support
             graceful-restart has been advertised to the peer";
    }
}

    uses mp-all-afi-safi-list-contents;
    uses bgp-neighbor-use-multiple-paths;
}

grouping bgp-neighbor-base {
    description
        "Parameters related to a BGP neighbor";

    leaf peer-group {
        type leafref {
            path "../.../peer-groups/peer-group/peer-group-name";
        }
        description
            "The peer-group with which this neighbor is associated";
    }

    leaf neighbor-address {
        type inet:ip-address;
        description
            "Address of the BGP peer, either in IPv4 or IPv6";
    }

    leaf enabled {
        type boolean;
        default true;
        description
```



```
    "Whether the BGP peer is enabled. In cases where the enabled
    leaf is set to false, the local system should not initiate
    connections to the neighbor, and should not respond to TCP
    connections attempts from the neighbor. If the state of the
    BGP session is ESTABLISHED at the time that this leaf is set
    to false, the BGP session should be ceased.";
}

uses neighbor-group-config;

leaf session-state {
  type enumeration {
    enum IDLE {
      description
        "neighbor is down, and in the Idle state of the FSM";
    }
    enum CONNECT {
      description
        "neighbor is down, and the session is waiting for the
        underlying transport session to be established";
    }
    enum ACTIVE {
      description
        "neighbor is down, and the local system is awaiting a
        connection from the remote peer";
    }
    enum OPENSENT {
      description
        "neighbor is in the process of being established. The
        local system has sent an OPEN message";
    }
    enum OPENCONFIRM {
      description
        "neighbor is in the process of being established. The
        local system is awaiting a NOTIFICATION or KEEPALIVE
        message";
    }
    enum ESTABLISHED {
      description
        "neighbor is up - the BGP session with the peer is
        established";
    }
  }
  config false;
  description
    "Operational state of the BGP peer";
}
```



```
leaf last-established {
    // Was oc-types:timeticks64
    type uint64;
    config false;
    description
        "This timestamp indicates the time that the BGP session last
        transitioned in or out of the Established state. The value
        is the timestamp in seconds relative to the Unix Epoch (Jan
        1, 1970 00:00:00 UTC).

        The BGP session uptime can be computed by clients as the
        difference between this value and the current time in UTC
        (assuming the session is in the ESTABLISHED state, per the
        session-state leaf).";
}

leaf established-transitions {
    type yang:counter64;
    config false;
    description
        "Number of transitions to the Established state for the
        neighbor session. This value is analogous to the
        bgpPeerFsmEstablishedTransitions object from the standard
        BGP-4 MIB";
    reference
        "RFC 4273 - Definitions of Managed Objects for BGP-4";
}

leaf-list supported-capabilities {
    type identityref {
        base bt:BGP_CAPABILITY;
    }
    config false;
    description
        "BGP capabilities negotiated as supported with the peer";
}

container messages {
    config false;
    description
        "Counters for BGP messages sent and received from the
        neighbor";
    container sent {
        description
            "Counters relating to BGP messages sent to the neighbor";
        uses bgp-neighbor-counters-message-types-state;
    }
}
```



```
    container received {
      description
        "Counters for BGP messages received from the neighbor";
      uses bgp-neighbor-counters-message-types-state;
    }
  }

  container queues {
    config false;
    description
      "Counters related to queued messages associated with the BGP
      neighbor";

    leaf input {
      type uint32;
      description
        "The number of messages received from the peer currently
        queued";
    }

    leaf output {
      type uint32;
      description
        "The number of messages queued to be sent to the peer";
    }
  }

  container timers {
    description
      "Timers related to a BGP neighbor";

    uses neighbor-group-timers-config;

    leaf negotiated-hold-time {
      type decimal64 {
        fraction-digits 2;
      }
      config false;
      description
        "The negotiated hold-time for the BGP session";
    }
  }

  container transport {
    description
      "Transport session parameters for the BGP neighbor";

    uses neighbor-group-transport-config;
```



```
leaf local-port {
  type inet:port-number;
  config false;
  description
    "Local TCP port being used for the TCP session supporting
    the BGP session";
}

leaf remote-address {
  type inet:ip-address;
  config false;
  description
    "Remote address to which the BGP session has been
    established";
}

leaf remote-port {
  type inet:port-number;
  config false;
  description
    "Remote port being used by the peer for the TCP session
    supporting the BGP session";
}
}

container error-handling {
  description
    "Error handling parameters used for the BGP neighbor or
    group";
  uses neighbor-group-error-handling-config;

  leaf erroneous-update-messages {
    type uint32;
    config false;
    description
      "The number of BGP UPDATE messages for which the
      treat-as-withdraw mechanism has been applied based on
      erroneous message contents";
  }
}

container graceful-restart {
  description
    "Parameters relating the graceful restart mechanism for BGP";

  uses graceful-restart-config;

  leaf peer-restart-time {
```



```
    type uint16 {
      range 0..4096;
    }
    config false;
    description
      "The period of time (advertised by the peer) that the peer
       expects a restart of a BGP session to take";
  }

  leaf peer-restarting {
    type boolean;
    config false;
    description
      "This flag indicates whether the remote neighbor is
       currently in the process of restarting, and hence received
       routes are currently stale";
  }

  leaf local-restarting {
    type boolean;
    config false;
    description
      "This flag indicates whether the local neighbor is
       currently restarting. The flag is unset after all NLRI
       have been advertised to the peer, and the End-of-RIB (EOR)
       marker has been unset";
  }

  leaf mode {
    type enumeration {
      enum HELPER_ONLY {
        description
          "The local router is operating in helper-only mode, and
           hence will not retain forwarding state during a local
           session restart, but will do so during a restart of
           the remote peer";
      }
      enum BILATERAL {
        description
          "The local router is operating in both helper mode, and
           hence retains forwarding state during a remote
           restart, and also maintains forwarding state during
           local session restart";
      }
      enum REMOTE_HELPER {
        description
          "The local system is able to retain routes during
           restart but the remote system is only able to act as a
```



```
        helper";
    }
}
config false;
description
    "This leaf indicates the mode of operation of BGP graceful
    restart with the peer";
}
}

uses structure-neighbor-group-logging-options;
uses structure-neighbor-group-ebgp-multihop;
uses structure-neighbor-group-route-reflector;
uses structure-neighbor-group-as-path-options;
uses structure-neighbor-group-add-paths;
uses bgp-neighbor-use-multiple-paths;
uses rpol:apply-policy-group;

container afi-safis {
    description
        "Per-address-family configuration parameters associated with
        the neighbor";
    uses bgp-neighbor-afi-safi-list;
}
}

grouping bgp-neighbor-list {
    description
        "The list of BGP neighbors";

    list neighbor {
        key "neighbor-address";
        description
            "List of BGP neighbors configured on the local system,
            uniquely identified by peer IPv[46] address";

        uses bgp-neighbor-base;
    }
}
}
}
<CODE ENDS>
```

```
<CODE BEGINS> file "ietf-bgp-global@2019-03-21.yang"
submodule ietf-bgp-global {
    yang-version "1.1";
    belongs-to ietf-bgp {
        prefix bgp;
```



```
}

import ietf-inet-types {
  prefix inet;
}
import ietf-yang-types {
  prefix yang;
}

include ietf-bgp-common;
include ietf-bgp-common-multiprotocol;

organization
  "IETF IDR Working Group";

contact
  "WG Web:   <http://tools.ietf.org/wg/idr>
  WG List:  <idr@ietf.org>

  Authors: Mahesh Jethanandani (mjethanandani at gmail.com),
           Keyur Patel (keyur at arrcus.com),
           Susan Hares (shares at ndzh.com);

description
  "This sub-module contains groupings that are specific to the
  global context of the BGP module";

revision "2019-03-21" {
  description
    "Initial Version";
  reference
    "RFC XXX, BGP Model for Service Provider Network.";
}

grouping bgp-global-config {
  description
    "Global configuration options for the BGP router.";

  leaf as {
    type inet:as-number;
    mandatory true;
    description
      "Local autonomous system number of the router. Uses
      the 32-bit as-number type from the model in RFC 6991.";
  }

  leaf router-id {
    type yang:dotted-quad;
```



```
    description
      "Router id of the router - an unsigned 32-bit integer
      expressed in dotted quad notation.";
    reference
      "RFC4271 - A Border Gateway Protocol 4 (BGP-4),
      Section 4.2";
  }
}

grouping bgp-global-state {
  description
    "Operational state parameters for the BGP neighbor";

  uses state;
}

grouping bgp-global-default-route-distance-config {
  description
    "Configuration options relating to the administrative distance
    (or preference) assigned to routes received from different
    sources (external, internal, and local).";

  leaf external-route-distance {
    type uint8 {
      range "1..255";
    }
    description
      "Administrative distance for routes learned from external
      BGP (eBGP).";
  }
  leaf internal-route-distance {
    type uint8 {
      range "1..255";
    }
    description
      "Administrative distance for routes learned from internal
      BGP (iBGP).";
  }
}

grouping bgp-global-confederation-config {
  description
    "Configuration options specifying parameters when the local
    router is within an autonomous system which is part of a BGP
    confederation.";

  leaf enabled {
    type boolean;
```



```
    description
      "When this leaf is set to true it indicates that
       the local-AS is part of a BGP confederation";
  }

  leaf identifier {
    type inet:as-number;
    description
      "Confederation identifier for the autonomous system.";
  }

  leaf-list member-as {
    type inet:as-number;
    description
      "Remote autonomous systems that are to be treated
       as part of the local confederation.";
  }
}

grouping bgp-global-afi-safi-list {
  description
    "List of address-families associated with the BGP instance";

  list afi-safi {
    key "afi-safi-name";

    description
      "AFI,SAFI configuration available for the
       neighbour or group";

    uses mp-afi-safi-config;
    uses state;

    container graceful-restart {
      description
        "Parameters relating to BGP graceful-restart";

      uses mp-afi-safi-graceful-restart-config;
    }

    uses route-selection-options;
    uses global-group-use-multiple-paths;
    uses mp-all-afi-safi-list-contents;
  }
}

// Structural groupings
grouping bgp-global-base {
```



```
description
  "Global configuration parameters for the BGP router";

uses bgp-global-config;
uses bgp-global-state;

container default-route-distance {
  description
    "Administrative distance (or preference) assigned to
    routes received from different sources
    (external, internal, and local).";

  uses bgp-global-default-route-distance-config;
}

container confederation {
  description
    "Parameters indicating whether the local system acts as part
    of a BGP confederation";

  uses bgp-global-confederation-config;
}

container graceful-restart {
  description
    "Parameters relating the graceful restart mechanism for BGP";
  uses graceful-restart-config;
}

uses global-group-use-multiple-paths;
uses route-selection-options;

container afi-safis {
  description
    "Address family specific configuration";
  uses bgp-global-afi-safi-list;
}
}
}
<CODE ENDS>
```

[7.2.](#) BGP types

```
<CODE BEGINS> file "ietf-bgp-types@2019-03-21.yang"
module ietf-bgp-types {
  yang-version "1.1";
```



```
namespace "urn:ietf:params:xml:ns:yang:ietf-bgp-types";

prefix "bt";

import ietf-inet-types {
  prefix inet;
}

// meta
organization
  "IETF IDR Working Group";

contact
  "WG Web:  <http://tools.ietf.org/wg/idr>
  WG List:  <idr@ietf.org>

  Authors: Mahesh Jethanandani (mjethanandani at gmail.com),
           Keyur Patel (keyur at arrcus.com),
           Susan Hares (shares at ndzh.com);

description
  "This module contains general data definitions for use in BGP
  policy. It can be imported by modules that make use of BGP
  attributes";

revision "2019-03-21" {
  description
    "Initial Version";
  reference
    "RFC XXX, BGP Model for Service Provider Network.";
}

identity BGP_CAPABILITY {
  description "Base identity for a BGP capability";
}

identity MPBGP {
  base BGP_CAPABILITY;
  description
    "Multi-protocol extensions to BGP";
  reference "RFC2858";
}

identity ROUTE_REFRESH {
  base BGP_CAPABILITY;
  description
    "The BGP route-refresh functionality";
  reference "RFC2918";
}
```



```
}

identity ASN32 {
  base BGP_CAPABILITY;
  description
    "4-byte (32-bit) AS number functionality";
  reference "RFC6793";
}

identity GRACEFUL_RESTART {
  base BGP_CAPABILITY;
  description
    "Graceful restart functionality";
  reference "RFC4724";
}

identity ADD_PATHS {
  base BGP_CAPABILITY;
  description
    "BGP add-paths";
  reference "draft-ietf-idr-add-paths";
}

identity afi-safi-type {
  description
    "Base identity type for AFI,SAFI tuples for BGP-4";
  reference "RFC4760 - multi-protocol extensions for BGP-4";
}

identity ipv4-unicast {
  base afi-safi-type;
  description
    "IPv4 unicast (AFI,SAFI = 1,1)";
  reference "RFC4760";
}

identity ipv6-unicast {
  base afi-safi-type;
  description
    "IPv6 unicast (AFI,SAFI = 2,1)";
  reference "RFC4760";
}

identity IPV4_LABELED_UNICAST {
  base afi-safi-type;
  description
    "Labeled IPv4 unicast (AFI,SAFI = 1,4)";
  reference "RFC3107";
}
```



```
}

identity IPV6_LABELED_UNICAST {
  base afi-safi-type;
  description
    "Labeled IPv6 unicast (AFI,SAFI = 2,4)";
  reference "RFC3107";
}

identity L3VPN_IPV4_UNICAST {
  base afi-safi-type;
  description
    "Unicast IPv4 MPLS L3VPN (AFI,SAFI = 1,128)";
  reference "RFC4364";
}

identity L3VPN_IPV6_UNICAST {
  base afi-safi-type;
  description
    "Unicast IPv6 MPLS L3VPN (AFI,SAFI = 2,128)";
  reference "RFC4659";
}

identity L3VPN_IPV4_MULTICAST {
  base afi-safi-type;
  description
    "Multicast IPv4 MPLS L3VPN (AFI,SAFI = 1,129)";
  reference "RFC6514";
}

identity L3VPN_IPV6_MULTICAST {
  base afi-safi-type;
  description
    "Multicast IPv6 MPLS L3VPN (AFI,SAFI = 2,129)";
  reference "RFC6514";
}

identity L2VPN_VPLS {
  base afi-safi-type;
  description
    "BGP-signalled VPLS (AFI,SAFI = 25,65)";
  reference "RFC4761";
}

identity L2VPN_EVPN {
  base afi-safi-type;
  description
    "BGP MPLS Based Ethernet VPN (AFI,SAFI = 25,70)";
```



```
}

identity BGP_WELL_KNOWN_STD_COMMUNITY {
  description
    "Reserved communities within the standard community space
    defined by RFC1997. These communities must fall within the
    range 0x00000000 to 0xFFFFFFFF";
  reference "RFC1997";
}

identity NO_EXPORT {
  base BGP_WELL_KNOWN_STD_COMMUNITY;
  description
    "Do not export NLRI received carrying this community outside
    the bounds of this autonomous system, or this confederation if
    the local autonomous system is a confederation member AS. This
    community has a value of 0xFFFFFFFF01.";
  reference "RFC1997";
}

identity NO_ADVERTISE {
  base BGP_WELL_KNOWN_STD_COMMUNITY;
  description
    "All NLRI received carrying this community must not be
    advertised to other BGP peers. This community has a value of
    0xFFFFFFFF02.";
  reference "RFC1997";
}

identity NO_EXPORT_SUBCONFED {
  base BGP_WELL_KNOWN_STD_COMMUNITY;
  description
    "All NLRI received carrying this community must not be
    advertised to external BGP peers - including over confederation
    sub-AS boundaries. This community has a value of 0xFFFFFFFF03.";
  reference "RFC1997";
}

identity NOPEER {
  base BGP_WELL_KNOWN_STD_COMMUNITY;
  description
    "An autonomous system receiving NLRI tagged with this community
    is advised not to re-advertise the NLRI to external bi-lateral
    peer autonomous systems. An AS may also filter received NLRI
    from bilateral peer sessions when they are tagged with this
    community value";
  reference "RFC3765";
}
```



```
identity as-path-segment-type {
  description
    "Base AS Path Segment Type. In [BGP-4], the path segment type
    is a 1-octet field with the following values defined.";
  reference
    "RFC 5065, Autonomous System Configuration for BGP.";
}

identity as-set {
  base as-path-segment-type;
  description
    "Unordered set of autonomous systems that a route in the UPDATE
    message has traversed.";
  reference
    "RFC 5065, Autonomous System Configuration for BGP.";
}

identity as-sequence {
  base as-path-segment-type;
  description
    "Ordered set of autonomous systems that a route in the UPDATE
    message has traversed.";
  reference
    "RFC 5065, Autonomous System Configuration for BGP.";
}

identity as-confed-sequence {
  base as-path-segment-type;
  description
    "Ordered set of Member Autonomous Systems in the local
    confederation that the UPDATE message has traversed.";
  reference
    "RFC 5065, Autonomous System Configuration for BGP.";
}

identity as-confed-set {
  base as-path-segment-type;
  description
    "Unordered set of Member Autonomous Systems in the local
    confederation that the UPDATE message has traversed.";
  reference
    "RFC 5065, Autonomous System Configuration for BGP.";
}

/*
 * Features.
 */
feature ttl-security {
```



```
    description
      "BGP Time To Live (TTL) security check support.";
    reference
      "RFC 5082, The Generalized TTL Security Mechanism (GTSM)";
  }

  feature bfd {
    description
      "Support for BFD detection of BGP neighbor reachability.";
    reference
      "RFC 5880, Bidirectional Forward Detection (BFD),
      RFC 5881, Bidirectional Forward Detection for IPv4 and IPv6
      (Single Hop).";
  }

  typedef bgp-session-direction {
    type enumeration {
      enum INBOUND {
        description
          "Refers to all NLRI received from the BGP peer";
      }
      enum OUTBOUND {
        description
          "Refers to all NLRI advertised to the BGP peer";
      }
    }
    description
      "Type to describe the direction of NLRI transmission";
  }

  typedef bgp-well-known-community-type {
    type identityref {
      base BGP_WELL_KNOWN_STD_COMMUNITY;
    }
    description
      "Type definition for well-known IETF community attribute
      values";
    reference
      "IANA Border Gateway Protocol (BGP) Well Known Communities";
  }

  typedef bgp-std-community-type {
    // TODO: further refine restrictions and allowed patterns
    // 4-octet value:
    //  <as number> 2 octets
    //  <community value> 2 octets
    type union {
```



```

    type uint32 {
        // per RFC 1997, 0x00000000 - 0x0000FFFF and 0xFFFF0000 -
        // 0xFFFFFFFF are reserved
        range "65536..4294901759"; // 0x00010000..0xFFFFEFFF
    }
    type string {
        pattern '([0-9]+:[0-9]+)';
    }
}
description
    "Type definition for standard community attributes";
reference
    "RFC 1997 - BGP Communities Attribute";
}

typedef bgp-ext-community-type {
    // TODO: needs more work to make this more precise given the
    // variability of extended community attribute specifications
    // 8-octet value:
    // <type> 2 octets
    // <value> 6 octets

    type union {
        type string {
            // Type 1: 2-octet global and 4-octet local
            //           (AS number)           (Integer)
            pattern '(6[0-5][0-5][0-3][0-5]|[1-5][0-9]{4}|' +
                '[1-9][0-9]{1,4}|[0-9]):' +
                '(4[0-2][0-9][0-4][0-9][0-6][0-7][0-2][0-9][0-6]|' +
                '[1-3][0-9]{9}|[1-9]([0-9]{1,7})?[0-9]|[1-9]))';
        }
        type string {
            // Type 2: 4-octet global and 2-octet local
            //           (ipv4-address)       (integer)
            pattern '((([0-9]|[1-9][0-9]|1[0-9][0-9]|2[0-4][0-9]|' +
                '25[0-5])\.){3}([0-9]|[1-9][0-9]|1[0-9][0-9]|' +
                '2[0-4][0-9]|25[0-5]):' +
                '(6[0-5][0-5][0-3][0-5]|[1-5][0-9]{4}|' +
                '[1-9][0-9]{1,4}|[0-9]))';
        }
        type string {
            // route-target with Type 1
            // route-target:(ASN):(local-part)
            pattern 'route-target:(6[0-5][0-5][0-3][0-5]|' +
                '[1-5][0-9]{4}|[1-9][0-9]{1,4}|[0-9]):' +
                '(4[0-2][0-9][0-4][0-9][0-6][0-7][0-2][0-9][0-6]|' +
                '[1-3][0-9]{9}|[1-9]([0-9]{1,7})?[0-9]|[1-9]))';
        }
    }
}

```



```

    type string {
        // route-target with Type 2
        // route-target:(IPv4):(local-part)
        pattern 'route\-target:' +
            '([0-9]|[1-9][0-9]|1[0-9][0-9]|2[0-4][0-9]|' +
            '25[0-5])\.){3}([0-9]|[1-9][0-9]|1[0-9][0-9]|' +
            '2[0-4][0-9]|25[0-5]):' +
            '(6[0-5][0-5][0-3][0-5]|1[1-5][0-9]{4}|' +
            '1[1-9][0-9]{1,4}|[0-9])';
    }
    type string {
        // route-origin with Type 1
        pattern 'route\-origin:(6[0-5][0-5][0-3][0-5]|' +
            '1[1-5][0-9]{4}|1[1-9][0-9]{1,4}|[0-9]):' +
            '(4[0-2][0-9][0-4][0-9][0-6][0-7][0-2][0-9][0-6]|' +
            '1[1-3][0-9]{9}|1[1-9]([0-9]{1,7})?[0-9]|1[1-9])';
    }
    type string {
        // route-origin with Type 2
        pattern 'route\-origin:' +
            '([0-9]|[1-9][0-9]|1[0-9][0-9]|2[0-4][0-9]|' +
            '25[0-5])\.){3}([0-9]|[1-9][0-9]|1[0-9][0-9]|' +
            '2[0-4][0-9]|25[0-5]):' +
            '(6[0-5][0-5][0-3][0-5]|1[1-5][0-9]{4}|' +
            '1[1-9][0-9]{1,4}|[0-9])';
    }
}
description
    "Type definition for extended community attributes";
reference
    "RFC 4360 - BGP Extended Communities Attribute";
}

typedef bgp-community-regexp-type {
    // TODO: needs more work to decide what format these regexps can
    // take.
    type string;
    description
        "Type definition for communities specified as regular
        expression patterns";
}

typedef bgp-origin-attr-type {
    type enumeration {
        enum IGP {
            description "Origin of the NLRI is internal";
        }
        enum EGP {

```



```
        description "Origin of the NLRI is EGP";
    }
    enum INCOMPLETE {
        description "Origin of the NLRI is neither IGP or EGP";
    }
}
description
    "Type definition for standard BGP origin attribute";
reference
    "RFC 4271 - A Border Gateway Protocol 4 (BGP-4), Sec 4.3";
}

typedef peer-type {
    type enumeration {
        enum INTERNAL {
            description "internal (iBGP) peer";
        }
        enum EXTERNAL {
            description "external (eBGP) peer";
        }
    }
}
description
    "labels a peer or peer group as explicitly internal or
    external";
}

identity REMOVE_PRIVATE_AS_OPTION {
    description
        "Base identity for options for removing private autonomous
        system numbers from the AS_PATH attribute";
}

identity PRIVATE_AS_REMOVE_ALL {
    base REMOVE_PRIVATE_AS_OPTION;
    description
        "Strip all private autonomous system numbers from the AS_PATH.
        This action is performed regardless of the other content of the
        AS_PATH attribute, and for all instances of private AS numbers
        within that attribute.";
}

identity PRIVATE_AS_REPLACE_ALL {
    base REMOVE_PRIVATE_AS_OPTION;
    description
        "Replace all instances of private autonomous system numbers in
        the AS_PATH with the local BGP speaker's autonomous system
        number. This action is performed regardless of the other
        content of the AS_PATH attribute, and for all instances of
```



```
        private AS number within that attribute.";
    }

typedef remove-private-as-option {
    type identityref {
        base REMOVE_PRIVATE_AS_OPTION;
    }
    description
        "set of options for configuring how private AS path numbers
        are removed from advertisements";
}

typedef percentage {
    type uint8 {
        range "0..100";
    }
    description
        "Integer indicating a percentage value";
}

typedef rr-cluster-id-type {
    type union {
        type uint32;
        type inet:ipv4-address;
    }
    description
        "union type for route reflector cluster ids:
        option 1: 4-byte number
        option 2: IP address";
}

typedef community-type {
    type enumeration {
        enum STANDARD {
            description "send only standard communities";
        }
        enum EXTENDED {
            description "send only extended communities";
        }
        enum BOTH {
            description "send both standard and extended communities";
        }
        enum NONE {
            description "do not send any community attribute";
        }
    }
    description
        "type describing variations of community attributes:
```



```
        STANDARD: standard BGP community [rfc1997]  
        EXTENDED: extended BGP community [rfc4360]  
        BOTH: both standard and extended community";  
    }  
}  
<CODE ENDS>
```

7.3. BGP policy data

```
<CODE BEGINS> file "ietf-bgp-policy@2019-03-21.yang"  
module ietf-bgp-policy {  
    yang-version "1.1";  
    namespace "urn:ietf:params:xml:ns:yang:ietf-bgp-policy";  
    prefix "bp";  
  
    // import some basic types  
    import ietf-inet-types {  
        prefix inet;  
    }  
    import ietf-routing-policy {  
        prefix rpol;  
    }  
    import ietf-bgp-types {  
        prefix bt;  
    }  
  
    import ietf-routing-types {  
        prefix rt-types;  
    }  
  
    organization  
        "IETF IDR Working Group";  
  
    contact  
        "WG Web:  <http://tools.ietf.org/wg/idr>  
        WG List:  <idr@ietf.org>  
  
        Authors: Mahesh Jethanandani (mjethanandani at gmail.com),  
                Keyur Patel (keyur at arrcus.com),  
                Susan Hares (shares at ndzh.com);  
  
    description  
        "This module contains data definitions for BGP routing policy.  
        It augments the base routing-policy module with BGP-specific  
        options for conditions and actions."  
  
    revision "2019-03-21" {
```



```
    description
      "Initial Version";
    reference
      "RFC XXX, BGP Model for Service Provider Network.";
  }

// typedef statements

typedef bgp-set-community-option-type {
  type enumeration {
    enum ADD {
      description
        "add the specified communities to the existing
        community attribute";
    }
    enum REMOVE {
      description
        "remove the specified communities from the
        existing community attribute";
    }
    enum REPLACE {
      description
        "replace the existing community attribute with
        the specified communities. If an empty set is
        specified, this removes the community attribute
        from the route.";
    }
  }
  description
    "Type definition for options when setting the community
    attribute in a policy action";
}

typedef bgp-next-hop-type {
  type union {
    type inet:ip-address-no-zone;
    type enumeration {
      enum SELF {
        description "special designation for local router's own
        address, i.e., next-hop-self";
      }
    }
  }
  description
    "type definition for specifying next-hop in policy actions";
}

typedef bgp-set-med-type {
```



```
type union {
  type uint32;
  type string {
    pattern "^[+-][0-9]+";
  }
  type enumeration {
    enum IGP {
      description "set the MED value to the IGP cost toward the
        next hop for the route";
    }
  }
}
description
  "Type definition for specifying how the BGP MED can
  be set in BGP policy actions. The three choices are to set
  the MED directly, increment/decrement using +/- notation,
  and setting it to the IGP cost (predefined value).";
}

// augment statements

augment "/rpol:routing-policy/rpol:defined-sets" {
  description
    "Adds BGP defined sets container to routing policy model.";

  container bgp-defined-sets {
    description
      "BGP-related set definitions for policy match conditions";

    container community-sets {
      description
        "Enclosing container for list of defined BGP community sets";

      list community-set {
        key "community-set-name";
        description
          "List of defined BGP community sets";

        leaf community-set-name {
          type string;
          mandatory true;
          description
            "name / label of the community set -- this is used to
            reference the set in match conditions";
        }
      }

      leaf-list community-member {
        type union {
```



```
        type bt:bgp-std-community-type;
        type bt:bgp-community-regexp-type;
        type bt:bgp-well-known-community-type;
    }
    description
        "members of the community set";
}
}
}

container ext-community-sets {
    description
        "Enclosing container for list of extended BGP community
sets";
    list ext-community-set {
        key "ext-community-set-name";
        description
            "List of defined extended BGP community sets";

        leaf ext-community-set-name {
            type string;
            description
                "name / label of the extended community set -- this is
used to reference the set in match conditions";
        }

        leaf-list ext-community-member {
            type union {
                type rt-types:route-target;
                type bt:bgp-community-regexp-type;
            }
            description
                "members of the extended community set";
        }
    }
}

container as-path-sets {
    description
        "Enclosing container for list of define AS path sets";

    list as-path-set {
        key "as-path-set-name";
        description
            "List of defined AS path sets";

        leaf as-path-set-name {
            type string;
```



```
        description
            "name of the AS path set -- this is used to reference the
            set in match conditions";
    }

    leaf-list as-path-set-member {
        // TODO: need to refine typedef for AS path expressions
        type string;
        description
            "AS path expression -- list of ASes in the set";
    }
}
}
}

grouping as-path-prepend-top {
    description
        "Top-level grouping for the AS path prepend action";

}

grouping set-community-action-common {
    description
        "Common leaves for set-community and set-ext-community
        actions";

    leaf method {
        type enumeration {
            enum INLINE {
                description
                    "The extended communities are specified inline as a
                    list";
            }
            enum REFERENCE {
                description
                    "The extended communities are specified by referencing a
                    defined ext-community set";
            }
        }
        description
            "Indicates the method used to specify the extended
            communities for the set-ext-community action";
    }

    leaf options {
        type bgp-set-community-option-type;
```



```
    description
      "Options for modifying the community attribute with
       the specified values. These options apply to both
       methods of setting the community attribute.";
  }
}

augment "/rpol:routing-policy/rpol:policy-definitions/" +
  "rpol:policy-definition/rpol:statements/rpol:statement/" +
  "rpol:conditions" {
  description
    "BGP policy conditions added to routing policy module";

  container bgp-conditions {
    description
      "Top-level container for BGP specific policy conditions ";

    leaf med-eq {
      type uint32;
      description
        "Condition to check if the received MED value is equal to
         the specified value";
    }

    leaf origin-eq {
      type bt:bgp-origin-attr-type;
      description
        "Condition to check if the route origin is equal to the
         specified value";
    }

    leaf-list next-hop-in {
      type inet:ip-address-no-zone;
      description
        "List of next hop addresses to check for in the route
         update";
    }

    leaf-list afi-safi-in {
      type identityref {
        base bt:afi-safi-type;
      }
      description
        "List of address families which the NLRI may be within";
    }

    leaf local-pref-eq {
      type uint32;
```



```
// TODO: add support for other comparisons if needed
description
  "Condition to check if the local pref attribute is equal to
  the specified value";
}

leaf route-type {
  // TODO: verify extent of vendor support for this comparison
  type enumeration {
    enum INTERNAL {
      description "route type is internal";
    }
    enum EXTERNAL {
      description "route type is external";
    }
  }
  description
    "Condition to check the route type in the route update";
}

container community-count {
  description
    "Value and comparison operations for conditions based on the
    number of communities in the route update";
}

container as-path-length {
  description
    "Value and comparison operations for conditions based on the
    length of the AS path in the route update";
}

container match-community-set {
  description
    "Top-level container for match conditions on communities.
    Match a referenced community-set according to the logic
    defined in the match-set-options leaf";

  leaf community-set {
    type leafref {
      path
        "/rpol:routing-policy/rpol:defined-sets/" +
        "bp:bgp-defined-sets/bp:community-sets/" +
        "bp:community-set/bp:community-set-name";
    }
    description
      "References a defined community set";
  }
}
```



```
    uses rpol:match-set-options-group;
  }

  container match-ext-community-set {
    description
      "Match a referenced extended community-set according to the
      logic defined in the match-set-options leaf";

    leaf ext-community-set {
      type leafref {
        path
          "/rpol:routing-policy/rpol:defined-sets/" +
          "bp:bgp-defined-sets/bp:ext-community-sets/" +
          "bp:ext-community-set/" +
          "bp:ext-community-set-name";
      }
      description "References a defined extended community set";
    }

    uses rpol:match-set-options-group;
  }

  container match-as-path-set {
    description
      "Match a referenced as-path set according to the logic
      defined in the match-set-options leaf";

    leaf as-path-set {
      type leafref {
        path "/rpol:routing-policy/rpol:defined-sets/" +
          "bp:bgp-defined-sets/bp:as-path-sets/" +
          "bp:as-path-set/bp:as-path-set-name";
      }
      description
        "References a defined AS path set";
    }
    uses rpol:match-set-options-group;
  }
}

augment "/rpol:routing-policy/rpol:policy-definitions/" +
  "rpol:policy-definition/rpol:statements/rpol:statement/" +
  "rpol:actions" {
  description
    "BGP policy actions added to routing policy module.";

  container bgp-actions {
```



```
description
  "Top-level container for BGP-specific actions";

leaf set-route-origin {
  type bt:bgp-origin-attr-type;
  description
    "set the origin attribute to the specified value";
}

leaf set-local-pref {
  type uint32;
  description
    "set the local pref attribute on the route update";
}

leaf set-next-hop {
  type bgp-next-hop-type;
  description
    "set the next-hop attribute in the route update";
}

leaf set-med {
  type bgp-set-med-type;
  description
    "set the med metric attribute in the route update";
}

container set-as-path-prepend {
  description
    "action to prepend local AS number to the AS-path a
    specified number of times";

  leaf repeat-n {
    type uint8 {
      range 1..max;
    }
    description
      "Number of times to prepend the local AS number to the AS
      path. The value should be between 1 and the maximum
      supported by the implementation.";
  }
}

container set-community {
  description
    "Action to set the community attributes of the route, along
    with options to modify how the community is modified.
    Communities may be set using an inline list OR
```



```
        reference to an existing defined set (not both).";

uses set-community-action-common;
container inline {
    when "../config/method=INLINE" {
        description
            "Active only when the set-community method is INLINE";
    }
    description
        "Set the community values for the action inline with
        a list.";

    leaf-list communities {
        type union {
            type bt:bgp-std-community-type;
            type bt:bgp-well-known-community-type;
        }
        description
            "Set the community values for the update inline with a
            list.";
    }
}

container reference {
    when "../config/method=REFERENCE" {
        description
            "Active only when the set-community method is REFERENCE";
    }
    description
        "Provide a reference to a defined community set for the
        set-community action";

    leaf community-set-ref {
        type leafref {
            path "/rpol:routing-policy/rpol:defined-sets/" +
                "bp:bgp-defined-sets/" +
                "bp:community-sets/bp:community-set/" +
                "bp:community-set-name";
        }
        description
            "References a defined community set by name";
    }
}

container set-ext-community {
    description
        "Action to set the extended community attributes of the
```



```
    route, along with options to modify how the community is
    modified. Extended communities may be set using an inline
    list OR a reference to an existing defined set (but not
    both).";

uses set-community-action-common;
container inline {
    when "../config/method=INLINE" {
        description
            "Active only when the set-community method is INLINE";
    }
    description
        "Set the extended community values for the action inline
        with a list.";

    leaf-list communities {
        type union {
            type rt-types:route-target;
            type bt:bgp-well-known-community-type;
        }
        description
            "Set the extended community values for the update inline
            with a list.";
    }
}

container reference {
    when "../config/method=REFERENCE" {
        description
            "Active only when the set-community method is REFERENCE";
    }
    description
        "Provide a reference to an extended community set for the
        set-ext-community action";

    leaf ext-community-set-ref {
        type leafref {
            path
                "/rpol:routing-policy/rpol:defined-sets/" +
                "bp:bgp-defined-sets/bp:ext-community-sets/" +
                "bp:ext-community-set/" +
                "bp:ext-community-set-name";
        }
        description
            "References a defined extended community set by name";
    }
}
}
```



```
    }  
  }  
  
  // rpc statements  
  
  // notification statements  
}  
  
<CODE ENDS>
```

7.4. RIB modules

```
<CODE BEGINS> file "ietf-bgp-rib@2019-03-21.yang"  
submodule ietf-bgp-rib {  
  yang-version "1.1";  
  belongs-to ietf-bgp {  
    prefix "br";  
  }  
  
  /*  
   * Import and Include  
   */  
  import ietf-bgp-types {  
    prefix "bt";  
    reference  
      "RFC XXXX: BGP YANG Model for Service Provider Networks.";  
  }  
  
  include ietf-bgp-rib-types;  
  include ietf-bgp-rib-tables;  
  include ietf-bgp-rib-shared-attributes;  
  
  // groupings of attributes in three categories:  
  // - shared across multiple routes  
  // - common to LOC-RIB and Adj-RIB, but not shared across routes  
  // - specific to LOC-RIB or Adj-RIB  
  include ietf-bgp-rib-attributes;  
  
  // groupings of annotations for each route or table  
  include ietf-bgp-rib-table-attributes;  
  
  organization  
    "IETF IDR Working Group";  
  
  contact  
    "WG Web:  <http://tools.ietf.org/wg/idr>  
    WG List:  <idr@ietf.org>  
  
    Authors: Mahesh Jethanandani (mjethanandani at gmail.com),
```


Keyur Patel (keyur at arrcus.com),
Susan Hares (shares at ndzh.com);

description

"Defines a submodule for representing BGP routing table (RIB) contents. The submodule supports 5 logical RIBs per address family:

loc-rib: This is the main BGP routing table for the local routing instance, containing best-path selections for each prefix. The loc-rib table may contain multiple routes for a given prefix, with an attribute to indicate which was selected as the best path. Note that multiple paths may be used or advertised even if only one path is marked as best, e.g., when using BGP add-paths. An implementation may choose to mark multiple paths in the RIB as best path by setting the flag to true for multiple entries.

adj-rib-in-pre: This is a per-neighbor table containing the NLRI updates received from the neighbor before any local input policy rules or filters have been applied. This can be considered the 'raw' updates from a given neighbor.

adj-rib-in-post: This is a per-neighbor table containing the routes received from the neighbor that are eligible for best-path selection after local input policy rules have been applied.

adj-rib-out-pre: This is a per-neighbor table containing routes eligible for sending (advertising) to the neighbor before output policy rules have been applied.

adj-rib-out-post: This is a per-neighbor table containing routes eligible for sending (advertising) to the neighbor after output policy rules have been applied.";

revision "2019-03-21" {

description

"Initial Version";

reference

"RFC XXXX, BGP YANG Model for Service Provider Network.";

}

grouping rib {

description

"Grouping for rib.";

container rib {


```
config false;
description
  "Top level container for BGP RIB";

uses attribute-sets;
uses community-sets;
uses ext-community-sets;

container afi-safis {
  config false;
  description
    "Enclosing container for address family list";

  list afi-safi {
    key "afi-safi-name";
    description
      "List of afi-safi types.";

    leaf afi-safi-name {
      type identityref {
        base bt:afi-safi-type;
      }
      description "AFI,SAFI name.";
    }
  }

  container ipv4-unicast {
    when "../afi-safi-name = 'bt:ipv4-unicast'" {
      description
        "Include this container for IPv4 unicast RIB";
    }
    description
      "Routing tables for IPv4 unicast -- active when the
      afi-safi name is ipv4-unicast";

    uses ipv4-loc-rib;
    uses ipv4-adj-rib;
  }

  container ipv6-unicast {
    when "../afi-safi-name = 'bt:ipv6-unicast'" {
      description
        "Include this container for IPv6 unicast RIB";
    }
    description
      "Routing tables for IPv6 unicast -- active when the
      afi-safi name is ipv6-unicast";

    uses ipv6-loc-rib;
```


"IETF IDR Working Group";

contact

"WG Web: <<http://tools.ietf.org/wg/idr>>

WG List: <idr@ietf.org>

Authors: Mahesh Jethanandani (mjethanandani at gmail.com),
Keyur Patel (keyur at arrcus.com),
Susan Hares (shares at ndzh.com);

description

"Defines additional data nodes for the OpenConfig BGP RIB model.
These items reflect extensions that are desirable features but
are not currently supported in a majority of BGP
implementations.";

revision "2019-03-21" {

description

"Initial Revision.";

reference

"RFC XXXX: BGP YANG Model for Service Providers.";

}

grouping rib-ext-route-annotations {

description

"Extended annotations for routes in the routing tables";

leaf reject-reason {

type union {

type identityref {

base bgp-not-selected-bestpath;

}

type identityref {

base bgp-not-selected-policy;

}

}

description

"Indicates the reason the route is not used, either due to
policy filtering or bestpath selection";

}

}

}

<CODE ENDS>

<CODE BEGINS> file "ietf-bgp-rib-types@2019-03-21.yang"

submodule ietf-bgp-rib-types {

yang-version "1.1";


```
belongs-to ietf-bgp {
  prefix "br";
}

organization
  "IETF IDR Working Group";

contact
  "WG Web:  <http://tools.ietf.org/wg/idr>
  WG List:  <idr@ietf.org>

  Authors: Mahesh Jethanandani (mjethanandani at gmail.com),
           Keyur Patel (keyur at arrcus.com),
           Susan Hares (shares at ndzh.com);

description
  "Defines identity and type definitions associated with
  the BGP RIB modules";

revision "2019-03-21" {
  description
    "Initial Version";
  reference
    "RFC XXXX, BGP Model for Service Provider Network.";
}

identity invalid-route-reason {
  description
    "Base identity for reason code for routes that are rejected as
    invalid.  Some derived entities are based on BMP v3";
  reference
    "BGP Monitoring Protocol (draft-ietf-grow-bmp-07)";
}

identity invalid-cluster-loop {
  base invalid-route-reason;
  description
    "Route was invalid due to CLUSTER_LIST loop";
}

identity invalid-as-loop {
  base invalid-route-reason;
  description
    "Route was invalid due to AS_PATH loop";
}

identity invalid-originator {
  base invalid-route-reason;
```



```
    description
      "Route was invalid due to ORIGINATOR_ID, e.g., update has
      local router as originator";
  }

  identity invalid-confed {
    base invalid-route-reason;
    description
      "Route was invalid due to a loop in the AS_CONFED_SEQUENCE or
      AS_CONFED_SET attributes";
  }

  identity bgp-not-selected-bestpath {
    description
      "Base identity for indicating reason a route was was not
      selected by BGP route selection algorithm";
    reference
      "RFC 4271 - Section 9.1";
  }

  identity local-pref-lower {
    base bgp-not-selected-bestpath;
    description
      "Route has a lower localpref attribute than current best path";
    reference
      "RFC 4271 - Section 9.1.2";
  }

  identity as-path-longer {
    base bgp-not-selected-bestpath;
    description
      "Route has a longer AS path attribute than current best path";
    reference
      "RFC 4271 - Section 9.1.2.2 (a)";
  }

  identity origin-type-higher {
    base bgp-not-selected-bestpath;
    description
      "Route has a higher origin type, i.e., IGP origin is preferred
      over EGP or incomplete";
    reference
      "RFC 4271 - Section 9.1.2.2 (b)";
  }

  identity med-higher {
    base bgp-not-selected-bestpath;
    description
```



```
        "Route has a higher MED, or metric, attribute than the current
        best path";
    reference
        "RFC 4271 - Section 9.1.2.2 (c)";
}

identity prefer-external {
    base bgp-not-selected-bestpath;
    description
        "Route source is via IGP, rather than EGP.";
    reference
        "RFC 4271 - Section 9.1.2.2 (d)";
}

identity nexthop-cost-higher {
    base bgp-not-selected-bestpath;
    description
        "Route has a higher interior cost to the next hop.";
    reference
        "RFC 4271 - Section 9.1.2.2 (e)";
}

identity higher-router-id {
    base bgp-not-selected-bestpath;
    description
        "Route was sent by a peer with a higher BGP Identifier value,
        or router id";
    reference
        "RFC 4271 - Section 9.1.2.2 (f)";
}

identity higher-peer-address {
    base bgp-not-selected-bestpath;
    description
        "Route was sent by a peer with a higher IP address";
    reference
        "RFC 4271 - Section 9.1.2.2 (g)";
}

identity bgp-not-selected-policy {
    description
        "Base identity for reason code for routes that are rejected
        due to policy";
}

identity rejected-import-policy {
    base bgp-not-selected-policy;
    description
```



```
    "Route was rejected after apply import policies";
}

identity tunnel-encapsulation-type {
  description
    "Types of tunnel encapsulation, as described by the Tunnel
    Encapsulation attribute";
  reference
    "RFC5512";
}

identity srte-policy {
  description
    "Segment Routing Traffic Engineering Policy.";
  reference
    "TODO: Insert reference here.";
}

identity srte-policy-ipv4 {
  base srte-policy;
  description
    "Segment Routing Traffice Engineering Policy for IPv4.";
  reference
    "TODO: Insert reference here.";
}

identity srte-policy-ipv6 {
  base srte-policy;
  description
    "Segment Routing Traffic Engineering Policy for IPv6.";
  reference
    "TODO: Insert reference here.";
}

identity srte-policy-tunnel {
  base tunnel-encapsulation-type;
  description
    "Segment Routing Traffic Engineering Policy tunnel.";
  reference
    "draft-previdi-idr-segment-routing-te-policy";
}

identity tunnel-encapsulation-subtlv-type {
  description
    "SubTLVs of the Tunnel Encapsulation attribute";
  reference
    "RFC5512";
}
```



```
identity tunnel-remote-endpoint {
  base tunnel-encapsulation-subtlv-type;
  description
    "Remote endpoint of the tunnel.";
  reference
    "RFC5512";
}

identity tunnel-color {
  base tunnel-encapsulation-subtlv-type;
  description
    "Colour of the tunnel";
  reference
    "RFC5512";
}

identity srte-preference {
  base tunnel-encapsulation-subtlv-type;
  description
    "Preference of the SR-TE policy entry described by
    the tunnel encapsulation attribute.";
  reference
    "draft-previdi-idr-segment-routing-te-policy";
}

identity srte-binding-sid {
  base tunnel-encapsulation-subtlv-type;
  description
    "Binding SID to be used by the SR-TE policy described
    by the tunnel encapsulation attribute.";
  reference
    "draft-previdi-idr-segment-routing-te-policy";
}

identity srte-segment-list {
  base tunnel-encapsulation-subtlv-type;
  description
    "Segment lists to be used by the SR-TE policy described
    by the tunnel encapsulation attribute.";
  reference
    "draft-previdi-idr-segment-routing-te-policy";
}

identity srte-segment-list-subtlv {
  description
    "SubTLVs of the SR-TE Policy Segment List sub-TLV of the
    Tunnel Encapsulation attribute.";
  reference
```



```
    "draft-previdi-idr-segment-routing-te-policy";
  }

  identity srte-segment-list-weight {
    base srte-segment-list-subtlv;
    description
      "Weight of the segment list within the SR-TE policy";
    reference
      "draft-previdi-idr-segment-routing-te-policy";
  }

  identity srte-segment-list-segment {
    base srte-segment-list-subtlv;
    description
      "An individual element within the SR-TE Policy Segment
      List.";
  }
}
<CODE ENDS>
```

<CODE BEGINS> file "ietf-bgp-rib-attributes@2019-03-21.yang"

```
submodule ietf-bgp-rib-attributes {
  yang-version "1.1";
  belongs-to ietf-bgp {
    prefix "br";
  }

  // import some basic types
  import ietf-bgp-types {
    prefix bgpt;
  }

  import ietf-inet-types {
    prefix inet;
  }

  include ietf-bgp-rib-types;

  // meta
  organization
    "IETF IDR Working Group";

  contact
    "WG Web:  <http://tools.ietf.org/wg/idr>
    WG List:  <idr@ietf.org>

    Authors: Mahesh Jethanandani (mjethanandani at gmail.com),
```


Keyur Patel (keyur at arrcus.com),
Susan Hares (shares at ndzh.com);

description

"This submodule contains common data definitions for BGP
attributes for use in BGP RIB tables.";

revision "2019-03-21" {

description

"Initial version";

reference

"RFC XXXX: BGP YANG Model for Service Provider Network";

}

grouping bgp-as-path-attr {

description

"Data for representing BGP AS-PATH attribute";

leaf type {

type identityref {

base bgpt:as-path-segment-type;

}

description

"The type of AS-PATH segment";

}

leaf-list member {

type inet:as-number;

description

"List of the AS numbers in the AS-PATH segment";

}

}

grouping bgp-as-path-attr-top {

description

"Top-level grouping for AS-PATH attribute data";

container as-path {

description

"Enclosing container for the list of AS path segments.

In the Adj-RIB-In or Adj-RIB-Out, this list should show
the received or sent AS_PATH, respectively. For
example, if the local router is not 4-byte capable, this
value should consist of 2-octet ASNs or the AS_TRANS
(AS 23456) values received or sent in route updates.

In the Loc-RIB, this list should reflect the effective AS path for the route, e.g., a 4-octet value if the local router is 4-octet capable.";

reference

[RFC 4271](#) - A Border Gateway Protocol 4 (BGP-4)
[RFC 6793](#) - BGP Support for Four-octet AS Number Space
[RFC 5065](#) - Autonomous System Confederations for BGP";

```
list segment {
  key "type";

  config false;
  uses bgp-as-path-attr;
  description
    "List of AS PATH segments";
}
}
}
```

grouping bgp-as4-path-attr-top {
 description
 "Top-level grouping for AS4-PATH attribute data";

container as4-path {
 description
 "This is the path encoded with 4-octet
 AS numbers in the optional transitive AS4_PATH attribute.
 This value is populated with the received or sent attribute
 in Adj-RIB-In or Adj-RIB-Out, respectively. It should not
 be populated in Loc-RIB since the Loc-RIB is expected to
 store the effective AS-Path in the as-path leaf regardless
 of being 4-octet or 2-octet.";

reference

[RFC 6793](#) - BGP Support for Four-octet AS Number Space";

```
list segment {
  key "type";

  config false;
  uses bgp-as-path-attr;
  description
    "List of AS PATH segments";
}
}
}
```

grouping bgp-community-attr-state {
 description


```
"Common definition of BGP community attributes";

leaf-list community {
  type union {
    type bgpt:bgp-well-known-community-type;
    type bgpt:bgp-std-community-type;
  }
  description
    "List of standard or well-known BGP community
    attributes.";
}

grouping bgp-extended-community-attr-state {
  description
    "Common definition of BGP extended community attribute";

  leaf-list ext-community {
    // type bgpt:bgp-ext-community-recv-type;
    type bgpt:bgp-ext-community-type;
    description
      "List of BGP extended community attributes. The received
      extended community may be an explicitly modeled
      type or unknown, represented by an 8-octet value
      formatted according to RFC 4360.";
    reference
      "RFC 4360 - BGP Extended Communities Attribute";
  }
}

grouping bgp-aggregator-attr-top {
  description
    "Common definition of the BGP aggregator attribute";

  container aggregator {
    config false;
    description
      "BGP attribute indicating the prefix has been aggregated by
      the specified AS and router.";

    leaf as {
      type inet:as-number;
      description
        "AS number of the autonomous system that performed the
        aggregation.";
    }
  }
}
```



```
leaf as4 {
  type inet:as-number;
  description
    "AS number of the autonomous system that performed the
    aggregation (4-octet representation). This value is
    populated if an upstream router is not 4-octet capable.
    Its semantics are similar to the AS4_PATH optional
    transitive attribute";
  reference
    "RFC 6793 - BGP Support for Four-octet AS Number Space";
}

leaf address {
  type inet:ipv4-address;
  description
    "IP address of the router that performed the
    aggregation.";
}
}

grouping bgp-shared-common-attr-state {
  description
    "Route attributes shared across route table entries,
    common to both LOC-Rib and Adj-RIB";

  leaf origin {
    type bgpt:bgp-origin-attr-type;
    description
      "BGP attribute defining the origin of the path information.";
  }

  leaf atomic-aggregate {
    type boolean;
    description
      "BGP attribute indicating that the prefix is an atomic
      aggregate, i.e., the peer selected a less specific
      route without selecting a more specific route that is
      included in it.";
  }

  leaf next-hop {
    type inet:ip-address;
    description
      "BGP next hop attribute defining the IP address of the router
      that should be used as the next hop to the destination";
  }
}
```



```
leaf med {
  type uint32;
  description
    "BGP multi-exit discriminator attribute used in BGP route
    selection process";
}

leaf local-pref {
  type uint32;
  description
    "BGP local preference attribute sent to internal peers to
    indicate the degree of preference for externally learned
    routes. The route with the highest local preference value
    is preferred.";
}

leaf originator-id {
  type inet:ipv4-address;
  description
    "BGP attribute that provides the id as an IPv4 address
    of the originator of the announcement.";
  reference
    "RFC 4456 - BGP Route Reflection: An Alternative to Full
    Mesh Internal BGP (IBGP)";
}

leaf-list cluster-list {
  type inet:ipv4-address;
  description
    "Represents the reflection path that the route has passed.";
  reference
    "RFC 4456 - BGP Route Reflection: An Alternative to Full
    Mesh Internal BGP (IBGP)";
}

leaf aigp {
  type uint64;
  description
    "BGP path attribute representing the accumulated IGP metric
    for the path";
  reference
    "RFC 7311 - The Accumulated IGP Metric Attribute for BGP";
}

grouping bgp-unknown-attr-flags-state {
  description
    "Operational state data for path attribute flags";
}
```



```
leaf optional {
  type boolean;
  description
    "Defines whether the attribute is optional (if
     set to true) or well-known (if set to false).
     Set in the high-order bit of the BGP attribute
     flags octet.";
  reference
    "RFC 4271 - A Border Gateway Protocol 4 (BGP-4)";
}

leaf transitive {
  type boolean;
  description
    "Defines whether an optional attribute is transitive
     (if set to true) or non-transitive (if set to false). For
     well-known attributes, the transitive flag must be set to
     true. Set in the second high-order bit of the BGP attribute
     flags octet.";
  reference
    "RFC 4271 - A Border Gateway Protocol 4 (BGP-4)";
}

leaf partial {
  type boolean;
  description
    "Defines whether the information contained in the optional
     transitive attribute is partial (if set to true) or complete
     (if set to false). For well-known attributes and for
     optional non-transitive attributes, the partial flag
     must be set to false. Set in the third high-order bit of
     the BGP attribute flags octet.";
  reference
    "RFC 4271 - A Border Gateway Protocol 4 (BGP-4)";
}

leaf extended {
  type boolean;
  description
    "Defines whether the attribute length is one octet
     (if set to false) or two octets (if set to true). Set in
     the fourth high-order bit of the BGP attribute flags
     octet.";
  reference
    "RFC 4271 - A Border Gateway Protocol 4 (BGP-4)";
}
}
```



```
grouping bgp-unknown-attr-state {
  description
    "Operational state data for path attributes not shared
    across route entries, common to LOC-RIB and Adj-RIB";

  leaf attr-type {
    type uint8;
    description
      "1-octet value encoding the attribute type code";
    reference
      "RFC 4271 - A Border Gateway Protocol 4 (BGP-4)";
  }

  leaf attr-len {
    type uint16;
    description
      "One or two octet attribute length field indicating the
      length of the attribute data in octets. If the Extended
      Length attribute flag is set, the length field is 2 octets,
      otherwise it is 1 octet";
    reference
      "RFC 4271 - A Border Gateway Protocol 4 (BGP-4)";
  }

  leaf attr-value {
    type binary {
      length 1..65535;
    }
    description
      "Raw attribute value, not including the attribute
      flags, type, or length. The maximum length
      of the attribute value data is 2^16-1 per the max value
      of the attr-len field (2 octets).";
    reference
      "RFC 4271 - A Border Gateway Protocol 4 (BGP-4)";
  }
}

grouping bgp-unknown-attr-top {
  description
    "Unknown path attributes that are not expected to be shared
    across route entries, common to LOC-RIB and Adj-RIB";

  container unknown-attributes {
    description
      "Unknown path attributes that were received in the UPDATE
      message which contained the prefix.";
  }
}
```



```
list unknown-attribute {
  key "attr-type";
  description
    "This list contains received attributes that are unrecognized
    or unsupported by the local router. The list may be empty.";

  uses bgp-unknown-attr-flags-state;
  uses bgp-unknown-attr-state;
}
}
}

grouping bgp-loc-rib-attr-state {
  description
    "Path attributes that are not expected to be shared across
    route entries, specific to LOC-RIB";
}

grouping bgp-adj-rib-attr-state {
  description
    "Path attributes that are not expected to be shared across
    route entries, specific to Adj-RIB";

  leaf path-id {
    type uint32;
    description
      "When the BGP speaker supports advertisement of multiple
      paths for a prefix, the path identifier is used to
      uniquely identify a route based on the combination of the
      prefix and path id. In the Adj-RIB-In, the path-id value is
      the value received in the update message. In the Loc-RIB,
      if used, it should represent a locally generated path-id
      value for the corresponding route. In Adj-RIB-Out, it
      should be the value sent to a neighbor when add-paths is
      used, i.e., the capability has been negotiated.";
    reference
      "draft-ietf-idr-add-paths - Advertisement of Multiple Paths
      in BGP";
  }
}

grouping bgp-tunnel-encapsulation-attr-top {
  description
    "Top-level definition of the BGP Tunnel encapsulation
    attribute.";

  container tunnel-encapsulation {
```



```
config false;
description
  "The Tunnel Encapsulation attribute specifies a set of
  tunnels to a remote destination. The attribute is TLV
  based and allows description of a tunnel type, and the
  relevant information to create the tunnel to the remote
  destination.";

reference "RFC5512, draft-ietf-idr-tunnel-encaps";

container tunnels {
  description
    "Surrounding container for the set of tunnels included
    within the tunnel encapsulation attribute.";

  list tunnel {
    key "type";
    description
      "List of the tunnels that are specified within the
      attribute. Keyed on the type of tunnel that the
      TLV describes.";

    leaf type {
      type identityref {
        base "tunnel-encapsulation-type";
      }
      description
        "Type of the tunnel described within the tunnel
        encapsulation attribute.";
    }
  }

  container subtlvs {
    description
      "Surrounding container for the list of sub-TLVs within
      the tunnel encapsulation attribute.";

    list subtlv {
      key "type";
      description
        "List of the subTLVs that are specified within the
        TLV instance inside the tunnel encapsulation
        attribute.";

      leaf type {
        type identityref {
          base "tunnel-encapsulation-subtlv-type";
        }
        description

```



```
        "Type of the sub-TLV within the tunnel encapsulation
        attribute";
    }

    leaf-list colors {
        when "../type = 'tunnel-color'" {
            description
                "Only allow list of colors to be specified when
                the sub-TLV specifies colors associated with the
                tunnel encapsulation attribute.";
        }
        type uint32;
        description
            "The colors associated with the tunnel encapsulation
            attribute, as described by RFC5512.";
    }

    leaf preference {
        when "../type = 'srte-preference'" {
            description
                "Only allow the preference to be specified when the
                sub-TLV specifies the preference associated with
                the tunnel encapsulation attribute.";
        }
        type uint32;
        default 100;
        description
            "The preference of the SR-TE policy described by the
            tunnel encapsulation attribute. If unspecified, the
            preference defaults to 100.";
    }

    leaf binding-sid {
        when "../type = 'srte-binding-sid'" {
            description
                "Only allow the binding SID to be specified when the
                sub-TLV is specified to be the of the relevant
                type.";
        }
        // type sr:sr-sid-type;
        // defining it as string, till we figure what this
        // should be.
        type string;
        description
            "Binding SID associated with the SR-TE policy";
    }

    container remote-endpoints {
```



```
when "../type = 'tunnel-remote-endpoint'" {
  description
    "Only allow the remote endpoint to be specified
    when the subTLV is specified to describe remote
    endpoints.";
}

description
  "The remote endpoints associated with the tunnel
  described by the attribute.";

list remote-endpoint {
  key "endpoint";
  config false;
  description
    "List of the remote endpoints described within
    the TLV.";

  leaf as {
    type inet:as-number;
    description
      "The remote AS to which the IP address of the
      remote endpoint belongs.";
  }

  leaf endpoint {
    type inet:ip-address;
    description
      "IP address of the remote endpoint.";
  }
}

container segment-lists {
  when "../type = 'srte-segment-list'" {
    description
      "Only allow the segment lists to be specified when
      the sub-TLV is of the relevant type.";
  }

  description
    "Surrounding container for the list of segment lists
    that are associated with a SR-TE Policy tunnel.";

  list segment-list {
    key "instance-id";
    config false;
```



```
description
  "List of segment lists that are specified within the
  tunnel encapsulation attribute.";

leaf instance-id {
  type uint64;
  description
    "Instance of the segment list within the
    sub-TLV";
}

leaf weight {
  type uint32;
  description
    "The weight given to the path within the set of
    segment lists that are included in the tunnel
    attribute sub-TLV.";
}

container segments {
  description
    "Surrounding container for the list of segments
    within the SR-TE segment list.";

  list segment {
    key "index";

    config false;
    description
      "List of segments within the SR-TE segment
      list.";

    leaf index {
      type uint64;
      description
        "Index of the segment within the segment
        list. The segments are ordered in ascending
        order, beginning at 0.";
    }

    leaf type {
      type enumeration {
        enum MPLS_SID {
          value 1;
          description
            "The segment is specified as an MPLS
            label.";
        }
      }
    }
  }
}
```



```
enum IPV6_SID {
  value 2;
  description
    "The segment is specified as an IPv6
    address.";
}
enum IPV4_NODE_ADDRESS {
  value 3;
  description
    "The segment is specified as an IPv4
    node address with optional SID.";
}
enum IPV6_NODE_ADDRESS {
  value 4;
  description
    "The segment is specified as an IPv6
    node address with optional SID.";
}
enum IPV4_LOCAL_INTF_ID {
  value 5;
  description
    "The segment is specified as an IPv4
    address with a local interface
    identifier along with an .";
}
enum IPV4_LOCAL_REMOTE_ADDR {
  value 6;
  description
    "The segment is specified as an IPv4
    local and remote address with an
    optional SID.";
}
enum IPV6_LOCAL_INTF_ID {
  value 7;
  description
    "The segment is specified as an IPv6
    address with an index, along with an
    optional SID.";
}
enum IPV6_LOCAL_REMOTE_ADDR {
  value 8;
  description
    "The segmetn is specified as an IPv6
    local and remote address with an
    optional SID.";
}
}
description
```



```
        "The type of segment specified within the
        segment entry.";
    }

    leaf sid {
        // TODO:      type sr:sr-sid-type;
        // using string till this is resolved.
        type string;
        description
            "SID value for the segment entry, specified
            as an MPLS label or IPv6 address.";
    }

    leaf mpls-tc {
        when "../type = 'MPLS_SID'" {
            description
                "The MPLS TC bits can only be specified
                when the segment time is an MPLS label.";
        }
        type uint8 {
            range "0..7";
        }
        description
            "The MPLS TC bits used when the SID is
            specified as an MPLS label. If set to zero,
            the receiving system specifies the value of
            the TC bits.";
    }

    leaf mpls-bos {
        when "../type = 'MPLS_SID'" {
            description
                "The MPLS BoS bit can only be specified
                when the segment type is an MPLS label.";
        }
        type boolean;
        description
            "When this leaf is set to true the MPLS
            bottom-of-stack (BoS) bit is set in the
            MPLS segment. The BoS bit should always be
            set to zero by the sender.";
    }

    leaf mpls-ttl {
        when "../type = 'MPLS_SID'" {
            description
                "The MPLS TTL can only be set when the
                segment type is an MPLS label.";
        }
    }
}
```



```
}
type uint8;
description
    "The MPLS time to live (TTL) to be set for
    the MPLS segment. If set to 255, the
    receiver specifies the TTL value that is
    used for packets sent with this segment in
    the stack.";
}

leaf remote-ipv4-address {
    when "../type = 'IPV4_NODE_ADDRESS' or" +
        // "../type='../IPV4_ADDRESS_INDEX' or" +
        "../type='IPV4_LOCAL_INTF_ID' or " +
        "../type='IPV4_LOCAL_REMOTE_ADDR'" {
        description
            "An IPv4 address can only be associated
            with the segment entry when the type of
            the SID is a node address, or an IPv6
            address with an index.";
    }
    type inet:ipv4-address;
    description
        "An IPv4 address specified as the remote
        node address. When the type of the segment
        specifies only the remote address, no other
        addresses are specified. When the type of
        the segment requires a local address,
        this leaf specifies the remote IPv4
        address.";
}

leaf local-ipv4-address {
    when "../type = 'IPV4_LOCAL_REMOTE_ADDR'" {
        description
            "A local IPv4 address can only be specified
            when the segment is specified by the
            local and remote IPv4 interface
            addresses.";
    }
    type inet:ipv4-address;
    description
        "An IPv4 address of a local adjacency that is
        used to identify the segment.";
}

leaf remote-ipv6-address {
    when "../type = 'IPV6_NODE_ADDRESS' or" +
```



```
// "../type='IPV6_ADDRESS_INDEX' or" +
"../type='IPV6_LOCAL_INTF_ID' or " +
"../type='IPV6_LOCAL_REMOTE_ADDR'" {
description
    "An IPv6 address can only be specified with
    a segment entry when the type of the SID
    is a node address, or an IPv6 address
    with an index.";
}
type inet:ipv6-address;
description
    "An IPv6 address specified as the remote node
    address. When the type of the segment
    specifies only the remote address, no other
    addresses are specified. When the type of
    the segment requires a local address,
    this leaf specifies the remote IPv6
    address.";
}

leaf local-ipv6-address {
    when "../type = 'IPV6_LOCAL_REMOTE_ADDR'" {
        description
            "A local IPv6 address can only be
            specified when the segment is specified
            by the local and remote IPv6 interface
            addresses.";
    }
    type inet:ipv6-address;
    description
        "An IPv6 address of a local adjacency that is
        used to identify the segment.";
}

leaf local-interface-id {
    when "../type = 'IPV4_LOCAL_INTF_ID' or" +
        "../type='IPV6_LOCAL_INTF_ID'" {
        description
            "A local interface identifier can only be
            specified when the type of the segment
            is an IPv4 address with local interface
            ID, or IPv6 address with local interface
            ID.";
    }
    type uint32;
    description
        "The local interface identifier to be
        utilised for the segment.";
```



```
<CODE ENDS>  
}  
}  
}  
}  
}  
}  
}  
}  
}  
}  
}  
}  
}  
}  
}  
}  
reference  
"draft-ietf-pce-segment-routing";
```

```
<CODE BEGINS> file "ietf-bgp-rib-shared-attributes@2019-03-21.yang"
submodule ietf-bgp-rib-shared-attributes {
  yang-version "1.1";
  belongs-to ietf-bgp {
    prefix "br";
  }

  // import some basic types
  include ietf-bgp-rib-attributes;

  organization
    "IETF IDR Working Group";

  contact
    "WG Web:   <http://tools.ietf.org/wg/idr>
     WG List:  <idr@ietf.org>

     Authors:  Mahesh Jethanandani (mjethanandani at gmail.com),
                Keyur Patel (keyur at arrcus.com),
                Susan Hares (shares at ndzh.com";

  description
    "This submodule contains structural data definitions for
     attribute sets shared across routes.";

  revision "2019-03-21" {
    description
      "Initial version";
    reference
      "RFC XXXX: BGP YANG Model for Service Provider Network.";
  }
}
```



```
grouping attribute-sets {
  description
    "Top level grouping for list of common attribute sets";

  container attr-sets {
    description
      "Enclosing container for the list of path attribute sets";

    list attr-set {
      key "index";

      description
        "List of path attributes that may be in use by multiple
        routes in the table";

      leaf index {
        type uint64;
        description
          "System generated index for each attribute set. The
          index is used to reference an attribute set from a
          specific path. Multiple paths may reference the same
          attribute set.";
      }

      uses bgp-shared-common-attr-state;
      uses bgp-aggregator-attr-top;
      uses bgp-as-path-attr-top;
      uses bgp-as4-path-attr-top;
      uses bgp-tunnel-encapsulation-attr-top;
    }
  }
}

grouping community-sets {
  description
    "Top level grouping for list of shared community attribute
    sets";

  container communities {
    description
      "Enclosing container for the list of community attribute
      sets";

    list community {
      key "index";

      config false;
      description
```



```
    "List of path attributes that may be in use by multiple
    routes in the table";

    leaf index {
        type uint64;
        description
            "System generated index for each attribute set. The
            index is used to reference an attribute set from a
            specific path. Multiple paths may reference the same
            attribute set.";
    }

    uses bgp-community-attr-state;
}
}

grouping ext-community-sets {
    description
        "Top level grouping for list of extended community attribute
        sets";

    container ext-communities {
        description
            "Enclosing container for the list of extended community
            attribute sets";

        list ext-community {
            key "index";

            config false;
            description
                "List of path attributes that may be in use by multiple
                routes in the table";

            leaf index {
                type uint64;
                description
                    "System generated index for each attribute set. The
                    index is used to reference an attribute set from a
                    specific path. Multiple paths may reference the same
                    attribute set.";
            }

            uses bgp-extended-community-attr-state;
        }
    }
}
```



```
}
<CODE ENDS>

<CODE BEGINS> file "ietf-bgp-rib-table-attributes@2019-03-21.yang"
submodule ietf-bgp-rib-table-attributes {
  yang-version "1.1";
  belongs-to ietf-bgp {
    prefix "br";
  }

  // import some basic types
  import ietf-yang-types {
    prefix types;
    reference
      "RFC 6991, Common YANG Data Types.";
  }

  include ietf-bgp-rib-types;

  organization
    "IETF IDR Working Group";

  contact
    "WG Web:  <http://tools.ietf.org/wg/idr>
    WG List:  <idr@ietf.org>

    Authors: Mahesh Jethanandani (mjethanandani at gmail.com),
             Keyur Patel (keyur at arccus.com),
             Susan Hares (shares at ndzh.com);

  description
    "This submodule contains common data definitions for data
    related to a RIB entry, or RIB table.";

  revision "2019-03-21" {
    description
      "Initial version.";
    reference
      "RFC XXXX: BGP YANG Model for Service Provider Network.";
  }

  grouping bgp-common-route-annotations-state {
    description
      "Data definitions for flags and other information attached
      to routes in both LOC-RIB and Adj-RIB";
```



```
leaf last-modified {
  type types:timeticks;
  description
    "Timestamp when this path was last modified.

    The value is the timestamp in seconds relative to
    the Unix Epoch (Jan 1, 1970 00:00:00 UTC).";
}

leaf valid-route {
  type boolean;
  description
    "Indicates that the route is considered valid by the
    local router";
}

leaf invalid-reason {
  type identityref {
    base invalid-route-reason;
  }
  description
    "If the route is rejected as invalid, this indicates the
    reason.";
}
}

grouping bgp-loc-rib-route-annotations-state {
  description
    "Data definitions for information attached to routes in the
    LOC-RIB";

    // placeholder for route metadata specific to the LOC-RIB
}

grouping bgp-adj-rib-in-post-route-annotations-state {
  description
    "Data definitions for information attached to routes in the
    Adj-RIB-in post-policy table";

  leaf best-path {
    type boolean;
    description
      "Current path was selected as the best path.";
  }
}

grouping bgp-common-table-attrs-state {
  description
```



```
    "Common attributes attached to all routing tables";

    // placeholder for metadata associated with all tables
}

grouping bgp-common-table-attrs-top {
    // no enclosing container as this data will fit under an
    // existing LOC-RIB container

    uses bgp-common-table-attrs-state;
    description
        "Operational state data for data related to the entire
        LOC-RIB";
}
}
<CODE ENDS>
```

```
<CODE BEGINS> file "ietf-bgp-rib-tables@2019-03-21.yang"
submodule ietf-bgp-rib-tables {
    yang-version "1.1";
    belongs-to ietf-bgp {
        prefix "br";
    }

    // import some basic types
    import ietf-inet-types {
        prefix inet;
    }

    import ietf-routing {
        prefix "rt";
        reference
            "RFC 8022: A YANG Data Model for Routing Management";
    }

    include ietf-bgp-rib-ext;
    include ietf-bgp-rib-attributes;
    include ietf-bgp-rib-shared-attributes;
    include ietf-bgp-rib-table-attributes;

    organization
        "IETF IDR Working Group";

    contact
        "WG Web:  <http://tools.ietf.org/wg/idr>
        WG List:  <idr@ietf.org>
```


Editor: Mahesh Jethanandani (mjethanandani@gmail.com)
Authors: Keyur Patel,
Mahesh Jethanandani,
Susan Hares";

description

"This submodule contains structural data definitions for
BGP routing tables.";

revision "2019-03-21" {

description

"Initial Version";

reference

"RFC XXXX, BGP YANG Model for Service Provider Network.";

}

grouping bgp-adj-rib-common-attr-refs {

description

"Definitions of common references to attribute sets for
multiple AFI-SAFIs for Adj-RIB tables";

leaf attr-index {

type leafref {

path "../..../attr-sets/attr-set/" +
"index";

}

description

"Reference to the common attribute group for the
route";

}

leaf community-index {

type leafref {

path "../..../communities/community/" +
"index";

}

description

"Reference to the community attribute for the route";

}

leaf ext-community-index {

type leafref {

path "../..../ext-communities/" +
"ext-community/index";

}

description

"Reference to the extended community attribute for the


```
        route";
    }
}

grouping bgp-loc-rib-common-attr-refs {
    description
        "Definitions of common references to attribute sets for
        multiple AFI-SAFIs for LOC-RIB tables";

    leaf attr-index {
        type leafref {
            path "../.../.../.../.../attr-sets/attr-set/" +
                "index";
        }
        description
            "Reference to the common attribute group for the
            route";
    }

    leaf community-index {
        type leafref {
            path "../.../.../.../.../communities/community/" +
                "index";
        }
        description
            "Reference to the community attribute for the route";
    }

    leaf ext-community-index {
        type leafref {
            path "../.../.../.../.../ext-communities/" +
                "ext-community/index";
        }
        description
            "Reference to the extended community attribute for the
            route";
    }
}

grouping bgp-loc-rib-common-keys {
    description
        "Common references used in keys for IPv4 and IPv6
        LOC-RIB entries";

    leaf origin {
        type union {
            type inet:ip-address;
            type identityref {
```



```
        base rt:routing-protocol;
    }
}
description
    "Indicates the origin of the route.  If the route is learned
    from a neighbor, this value is the neighbor address.  If
    the route was injected or redistributed from another
    protocol, the origin indicates the source protocol for the
    route.";
}

leaf path-id {
    type uint32;
    // TODO: YANG does not allow default values for key
    // default 0;
    description
        "If the route is learned from a neighbor, the path-id
        corresponds to the path-id for the route in the
        corresponding adj-rib-in-post table.  If the route is
        injected from another protocol, or the neighbor does not
        support BGP add-paths, the path-id should be set
        to zero, also the default value.";
}
}

grouping ipv4-loc-rib {
    description
        "Top-level grouping for IPv4 routing tables";

    container loc-rib {
        config false;
        description
            "Container for the IPv4 BGP LOC-RIB data";

        uses bgp-common-table-attrs-top;

        container routes {
            description
                "Enclosing container for list of routes in the routing
                table.";

            list route {
                key "prefix origin path-id";

                description
                    "List of routes in the table, keyed by the route
                    prefix, the route origin, and path-id.  The route
                    origin can be either the neighbor address from which
```



```
    the route was learned, or the source protocol that
    injected the route. The path-id distinguishes routes
    for the same prefix received from a neighbor (e.g.,
    if add-paths is enabled).";

    leaf prefix {
        type inet:ipv4-prefix;
        description
            "The IPv4 prefix corresponding to the route";
    }

    uses bgp-loc-rib-common-keys;
    uses bgp-loc-rib-common-attr-refs;
    uses bgp-loc-rib-attr-state;
    uses bgp-common-route-annotations-state;
    uses bgp-loc-rib-route-annotations-state;
    uses bgp-unknown-attr-top;
    uses rib-ext-route-annotations;
}
}
}

grouping ipv6-loc-rib {
    description
        "Top-level grouping for IPv6 routing tables";

    container loc-rib {
        config false;
        description
            "Container for the IPv6 BGP LOC-RIB data";

        uses bgp-common-table-attrs-top;

        container routes {
            description
                "Enclosing container for list of routes in the routing
                table.";

            list route {
                key "prefix origin path-id";

                description
                    "List of routes in the table, keyed by the route
                    prefix, the route origin, and path-id. The route
                    origin can be either the neighbor address from which
                    the route was learned, or the source protocol that
                    injected the route. The path-id distinguishes routes
```



```
    for the same prefix received from a neighbor (e.g.,
    if add-paths is enabled).";

    leaf prefix {
        type inet:ipv6-prefix;
        description
            "The IPv6 prefix corresponding to the route";
    }

    uses bgp-loc-rib-common-keys;
    uses bgp-loc-rib-common-attr-refs;
    uses bgp-loc-rib-attr-state;
    uses bgp-common-route-annotations-state;
    uses bgp-loc-rib-route-annotations-state;
    uses bgp-unknown-attr-top;
    uses rib-ext-route-annotations;
}
}
}

grouping ipv4-adj-rib-common {
    description
        "Common structural grouping for each IPv4 adj-RIB table";

    uses bgp-common-table-attrs-top;

    container routes {
        config false;
        description
            "Enclosing container for list of routes in the routing
            table.";

        list route {
            key "prefix path-id";

            description
                "List of routes in the table, keyed by a combination of
                the route prefix and path-id to distinguish multiple
                routes received from a neighbor for the same prefix,
                e.g., when BGP add-paths is enabled.";

            leaf prefix {
                type inet:ipv4-prefix;
                description
                    "Prefix for the route";
            }
        }
    }
}
```



```
        uses bgp-adj-rib-attr-state;
        uses bgp-adj-rib-common-attr-refs;
        uses bgp-common-route-annotations-state;
        uses bgp-unknown-attr-top;
        uses rib-ext-route-annotations;
    }
}

grouping ipv4-adj-rib-in-post {
    description
        "Common structural grouping for the IPv4 adj-rib-in
        post-policy table";

    uses bgp-common-table-attrs-top;

    container routes {
        config false;
        description
            "Enclosing container for list of routes in the routing
            table.";

        list route {
            key "prefix path-id";

            description
                "List of routes in the table, keyed by a combination of
                the route prefix and path-id to distinguish multiple
                routes received from a neighbor for the same prefix,
                e.g., when BGP add-paths is enabled.";

            leaf prefix {
                type inet:ipv4-prefix;
                description
                    "Prefix for the route";
            }

            uses bgp-adj-rib-attr-state;
            uses bgp-adj-rib-common-attr-refs;
            uses bgp-common-route-annotations-state;
            uses bgp-adj-rib-in-post-route-annotations-state;
            uses bgp-unknown-attr-top;
            uses rib-ext-route-annotations;
        }
    }
}
```



```
grouping ipv4-adj-rib {
  description
    "Top-level grouping for Adj-RIB table";

  container neighbors {
    config false;
    description
      "Enclosing container for neighbor list";

    list neighbor {
      key "neighbor-address";
      description
        "List of neighbors (peers) of the local BGP speaker";

      leaf neighbor-address {
        type inet:ip-address;
        description
          "IP address of the BGP neighbor or peer";
      }

      container adj-rib-in-pre {
        description
          "Per-neighbor table containing the NLRI updates
          received from the neighbor before any local input
          policy rules or filters have been applied. This can
          be considered the 'raw' updates from the neighbor.";

        uses ipv4-adj-rib-common;
      }

      container adj-rib-in-post {
        description
          "Per-neighbor table containing the paths received from
          the neighbor that are eligible for best-path selection
          after local input policy rules have been applied.";

        uses ipv4-adj-rib-in-post;
      }

      container adj-rib-out-pre {
        description
          "Per-neighbor table containing paths eligible for
          sending (advertising) to the neighbor before output
          policy rules have been applied";

        uses ipv4-adj-rib-common;
      }
    }
  }
}
```



```
    }

    container adj-rib-out-post {
      description
        "Per-neighbor table containing paths eligible for
        sending (advertising) to the neighbor after output
        policy rules have been applied";

      uses ipv4-adj-rib-common;
    }
  }
}

grouping ipv6-adj-rib-common {
  description
    "Common structural grouping for each IPv6 adj-RIB table";

  uses bgp-common-table-attrs-state;

  container routes {
    config false;
    description
      "Enclosing container for list of routes in the routing
      table.";

    list route {
      key "prefix path-id";

      description
        "List of routes in the table";

      leaf prefix {
        type inet:ipv6-prefix;
        description
          "Prefix for the route";
      }

      uses bgp-adj-rib-attr-state;
      uses bgp-adj-rib-common-attr-refs;
      uses bgp-common-route-annotations-state;
      uses bgp-unknown-attr-top;
      uses rib-ext-route-annotations;
    }
  }
}
```



```
grouping ipv6-adj-rib-in-post {
  description
    "Common structural grouping for the IPv6 adj-rib-in
    post-policy table";

  uses bgp-common-table-attrs-state;

  container routes {
    config false;
    description
      "Enclosing container for list of routes in the routing
      table.";

    list route {
      key "prefix path-id";

      description
        "List of routes in the table";

      leaf prefix {
        type inet:ipv6-prefix;
        description
          "Prefix for the route";
      }

      uses bgp-adj-rib-attr-state;
      uses bgp-adj-rib-common-attr-refs;
      uses bgp-common-route-annotations-state;
      uses bgp-adj-rib-in-post-route-annotations-state;
      uses bgp-unknown-attr-top;
      uses rib-ext-route-annotations;
    }
  }
}

grouping ipv6-adj-rib {
  description
    "Top-level grouping for Adj-RIB table";

  container neighbors {
    config false;
    description
      "Enclosing container for neighbor list";

    list neighbor {
      key "neighbor-address";
      description
        "List of neighbors (peers) of the local BGP speaker";
    }
  }
}
```



```
leaf neighbor-address {
  type inet:ip-address;
  description
    "IP address of the BGP neighbor or peer";
}

container adj-rib-in-pre {
  description
    "Per-neighbor table containing the NLRI updates
    received from the neighbor before any local input
    policy rules or filters have been applied. This can
    be considered the 'raw' updates from the neighbor.";

  uses ipv6-adj-rib-common;
}

container adj-rib-in-post {
  description
    "Per-neighbor table containing the paths received from
    the neighbor that are eligible for best-path selection
    after local input policy rules have been applied.";

  uses ipv6-adj-rib-in-post;
}

container adj-rib-out-pre {
  description
    "Per-neighbor table containing paths eligible for
    sending (advertising) to the neighbor before output
    policy rules have been applied";

  uses ipv6-adj-rib-common;
}

container adj-rib-out-post {
  description
    "Per-neighbor table containing paths eligible for
    sending (advertising) to the neighbor after output
    policy rules have been applied";

  uses ipv6-adj-rib-common;
}
}
}
```



```
grouping ipvX-srte-policy-adjrib {
  description
    "Top-level grouping for the IPv4 and IPv6 AFI, SR-TE Policy SAFI
    Adj-RIBs.";

  container neighbors {
    description
      "Surrounding container for the list of neighbours that are
      enabled for the IPv4 and IPv6 AFI, SR-TE Policy SAFI address
      family.";

    list neighbor {
      key "neighbor-address";

      description
        "An individual neighbour that is enabled for the SR-TE
        Policy SAFI.";

      uses ipvX-srte-policy-adjrib-neighbor-state;

      container adj-rib-in-pre {
        description
          "The Adj-RIB-In for the SR-TE Policy SAFI for the neighbour,
          prior to any inbound policy constraints or modifications
          having been applied.";
        uses ipvX-srte-policy-adjrib-common;
      }

      container adj-rib-in-post {
        description
          "The Adj-RIB-In for the SR-TE Policy SAFI for the neighbour,
          following any inbound policy constraints or modifications
          being made.";
        uses ipvX-srte-policy-adjrib-in-post;
      }

      container adj-rib-out-pre {
        description
          "The Adj-RIB-Out for the SR-TE Policy SAFI for the
          neighbour, prior to any outgoing policy modifications or
          constraints having been applied.";
        uses ipvX-srte-policy-adjrib-common;
      }

      container adj-rib-out-post {
        description
          "The Adj-RIB-Out for the SR-TE Policy SAFI for the
          neighbour, follow any outbound policy constraints or
```



```
        modifications being made.";
        uses ipvX-srte-policy-adjrib-common;
    }
}
}

grouping ipvX-srte-policy-adjrib-neighbor-state {
    description
        "Common attributes for each neighbour for which the SR-TE
        Policy SAFI RIBs are being maintained.";

    leaf neighbor-address {
        type inet:ip-address;
        description
            "The address of the neighbour for which the SR-TE policy
            SAFI has been negotiated.";
    }
}

grouping ipvX-srte-policy-adjrib-common {
    description
        "Common structure containing the routes that are learnt via
        the IPv4 or IPv6 SR-TE Policy SAFI.";

    container routes {
        description
            "Surrounding container for the list of routes within the
            SR-TE Policy SAFI.";

        list route {
            key "path-id endpoint color";

            description
                "The routes within the SR-TE Policy SAFI Adj-RIB. The
                routes are keyed on the path-id - set to a non-zero
                value only if ADD-PATHS is being used; the color; and
                the endpoint. The colour and endpoint are extracted from
                the NLRI.";

            uses ipvX-srte-policy-common-route-state;
            uses bgp-adj-rib-common-attr-refs;
            uses bgp-common-route-annotations-state;
            uses bgp-unknown-attr-top;
        }
    }
}
```



```
grouping ipvX-srte-policy-common-route-state {
  description
    "Common attributes used SR-TE Policy SAFI routes.";

  leaf path-id {
    type uint32;
    // TODO: YANG does not allow default values for key
    // default 0;
    description
      "Identifier for the path when using BGP ADD-PATHS for the SR-TE
      policy SAFI.";
  }

  leaf endpoint {
    type inet:ip-address;
    description
      "A unique identifier for the remote set of nodes. When the
      address family is IPv4, the value is a 4-octet IPv4 address.
      When the address family is IPv6, the value is a 16-octet IPv6
      address.";
  }

  leaf color {
    type uint32;
    description
      "A 4-octet value identifying the policy. Combined with the
      endpoint the endpoint and colour represent the unique policy.";
  }
}

grouping ipvX-srte-policy-adjrib-in-post {
  description
    "Grouping for the post-policy Adj-RIB-In for SR-TE Policy SAFI
    routes";

  container routes {
    description
      "The set of routes that are within the Adj-RIB-Out for the
      neighbour.";

    list route {
      key "path-id endpoint color";

      description
        "The routes that are in the Adj-RIB-In-Post for the specified
        BGP neighbour within the SR-TE Policy SAFI for the specified
        address family.";
```



```

    uses ipvX-srte-policy-common-route-state;
    uses bgp-adj-rib-common-attr-refs;
    uses bgp-common-route-annotations-state;
    uses bgp-adj-rib-in-post-route-annotations-state;
    uses bgp-unknown-attr-top;
  }
}

grouping ipvX-srte-policy-locrib {
  description
    "Top-level grouping for the Loc-RIB for IPv4 or IPv6 Adj-RIB
    for SR-TE Policy SAFI.";

  container loc-rib {
    description
      "The Loc-RIB for the SR-TE Policy SAFI for IPv4 or IPv6 Unicast
      AFIs.";

    container routes {
      description
        "List of routes within the SR-TE Policy SAFI, for the IPv4 or
        IPv6 AFI.";

      list route {
        key "path-id endpoint color";

        description
          "Route within the specified address family for the SR-TE
          Policy SAFI.";

        uses ipvX-srte-policy-common-route-state;
        uses bgp-loc-rib-common-attr-refs;
        uses bgp-common-route-annotations-state;
        uses bgp-unknown-attr-top;
      }
    }
  }
}

}
<CODE ENDS>

```

```
<CODE BEGINS> file "ietf-bgp-rib-table-attributes@2019-03-21.yang"
submodule ietf-bgp-rib-table-attributes {
  yang-version "1.1";
  belongs-to ietf-bgp {
    prefix "br";
```



```
}

// import some basic types
import ietf-yang-types {
  prefix types;
  reference
    "RFC 6991, Common YANG Data Types.";
}

include ietf-bgp-rib-types;

organization
  "IETF IDR Working Group";

contact
  "WG Web:  <http://tools.ietf.org/wg/idr>
  WG List:  <idr@ietf.org>

  Authors: Mahesh Jethanandani (mjethanandani at gmail.com),
           Keyur Patel (keyur at arrcus.com),
           Susan Hares (shares at ndzh.com";

description
  "This submodule contains common data definitions for data
  related to a RIB entry, or RIB table.";

revision "2019-03-21" {
  description
    "Initial version.";
  reference
    "RFC XXXX: BGP YANG Model for Service Provider Network.";
}

grouping bgp-common-route-annotations-state {
  description
    "Data definitions for flags and other information attached
    to routes in both LOC-RIB and Adj-RIB";

  leaf last-modified {
    type types:timeticks;
    description
      "Timestamp when this path was last modified.

      The value is the timestamp in seconds relative to
      the Unix Epoch (Jan 1, 1970 00:00:00 UTC).";
  }
}
```



```
    leaf valid-route {
      type boolean;
      description
        "Indicates that the route is considered valid by the
         local router";
    }

    leaf invalid-reason {
      type identityref {
        base invalid-route-reason;
      }
      description
        "If the route is rejected as invalid, this indicates the
         reason.";
    }
  }

  grouping bgp-loc-rib-route-annotations-state {
    description
      "Data definitions for information attached to routes in the
       LOC-RIB";

    // placeholder for route metadata specific to the LOC-RIB
  }

  grouping bgp-adj-rib-in-post-route-annotations-state {
    description
      "Data definitions for information attached to routes in the
       Adj-RIB-in post-policy table";

    leaf best-path {
      type boolean;
      description
        "Current path was selected as the best path.";
    }
  }

  grouping bgp-common-table-attrs-state {
    description
      "Common attributes attached to all routing tables";

    // placeholder for metadata associated with all tables
  }

  grouping bgp-common-table-attrs-top {
    // no enclosing container as this data will fit under an
    // existing LOC-RIB container
```



```
    uses bgp-common-table-attrs-state;
    description
      "Operational state data for data related to the entire
       LOC-RIB";
  }
}
<CODE ENDS>
```

8. Examples

This section tries to show some examples in how the model can be used.

8.1. Creating BGP Instance

This example shows how to enable BGP with the IPv4 unicast address family, while adding one network to advertise.

[note: '\\' line wrapping for formatting only]

```
<?xml version="1.0" encoding="UTF-8"?>
<config xmlns="urn:ietf:params:xml:ns:netconf:base:1.0">
  <routing
    xmlns="urn:ietf:params:xml:ns:yang:ietf-routing">
    <control-plane-protocols>
      <control-plane-protocol>
        <type
          xmlns:bgp="urn:ietf:params:xml:ns:yang:ietf-bgp">bgp:bgp
        </type>
        <name>name:BGP</name>
        <bgp
          xmlns="urn:ietf:params:xml:ns:yang:ietf-bgp">
          <global>
            <as>64496</as>
            <afi-safis>
              <afi-safi>
                <afi-safi-name
                  xmlns:bt="urn:ietf:params:xml:ns:yang:ietf-bgp-
types">bt:ipv4-
unicast
                  </afi-safi-name>
                </afi-safi>
              </afi-safis>
            </global>
          </bgp>
        </control-plane-protocol>
      </control-plane-protocols>
    </routing>
  </config>
```

8.2. Neighbor Address Family Configuration

This example shows how to configure a neighbor.

[note: '\\' line wrapping for formatting only]

```
<?xml version="1.0" encoding="UTF-8"?>
<config xmlns="urn:ietf:params:xml:ns:netconf:base:1.0">
  <routing
    xmlns="urn:ietf:params:xml:ns:yang:ietf-routing">
    <control-plane-protocols>
      <control-plane-protocol>
        <type
          xmlns:bgp="urn:ietf:params:xml:ns:yang:ietf-bgp">bgp:bgp
        </type>
        <name>name:BGP</name>
        <bgp
          xmlns="urn:ietf:params:xml:ns:yang:ietf-bgp">
          <global>
            <as>64496</as>
            <afi-safis>
              <afi-safi>
                <afi-safi-name
                  xmlns:bt="urn:ietf:params:xml:ns:yang:ietf-bgp-
types">bt:ipv4-
unicast
                  </afi-safi-name>
                </afi-safi>
              </afi-safis>
            </global>
            <neighbors>
              <neighbor>
                <neighbor-address>192.0.2.1</neighbor-address>
                <peer-as>64497</peer-as>
                <description>"Peer Router B"</description>
                <afi-safis>
                  <afi-safi>
                    <afi-safi-name
                      xmlns:bt="urn:ietf:params:xml:ns:yang:ietf-bgp-
types">bt:ipv\
4-unicast
                    </afi-safi-name>
                  </afi-safi>
                </afi-safis>
              </neighbor>
            </neighbors>
          </bgp>
        </control-plane-protocol>
      </control-plane-protocols>
    </routing>
  </config>
```


9. Contributors

Previous versions of this document saw contributions from Anees Shaikh, Rob Shakir, Kevin D'Souza, Alexander Clemm, Aleksandr Zhadkin, and Xyfeng Liu.

10. Acknowledgements

The authors are grateful for valuable contributions to this document and the associated models from: Ebben Aires, Pavan Beeram, Chris Chase, Ed Crabbe, Luyuan Fang, Bill Fenner, Akshay Gattani, Josh George, Vijay Gill, Matt John, Jeff Haas, Dhanendra Jain, Acee Lindem, Ina Minei, Carl Moberg, Ashok Narayanan, Einar Nilsen-Nygaard, Adam Simpson, Puneet Sood, Jason Sterne, Jeff Tantsura, Jim Uttaro, and Gunter Vandeveld.

Credit is also due to authors of the OpenConfig, whose model was relied upon to come up with this model.

Special thanks to Robert Wilton who helped convert the YANG models to a NMDA compatible model.

11. References

11.1. Normative references

- [RFC1997] Chandra, R., Traina, P., and T. Li, "BGP Communities Attribute", [RFC 1997](#), DOI 10.17487/RFC1997, August 1996, <<https://www.rfc-editor.org/info/rfc1997>>.
- [RFC2439] Villamizar, C., Chandra, R., and R. Govindan, "BGP Route Flap Damping", [RFC 2439](#), DOI 10.17487/RFC2439, November 1998, <<https://www.rfc-editor.org/info/rfc2439>>.
- [RFC3688] Mealling, M., "The IETF XML Registry", [BCP 81](#), [RFC 3688](#), DOI 10.17487/RFC3688, January 2004, <<https://www.rfc-editor.org/info/rfc3688>>.
- [RFC4271] Rekhter, Y., Ed., Li, T., Ed., and S. Hares, Ed., "A Border Gateway Protocol 4 (BGP-4)", [RFC 4271](#), DOI 10.17487/RFC4271, January 2006, <<https://www.rfc-editor.org/info/rfc4271>>.
- [RFC4456] Bates, T., Chen, E., and R. Chandra, "BGP Route Reflection: An Alternative to Full Mesh Internal BGP (IBGP)", [RFC 4456](#), DOI 10.17487/RFC4456, April 2006, <<https://www.rfc-editor.org/info/rfc4456>>.

- [RFC4724] Sangli, S., Chen, E., Fernando, R., Scudder, J., and Y. Rekhter, "Graceful Restart Mechanism for BGP", [RFC 4724](#), DOI 10.17487/RFC4724, January 2007, <<https://www.rfc-editor.org/info/rfc4724>>.
- [RFC4760] Bates, T., Chandra, R., Katz, D., and Y. Rekhter, "Multiprotocol Extensions for BGP-4", [RFC 4760](#), DOI 10.17487/RFC4760, January 2007, <<https://www.rfc-editor.org/info/rfc4760>>.
- [RFC5065] Traina, P., McPherson, D., and J. Scudder, "Autonomous System Confederations for BGP", [RFC 5065](#), DOI 10.17487/RFC5065, August 2007, <<https://www.rfc-editor.org/info/rfc5065>>.
- [RFC6020] Bjorklund, M., Ed., "YANG - A Data Modeling Language for the Network Configuration Protocol (NETCONF)", [RFC 6020](#), DOI 10.17487/RFC6020, October 2010, <<https://www.rfc-editor.org/info/rfc6020>>.
- [RFC6241] Enns, R., Ed., Bjorklund, M., Ed., Schoenwaelder, J., Ed., and A. Bierman, Ed., "Network Configuration Protocol (NETCONF)", [RFC 6241](#), DOI 10.17487/RFC6241, June 2011, <<https://www.rfc-editor.org/info/rfc6241>>.
- [RFC6242] Wasserman, M., "Using the NETCONF Protocol over Secure Shell (SSH)", [RFC 6242](#), DOI 10.17487/RFC6242, June 2011, <<https://www.rfc-editor.org/info/rfc6242>>.
- [RFC6811] Mohapatra, P., Scudder, J., Ward, D., Bush, R., and R. Austein, "BGP Prefix Origin Validation", [RFC 6811](#), DOI 10.17487/RFC6811, January 2013, <<https://www.rfc-editor.org/info/rfc6811>>.
- [RFC6991] Schoenwaelder, J., Ed., "Common YANG Data Types", [RFC 6991](#), DOI 10.17487/RFC6991, July 2013, <<https://www.rfc-editor.org/info/rfc6991>>.
- [RFC7950] Bjorklund, M., Ed., "The YANG 1.1 Data Modeling Language", [RFC 7950](#), DOI 10.17487/RFC7950, August 2016, <<https://www.rfc-editor.org/info/rfc7950>>.
- [RFC8040] Bierman, A., Bjorklund, M., and K. Watsen, "RESTCONF Protocol", [RFC 8040](#), DOI 10.17487/RFC8040, January 2017, <<https://www.rfc-editor.org/info/rfc8040>>.

- [RFC8341] Bierman, A. and M. Bjorklund, "Network Configuration Access Control Model", STD 91, [RFC 8341](#), DOI 10.17487/RFC8341, March 2018, <<https://www.rfc-editor.org/info/rfc8341>>.
- [RFC8349] Lhotka, L., Lindem, A., and Y. Qu, "A YANG Data Model for Routing Management (NMDA Version)", [RFC 8349](#), DOI 10.17487/RFC8349, March 2018, <<https://www.rfc-editor.org/info/rfc8349>>.
- [RFC8446] Rescorla, E., "The Transport Layer Security (TLS) Protocol Version 1.3", [RFC 8446](#), DOI 10.17487/RFC8446, August 2018, <<https://www.rfc-editor.org/info/rfc8446>>.

11.2. Informative references

- [I-D.ietf-bfd-yang]
Rahman, R., Zheng, L., Jethanandani, M., Networks, J., and G. Mirsky, "YANG Data Model for Bidirectional Forwarding Detection (BFD)", [draft-ietf-bfd-yang-17](#) (work in progress), August 2018.
- [I-D.ietf-grow-bmp]
Scudder, J., Fernando, R., and S. Stuart, "BGP Monitoring Protocol", [draft-ietf-grow-bmp-17](#) (work in progress), January 2016.
- [I-D.ietf-rtgwg-policy-model]
Qu, Y., Tantsura, J., Lindem, A., and X. Liu, "A YANG Data Model for Routing Policy Management", [draft-ietf-rtgwg-policy-model-06](#) (work in progress), March 2019.
- [RFC5880] Katz, D. and D. Ward, "Bidirectional Forwarding Detection (BFD)", [RFC 5880](#), DOI 10.17487/RFC5880, June 2010, <<https://www.rfc-editor.org/info/rfc5880>>.
- [RFC8342] Bjorklund, M., Schoenwaelder, J., Shafer, P., Watsen, K., and R. Wilton, "Network Management Datastore Architecture (NMDA)", [RFC 8342](#), DOI 10.17487/RFC8342, March 2018, <<https://www.rfc-editor.org/info/rfc8342>>.

Authors' Addresses

Mahesh Jethanandani
VMware

Email: mjethanandani@gmail.com

Keyur Patel

Arcus

CA

USA

Email: keyur@arcus.com

Susan Hares

Huawei

7453 Hickory Hill

Saline, MI 48176

USA

Email: shares@ndzh.com

