

Interdomain Routing
Internet-Draft
Intended status: Standards Track
Expires: April 6, 2020

M. Jethanandani
VMware
K. Patel
Arrcus
S. Hares
Huawei
J. Haas
Juniper Networks
October 4, 2019

BGP YANG Model for Service Provider Networks
draft-ietf-idr-bgp-model-07

Abstract

This document defines a YANG data model for configuring and managing BGP, including protocol, policy, and operational aspects, such as RIB, based on data center, carrier and content provider operational requirements.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on April 6, 2020.

Copyright Notice

Copyright (c) 2019 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect

to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	3
1.1.	Goals and approach	3
1.2.	Note to RFC Editor	4
1.3.	Terminology	5
1.4.	Abbreviations	5
2.	Model overview	5
2.1.	BGP protocol configuration	6
2.2.	Policy configuration overview	9
2.3.	BGP RIB overview	10
2.3.1.	Local Routing	12
2.3.2.	Pre updates per-neighbor	12
2.3.3.	Post updates per-neighbor	12
2.3.4.	Pre route advertisements per-neighbor	12
2.3.5.	Post route advertisements per-neighbor	12
3.	Relation to other YANG data models	12
4.	Security Considerations	13
5.	IANA Considerations	13
5.1.	URI Registration	14
5.2.	YANG Module Name Registration	14
6.	YANG modules	14
7.	Structure of the YANG modules	15
7.1.	Main module and submodules for base items	15
7.2.	BGP types	64
7.3.	BGP policy data	75
7.4.	RIB modules	86
8.	Examples	120
8.1.	Creating BGP Instance	120
8.2.	Neighbor Address Family Configuration	121
8.3.	IPv6 Neighbor Configuration	123
8.4.	VRF Configuration	124
9.	Contributors	125
10.	Acknowledgements	126
11.	References	126
11.1.	Normative references	126
11.2.	Informative references	128
Appendix A.	How to add a new AFI and Augment a Module	129
Appendix B.	How to deviate a module	131
	Authors' Addresses	132

1. Introduction

This document describes a YANG [\[RFC7950\]](#) data model for the BGP-4 [\[RFC4271\]](#) protocol, including various protocol extensions, policy configuration, as well as defining key operational state data, including Routing Information Base (RIB). The model is intended to be vendor-neutral, in order to allow operators to manage BGP configuration in heterogeneous environments with routers supplied by multiple vendors. The model is also intended to be readily mapped to existing implementations to facilitate support from as large a set of routing hardware and software vendors as possible. This module does not support previous versions of BGP, and cannot support establishing and maintaining state information of neighbors with previous versions of BGP.

1.1. Goals and approach

The model covers the base BGP features that are deployed across major implementations and the common BGP configurations in use across a number of operator network deployments. In particular, this model attempts to cover BGP features defined in BGP [\[RFC4271\]](#), BGP Communities Attribute [\[RFC1997\]](#), BGP Route Reflection [\[RFC4456\]](#), Multiprotocol Extensions for BGP-4 [\[RFC4760\]](#), Autonomous System Confederations for BGP [\[RFC5065\]](#), BGP Route Flap Damping [\[RFC2439\]](#), Graceful Restart Mechanism for BGP [\[RFC4724\]](#), and BGP Prefix Origin Validation [\[RFC6811\]](#).

Along with configuration of base BGP features, this model also addresses policy configuration, by providing "hooks" for applying policies, and also defining BGP-specific policy features. The BGP policy features are intended to be used with the general routing policy model defined in A YANG Data Model for Routing Policy Management [\[I-D.ietf-rtgwg-policy-model\]](#). The model conforms to the NMDA [\[RFC8342\]](#) architecture and has support for configuring Bidirectional Forward Detection (BFD) [\[RFC5880\]](#) for fast next hop liveness check.

For the base BGP features, the focus of the model described in this document is on providing configuration and operational state information relating to:

- o The global BGP instance, and neighbors whose configuration is specified individually, or templated with the use of peer-groups.
- o The address families that are supported by peers, and the global configuration which relates to them.

- o The policy configuration "hooks" and BGP-specific policy features that relate to a neighbor - controlling the import and export of NLRI's.
- o RIB contents.

As mentioned earlier, any configuration items that are deemed to be widely available in existing major BGP implementations are included in the model. Additional, more esoteric, configuration items that are not commonly used, or only available from a single implementation, are omitted from the model with an expectation that they will be available in companion modules that augment or extend the current model. This allows clarity in identifying data that is part of the vendor-neutral base model.

Where possible, naming in the model follows conventions used in available standards documents, and otherwise tries to be self-explanatory with sufficient descriptions of the intended behavior. Similarly, configuration data value constraints and default values, where used, are based on recommendations in current standards documentation, or those commonly used in multiple implementations. Since implementations can vary widely in this respect, this version of the model specifies only a limited set of defaults and ranges with the expectation of being more prescriptive in future versions based on actual operator use.

1.2. Note to RFC Editor

This document uses several placeholder values throughout the document. Please replace them as follows and remove this note before publication.

RFC XXXX, where XXXX is the number assigned to this document at the time of publication.

2019-10-03 with the actual date of the publication of this document.

RFC ZZZZ, where ZZZZ is the number assigned to A YANG Data Model for Routing Policy Management [[I-D.ietf-rtgwg-policy-model](#)].

RFC AAAA, where AAAA is the number assigned to BGP Monitoring Protocol [[RFC7854](#)].

RFC BBBB, where BBBB is the number assigned to YANG Data Model for Bidirectional Forward Detection [[I-D.ietf-bfd-yang](#)].

1.3. Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [BCP 14](#) [[RFC2119](#)] [[RFC8174](#)] when, and only when, they appear in all capitals, as shown here.

1.4. Abbreviations

+-----+-----+-----+		
Abbreviation		
+-----+-----+-----+		
AFI	Address Family Identifier	
BFD	Bidirectional Forward Detection	
NLRI	Network Layer Reachability Information	
NMDA	Network Management Datastore Architecture	
RIB	Routing Information Base	
SAFI	Subsequent Address Family Identifier	
VRF	Virtual Routing and Forwarding	
+-----+-----+-----+		

2. Model overview

The BGP model is defined across several YANG modules and submodules, but at a high level is organized into six elements:

- o base protocol configuration -- configuration affecting BGP protocol-related operations, defined at various levels of hierarchy.
- o multiprotocol configuration -- configuration affecting individual address-families within BGP Multiprotocol Extensions for BGP-4 [[RFC4760](#)].
- o neighbor configuration -- configuration affecting an individual neighbor within BGP.
- o neighbor multiprotocol configuration -- configuration affecting individual address-families for a neighbor within BGP.

- o policy configuration -- hooks for application of the policies defined in A YANG Data Model for Routing Policy Management [[I-D.ietf-rtgwg-policy-model](#)] that act on routes sent (received) to (from) peers or other routing protocols and BGP-specific policy features.
- o operational state -- variables used for monitoring and management of BGP operations.

These modules also make use of standard Internet types, such as IP addresses and prefixes, autonomous system numbers, etc., defined in Common YANG Data Types [[RFC6991](#)].

[2.1.](#) BGP protocol configuration

The BGP protocol configuration model is organized hierarchically, much like the majority of router implementations. That is, configuration items can be specified at multiple levels, as shown below.


```
module: ietf-bgp
```

```
augment /rt:routing/rt:control-plane-protocols/rt:control-plane-protocol:
```

```
col:
  +--rw bgp
    +--rw global!
      | +--rw as inet:as-number
      | +--rw identifier? yang:dotted-quad
      | +--rw distance
      | +--rw confederation
      | +--rw graceful-restart {graceful-restart}?
      | +--rw use-multiple-paths
      | +--rw route-selection-options
      | +--rw afi-safis
      | +--rw apply-policy
      | +--ro total-paths? uint32
      | +--ro total-prefixes? uint32
    +--rw neighbors
      | +--rw neighbor* [remote-address]
      | +---n established
      | +---n backward-transition
      | +--rw clear-neighbors {clear-neighbors}?
    +--rw peer-groups
      | +--rw peer-group* [peer-group-name]
    +--rw interfaces
      | +--rw interface* [name]
    +--ro rib
      +--ro attr-sets
      +--ro communities
      +--ro ext-communities
      +--ro afi-safis
```

Users may specify configuration at a higher level and have it apply to all lower-level items, or provide overriding configuration at a lower level of the hierarchy. Overriding configuration items are optional, with neighbor specific configuration being the most specific or lowest level, followed by peer-group, and finally global. Global configuration options reflect a subset of the peer-group or neighbor specific configuration options which are relevant to the entire BGP instance.

The model makes the simplifying assumption that most of the configuration items are available at all levels of the hierarchy. That is, very little configuration is specific to a particular level in the hierarchy, other than obvious items such as "group-name" only being available for the peer group-level config. A notable exception

is for sub-address family configuration where some items are only applicable for a given AFI-SAFI combination.

In order to allow common configuration to be applied to a set of neighbors, all neighbor configuration options are available within a peer-group. A neighbor is associated to a particular peer-group through the use of a peer-group leaf (which provides a reference to a configured item in the peer-group list).

Address-family configuration is made available in multiple points within the model - primarily within the global container, where instance-wide configuration can be set (for example, global protocol parameters, the BGP best path route selection options, or global policies relating to the address-family); and on a per-neighbor or per-peer-group basis, where address-families can be enabled or disabled, and policy associated with the parent entity applied. Within the afi-safi container, generic configuration that applies to all address-families (e.g., whether the AFI-SAFI is enabled) is presented at the top-level, with address-family specific containers made available for options relating to only that AFI-SAFI. Within the current revision of the model a generic set of address-families, and common configuration and state options are included - further work is expected to add additional parameters to this area of the model.

The following address-families are currently supported by the model:


```
+--rw bgp
  +--rw global!
    +--rw afi-safis
      +--rw afi-safi* [afi-safi-name]
        +--rw afi-safi-name          identityref
        |
        +--rw ipv4-unicast
        |   ...
        +--rw ipv6-unicast
        |   ...
        +--rw ipv4-labeled-unicast
        |   ...
        +--rw ipv6-labeled-unicast
        |   ...
        +--rw l3vpn-ipv4-unicast
        |   ...
        +--rw l3vpn-ipv6-unicast
        |   ...
        +--rw l3vpn-ipv4-multicast
        |   ...
        +--rw l3vpn-ipv6-multicast
        |   ...
        +--rw l2vpn-vpls
        |   ...
        +--rw l2vpn-evpn
        |   ...
```

2.2. Policy configuration overview

The BGP policy configuration model augments the generic YANG routing policy model described in A YANG Data Model for Routing Policy Management [[I-D.ietf-rtgwg-policy-model](#)], which represents a condition-action policy framework for routing. This model adds BGP-specific conditions (e.g., matching on the community attribute), and actions (e.g., setting local preference) to the generic policy framework.

Policies that are defined in the routing-policy model are referenced in multiple places within the model:

- o within the global instance, where a policy applies to all address-families for all peers.
- o on a global AFI-SAFI basis, where policies apply to all peers for a particular address-family.

- o on a per-peer-group or per-neighbor basis - where the policy applies to all address-families for the particular group or neighbor.
- o on a per-afi-safi basis within a neighbor or peer-group context, where the policy is specific to the AFI-SAFI for a a specific neighbor or group.

```
module: ietf-bgp-policy
  augment /rpol:routing-policy/rpol:defined-sets:
    +-rw bgp-defined-sets
    ...
  augment /rpol:routing-policy/rpol:policy-definitions
    /rpol:policy-definition/rpol:statements/rpol:statement
    /rpol:conditions:
    +-rw bgp-conditions
    ...
  augment /rpol:routing-policy/rpol:policy-definitions
    /rpol:policy-definition/rpol:statements/rpol:statement
    /rpol:actions:
    +-rw bgp-actions
    ...
```

2.3. BGP RIB overview

The RIB data model represents the BGP RIB contents. The model supports five logical RIBs per address family.

A abridged version of the tree shows the RIB portion of the tree diagram.


```

module: ietf-bgp
augment /rt:routing/rt:control-plane-protocols
  /rt:control-plane-protocol:
    +--rw bgp
      +--ro rib
        +--ro afi-safis
          +--ro afi-safi* [afi-safi-name]
            +--ro afi-safi-name      identityref
            +--ro ipv4-unicast
              | +--ro loc-rib
              | | +--ro routes
              | |   +--ro route* [prefix origin path-id]
              | |     | ...
              | |   +--ro clear-routes {clear-routes}?
              | |     | ...
              | +--ro neighbors
              |   +--ro neighbor* [neighbor-address]
              |   +--ro neighbor-address      inet:ip-address
              |   +--ro adj-rib-in-pre
              |   | ...
              |   +--ro adj-rib-in-post
              |   | ...
              |   +--ro adj-rib-out-pre
              |   | ...
              |   +--ro adj-rib-out-post
              |   | ...
            +--ro ipv6-unicast
              +--ro loc-rib
              | +--ro routes
              |   +--ro route* [prefix origin path-id]
              |   | ...
              |   +--ro clear-routes {clear-routes}?
              |   | ...
            +--ro neighbors
              +--ro neighbor* [neighbor-address]
              +--ro neighbor-address      inet:ip-address
              +--ro adj-rib-in-pre
              | ...
              +--ro adj-rib-in-post
              | ...
              +--ro adj-rib-out-pre
              | ...
              +--ro adj-rib-out-post
              | ...

```


2.3.1. Local Routing

The loc-rib is the main BGP routing table for the local routing instance, containing best-path selections for each prefix. The loc-rib table may contain multiple routes for a given prefix, with an attribute to indicate which was selected as the best path. Note that multiple paths may be used or advertised even if only one path is marked as best, e.g., when using BGP add-paths. An implementation may choose to mark multiple paths in the RIB as best path by setting the flag to true for multiple entries.

2.3.2. Pre updates per-neighbor

The adj-rib-in-pre table is a per-neighbor table containing the NLRI updates received from the neighbor before any local input policy rules or filters have been applied. This can be considered the 'raw' updates from a given neighbor.

2.3.3. Post updates per-neighbor

The adj-rib-in-post table is a per-neighbor table containing the routes received from the neighbor that are eligible for best-path selection after local input policy rules have been applied.

2.3.4. Pre route advertisements per-neighbor

The adj-rib-out-pre table is a per-neighbor table containing routes eligible for sending (advertising) to the neighbor before output policy rules have been applied.

2.3.5. Post route advertisements per-neighbor

The adj-rib-out-post table is a per-neighbor table containing routes eligible for sending (advertising) to the neighbor after output policy rules have been applied

3. Relation to other YANG data models

The BGP model augments the Routing Management model A YANG Data Model for Routing Management [[RFC8349](#)] which defines the notion of routing, routing protocols, and RIBs. The notion of Virtual Routing and Forwarding (VRF) is derived by using the YANG Schema Mount [[RFC8528](#)] to mount the Routing Management module under the YANG Data Model for Network Instances [[RFC8529](#)].

4. Security Considerations

The YANG module specified in this document defines a schema for data that is designed to be accessed via network management protocols such as NETCONF [[RFC6241](#)] or RESTCONF [[RFC8040](#)]. The lowest NETCONF layer is the secure transport layer, and the mandatory-to-implement secure transport is Secure Shell (SSH) [[RFC6242](#)]. The lowest RESTCONF layer is HTTPS, and the mandatory-to-implement secure transport is TLS [[RFC8446](#)]. The NETCONF Access Control Model (NACM) [[RFC8341](#)] provides the means to restrict access for particular NETCONF or RESTCONF users to a preconfigured subset of all available NETCONF or RESTCONF protocol operations and content.

There are a number of data nodes defined in this YANG module that are writable/creatable/deletable (i.e., config true, which is the default). These data nodes may be considered sensitive or vulnerable in some network environments. Write operations (e.g., edit-config) to these data nodes without proper protection can have a negative effect on network operations. These are the subtrees and data nodes and their sensitivity/vulnerability:

Some of the readable data nodes in this YANG module may be considered sensitive or vulnerable in some network environments. It is thus important to control read access (e.g., via get, get-config, or notification) to these data nodes. These are the subtrees and data nodes and their sensitivity/vulnerability:

Some of the RPC operations in this YANG module may be considered sensitive or vulnerable in some network environments. It is thus important to control access to these operations. These are the operations and their sensitivity/vulnerability:

BGP OPSEC [[RFC7454](#)] describes several policies that can be used to secure a BGP. In particular, it recommends securing the underlying TCP session and to use Generalized TTL Security Mechanism (GTSM) [[RFC5082](#)] capability to make it harder to spoof a BGP session. This module allows implementations that want to support the capability to configure a TTL value, under a feature flag. It also defines a container 'secure-session' that can be augmented with TCP-Authentication Option (TCP-AO) [[RFC5925](#)], or other methods to secure a BGP session, and will be developed in a future version of this draft.

5. IANA Considerations

This document registers three URIs and three YANG modules.

5.1. URI Registration

in the IETF XML registry [[RFC3688](#)] [[RFC3688](#)]. Following the format in [RFC 3688](#), the following registration is requested to be made:

URI: urn:ietf:params:xml:ns:yang:ietf-bgp
URI: urn:ietf:params:xml:ns:yang:ietf-bgp-policy
URI: urn:ietf:params:xml:ns:yang:ietf-bgp-types

Registrant Contact: The IESG. XML: N/A, the requested URI is an XML namespace.

5.2. YANG Module Name Registration

This document registers three YANG module in the YANG Module Names registry YANG [[RFC6020](#)].

name: ietf-bgp
namespace: urn:ietf:params:xml:ns:yang:ietf-bgp
prefix: bgp
reference: RFC XXXX

name: ietf-bgp-policy
namespace: urn:ietf:params:xml:ns:yang:ietf-bgp-policy
prefix: bp
reference: RFC XXXX

name: ietf-bgp-types
namespace: urn:ietf:params:xml:ns:yang:ietf-bgp-types
prefix: bt
reference: RFC XXXX

6. YANG modules

The modules comprising the BGP configuration and operational model are described by the YANG modules and submodules in the sections below.

The main module, `ietf-bgp.yang`, includes the following submodules:

- o `ietf-bgp-common` - defines the groupings that are common across more than one context (where contexts are neighbor, group, global)
- o `ietf-bgp-common-multiprotocol` - defines the groupings that are common across more than one context, and relate to multiprotocol BGP

- o ietf-bgp-common-structure - defines groupings that are shared by multiple contexts, but are used only to create structural elements, i.e., containers (leaf nodes are defined in separate groupings)
- o ietf-bgp-global - groupings with data specific to the global context
- o ietf-bgp-peer-group - groupings with data specific to the peer group context
- o ietf-bgp-neighbor - groupings with data specific to the neighbor context
- o ietf-bgp-rib - grouping for representing BGP RIB.

Additionally, modules include:

- o ietf-bgp-types - common type and identity definitions for BGP, including BGP policy
- o ietf-bgp-policy - BGP-specific policy data definitions for use with [[I-D.ietf-rtgwg-policy-model](#)] (described in more detail [Section 2.2](#))

7. Structure of the YANG modules

The YANG model can be subdivided between the main module for base items, types, policy data, and the RIB module.

7.1. Main module and submodules for base items

```
<CODE BEGINS> file "ietf-bgp@2019-10-03.yang"
module ietf-bgp {
  yang-version 1.1;
  namespace "urn:ietf:params:xml:ns:yang:ietf-bgp";
  prefix bgp;

  /*
   * Import and Include
   */

  import ietf-routing {
    prefix rt;
    reference
      "RFC 8349, A YANG Data Model for Routing Management
      (NMDA Version)";
  }
}
```



```
import ietf-routing-policy {
  prefix rpol;
  reference
    "RFC ZZZZ, A YANG Data Model for Routing Policy Management";
}
import ietf-interfaces {
  prefix if;
  reference
    "RFC 8343, A YANG Data Model for Interface Management.";
}
import ietf-bgp-types {
  prefix bt;
  reference
    "RFC XXXX, BGP YANG Model for Service Provider Network.";
}
import ietf-bfd-types {
  prefix bfd;
  reference
    "RFC BBBB, YANG Data Model for Bidirectional Forward Detection.";
}
import ietf-inet-types {
  prefix inet;
  reference
    "RFC 6991: Common YANG Data Types.";
}
import ietf-yang-types {
  prefix yang;
  reference
    "RFC 6991: Common YANG Data Types.";
}

include ietf-bgp-common;
include ietf-bgp-common-multiprotocol;
include ietf-bgp-common-structure;
include ietf-bgp-neighbor;
include ietf-bgp-peer-group;
include ietf-bgp-rib-types;
include ietf-bgp-rib;
include ietf-bgp-rib-ext;
include ietf-bgp-rib-attributes;
include ietf-bgp-rib-table-attributes;
include ietf-bgp-rib-tables;

organization
  "IETF IDR Working Group";
contact
  "WG Web:  <http://tools.ietf.org/wg/idr>
```


WG List: <idr@ietf.org>

Authors: Mahesh Jethanandani (mjethanandani at gmail.com),
Keyur Patel (keyur at arrcus.com),
Susan Hares (shares at ndzh.com),
Jeffrey Haas (jhaas at pfrc.org).";

description

"This module describes a YANG model for BGP protocol configuration. It is a limited subset of all of the configuration parameters available in the variety of vendor implementations, hence it is expected that it would be augmented with vendor-specific configuration data as needed. Additional modules or submodules to handle other aspects of BGP configuration, including policy, VRFs, VPNs, and additional address families are also expected.

This model supports the following BGP configuration level hierarchy:

BGP

```
|
+--> [ global BGP configuration ]
    +--> AFI / SAFI global
    +--> peer group
        +--> [ peer group config ]
        +--> AFI / SAFI [ per-AFI overrides ]
    +--> neighbor
        +--> [ neighbor config ]
        +--> [ optional pointer to peer-group ]
        +--> AFI / SAFI [ per-AFI overrides ]";
```

```
revision 2019-10-03 {
  description
    "Initial Version";
  reference
    "RFC XXXX, BGP Model for Service Provider Network ";
}
```

```
/*
 * Identity
 */
```

```
identity bgp {
  base rt:routing-protocol;
  description
    "BGP protocol.";
}
```



```
/*
 * Feature(s)
 */
feature graceful-restart {
  description
    "Graceful restart as defined in RFC 4724 is supported.";
}

feature clear-neighbors {
  description
    "Clearing of BGP neighbors is supported.";
}

feature clear-statistics {
  description
    "Clearing of BGP statistics is supported.";
}

/*
 * Containers
 */

augment "/rt:routing/rt:control-plane-protocols/"
  + "rt:control-plane-protocol" {
  when "derived-from-or-self(rt:type, 'bgp')" {
    description
      "This augmentation is valid for a routing protocol
        instance of BGP.";
  }
  description
    "BGP protocol augmentation of ietf-routing module
      control-plane-protocol.";

  container bgp {
    description
      "Top-level configuration for the BGP router";

    container global {
      presence "Enables global configuration of BGP";
      description
        "Global configuration for the BGP router";

      leaf as {
        type inet:as-number;
        mandatory true;
        description
          "Local autonomous system number of the router. Uses
            the 32-bit as-number type from the model in RFC 6991.";
      }
    }
  }
}
```



```
}

leaf identifier {
  type yang:dotted-quad;
  description
    "BGP Identifier of the router - an unsigned 32-bit,
    non-zero integer that should be unique within an AS.
    The value of the BGP Identifier for a BGP speaker is
    determined upon startup and is the same for every local
    interface and BGP peer.";
  reference
    "RFC 6286: AS-Wide Unique BGP ID for BGP-4. Section 2.1";
}

container distance {
  description
    "Administrative distance (or preference) assigned to
    routes received from different sources
    (external, internal, and local).";

  leaf external {
    type uint8 {
      range "1..255";
    }
    description
      "Administrative distance for routes learned from
      external BGP (eBGP).";
  }
  leaf internal {
    type uint8 {
      range "1..255";
    }
    description
      "Administrative distance for routes learned from
      internal BGP (iBGP).";
  }
}

container confederation {
  description
    "Configuration options specifying parameters when the
    local router is within an autonomous system which is
    part of a BGP confederation.";

  leaf enabled {
    type boolean;
    description
      "When this leaf is set to true it indicates that
```



```
        the local-AS is part of a BGP confederation";
    }

    leaf identifier {
        type inet:as-number;
        description
            "Confederation identifier for the autonomous system.";
    }

    leaf-list member-as {
        type inet:as-number;
        description
            "Remote autonomous systems that are to be treated
            as part of the local confederation.";
    }
}

container graceful-restart {
    if-feature graceful-restart;
    description
        "Parameters relating the graceful restart mechanism for
        BGP";
    uses graceful-restart-config;
}

uses global-group-use-multiple-paths;
uses route-selection-options;

container afi-safis {
    description
        "List of address-families associated with the BGP
        instance";
    list afi-safi {
        key "afi-safi-name";

        description
            "AFI,SAFI configuration available for the
            neighbour or group";

        uses mp-afi-safi-config;
        uses state;

        container graceful-restart {
            if-feature graceful-restart;
            description
                "Parameters relating to BGP graceful-restart";

            uses mp-afi-safi-graceful-restart-config;
```



```
    }

    uses route-selection-options;
    uses global-group-use-multiple-paths;
    uses mp-all-afi-safi-list-contents;
  }
}
uses rpol:apply-policy-group;
uses state;
}

container neighbors {
  description
    "Configuration for BGP neighbors";

  list neighbor {
    key "remote-address";

    description
      "List of BGP neighbors configured on the local system,
        uniquely identified by remote IPv[46] address";

    leaf local-address {
      type inet:ip-address;
      config false;
      description
        "The local IP address of this entry's BGP connection.";
    }

    leaf local-port {
      type inet:port-number {
        range "0..65535";
      }
      config false;
      description
        "The local port for the TCP connection between
          the BGP peers.";
    }
  }

  leaf peer-group {
    type leafref {
      path "../.../peer-groups/peer-group/peer-group-name";
    }
    description
      "The peer-group with which this neighbor is associated";
  }

  leaf identifier {
```



```
    type yang:dotted-quad;
    config false;
    description
      "The BGP Identifier of this entry's BGP peer.
      This entry MUST be 0.0.0.0 unless the
      sessionstate is in the openconfirm or the
      established state.";
    reference
      "RFC 4271, Section 4.2, 'BGP Identifier'.";
  }

  leaf remote-address {
    type inet:ip-address;
    description
      "The remote IP address of this entry's BGP peer.";
  }

  leaf remote-port {
    type inet:port-number {
      range "0..65535";
    }
    config false;
    description
      "The remote port for the TCP connection
      between the BGP peers. Note that the
      objects local-addr, local-port, remote-addr, and
      reemote-port provide the appropriate
      reference to the standard MIB TCP
      connection table.";
  }

  leaf enabled {
    type boolean;
    default "true";
    description
      "Whether the BGP peer is enabled. In cases where the
      enabled leaf is set to false, the local system should
      not initiate connections to the neighbor, and should
      not respond to TCP connections attempts from the
      neighbor. If the state of the BGP session is
      ESTABLISHED at the time that this leaf is set to false,
      the BGP session should be ceased.

      A transition from 'false' to 'true' will cause
      the BGP Manual Start Event to be generated.
      A transition from 'true' to 'false' will cause
      the BGP Manual Stop Event to be generated.
      This parameter can be used to restart BGP peer
```



```
        connections. Care should be used in providing
        write access to this object without adequate
        authentication.";
    reference
        "RFC 4271, Section 8.1.2.";
}

leaf ttl-security {
    if-feature "bt:ttl-security";
    type uint8;
    default "255";
    description
        "BGP Time To Live (TTL) security check.";
    reference
        "RFC 5082: The Genaralized TTL Security Mechanism
        (GTSM),
        RFC 7454: BGP Operations and Security.";
}

uses neighbor-group-config;
uses route-selection-options;

leaf session-state {
    type enumeration {
        enum idle {
            description
                "Neighbor is down, and in the Idle state of the FSM";
        }
        enum connect {
            description
                "Neighbor is down, and the session is waiting for the
                underlying transport session to be established";
        }
        enum active {
            description
                "Neighbor is down, and the local system is awaiting a
                connection from the remote peer";
        }
        enum opensent {
            description
                "Neighbor is in the process of being established. The
                local system has sent an OPEN message";
        }
        enum openconfirm {
            description
                "Neighbor is in the process of being established.
                The local system is awaiting a NOTIFICATION or
                KEEPALIVE message";
        }
    }
}
```



```
    }
    enum established {
      description
        "Neighbor is up - the BGP session with the peer is
        established";
    }
  }
  // notification does not like a non-config statement.
  // config false;
  description
    "The BGP peer connection state.";
  reference
    "RFC 4271, Section 8.1.2.";
}

leaf last-established {
  type uint64;
  config false;
  description
    "This timestamp indicates the time that the BGP session
    last transitioned in or out of the Established state.
    The value is the timestamp in seconds relative to the
    Unix Epoch (Jan 1, 1970 00:00:00 UTC).

    The BGP session uptime can be computed by clients as
    the difference between this value and the current time
    in UTC (assuming the session is in the ESTABLISHED
    state, per the session-state leaf).";
}

leaf-list supported-capabilities {
  type identityref {
    base bt:bgp-capability;
  }
  config false;
  description
    "BGP capabilities negotiated as supported with the peer";
}

leaf negotiated-hold-time {
  type decimal64 {
    fraction-digits 2;
  }
  config false;
  description
    "The negotiated hold-time for the BGP session";
}
```



```
leaf last-error {
  type binary {
    length "2";
  }
  // notification does not like non-config statement.
  // config false;
  description
    "The last error code and subcode seen by this
    peer on this connection.  If no error has
    occurred, this field is zero.  Otherwise, the
    first byte of this two byte OCTET STRING
    contains the error code, and the second byte
    contains the subcode.";
  reference
    "RFC 4271, Section 4.5.";
}

leaf fsm-established-time {
  type yang:gauge32;
  units "seconds";
  config false;
  description
    "This timer indicates how long (in
    seconds) this peer has been in the
    established state or how long
    since this peer was last in the
    established state.  It is set to zero when
    a new peer is configured or when the router is
    booted.";
  reference
    "RFC 4271, Section 8.";
}

container timers {
  description
    "Timers related to a BGP neighbor";

  uses neighbor-group-timers-config;
}

container transport {
  description
    "Transport session parameters for the BGP neighbor";

  uses neighbor-group-transport-config;
}
```



```
leaf treat-as-withdraw {
  type boolean;
  default "false";
  description
    "Specify whether erroneous UPDATE messages for which
     the NLRI can be extracted are treated as though the
     NLRI is withdrawn - avoiding session reset";
  reference
    "RFC 7606: Revised Error Handling for BGP UPDATE
     Messages.";
}

leaf erroneous-update-messages {
  type uint32;
  config false;
  description
    "The number of BGP UPDATE messages for which the
     treat-as-withdraw mechanism has been applied based on
     erroneous message contents";
}

container graceful-restart {
  if-feature graceful-restart;
  description
    "Parameters relating the graceful restart mechanism for
     BGP";

  uses graceful-restart-config;

  leaf peer-restart-time {
    type uint16 {
      range "0..4096";
    }
    config false;
    description
      "The period of time (advertised by the peer) that the
       peer expects a restart of a BGP session to take";
  }

  leaf peer-restarting {
    type boolean;
    config false;
    description
      "This flag indicates whether the remote neighbor is
       currently in the process of restarting, and hence
       received routes are currently stale";
  }
}
```



```
leaf local-restarting {
  type boolean;
  config false;
  description
    "This flag indicates whether the local neighbor is
    currently restarting. The flag is unset after all NLRI
    have been advertised to the peer, and the End-of-RIB
    (EOR) marker has been unset";
}

leaf mode {
  type enumeration {
    enum helper-only {
      description
        "The local router is operating in helper-only
        mode, and hence will not retain forwarding state
        during a local session restart, but will do so
        during a restart of the remote peer";
    }
    enum bilateral {
      description
        "The local router is operating in both helper
        mode, and hence retains forwarding state during
        a remote restart, and also maintains forwarding
        state during local session restart";
    }
    enum remote-helper {
      description
        "The local system is able to retain routes during
        restart but the remote system is only able to
        act as a helper";
    }
  }
  config false;
  description
    "This leaf indicates the mode of operation of BGP
    graceful restart with the peer";
}

uses structure-neighbor-group-logging-options;
uses structure-neighbor-group-ebgp-multihop;
uses structure-neighbor-group-route-reflector;
uses structure-neighbor-group-as-path-options;
uses structure-neighbor-group-add-paths;
uses bgp-neighbor-use-multiple-paths;
uses rpol:apply-policy-group;
```



```
container afi-safis {
  description
    "Per-address-family configuration parameters associated
    with the neighbor";
  uses bgp-neighbor-afi-safi-list;
}

container statistics {

  leaf established-transitions {
    type yang:counter64;
    config false;
    description
      "Number of transitions to the Established state for the
      neighbor session. This value is analogous to the
      bgpPeerFsmEstablishedTransitions object from the standard
      BGP-4 MIB";
    reference
      "RFC 4273 - Definitions of Managed Objects for BGP-4";
  }

  leaf fsm-established-transitions {
    type yang:counter32;
    config false;
    description
      "The total number of times the BGP FSM
      transitioned into the established state
      for this peer.";
    reference
      "RFC 4271, Section 8.";
  }

  container messages {
    config false;
    description
      "Counters for BGP messages sent and received from the
      neighbor";

    leaf in-total-messages {
      type yang:counter32;
      config false;
      description
        "The total number of messages received
        from the remote peer on this connection.";
      reference
        "RFC 4271, Section 4.";
    }
  }
}
```



```
leaf out-total-messages {
  type yang:counter32;
  config false;
  description
    "The total number of messages transmitted to
    the remote peer on this connection.";
  reference
    "RFC 4271, Section 4.";
}

leaf in-update-elapsed-time {
  type yang:gauge32;
  units "seconds";
  config false;
  description
    "Elapsed time (in seconds) since the last BGP
    UPDATE message was received from the peer.
    Each time in-updates is incremented,
    the value of this object is set to zero (0).";
  reference
    "RFC 4271, Section 4.3.
    RFC 4271, Section 8.2.2, Established state.";
}

container sent {
  description
    "Counters relating to BGP messages sent to the
    neighbor";
  uses bgp-neighbor-counters-message-types-state;
}

container received {
  description
    "Counters for BGP messages received from the
    neighbor";
  uses bgp-neighbor-counters-message-types-state;
}

container queues {
  config false;
  description
    "Counters related to queued messages associated with
    the BGP neighbor";

  leaf input {
    type uint32;
    description
```



```
        "The number of messages received from the peer
        currently queued";
    }

    leaf output {
        type uint32;
        description
            "The number of messages queued to be sent to the
            peer";
    }
}

container clear-statistics {
    if-feature "clear-statistics";

    action clear {
        input {
            leaf clear-at {
                type yang:date-and-time;
                description
                    "Time when the clear action needs to be
                    executed.";
            }
        }

        output {
            leaf clear-finished-at {
                type yang:date-and-time;
                description
                    "Time when the clear action command completed.";
            }
        }
    }
    description
        "Clear statistics action command.";
}
description
    "Statistics per neighbor.";
}

notification established {
    description
        "The established event is generated
        when the BGP FSM enters the established state.";

    leaf remote-address {
        type leafref {
```



```
    path "../../neighbor/remote-address";
  }
  description
    "IP address of the neighbor that went into established
    state.";
}

leaf last-error {
  type leafref {
    path "../../neighbor/last-error";
  }
  description
    "The last error code and subcode seen by this
    peer on this connection.  If no error has
    occurred, this field is zero.  Otherwise, the
    first byte of this two byte OCTET STRING
    contains the error code, and the second byte
    contains the subcode.";
  reference
    "RFC 4271, Section 4.5.";
}

leaf session-state {
  type leafref {
    path "../../neighbor/session-state";
  }
  description
    "The BGP peer connection state.";
  reference
    "RFC 4271, Section 8.2.2.";
}
}

notification backward-transition {
  description
    "The backward-transition event is
    generated when the BGP FSM moves from a higher
    numbered state to a lower numbered state.";

  leaf remote-addr {
    type leafref {
      path "../../neighbor/remote-address";
    }
    description
      "IP address of the neighbor that went away from
      established state.";
  }
}
```



```
leaf last-error {
  type leafref {
    path "../../neighbor/last-error";
  }
  description
    "The last error code and subcode seen by this
    peer on this connection. If no error has
    occurred, this field is zero. Otherwise, the
    first byte of this two byte OCTET STRING
    contains the error code, and the second byte
    contains the subcode.";
  reference
    "RFC 4271, Section 4.5.";
}

leaf session-state {
  type leafref {
    path "../../neighbor/session-state";
  }
  description
    "The BGP peer connection state.";
  reference
    "RFC 4271, Section 8.2.2.";
}
}

container clear-neighbors {
  if-feature "clear-neighbors";

  action clear {
    input {
      leaf clear-at {
        type yang:date-and-time;
        description
          "Time when the clear action command needs to be
          executed.";
      }
    }

    output {
      leaf clear-finished-at {
        type yang:date-and-time;
        description
          "Time when the clear action command completed.";
      }
    }
  }
}
description
```



```
        "Clear neighbors action.";
    }
}

container peer-groups {
    description
        "Configuration for BGP peer-groups";
    uses bgp-peer-group-list;
}

container interfaces {
    list interface {
        key "name";

        leaf name {
            type if:interface-ref;
            description
                "Reference to the interface within the routing instance.";
        }

        container bfd {
            if-feature "bt:bfd";

            uses bfd:client-cfg-parms;
            description
                "BFD client configuration.";
            reference
                "RFC BBBB - YANG Data Model for Bidirectional Forwarding
                Detection.";
        }
        description
            "List of interfaces within the routing instance.";
    }
    description
        "Interface specific parameters.";
}
uses rib;
}
}
}
<CODE ENDS>
```

```
<CODE BEGINS> file "ietf-bgp-common@2019-10-03.yang"
submodule ietf-bgp-common {
    yang-version "1.1";
    belongs-to ietf-bgp {
```



```
    prefix "bgp";
  }

  import ietf-bgp-types {
    prefix bt;
    reference
      "RFC XXXX: BGP Model for Service Provider Network.";
  }
  import ietf-inet-types {
    prefix inet;
    reference
      "RFC 6991: Common YANG Data Types.";
  }
  import ietf-yang-types {
    prefix yang;
    reference
      "RFC 6991: Common YANG Data Types.";
  }

  organization
    "IETF IDR Working Group";

  contact
    "WG Web:  <http://tools.ietf.org/wg/idr>
    WG List:  <idr@ietf.org>

    Authors: Mahesh Jethanandani (mjethanandani at gmail.com),
             Keyur Patel (keyur at arrcus.com),
             Susan Hares (shares at ndzh.com),
             Jeffrey Haas (jhaas at pfrc.org).";

  description
    "This sub-module contains common groupings that are common across
    multiple contexts within the BGP module. That is to say that
    they may be application to a subset of global, peer-group or
    neighbor contexts.";

  revision "2019-10-03" {
    description
      "Initial Version";
    reference
      "RFC XXXX, BGP Model for Service Provider Network.";
  }

  /*
   * Features.
   */
  feature damping {
```



```
    description
      "Weighted route dampening is supported.";
  }

  grouping neighbor-group-timers-config {
    description
      "Config parameters related to timers associated with the BGP
      peer";

    leaf connect-retry-interval {
      type uint16 {
        range "1..max";
      }
      units "seconds";
      default "120";
      description
        "Time interval (in seconds) for the ConnectRetryTimer. The
        suggested value for this timer is 120 seconds.";
      reference
        "RFC 4271, Section 8.2.2. This is the value used
        to initialize the 'ConnectRetryTimer'.";
    }

    leaf hold-time {
      type uint16 {
        range "0 | 3..65535";
      }
      units "seconds";
      default "90";
      description
        "Time interval (in seconds) for the HoldTimer established
        with the peer. When read as operational data (ro), the
        value of this object is calculated by this BGP speaker,
        using the smaller of the values in hold-time that was
        configured (rw) in the running datastore and the Hold Time
        received in the OPEN message.

        This value must be at least three seconds
        if it is not zero (0).

        If the Hold Timer has not been established
        with the peer this object MUST have a value
        of zero (0).

        If the configured value of hold-time object was
        a value of (0), then when read this object MUST have a
        value of (0) also.";
      reference
```



```
    "RFC 4271, Section 4.2.  
    RFC 4271, Section 10.";  
}  
  
leaf keepalive {  
    type uint16 {  
        range "0..21845";  
    }  
    units "seconds";  
    default "30";  
    description  
        "When used as a configuration (rw) value, this Time interval  
        (in seconds) for the KeepAlive timer configured for this BGP  
        speaker with this peer. The value of this object will only  
        determine the KEEPALIVE messages' frequency relative to  
        the value specified in configured value for hold-time.  
  
        If the value of this object is zero (0), no periodical  
        KEEPALIVE messages are sent to the peer after the BGP  
        connection has been established. The suggested value for  
        this timer is 30 seconds.;  
  
        The actual time interval for the KEEPALIVE messages is  
        indicated by operational value of keepalive. That value  
        of this object is calculated by this BGP speaker such that,  
        when compared with hold-time, it has the same proportion  
        that keepalive has, compared with hold-time. A  
        reasonable maximum value for this timer would be one third  
        of that of hold-time.";  
    reference  
        "RFC 4271, Section 4.4.  
        RFC 4271, Section 10.";  
}  
  
leaf min-as-origination-interval {  
    type uint16 {  
        range "0..max";  
    }  
    units "seconds";  
    default "15";  
    description  
        "Time interval (in seconds) for the MinASOriginationInterval  
        timer. The suggested value for this timer is 15 seconds.";  
    reference  
        "RFC 4271, Section 9.2.1.2.  
        RFC 4271, Section 10.";  
}
```



```
leaf min-route-advertisement-interval {
  type uint16 {
    range "0..max";
  }
  units "seconds";
  description
    "Time interval (in seconds) for the
     MinRouteAdvertisementInterval timer.
     The suggested value for this timer is 30
     seconds for EBGP connections and 5
     seconds for IBGP connections.";
  reference
    "RFC 4271, Section 9.2.1.1.
     RFC 4271, Section 10.";
}
}

grouping neighbor-group-config {
  description
    "Neighbor level configuration items.";

  leaf remote-as {
    type inet:as-number;
    description
      "The remote autonomous system number received in
       the BGP OPEN message.";
    reference
      "RFC 4271, Section 4.2.";
  }

  leaf peer-as {
    type inet:as-number;
    description
      "AS number of the peer.";
  }

  leaf local-as {
    type inet:as-number;
    description
      "The local autonomous system number that is to be used when
       establishing sessions with the remote peer or peer group, if
       this differs from the global BGP router autonomous system
       number.";
  }

  leaf peer-type {
    type bt:peer-type;
    description
```



```
        "Explicitly designate the peer or peer group as internal
        (iBGP) or external (eBGP).";
    }

    leaf remove-private-as {
        // could also make this a container with a flag to enable
        // remove-private and separate option. here, option implies
        // remove-private is enabled.
        type bt:remove-private-as-option;
        description
            "Remove private AS numbers from updates sent to peers - when
            this leaf is not specified, the AS_PATH attribute should be
            sent to the peer unchanged";
    }

    container route-flap-damping {
        if-feature damping;

        leaf enable {
            type boolean;
            default false;
            description
                "Enable route flap damping.";
        }

        leaf suppress-above {
            type decimal64 {
                fraction-digits 1;
            }
            default "3.0";
            description
                "This is the value of the instability metric at which
                route suppression takes place. A route is not installed
                in the forwarding information base (FIB), or announced
                even if it is reachable during the period that it is
                suppressed.";
        }

        leaf reuse-above {
            type decimal64 {
                fraction-digits 1;
            }
            default "2.0";
            description
                "This is the value of the instability metric at which a
                suppressed route becomes unsuppressed if it is reachable
                but currently suppressed. The value assigned to
                reuse-below must be less than suppress-above.";
```



```
}

leaf max-flap {
  type decimal64 {
    fraction-digits 1;
  }
  default "16.0";
  description
    "This is the upper limit of the instability metric. This
    value must be greater than the larger of 1 and
    suppress-above.";
}

leaf reach-decay {
  type yang:gauge32;
  units "seconds";
  default "300";
  description
    "This value specifies the time desired for the instability
    metric value to reach one-half of its current value when
    the route is reachable. This half-life value determines
    the rate at which the metric value is decayed. A smaller
    half-life value makes a suppressed route reusable sooner
    than a larger value.";
}

leaf unreach-decay {
  type yang:gauge32;
  units "seconds";
  default "900";
  description
    "This value acts the same as reach-decay except that it
    specifies the rate at which the instability metric is
    decayed when a route is unreachable. It should have a
    value greater than or equal to reach-decay.";
}

leaf keep-history {
  type yang:gauge32;
  units "seconds";
  default "1800";
  description
    "This value specifies the period over which the route
    flapping history is to be maintained for a given route.
    The size of the configuration arrays described below is
    directly affected by this value.";
}
description
```



```
        "Routes learned via BGP are subject to weighted route
        dampening.";
    }

    leaf send-community {
        if-feature "bt:send-communities";
        type bt:community-type;
        description
            "When supported, this tells the router to propogate any
            prefixes that are attached to this community. The value
            of 0 implies 'none'.";
    }

    leaf description {
        type string;
        description
            "An optional textual description (intended primarily for use
            with a peer or group";
    }
}

grouping neighbor-group-transport-config {
    description
        "Configuration parameters relating to the transport protocol
        used by the BGP session to the peer";

    leaf tcp-mss {
        type uint16;
        description
            "Sets the max segment size for BGP TCP sessions.";
    }

    leaf mtu-discovery {
        type boolean;
        default false;
        description
            "Turns path mtu discovery for BGP TCP sessions on (true) or
            off (false)";
    }

    leaf passive-mode {
        type boolean;
        default false;
        description
            "Wait for peers to issue requests to open a BGP session,
            rather than initiating sessions from the local router.";
    }
}
```



```
leaf local-address {
  type union {
    type inet:ip-address;
    type leafref {
      path "../../../../../interfaces/interface/name";
    }
  }
  description
    "Set the local IP (either IPv4 or IPv6) address to use for
    the session when sending BGP update messages. This may be
    expressed as either an IP address or reference to the name
    of an interface.";
}

// TODO: Better form of authentication of the BGP session should
// be added here. It can be in the form of TCP-AO [RFC 5925],
// IPsec, or any other protocol deemed desirable.
leaf auth-password {
  type string;
  description
    "Configures an MD5 authentication password for use with
    neighboring devices.";
}
}

grouping graceful-restart-config {
  description
    "Configuration parameters relating to BGP graceful restart.";

  leaf enabled {
    type boolean;
    description
      "Enable or disable the graceful-restart capability.";
  }

  leaf restart-time {
    type uint16 {
      range 0..4096;
    }
    description
      "Estimated time (in seconds) for the local BGP speaker to
      restart a session. This value is advertise in the graceful
      restart BGP capability. This is a 12-bit value, referred to
      as Restart Time in RFC4724. Per RFC4724, the suggested
      default value is <= the hold-time value.";
    reference
      "RFC 4724: Graceful Restart Mechanism for BGP.";
  }
}
```



```
leaf stale-routes-time {
  type uint32;
  description
    "An upper-bound on the time that stale routes will be
    retained by a router after a session is restarted. If an
    End-of-RIB (EOR) marker is received prior to this timer
    expiring stale-routes will be flushed upon its receipt - if
    no EOR is received, then when this timer expires stale paths
    will be purged. This timer is referred to as the
    Selection_Deferral_Timer in RFC4724";
  reference
    "RFC 4724: Graceful Restart Mechanism for BGP.";
}

leaf helper-only {
  type boolean;
  default true;
  description
    "Enable graceful-restart in helper mode only. When this leaf
    is set, the local system does not retain forwarding its own
    state during a restart, but supports procedures for the
    receiving speaker, as defined in RFC4724.";
  reference
    "RFC 4724: Graceful Restart Mechanism for BGP.";
}

grouping global-group-use-multiple-paths {
  description
    "Common grouping used for both global and groups which provides
    configuration and state parameters relating to use of multiple
    paths";

  container use-multiple-paths {
    description
      "Parameters related to the use of multiple paths for the
      same NLRI";

    leaf enabled {
      type boolean;
      default false;
      description
        "Whether the use of multiple paths for the same NLRI is
        enabled for the neighbor. This value is overridden by any
        more specific configuration value.";
    }
  }

  container ebgp {
```



```
    description
      "Multi-Path parameters for eBGP";

    leaf allow-multiple-as {
      type boolean;
      default "false";
      description
        "Allow multi-path to use paths from different neighboring
        ASes. The default is to only consider multiple paths
        from the same neighboring AS.";
    }

    leaf maximum-paths {
      type uint32;
      default 1;
      description
        "Maximum number of parallel paths to consider when using
        BGP multi-path. The default is use a single path.";
    }
  }

  container ibgp {
    description
      "Multi-Path parameters for iBGP";

    leaf maximum-paths {
      type uint32;
      default 1;
      description
        "Maximum number of parallel paths to consider when using
        iBGP multi-path. The default is to use a single path";
    }
  }
}

grouping route-selection-options {
  description
    "Configuration and state relating to route selection options";

  container route-selection-options {
    description
      "Parameters relating to options for route selection";

    leaf always-compare-med {
      type boolean;
      default "false";
      description
```



```
        "Compare multi-exit discriminator (MED) value from
        different ASes when selecting the best route. The default
        behavior is to only compare MEDs for paths received from
        the same AS.";
    }

    leaf ignore-as-path-length {
        type boolean;
        default "false";
        description
            "Ignore the AS path length when selecting the best path.
            The default is to use the AS path length and prefer paths
            with shorter length.";
    }

    leaf external-compare-router-id {
        type boolean;
        default "true";
        description
            "When comparing similar routes received from external BGP
            peers, use the router-id as a criterion to select the
            active path.";
    }

    leaf advertise-inactive-routes {
        type boolean;
        default "false";
        description
            "Advertise inactive routes to external peers. The default
            is to only advertise active routes.";
        reference
            "I-D.ietf-idr-best-external: Advertisement of the best
            external route in BGP.";
    }

    leaf enable-aigp {
        type boolean;
        default false;
        description
            "Flag to enable sending / receiving accumulated IGP
            attribute in routing updates";
        reference
            "RFC 7311: AIGP Metric Attribute for BGP.";
    }

    leaf ignore-next-hop-igp-metric {
        type boolean;
        default "false";
    }
```



```
        description
            "Ignore the IGP metric to the next-hop when calculating BGP
            best-path. The default is to select the route for which
            the metric to the next-hop is lowest";
    }

    leaf enable-med {
        type boolean;
        default false;
        description
            "Flag to enable sending/receiving of MED metric attribute
            in routing updates.";
    }
}

grouping state {
    description
        "Grouping containing common counters relating to prefixes and
        paths";

    leaf total-paths {
        type uint32;
        config false;
        description
            "Total number of BGP paths within the context";
    }

    leaf total-prefixes {
        type uint32;
        config false;
        description
            "Total number of BGP prefixes received within the context";
    }
}
}
<CODE ENDS>
```

```
<CODE BEGINS> file "ietf-bgp-common-multiprotocol@2019-10-03.yang"
submodule ietf-bgp-common-multiprotocol {
    yang-version "1.1";
    belongs-to ietf-bgp {
        prefix "bgp";
    }

    import ietf-bgp-types {
        prefix bt;
```



```
}
import ietf-routing-policy {
  prefix rpol;
}

include ietf-bgp-common;

// meta
organization
  "IETF IDR Working Group";

contact
  "WG Web:   <http://tools.ietf.org/wg/idr>
  WG List:  <idr@ietf.org>

  Authors: Mahesh Jethanandani (mjethanandani at gmail.com),
           Keyur Patel (keyur at arccus.com),
           Susan Hares (shares at ndzh.com)";

description
  "This sub-module contains groupings that are related to support
  for multiple protocols in BGP. The groupings are common across
  multiple contexts.";

revision "2019-10-03" {
  description
    "Initial Version";
  reference
    "RFC XXX, BGP Model for Service Provider Network.";
}

grouping mp-afi-safi-graceful-restart-config {
  description
    "BGP graceful restart parameters that apply on a per-AFI-SAFI
    basis";

  leaf enabled {
    type boolean;
    default false;
    description
      "This leaf indicates whether graceful-restart is enabled for
      this AFI-SAFI";
  }
}

grouping mp-afi-safi-config {
  description
    "Configuration parameters used for all BGP AFI-SAFIs";
```



```
leaf afi-safi-name {
  type identityref {
    base "bt:afi-safi-type";
  }
  description "AFI,SAFI";
}

leaf enabled {
  type boolean;
  default false;
  description
    "This leaf indicates whether the IPv4 Unicast AFI,SAFI is
    enabled for the neighbour or group";
}
}

grouping mp-all-afi-safi-list-contents {
  description
    "A common grouping used for contents of the list that is used
    for AFI-SAFI entries";

  // import and export policy included for the afi/safi
  uses rpol:apply-policy-group;

  container ipv4-unicast {
    when "../afi-safi-name = 'bt:ipv4-unicast'" {
      description
        "Include this container for IPv4 Unicast specific
        configuration";
    }

    description
      "IPv4 unicast configuration options";

    // include common IPv[46] unicast options
    uses mp-ipv4-ipv6-unicast-common;

    // placeholder for IPv4 unicast specific configuration
  }

  container ipv6-unicast {
    when "../afi-safi-name = 'bt:ipv6-unicast'" {
      description
        "Include this container for IPv6 Unicast specific
        configuration";
    }

    description
```



```
    "IPv6 unicast configuration options";

    // include common IPv[46] unicast options
    uses mp-ipv4-ipv6-unicast-common;

    // placeholder for IPv6 unicast specific configuration
    // options
}

container ipv4-labeled-unicast {
  when "../afi-safi-name = 'bt:ipv4-labeled-unicast'" {
    description
      "Include this container for IPv4 Labeled Unicast specific
      configuration";
  }

  description
    "IPv4 Labeled Unicast configuration options";

  uses mp-all-afi-safi-common;

  // placeholder for IPv4 Labeled Unicast specific config
  // options
}

container ipv6-labeled-unicast {
  when "../afi-safi-name = 'bt:ipv6-labeled-unicast'" {
    description
      "Include this container for IPv6 Labeled Unicast specific
      configuration";
  }

  description
    "IPv6 Labeled Unicast configuration options";

  uses mp-all-afi-safi-common;

  // placeholder for IPv6 Labeled Unicast specific config
  // options.
}

container l3vpn-ipv4-unicast {
  when "../afi-safi-name = 'bt:l3vpn-ipv4-unicast'" {
    description
      "Include this container for IPv4 Unicast L3VPN specific
      configuration";
  }
}
```



```
description
  "Unicast IPv4 L3VPN configuration options";

// include common L3VPN configuration options
uses mp-l3vpn-ipv4-ipv6-unicast-common;

// placeholder for IPv4 Unicast L3VPN specific config options.
}

container l3vpn-ipv6-unicast {
  when "../afi-safi-name = 'bt:l3vpn-ipv6-unicast'" {
    description
      "Include this container for unicast IPv6 L3VPN specific
        configuration";
  }

  description
    "Unicast IPv6 L3VPN configuration options";

  // include common L3VPN configuration options
  uses mp-l3vpn-ipv4-ipv6-unicast-common;

  // placeholder for IPv6 Unicast L3VPN specific configuration
  // options
}

container l3vpn-ipv4-multicast {
  when "../afi-safi-name = 'bt:l3vpn-ipv4-multicast'" {
    description
      "Include this container for multicast IPv6 L3VPN specific
        configuration";
  }

  description
    "Multicast IPv4 L3VPN configuration options";

  // include common L3VPN multicast options
  uses mp-l3vpn-ipv4-ipv6-multicast-common;

  // placeholder for IPv4 Multicast L3VPN specific configuration
  // options
}

container l3vpn-ipv6-multicast {
  when "../afi-safi-name = 'bt:l3vpn-ipv6-multicast'" {
    description
      "Include this container for multicast IPv6 L3VPN specific
        configuration";
```



```
    }
    description
      "Multicast IPv6 L3VPN configuration options";

    // include common L3VPN multicast options
    uses mp-l3vpn-ipv4-ipv6-multicast-common;

    // placeholder for IPv6 Multicast L3VPN specific configuration
    // options
  }

  container l2vpn-vpls {
    when "../afi-safi-name = 'bt:l2vpn-vpls'" {
      description
        "Include this container for BGP-signalled VPLS specific
        configuration";
    }

    description
      "BGP-signalled VPLS configuration options";

    // include common L2VPN options
    uses mp-l2vpn-common;

    // placeholder for BGP-signalled VPLS specific configuration
    // options
  }

  container l2vpn-evpn {
    when "../afi-safi-name = 'bt:l2vpn-evpn'" {
      description
        "Include this container for BGP EVPN specific
        configuration";
    }

    description
      "BGP EVPN configuration options";

    // include common L2VPN options
    uses mp-l2vpn-common;

    // placeholder for BGP EVPN specific configuration options
  }
}

// Common groupings across multiple AFI,SAFIs
grouping mp-all-afi-safi-common {
  description
```



```
"Grouping for configuration common to all AFI,SAFI";

container prefix-limit {
  description
    "Parameters relating to the prefix limit for the AFI-SAFI";
  leaf max-prefixes {
    type uint32;
    description
      "Maximum number of prefixes that will be accepted from the
      neighbour";
  }
  leaf shutdown-threshold-pct {
    type bt:percentage;
    description
      "Threshold on number of prefixes that can be received from
      a neighbour before generation of warning messages or log
      entries. Expressed as a percentage of max-prefixes";
  }
  leaf restart-timer {
    type uint32;
    units "seconds";
    description
      "Time interval in seconds after which the BGP session is
      re-established after being torn down due to exceeding the
      max-prefix limit.";
  }
}

grouping mp-ipv4-ipv6-unicast-common {
  description
    "Common configuration that is applicable for IPv4 and IPv6
    unicast";

  // include common afi-safi options.
  uses mp-all-afi-safi-common;

  // configuration options that are specific to IPv[46] unicast
  leaf send-default-route {
    type boolean;
    default "false";
    description
      "If set to true, send the default-route to the neighbour(s)";
  }
}

grouping mp-l3vpn-ipv4-ipv6-unicast-common {
```



```
    description
      "Common configuration applied across L3VPN for IPv4
      and IPv6";

    // placeholder -- specific configuration options that are generic
    // across IPv[46] unicast address families.
    uses mp-all-afi-safi-common;
  }

  grouping mp-l3vpn-ipv4-ipv6-multicast-common {
    description
      "Common configuration applied across L3VPN for IPv4
      and IPv6";

    // placeholder -- specific configuration options that are
    // generic across IPv[46] multicast address families.
    uses mp-all-afi-safi-common;
  }

  grouping mp-l2vpn-common {
    description
      "Common configuration applied across L2VPN address
      families";

    // placeholder -- specific configuration options that are
    // generic across L2VPN address families
    uses mp-all-afi-safi-common;
  }

  // Config groupings for common groups
  grouping mp-all-afi-safi-common-prefix-limit-config {
    description
      "Configuration parameters relating to prefix-limits for an
      AFI-SAFI";

  }
}
<CODE ENDS>
```

```
<CODE BEGINS> file "ietf-bgp-common-structure@2019-10-03.yang"
submodule ietf-bgp-common-structure {
  yang-version "1.1";
  belongs-to ietf-bgp {
    prefix "bgp";
  }

  import ietf-bgp-types { prefix bt; }
```



```
import ietf-routing-policy { prefix rpol; }
include ietf-bgp-common-multiprotocol;
include ietf-bgp-common;

// meta
organization
  "IETF IDR Working Group";

contact
  "WG Web:  <http://tools.ietf.org/wg/idr>
  WG List:  <idr@ietf.org>

  Authors: Mahesh Jethanandani (mjethanandani at gmail.com),
           Keyur Patel (keyur at arrcus.com),
           Susan Hares (shares at ndzh.com),
           Jeffrey Haas (jhaas at pfrc.org).";

description
  "This sub-module contains groupings that are common across
  multiple BGP contexts and provide structure around other
  primitive groupings.";

revision "2019-10-03" {
  description
    "Initial Version";
  reference
    "RFC XXX, BGP Model for Service Provider Network.";
}

grouping structure-neighbor-group-logging-options {
  description
    "Structural grouping used to include error handling
    configuration and state for both BGP neighbors and groups";

  container logging-options {
    description
      "Logging options for events related to the BGP neighbor or
      group";

    leaf log-neighbor-state-changes {
      type boolean;
      default "true";
      description
        "Configure logging of peer state changes.  Default is to
        enable logging of peer state changes.

        Note: Documenting out of ESTABLISHED state is desirable,
```



```
        but documenting all backward transitions is
        problematic, and should be avoided.";
    }
}
}

grouping structure-neighbor-group-ebgp-multihop {
    description
        "Structural grouping used to include eBGP multi-hop
        configuration and state for both BGP neighbors and peer
        groups";

    container ebgp-multihop {
        description
            "eBGP multi-hop parameters for the BGPgroup";

        leaf enabled {
            type boolean;
            default "false";
            description
                "When enabled the referenced group or neighbors are
                permitted to be indirectly connected - including cases
                where the TTL can be decremented between the BGP peers";
        }

        leaf multihop-ttl {
            type uint8;
            description
                "Time-to-live value to use when packets are sent to the
                referenced group or neighbors and ebgp-multihop is
                enabled";
        }
    }
}

grouping structure-neighbor-group-route-reflector {
    description
        "Structural grouping used to include route reflector
        configuration and state for both BGP neighbors and peer
        groups";

    container route-reflector {
        description
            "Route reflector parameters for the BGPgroup";
        reference
            "RFC 4456: BGP Route Reflection.";

        leaf route-reflector-cluster-id {
```



```
    when "../route-reflector-client = 'false'";
    type bt:rr-cluster-id-type;
    description
      "Route Reflector cluster id to use when local router is
       configured as a route reflector.  Commonly set at the
       group level, but allows a different cluster id to be set
       for each neighbor.";
    reference
      "RFC 4456: BGP Route Reflection: An Alternative to
       Full Mesh.";
  }

  leaf no-client-reflect {
    type boolean;
    default "false";
    description
      "When set to 'true', this disables route redistribution
       by the Route Reflector. It is set 'true' when the client is
       fully meshed to prevent sending of redundant route
       advertisements.";
    reference
      "TODO: Add reference when IETF writes a draft describing
       this.";
  }

  leaf route-reflector-client {
    type boolean;
    default "false";
    description
      "Configure the neighbor as a route reflector client.";
    reference
      "RFC 4456: BGP Route Reflection: An Alternative to
       Full Mesh.";
  }
}

grouping structure-neighbor-group-as-path-options {
  description
    "Structural grouping used to include AS_PATH manipulation
     configuration and state for both BGP neighbors and peer
     groups";

  container as-path-options {
    description
      "AS_PATH manipulation parameters for the BGP neighbor or
       group";
```



```
    leaf allow-own-as {
      type uint8;
      default 0;
      description
        "Specify the number of occurrences of the local BGP
        speaker's AS that can occur within the AS_PATH before it
        is rejected.";
    }

    leaf replace-peer-as {
      type boolean;
      default "false";
      description
        "Replace occurrences of the peer's AS in the AS_PATH with
        the local autonomous system number";
    }
  }
}

grouping structure-neighbor-group-add-paths {
  description
    "Structural grouping used to include ADD-PATHS configuration
    and state for both BGP neighbors and peer groups";

  container add-paths {
    description
      "Parameters relating to the advertisement and receipt of
      multiple paths for a single NLRI (add-paths)";
    reference
      "RFC 7911: ADD-PATH.";

    leaf receive {
      type boolean;
      default false;
      description
        "Enable ability to receive multiple path advertisements for
        an NLRI from the neighbor or group";
    }

    choice send {
      default "all";
      description
        "Choice of sending the max. number of paths or to send all.";

      case max {
        leaf max {
          type uint8;
          description
```



```
        "The maximum number of paths to advertise to neighbors
        for a single NLRI";
    }
}

case all {
  leaf all {
    type empty;
    description
      "Send all the path advertisements to neighbors for a
      single NLRI.";
  }
}

leaf eligible-prefix-policy {
  type leafref {
    path "/rpol:routing-policy/rpol:policy-definitions/" +
      "rpol:policy-definition/rpol:name";
  }
  description
    "A reference to a routing policy which can be used to
    restrict the prefixes for which add-paths is enabled";
}
}
}
}
}
<CODE ENDS>
```

```
<CODE BEGINS> file "ietf-bgp-peer-group@2019-10-03.yang"
submodule ietf-bgp-peer-group {
  yang-version "1.1";
  belongs-to ietf-bgp {
    prefix "bgp";
  }

  import ietf-routing-policy {
    prefix rpol;
  }

  // Include the common submodule
  include ietf-bgp-common;
  include ietf-bgp-common-multiprotocol;
  include ietf-bgp-common-structure;

  // meta
  organization
```



```
"IETF IDR Working Group";
```

```
contact
```

```
"WG Web:  <http://tools.ietf.org/wg/idr>
```

```
WG List:  <idr@ietf.org>
```

```
Authors: Mahesh Jethanandani (mjethanandani at gmail.com),  
         Keyur Patel (keyur at arrcus.com),  
         Susan Hares (shares at ndzh.com),  
         Jeffrey Haas (jhaas at pfrc.org).";
```

```
description
```

```
"This sub-module contains groupings that are specific to the  
peer-group context of the BGP module.";
```

```
revision "2019-10-03" {
```

```
  description
```

```
    "Initial Version";
```

```
  reference
```

```
    "RFC XXX, BGP Model for Service Provider Network.";
```

```
}
```

```
grouping bgp-peer-group-afi-safi-list {
```

```
  description
```

```
    "List of address-families associated with the BGP peer-group";
```

```
  list afi-safi {
```

```
    key "afi-safi-name";
```

```
    description
```

```
      "AFI, SAFI configuration available for the  
      neighbour or group";
```

```
    uses mp-afi-safi-config;
```

```
    container graceful-restart {
```

```
      if-feature graceful-restart;
```

```
      description
```

```
        "Parameters relating to BGP graceful-restart";
```

```
      uses mp-afi-safi-graceful-restart-config;
```

```
    }
```

```
    uses route-selection-options;
```

```
    uses global-group-use-multiple-paths;
```

```
    uses mp-all-afi-safi-list-contents;
```

```
  }
```

```
}
```



```
grouping bgp-peer-group-base {
  description
    "Parameters related to a BGP group.";

  leaf peer-group-name {
    type string;
    description
      "Name of the BGP peer-group";
  }

  uses neighbor-group-config;

  container timers {
    description
      "Timers related to a BGP peer-group.";

    uses neighbor-group-timers-config;
  }

  container transport {
    description
      "Transport session parameters for the BGP peer-group.";

    uses neighbor-group-transport-config;
  }

  container graceful-restart {
    if-feature graceful-restart;
    description
      "Parameters relating the graceful restart mechanism for BGP.";

    uses graceful-restart-config;
  }

  uses structure-neighbor-group-ebgp-multihop;
  uses structure-neighbor-group-route-reflector;
  uses structure-neighbor-group-as-path-options;
  uses structure-neighbor-group-add-paths;
  uses global-group-use-multiple-paths;
  uses rpol:apply-policy-group;

  container afi-safis {
    description
      "Per-address-family configuration parameters associated with
      the group.";
    uses bgp-peer-group-afi-safi-list;
  }
}
```



```
grouping bgp-peer-group-list {
  description
    "The list of BGP peer groups";

  list peer-group {
    key "peer-group-name";
    description
      "List of BGP peer-groups configured on the local system -
      uniquely identified by peer-group name";

    uses bgp-peer-group-base;
  }
}
}
<CODE ENDS>
```

```
<CODE BEGINS> file "ietf-bgp-neighbor@2019-10-03.yang"
submodule ietf-bgp-neighbor {
  yang-version "1.1";
  belongs-to ietf-bgp {
    prefix "bgp";
  }

  // Include the common submodule
  include ietf-bgp-common;
  include ietf-bgp-common-multiprotocol;
  include ietf-bgp-peer-group;
  include ietf-bgp-common-structure;

  // meta
  organization
    "IETF IDR Working Group";

  contact
    "WG Web:  <http://tools.ietf.org/wg/idr>
    WG List:  <idr@ietf.org>

    Authors: Mahesh Jethanandani (mjethanandani at gmail.com),
             Keyur Patel (keyur at arrcus.com),
             Susan Hares (shares at ndzh.com),
             Jeffrey Haas (jhaas at pfrc.org).";

  description
    "This sub-module contains groupings that are specific to the
    neighbor context of the BGP module.";

  revision "2019-10-03" {
```



```
    description
      "Initial Version";
    reference
      "RFC XXX, BGP Model for Service Provider Network.";
  }

  grouping bgp-neighbor-use-multiple-paths {
    description
      "Multi-path configuration and state applicable to a BGP
      neighbor";

    container use-multiple-paths {
      description
        "Parameters related to the use of multiple-paths for the same
        NLRI when they are received only from this neighbor";

      leaf enabled {
        type boolean;
        default false;
        description
          "Whether the use of multiple paths for the same NLRI is
          enabled for the neighbor. This value is overridden by any
          more specific configuration value.";
      }
    }

    container ebgp {
      description
        "Multi-path configuration for eBGP";

      leaf allow-multiple-as {
        type boolean;
        default "false";
        description
          "Allow multi-path to use paths from different neighboring
          ASes. The default is to only consider multiple paths
          from the same neighboring AS.";
      }
    }
  }
}

grouping bgp-neighbor-counters-message-types-state {
  description
    "Grouping of BGP message types, included for re-use across
    counters";

  leaf updates-received {
    type uint64;
```



```
    description
      "Number of BGP UPDATE messages received from this neighbor.";
    reference
      "RFC 4273: bgpPeerInUpdates.";
  }

  leaf updates-sent {
    type uint64;
    description
      "Number of BGP UPDATE messages sent to this neighbor";
    reference
      "RFC 4273 - bgpPeerOutUpdates";
  }

  leaf messages-received {
    type uint64;
    description
      "Number of BGP messages received from this neighbor";
    reference
      "RFC 4273 - bgpPeerInTotalMessages";
  }

  leaf messages-sent {
    type uint64;
    description
      "Number of BGP messages sent to this neighbor";
    reference
      "RFC 4273 - bgpPeerOutTotalMessages";
  }

  leaf notification {
    type uint64;
    description
      "Number of BGP NOTIFICATION messages indicating an error
        condition has occurred exchanged.";
  }
}

grouping bgp-neighbor-afi-safi-list {
  description
    "List of address-families associated with the BGP neighbor";

  list afi-safi {
    key "afi-safi-name";

    description
      "AFI, SAFI configuration available for the neighbor or
        group";
  }
}
```



```
uses mp-afi-safi-config;

leaf active {
  type boolean;
  config false;
  description
    "This value indicates whether a particular AFI-SAFI has
    been successfully negotiated with the peer. An AFI-SAFI may
    be enabled in the current running configuration, but a
    session restart may be required in order to negotiate the
    new capability.";
}

container prefixes {
  config false;
  description
    "Prefix counters for the BGP session";

  leaf received {
    type uint32;
    description
      "The number of prefixes received from the neighbor";
  }

  leaf sent {
    type uint32;
    description
      "The number of prefixes advertised to the neighbor";
  }

  leaf installed {
    type uint32;
    description
      "The number of advertised prefixes installed in the
      Loc-RIB";
  }
}

container graceful-restart {
  if-feature bgp:graceful-restart;
  description
    "Parameters relating to BGP graceful-restart";

  uses mp-afi-safi-graceful-restart-config;

  leaf received {
    type boolean;
    config false;
```



```
        description
          "This leaf indicates whether the neighbor advertised the
           ability to support graceful-restart for this AFI-SAFI";
      }

      leaf advertised {
        type boolean;
        config false;
        description
          "This leaf indicates whether the ability to support
           graceful-restart has been advertised to the peer";
      }
    }

    uses mp-all-afi-safi-list-contents;
    uses bgp-neighbor-use-multiple-paths;
  }
}
<CODE ENDS>
```

7.2. BGP types

```
<CODE BEGINS> file "ietf-bgp-types@2019-10-03.yang"
module ietf-bgp-types {
  yang-version "1.1";
  namespace "urn:ietf:params:xml:ns:yang:ietf-bgp-types";

  prefix "bt";

  import ietf-inet-types {
    prefix inet;
  }

  // meta
  organization
    "IETF IDR Working Group";

  contact
    "WG Web:  <http://tools.ietf.org/wg/idr>
     WG List: <idr@ietf.org>

    Authors: Mahesh Jethanandani (mjethanandani at gmail.com),
             Keyur Patel (keyur at arrcus.com),
             Susan Hares (shares at ndzh.com),
             Jeffrey Haas (jhaas at pfrc.org).";
```



```
description
  "This module contains general data definitions for use in BGP
  policy. It can be imported by modules that make use of BGP
  attributes";

revision "2019-10-03" {
  description
    "Initial Version";
  reference
    "RFC XXX, BGP Model for Service Provider Network.";
}

identity bgp-capability {
  description "Base identity for a BGP capability";
}

identity mp-bgp {
  base bgp-capability;
  description
    "Multi-protocol extensions to BGP";
  reference
    "RFC 4760";
}

identity route-refresh {
  base bgp-capability;
  description
    "The BGP route-refresh functionality";
  reference
    "RFC2918";
}

identity asn32 {
  base bgp-capability;
  description
    "4-byte (32-bit) AS number functionality";
  reference
    "RFC6793";
}

identity graceful-restart {
  base bgp-capability;
  description
    "Graceful restart functionality";
  reference
    "RFC4724";
}
```



```
identity add-paths {
  base bgp-capability;
  description
    "BGP add-paths";
  reference
    "RFC 7911";
}

identity afi-safi-type {
  description
    "Base identity type for AFI,SAFI tuples for BGP-4";
  reference
    "RFC4760 - multi-protocol extensions for BGP-4";
}

identity ipv4-unicast {
  base afi-safi-type;
  description
    "IPv4 unicast (AFI,SAFI = 1,1)";
  reference
    "RFC4760";
}

identity ipv6-unicast {
  base afi-safi-type;
  description
    "IPv6 unicast (AFI,SAFI = 2,1)";
  reference
    "RFC4760";
}

identity ipv4-labeled-unicast {
  base afi-safi-type;
  description
    "Labeled IPv4 unicast (AFI,SAFI = 1,4)";
  reference
    "RFC3107";
}

identity ipv6-labeled-unicast {
  base afi-safi-type;
  description
    "Labeled IPv6 unicast (AFI,SAFI = 2,4)";
  reference
    "RFC3107";
}

identity l3vpn-ipv4-unicast {
```



```
    base afi-safi-type;
    description
      "Unicast IPv4 MPLS L3VPN (AFI,SAFI = 1,128)";
    reference
      "RFC4364";
  }

  identity l3vpn-ipv6-unicast {
    base afi-safi-type;
    description
      "Unicast IPv6 MPLS L3VPN (AFI,SAFI = 2,128)";
    reference
      "RFC4659";
  }

  identity l3vpn-ipv4-multicast {
    base afi-safi-type;
    description
      "Multicast IPv4 MPLS L3VPN (AFI,SAFI = 1,129)";
    reference
      "RFC6514";
  }

  identity l3vpn-ipv6-multicast {
    base afi-safi-type;
    description
      "Multicast IPv6 MPLS L3VPN (AFI,SAFI = 2,129)";
    reference
      "RFC6514";
  }

  identity l2vpn-vpls {
    base afi-safi-type;
    description
      "BGP-signalled VPLS (AFI,SAFI = 25,65)";
    reference
      "RFC4761";
  }

  identity l2vpn-evpn {
    base afi-safi-type;
    description
      "BGP MPLS Based Ethernet VPN (AFI,SAFI = 25,70)";
  }

  identity bgp-well-known-std-community {
    description
      "Base identity for reserved communities within the standard
```



```
        community space defined by RFC1997. These communities must
        fall within the range 0xFFFF0000 to 0xFFFFFFFF";
    reference
        "RFC 1997: BGP Communities Attribute.";
}

identity no-export {
    base bgp-well-known-std-community;
    description
        "Do not export NLRI received carrying this community outside
        the bounds of this autonomous system, or this confederation if
        the local autonomous system is a confederation member AS. This
        community has a value of 0xFFFFFFFF01.";
    reference
        "RFC 1997: BGP Communities Attribute.";
}

identity no-advertise {
    base bgp-well-known-std-community;
    description
        "All NLRI received carrying this community must not be
        advertised to other BGP peers. This community has a value of
        0xFFFFFFFF02.";
    reference
        "RFC 1997: BGP Communities Attribute.";
}

identity no-export-subconfed {
    base bgp-well-known-std-community;
    description
        "All NLRI received carrying this community must not be
        advertised to external BGP peers - including over confederation
        sub-AS boundaries. This community has a value of 0xFFFFFFFF03.";
    reference
        "RFC 1997: BGP Communities Attribute.";
}

identity no-peer {
    base bgp-well-known-std-community;
    description
        "An autonomous system receiving NLRI tagged with this community
        is advised not to re-advertise the NLRI to external bi-lateral
        peer autonomous systems. An AS may also filter received NLRI
        from bilateral peer sessions when they are tagged with this
        community value";
    reference
        "RFC 3765: NOPEER Community for BGP.";
}
```



```
identity as-path-segment-type {
  description
    "Base AS Path Segment Type. In [BGP-4], the path segment type
    is a 1-octet field with the following values defined.";
  reference
    "RFC 4271: A Border Gateway Protocol 4 (BGP-4), Section 4.3.";
}

identity as-set {
  base as-path-segment-type;
  description
    "Unordered set of autonomous systems that a route in the UPDATE
    message has traversed.";
  reference
    "RFC 4271: A Border Gateway Protocol 4 (BGP-4), Section 4.3.";
}

identity as-sequence {
  base as-path-segment-type;
  description
    "Ordered set of autonomous systems that a route in the UPDATE
    message has traversed.";
  reference
    "RFC 4271: A Border Gateway Protocol 4 (BGP-4), Section 4.3.";
}

identity as-confed-sequence {
  base as-path-segment-type;
  description
    "Ordered set of Member Autonomous Systems in the local
    confederation that the UPDATE message has traversed.";
  reference
    "RFC 5065, Autonomous System Configuration for BGP.";
}

identity as-confed-set {
  base as-path-segment-type;
  description
    "Unordered set of Member Autonomous Systems in the local
    confederation that the UPDATE message has traversed.";
  reference
    "RFC 5065, Autonomous System Configuration for BGP.";
}

/*
 * Features.
 */
feature send-communities {
```



```
    description
      "Enable the propogation of communities.";
  }

  feature ttl-security {
    description
      "BGP Time To Live (TTL) security check support.";
    reference
      "RFC 5082, The Generalized TTL Security Mechanism (GTSM)";
  }

  feature bfd {
    description
      "Support for BFD detection of BGP neighbor reachability.";
    reference
      "RFC 5880, Bidirectional Forward Detection (BFD),
      RFC 5881, Bidirectional Forward Detection for IPv4 and IPv6
      (Single Hop).
      RFC 5883, Bidirectional Forwarding Detection (BFD) for Multihop
      Paths";
  }

  typedef bgp-session-direction {
    type enumeration {
      enum INBOUND {
        description
          "Refers to all NLRI received from the BGP peer";
      }
      enum OUTBOUND {
        description
          "Refers to all NLRI advertised to the BGP peer";
      }
    }
    description
      "Type to describe the direction of NLRI transmission";
  }

  typedef bgp-well-known-community-type {
    type identityref {
      base bgp-well-known-std-community;
    }
    description
      "Type definition for well-known IETF community attribute
      values";
    reference
      "IANA Border Gateway Protocol (BGP) Well Known Communities";
  }
```



```

typedef bgp-std-community-type {
    // TODO: further refine restrictions and allowed patterns
    // 4-octet value:
    // <as number> 2 octets
    // <community value> 2 octets
    type union {
        type uint32 {
            // per RFC 1997, 0x00000000 - 0x0000FFFF and 0xFFFF0000 -
            // 0xFFFFFFFF are reserved
            range "65536..4294901759"; // 0x00010000..0xFFFEFFFF
        }
        type string {
            pattern '([0-9]+:[0-9]+)';
        }
    }
    description
        "Type definition for standard community attributes";
    reference
        "RFC 1997 - BGP Communities Attribute";
}

typedef bgp-ext-community-type {
    // TODO: needs more work to make this more precise given the
    // variability of extended community attribute specifications
    // 8-octet value:
    // <type> 2 octets
    // <value> 6 octets

    type union {
        type string {
            // Type 1: 2-octet global and 4-octet local
            //      (AS number)      (Integer)
            pattern '(6[0-5][0-5][0-3][0-5]|[1-5][0-9]{4}|' +
                '[1-9][0-9]{1,4}|[0-9]):' +
                '(4[0-2][0-9][0-4][0-9][0-6][0-7][0-2][0-9][0-6]|' +
                '[1-3][0-9]{9}|[1-9]([0-9]{1,7})?[0-9]|[1-9])';
        }
        type string {
            // Type 2: 4-octet global and 2-octet local
            //      (ipv4-address)      (integer)
            pattern '((([0-9]|[1-9][0-9]|1[0-9][0-9]|2[0-4][0-9]|' +
                '25[0-5])\.){3}([0-9]|[1-9][0-9]|1[0-9][0-9]|' +
                '2[0-4][0-9]|25[0-5]):' +
                '(6[0-5][0-5][0-3][0-5]|[1-5][0-9]{4}|' +
                '[1-9][0-9]{1,4}|[0-9])';
        }
        type string {
            // route-target with Type 1

```



```

    // route-target:(ASN):(local-part)
    pattern 'route\-target:(6[0-5][0-5][0-3][0-5]|' +
        '[1-5][0-9]{4}|[1-9][0-9]{1,4}|[0-9]):' +
        '(4[0-2][0-9][0-4][0-9][0-6][0-7][0-2][0-9][0-6]|' +
        '[1-3][0-9]{9}|[1-9]([0-9]{1,7})?[0-9]|[1-9])';
}
type string {
    // route-target with Type 2
    // route-target:(IPv4):(local-part)
    pattern 'route\-target:' +
        '([0-9]|[1-9][0-9]|1[0-9][0-9]|2[0-4][0-9]|' +
        '25[0-5])\.){3}([0-9]|[1-9][0-9]|1[0-9][0-9]|' +
        '2[0-4][0-9]|25[0-5]):' +
        '(6[0-5][0-5][0-3][0-5]|[1-5][0-9]{4}|' +
        '[1-9][0-9]{1,4}|[0-9])';
}
type string {
    // route-origin with Type 1
    pattern 'route\-origin:(6[0-5][0-5][0-3][0-5]|' +
        '[1-5][0-9]{4}|[1-9][0-9]{1,4}|[0-9]):' +
        '(4[0-2][0-9][0-4][0-9][0-6][0-7][0-2][0-9][0-6]|' +
        '[1-3][0-9]{9}|[1-9]([0-9]{1,7})?[0-9]|[1-9])';
}
type string {
    // route-origin with Type 2
    pattern 'route\-origin:' +
        '([0-9]|[1-9][0-9]|1[0-9][0-9]|2[0-4][0-9]|' +
        '25[0-5])\.){3}([0-9]|[1-9][0-9]|1[0-9][0-9]|' +
        '2[0-4][0-9]|25[0-5]):' +
        '(6[0-5][0-5][0-3][0-5]|[1-5][0-9]{4}|' +
        '[1-9][0-9]{1,4}|[0-9])';
}
}
description
    "Type definition for extended community attributes";
reference
    "RFC 4360 - BGP Extended Communities Attribute";
}

typedef bgp-community-regexp-type {
    // TODO: needs more work to decide what format these regexps can
    // take.
    type string;
    description
        "Type definition for communities specified as regular
        expression patterns";
}

```



```
typedef bgp-origin-attr-type {
  type enumeration {
    enum igp {
      description "Origin of the NLRI is internal";
    }
    enum egp {
      description "Origin of the NLRI is EGP";
    }
    enum incomplete {
      description "Origin of the NLRI is neither IGP or EGP";
    }
  }
  description
    "Type definition for standard BGP origin attribute";
  reference
    "RFC 4271 - A Border Gateway Protocol 4 (BGP-4), Sec 4.3";
}
```

```
typedef peer-type {
  type enumeration {
    enum internal {
      description
        "internal (iBGP) peer";
    }
    enum external {
      description
        "external (eBGP) peer";
    }
    enum confederation {
      description
        "Confederation as peer";
    }
  }
  description
    "Labels a peer or peer group as explicitly internal,
    external or confederation.";
}
```

```
identity REMOVE_PRIVATE_AS_OPTION {
  description
    "Base identity for options for removing private autonomous
    system numbers from the AS_PATH attribute";
}
```

```
identity PRIVATE_AS_REMOVE_ALL {
  base REMOVE_PRIVATE_AS_OPTION;
  description
    "Strip all private autonomous system numbers from the AS_PATH.
```



```
        This action is performed regardless of the other content of the
        AS_PATH attribute, and for all instances of private AS numbers
        within that attribute.";
    }

    identity PRIVATE_AS_REPLACE_ALL {
        base REMOVE_PRIVATE_AS_OPTION;
        description
            "Replace all instances of private autonomous system numbers in
            the AS_PATH with the local BGP speaker's autonomous system
            number. This action is performed regardless of the other
            content of the AS_PATH attribute, and for all instances of
            private AS number within that attribute.";
    }

    typedef remove-private-as-option {
        type identityref {
            base REMOVE_PRIVATE_AS_OPTION;
        }
        description
            "Set of options for configuring how private AS path numbers
            are removed from advertisements";
    }

    typedef percentage {
        type uint8 {
            range "0..100";
        }
        description
            "Integer indicating a percentage value";
    }

    typedef rr-cluster-id-type {
        type union {
            type uint32;
            type inet:ipv4-address;
        }
        description
            "Union type for route reflector cluster ids:
            option 1: 4-byte number
            option 2: IP address";
    }

    typedef community-type {
        type bits {
            bit standard {
                position 0;
                description
```



```
        "Send only standard communities.";
    reference
        "RFC 1997: BGP Communities Attribute.";
}
bit extended {
    description
        "Send only extended communities.";
    reference
        "RFC 4360: BGP Extended Communities Attribute.";
}
bit large {
    description
        "Send only large communities.";
    reference
        "RFC 8092: BGP Large Communities Attribute.";
}
}
description
    "Type describing variations of community attributes.
    The community types can be combined and a value of 0
    implies 'none'";
}
}
<CODE ENDS>
```

[7.3.](#) BGP policy data

```
<CODE BEGINS> file "ietf-bgp-policy@2019-10-03.yang"
module ietf-bgp-policy {
    yang-version "1.1";
    namespace "urn:ietf:params:xml:ns:yang:ietf-bgp-policy";
    prefix "bp";

    // import some basic types
    import ietf-inet-types {
        prefix inet;
    }
    import ietf-routing-policy {
        prefix rpol;
    }
    import ietf-bgp-types {
        prefix bt;
    }

    import ietf-routing-types {
        prefix rt-types;
    }
}
```


organization

"IETF IDR Working Group";

contact

"WG Web: <<http://tools.ietf.org/wg/idr>>

WG List: <idr@ietf.org>

Authors: Mahesh Jethanandani (mjethanandani at gmail.com),
Keyur Patel (keyur at arrcus.com),
Susan Hares (shares at ndzh.com),
Jeffrey Haas (jhaas at pfrc.org).";

description

"This module contains data definitions for BGP routing policy.
It augments the base routing-policy module with BGP-specific
options for conditions and actions.";

revision "2019-10-03" {

description

"Initial Version";

reference

"RFC XXX, BGP Model for Service Provider Network.";

}

// typedef statements

typedef bgp-set-community-option-type {

type enumeration {

enum add {

description

"Add the specified communities to the existing
community attribute";

}

enum remove {

description

"Remove the specified communities from the
existing community attribute";

}

enum replace {

description

"Replace the existing community attribute with
the specified communities. If an empty set is
specified, this removes the community attribute
from the route.";

}

}

description

"Type definition for options when setting the community


```

        attribute in a policy action";
    }

typedef bgp-next-hop-type {
    type union {
        type inet:ip-address-no-zone;
        type enumeration {
            enum self {
                description
                    "Special designation for local router's own
                    address, i.e., next-hop-self";
            }
        }
    }
    description
        "Type definition for specifying next-hop in policy actions";
}

typedef bgp-set-med-type {
    type union {
        type uint32;
        type string {
            pattern "[+-]([0-9]{1,8}|[0-3][0-9]{1,9}|4[0-1][0-9]{1,8}|" +
                "428[0-9]{1,7}|429[0-3][0-9]{1,6}|42948[0-9]{1,5}|" +
                "42949[0-5][0-9]{1,4}|429496[0-6][0-9]{1,3}|" +
                "4294971[0-9]{1,2}|42949728[0-9]|42949729[0-5])$";
        }
    }
    type enumeration {
        enum igp {
            description
                "Set the MED value to the IGP cost toward the
                next hop for the route";
        }
        enum med-plus-igp {
            description
                "Before comparing MED values for path selection, adds to
                the MED the cost of the IGP route to the BGP next-hop
                destination.

                This option replaces the MED value for the router,
                but does not affect the IGP metric comparison. As a
                result, when multiple routes have the same value
                after the MED-plus-IPG comparison, and route selection
                continues, the IGP route metric is also compared, even
                though it was added to the MED value and compared
                earlier in the selection process.

                Useful when the downstream AS requires the complete

```



```
        cost of a certain route that is received across
        multiple ASs.";
    }
}
}
description
    "Type definition for specifying how the BGP MED can
    be set in BGP policy actions. The three choices are to set
    the MED directly, increment/decrement using +/- notation,
    and setting it to the IGP cost (predefined value).";
reference
    "None. WG needs to decide if this is going to be a standard.";
}

// augment statements

augment "/rpol:routing-policy/rpol:defined-sets" {
    description
        "Adds BGP defined sets container to routing policy model.";

    container bgp-defined-sets {
        description
            "BGP-related set definitions for policy match conditions";

        container community-sets {
            description
                "Enclosing container for list of defined BGP community sets";

            list community-set {
                key "name";
                description
                    "List of defined BGP community sets";

                leaf name {
                    type string;
                    mandatory true;
                    description
                        "Name / label of the community set -- this is used to
                        reference the set in match conditions";
                }

                leaf-list member {
                    type union {
                        type bt:bgp-std-community-type;
                        type bt:bgp-community-regexp-type;
                        type bt:bgp-well-known-community-type;
                    }
                    description
```



```
        "Members of the community set";
    }
}

container ext-community-sets {
    description
        "Enclosing container for list of extended BGP community
        sets";
    list ext-community-set {
        key "name";
        description
            "List of defined extended BGP community sets";

        leaf name {
            type string;
            description
                "Name / label of the extended community set -- this is
                used to reference the set in match conditions";
        }

        leaf-list member {
            type union {
                type rt-types:route-target;
                type bt:bgp-community-regexp-type;
            }
            description
                "Members of the extended community set";
        }
    }
}

container as-path-sets {
    description
        "Enclosing container for list of define AS path sets";

    list as-path-set {
        key "name";
        description
            "List of defined AS path sets";

        leaf name {
            type string;
            description
                "Name of the AS path set -- this is used to reference the
                set in match conditions";
        }
    }
}
```



```
    leaf-list member {
      // TODO: need to refine typedef for AS path expressions
      type string;
      description
        "AS path expression -- list of ASes in the set";
    }
  }
}
}

grouping set-community-action-common {
  description
    "Common leaves for set-community and set-ext-community
    actions";

  leaf method {
    type enumeration {
      enum inline {
        description
          "The extended communities are specified inline as a
          list";
      }
      enum reference {
        description
          "The extended communities are specified by referencing a
          defined ext-community set";
      }
    }
    description
      "Indicates the method used to specify the extended
      communities for the set-ext-community action";
  }

  leaf options {
    type bgp-set-community-option-type;
    description
      "Options for modifying the community attribute with
      the specified values. These options apply to both
      methods of setting the community attribute.";
  }
}

augment "/rpol:routing-policy/rpol:policy-definitions/" +
  "rpol:policy-definition/rpol:statements/rpol:statement/" +
  "rpol:conditions" {
  description
    "BGP policy conditions added to routing policy module";
}
```



```
container bgp-conditions {
  description
    "Top-level container for BGP specific policy conditions ";

  leaf med-eq {
    type uint32;
    description
      "Condition to check if the received MED value is equal to
      the specified value";
  }

  leaf origin-eq {
    type bt:bgp-origin-attr-type;
    description
      "Condition to check if the route origin is equal to the
      specified value";
  }

  leaf-list next-hop-in {
    type inet:ip-address-no-zone;
    description
      "List of next hop addresses to check for in the route
      update";
  }

  leaf-list afi-safi-in {
    type identityref {
      base bt:afi-safi-type;
    }
    description
      "List of address families which the NLRI may be within";
  }

  leaf local-pref-eq {
    type uint32;
    // TODO: add support for other comparisons if needed
    description
      "Condition to check if the local pref attribute is equal to
      the specified value";
  }

  leaf route-type {
    // TODO: verify extent of vendor support for this comparison
    type enumeration {
      enum internal {
        description "route type is internal";
      }
      enum external {
```



```
        description "route type is external";
    }
}
description
    "Condition to check the route type in the route update";
}

container community-count {
    description
        "Value and comparison operations for conditions based on the
        number of communities in the route update";
}

container as-path-length {
    description
        "Value and comparison operations for conditions based on the
        length of the AS path in the route update";
}

container match-community-set {
    description
        "Top-level container for match conditions on communities.
        Match a referenced community-set according to the logic
        defined in the match-set-options leaf";

    leaf community-set {
        type leafref {
            path
                "/rpol:routing-policy/rpol:defined-sets/" +
                "bp:bgp-defined-sets/bp:community-sets/" +
                "bp:community-set/bp:name";
        }
        description
            "References a defined community set";
    }

    uses rpol:match-set-options-group;
}

container match-ext-community-set {
    description
        "Match a referenced extended community-set according to the
        logic defined in the match-set-options leaf";

    leaf ext-community-set {
        type leafref {
            path
                "/rpol:routing-policy/rpol:defined-sets/" +
```



```
        "bp:bgp-defined-sets/bp:ext-community-sets/" +
        "bp:ext-community-set/bp:name";
    }
    description "References a defined extended community set";
}

uses rpol:match-set-options-group;
}

container match-as-path-set {
    description
        "Match a referenced as-path set according to the logic
        defined in the match-set-options leaf";

    leaf as-path-set {
        type leafref {
            path "/rpol:routing-policy/rpol:defined-sets/" +
                "bp:bgp-defined-sets/bp:as-path-sets/" +
                "bp:as-path-set/bp:name";
        }
        description
            "References a defined AS path set";
    }
    uses rpol:match-set-options-group;
}
}

augment "/rpol:routing-policy/rpol:policy-definitions/" +
    "rpol:policy-definition/rpol:statements/rpol:statement/" +
    "rpol:actions" {
    description
        "BGP policy actions added to routing policy module.";

    container bgp-actions {
        description
            "Top-level container for BGP-specific actions";

        leaf set-route-origin {
            type bt:bgp-origin-attr-type;
            description
                "Set the origin attribute to the specified value";
        }

        leaf set-local-pref {
            type uint32;
            description
                "Set the local pref attribute on the route update";
        }
    }
}
```



```
}

leaf set-next-hop {
  type bgp-next-hop-type;
  description
    "Set the next-hop attribute in the route update";
}

leaf set-med {
  type bgp-set-med-type;
  description
    "Set the med metric attribute in the route update";
}

container set-as-path-prepend {
  description
    "Action to prepend local AS number to the AS-path a
    specified number of times";

  leaf repeat-n {
    type uint8 {
      range 1..max;
    }
    description
      "Number of times to prepend the local AS number to the AS
      path. The value should be between 1 and the maximum
      supported by the implementation.";
  }
}

container set-community {
  description
    "Action to set the community attributes of the route, along
    with options to modify how the community is modified.
    Communities may be set using an inline list OR
    reference to an existing defined set (not both).";

  uses set-community-action-common;
  container inline {
    when "../method = 'inline'" {
      description
        "Active only when the set-community method is inline";
    }
    description
      "Set the community values for the action inline with
      a list.";

    leaf-list communities {
```



```
    type union {
      type bt:bgp-std-community-type;
      type bt:bgp-well-known-community-type;
    }
    description
      "Set the community values for the update inline with a
      list.";
  }
}

container reference {
  when "../method = 'reference'" {
    description
      "Active only when the set-community method is reference";
  }
  description
    "Provide a reference to a defined community set for the
    set-community action";

  leaf community-set-ref {
    type leafref {
      path "/rpol:routing-policy/rpol:defined-sets/" +
        "bp:bgp-defined-sets/" +
        "bp:community-sets/bp:community-set/bp:name";
    }
    description
      "References a defined community set by name";
  }
}

container set-ext-community {
  description
    "Action to set the extended community attributes of the
    route, along with options to modify how the community is
    modified. Extended communities may be set using an inline
    list OR a reference to an existing defined set (but not
    both).";

  uses set-community-action-common;
  container inline {
    when "../method = 'inline'" {
      description
        "Active only when the set-community method is inline";
    }
    description
      "Set the extended community values for the action inline
      with a list.";
  }
}
```



```

    leaf-list communities {
      type union {
        type rt-types:route-target;
        type bt:bgp-well-known-community-type;
      }
      description
        "Set the extended community values for the update inline
        with a list.";
    }
  }

  container reference {
    when "../method = 'reference'" {
      description
        "Active only when the set-community method is reference";
    }
    description
      "Provide a reference to an extended community set for the
      set-ext-community action";

    leaf ext-community-set-ref {
      type leafref {
        path
          "/rpol:routing-policy/rpol:defined-sets/" +
          "bp:bgp-defined-sets/bp:ext-community-sets/" +
          "bp:ext-community-set/bp:name";
      }
      description
        "References a defined extended community set by name";
    }
  }
}

// rpc statements

// notification statements
}

<CODE ENDS>

```

7.4. RIB modules

```

<CODE BEGINS> file "ietf-bgp-rib@2019-10-03.yang"
submodule ietf-bgp-rib {
  yang-version "1.1";
  belongs-to ietf-bgp {
    prefix "br";
  }
}

```



```
}

/*
 * Import and Include
 */
import ietf-bgp-types {
  prefix "bt";
  reference
    "RFC XXXX: BGP YANG Model for Service Provider Networks.";
}

import ietf-inet-types {
  prefix inet;
  reference
    "RFC 6991: Common YANG Types.";
}

import ietf-yang-types {
  prefix yang;
  reference
    "RFC 6991: Common YANG Types.";
}

import ietf-routing-types {
  prefix "rt";
  reference
    "RFC 8294: Routing Area YANG Types.";
}

include ietf-bgp-rib-types;
include ietf-bgp-rib-tables;

// groupings of attributes in three categories:
// - shared across multiple routes
// - common to LOC-RIB and Adj-RIB, but not shared across routes
// - specific to LOC-RIB or Adj-RIB
include ietf-bgp-rib-attributes;

// groupings of annotations for each route or table
include ietf-bgp-rib-table-attributes;

organization
  "IETF IDR Working Group";

contact
  "WG Web:  <http://tools.ietf.org/wg/idr>
  WG List:  <idr@ietf.org>
```


Authors: Mahesh Jethanandani (mjethanandani at gmail.com),
Keyur Patel (keyur at arrcus.com),
Susan Hares (shares at ndzh.com)";

description

"Defines a submodule for representing BGP routing table (RIB) contents. The submodule supports 5 logical RIBs per address family:

loc-rib: This is the main BGP routing table for the local routing instance, containing best-path selections for each prefix. The loc-rib table may contain multiple routes for a given prefix, with an attribute to indicate which was selected as the best path. Note that multiple paths may be used or advertised even if only one path is marked as best, e.g., when using BGP add-paths. An implementation may choose to mark multiple paths in the RIB as best path by setting the flag to true for multiple entries.

adj-rib-in-pre: This is a per-neighbor table containing the NLRI updates received from the neighbor before any local input policy rules or filters have been applied. This can be considered the 'raw' updates from a given neighbor.

adj-rib-in-post: This is a per-neighbor table containing the routes received from the neighbor that are eligible for best-path selection after local input policy rules have been applied.

adj-rib-out-pre: This is a per-neighbor table containing routes eligible for sending (advertising) to the neighbor before output policy rules have been applied.

adj-rib-out-post: This is a per-neighbor table containing routes eligible for sending (advertising) to the neighbor after output policy rules have been applied.";

```
revision "2019-10-03" {  
  description  
    "Initial Version";  
  reference  
    "RFC XXXX, BGP YANG Model for Service Provider Network.";  
}
```

```
grouping rib {  
  description  
    "Grouping for rib.";
```



```
container rib {
  config false;

  container attr-sets {
    description
      "Enclosing container for the list of path attribute sets";

    list attr-set {
      key "index";

      description
        "List of path attributes that may be in use by multiple
        routes in the table";

      leaf index {
        type uint64;
        description
          "System generated index for each attribute set. The
          index is used to reference an attribute set from a
          specific path. Multiple paths may reference the same
          attribute set.";
      }

      leaf origin {
        type bt:bgp-origin-attr-type;
        description
          "BGP attribute defining the origin of the path
          information.";
      }

      leaf atomic-aggregate {
        type boolean;
        description
          "BGP attribute indicating that the prefix is an atomic
          aggregate; i.e., the peer selected a less specific
          route without selecting a more specific route that is
          included in it.";
        reference
          "RFC 4271: Section 5.1.6.";
      }

      leaf next-hop {
        type inet:ip-address;
        description
          "BGP next hop attribute defining the IP address of the
          router that should be used as the next hop to the
          destination";
        reference
```



```
    "RFC 4271: Section 5.1.3.";
  }

  leaf med {
    type uint32;
    description
      "BGP multi-exit discriminator attribute used in BGP route
       selection process";
    reference
      "RFC 4271: Section 5.1.4.";
  }

  leaf local-pref {
    type uint32;
    description
      "BGP local preference attribute sent to internal peers to
       indicate the degree of preference for externally learned
       routes. The route with the highest local preference
       value is preferred.";
    reference
      "RFC 4271: Section 5.1.5.";
  }

  leaf originator-id {
    type yang:dotted-quad;
    description
      "BGP attribute that provides the id as an IPv4 address
       of the originator of the announcement.";
    reference
      "RFC 4456 - BGP Route Reflection: An Alternative to Full
       Mesh Internal BGP (IBGP)";
  }

  leaf-list cluster-list {
    type yang:dotted-quad;
    description
      "Represents the reflection path that the route has
       passed.";
    reference
      "RFC 4456 - BGP Route Reflection: An Alternative to Full
       Mesh Internal BGP (IBGP)";
  }

  leaf aigp-metric {
    type uint64;
    description
      "BGP path attribute representing the accumulated IGP
       metric for the path";
```



```
    reference
      "RFC 7311 - The Accumulated IGP Metric Attribute for BGP";
  }
  container aggregator {
    config false;
    description
      "BGP attribute indicating the prefix has been
       aggregated by the specified AS and router.";
    reference
      "RFC 4271: Section 5.1.7.";

    leaf as {
      type inet:as-number;
      description
        "AS number of the autonomous system that performed the
         aggregation.";
    }

    leaf as4 {
      type inet:as-number;
      description
        "AS number of the autonomous system that performed the
         aggregation (4-octet representation). This value is
         populated if an upstream router is not 4-octet capable.
         Its semantics are similar to the AS4_PATH optional
         transitive attribute";
      reference
        "RFC 6793 - BGP Support for Four-octet AS Number Space";
    }

    leaf address {
      type inet:ipv4-address;
      description
        "IP address of the router that performed the
         aggregation.";
    }
  }
  container as-path {
    description
      "Enclosing container for the list of AS path segments.

      In the Adj-RIB-In or Adj-RIB-Out, this list should show
      the received or sent AS_PATH, respectively. For
      example, if the local router is not 4-byte capable, this
      value should consist of 2-octet ASNs or the AS_TRANS
      (AS 23456) values received or sent in route updates.

      In the Loc-RIB, this list should reflect the effective
```



```
        AS path for the route, e.g., a 4-octet value if the
        local router is 4-octet capable.";
reference
  "RFC 4271 - A Border Gateway Protocol 4 (BGP-4)
  RFC 6793 - BGP Support for Four-octet AS Number Space
  RFC 5065 - Autonomous System Confederations for BGP";

list segment {
  key "type";

  config false;
  uses bgp-as-path-attr;
  description
    "List of AS PATH segments";
}
}
container as4-path {
  description
    "This is the path encoded with 4-octet
    AS numbers in the optional transitive AS4_PATH attribute.
    This value is populated with the received or sent
    attribute in Adj-RIB-In or Adj-RIB-Out, respectively.
    It should not be populated in Loc-RIB since the Loc-RIB
    is expected to store the effective AS-Path in the
    as-path leaf regardless of being 4-octet or 2-octet.";
  reference
    "RFC 6793 - BGP Support for Four-octet AS Number Space";

  list segment {
    key "type";

    config false;
    uses bgp-as-path-attr;
    description
      "List of AS PATH segments";
  }
}
}
}

container communities {
  description
    "Enclosing container for the list of community attribute
    sets";

  list community {
    key "index";
```



```
    config false;
    description
      "List of path attributes that may be in use by multiple
      routes in the table";

    leaf index {
      type uint64;
      description
        "System generated index for each attribute set. The
        index is used to reference an attribute set from a
        specific path. Multiple paths may reference the same
        attribute set.";
    }

    uses bgp-community-attr-state;
  }
}

container ext-communities {
  description
    "Enclosing container for the list of extended community
    attribute sets";

  list ext-community {
    key "index";

    config false;
    description
      "List of path attributes that may be in use by multiple
      routes in the table";

    leaf index {
      type uint64;
      description
        "System generated index for each attribute set. The
        index is used to reference an attribute set from a
        specific path. Multiple paths may reference the same
        attribute set.";
    }
  }

  leaf-list ext-community {
    type rt:route-target;
    description
      "List of BGP extended community attributes. The received
      extended community may be an explicitly modeled
      type or unknown, represented by an 8-octet value
      formatted according to RFC 4360.";
    reference
```



```
        "RFC 4360 - BGP Extended Communities Attribute";
    }
}
}

container afi-safis {
  config false;
  description
    "Enclosing container for address family list";

  list afi-safi {
    key "afi-safi-name";
    description
      "List of afi-safi types.";

    leaf afi-safi-name {
      type identityref {
        base bt:afi-safi-type;
      }
      description "AFI,SAFI name.";
    }

    container ipv4-unicast {
      when "../afi-safi-name = 'bt:ipv4-unicast'" {
        description
          "Include this container for IPv4 unicast RIB";
      }
      description
        "Routing tables for IPv4 unicast -- active when the
        afi-safi name is ipv4-unicast";

      uses ipv4-loc-rib;
      uses ipv4-adj-rib;
    }

    container ipv6-unicast {
      when "../afi-safi-name = 'bt:ipv6-unicast'" {
        description
          "Include this container for IPv6 unicast RIB";
      }
      description
        "Routing tables for IPv6 unicast -- active when the
        afi-safi name is ipv6-unicast";

      uses ipv6-loc-rib;
      uses ipv6-adj-rib;
    }
  }
}
```



```
    }
    description
      "Top level container for BGP RIB";
  }
}
}
<CODE ENDS>
```

```
<CODE BEGINS> file "ietf-bgp-rib-ext@2019-10-03.yang"
submodule ietf-bgp-rib-ext {
  yang-version "1.1";
  belongs-to ietf-bgp {
    prefix "bre";
  }

  include ietf-bgp-rib-types;

  organization
    "IETF IDR Working Group";

  contact
    "WG Web:  <http://tools.ietf.org/wg/idr>
    WG List:  <idr@ietf.org>

    Authors: Mahesh Jethanandani (mjethanandani at gmail.com),
             Keyur Patel (keyur at arccus.com),
             Susan Hares (shares at ndzh.com),
             Jeffrey Haas (jhaas at pfrc.org).";

  description
    "Defines additional data nodes for the BGP RIB model.
    These items reflect extensions that are desirable features but
    are not currently supported in a majority of BGP
    implementations.";

  revision "2019-10-03" {
    description
      "Initial Revision.";
    reference
      "RFC XXXX: BGP YANG Model for Service Providers.";
  }

  grouping rib-ext-route-annotations {
    description
      "Extended annotations for routes in the routing tables";

    leaf reject-reason {
```



```
    type union {
      type identityref {
        base bgp-not-selected-bestpath;
      }
      type identityref {
        base bgp-not-selected-policy;
      }
    }
    description
      "Indicates the reason the route is not used, either due to
       policy filtering or bestpath selection";
  }
}
}
<CODE ENDS>
```

```
<CODE BEGINS> file "ietf-bgp-rib-types@2019-10-03.yang"
submodule ietf-bgp-rib-types {
  yang-version "1.1";
  belongs-to ietf-bgp {
    prefix "br";
  }

  organization
    "IETF IDR Working Group";

  contact
    "WG Web:  <http://tools.ietf.org/wg/idr>
    WG List:  <idr@ietf.org>

    Authors: Mahesh Jethanandani (mjethanandani at gmail.com),
             Keyur Patel (keyur at arrcus.com),
             Susan Hares (shares at ndzh.com),
             Jeffrey Haas (jhaas at pfrc.org).";

  description
    "Defines identity and type definitions associated with
     the BGP RIB modules";

  revision "2019-10-03" {
    description
      "Initial Version";
    reference
      "RFC XXXX, BGP Model for Service Provider Network.";
  }

  identity invalid-route-reason {
```



```
    description
      "Base identity for reason code for routes that are rejected as
      invalid. Some derived entities are based on BMP v3";
    reference
      "RFC 7854: BGP Monitoring Protocol.";
  }

  identity invalid-cluster-loop {
    base invalid-route-reason;
    description
      "Route was invalid due to CLUSTER_LIST loop";
  }

  identity invalid-as-loop {
    base invalid-route-reason;
    description
      "Route was invalid due to AS_PATH loop";
  }

  identity invalid-originator {
    base invalid-route-reason;
    description
      "Route was invalid due to ORIGINATOR_ID, e.g., update has
      local router as originator";
  }

  identity invalid-confed {
    base invalid-route-reason;
    description
      "Route was invalid due to a loop in the AS_CONFED_SEQUENCE or
      AS_CONFED_SET attributes";
  }

  identity bgp-not-selected-bestpath {
    description
      "Base identity for indicating reason a route was was not
      selected by BGP route selection algorithm";
    reference
      "RFC 4271 - Section 9.1";
  }

  identity local-pref-lower {
    base bgp-not-selected-bestpath;
    description
      "Route has a lower localpref attribute than current best path";
    reference
      "RFC 4271 - Section 9.1.2";
  }
```



```
identity as-path-longer {
  base bgp-not-selected-bestpath;
  description
    "Route has a longer AS path attribute than current best path";
  reference
    "RFC 4271 - Section 9.1.2.2 (a)";
}
```

```
identity origin-type-higher {
  base bgp-not-selected-bestpath;
  description
    "Route has a higher origin type, i.e., IGP origin is preferred
    over EGP or incomplete";
  reference
    "RFC 4271 - Section 9.1.2.2 (b)";
}
```

```
identity med-higher {
  base bgp-not-selected-bestpath;
  description
    "Route has a higher MED, or metric, attribute than the current
    best path";
  reference
    "RFC 4271 - Section 9.1.2.2 (c)";
}
```

```
identity prefer-external {
  base bgp-not-selected-bestpath;
  description
    "Route source is via IGP, rather than EGP.";
  reference
    "RFC 4271 - Section 9.1.2.2 (d)";
}
```

```
identity nexthop-cost-higher {
  base bgp-not-selected-bestpath;
  description
    "Route has a higher interior cost to the next hop.";
  reference
    "RFC 4271 - Section 9.1.2.2 (e)";
}
```

```
identity higher-router-id {
  base bgp-not-selected-bestpath;
  description
    "Route was sent by a peer with a higher BGP Identifier value,
    or router id";
  reference
```



```
    "RFC 4271 - Section 9.1.2.2 (f)";
  }

  identity higher-peer-address {
    base bgp-not-selected-bestpath;
    description
      "Route was sent by a peer with a higher IP address";
    reference
      "RFC 4271 - Section 9.1.2.2 (g)";
  }

  identity bgp-not-selected-policy {
    description
      "Base identity for reason code for routes that are rejected
       due to policy";
  }

  identity rejected-import-policy {
    base bgp-not-selected-policy;
    description
      "Route was rejected after apply import policies";
  }
}
<CODE ENDS>
```

```
<CODE BEGINS> file "ietf-bgp-rib-attributes@2019-10-03.yang"
submodule ietf-bgp-rib-attributes {
  yang-version "1.1";
  belongs-to ietf-bgp {
    prefix "br";
  }

  // import some basic types
  import ietf-bgp-types {
    prefix bgpt;
  }

  import ietf-inet-types {
    prefix inet;
  }

  include ietf-bgp-rib-types;

  // meta
  organization
    "IETF IDR Working Group";
```


contact

"WG Web: <<http://tools.ietf.org/wg/idr>>
WG List: <idr@ietf.org>

Authors: Mahesh Jethanandani (mjethanandani at gmail.com),
Keyur Patel (keyur at arrcus.com),
Susan Hares (shares at ndzh.com)";

description

"This submodule contains common data definitions for BGP
attributes for use in BGP RIB tables.";

revision "2019-10-03" {

description

"Initial version";

reference

"RFC XXXX: BGP YANG Model for Service Provider Network";

}

grouping bgp-as-path-attr {

description

"Data for representing BGP AS-PATH attribute";

leaf type {

type identityref {

base bgpt:as-path-segment-type;

}

description

"The type of AS-PATH segment";

}

leaf-list member {

type inet:as-number;

description

"List of the AS numbers in the AS-PATH segment";

}

}

grouping bgp-community-attr-state {

description

"Common definition of BGP community attributes";

leaf-list community {

type union {

type bgpt:bgp-well-known-community-type;

type bgpt:bgp-std-community-type;

}


```
    description
      "List of standard or well-known BGP community
      attributes.";
  }
}

grouping bgp-unknown-attr-flags-state {
  description
    "Operational state data for path attribute flags";

  leaf optional {
    type boolean;
    description
      "Defines whether the attribute is optional (if
      set to true) or well-known (if set to false).
      Set in the high-order bit of the BGP attribute
      flags octet.";
    reference
      "RFC 4271 - A Border Gateway Protocol 4 (BGP-4)";
  }

  leaf transitive {
    type boolean;
    description
      "Defines whether an optional attribute is transitive
      (if set to true) or non-transitive (if set to false). For
      well-known attributes, the transitive flag must be set to
      true. Set in the second high-order bit of the BGP attribute
      flags octet.";
    reference
      "RFC 4271 - A Border Gateway Protocol 4 (BGP-4)";
  }

  leaf partial {
    type boolean;
    description
      "Defines whether the information contained in the optional
      transitive attribute is partial (if set to true) or complete
      (if set to false). For well-known attributes and for
      optional non-transitive attributes, the partial flag
      must be set to false. Set in the third high-order bit of
      the BGP attribute flags octet.";
    reference
      "RFC 4271 - A Border Gateway Protocol 4 (BGP-4)";
  }

  leaf extended {
    type boolean;
```



```
    description
      "Defines whether the attribute length is one octet
      (if set to false) or two octets (if set to true). Set in
      the fourth high-order bit of the BGP attribute flags
      octet.";
    reference
      "RFC 4271 - A Border Gateway Protocol 4 (BGP-4)";
  }
}

grouping bgp-unknown-attr-state {
  description
    "Operational state data for path attributes not shared
    across route entries, common to LOC-RIB and Adj-RIB";

  leaf attr-type {
    type uint8;
    description
      "1-octet value encoding the attribute type code";
    reference
      "RFC 4271 - A Border Gateway Protocol 4 (BGP-4)";
  }

  leaf attr-len {
    type uint16;
    description
      "One or two octet attribute length field indicating the
      length of the attribute data in octets. If the Extended
      Length attribute flag is set, the length field is 2 octets,
      otherwise it is 1 octet";
    reference
      "RFC 4271 - A Border Gateway Protocol 4 (BGP-4)";
  }

  leaf attr-value {
    type binary {
      length 0..65535;
    }
    description
      "Raw attribute value, not including the attribute
      flags, type, or length. The maximum length
      of the attribute value data is 2^16-1 per the max value
      of the attr-len field (2 octets).";
    reference
      "RFC 4271 - A Border Gateway Protocol 4 (BGP-4)";
  }
}
```



```
grouping bgp-unknown-attr-top {
  description
    "Unknown path attributes that are not expected to be shared
    across route entries, common to LOC-RIB and Adj-RIB";

  container unknown-attributes {
    description
      "Unknown path attributes that were received in the UPDATE
      message which contained the prefix.";

    list unknown-attribute {
      key "attr-type";
      description
        "This list contains received attributes that are unrecognized
        or unsupported by the local router. The list may be empty.";

      uses bgp-unknown-attr-flags-state;
      uses bgp-unknown-attr-state;
    }
  }
}

grouping bgp-loc-rib-attr-state {
  description
    "Path attributes that are not expected to be shared across
    route entries, specific to LOC-RIB";
}

grouping bgp-adj-rib-attr-state {
  description
    "Path attributes that are not expected to be shared across
    route entries, specific to Adj-RIB";

  leaf path-id {
    type uint32;
    description
      "When the BGP speaker supports advertisement of multiple
      paths for a prefix, the path identifier is used to
      uniquely identify a route based on the combination of the
      prefix and path id. In the Adj-RIB-In, the path-id value is
      the value received in the update message. In the Loc-RIB,
      if used, it should represent a locally generated path-id
      value for the corresponding route. In Adj-RIB-Out, it
      should be the value sent to a neighbor when add-paths is
      used, i.e., the capability has been negotiated.";
    reference
      "RFC 7911: Advertisement of Multiple Paths in BGP";
```



```
    }  
  }  
}  
<CODE ENDS>
```

```
<CODE BEGINS> file "ietf-bgp-rib-table-attributes@2019-10-03.yang"  
submodule ietf-bgp-rib-table-attributes {  
  yang-version "1.1";  
  belongs-to ietf-bgp {  
    prefix "br";  
  }  
  
  // import some basic types  
  import ietf-yang-types {  
    prefix types;  
    reference  
      "RFC 6991, Common YANG Data Types.";  
  }  
  
  include ietf-bgp-rib-types;  
  
  organization  
    "IETF IDR Working Group";  
  
  contact  
    "WG Web:  <http://tools.ietf.org/wg/idr>  
    WG List:  <idr@ietf.org>  
  
    Authors: Mahesh Jethanandani (mjethanandani at gmail.com),  
             Keyur Patel (keyur at arccus.com),  
             Susan Hares (shares at ndzh.com);  
  
  description  
    "This submodule contains common data definitions for data  
    related to a RIB entry, or RIB table."  
  
  revision "2019-10-03" {  
    description  
      "Initial version.";  
    reference  
      "RFC XXXX: BGP YANG Model for Service Provider Network.";  
  }  
  
  grouping bgp-common-route-annotations-state {  
    description  
      "Data definitions for flags and other information attached
```



```
    to routes in both LOC-RIB and Adj-RIB";

    leaf last-modified {
        type types:timeticks;
        description
            "Timestamp when this path was last modified.

            The value is the timestamp in seconds relative to
            the Unix Epoch (Jan 1, 1970 00:00:00 UTC).";
    }

    leaf valid-route {
        type boolean;
        description
            "Indicates that the route is considered valid by the
            local router";
    }

    leaf invalid-reason {
        type identityref {
            base invalid-route-reason;
        }
        description
            "If the route is rejected as invalid, this indicates the
            reason.";
    }
}

grouping bgp-loc-rib-route-annotations-state {
    description
        "Data definitions for information attached to routes in the
        LOC-RIB";

    // placeholder for route metadata specific to the LOC-RIB
}

grouping bgp-adj-rib-in-post-route-annotations-state {
    description
        "Data definitions for information attached to routes in the
        Adj-RIB-in post-policy table";

    leaf best-path {
        type boolean;
        description
            "Current path was selected as the best path.";
    }
}
```



```
    grouping bgp-common-table-attrs-state {
      description
        "Common attributes attached to all routing tables";

      // placeholder for metadata associated with all tables
    }

    grouping bgp-common-table-attrs-top {
      // no enclosing container as this data will fit under an
      // existing LOC-RIB container

      uses bgp-common-table-attrs-state;
      description
        "Operational state data for data related to the entire
        LOC-RIB";
    }
  }
}
<CODE ENDS>
```

```
<CODE BEGINS> file "ietf-bgp-rib-tables@2019-10-03.yang"
submodule ietf-bgp-rib-tables {
  yang-version "1.1";
  belongs-to ietf-bgp {
    prefix "br";
  }

  // import some basic types
  import ietf-inet-types {
    prefix inet;
    reference
      "RFC 6991: Common YANG Data Types.";
  }

  import ietf-yang-types {
    prefix yang;
    reference
      "RFC 6991: Common YANG Data Types.";
  }

  import ietf-routing {
    prefix "rt";
    reference
      "RFC 8022: A YANG Data Model for Routing Management";
  }

  include ietf-bgp-rib-ext;
  include ietf-bgp-rib-attributes;
```



```
include ietf-bgp-rib-table-attributes;

organization
  "IETF IDR Working Group";

contact
  "WG Web:   <http://tools.ietf.org/wg/idr>
  WG List:  <idr@ietf.org>

  Editor:   Mahesh Jethanandani (mjethanandani@gmail.com)
  Authors:  Keyur Patel,
            Mahesh Jethanandani,
            Susan Hares";

description
  "This submodule contains structural data definitions for
  BGP routing tables.";

revision "2019-10-03" {
  description
    "Initial Version";
  reference
    "RFC XXXX, BGP YANG Model for Service Provider Network.";
}

/*
 * Feature(s)
 */
feature clear-routes {
  description
    "Clearing of BGP routes is supported.";
}

grouping bgp-adj-rib-common-attr-refs {
  description
    "Definitions of common references to attribute sets for
    multiple AFI-SAFIs for Adj-RIB tables";

  leaf attr-index {
    type leafref {
      path "../.../.../.../.../.../.../attr-sets/" +
        "attr-set/index";
    }
    description
      "Reference to the common attribute group for the
      route";
  }
}
```



```
leaf community-index {
  type leafref {
    path "../../../../../communities/community/" +
      "index";
  }
  description
    "Reference to the community attribute for the route";
}

leaf ext-community-index {
  type leafref {
    path "../../../../../ext-communities/" +
      "ext-community/index";
  }
  description
    "Reference to the extended community attribute for the
    route";
}

grouping bgp-loc-rib-common-attr-refs {
  description
    "Definitions of common references to attribute sets for
    multiple AFI-SAFIs for LOC-RIB tables";

  leaf attr-index {
    type leafref {
      path "../../../../attr-sets/attr-set/" +
        "index";
    }
    description
      "Reference to the common attribute group for the
      route";
  }

  leaf community-index {
    type leafref {
      path "../../../../../communities/community/" +
        "index";
    }
    description
      "Reference to the community attribute for the route";
  }

  leaf ext-community-index {
    type leafref {
      path "../../../../../ext-communities/" +
        "ext-community/index";
    }
  }
}
```



```
    }
    description
      "Reference to the extended community attribute for the
       route";
  }
}

grouping bgp-loc-rib-common-keys {
  description
    "Common references used in keys for IPv4 and IPv6
     LOC-RIB entries";

  leaf origin {
    type union {
      type inet:ip-address;
      type identityref {
        base rt:routing-protocol;
      }
    }
    description
      "Indicates the origin of the route.  If the route is learned
       from a neighbor, this value is the neighbor address.  If
       the route was injected or redistributed from another
       protocol, the origin indicates the source protocol for the
       route.";
  }

  leaf path-id {
    type uint32;
    // TODO: YANG does not allow default values for key
    // default 0;
    description
      "If the route is learned from a neighbor, the path-id
       corresponds to the path-id for the route in the
       corresponding adj-rib-in-post table.  If the route is
       injected from another protocol, or the neighbor does not
       support BGP add-paths, the path-id should be set
       to zero, also the default value.";
  }
}

grouping clear-routes {
  description
    "Action to clear BGP routes.";

  container clear-routes {
    if-feature "clear-routes";
  }
}
```



```
    action clear {
      input {
        leaf clear-at {
          type yang:date-and-time;
          description
            "The time, in the future when the clear operation will
             be initiated.";
        }
      }

      output {
        leaf clear-finished-at {
          type yang:date-and-time;
          description
            "The time when the clear operation finished.";
        }
      }
    }
  }
  description
    "Action commands to clear routes governed by a if-feature.";
}

grouping ipv4-loc-rib {
  description
    "Top-level grouping for IPv4 routing tables";

  container loc-rib {
    config false;
    description
      "Container for the IPv4 BGP LOC-RIB data";

    uses bgp-common-table-attrs-top;

    container routes {
      description
        "Enclosing container for list of routes in the routing
         table.";

      list route {
        key "prefix origin path-id";

        description
          "List of routes in the table, keyed by the route
           prefix, the route origin, and path-id. The route
           origin can be either the neighbor address from which
           the route was learned, or the source protocol that
           injected the route. The path-id distinguishes routes
```



```
        for the same prefix received from a neighbor (e.g.,
        if add-paths is enabled).";

    leaf prefix {
        type inet:ipv4-prefix;
        description
            "The IPv4 prefix corresponding to the route";
    }

    uses bgp-loc-rib-common-keys;
    uses bgp-loc-rib-common-attr-refs;
    uses bgp-loc-rib-attr-state;
    uses bgp-common-route-annotations-state;
    uses bgp-loc-rib-route-annotations-state;
    uses bgp-unknown-attr-top;
    uses rib-ext-route-annotations;
}

    uses clear-routes;
}
}

grouping ipv6-loc-rib {
    description
        "Top-level grouping for IPv6 routing tables";

    container loc-rib {
        config false;
        description
            "Container for the IPv6 BGP LOC-RIB data";

        uses bgp-common-table-attrs-top;

        container routes {
            description
                "Enclosing container for list of routes in the routing
                table.";

            list route {
                key "prefix origin path-id";

                description
                    "List of routes in the table, keyed by the route
                    prefix, the route origin, and path-id. The route
                    origin can be either the neighbor address from which
                    the route was learned, or the source protocol that
                    injected the route. The path-id distinguishes routes
```



```
        for the same prefix received from a neighbor (e.g.,
        if add-paths is enabled).";

    leaf prefix {
        type inet:ipv6-prefix;
        description
            "The IPv6 prefix corresponding to the route";
    }

    uses bgp-loc-rib-common-keys;
    uses bgp-loc-rib-common-attr-refs;
    uses bgp-loc-rib-attr-state;
    uses bgp-common-route-annotations-state;
    uses bgp-loc-rib-route-annotations-state;
    uses bgp-unknown-attr-top;
    uses rib-ext-route-annotations;
}

uses clear-routes;
}
}

grouping ipv4-adj-rib-common {
    description
        "Common structural grouping for each IPv4 adj-RIB table";

    uses bgp-common-table-attrs-top;

    container routes {
        config false;
        description
            "Enclosing container for list of routes in the routing
            table.";

        list route {
            key "prefix path-id";

            description
                "List of routes in the table, keyed by a combination of
                the route prefix and path-id to distinguish multiple
                routes received from a neighbor for the same prefix,
                e.g., when BGP add-paths is enabled.";

            leaf prefix {
                type inet:ipv4-prefix;
                description
                    "Prefix for the route";
```



```
    }

    uses bgp-adj-rib-attr-state;
    uses bgp-adj-rib-common-attr-refs;
    uses bgp-common-route-annotations-state;
    uses bgp-unknown-attr-top;
    uses rib-ext-route-annotations;
  }

  uses clear-routes;
}

grouping ipv4-adj-rib-in-post {
  description
    "Common structural grouping for the IPv4 adj-rib-in
    post-policy table";

  uses bgp-common-table-attrs-top;

  container routes {
    config false;
    description
      "Enclosing container for list of routes in the routing
      table.";

    list route {
      key "prefix path-id";

      description
        "List of routes in the table, keyed by a combination of
        the route prefix and path-id to distinguish multiple
        routes received from a neighbor for the same prefix,
        e.g., when BGP add-paths is enabled.";

      leaf prefix {
        type inet:ipv4-prefix;
        description
          "Prefix for the route";
      }

      uses bgp-adj-rib-attr-state;
      uses bgp-adj-rib-common-attr-refs;
      uses bgp-common-route-annotations-state;
      uses bgp-adj-rib-in-post-route-annotations-state;
      uses bgp-unknown-attr-top;
      uses rib-ext-route-annotations;
    }
  }
}
```



```
}  
}
```

```
grouping ipv4-adj-rib {  
  description  
    "Top-level grouping for Adj-RIB table";  
  
  container neighbors {  
    config false;  
    description  
      "Enclosing container for neighbor list";  
  
    list neighbor {  
      key "neighbor-address";  
      description  
        "List of neighbors (peers) of the local BGP speaker";  
  
      leaf neighbor-address {  
        type inet:ip-address;  
        description  
          "IP address of the BGP neighbor or peer";  
      }  
    }  
  
    container adj-rib-in-pre {  
      description  
        "Per-neighbor table containing the NLRI updates  
        received from the neighbor before any local input  
        policy rules or filters have been applied. This can  
        be considered the 'raw' updates from the neighbor.";  
  
      uses ipv4-adj-rib-common;  
    }  
  
    container adj-rib-in-post {  
      description  
        "Per-neighbor table containing the paths received from  
        the neighbor that are eligible for best-path selection  
        after local input policy rules have been applied.";  
  
      uses ipv4-adj-rib-in-post;  
    }  
  
    container adj-rib-out-pre {  
      description  
        "Per-neighbor table containing paths eligible for  
        sending (advertising) to the neighbor before output
```



```
        policy rules have been applied";

    uses ipv4-adj-rib-common;

}

container adj-rib-out-post {
    description
        "Per-neighbor table containing paths eligible for
        sending (advertising) to the neighbor after output
        policy rules have been applied";

    uses ipv4-adj-rib-common;
}
}
}

grouping ipv6-adj-rib-common {
    description
        "Common structural grouping for each IPv6 adj-RIB table";

    uses bgp-common-table-attrs-state;

    container routes {
        config false;
        description
            "Enclosing container for list of routes in the routing
            table.";

        list route {
            key "prefix path-id";

            description
                "List of routes in the table";

            leaf prefix {
                type inet:ipv6-prefix;
                description
                    "Prefix for the route";
            }

            uses bgp-adj-rib-attr-state;
            uses bgp-adj-rib-common-attr-refs;
            uses bgp-common-route-annotations-state;
            uses bgp-unknown-attr-top;
            uses rib-ext-route-annotations;
        }
    }
}
```



```
        uses clear-routes;
    }
}

grouping ipv6-adj-rib-in-post {
    description
        "Common structural grouping for the IPv6 adj-rib-in
        post-policy table";

    uses bgp-common-table-attrs-state;

    container routes {
        config false;
        description
            "Enclosing container for list of routes in the routing
            table.";

        list route {
            key "prefix path-id";

            description
                "List of routes in the table";

            leaf prefix {
                type inet:ipv6-prefix;
                description
                    "Prefix for the route";
            }

            uses bgp-adj-rib-attr-state;
            uses bgp-adj-rib-common-attr-refs;
            uses bgp-common-route-annotations-state;
            uses bgp-adj-rib-in-post-route-annotations-state;
            uses bgp-unknown-attr-top;
            uses rib-ext-route-annotations;
        }
    }
}

grouping ipv6-adj-rib {
    description
        "Top-level grouping for Adj-RIB table";

    container neighbors {
        config false;
        description
            "Enclosing container for neighbor list";
    }
}
```



```
list neighbor {
  key "neighbor-address";
  description
    "List of neighbors (peers) of the local BGP speaker";

  leaf neighbor-address {
    type inet:ip-address;
    description
      "IP address of the BGP neighbor or peer";
  }

  container adj-rib-in-pre {
    description
      "Per-neighbor table containing the NLRI updates
      received from the neighbor before any local input
      policy rules or filters have been applied. This can
      be considered the 'raw' updates from the neighbor.";

    uses ipv6-adj-rib-common;
  }

  container adj-rib-in-post {
    description
      "Per-neighbor table containing the paths received from
      the neighbor that are eligible for best-path selection
      after local input policy rules have been applied.";

    uses ipv6-adj-rib-in-post;
  }

  container adj-rib-out-pre {
    description
      "Per-neighbor table containing paths eligible for
      sending (advertising) to the neighbor before output
      policy rules have been applied";

    uses ipv6-adj-rib-common;
  }

  container adj-rib-out-post {
    description
      "Per-neighbor table containing paths eligible for
      sending (advertising) to the neighbor after output
      policy rules have been applied";

    uses ipv6-adj-rib-common;
  }
}
```



```
    }  
  }  
}  
}  
}  
<CODE ENDS>
```

```
<CODE BEGINS> file "ietf-bgp-rib-table-attributes@2019-10-03.yang"  
submodule ietf-bgp-rib-table-attributes {  
  yang-version "1.1";  
  belongs-to ietf-bgp {  
    prefix "br";  
  }  
  
  // import some basic types  
  import ietf-yang-types {  
    prefix types;  
    reference  
      "RFC 6991, Common YANG Data Types.";  
  }  
  
  include ietf-bgp-rib-types;  
  
  organization  
    "IETF IDR Working Group";  
  
  contact  
    "WG Web:  <http://tools.ietf.org/wg/idr>  
    WG List:  <idr@ietf.org>  
  
    Authors: Mahesh Jethanandani (mjethanandani at gmail.com),  
             Keyur Patel (keyur at arccus.com),  
             Susan Hares (shares at ndzh.com);  
  
  description  
    "This submodule contains common data definitions for data  
    related to a RIB entry, or RIB table.";  
  
  revision "2019-10-03" {  
    description  
      "Initial version.";  
    reference  
      "RFC XXXX: BGP YANG Model for Service Provider Network.";  
  }  
  
  grouping bgp-common-route-annotations-state {
```



```
description
  "Data definitions for flags and other information attached
  to routes in both LOC-RIB and Adj-RIB";

leaf last-modified {
  type types:timeticks;
  description
    "Timestamp when this path was last modified.

    The value is the timestamp in seconds relative to
    the Unix Epoch (Jan 1, 1970 00:00:00 UTC).";
}

leaf valid-route {
  type boolean;
  description
    "Indicates that the route is considered valid by the
    local router";
}

leaf invalid-reason {
  type identityref {
    base invalid-route-reason;
  }
  description
    "If the route is rejected as invalid, this indicates the
    reason.";
}
}

grouping bgp-loc-rib-route-annotations-state {
  description
    "Data definitions for information attached to routes in the
    LOC-RIB";

  // placeholder for route metadata specific to the LOC-RIB
}

grouping bgp-adj-rib-in-post-route-annotations-state {
  description
    "Data definitions for information attached to routes in the
    Adj-RIB-in post-policy table";

  leaf best-path {
    type boolean;
    description
      "Current path was selected as the best path.";
  }
}
```



```
}

grouping bgp-common-table-attrs-state {
  description
    "Common attributes attached to all routing tables";

    // placeholder for metadata associated with all tables
}

grouping bgp-common-table-attrs-top {
  // no enclosing container as this data will fit under an
  // existing LOC-RIB container

  uses bgp-common-table-attrs-state;
  description
    "Operational state data for data related to the entire
    LOC-RIB";
}
}
<CODE ENDS>
```

8. Examples

This section tries to show some examples in how the model can be used.

8.1. Creating BGP Instance

This example shows how to enable BGP with the IPv4 unicast address family, while adding one network to advertise.

[note: '\\' line wrapping for formatting only]

```
<?xml version="1.0" encoding="UTF-8"?>
<config xmlns="urn:ietf:params:xml:ns:netconf:base:1.0">
  <routing
    xmlns="urn:ietf:params:xml:ns:yang:ietf-routing">
    <control-plane-protocols>
      <control-plane-protocol>
        <type
          xmlns:bgpm="urn:ietf:params:xml:ns:yang:ietf-bgp">bgpm:bgp
        </type>
        <name>BGP</name>
        <bgp
          xmlns="urn:ietf:params:xml:ns:yang:ietf-bgp">
          <global>
            <as>64496</as>
            <afi-safis>
              <afi-safi>
                <afi-safi-name
                  xmlns:bt="urn:ietf:params:xml:ns:yang:ietf-bgp-
types">bt:ipv4-\\
unicast
                </afi-safi-name>
              </afi-safi>
            </afi-safis>
          </global>
        </bgp>
      </control-plane-protocol>
    </control-plane-protocols>
  </routing>
</config>
```

8.2. Neighbor Address Family Configuration

This example shows how to configure a BGP peer, where the remote address is 192.0.2.1, the remote AS number is 64497, and the address family of the peer is IPv4 unicast.

[note: '\\' line wrapping for formatting only]

```
<!--
  This example shows a neighbor configuration with damping.
-->

<?xml version="1.0" encoding="UTF-8"?>
<config xmlns="urn:ietf:params:xml:ns:netconf:base:1.0">
  <routing
```


xmlns="urn:ietf:params:xml:ns:yang:ietf-routing">

```

<control-plane-protocols>
  <control-plane-protocol>
    <type
      xmlns:bgp="urn:ietf:params:xml:ns:yang:ietf-bgp">bgp:bgp
    </type>
    <name>name:BGP</name>
    <bgp
      xmlns="urn:ietf:params:xml:ns:yang:ietf-bgp">
      <global>
        <as>64496</as>
        <afi-safis>
          <afi-safi>
            <afi-safi-name
              xmlns:bt="urn:ietf:params:xml:ns:yang:ietf-bgp-
types">bt:ipv4-\
unicast
              </afi-safi-name>
            </afi-safi>
          </afi-safis>
        </global>
        <neighbors>
          <neighbor>
            <remote-address>192.0.2.1</remote-address>
            <peer-as>64497</peer-as>
            <route-flap-damping>
              <enable>true</enable>
              <suppress-above>4.0</suppress-above>
              <reuse-above>3.0</reuse-above>
              <max-flap>15.0</max-flap>
              <reach-decay>100</reach-decay>
              <unreach-decay>500</unreach-decay>
              <keep-history>1000</keep-history>
            </route-flap-damping>
            <description>"Peer Router B"</description>
          <afi-safis>
            <afi-safi>
              <afi-safi-name
                xmlns:bt="urn:ietf:params:xml:ns:yang:ietf-bgp-
types">bt:ipv\
4-unicast
                </afi-safi-name>
              </afi-safi>
            </afi-safis>
          </neighbor>
        </neighbors>
      </bgp>
    </control-plane-protocol>
  </control-plane-protocols>

```

```
</routing>  
</config>
```

8.3. IPv6 Neighbor Configuration

This example shows how to configure a BGP peer, where the remote peer has a IPv6 address, and uses non-default timers for hold-time and keepalive.

[note: '\\' line wrapping for formatting only]

```
<?xml version="1.0" encoding="UTF-8"?>
<config xmlns="urn:ietf:params:xml:ns:netconf:base:1.0">
  <routing
    xmlns="urn:ietf:params:xml:ns:yang:ietf-routing">
    <control-plane-protocols>
      <control-plane-protocol>
        <type
          xmlns:bgp="urn:ietf:params:xml:ns:yang:ietf-bgp">bgp:bgp
        </type>
        <name>name:BGP</name>
        <bgp
          xmlns="urn:ietf:params:xml:ns:yang:ietf-bgp">
          <global>
            <as>64496</as>
            <afi-safis>
              <afi-safi>
                <afi-safi-name
                  xmlns:bt="urn:ietf:params:xml:ns:yang:ietf-bgp-
types">bt:ipv6-\\
unicast
                  </afi-safi-name>
                </afi-safi>
              </afi-safis>
            </global>
            <neighbors>
              <neighbor>
                <remote-address>2001:db8::</remote-address>
                <enabled>true</enabled>
                <peer-as>64497</peer-as>
                <description>"Peer Router B"</description>
                <timers>
                  <hold-time>120</hold-time>
                  <keepalive>70</keepalive>
                </timers>
                <afi-safis>
                  <afi-safi>
                    <afi-safi-name
                      xmlns:bt="urn:ietf:params:xml:ns:yang:ietf-bgp-
types">bt:ipv\\
6-unicast
                    </afi-safi-name>
                  </afi-safi>
                </afi-safis>
              </neighbor>
            </neighbors>
          </bgp>
        </control-plane-protocol>
      </control-plane-protocols>
    </routing>
  </config>
```

</afi-safi-name>
</afi-safi>

```

        </afi-safis>
      </neighbor>
    </neighbors>
  </bgp>
</control-plane-protocol>
</control-plane-protocols>
</routing>
</config>

```

8.4. VRF Configuration

This example shows how BGP can be configured for two VRFs, red and blue. In this case, the two network instances share a common AS, and distinguish between the instances using the router id.

[note: '\\' line wrapping for formatting only]

```

<?xml version="1.0" encoding="UTF-8"?>
<config xmlns="urn:ietf:params:xml:ns:netconf:base:1.0">
  <network-instances
    xmlns="urn:ietf:params:xml:ns:yang:ietf-network-instance">
    <network-instance>
      <name>vrf-red</name>
      <vrf-root>
        <routing
          xmlns="urn:ietf:params:xml:ns:yang:ietf-routing">
            <router-id>192.0.2.1</router-id>
            <control-plane-protocols>
              <control-plane-protocol>
                <type
                  xmlns:bgpm="urn:ietf:params:xml:ns:yang:ietf-bgp">bgpm:bgp
                </type>
                <name>BGP</name>
                <bgp
                  xmlns="urn:ietf:params:xml:ns:yang:ietf-bgp">
                  <global>
                    <as>64496</as>
                    <afi-safis>
                      <afi-safi>
                        <afi-safi-name
                          xmlns:bt="urn:ietf:params:xml:ns:yang:ietf-bgp-
types">bt:ipv4-u\
nicast
                        </afi-safi-name>
                      </afi-safi>
                    </afi-safis>
                  </global>

```


Jethanandani, et al.

Expires April 6, 2020

[Page 124]

```

        </control-plane-protocol>
      </control-plane-protocols>
    </routing>
  </vrf-root>
</network-instance>
<network-instance>
  <name>vrf-blue</name>
  <vrf-root>
    <routing>
      xmlns="urn:ietf:params:xml:ns:yang:ietf-routing">
      <router-id>192.0.2.2</router-id>
      <control-plane-protocols>
        <control-plane-protocol>
          <type
            xmlns:bgpm="urn:ietf:params:xml:ns:yang:ietf-bgp">bgpm:bgp
          </type>
          <name>BGP</name>
          <bgp
            xmlns="urn:ietf:params:xml:ns:yang:ietf-bgp">
            <global>
              <as>64496</as>
              <afi-safis>
                <afi-safi>
                  <afi-safi-name
                    xmlns:bt="urn:ietf:params:xml:ns:yang:ietf-bgp-
types">bt:ipv4-u\
nicast
                  </afi-safi-name>
                </afi-safi>
              </afi-safis>
            </global>
          </bgp>
        </control-plane-protocol>
      </control-plane-protocols>
    </routing>
  </vrf-root>
</network-instance>
</network-instances>
</config>

```

9. Contributors

Previous versions of this document saw contributions from Anees Shaikh, Rob Shakir, Kevin D'Souza, Alexander Clemm, Aleksandr Zhadkin, and Xyfeng Liu.

10. Acknowledgements

The authors are grateful for valuable contributions to this document and the associated models from: Ebben Aires, Pavan Beeram, Chris Chase, Ed Crabbe, Luyuan Fang, Bill Fenner, Akshay Gattani, Josh George, Vijay Gill, Matt John, Jeff Haas, Dhanendra Jain, Acee Lindem, Ina Minei, Carl Moberg, Ashok Narayanan, Einar Nilsen-Nygaard, Adam Simpson, Puneet Sood, Jason Sterne, Jeff Tantsura, Jim Uttaro, and Gunter Vandeveld.

Credit is also due to authors of the OpenConfig, whose model was relied upon to come up with this model.

Special thanks to Robert Wilton who helped convert the YANG models to a NMDA compatible model.

11. References

11.1. Normative references

- [RFC1997] Chandra, R., Traina, P., and T. Li, "BGP Communities Attribute", [RFC 1997](#), DOI 10.17487/RFC1997, August 1996, <<https://www.rfc-editor.org/info/rfc1997>>.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC2439] Villamizar, C., Chandra, R., and R. Govindan, "BGP Route Flap Damping", [RFC 2439](#), DOI 10.17487/RFC2439, November 1998, <<https://www.rfc-editor.org/info/rfc2439>>.
- [RFC3688] Mealling, M., "The IETF XML Registry", [BCP 81](#), [RFC 3688](#), DOI 10.17487/RFC3688, January 2004, <<https://www.rfc-editor.org/info/rfc3688>>.
- [RFC4271] Rekhter, Y., Ed., Li, T., Ed., and S. Hares, Ed., "A Border Gateway Protocol 4 (BGP-4)", [RFC 4271](#), DOI 10.17487/RFC4271, January 2006, <<https://www.rfc-editor.org/info/rfc4271>>.
- [RFC4456] Bates, T., Chen, E., and R. Chandra, "BGP Route Reflection: An Alternative to Full Mesh Internal BGP (IBGP)", [RFC 4456](#), DOI 10.17487/RFC4456, April 2006, <<https://www.rfc-editor.org/info/rfc4456>>.

- [RFC4724] Sangli, S., Chen, E., Fernando, R., Scudder, J., and Y. Rekhter, "Graceful Restart Mechanism for BGP", [RFC 4724](#), DOI 10.17487/RFC4724, January 2007, <<https://www.rfc-editor.org/info/rfc4724>>.
- [RFC4760] Bates, T., Chandra, R., Katz, D., and Y. Rekhter, "Multiprotocol Extensions for BGP-4", [RFC 4760](#), DOI 10.17487/RFC4760, January 2007, <<https://www.rfc-editor.org/info/rfc4760>>.
- [RFC5065] Traina, P., McPherson, D., and J. Scudder, "Autonomous System Confederations for BGP", [RFC 5065](#), DOI 10.17487/RFC5065, August 2007, <<https://www.rfc-editor.org/info/rfc5065>>.
- [RFC6020] Bjorklund, M., Ed., "YANG - A Data Modeling Language for the Network Configuration Protocol (NETCONF)", [RFC 6020](#), DOI 10.17487/RFC6020, October 2010, <<https://www.rfc-editor.org/info/rfc6020>>.
- [RFC6241] Enns, R., Ed., Bjorklund, M., Ed., Schoenwaelder, J., Ed., and A. Bierman, Ed., "Network Configuration Protocol (NETCONF)", [RFC 6241](#), DOI 10.17487/RFC6241, June 2011, <<https://www.rfc-editor.org/info/rfc6241>>.
- [RFC6242] Wasserman, M., "Using the NETCONF Protocol over Secure Shell (SSH)", [RFC 6242](#), DOI 10.17487/RFC6242, June 2011, <<https://www.rfc-editor.org/info/rfc6242>>.
- [RFC6811] Mohapatra, P., Scudder, J., Ward, D., Bush, R., and R. Austein, "BGP Prefix Origin Validation", [RFC 6811](#), DOI 10.17487/RFC6811, January 2013, <<https://www.rfc-editor.org/info/rfc6811>>.
- [RFC6991] Schoenwaelder, J., Ed., "Common YANG Data Types", [RFC 6991](#), DOI 10.17487/RFC6991, July 2013, <<https://www.rfc-editor.org/info/rfc6991>>.
- [RFC7950] Bjorklund, M., Ed., "The YANG 1.1 Data Modeling Language", [RFC 7950](#), DOI 10.17487/RFC7950, August 2016, <<https://www.rfc-editor.org/info/rfc7950>>.
- [RFC8040] Bierman, A., Bjorklund, M., and K. Watsen, "RESTCONF Protocol", [RFC 8040](#), DOI 10.17487/RFC8040, January 2017, <<https://www.rfc-editor.org/info/rfc8040>>.

- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in [RFC 2119](#) Key Words", [BCP 14](#), [RFC 8174](#), DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.
- [RFC8341] Bierman, A. and M. Bjorklund, "Network Configuration Access Control Model", STD 91, [RFC 8341](#), DOI 10.17487/RFC8341, March 2018, <<https://www.rfc-editor.org/info/rfc8341>>.
- [RFC8349] Lhotka, L., Lindem, A., and Y. Qu, "A YANG Data Model for Routing Management (NMDA Version)", [RFC 8349](#), DOI 10.17487/RFC8349, March 2018, <<https://www.rfc-editor.org/info/rfc8349>>.
- [RFC8446] Rescorla, E., "The Transport Layer Security (TLS) Protocol Version 1.3", [RFC 8446](#), DOI 10.17487/RFC8446, August 2018, <<https://www.rfc-editor.org/info/rfc8446>>.
- [RFC8528] Bjorklund, M. and L. Lhotka, "YANG Schema Mount", [RFC 8528](#), DOI 10.17487/RFC8528, March 2019, <<https://www.rfc-editor.org/info/rfc8528>>.
- [RFC8529] Berger, L., Hopps, C., Lindem, A., Bogdanovic, D., and X. Liu, "YANG Data Model for Network Instances", [RFC 8529](#), DOI 10.17487/RFC8529, March 2019, <<https://www.rfc-editor.org/info/rfc8529>>.

11.2. Informative references

- [I-D.ietf-bfd-yang]
Rahman, R., Zheng, L., Jethanandani, M., Networks, J., and G. Mirsky, "YANG Data Model for Bidirectional Forwarding Detection (BFD)", [draft-ietf-bfd-yang-17](#) (work in progress), August 2018.
- [I-D.ietf-rtgwg-policy-model]
Qu, Y., Tantsura, J., Lindem, A., and X. Liu, "A YANG Data Model for Routing Policy Management", [draft-ietf-rtgwg-policy-model-07](#) (work in progress), September 2019.
- [RFC5082] Gill, V., Heasley, J., Meyer, D., Savola, P., Ed., and C. Pignataro, "The Generalized TTL Security Mechanism (GTSM)", [RFC 5082](#), DOI 10.17487/RFC5082, October 2007, <<https://www.rfc-editor.org/info/rfc5082>>.
- [RFC5880] Katz, D. and D. Ward, "Bidirectional Forwarding Detection (BFD)", [RFC 5880](#), DOI 10.17487/RFC5880, June 2010, <<https://www.rfc-editor.org/info/rfc5880>>.

- [RFC5925] Touch, J., Mankin, A., and R. Bonica, "The TCP Authentication Option", [RFC 5925](#), DOI 10.17487/RFC5925, June 2010, <<https://www.rfc-editor.org/info/rfc5925>>.
- [RFC7454] Durand, J., Pepelnjak, I., and G. Doering, "BGP Operations and Security", [BCP 194](#), [RFC 7454](#), DOI 10.17487/RFC7454, February 2015, <<https://www.rfc-editor.org/info/rfc7454>>.
- [RFC7854] Scudder, J., Ed., Fernando, R., and S. Stuart, "BGP Monitoring Protocol (BMP)", [RFC 7854](#), DOI 10.17487/RFC7854, June 2016, <<https://www.rfc-editor.org/info/rfc7854>>.
- [RFC8342] Bjorklund, M., Schoenwaelder, J., Shafer, P., Watsen, K., and R. Wilton, "Network Management Datastore Architecture (NMDA)", [RFC 8342](#), DOI 10.17487/RFC8342, March 2018, <<https://www.rfc-editor.org/info/rfc8342>>.

Appendix A. How to add a new AFI and Augment a Module

This section explains how a new AFI can be defined in a new module and how that module can then be augmented. Assume that the new AFI being defined is called 'foo' which extends the base identity of 'afi-safi-type', and the augmentation is to add a new container for 'foo' under two different XPaths. The example shows how the base identity can be extended to add this new AFI, and then use the augmented containers be used to add 'foo' specific information.

```
module example-newafi-bgp {
  yang-version 1.1;
  namespace "http://example.com/ns/example-newafi-bgp";
  prefix example-newafi-bgp;

  import ietf-routing {
    prefix rt;
    reference
      "RFC 8349, A YANG Data Model for Routing Management
      (NMDA Version)";
  }

  import ietf-bgp {
    prefix "bgp";
    reference
      "RFC XXXX: BGP YANG module for Service Provider Network.";
  }

  import ietf-bgp-types {
    prefix "bt";
```



```
}

organization
  "Newafi model group.";

contact
  "abc@newafi.com";
description
  "This YANG module defines and uses new AFI.";

revision 2019-10-03 {
  description
    "Creating new AFI and using in this model";

  reference
    "RFC XXXX: BGP YANG Model for Service Provider Network.";
}

identity foo {
  base bt:afi-safi-type;
  description
    "New AFI type foo.";
}

augment "/rt:routing/rt:control-plane-protocols/" +
  "rt:control-plane-protocol/bgp:bgp/bgp:global/" +
  "bgp:afi-safis/bgp:afi-safi" {
  when "derived-from-or-self(bgp:afi-safi-name, 'foo')" {
    description
      "This augmentation is valid for a AFI/SAFI instance
        of 'foo'";
  }
  container foo {
    description
      "Container to add 'foo' specific AFI/SAFI information.";
  }
}

augment "/rt:routing/rt:control-plane-protocols/" +
  "rt:control-plane-protocol/bgp:bgp/" +
  "bgp:rib/bgp:afi-safis/bgp:afi-safi" {
  when "derived-from-or-self(bgp:afi-safi-name, 'foo')" {
    description
      "This augmentation is valid for a AFI/SAFI instance
        of 'foo'";
  }
  container foo {
    description
```



```
        "Container to add 'foo' rib specific information.";
    }
}
}
```

[Appendix B](#). How to deviate a module

This example shows how the BGP can be deviated to indicate two nodes that the particular implementation is choosing not to support.

```
module example-newco-bgp {
  yang-version 1.1;
  namespace "http://example.com/ns/example-newco-bgp";
  prefix example-newco-bgp;

  import ietf-bgp {
    prefix "bgp";
  }

  organization
    "Newco model group.";

  contact
    "abc@newco.com";
  description
    "This YANG module deviates IETF BGP YANG module.";

  revision 2019-10-03 {
    description
      "Creating NewCo deviations to ietf-bgp model";

    reference
      "RFC XXXX: BGP YANG module for Service Provider Network.";
  }

  deviation "/bgp:bgp/bgp:global/bgp:graceful-restart/" +
    "bgp:restart-time" {
    deviate not-supported;
  }

  deviation "/bgp:bgp/bgp:global/bgp:graceful-restart/" +
    "bgp:stale-route-time" {
    deviate not-supported;
  }
}
```


Authors' Addresses

Mahesh Jethanandani
VMware

Email: mjethanandani@gmail.com

Keyur Patel
Arrcus
CA
USA

Email: keyur@arrcus.com

Susan Hares
Huawei
7453 Hickory Hill
Saline, MI 48176
USA

Email: shares@ndzh.com

Jeffrey Haas
Juniper Networks

Email: jhaas@pfrc.org

