

Inter-Domain Routing Working Group	J. Haas	
Internet-Draft	Arbor Networks	
Intended status: Standards Track	November 03, 2008	
Expires: May 7, 2009		

[TOC](#)

Definitions of Managed Objects for the Fourth Version of Border Gateway Protocol (BGP-4), Second Version draft-ietf-idr-bgp4-mibv2-08

Status of This Memo

By submitting this Internet-Draft, each author represents that any applicable patent or other IPR claims of which he or she is aware have been or will be disclosed, and any of which he or she becomes aware will be disclosed, in accordance with Section 6 of BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/1id-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

This Internet-Draft will expire on May 7, 2009.

Abstract

This memo defines a portion of the Management Information Base (MIB) for use with network management protocols. In particular it defines objects for managing the Border Gateway Protocol, Version 4.

Table of Contents

- [1.](#) Introduction
- [2.](#) The Internet-Standard Management Framework
- [3.](#) Conventions
- [4.](#) Overview
- [5.](#) Structure of the MIB Module
 - [5.1.](#) Notifications

5.2.	Tables
6.	Relationship to Other MIB Modules
6.1.	Relationship to the TCP-MIB
6.2.	MIB modules required for IMPORTS
7.	Definitions
8.	Security Considerations
9.	IANA Considerations
10.	Contributors
11.	Acknowledgements
12.	References
12.1.	Normative References
12.2.	Informative References

1. Introduction

[TOC](#)

This memo defines a portion of the Management Information Base (MIB) for use with network management protocols. In particular it defines objects for managing the Border Gateway Protocol, Version 4 [\[RFC4271\]](#) (Rekhter, Y., Li, T., and S. Hares, "A Border Gateway Protocol 4 (BGP-4)," January 2006.).

2. The Internet-Standard Management Framework

[TOC](#)

For a detailed overview of the documents that describe the current Internet-Standard Management Framework, please refer to section 7 of RFC 3410 [\[RFC3410\]](#) (Case, J., Mundy, R., Partain, D., and B. Stewart, "Introduction and Applicability Statements for Internet-Standard Management Framework," December 2002.).

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. MIB objects are generally accessed through the Simple Network Management Protocol (SNMP). Objects in the MIB are defined using the mechanisms defined in the Structure of Management Information (SMI). This memo specifies a MIB module that is compliant to the SMIV2, which is described in STD 58, RFC 2578 [\[RFC2578\]](#) (McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Structure of Management Information Version 2 (SMIV2)," April 1999.), STD 58, RFC 2579 [\[RFC2579\]](#) (McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Textual Conventions for SMIV2," April 1999.) and STD 58, RFC 2580 [\[RFC2580\]](#) (McCloghrie, K., Perkins, D., and J. Schoenwaelder, "Conformance Statements for SMIV2," April 1999.).

3. Conventions

[TOC](#)

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in RFC 2119 [\[RFC2119\]](#) (Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels," March 1997.).

4. Overview

[TOC](#)

As part of the IETF standardization effort for the BGP-4 protocol, [\[RFC4273\]](#) (Haas, J. and S. Hares, "Definitions of Managed Objects for BGP-4," January 2006.) was written to address open issues in the previous version of the BGP-4 MIB, [\[RFC1657\]](#) (Willis, S., Burruss, J., and J. Chu, "Definitions of Managed Objects for the Fourth Version of the Border Gateway Protocol (BGP-4) using SMIV2," July 1994.). However, that RFC was primarily intended to address the base BGP-4 protocol as documented in [\[RFC4271\]](#) (Rekhter, Y., Li, T., and S. Hares, "A Border Gateway Protocol 4 (BGP-4)," January 2006.).

The BGP-4 protocol has greatly increased in scope over the years from its original definition. Scaling mechanisms such as [Route Reflection](#) (Bates, T., Chen, E., and R. Chandra, "BGP Route Reflection: An Alternative to Full Mesh Internal BGP (IBGP)," April 2006.) [\[RFC4456\]](#) and [Confederations](#) (Traina, P., McPherson, D., and J. Scudder, "Autonomous System Confederations for BGP," August 2007.) [\[RFC5065\]](#) have been introduced. [Multi-protocol extensions](#) (Bates, T., Chandra, R., Katz, D., and Y. Rekhter, "Multiprotocol Extensions for BGP-4," January 2007.) [\[RFC4760\]](#) were introduced which allowed advertisement of reachability such as [IPv6](#) (Marques, P. and F. Dupont, "Use of BGP-4 Multiprotocol Extensions for IPv6 Inter-Domain Routing," March 1999.) [\[RFC2545\]](#), [MPLS Labeled routes](#) (Rekhter, Y. and E. Rosen, "Carrying Label Information in BGP-4," May 2001.) [\[RFC3107\]](#), etc.

This MIB addresses several of the deficiencies of the previous BGP-4 MIB. In particular:

- *Add the ability to monitor IPv6 BGP-4 peering sessions and carry IPv6 reachability. Other forms of reachability can be added at a later date courtesy of the address-family independent manner in which this was done.
- *Add several counters of operational interest. For example, the number of routes received from a given BGP peer.
- *Replaces objects that were incapable of carrying the full range of their values with ones that can.

*Provides human-readable output for some complex data structures, such as the AS_PATH while also preserving a version of the data that is canonically machine readable.

5. Structure of the MIB Module

[TOC](#)

5.1. Notifications

[TOC](#)

*bgp4V2EstablishedNotification - Sent when a BGP peer transitions into the Established state. Replaces the previous bgpEstablishedNotification from RFC 4273 which was not address family independent.

*bgp4V2BackwardTransitionNotification - Sent when a BGP peer transitions out of the Established state. Replaces the previous bgpBackwardTransNotification, which was not address family independent.

5.2. Tables

[TOC](#)

*bgp4V2DiscontinuityTable - This MIB allows management of more than one instance of the BGP-4 protocol. This table provides the ability to show when a given instance of BGP-4 has suffered an event that may lead to a discontinuity in its objects.

*bgp4V2PeerTable - The BGP peer table. This table is capable of representing IPv6 and other address-family independent peering sessions. This table replaces the bgpPeerTable from RFC 4273.

*bgp4V2PeerErrorsTable - A table of peering session errors. This table covers information previously present in bgpPeerTable from RFC 4273.

*bgp4V2PeerEventTimesTable - A table of peer-specific event timers. This table covers information previously present in bgpPeerTable in RFC 4273 .

- *bgp4V2PeerConfiguredTimersTable - A table of the configured values of peer-specific event timers. This table covers information previously present in bgpPeerTable from RFC 4273.
- *bgp4V2PeerNegotiatedTimersTable - A table of per-peer negotiated timers. This information covers information previously derived from the bgpPeerTable from RFC 4273.
- *bgp4V2PeerCountersTable - A table of per-peer counters for messages and the BGP FSM.
- *bgp4V2PrefixGaugesTable - A table of per-peer per Address Family Identifier-Subsequent Address Family Identifier (AFI-SAFI) [\[RFC4760\] \(Bates, T., Chandra, R., Katz, D., and Y. Rekhter, "Multiprotocol Extensions for BGP-4," January 2007.\)](#) gauges for prefixes.
- *bgp4V2NlriTable - A table of per-peer per AFI-SAFI prefix data. This table covers information previously present in bgp4PathAttrTable from RFC 4273.
- *bgp4V2AdjRibsOutTable - A per-peer per AFI-SAFI table indicating what reachability has been advertised to a given peer.

6. Relationship to Other MIB Modules

[TOC](#)

6.1. Relationship to the TCP-MIB

[TOC](#)

The bgp4V2PeerLocalAddrType/bgp4V2PeerLocalAddr/bgp4V2PeerLocalPort and bgp4V2PeerRemoteAddrType/bgp4V2PeerRemoteAddr/bgp4V2PeerRemotePort objects may provide a suitable index for monitoring the BGP peering session's TCP session via the [TCP-MIB \(Raghunarayan, R., "Management Information Base for the Transmission Control Protocol \(TCP\)," March 2005.\)](#) [RFC4022].

Note that conducting BGP peering sessions over transport protocols other than TCP over IP are out of scope of the current BGP specifications.

[TOC](#)

6.2. MIB modules required for IMPORTS

The following MIB module IMPORTS objects from BGP4V2-TC-MIB [I-D.draft-ietf-idr-bgp4-mibv2-tc], SNMPv2-SMI [\[RFC2578\]](#) (McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Structure of Management Information Version 2 (SMIv2)," April 1999.), SNMPv2-TC [\[RFC2579\]](#) (McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Textual Conventions for SMIv2," April 1999.), SNMPv2-CONF [\[RFC2580\]](#) (McCloghrie, K., Perkins, D., and J. Schoenwaelder, "Conformance Statements for SMIv2," April 1999.), INET-ADDRESS-MIB [\[RFC4001\]](#) (Daniele, M., Haberman, B., Routhier, S., and J. Schoenwaelder, "Textual Conventions for Internet Network Addresses," February 2005.) and SNMP-FRAMEWORK-MIB [\[RFC3411\]](#) (Harrington, D., Presuhn, R., and B. Wijnen, "An Architecture for Describing Simple Network Management Protocol (SNMP) Management Frameworks," December 2002.).

7. Definitions

```
BGP4V2-MIB DEFINITIONS ::= BEGIN
```

```
IMPORTS
```

```
    MODULE-IDENTITY, OBJECT-TYPE, NOTIFICATION-TYPE,
    mib-2, Counter32, Gauge32, Unsigned32
        FROM SNMPv2-SMI
    InetAddressType, InetAddress, InetPortNumber,
    InetAutonomousSystemNumber, InetAddressPrefixLength
        FROM INET-ADDRESS-MIB
    TruthValue, RowPointer, TimeStamp
        FROM SNMPv2-TC
    MODULE-COMPLIANCE, OBJECT-GROUP, NOTIFICATION-GROUP
        FROM SNMPv2-CONF
    SnmpAdminString
        FROM SNMP-FRAMEWORK-MIB
    Bgp4V2IdentifierTC, Bgp4V2AddressFamilyIdentifierTC,
    Bgp4V2SubsequentAddressFamilyIdentifierTC
        FROM BGP4V2-TC-MIB;
```

```
bgp4V2 MODULE-IDENTITY
```

```
    LAST-UPDATED "200811020000Z"
    ORGANIZATION "IETF IDR Working Group"
    CONTACT-INFO "E-mail: idr@ietf.org"
```

```
DESCRIPTION
```

```
    "The MIB module for the BGP-4 protocol.
```

```

    Copyright (C) The IETF Trust (2008). This
    version of this MIB module is part of RFC XXX;
    see the RFC itself for full legal notices."
```

```
-- RFC Editor - replace XXX with RFC number
```

```
REVISION "200811020000Z"
```

```
DESCRIPTION
```

```
    "This MIB updates and replaces the BGP MIB defined in
    RFC 4273."
```

```
::= { mib-2 XXX }
```

```
-- Top level components of this MIB module
```

```
-- Notifications
```

```
bgp4V2Notifications OBJECT IDENTIFIER ::= { bgp4V2 0 }
```

```
-- Objects
```

```
bgp4V2Objects OBJECT IDENTIFIER ::= { bgp4V2 1 }
```

```
-- Conformance
```

```
bgp4V2Conformance OBJECT IDENTIFIER ::= { bgp4V2 2 }
```

```

--
-- Per-instance BGP discontinuities
--

bgp4V2DiscontinuityTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF Bgp4V2DiscontinuityEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Table of BGP-4 discontinuities.  Discontinuities that have
        external visibility occur on a per-BGP instance basis.
        Transitions by a given BGP peer will result in a consistent
        BGP view within that instance and thus do not represent a
        discontinuity from a protocol standpoint."
    ::= { bgp4V2Objects 1 }

bgp4V2DiscontinuityEntry OBJECT-TYPE
    SYNTAX      Bgp4V2DiscontinuityEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Entry representing information about a discontinuity event
        for a given BGP instance."
    INDEX {
        bgp4V2PeerInstance
    }
    ::= { bgp4V2DiscontinuityTable 1 }

Bgp4V2DiscontinuityEntry ::= SEQUENCE {
    bgp4V2DiscontinuityTime
        TimeStamp
}

bgp4V2DiscontinuityTime OBJECT-TYPE
    SYNTAX      TimeStamp
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The value of sysUpTime at the most recent occasion at which
        this BGP management instance has suffered a discontinuity."
    ::= { bgp4V2DiscontinuityEntry 1 }

--
-- Per-peer session management information.
--

bgp4V2PeerTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF Bgp4V2PeerEntry

```

```

MAX-ACCESS not-accessible
STATUS      current
DESCRIPTION
    "BGP peer table.  This table contains, one entry per BGP
    peer, information about the connections with BGP peers."
 ::= { bgp4V2Objects 2 }

```

bgp4V2PeerEntry OBJECT-TYPE

```
SYNTAX      Bgp4V2PeerEntry
```

```
MAX-ACCESS not-accessible
```

```
STATUS      current
```

```
DESCRIPTION
```

```
    "Entry containing information about the connection with
    a remote BGP peer."
```

```
INDEX {
```

```
    bgp4V2PeerInstance,
    bgp4V2PeerLocalAddrType,
    bgp4V2PeerLocalAddr,
    bgp4V2PeerRemoteAddrType,
    bgp4V2PeerRemoteAddr
```

```
}
```

```
::= { bgp4V2PeerTable 1 }
```

Bgp4V2PeerEntry ::= SEQUENCE {

```
-- INDEX information
```

```
    bgp4V2PeerInstance
```

```
        Unsigned32,
```

```
    bgp4V2PeerLocalAddrType
```

```
        InetAddressType,
```

```
    bgp4V2PeerLocalAddr
```

```
        InetAddress,
```

```
    bgp4V2PeerRemoteAddrType
```

```
        InetAddressType,
```

```
    bgp4V2PeerRemoteAddr
```

```
        InetAddress,
```

```
-- Local
```

```
    bgp4V2PeerLocalPort
```

```
        InetPortNumber,
```

```
    bgp4V2PeerLocalAs
```

```
        InetAutonomousSystemNumber,
```

```
    bgp4V2PeerLocalIdentifier
```

```
        Bgp4V2IdentifierTC,
```

```
-- Remote
```

```
    bgp4V2PeerRemotePort
```

```
        InetPortNumber,
```

```
    bgp4V2PeerRemoteAs
```

```
        InetAutonomousSystemNumber,
```

```

    bgp4V2PeerRemoteIdentifier
        Bgp4V2IdentifierTC,

    -- Session status
    bgp4V2PeerAdminStatus
        INTEGER,
    bgp4V2PeerState
        INTEGER,
    bgp4V2PeerDescription
        SnmpAdminString
}

bgp4V2PeerInstance OBJECT-TYPE
    SYNTAX      Unsigned32 (1..4294967295)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The routing instance index.

        Some BGP implementations permit the creation of
        multiple instances of a BGP routing process. An
        example includes routers running BGP/MPLS IP Virtual
        Private Networks.

        Implementations that do not support multiple
        routing instances should return 1 for this object."
    ::= { bgp4V2PeerEntry 1 }

bgp4V2PeerLocalAddrType OBJECT-TYPE
    SYNTAX      InetAddressType
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The address family of the local end of the peering
        session."
    ::= { bgp4V2PeerEntry 2 }

bgp4V2PeerLocalAddr OBJECT-TYPE
    SYNTAX      InetAddress
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The local IP address of this entry's BGP connection."
    ::= { bgp4V2PeerEntry 3 }

bgp4V2PeerRemoteAddrType OBJECT-TYPE
    SYNTAX      InetAddressType
    MAX-ACCESS  not-accessible
    STATUS      current

```

DESCRIPTION

"The address family of the remote end of the peering session."

::= { bgp4V2PeerEntry 4 }

bgp4V2PeerRemoteAddr OBJECT-TYPE

SYNTAX InetAddress

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The remote IP address of this entry's BGP peer."

::= { bgp4V2PeerEntry 5 }

bgp4V2PeerLocalPort OBJECT-TYPE

SYNTAX InetPortNumber

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The local port for the TCP connection between the BGP peers."

::= { bgp4V2PeerEntry 6 }

bgp4V2PeerLocalAs OBJECT-TYPE

SYNTAX InetAutonomousSystemNumber

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Some implementations of BGP can represent themselves as multiple ASes. This is the AS that this peering session is representing itself as to the remote peer."

::= { bgp4V2PeerEntry 7 }

bgp4V2PeerLocalIdentifier OBJECT-TYPE

SYNTAX Bgp4V2IdentifierTC

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The BGP Identifier of the local system for this peering session. It is REQUIRED that all bgp4V2PeerLocalIdentifier values for the same bgp4V2PeerInstance be identical."

REFERENCE

"RFC 4271, Section 4.2, 'BGP Identifier'."

::= { bgp4V2PeerEntry 8 }

bgp4V2PeerRemotePort OBJECT-TYPE

SYNTAX InetPortNumber

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The remote port for the TCP connection between the BGP peers.

Note that the objects bgp4V2PeerLocalAddr, bgp4V2PeerLocalPort, bgp4V2PeerRemoteAddr and bgp4V2PeerRemotePort provide the appropriate reference to the standard MIB TCP connection table, or even the ipv6 TCP MIB as in RFC 4022."

REFERENCE

"RFC 2012 - SNMPv2 Management Information Base for the Transmission Control Protocol using SMIPv2.

RFC 4022 - IP Version 6 Management Information Base for the Transmission Control Protocol."

::= { bgp4V2PeerEntry 9 }

bgp4V2PeerRemoteAs OBJECT-TYPE

SYNTAX InetAutonomousSystemNumber

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The remote autonomous system number received in the BGP OPEN message."

REFERENCE

"RFC 4271, Section 4.2."

::= { bgp4V2PeerEntry 10 }

bgp4V2PeerRemoteIdentifier OBJECT-TYPE

SYNTAX Bgp4V2IdentifierTC

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The BGP Identifier of this entry's remote BGP peer.

This entry should be 0.0.0.0 unless the bgp4V2PeerState is in the openconfirm or the established state."

REFERENCE

"RFC 4271, Section 4.2, 'BGP Identifier'."

::= { bgp4V2PeerEntry 11 }

bgp4V2PeerAdminStatus OBJECT-TYPE

SYNTAX INTEGER {
halted(1),
running(2)
}

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Whether or not the BGP FSM for this remote peer is

halted or running. The BGP FSM for a remote peer is halted after processing a Stop event. Likewise, it is in the running state after a Start event.

The bgp4V2PeerState will generally be in the idle state when the FSM is halted, although some extensions such as Graceful Restart will leave the peer in the Idle state but with the FSM running."

REFERENCE

"RFC 4271, Section 8.1.2."

::= { bgp4V2PeerEntry 12 }

bgp4V2PeerState OBJECT-TYPE

SYNTAX INTEGER {

idle(1),

connect(2),

active(3),

opensent(4),

openconfirm(5),

established(6)

}

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The BGP peer connection state."

REFERENCE

"RFC 4271, Section 8.2.2."

::= { bgp4V2PeerEntry 13 }

bgp4V2PeerDescription OBJECT-TYPE

SYNTAX SnmpAdminString

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A user configured description identifying this peer. When this object is not the empty string, this object SHOULD contain a description that is unique within a given BGP instance for this peer."

::= { bgp4V2PeerEntry 14 }

--

-- Per-peer error management information.

--

bgp4V2PeerErrorsTable OBJECT-TYPE

SYNTAX SEQUENCE OF Bgp4V2PeerErrorsEntry

MAX-ACCESS not-accessible

```

STATUS      current
DESCRIPTION
    "On a per-peer basis, this table reflects the last
    protocol-defined error encountered and reported on
    the peer session."
 ::= { bgp4V2Objects 3 }

```

```

bgp4V2PeerErrorsEntry OBJECT-TYPE
    SYNTAX      Bgp4V2PeerErrorsEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Each entry contains information about errors sent
        and received for a particular BGP peer."
    AUGMENTS {
        bgp4V2PeerEntry
    }
    ::= { bgp4V2PeerErrorsTable 1 }

```

```

Bgp4V2PeerErrorsEntry ::= SEQUENCE {
    bgp4V2PeerLastErrorCodeReceived
        OCTET STRING,
    bgp4V2PeerLastErrorSubCodeReceived
        OCTET STRING,
    bgp4V2PeerLastErrorReceivedTime
        TimeStamp,
    bgp4V2PeerLastErrorReceivedText
        SnmpAdminString,
    bgp4V2PeerLastErrorReceivedData
        OCTET STRING,
    bgp4V2PeerLastErrorCodeSent
        OCTET STRING,
    bgp4V2PeerLastErrorSubCodeSent
        OCTET STRING,
    bgp4V2PeerLastErrorSentTime
        TimeStamp,
    bgp4V2PeerLastErrorSentText
        SnmpAdminString,
    bgp4V2PeerLastErrorSentData
        OCTET STRING
}

```

```

bgp4V2PeerLastErrorCodeReceived OBJECT-TYPE
    SYNTAX      OCTET STRING (SIZE (1))
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The last error code received from this peer via
        NOTIFICATION message on this connection. If no error has

```

occurred, this field is zero."
REFERENCE
"RFC 4271, Section 4.5.
RFC 4486 optionally supported.
RFC 3362, Section 5 optionally supported."
::= { bgp4V2PeerErrorsEntry 1 }

bgp4V2PeerLastErrorSubCodeReceived OBJECT-TYPE

SYNTAX OCTET STRING (SIZE (1))
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The last subcode received from this peer via NOTIFICATION
message on this connection. If no error has occurred, this
field is zero."
REFERENCE
"RFC 4271, Section 4.5.
RFC 4486 optionally supported.
RFC 3362, Section 5 optionally supported."
::= { bgp4V2PeerErrorsEntry 2 }

bgp4V2PeerLastErrorReceivedTime OBJECT-TYPE

SYNTAX TimeStamp
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The timestamp that the last NOTIFICATION was received from
this peer."
REFERENCE
"RFC 4271, Section 4.5."
::= { bgp4V2PeerErrorsEntry 3 }

bgp4V2PeerLastErrorReceivedText OBJECT-TYPE

SYNTAX SnmpAdminString
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"This object contains an implementation specific
explanation of the error that was reported."
::= { bgp4V2PeerErrorsEntry 4 }

bgp4V2PeerLastErrorReceivedData OBJECT-TYPE

SYNTAX OCTET STRING (SIZE(0..4075))
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The last error code's data seen by this peer.

Per RFC 2578, some implementations may have limitations

dealing with OCTET STRINGS larger than 255. Thus, this data may be truncated."

REFERENCE

"RFC 4271, Section 4.5,
RFC 2578, Section 7.1.2,
RFC 4486 optionally supported.
RFC 3362, Section 5 optionally supported."

::= { bgp4V2PeerErrorsEntry 5 }

bgp4V2PeerLastErrorCodeSent OBJECT-TYPE

SYNTAX OCTET STRING (SIZE (1))

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The last error code sent to this peer via NOTIFICATION message on this connection. If no error has occurred, this field is zero."

REFERENCE

"RFC 4271, Section 4.5.
RFC 4486 optionally supported.
RFC 3362, Section 5 optionally supported."

::= { bgp4V2PeerErrorsEntry 6 }

bgp4V2PeerLastErrorSubCodeSent OBJECT-TYPE

SYNTAX OCTET STRING (SIZE (1))

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The last subcode sent to this peer via NOTIFICATION message on this connection. If no error has occurred, this field is zero."

REFERENCE

"RFC 4271, Section 4.5.
RFC 4486 optionally supported.
RFC 3362, Section 5 optionally supported."

::= { bgp4V2PeerErrorsEntry 7 }

bgp4V2PeerLastErrorSentTime OBJECT-TYPE

SYNTAX TimeStamp

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The timestamp that the last NOTIFICATION was sent to this peer."

REFERENCE

"RFC 4271, Section 4.5."

::= { bgp4V2PeerErrorsEntry 8 }

bgp4V2PeerLastErrorSentText OBJECT-TYPE

```

SYNTAX      SnmpAdminString
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "This object contains an implementation specific
    explanation of the error that is being reported."
 ::= { bgp4V2PeerErrorsEntry 9 }

```

bgp4V2PeerLastErrorSentData OBJECT-TYPE

```

SYNTAX      OCTET STRING (SIZE(0..4075))
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The last error code's data sent to this peer.

    Per RFC 2578, some implementations may have limitations
    dealing with OCTET STRINGS larger than 255. Thus, this
    data may be truncated."
REFERENCE
    "RFC 4271, Section 4.5,
    RFC 2578, Section 7.1.2
    RFC 4486 optionally supported.
    RFC 3362, Section 5 optionally supported."
 ::= { bgp4V2PeerErrorsEntry 10 }

```

```

--
-- Per-peer Event Times
--

```

bgp4V2PeerEventTimesTable OBJECT-TYPE

```

SYNTAX      SEQUENCE OF Bgp4V2PeerEventTimesEntry
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
    "A table reporting the per-peering session amount
    of time elapsed and update events since the peering
    session advanced into the established state."
 ::= { bgp4V2Objects 4 }

```

bgp4V2PeerEventTimesEntry OBJECT-TYPE

```

SYNTAX      Bgp4V2PeerEventTimesEntry
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
    "Each row contains a set of statistics about time
    spent and events encountered in the peer session
    established state."
AUGMENTS {

```

```

        bgp4V2PeerEntry
    }
    ::= { bgp4V2PeerEventTimesTable 1 }

Bgp4V2PeerEventTimesEntry ::= SEQUENCE {
    bgp4V2PeerFsmEstablishedTime
        Gauge32,
    bgp4V2PeerInUpdatesElapsedTime
        Gauge32
}

bgp4V2PeerFsmEstablishedTime OBJECT-TYPE
    SYNTAX      Gauge32
    UNITS        "seconds"
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
        "This timer indicates how long (in seconds) this peer
         has been in the established state or how long since this
         peer was last in the established state. It is set to
         zero when a new peer is configured or when the router is
         booted. If the peer has never reached the established
         state, the value remains zero."
    REFERENCE
        "RFC 4271, Section 8."
    ::= { bgp4V2PeerEventTimesEntry 1 }

bgp4V2PeerInUpdatesElapsedTime OBJECT-TYPE
    SYNTAX      Gauge32
    UNITS        "seconds"
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
        "Elapsed time (in seconds) since the last BGP UPDATE
         message was received from the peer. Each time
         bgpPeerInUpdates is incremented, the value of this
         object is set to zero (0)."
    REFERENCE
        "RFC 4271, Section 4.3.
         RFC 4271, Section 8.2.2, Established state."
    ::= { bgp4V2PeerEventTimesEntry 2 }

--
-- Per-Peer Configured Timers
--

bgp4V2PeerConfiguredTimersTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF Bgp4V2PeerConfiguredTimersEntry

```

```

MAX-ACCESS not-accessible
STATUS      current
DESCRIPTION
    "Per peer management data on BGP session timers."
::= { bgp4V2Objects 5 }

```

```

bgp4V2PeerConfiguredTimersEntry OBJECT-TYPE
    SYNTAX      Bgp4V2PeerConfiguredTimersEntry
    MAX-ACCESS not-accessible
    STATUS      current
    DESCRIPTION
        "Each entry corresponds to the current state of
         BGP timers on a given peering session."
    AUGMENTS {
        bgp4V2PeerEntry
    }
    ::= { bgp4V2PeerConfiguredTimersTable 1 }

```

```

Bgp4V2PeerConfiguredTimersEntry ::= SEQUENCE {
    bgp4V2PeerConnectRetryInterval
        Unsigned32,
    bgp4V2PeerHoldTimeConfigured
        Unsigned32,
    bgp4V2PeerKeepAliveConfigured
        Unsigned32,
    bgp4V2PeerMinASOrigInterval
        Unsigned32,
    bgp4V2PeerMinRouteAdverInterval
        Unsigned32
}

```

```

bgp4V2PeerConnectRetryInterval OBJECT-TYPE
    SYNTAX      Unsigned32 (1..65535)
    UNITS        "seconds"
    MAX-ACCESS read-only
    STATUS      current
    DESCRIPTION
        "Time interval (in seconds) for the ConnectRetry timer.
         The suggested value for this timer is 120 seconds."
    REFERENCE
        "RFC 4271, Section 8.2.2. This is the value used
         to initialize the 'ConnectRetryTimer'."
    ::= { bgp4V2PeerConfiguredTimersEntry 1 }

```

```

bgp4V2PeerHoldTimeConfigured OBJECT-TYPE
    SYNTAX      Unsigned32 ( 0 | 3..65535 )
    UNITS        "seconds"
    MAX-ACCESS read-only
    STATUS      current

```

DESCRIPTION

"Time interval (in seconds) for the Hold Timer established with the peer. The value of this object is calculated by this BGP speaker, using the smaller of the values in bgpPeerHoldTimeConfigured and the Hold Time received in the OPEN message.

This value must be at least three seconds if it is not zero (0).

If the Hold Timer has not been established with the peer this object MUST have a value of zero (0).

If the bgpPeerHoldTimeConfigured object has a value of (0), then this object MUST have a value of (0)."

REFERENCE

"RFC 4271, Section 4.2."

::= { bgp4V2PeerConfiguredTimersEntry 2 }

bgp4V2PeerKeepAliveConfigured OBJECT-TYPE

SYNTAX Unsigned32 (0 | 1..21845)

UNITS "seconds"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Time interval (in seconds) for the KeepAlive timer configured for this BGP speaker with this peer. The value of this object will only determine the KEEPALIVE messages' frequency relative to the value specified in bgpPeerHoldTimeConfigured; the actual time interval for the KEEPALIVE messages is indicated by bgpPeerKeepAlive.

A reasonable maximum value for this timer would be one third of that of bgpPeerHoldTimeConfigured.

If the value of this object is zero (0), no periodic KEEPALIVE messages are sent to the peer after the BGP connection has been established. The suggested value for this timer is 30 seconds."

REFERENCE

"RFC 4271, Section 4.4.

RFC 4271, Section 10."

::= { bgp4V2PeerConfiguredTimersEntry 3 }

bgp4V2PeerMinASOrigInterval OBJECT-TYPE

SYNTAX Unsigned32 (0..65535)

UNITS "seconds"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Time interval (in seconds) for the
MinASOriginationInterval timer.

The suggested value for this timer is 15 seconds."

REFERENCE

"RFC 4271, Section 9.2.1.2.

RFC 4271, Section 10."

::= { bgp4V2PeerConfiguredTimersEntry 4 }

bgp4V2PeerMinRouteAdverInterval OBJECT-TYPE

SYNTAX Unsigned32 (0..65535)

UNITS "seconds"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Time interval (in seconds) for the
MinRouteAdvertisementInterval timer.

The suggested value for this timer is 30 seconds for
EBGP connections and 5 seconds for IBGP connections."

REFERENCE

"RFC 4271, Section 9.2.1.1.

RFC 4271, Section 10."

::= { bgp4V2PeerConfiguredTimersEntry 5 }

--

-- Per-Peer Negotiated Timers

--

bgp4V2PeerNegotiatedTimersTable OBJECT-TYPE

SYNTAX SEQUENCE OF Bgp4V2PeerNegotiatedTimersEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"Configured values of per-peer timers are seen
in the bgp4V2PeerConfiguredTimersTable.

Values in this table reflect the current
operational values, after negotiation from values
derived from initial configuration."

::= { bgp4V2Objects 6 }

bgp4V2PeerNegotiatedTimersEntry OBJECT-TYPE

SYNTAX Bgp4V2PeerNegotiatedTimersEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"Each entry reflects a value of the currently

```

        operational, negotiated timer as reflected in the
        Bgp4V2PeerNegotiatedTimersEntry."
AUGMENTS {
    bgp4V2PeerEntry
}
::= { bgp4V2PeerNegotiatedTimersTable 1 }

Bgp4V2PeerNegotiatedTimersEntry ::= SEQUENCE {
    bgp4V2PeerHoldTime
        Unsigned32,
    bgp4V2PeerKeepAlive
        Unsigned32
}

bgp4V2PeerHoldTime OBJECT-TYPE
    SYNTAX      Unsigned32 ( 0 | 3..65535 )
    UNITS        "seconds"
    MAX-ACCESS  read-only
    STATUS       current
    DESCRIPTION
        "The value of this object is calculated by this BGP
        Speaker as being;

        zero (0) - if this was the value sent by the peer and
        this value is permitted by this BGP Speaker. In this
        case, no keepalive messages are sent and the Hold Timer
        is not set.

        At least three (3). This value is the smaller of
        the value sent by this peer in the OPEN message and
        bgp4V2PeerHoldTimeConfigured for this peer.

        This value is only defined when the peering session is
        in the Established state."
    REFERENCE
        "RFC 4271, Section 4.2."
    ::= { bgp4V2PeerNegotiatedTimersEntry 1 }

bgp4V2PeerKeepAlive OBJECT-TYPE
    SYNTAX      Unsigned32 ( 0 | 1..21845 )
    UNITS        "seconds"
    MAX-ACCESS  read-only
    STATUS       current
    DESCRIPTION
        "Time interval in seconds for the KeepAlive timer
        established with the peer. The value of this object
        is calculated by this BGP speaker such that, when
        compared with bgp4V2PeerHoldTime, it has the same
        proportion as what bgp4V2PeerKeepAliveConfigured has

```

when compared with bgp4V2PeerHoldTimeConfigured. If the value of this object is zero (0), it indicates that the KeepAlive timer has not been established with the peer, or, the value of bgp4V2PeerKeepAliveConfigured is zero (0).

This value is only defined when the peering session is in the Established state."

REFERENCE

"RFC 4271, Section 4.4."

::= { bgp4V2PeerNegotiatedTimersEntry 2 }

--

-- Per-peer counters

--

bgp4V2PeerCountersTable OBJECT-TYPE

SYNTAX SEQUENCE OF Bgp4V2PeerCountersEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The counters associated with a BGP Peer."

::= { bgp4V2Objects 7 }

bgp4V2PeerCountersEntry OBJECT-TYPE

SYNTAX Bgp4V2PeerCountersEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"Each entry contains counters of message transmissions and FSM transitions for a given BGP Peering session."

AUGMENTS {

bgp4V2PeerEntry

}

::= { bgp4V2PeerCountersTable 1 }

Bgp4V2PeerCountersEntry ::= SEQUENCE {

bgp4V2PeerInUpdates

Counter32,

bgp4V2PeerOutUpdates

Counter32,

bgp4V2PeerInTotalMessages

Counter32,

bgp4V2PeerOutTotalMessages

Counter32,

bgp4V2PeerFsmEstablishedTransitions

Counter32

}

```

bgp4V2PeerInUpdates OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The number of BGP UPDATE messages received on this
        connection."
    ::= { bgp4V2PeerCountersEntry 1 }

bgp4V2PeerOutUpdates OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The number of BGP UPDATE messages transmitted on this
        connection."
    ::= { bgp4V2PeerCountersEntry 2 }

bgp4V2PeerInTotalMessages OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The total number of messages received from the remote
        peer on this connection."
    ::= { bgp4V2PeerCountersEntry 3 }

bgp4V2PeerOutTotalMessages OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The total number of messages transmitted to the remote
        peer on this connection."
    ::= { bgp4V2PeerCountersEntry 4 }

bgp4V2PeerFsmEstablishedTransitions OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The total number of times the BGP FSM transitioned into
        the established state for this peer."
    ::= { bgp4V2PeerCountersEntry 5 }

--
-- Per-Peer Prefix Gauges
--

```

```

bgp4V2PrefixGaugesTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF Bgp4V2PrefixCountersEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Additional per-peer, per AFI-SAFI counters for
        prefixes"
    ::= { bgp4V2Objects 8 }

bgp4V2PrefixGaugesEntry OBJECT-TYPE
    SYNTAX      Bgp4V2PrefixCountersEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Entry containing information about a bgp-peers prefix
        counters."
    INDEX {
        bgp4V2PeerInstance,
        bgp4V2PeerLocalAddrType,
        bgp4V2PeerLocalAddr,
        bgp4V2PeerRemoteAddrType,
        bgp4V2PeerRemoteAddr,
        bgp4V2PrefixGaugesAfi,
        bgp4V2PrefixGaugesSafi
    }
    ::= { bgp4V2PrefixGaugesTable 1 }

Bgp4V2PrefixCountersEntry ::= SEQUENCE {
    bgp4V2PrefixGaugesAfi
        Bgp4V2AddressFamilyIdentifierTC,
    bgp4V2PrefixGaugesSafi
        Bgp4V2SubsequentAddressFamilyIdentifierTC,
    bgp4V2PrefixInPrefixes
        Gauge32,
    bgp4V2PrefixInPrefixesAccepted
        Gauge32,
    bgp4V2PrefixOutPrefixes
        Gauge32
}

bgp4V2PrefixGaugesAfi OBJECT-TYPE
    SYNTAX      Bgp4V2AddressFamilyIdentifierTC
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The AFI index of the per-peer, per prefix counters"
    ::= { bgp4V2PrefixGaugesEntry 1 }

bgp4V2PrefixGaugesSafi OBJECT-TYPE

```

SYNTAX Bgp4V2SubsequentAddressFamilyIdentifierTC
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
 "The SAFI index of the per-peer, per prefix counters"
 ::= { bgp4V2PrefixGaugesEntry 2 }

bgp4V2PrefixInPrefixes OBJECT-TYPE

SYNTAX Gauge32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "The number of prefixes received from a peer and are
 stored in the Adj-Ribs-In for that peer.

 Note that this number does not reflect prefixes that
 have been discarded due to policy."
REFERENCE
 "RFC 4271, Sections 3.2 and 9."
 ::= { bgp4V2PrefixGaugesEntry 3 }

bgp4V2PrefixInPrefixesAccepted OBJECT-TYPE

SYNTAX Gauge32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "The number of prefixes for a peer that are installed
 in the Adj-Ribs-In and are eligible to become active
 in the Loc-Rib."
REFERENCE
 "RFC 4271, Sections 3.2 and 9."
 ::= { bgp4V2PrefixGaugesEntry 4 }

bgp4V2PrefixOutPrefixes OBJECT-TYPE

SYNTAX Gauge32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "The number of prefixes for a peer that are installed
 in that peer's Adj-Ribs-Out."
REFERENCE
 "RFC 4271, Sections 3.2 and 9."
 ::= { bgp4V2PrefixGaugesEntry 5 }

--
-- BGP NLRI
--

bgp4V2NlriTable OBJECT-TYPE

```

SYNTAX      SEQUENCE OF Bgp4V2NlriEntry
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
    "The BGP-4 Received Path Attribute Table contains
    information about paths to destination networks
    received from all BGP4 peers. Collectively, this
    represents the Adj-Ribs-In. The route where
    bgp4V2NlriBest is true represents, for this NLRI,
    the route that is installed in the LocRib from the
    Adj-Ribs-In."
REFERENCE
    "RFC 4271, Sections 3.2 and 9."
 ::= { bgp4V2Objects 9 }

```

```

bgp4V2NlriEntry OBJECT-TYPE
    SYNTAX      Bgp4V2NlriEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Information about a path to a network."
    INDEX {
        bgp4V2PeerInstance,
        bgp4V2NlriAfi,
        bgp4V2NlriSafi,
        bgp4V2NlriPrefix,
        bgp4V2NlriPrefixLen,
        bgp4V2PeerLocalAddrType,
        bgp4V2PeerLocalAddr,
        bgp4V2PeerRemoteAddrType,
        bgp4V2PeerRemoteAddr,
        bgp4V2NlriIndex
    }
 ::= { bgp4V2NlriTable 1 }

```

```

Bgp4V2NlriEntry ::= SEQUENCE {
    bgp4V2NlriIndex
        Unsigned32,
    bgp4V2NlriAfi
        Bgp4V2AddressFamilyIdentifierTC,
    bgp4V2NlriSafi
        Bgp4V2SubsequentAddressFamilyIdentifierTC,
    bgp4V2NlriPrefixType
        InetAddressType,
    bgp4V2NlriPrefix
        InetAddress,
    bgp4V2NlriPrefixLen
        InetAddressPrefixLength,
    bgp4V2NlriBest

```

```

        TruthValue,
    bgp4V2NlriCalcLocalPref
        Unsigned32,
    bgp4V2NlriOrigin
        INTEGER,
    bgp4V2NlriNextHopAddrType
        InetAddressType,
    bgp4V2NlriNextHopAddr
        InetAddress,
    bgp4V2NlriLinkLocalNextHopAddrType
        InetAddressType,
    bgp4V2NlriLinkLocalNextHopAddr
        InetAddress,
    bgp4V2NlriLocalPrefPresent
        TruthValue,
    bgp4V2NlriLocalPref
        Unsigned32,
    bgp4V2NlriMedPresent
        TruthValue,
    bgp4V2NlriMed
        Unsigned32,
    bgp4V2NlriAtomicAggregate
        INTEGER,
    bgp4V2NlriAggregatorPresent
        TruthValue,
    bgp4V2NlriAggregatorAS
        InetAutonomousSystemNumber,
    bgp4V2NlriAggregatorAddr
        Bgp4V2IdentifierTC,
    bgp4V2NlriAsPathCalcLength
        Unsigned32,
    bgp4V2NlriAsPathString
        SnmpAdminString,
    bgp4V2NlriAsPath
        OCTET STRING,
    bgp4V2NlriPathAttrUnknown
        OCTET STRING
}

```

bgp4V2NlriIndex OBJECT-TYPE

SYNTAX Unsigned32

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"This index allows for multiple instances of a base prefix for a certain AFI-SAFI from a given peer. This is currently useful for two things:

1. Allowing for a peer in future implementations to send more than a single route instance.

2. Allow for extensions which extend the NLRI field to send the same prefix while utilizing other extension specific information. An example of this is RFC 3107 - Carrying MPLS labels in BGP."

REFERENCE

"RFC 3107 - Carrying Label Information in BGP-4."

::= { bgp4V2NlriEntry 1 }

bgp4V2NlriAfi OBJECT-TYPE

SYNTAX Bgp4V2AddressFamilyIdentifierTC

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The address family of the prefix for this NLRI.

Note that the AFI is not necessarily equivalent to the an InetAddressType."

REFERENCE

"RFC 4760 - Multiprotocol Extensions for BGP-4"

::= { bgp4V2NlriEntry 2 }

bgp4V2NlriSafi OBJECT-TYPE

SYNTAX Bgp4V2SubsequentAddressFamilyIdentifierTC

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The subsequent address family of the prefix for this NLRI"

REFERENCE

"RFC 4760 - Multiprotocol Extensions for BGP-4"

::= { bgp4V2NlriEntry 3 }

bgp4V2NlriPrefixType OBJECT-TYPE

SYNTAX InetAddressType

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The type of the IP address prefix in the Network Layer Reachability Information field. The value of this object is derived from the appropriate value from the bgp4V2NlriAfi field. Where an appropriate InetAddressType is not available, the value of the object must be unknown(0)."

::= { bgp4V2NlriEntry 4 }

bgp4V2NlriPrefix OBJECT-TYPE

SYNTAX InetAddress

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"An IP address prefix in the Network Layer Reachability Information field. This object is an IP address containing the prefix with length specified by bgp4V2NlriPrefixLen. Any bits beyond the length specified by bgp4V2NlriPrefixLen are zeroed."

REFERENCE

"RFC 4271, Section 4.3."

::= { bgp4V2NlriEntry 5 }

bgp4V2NlriPrefixLen OBJECT-TYPE

SYNTAX InetAddressPrefixLength

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"Length in bits of the address prefix in the Network Layer Reachability Information field."

::= { bgp4V2NlriEntry 6 }

bgp4V2NlriBest OBJECT-TYPE

SYNTAX TruthValue

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"An indication of whether or not this route was chosen as the best BGP4 route for this destination."

REFERENCE

"RFC 4271, Section 9.1.2."

::= { bgp4V2NlriEntry 7 }

bgp4V2NlriCalcLocalPref OBJECT-TYPE

SYNTAX Unsigned32

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The degree of preference calculated by the receiving BGP4 speaker for an advertised route.

In the case where this prefix is ineligible, the value of this object will be zero (0)."

REFERENCE

"RFC 4271, Section 9.1.1"

::= { bgp4V2NlriEntry 8 }

bgp4V2NlriOrigin OBJECT-TYPE

```

SYNTAX      INTEGER {
    igp(1), -- networks are interior
    egp(2), -- networks learned via the EGP protocol
    incomplete(3) -- networks that
                  -- are learned by some other
                  -- means
    }
MAX-ACCESS read-only
STATUS      current
DESCRIPTION
    "The ultimate origin of the path information."
REFERENCE
    "RFC 4271, Section 4.3.
     RFC 4271, Section 5.1.1."
::= { bgp4V2NlriEntry 9 }

```

bgp4V2NlriNextHopAddrType OBJECT-TYPE

```

SYNTAX      InetAddressType
MAX-ACCESS read-only
STATUS      current
DESCRIPTION
    "The address family of the address for
     the border router that should be used
     to access the destination network."
::= { bgp4V2NlriEntry 10 }

```

bgp4V2NlriNextHopAddr OBJECT-TYPE

```

SYNTAX      InetAddress (SIZE(4..20))
MAX-ACCESS read-only
STATUS      current
DESCRIPTION
    "The address of the border router that
     should be used to access the destination
     network. This address is the nexthop
     address received in the UPDATE packet associated with
     this prefix.

```

Note that for RFC2545 style double nexthops, this object will always contain the global scope nexthop. bgpPathAttrLinkLocalNextHop will contain the linklocal scope nexthop, if it is present.

In the case a mechanism is developed to use only a link local nexthop, bgp4V2NlriNextHopAddr will contain the link local nexthop."

```

REFERENCE
    "RFC 4271, Section 4.3,
     RFC 4271, Section 5.1.3,
     RFC 2545, Section 3."

```

::= { bgp4V2NlriEntry 11 }

bgp4V2NlriLinkLocalNextHopAddrType OBJECT-TYPE

SYNTAX InetAddressType

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The address type for IPv6 link local addresses.
This is present only when receiving RFC 2545
style double nexthops.

This object is optionally present in BGP
implementations that do not support IPv6.

When no IPv6 link local nexthop is present, the value of
this object should be unknown(0)."

REFERENCE

"RFC 2545, Section 3."

::= { bgp4V2NlriEntry 12 }

bgp4V2NlriLinkLocalNextHopAddr OBJECT-TYPE

SYNTAX InetAddress

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"This value contains an IPv6 link local address
and is present only when receiving RFC 2545 style
double nexthops.

This object is optionally present in BGP
implementations that do not support IPv6.

When no IPv6 link local nexthop is present, the length of
this object should be zero."

REFERENCE

"RFC 2545, Section 3."

::= { bgp4V2NlriEntry 13 }

bgp4V2NlriLocalPrefPresent OBJECT-TYPE

SYNTAX TruthValue

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"This value is true when the LOCAL_PREF value was sent in
the UPDATE message."

::= { bgp4V2NlriEntry 14 }

bgp4V2NlriLocalPref OBJECT-TYPE

SYNTAX Unsigned32

MAX-ACCESS read-only

STATUS current
DESCRIPTION
"The originating BGP4 speakers degree of preference for an advertised route."
REFERENCE
"RFC 4271, Section 4.3.
RFC 4271, Section 5.1.5."
::= { bgp4V2NlriEntry 15 }

bgp4V2NlriMedPresent OBJECT-TYPE

SYNTAX TruthValue
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"This value is true when the MED value was sent in the UPDATE message."
::= { bgp4V2NlriEntry 16 }

bgp4V2NlriMed OBJECT-TYPE

SYNTAX Unsigned32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"This metric is used to discriminate between multiple exit points to an adjacent autonomous system. When the MED value is absent but has a calculated default value, this object will contain the calculated value."
REFERENCE
"RFC 4271, Section 4.3.
RFC 4271, Section 5.1.4."
::= { bgp4V2NlriEntry 17 }

bgp4V2NlriAtomicAggregate OBJECT-TYPE

SYNTAX TruthValue
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"This value is true when the ATOMIC_AGGREGATE Path Attribute is present and indicates that the NLRI MUST NOT be made more specific."
REFERENCE
"RFC 4271, Sections 5.1.6 and 9.1.4."
::= { bgp4V2NlriEntry 18 }

bgp4V2NlriAggregatorPresent OBJECT-TYPE

SYNTAX TruthValue
MAX-ACCESS read-only
STATUS current
DESCRIPTION

"This value is true when the AGGREGATOR path attribute was sent in the UPDATE message."
::= { bgp4V2NlriEntry 19 }

bgp4V2NlriAggregatorAS OBJECT-TYPE

SYNTAX InetAutonomousSystemNumber
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The AS number of the last BGP4 speaker that performed route aggregation. When bgp4V2NlriAggregatorPresent is false, the value of this object should be zero (0)."
REFERENCE
"RFC 4271, Section 5.1.7.
RFC 4271, Section 9.2.2.2."
::= { bgp4V2NlriEntry 20 }

bgp4V2NlriAggregatorAddr OBJECT-TYPE

SYNTAX Bgp4V2IdentifierTC
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The IP address of the last BGP4 speaker that performed route aggregation. When bgp4V2NlriAggregatorPresent is false, the value of this object should be 0.0.0.0"
REFERENCE
"RFC 4271, Section 5.1.7.
RFC 4271, Section 9.2.2.2."
::= { bgp4V2NlriEntry 21 }

bgp4V2NlriAsPathCalcLength OBJECT-TYPE

SYNTAX Unsigned32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"This value represents the calculated length of the AS Path according to the rules of the BGP specification. This value is used in route selection."
REFERENCE
"RFC 4271, Section 9.1.2.2.a"
::= { bgp4V2NlriEntry 22 }

bgp4V2NlriAsPathString OBJECT-TYPE

SYNTAX SnmpAdminString
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"This is a string depicting the autonomous system path to this network which was received from the

peer which advertised it. The format of the string is implementation-dependent, and should be designed for operator readability.

Note that SnmpAdminString is only capable of representing a maximum of 255 characters. This may lead to the string being truncated in the presence of a large AS Path. It is RECOMMENDED that when this object's contents will be truncated that the final 3 octets be reserved for the ellipses string, '...'. bgp4V2NlriAsPath may give access to the full AS Path."

::= { bgp4V2NlriEntry 23 }

-- Maximum size of the following is derived as
-- 4096 max message size
-- - 16 BGP message marker bytes
-- - 2 BGP message size
-- - 1 BGP message type (UPDATE with unknown attr)
-- - 2 UPDATE routes length (even assuming no routes)
-- - 2 UPDATE path attributes length
-- - 1 path attribute flag octet
-- -----
-- 4072 bytes maximum per-message attribute value data

bgp4V2NlriAsPath OBJECT-TYPE

SYNTAX OCTET STRING (SIZE(2..4072))

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"In order to provide a canonicalized form of the BGP-4 AS_PATH along with the human-readable bgp4V2NlriAsPathString, which may be truncated, this object contains the contents of the BGP-4 AS_PATH Path Attribute. This object may be parsed using the rules defined for Four-octet ASes as defined in RFC 4893. RFC 4271, Section 4.3, 'Path Attributes: b) AS_PATH' as amended by RFC 5065, Section 3 defines the general format of the AS_PATH path attribute and its code points.

In brief, the AS_PATH is composed of a sequence of AS Segments. Each AS Segment is represented by a triple:
<path segment type, path segment length,
path segment value>.

The path segment type and path segment length fields are one octet in length each.

The path segment type field may be one of:

1 - AS_SET (RFC 4721, Section 4.3)

- 2 - AS_SEQUENCE (RFC 4271, Section 4.3)
- 3 - AS_CONFED_SEQUENCE (RFC 3065, Section 5)
- 4 - AS_CONFED_SET (RFC 3065, Section 5)

The path segment length field contains the number of ASes (not the number of octets) in the path segment value field.

The path segment value field contains one or more AS numbers, each encoded as a 4-octet length field in network byte order.

Note that since an SNMP agent may truncate this object to less than its maximum theoretical length of 4072 octets users of this object should be prepared to deal with a truncated and thus malformed AS_PATH. It is RECOMMENDED that when such truncation would occur on the boundary of an encoded AS that the partial AS be discarded from this object and the object's size be adjusted accordingly. Further, it is also RECOMMENDED that when such truncation, either alone or in conjunction with the truncation of a partially encoded AS described previously, would yield an empty path segment value field that the path segment type and path segment length components of the truncated AS_PATH also be discarded and the object's size be adjusted accordingly."

REFERENCE

"RFC 4271, Section 4.3.
RFC 5065, Section 5.
RFC 4893."

::= { bgp4V2NlriEntry 24 }

bgp4V2NlriPathAttrUnknown OBJECT-TYPE

SYNTAX OCTET STRING (SIZE(0..4072))

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Path Attributes not understood by this implementation SHOULD be presented in this object. Those Path Attributes use the type, length, value encoding documented in RFC 4271, Section 4.3, 'Path Attributes'.

Note that since an SNMP agent may truncate this object to less than its maximum theoretical length of 4072 octets users of this object should be prepared to deal with a truncated and thus malformed Path Attribute."

REFERENCE

"RFC 4271, Section 4.3."

::= { bgp4V2NlriEntry 25 }

--

-- Adj-Ribs-Out Table

--

bgp4V2AdjRibsOutTable OBJECT-TYPE

SYNTAX SEQUENCE OF Bgp4V2AdjRibsOutEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"This table contains on a per-peer basis one or more routes from the bgp4V2NlriTable that have been placed in this peer's Adj-Ribs-Out."

REFERENCE

"RFC 4271, Section 3.2."

::= { bgp4V2Objects 10 }

bgp4V2AdjRibsOutEntry OBJECT-TYPE

SYNTAX Bgp4V2AdjRibsOutEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"List of BGP routes that have been placed into a peer's Adj-Ribs-Out."

INDEX {

bgp4V2PeerInstance,
bgp4V2NlriAfi,
bgp4V2NlriSafi,
bgp4V2NlriPrefix,
bgp4V2NlriPrefixLen,
bgp4V2PeerLocalAddrType,
bgp4V2PeerLocalAddr,
bgp4V2PeerRemoteAddrType,
bgp4V2PeerRemoteAddr,
bgp4V2AdjRibsOutIndex

}

::= { bgp4V2AdjRibsOutTable 1 }

Bgp4V2AdjRibsOutEntry ::= SEQUENCE {

bgp4V2AdjRibsOutIndex

Unsigned32,

bgp4V2AdjRibsOutRoute

RowPointer

}

bgp4V2AdjRibsOutIndex OBJECT-TYPE

SYNTAX Unsigned32

MAX-ACCESS not-accessible

```

STATUS      current
DESCRIPTION
    "Certain extensions to BGP permit multiple instance of
      a per afi, per safi prefix to be advertised to a peer.
      This object allows the enumeration of them."
::= { bgp4V2AdjRibsOutEntry 1 }

```

bgp4V2AdjRibsOutRoute OBJECT-TYPE

```

SYNTAX      RowPointer
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "This object points to the route in the bgp4V2NlriTable
      that corresponds to the entry in the peer's
      Adj-Rib-Out. Outgoing route maps are not
      reflected at this point as those are part of the
      Update-Send process."
REFERENCE
    "RFC 4271, Section 9.2."
::= { bgp4V2AdjRibsOutEntry 2 }

```

```

--
-- Notifications
--

```

bgp4V2EstablishedNotification NOTIFICATION-TYPE

```

OBJECTS {
    bgp4V2PeerState,
    bgp4V2PeerLocalPort,
    bgp4V2PeerRemotePort
}
STATUS current
DESCRIPTION
    "The BGP Established event is generated when
      the BGP FSM enters the established state."
::= { bgp4V2Notifications 1 }

```

bgp4V2BackwardTransitionNotification NOTIFICATION-TYPE

```

OBJECTS {
    bgp4V2PeerState,
    bgp4V2PeerLocalPort,
    bgp4V2PeerRemotePort,
    bgp4V2PeerLastErrorCodeReceived,
    bgp4V2PeerLastErrorSubCodeReceived,
    bgp4V2PeerLastErrorReceivedText
}
STATUS current
DESCRIPTION
    "The BGPBackwardTransition Event is generated

```

when the BGP FSM moves from a higher numbered state to a lower numbered state.

Due to the nature of the BGP state machine, an implementation MAY rate limit the generation of this event. An implementation MAY also generate this notification ONLY when the state machine moves out of the established state. An implementation should document its specific behavior."

::= { bgp4V2Notifications 2 }

--

-- Conformance Information

--

bgp4V2Compliances OBJECT IDENTIFIER ::= { bgp4V2Conformance 1 }

bgp4V2Groups OBJECT IDENTIFIER ::= { bgp4V2Conformance 2 }

bgp4V2Compliance MODULE-COMPLIANCE

STATUS current

DESCRIPTION

"The compliance statement for entities which implement the BGP4 mib."

MODULE -- this module

MANDATORY-GROUPS {

bgp4V2StdMIBTimersGroup,
bgp4V2StdMIBCountersGroup,
bgp4V2StdMIBErrorsGroup,
bgp4V2StdMIBPeerGroup,
bgp4V2StdMIBNlriGroup,
bgp4V2GlobalsGroup
}

GROUP bgp4V2StdMIBNotificationGroup

DESCRIPTION

"Implementation of BGP Notifications are completely optional in this MIB."

OBJECT bgp4V2PeerLocalAddr

SYNTAX InetAddress (SIZE(4|16|20))

DESCRIPTION

"An implementation is required to support IPv4 peering sessions. An implementation MAY support IPv6 peering sessions. IPv6 link-local peering sessions MAY be supported by this MIB."

OBJECT bgp4V2PeerRemoteAddr

SYNTAX InetAddress (SIZE(4|16|20))

DESCRIPTION

"An implementation is required to support IPv4 peering sessions. An implementation MAY support IPv6 peering sessions. IPv6 link-local peering sessions MAY be supported by this MIB."

OBJECT bgp4V2NlriPrefix

SYNTAX InetAddress (SIZE(0..16))

DESCRIPTION

"An implementation is required to support IPv4 prefixes. An implementation MAY support IPv6 prefixes."

OBJECT bgp4V2NlriLinkLocalNextHopAddrType

SYNTAX InetAddressType

DESCRIPTION

"This object is only present when RFC 2545 extensions for IPv6 are supported by the implementation. When present, this object shall only have a value of ipv6z or none."

OBJECT bgp4V2NlriLinkLocalNextHopAddr

SYNTAX InetAddress (SIZE(0|20))

DESCRIPTION

"This object is only present when RFC 2545 extensions for IPv6 are supported by the implementation. When present, this object shall only have a size of 20 or 0 when no RFC 2545 double-nexthop is present."

OBJECT bgp4V2PeerInstance

SYNTAX Unsigned32 (1..4294967295)

DESCRIPTION

"This object represents an abstract index which can utilize the full range of acceptable SNMP index values."

::= { bgp4V2Compliances 4 }

bgp4V2GlobalsGroup OBJECT-GROUP

OBJECTS { bgp4V2DiscontinuityTime }

STATUS current

DESCRIPTION

"A collection of objects providing information on global BGP state."

::= { bgp4V2Groups 1 }

bgp4V2StdMIBTimersGroup OBJECT-GROUP

OBJECTS {

bgp4V2PeerFsmEstablishedTime,
bgp4V2PeerInUpdatesElapsedTime,
bgp4V2PeerConnectRetryInterval,
bgp4V2PeerHoldTimeConfigured,

```

        bgp4V2PeerKeepAliveConfigured,
        bgp4V2PeerMinASOrigInterval,
        bgp4V2PeerMinRouteAdverInterval,
        bgp4V2PeerHoldTime,
        bgp4V2PeerKeepAlive
    }
    STATUS current
    DESCRIPTION
        "Objects associated with BGP peering timers."
    ::= { bgp4V2Groups 2 }

```

bgp4V2StdMIBCountersGroup OBJECT-GROUP

```

    OBJECTS {
        bgp4V2PeerInUpdates,
        bgp4V2PeerOutUpdates,
        bgp4V2PeerInTotalMessages,
        bgp4V2PeerOutTotalMessages,
        bgp4V2PeerFsmEstablishedTransitions,
        bgp4V2PrefixInPrefixes,
        bgp4V2PrefixInPrefixesAccepted,
        bgp4V2PrefixOutPrefixes
    }
    STATUS current
    DESCRIPTION
        "Objects to count discrete events and exchanges on BGP
        sessions."
    ::= { bgp4V2Groups 3 }

```

bgp4V2StdMIBErrorsGroup OBJECT-GROUP

```

    OBJECTS {
        bgp4V2PeerLastErrorCodeReceived,
        bgp4V2PeerLastErrorSubCodeReceived,
        bgp4V2PeerLastErrorReceivedData,
        bgp4V2PeerLastErrorReceivedTime,
        bgp4V2PeerLastErrorReceivedText,
        bgp4V2PeerLastErrorCodeSent,
        bgp4V2PeerLastErrorSubCodeSent,
        bgp4V2PeerLastErrorSentData,
        bgp4V2PeerLastErrorSentTime,
        bgp4V2PeerLastErrorSentText
    }
    STATUS current
    DESCRIPTION
        "Errors received on BGP peering sessions."
    ::= { bgp4V2Groups 5 }

```

bgp4V2StdMIBPeerGroup OBJECT-GROUP

```

    OBJECTS {
        bgp4V2PeerState,

```

```

        bgp4V2PeerAdminStatus,
        bgp4V2PeerLocalPort,
        bgp4V2PeerLocalAs,
        bgp4V2PeerRemotePort,
        bgp4V2PeerRemoteAs,
        bgp4V2PeerLocalIdentifier,
        bgp4V2PeerRemoteIdentifier,
        bgp4V2PeerDescription
    }
    STATUS current
    DESCRIPTION
        "Core object types on BGP peering sessions."
    ::= { bgp4V2Groups 6 }

```

bgp4V2StdMIBNlriGroup OBJECT-GROUP

```

    OBJECTS {
        bgp4V2NlriAsPathCalcLength,
        bgp4V2NlriAsPathString,
        bgp4V2NlriBest,
        bgp4V2NlriCalcLocalPref,
        bgp4V2NlriPrefixType,
        bgp4V2AdjRibsOutRoute,
        bgp4V2NlriAggregatorPresent,
        bgp4V2NlriAggregatorAS,
        bgp4V2NlriAggregatorAddr,
        bgp4V2NlriAtomicAggregate,
        bgp4V2NlriLocalPref,
        bgp4V2NlriLocalPrefPresent,
        bgp4V2NlriMed,
        bgp4V2NlriMedPresent,
        bgp4V2NlriNextHopAddr,
        bgp4V2NlriNextHopAddrType,
        bgp4V2NlriLinkLocalNextHopAddrType,
        bgp4V2NlriLinkLocalNextHopAddr,
        bgp4V2NlriOrigin,
        bgp4V2NlriAsPath,
        bgp4V2NlriPathAttrUnknown
    }
    STATUS current
    DESCRIPTION
        "Attributes received on BGP peering sessions."
    ::= { bgp4V2Groups 7 }

```

bgp4V2StdMIBNotificationGroup NOTIFICATION-GROUP

```

    NOTIFICATIONS {
        bgp4V2EstablishedNotification,
        bgp4V2BackwardTransitionNotification
    }
    STATUS current

```

DESCRIPTION

"Notifications in this modules are completely optional."
::= { bgp4V2Groups 8 }

END

8. Security Considerations

[TOC](#)

There are no management objects defined in this MIB module that have a MAX-ACCESS clause of read-write and/or read-create. So, if this MIB module is implemented correctly, then there is no risk that an intruder can alter or create any management objects of this MIB module via direct SNMP SET operations.

Some of the readable objects in this MIB module (i.e., objects with a MAX-ACCESS other than not-accessible) may be considered sensitive or vulnerable in some network environments. It is thus important to control even GET and/or NOTIFY access to these objects and possibly to even encrypt the values of these objects when sending them over the network via SNMP. These are the tables and objects and their sensitivity/vulnerability:

*bgp4V2PeerLocalAddrType, bgp4V2PeerLocalAddr, bgp4V2PeerLocalPort
bgp4V2PeerRemoteAddrType, bgp4V2PeerRemoteAddr,
bgp4V2PeerRemotePort, bgp4V2PeerLocalAddr, bgp4V2PeerLocalPort,
bgp4V2PeerRemoteAddr, bgp4V2PeerRemotePort - A BGP peer's local
and remote addresses might be sensitive for ISPs who want to keep
interface addresses on routers confidential in order to prevent
router addresses used for a denial of service attack or spoofing.
Note that other tables which share elements of these objects as
indexes may similarly expose sensitive information.

*bgp4V2NlriTable, bgp4V2AdjRibsOutTable - A BGP peer's routing
information may be sensitive for ISPs as the contents of their
routing tables may expose details related to business
relationships as implemented in Internet routing.

SNMP versions prior to SNMPv3 did not include adequate security. Even if the network itself is secure (for example by using IPSec), even then, there is no control as to who on the secure network is allowed to access and GET/SET (read/change/create/delete) the objects in this MIB module.

It is RECOMMENDED that implementers consider the security features as provided by the SNMPv3 framework (see [\[RFC3410\]](#) (Case, J., Mundy, R., Partain, D., and B. Stewart, "Introduction and Applicability Statements for Internet-Standard Management Framework," December 2002.)), section

8), including full support for the SNMPv3 cryptographic mechanisms (for authentication and privacy).

Further, deployment of SNMP versions prior to SNMPv3 is NOT RECOMMENDED. Instead, it is RECOMMENDED to deploy SNMPv3 and to enable cryptographic security. It is then a customer/operator responsibility to ensure that the SNMP entity giving access to an instance of this MIB module is properly configured to give access to the objects only to those principals (users) that have legitimate rights to indeed GET or SET (change/create/delete) them.

9. IANA Considerations

[TOC](#)

IANA is requested to assign this MIB module an OID under mib-2.

10. Contributors

[TOC](#)

This document owes significant thanks over the years to Wayne Tackabury, Susan Hares and the members of the IDR and OPS-NM mailing lists. This document represents several years of negotiating operational needs, Internet operational security considerations and the sheer messiness of representing the BGP protocol in SMIV2.

I owe particular thanks to Susan Hares as a mentor who let me dive head-first into the world of Internet standards work by saying, "We have this MIB that just needs a little cleanup to advance in the standards process."

11. Acknowledgements

[TOC](#)

We would like to acknowledge the assistance of all the members of the Inter-Domain Routing Working Group, all individuals you contributed to RFCs 1269, 1657 and 4273.

The origin of this document is from RFC 1269 "Definitions of Managed Objects for the Border Gateway Protocol (Version 3)" written by Steve Willis and John Burruss, which was updated by John Chu to support BGP-4 in RFC 1657. The author wishes to acknowledge the fine work of these original authors.

[TOC](#)

12. References

12.1. Normative References

[TOC](#)

[RFC2119]	Bradner, S. , " Key words for use in RFCs to Indicate Requirement Levels ," BCP 14, RFC 2119, March 1997 (TXT , HTML , XML).
[RFC2578]	McCloghrie, K., Ed. , Perkins, D., Ed. , and J. Schoenwaelder, Ed. , " Structure of Management Information Version 2 (SMIv2) ," STD 58, RFC 2578, April 1999 (TXT).
[RFC2579]	McCloghrie, K., Ed. , Perkins, D., Ed. , and J. Schoenwaelder, Ed. , " Textual Conventions for SMIv2 ," STD 58, RFC 2579, April 1999 (TXT).
[RFC2580]	McCloghrie, K. , Perkins, D. , and J. Schoenwaelder , " Conformance Statements for SMIv2 ," STD 58, RFC 2580, April 1999 (TXT).
[RFC3411]	Harrington, D., Presuhn, R., and B. Wijnen, " An Architecture for Describing Simple Network Management Protocol (SNMP) Management Frameworks ," STD 62, RFC 3411, December 2002 (TXT).
[RFC4271]	Rekhter, Y., Li, T., and S. Hares, " A Border Gateway Protocol 4 (BGP-4) ," RFC 4271, January 2006 (TXT).
[RFC4273]	Haas, J. and S. Hares, " Definitions of Managed Objects for BGP-4 ," RFC 4273, January 2006 (TXT).
[RFC2545]	Marques, P. and F. Dupont , " Use of BGP-4 Multiprotocol Extensions for IPv6 Inter-Domain Routing ," RFC 2545, March 1999 (TXT).
[RFC4001]	Daniele, M., Haberman, B., Routhier, S., and J. Schoenwaelder, " Textual Conventions for Internet Network Addresses ," RFC 4001, February 2005 (TXT).
[RFC4760]	Bates, T., Chandra, R., Katz, D., and Y. Rekhter, " Multiprotocol Extensions for BGP-4 ," RFC 4760, January 2007 (TXT).
[RFC5065]	Traina, P., McPherson, D., and J. Scudder, " Autonomous System Confederations for BGP ," RFC 5065, August 2007 (TXT).

12.2. Informative References

[TOC](#)

[RFC3410]	Case, J., Mundy, R., Partain, D., and B. Stewart, " Introduction and Applicability Statements for Internet-Standard Management Framework ," RFC 3410, December 2002 (TXT).
[RFC1657]	

	Willis, S., Burruss, J., and J. Chu, "Definitions of Managed Objects for the Fourth Version of the Border Gateway Protocol (BGP-4) using SMIV2," RFC 1657, July 1994 (TXT).
[RFC3107]	Rekhter, Y. and E. Rosen, " Carrying Label Information in BGP-4 ," RFC 3107, May 2001 (TXT).
[RFC4022]	Raghunarayan, R., " Management Information Base for the Transmission Control Protocol (TCP) ," RFC 4022, March 2005 (TXT).
[RFC4456]	Bates, T., Chen, E., and R. Chandra, " BGP Route Reflection: An Alternative to Full Mesh Internal BGP (IBGP) ," RFC 4456, April 2006 (TXT).

Author's Address

[TOC](#)

	Jeffrey Haas
	Arbor Networks
Phone:	
EMail:	jhaas@arbor.net

Full Copyright Statement

[TOC](#)

Copyright © The IETF Trust (2008).

This document is subject to the rights, licenses and restrictions contained in BCP 78, and except as set forth therein, the authors retain all their rights.

This document and the information contained herein are provided on an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY, THE IETF TRUST AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Intellectual Property

The IETF takes no position regarding the validity or scope of any Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; nor does it represent that it has made any independent effort to identify any such rights. Information on the procedures with respect to rights in RFC documents can be found in BCP 78 and BCP 79.

Copies of IPR disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF on-line IPR repository at <http://www.ietf.org/ipr>.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement this standard. Please address the information to the IETF at ietf-ipr@ietf.org.