Internet Engineering Task Force Internet-Draft Updates: <u>5575</u> (if approved) Intended status: Standards Track Expires: April 27, 2015

Clarification of the Flowspec Redirect Extended Community draft-ietf-idr-flowspec-redirect-rt-bis-02

Abstract

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of <u>BCP 78</u> and <u>BCP 79</u>.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <u>http://datatracker.ietf.org/drafts/current/</u>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on April 27, 2015.

Copyright Notice

Copyright (c) 2014 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to <u>BCP 78</u> and the IETF Trust's Legal Provisions Relating to IETF Documents (<u>http://trustee.ietf.org/license-info</u>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License. Table of Contents

<u>1</u> .	Introduction	•	 						2
<u>2</u> .	IANA Considerations		 						4
<u>3</u> .	Security Considerations .		 						4
<u>4</u> .	Acknowledgements		 						4
<u>5</u> .	Normative References		 						<u>5</u>
Aut	hor's Address		 						<u>5</u>

1. Introduction

Dissemination of Flow Specification Rules [<u>RFC5575</u>], commonly known as BGP Flowspec, provided for a BGP Extended Community [<u>RFC4360</u>] that served to redirect traffic to a VRF routing instance that matched the flow specification NLRI. In that RFC, the Redirect Extended Community was documented as follows:

```
: | type | extended community | encoding
: +----+
: | 0x8008 | redirect | 6-byte Route Target
: +----+
: [...]
: Redirect: The redirect extended community allows the traffic to be
: redirected to a VRF routing instance that lists the specified
: route-target in its import policy. If several local instances
: match this criteria, the choice between them is a local matter
: (for example, the instance with the lowest Route Distinguisher
: value can be elected). This extended community uses the same
: encoding as the Route Target extended community [RFC4360].
: [...]
Ξ.
: 11. IANA Considerations
: [...]
: The following traffic filtering flow specification rules have been
: allocated by IANA from the "BGP Extended Communities Type -
: Experimental Use" registry as follows:
: [...]
۰.
: 0x8008 - Flow spec redirect
```

The IANA registry of BGP Extended Communities clearly identifies communities of specific formats. For example, "Two-octet AS Specific Extended Community" [<u>RFC4360</u>], "Four-octet AS Specific Extended Community" [<u>RFC5668</u>] and "IPv4 Address Specific Extended Community"

[Page 2]

Internet-Draft <u>draft-ietf-idr-flowspec-redirect-rt-bis</u> October 2014

[<u>RFC4360</u>]. Route Targets [<u>RFC4360</u>] identify this format in the highorder (Type) octet of the Extended Community and set the value of the low-order (Sub-Type) octet to 0x02. The Value field of the Route Target Extended Community is intended to be interpreted in the context of its format.

Since the Redirect Extended Community only registered a single codepoint in the IANA BGP Extended Community registry, a common interpretation of the redirect extended community's "6-byte route target" has been to look, at a receiving router, for a route target value that matches the route target value in the received redirect extended community, and import the advertised route to the corresponding VRF instance subject to the rules defined in <u>RFC 5575</u> [<u>RFC 5575</u>]. However, because the route target format in the redirect extended community is not clearly defined, the wrong match may occur.

This "value wildcard" matching behavior, that does not take into account the format of the route target defined for a local VRF and may result in the wrong matching decision, does not match deployed implementations of BGP flowspec. Deployed implementations of BGP flowspec solve this problem by defining different redirect extended communities that are specific to the format of the route target value. This document defines the following redirect extended communities:

type	extended community	+ encoding +	
0x8008	redirect AS-2byte	2-octet AS, 4-octet Value	
0x8108	redirect IPv4	4-octet IPv4 Address, 2-octet Value	
0x8208	redirect AS-4byte	4-octet AS, 2-octet Value	

It should be noted that the low-order nybble of the Redirect's Type field corresponds to the Route Target Extended Community format field (Type). (See [<u>RFC4360</u>], Secs. 3.1, 3.2, and 4 plus [<u>RFC5668</u>], Sec. 2.) The low order octet (Sub-Type) of the Redirect Extended Community remains 0x08, contrasted to 0x02 for Route Targets.

The IANA Registries for BGP Extended Communities [RFC7153] document was written to update the previously-mentioned IANA registries to better document BGP Extended Community formats. The IANA Considerations section below further amends those registry updates in order to properly document the flowspec redirect communities.

[Page 3]

2. IANA Considerations

IANA is requested to update the "BGP Generic Transitive Experimental Use Extended Community Sub-Types" registry as follows:

0x08 - Flow spec redirect AS-2byte format.

IANA is requested to update the "BGP Transitive Extended Community Types" registry as follows:

- 0x81 Generic Transitive Experimental Use Extended Community Part 2 (Sub-Types are defined in the "Generic Transitive Experimental Extended Community Part 2 Sub-Types" Registry)
- 0x82 Generic Transitive Experimental Use Extended Community
 Part 3 (Sub-Types are defined in the "Generic Transitive
 Experimental Extended Community Part 3 Sub-Types" Registry)

IANA is requested to create the "Generic Transitive Experimental Use Extended Community Part 2 Sub-Types" registry. It should be seeded with the following Sub-Type:

0x08 - Flow spec redirect IPv4 format.

IANA is requested to create the "Generic Transitive Experimental Use Extended Community Part 3 Sub-Types" registry. It should be seeded with the following Sub-Type:

0x08 - Flow spec redirect AS-4byte format.

3. Security Considerations

This document introduces no additional security considerations than those already covered in [<u>RFC5575</u>].

4. Acknowledgements

The contents of this document was raised as part of implementation discussions of BGP Flowspec with the following individuals:

Andrew Karch (Cisco) Robert Raszuk Adam Simpson (Alcatel-Lucent) Matthieu Texier (Arbor Networks) Kaliraj Vairavakkalai (Juniper)

Expires April 27, 2015 [Page 4]

5. Normative References

- [RFC4360] Sangli, S., Tappan, D., and Y. Rekhter, "BGP Extended Communities Attribute", <u>RFC 4360</u>, February 2006.
- [RFC5575] Marques, P., Sheth, N., Raszuk, R., Greene, B., Mauch, J., and D. McPherson, "Dissemination of Flow Specification Rules", <u>RFC 5575</u>, August 2009.
- [RFC5668] Rekhter, Y., Sangli, S., and D. Tappan, "4-Octet AS Specific BGP Extended Community", <u>RFC 5668</u>, October 2009.
- [RFC7153] Rosen, E. and Y. Rekhter, "IANA Registries for BGP Extended Communities", <u>RFC 7153</u>, March 2014.

Author's Address

Jeffrey Haas (editor) Juniper Networks 1194 N. Mathida Ave. Sunnyvale, CA 94089 US

Email: jhaas@juniper.net

Expires April 27, 2015 [Page 5]