

IDR  
Internet-Draft  
Intended status: Standards Track  
Expires: April 27, 2017

J. Heitz, Ed.  
Cisco  
J. Snijders, Ed.  
NTT  
K. Patel  
Arrcus  
I. Bagdonas  
Equinix  
A. Simpson  
Nokia  
N. Hilliard  
INEX  
October 24, 2016

**Large BGP Communities**  
**draft-ietf-idr-large-community-04**

Abstract

This document describes the Large BGP Communities attribute, an extension to BGP-4. This attribute provides a mechanism to signal opaque information within separate namespaces to aid in routing management. The attribute is suitable for use in four-octet ASNs.

Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on April 27, 2017.

## Copyright Notice

Copyright (c) 2016 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](http://trustee.ietf.org/license-info) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

<a href="#">1.</a>	Introduction . . . . .	<a href="#">2</a>
<a href="#">2.</a>	Large BGP Communities Attribute . . . . .	<a href="#">3</a>
<a href="#">3.</a>	Aggregation . . . . .	<a href="#">4</a>
<a href="#">4.</a>	Canonical Representation . . . . .	<a href="#">4</a>
<a href="#">5.</a>	Reserved Large BGP Community values . . . . .	<a href="#">4</a>
<a href="#">6.</a>	Error Handling . . . . .	<a href="#">4</a>
<a href="#">7.</a>	Security Considerations . . . . .	<a href="#">5</a>
8.	Implementation status - RFC EDITOR: REMOVE BEFORE PUBLICATION	5
<a href="#">9.</a>	IANA Considerations . . . . .	<a href="#">6</a>
<a href="#">10.</a>	Acknowledgments . . . . .	<a href="#">6</a>
<a href="#">11.</a>	References . . . . .	<a href="#">6</a>
<a href="#">11.1.</a>	Normative References . . . . .	<a href="#">6</a>
<a href="#">11.2.</a>	Informative References . . . . .	<a href="#">7</a>
<a href="#">11.3.</a>	URIs . . . . .	<a href="#">7</a>
	Authors' Addresses . . . . .	<a href="#">8</a>

## [1.](#) Introduction

BGP implementations typically support a routing policy language to control the distribution of routing information. Network operators attach BGP communities to routes to identify intrinsic properties of these routes. These properties may include information such as the route origin location, or specification of a routing policy action to be taken, or one that has been taken, and may apply to an individual route or to a group of routes. Because BGP communities are optional transitive BGP attributes, BGP communities may be acted upon or otherwise used by routing policies in other Autonomous Systems (ASes) on the Internet.

[RFC1997] BGP Communities attributes are four-octet values split into two two-octet words. The most significant word is interpreted as an



Local Data Part 2: A four-octet operator-defined value.



The Global Administrator field is intended to allow different Autonomous Systems to define Large BGP Communities without collision. Implementations MUST allow the operator to specify any value for the Global Administrator field.

There is no significance to the order in which Large BGP Communities are encoded in the BGP path attribute payload. A BGP speaker can transmit them in any order.

Duplicate Large BGP Communities SHOULD NOT be transmitted. A receiving speaker SHOULD silently remove duplicate Large BGP Communities from a BGP UPDATE message.

### **3. Aggregation**

If a range of routes is aggregated, then the resulting aggregate should have a Large BGP Communities attribute which contains all of the Large BGP Communities attributes from all of the aggregated routes.

### **4. Canonical Representation**

Large BGP Communities MUST be represented as three separate unsigned integers in decimal notation, without leading zeros, in the following order: Global Administrator, Local Data 1, Local Data 2. Numbers MUST not be omitted, even when zero. For example: 64496:4294967295:2 or 64496:0:0 or (64496, 111, 222).

### **5. Reserved Large BGP Community values**

The following Global Administrator values are reserved: 0 (the first ASN) [[RFC7607](#)], 65535 (UINT\_MAX) and 4294967295 (the last ASN) [[RFC7300](#)]. Operators SHOULD NOT use these Global Administrator values.

Although this document does not define any Special-Use Large BGP Communities, the Global Administrator values specified above could be used if there is a future need for them.

### **6. Error Handling**

The error handling of Large BGP Communities is as follows:

- o A Large BGP Communities attribute with a length of zero MUST be ignored upon receipt and removed when sending.
- o A Large BGP Communities attribute SHALL be considered malformed if its length is not a non-zero multiple of 12.



- o A BGP UPDATE message with a malformed Large BGP Communities attribute SHALL be handled using the approach of "treat-as-withdraw" as described in [section 2 \[RFC7606\]](#).

The Large BGP Communities Global Administrator field may contain any value, and a Large BGP Communities attribute MUST NOT be considered malformed if the Global Administrator field contains an unallocated, unassigned or reserved ASN or is set to one of the reserved Large BGP Community values defined in [Section 5](#).

## **7. Security Considerations**

This extension to BGP has similar security implications as BGP Communities [[RFC1997](#)].

This document does not change any underlying security issues associated with any other BGP Communities mechanism. Specifically, an AS relying on the Large BGP Communities attribute carried in BGP must have trust in every other AS in the path, as any intermediate Autonomous System in the path may have added, deleted or altered the Large BGP Communities attribute. Specifying the mechanism to provide such trust is beyond the scope of this document.

Network administrators should note the recommendations in [Section 11](#) of BGP Operations and Security [[RFC7454](#)].

## **8. Implementation status - RFC EDITOR: REMOVE BEFORE PUBLICATION**

This section records the status of known implementations of the protocol defined by this specification at the time of posting of this Internet-Draft, and is based on a proposal described in [[RFC7942](#)]. The description of implementations in this section is intended to assist the IETF in its decision processes in progressing drafts to RFCs. Please note that the listing of any individual implementation here does not imply endorsement by the IETF. Furthermore, no effort has been spent to verify the information presented here that was supplied by IETF contributors. This is not intended as, and must not be construed to be, a catalog of available implementations or their features. Readers are advised to note that other implementations may exist.

As of today these vendors have produced an implementation of Large BGP Communities:

- o Cisco IOS XR
- o ExaBGP





- o GoBGP
- o BIRD
- o OpenBGPD
- o pmacct

The latest implementation news is tracked at <http://largebgpcommunities.net/> [1].

## **9. IANA Considerations**

IANA has made an Early Allocation of the value 30 (LARGE\_COMMUNITY) in the "BGP Path Attributes" registry under the "Border Gateway Protocol (BGP) Parameters" group and is now asked to make that Permanent.

## **10. Acknowledgments**

The authors would like to thank Ruediger Volk, Russ White, Acee Lindem, Shyam Sethuram, Jared Mauch, Joel M. Halpern, Jeffrey Haas, John Heasley, Gunter van de Velde, Marco Marzetti, Eduardo Ascenco Reis, Mark Schouten, Paul Hoogsteder, Martijn Schmidt, Greg Hankins, Bertrand Duvivier, Barry O'Donovan, Grzegorz Janoszka, Linda Dunbar, Marco Davids, Gaurab Raj Upadhaya, Jeff Tantsura, Teun Vink, Adam Davenport, Theodore Baschak, Pier Carlo Chiodi, Nabeel Cocker, Ian Dickinson, Jan Baggen, Duncan Lockwood, David Farmer, Randy Bush, Wim Henderickx, Stefan Plug, Kay Rechthien, Rob Shakir, Warren Kumari, Gert Doering, Thomas King, Mikael Abrahamsson, Wesley Steehouwer, Sander Steffann, Brad Dreisbach, Martin Millnert, Christopher Morrow, Jay Borkenhagen, Arnold Nipper, Joe Provo, Niels Bakker, Bill Fenner, Tom Daly, Ben Maddison, Alexander Azimov, Brian Dickson, Peter van Dijk, Julian Seifert, Tom Petch, Tom Scholl, Arjen Zonneveld, Remco van Mook, Adam Chappell, Jussi Peltola, Kristian Larsson, and Markus Hauschild for their support, insightful review and comments.

## **11. References**

### **11.1. Normative References**

- [RFC1997] Chandra, R., Traina, P., and T. Li, "BGP Communities Attribute", [RFC 1997](#), DOI 10.17487/RFC1997, August 1996, <<http://www.rfc-editor.org/info/rfc1997>>.



- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<http://www.rfc-editor.org/info/rfc2119>>.
- [RFC6793] Vohra, Q. and E. Chen, "BGP Support for Four-Octet Autonomous System (AS) Number Space", [RFC 6793](#), DOI 10.17487/RFC6793, December 2012, <<http://www.rfc-editor.org/info/rfc6793>>.
- [RFC7606] Chen, E., Ed., Scudder, J., Ed., Mohapatra, P., and K. Patel, "Revised Error Handling for BGP UPDATE Messages", [RFC 7606](#), DOI 10.17487/RFC7606, August 2015, <<http://www.rfc-editor.org/info/rfc7606>>.

### **11.2. Informative References**

- [RFC4360] Sangli, S., Tappan, D., and Y. Rekhter, "BGP Extended Communities Attribute", [RFC 4360](#), DOI 10.17487/RFC4360, February 2006, <<http://www.rfc-editor.org/info/rfc4360>>.
- [RFC7300] Haas, J. and J. Mitchell, "Reservation of Last Autonomous System (AS) Numbers", [BCP 6](#), [RFC 7300](#), DOI 10.17487/RFC7300, July 2014, <<http://www.rfc-editor.org/info/rfc7300>>.
- [RFC7454] Durand, J., Pepelnjak, I., and G. Doering, "BGP Operations and Security", [BCP 194](#), [RFC 7454](#), DOI 10.17487/RFC7454, February 2015, <<http://www.rfc-editor.org/info/rfc7454>>.
- [RFC7607] Kumari, W., Bush, R., Schiller, H., and K. Patel, "Codification of AS 0 Processing", [RFC 7607](#), DOI 10.17487/RFC7607, August 2015, <<http://www.rfc-editor.org/info/rfc7607>>.
- [RFC7942] Sheffer, Y. and A. Farrel, "Improving Awareness of Running Code: The Implementation Status Section", [BCP 205](#), [RFC 7942](#), DOI 10.17487/RFC7942, July 2016, <<http://www.rfc-editor.org/info/rfc7942>>.

### **11.3. URIs**

- [1] <http://largebgpcommunities.net>



Authors' Addresses

Jakob Heitz (editor)  
Cisco  
170 West Tasman Drive  
San Jose, CA 95054  
USA

Email: [jheitz@cisco.com](mailto:jheitz@cisco.com)

Job Snijders (editor)  
NTT Communications  
Theodorus Majofskistraat 100  
Amsterdam 1065 SZ  
The Netherlands

Email: [job@ntt.net](mailto:job@ntt.net)

Keyur Patel  
Arrcus, Inc

Email: [keyur@arrcus.com](mailto:keyur@arrcus.com)

Ignas Bagdonas  
Equinix  
London  
UK

Email: [ibagdona.ietf@gmail.com](mailto:ibagdona.ietf@gmail.com)

Adam Simpson  
Nokia  
600 March Road  
Ottawa Ontario K2K 2E6  
Canada

Email: [adam.1.simpson@nokia.com](mailto:adam.1.simpson@nokia.com)



Nick Hilliard  
INEX  
4027 Kingswood Road  
Dublin 24  
IE

Email: [nick@inex.ie](mailto:nick@inex.ie)