

Network Working Group
Internet Draft
Expiration Date: September 2006
Obsoletes [RFC2858](#)

Tony Bates (Cisco Systems)
Ravi Chandra (Sonos Systems)
Dave Katz (Juniper Networks)
Yakov Rekhter (Juniper Networks)

Multiprotocol Extensions for BGP-4

[draft-ietf-idr-rfc2858bis-10.txt](#)

Status of this Memo

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress".

The list of current Internet-Drafts can be accessed at
<http://www.ietf.org/ietf/1id-abstracts.txt>

The list of Internet-Draft Shadow Directories can be accessed at
<http://www.ietf.org/shadow.html>.

IPR Disclosure Acknowledgement

By submitting this Internet-Draft, each author represents that any applicable patent or other IPR claims of which he or she is aware have been or will be disclosed, and any of which he or she becomes aware will be disclosed, in accordance with [Section 6 of BCP 79](#).

Abstract

Currently BGP-4 is capable of carrying routing information only for IPv4. This document defines extensions to BGP-4 to enable it to carry routing information for multiple Network Layer protocols (e.g., IPv6, IPX, etc...). The extensions are backward compatible - a router that supports the extensions can interoperate with a router that doesn't support the extensions.

1. Specification of Requirements

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)].

2. Overview

The only three pieces of information carried by BGP-4 [[BGP-4](#)] that are IPv4 specific are (a) the NEXT_HOP attribute (expressed as an IPv4 address), (b) AGGREGATOR (contains an IPv4 address), and (c) NLRI (expressed as IPv4 address prefixes). This document assumes that any BGP speaker (including the one that supports multiprotocol capabilities defined in this document) has to have an IPv4 address (which will be used, among other things, in the AGGREGATOR attribute). Therefore, to enable BGP-4 to support routing for multiple Network Layer protocols the only two things that have to be added to BGP-4 are (a) the ability to associate a particular Network Layer protocol with the next hop information, and (b) the ability to associate a particular Network Layer protocol with NLRI. To identify individual Network Layer protocols associated with the next hop information and semantics of NLRI this document uses a combination of Address Family, as defined in [[RFC1700](#)], and Subsequent Address Family (as described in this document).

One could further observe that the next hop information (the information provided by the NEXT_HOP attribute) is meaningful (and necessary) only in conjunction with the advertisements of reachable destinations - in conjunction with the advertisements of unreachable destinations (withdrawing routes from service) the next hop information is meaningless. This suggests that the advertisement of reachable destinations should be grouped with the advertisement of the next hop to be used for these destinations, and that the advertisement of reachable destinations should be segregated from the advertisement of unreachable destinations.

To provide backward compatibility, as well as to simplify introduction of the multiprotocol capabilities into BGP-4 this document uses two new attributes, Multiprotocol Reachable NLRI (MP_REACH_NLRI), and Multiprotocol Unreachable NLRI (MP_UNREACH_NLRI). The first one (MP_REACH_NLRI) is used to carry the set of reachable destinations together with the next hop information to be used for forwarding to these destinations. The second one (MP_UNREACH_NLRI) is used to carry the set of unreachable destinations. Both of these attributes are optional and non-

transitive. This way a BGP speaker that doesn't support the multiprotocol capabilities will just ignore the information carried in these attributes, and will not pass it to other BGP speakers.

3. Multiprotocol Reachable NLRI - MP_REACH_NLRI (Type Code 14):

This is an optional non-transitive attribute that can be used for the following purposes:

- (a) to advertise a feasible route to a peer
- (b) to permit a router to advertise the Network Layer address of the router that should be used as the next hop to the destinations listed in the Network Layer Reachability Information field of the MP_NLRI attribute.

The attribute is encoded as shown below:

```
+-----+
| Address Family Identifier (2 octets)      |
+-----+
| Subsequent Address Family Identifier (1 octet) |
+-----+
| Length of Next Hop Network Address (1 octet) |
+-----+
| Network Address of Next Hop (variable)      |
+-----+
| Reserved (1 octet)                          |
+-----+
| Network Layer Reachability Information (variable) |
+-----+
```

The use and meaning of these fields are as follows:

Address Family Identifier (AFI):

This field in combination with the Subsequent Address Family Identifier field identifies the Network Layer protocol associated with the Network Address of Next Hop and the semantics of the Network Layer Reachability Information that

follows.

Presently defined values for the Address Family Identifier field are specified in [RFC1700](#) (see the Address Family Numbers section).

Subsequent Address Family Identifier (SAFI):

This field in combination with the Address Family Identifier field identifies the Network Layer protocol associated with the Network Address of the Next Hop and the semantics of the Network Layer Reachability Information that follows.

Length of Next Hop Network Address:

A 1 octet field whose value expresses the length of the "Network Address of Next Hop" field as measured in octets.

Network Address of Next Hop:

A variable length field that contains the Network Address of the next router on the path to the destination system. The Network Layer protocol associated with the Network Address of the Next Hop is identified by a combination of <AFI, SAFI> carried in the attribute.

Reserved:

A 1 octet field that MUST be set to 0, and SHOULD be ignored upon receipt.

Network Layer Reachability Information (NLRI):

A variable length field that lists NLRI for the feasible routes that are being advertised in this attribute. The semantics of NLRI is identified by a combination of <AFI, SAFI> carried in the attribute.

When the Subsequent Address Family Identifier field is set to one of the values defined in this document, each NLRI is encoded as specified in the "NLRI encoding" section of this document.

The next hop information carried in the MP_REACH_NLRI path attribute defines the Network Layer address of the router that SHOULD be used as the next hop to the destinations listed in the MP_NLRI attribute in the UPDATE message.

The rules for the next hop information are the same as the rules for the information carried in the NEXT_HOP BGP attribute (see [Section 5.1.3](#) of [\[BGP-4\]](#)).

An UPDATE message that carries the MP_REACH_NLRI MUST also carry the ORIGIN and the AS_PATH attributes (both in EBGp and in IBGP exchanges). Moreover, in IBGP exchanges such a message MUST also carry the LOCAL_PREF attribute.

An UPDATE message that carries no NLRI, other than the one encoded in the MP_REACH_NLRI attribute, SHOULD NOT carry the NEXT_HOP attribute. If such a message contains the NEXT_HOP attribute, the BGP speaker that receives the message SHOULD ignore this attribute.

An UPDATE message SHOULD NOT include the same address prefix (of the same <AFI, SAFI>) in more than one of the following fields: WITHDRAWN ROUTES field, Network Reachability Information fields, MP_REACH_NLRI field, and MP_UNREACH_NLRI field. The processing of an UPDATE message in this form is un-defined.

4. Multiprotocol Unreachable NLRI - MP_UNREACH_NLRI (Type Code 15):

This is an optional non-transitive attribute that can be used for the purpose of withdrawing multiple unfeasible routes from service.

The attribute is encoded as shown below:

```
+-----+
| Address Family Identifier (2 octets)          |
+-----+
| Subsequent Address Family Identifier (1 octet) |
+-----+
| Withdrawn Routes (variable)                  |
+-----+
```

The use and the meaning of these fields are as follows:

Address Family Identifier (AFI):

This field in combination with the Subsequent Address Family Identifier field identifies the semantics associated with the Network Layer Reachability Information (NLRI) that follows.

Presently defined values for the Address Family Identifier field are specified in [RFC1700](#) (see the Address Family Numbers section).

Subsequent Address Family Identifier (SAFI):

This field in combination with the Address Family Identifier field identifies the semantics associated with the Network Layer Reachability Information (NLRI) that follows.

Withdrawn Routes Network Layer Reachability Information:

A variable length field that lists NLRI for the routes that are being withdrawn from service. The semantics of NLRI is identified by a combination of <AFI, SAFI> carried in the attribute.

When the Subsequent Address Family Identifier field is set to one of the values defined in this document, each NLRI is encoded as specified in the "NLRI encoding" section of this document.

An UPDATE message that contains the MP_UNREACH_NLRI is not required to carry any other path attributes.

5. NLRI encoding

The Network Layer Reachability information is encoded as one or more 2-tuples of the form <length, prefix>, whose fields are described below:

```
+-----+
| Length (1 octet) |
+-----+
| Prefix (variable) |
+-----+
```

The use and the meaning of these fields are as follows:

a) Length:

The Length field indicates the length in bits of the address prefix. A length of zero indicates a prefix that matches all (as specified by the address family) addresses (with prefix, itself, of zero octets).

b) Prefix:

The Prefix field contains an address prefix followed by enough trailing bits to make the end of the field fall on an octet boundary. Note that the value of trailing bits is irrelevant.

6. Subsequent Address Family Identifier

This document defines the following values for the Subsequent Address Family Identifier field carried in the MP_REACH_NLRI and

MP_UNREACH_NLRI attributes:

1 - Network Layer Reachability Information used for unicast forwarding

2 - Network Layer Reachability Information used for multicast forwarding

An implementation MAY support all, some, or none of the Subsequent Address Family Identifier values defined in this document.

7. Error Handling

If a BGP speaker receives from a neighbor an Update message that contains the MP_REACH_NLRI or MP_UNREACH_NLRI attribute, and the speaker determines that the attribute is incorrect, the speaker MUST delete all the BGP routes received from that neighbor whose AFI/SAFI is the same as the one carried in the incorrect MP_REACH_NLRI or MP_UNREACH_NLRI attribute. For the duration of the BGP session over which the Update message was received, the speaker then SHOULD ignore all the subsequent routes with that AFI/SAFI received over that session.

In addition, the speaker MAY terminate the BGP session over which the Update message was received. The session SHOULD be terminated with the Notification message code/subcode indicating "Update Message Error"/"Optional Attribute Error".

8. Use of BGP Capability Advertisement

A BGP speaker that uses Multiprotocol Extensions SHOULD use the Capability Advertisement procedures [BGP-CAP] to determine whether the speaker could use Multiprotocol Extensions with a particular peer.

The fields in the Capabilities Optional Parameter are set as follows. The Capability Code field is set to 1 (which indicates Multiprotocol Extensions capabilities). The Capability Length field is set to 4. The Capability Value field is defined as:

0	7	15	23	31
+-----+-----+-----+-----+				
AFI		Res.		SAFI
+-----+-----+-----+-----+				

The use and meaning of this field is as follow:

AFI - Address Family Identifier (16 bit), encoded the same way as in the Multiprotocol Extensions

Res. - Reserved (8 bit) field. SHOULD be set to 0 by the sender and ignored by the receiver.

SAFI - Subsequent Address Family Identifier (8 bit), encoded the same way as in the Multiprotocol Extensions.

A speaker that supports multiple <AFI, SAFI> tuples includes them as multiple Capabilities in the Capabilities Optional Parameter.

To have a bi-directional exchange of routing information for a particular <AFI, SAFI> between a pair of BGP speakers, each such speaker MUST advertise to the other (via the Capability Advertisement mechanism) the capability to support that particular <AFI, SAFI> routes.

9. IANA Considerations

As specified in this document, the MP_REACH_NLRI and MP_UNREACH_NLRI attributes contain the Subsequence Address Family Identifier (SAFI) field. The SAFI name space is defined in this document. The IANA will maintain and register values for the SAFI namespace as follows:

- SAFI values 1 and 2 are assigned in this document.
- SAFI value 3 is reserved. It was assigned by [RFC 2858](#) for a use that was never fully implemented, so is deprecated by this document.
- SAFI values 5 through 63 are to be assigned by IANA using either the Standards Action process defined in [[RFC2434](#)], or the Early IANA Allocation process defined in [[RFC4020](#)].
- SAFI values 67 through 127 are to be assigned by IANA, using the "First Come First Served" policy defined in [RFC2434](#).
- SAFI values 0 and 255 are reserved.
- SAFI values 128 through 240 are part of the previous "private use" range. Of this space, allocations which are currently in use are to be recognized by IANA. Unused values, namely 130, 131, 135 through 139, and 141 through 240 should be considered reserved, in order to avoid conflicts.
- SAFI values 241 through 254 are for "private use", and values in this range are not to be assigned by IANA.

10. Comparison with [RFC2858](#)

This document makes the use of the next hop information consistent with the information carried in the NEXT_HOP BGP path attribute.

This document removes the definition of SAFI 3, and deprecates SAFI 3.

This document changes partitioning of the SAFI space. Specifically, in [RFC2858](#) SAFI values 128 through 240 were part of the "private use" range. This document specifies that of this range, allocations which are currently in use are to be recognized by IANA, and that unused values, namely 130, 131, 135 through 139, and 141 through 240 should be considered reserved.

This document renames the Number of SNPA's field to Reserved, and removes the rest of the SNPA-related information from the MP_REACH_NLRI attribute.

11. Comparison with [RFC2283](#)

This document restricts the MP_REACH_NLRI attribute to carry only a single instance of <AFI, SAFI, Next Hop Information, ...>.

This document restricts the MP_UNREACH_NLRI attribute to carry only a single instance of <AFI, SAFI, ...>.

This document clarifies handling of an UPDATE message that carries no NLRI, other than the one encoded in the MP_REACH_NLRI attribute.

This document clarifies error handling in the presence of MP_REACH_NLRI or MP_UNREACH_NLRI attributes.

This document specifies the use of BGP Capabilities Advertisements in conjunction with Multi-protocol extensions.

Finally, this document includes the "IANA Consideration" Section.

12. Security Considerations

This extension to BGP does not change the underlying security issues inherent in the existing BGP.

13. Intellectual Property Considerations

This section is taken from [Section 5 of RFC 3668](#).

The IETF takes no position regarding the validity or scope of any

Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; nor does it represent that it has made any independent effort to identify any such rights. Information on the procedures with respect to rights in RFC documents can be found in [BCP 78](#) and [BCP 79](#).

Copies of IPR disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF on-line IPR repository at <http://www.ietf.org/ipr>.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement this standard. Please address the information to the IETF at ietf-ipr@ietf.org.

14. Copyright Notice

Copyright (C) The Internet Society (2006).

This document is subject to the rights, licenses and restrictions contained in [BCP 78](#), and except as set forth therein, the authors retain all their rights.

This document and the information contained herein are provided on an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

15. Acknowledgements

The authors would like to thank members of the IDR Working Group for their review and comments.

16. Normative References

[BGP-CAP] "Capabilities Advertisement with BGP-4", R. Chandra, J. Scudder, [RFC2842](#), May 2000

[BGP-4] Rekhter, Y., and T. Li, "A Border Gateway Protocol 4 (BGP-4)", [RFC 1771](#), March 1995.

[RFC1700] "Assigned Numbers", J. Reynolds, J. Postel, [RFC1700](#), October 1994 (see also <http://www.iana.org/iana/assignments.html>)

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.

[RFC2434] Narten, T., Alvestrand, H., "Guidelines for Writing an IANA Considerations Section in RFCs", [RFC2434](#), October 1998

[RFC4020] "Early IANA Allocation of Standards Track Code Points", K. Kompella, A. Zinin, [BCP0100](#), [RFC 4020](#), February 2005.

[17. Author Information](#)

Tony Bates
Cisco Systems, Inc.
email: tbates@cisco.com

Ravi Chandra
Sonoa Systems
e-mail: rchandra@sonoasystems.com

Dave Katz
Juniper Networks, Inc.
email: dkatz@juniper.com

Yakov Rekhter
Juniper Networks, Inc.
email: yakov@juniper.com