

INTERNET-DRAFT

Paul Traina

Danny McPherson  
Arbor Networks, Inc.  
John Scudder  
Cisco Systems, Inc.  
October 2005

Expires: April 2006

Autonomous System Confederations for BGP  
<[draft-ietf-idr-rfc3065bis-05.txt](#)>

## Status of this Memo

By submitting this Internet-Draft, each author represents that any applicable patent or other IPR claims of which he or she is aware have been or will be disclosed, and any of which he or she becomes aware will be disclosed, in accordance with [Section 6 of BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress".

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/lid-abstracts.html>

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

## Copyright Notice

Copyright (C) The Internet Society (2005). All Rights Reserved.

## Abstract

The Border Gateway Protocol (BGP) is an inter-autonomous system routing protocol designed for Transmission Control Protocol/Internet Protocol (TCP/IP) networks. BGP requires that all BGP speakers within a single autonomous system (AS) must be fully meshed. This represents a serious scaling problem that has been well documented in a number of proposals.

This document describes an extension to BGP which may be used to create a confederation of autonomous systems that is represented as a single autonomous system to BGP peers external to the confederation, thereby removing the "full mesh" requirement. The intention of this extension is to aid in policy administration and reduce the management complexity of maintaining a large autonomous system.

INTERNET-DRAFT

Expires: April 2006

October 2005

Table of Contents

- [1. Introduction . . . . .](#) [4](#)
- [1.1. Terminology . . . . .](#) [4](#)
- [2. Discussion . . . . .](#) [5](#)
- [3. AS\\_CONFED Segment Type Extension . . . . .](#) [6](#)
- [4. Operation. . . . .](#) [6](#)
- [4.1. AS\\_PATH Modification Rules. . . . .](#) [7](#)
- [5. Error Handling . . . . .](#) [8](#)
- [5.1. Common Administrative Issues. . . . .](#) [9](#)
- [5.2. MED and LOCAL\\_PREF Handling . . . . .](#) [9](#)
- [5.3. AS\\_PATH and Path Selection. . . . .](#) [10](#)
- [6. Compatability Considerations . . . . .](#) [10](#)
- [7. Deployment Considerations. . . . .](#) [11](#)
- [8. Security Considerations. . . . .](#) [11](#)
- [9. Acknowledgments. . . . .](#) [11](#)
- [10. References. . . . .](#) [13](#)
- [10.1. Normative References . . . . .](#) [13](#)
- [10.2. Informative References . . . . .](#) [13](#)
- [11. Authors' Addresses. . . . .](#) [14](#)

INTERNET-DRAFT

Expires: April 2006

October 2005

## 1. Introduction

As currently defined, BGP requires that all BGP speakers within a single AS must be fully meshed. The result is that for  $n$  BGP speakers within an AS  $n*(n-1)/2$  unique IBGP sessions are required. This "full mesh" requirement clearly does not scale when there are a large number of IBGP speakers within the autonomous system, as is common in many networks today.

This scaling problem has been well documented and a number of proposals have been made to alleviate this [RFC 1863, [RFC 2796](#)]. This document presents another alternative alleviating the need for a "full mesh" and is known as "Autonomous System Confederations for BGP", or simply, "BGP Confederations". It has also been observed that BGP Confederations may provide improvements in routing policy control.

This document is a revision of [[RFC 3065](#)], which is itself a revision to [[RFC 1965](#)]. It includes editorial changes, terminology clarifications and more explicit protocol specifications based on extensive implementation and deployment experience with BGP Confederations.

### 1.1. Terminology

#### AS Confederation

A collection of autonomous systems represented and advertised as a single AS number to BGP speakers that are not members of

the local BGP confederation.

#### AS Confederation Identifier

An externally visible autonomous system number that identifies a BGP confederation as a whole.

#### Member Autonomous System (Member-AS)

An autonomous system that is contained in a given AS confederation. Note that "Member Autonomous System" and "Member-AS" are used entirely interchangeably throughout this document.

#### Member-AS Number

An autonomous system number identifier visible only within a BGP confederation, and used to represent a Member-AS within that confederation.

## [2.](#) Discussion

It may be useful to subdivide autonomous systems with a very large number of BGP speakers into smaller domains for purposes of controlling routing policy via information contained in the BGP AS\_PATH attribute. For example, one may choose to consider all BGP speakers in a geographic region as a single entity.

In addition to potential improvements in routing policy control, if techniques such as those presented here or in [[RFC 2796](#)] are not employed, [[BGP-4](#)] requires BGP speakers in the same autonomous system to establish a full mesh of TCP connections among all speakers for the purpose of exchanging exterior routing information. In autonomous systems the number of intra-domain connections that need to be maintained by each border router can become significant.

Subdividing a large autonomous system allows a significant reduction in the total number of intra-domain BGP connections, as the connectivity requirements simplify to the model used for inter-domain

connections.

Unfortunately, subdividing an autonomous system may increase the complexity of routing policy based on AS\_PATH information for all members of the Internet. Additionally, this division increases the maintenance overhead of coordinating external peering when the internal topology of this collection of autonomous systems is modified.

Therefore, division of an autonomous system into separate systems may adversely affect optimal routing of packets through the Internet.

However, there is usually no need to expose the internal topology of this divided autonomous system, which means it is possible to regard a collection of autonomous systems under a common administration as a single entity or autonomous system, when viewed from outside the confines of the confederation of autonomous systems itself.

### [3](#). AS\_CONFED Segment Type Extension

Currently, BGP specifies that the AS\_PATH attribute is a well-known mandatory attribute that is composed of a sequence of AS path segments. Each AS path segment is represented by a triple <path segment type, path segment length, path segment value>.

In [[BGP-4](#)], the path segment type is a 1-octet long field with the two following values defined:

Value	Segment Type
1	AS_SET: unordered set of autonomous systems a route in the UPDATE message has traversed
2	AS_SEQUENCE: ordered set of autonomous systems a route in the UPDATE message has traversed

This document specifies two additional segment types:

- 3 AS\_CONFED\_SEQUENCE: ordered set of Member Autonomous Systems in the local confederation that the UPDATE message has traversed
- 4 AS\_CONFED\_SET: unordered set of Member Autonomous Systems in the local confederation that the UPDATE message has traversed

#### [4.](#) Operation

A member of a BGP confederation MUST use its AS Confederation Identifier in all transactions with peers that are not members of its confederation. This AS confederation identifier is the "externally visible" AS number and this number is used in OPEN messages and advertised in the AS\_PATH attribute.

A member of a BGP confederation MUST use its Member-AS Number in all transactions with peers that are members of the same confederation as the local BGP speaker.

A BGP speaker receiving an AS\_PATH attribute containing an autonomous system matching its own AS Confederation Identifier SHALL treat the path in the same fashion as if it had received a path containing its own AS number.

A BGP speaker receiving an AS\_PATH attribute containing an AS\_CONFED\_SEQUENCE or AS\_CONFED\_SET which contains its own Member-AS Number SHALL treat the path in the same fashion as if it had received a path containing its own AS number.

##### [4.1.](#) AS\_PATH Modification Rules

When implementing BGP Confederations Section 5.1.2 of [[BGP-4](#)] is replaced with the following text:

When a BGP speaker propagates a route which it has learned from another BGP speaker's UPDATE message, it SHALL modify the route's AS\_PATH attribute based on the location of the BGP speaker to which the route will be sent:

- a) When a given BGP speaker advertises the route to another BGP speaker located in its own Member-AS, the advertising speaker SHALL NOT modify the AS\_PATH attribute associated with the route.
- b) When a given BGP speaker advertises the route to a BGP speaker located in a neighboring autonomous system that is a member of the local confederation, the advertising speaker SHALL update the AS\_PATH attribute as follows:
  - 1) if the first path segment of the AS\_PATH is of type AS\_CONFED\_SEQUENCE, the local system SHALL prepend its own Member-AS Number as the last element of the sequence (put it in the leftmost position).
  - 2) if the first path segment of the AS\_PATH is not of type AS\_CONFED\_SEQUENCE the local system SHALL prepend a new path segment of type AS\_CONFED\_SEQUENCE to the AS\_PATH, including its own Member-AS Number in that segment.
- c) When a given BGP speaker advertises the route to a BGP speaker located in a neighboring autonomous system that is not a member of the local confederation, the advertising speaker SHALL update the AS\_PATH attribute as follows:
  - 1) if any path segments of the AS\_PATH are of the type AS\_CONFED\_SEQUENCE or AS\_CONFED\_SET, those segments MUST be removed from the AS\_PATH attribute, leaving the sanitized AS\_PATH attribute to be operated on by steps 2 or 3.

- 2) if the first path segment of the remaining AS\_PATH is of type AS\_SEQUENCE, the local system SHALL prepend its own AS Confederation Identifier as the last element of the sequence (put it in the leftmost position).

- 3) if there are no path segments following the removal of the first AS\_CONFED\_SET/AS\_CONFED\_SEQUENCE segments, or if the first path segment of the remaining AS\_PATH is not of type AS\_SEQUENCE the local system SHALL prepend a new path segment of type AS\_SEQUENCE to the AS\_PATH, including its own AS Confederation Identifier in that segment.

When a BGP speaker originates a route:

- a) the originating speaker SHALL include an empty AS\_PATH attribute in all UPDATE messages sent to BGP speakers residing within the same Member-AS. (An empty AS\_PATH attribute is one whose length field contains the value zero).
- b) the originating speaker SHALL include its own Member-AS Number in an AS\_CONFED\_SEQUENCE segment of the AS\_PATH attribute of all UPDATE messages sent to BGP speakers located in neighboring Member Autonomous Systems that are members of the local confederation (i.e., the originating speaker's Member-AS Number will be the only entry in the AS\_PATH attribute).
- c) the originating speaker SHALL include its own AS Confederation Identifier in an AS\_SEQUENCE segment of the AS\_PATH attribute of all UPDATE messages sent to BGP speakers located in neighboring autonomous systems that are not members of the local confederation. (In this case, the originating speaker's AS Confederation Identifier will be the only entry in the AS\_PATH attribute).

## 5. Error Handling

A BGP speaker MUST NOT transmit updates containing AS\_CONFED\_SET or AS\_CONFED\_SEQUENCE attributes to peers that are not members of the local confederation.

It is an error for a BGP speaker to receive an update message with an AS\_PATH attribute which contains AS\_CONFED\_SEQUENCE or AS\_CONFED\_SET segments from a neighbor which is not located in the same confederation. If a BGP speaker receives such an update message, it

SHALL treat the message as having a malformed AS\_PATH according to the procedures of [[BGP-4](#)] [Section 6.3](#) ("UPDATE message error handling").

It is a error for a BGP speaker to receive an update message from a confederation peer which is not in the same Member-AS that does not have AS\_CONFED\_SEQUENCE as the first segment. If a BGP speaker receives such an update message, it SHALL treat the message as having a malformed AS\_PATH according to the procedures of [[BGP-4](#)] [Section 6.3](#) ("Update message error handling").

### [5.1.](#) Common Administrative Issues

It is reasonable for Member Autonomous Systems of a confederation to share a common administration and IGP information for the entire confederation. It is also reasonable for each Member-AS to run an independent IGP. In the latter case, the NEXT\_HOP may need to be set using policy (i.e., by default it is unchanged).

### [5.2.](#) MED and LOCAL\_PREF Handling

It SHALL be legal for a BGP speaker to advertise an unchanged NEXT\_HOP and MULTI\_EXIT\_DISC (MED) attribute to peers in a neighboring Member-AS of the local confederation.

MEDs of two routes SHOULD only be compared if the first autonomous systems in the first AS\_SEQUENCE in both routes are the same - i.e., skip all the autonomous systems in the AS\_CONFED\_SET and AS\_CONFED\_SEQUENCE. An implementation MAY provide the ability to configure path selection such that MEDs of two routes are comparable if the first autonomous systems in the AS\_PATHs are the same, regardless of AS\_SEQUENCE or AS\_CONFED\_SEQUENCE in the AS\_PATH.

An implementation MAY compare MEDs received from a Member-AS via multiple paths. An implementation MAY compare MEDs from different Member Autonomous Systems of the same confederation.

In addition, the restriction against sending the LOCAL\_PREF attribute to peers in a neighboring autonomous system within the same confederation is removed.

INTERNET-DRAFT

Expires: April 2006

October 2005

### [5.3.](#) AS\_PATH and Path Selection

Path selection criteria for information received from members inside a confederation MUST follow the same rules used for information received from members inside the same autonomous system, as specified in [[BGP-4](#)].

In addition, the following rules SHALL be applied:

- 1) If the AS\_PATH is internal to the local confederation (i.e., there are only AS\_CONFED\_\* segments) consider the neighbor AS to be the local AS.
- 2) Otherwise, if the first segment in the path which is not an AS\_CONFED\_SEQUENCE or AS\_CONFED\_SET is an AS\_SEQUENCE, consider the neighbor AS to be the leftmost AS\_SEQUENCE AS.
- 3) When comparing routes using AS\_PATH length, CONFED\_SEQUENCE and CONFED\_SETs SHOULD NOT be counted.
- 4) When comparing routes using the internal (iBGP learned) versus external (eBGP learned) rules, treat a route that is learned from a peer which is in the same confederation (not necessarily the same Member-AS) as "internal".

## [6.](#) Compatibility Considerations

All BGP speakers participating as member of a confederation MUST recognize the AS\_CONFED\_SET and AS\_CONFED\_SEQUENCE segment type extensions to the AS\_PATH attribute.

Any BGP speaker not supporting these extensions will generate a NOTIFICATION message specifying an "UPDATE Message Error" and a sub-code of "Malformed AS\_PATH".

This compatibility issue implies that all BGP speakers participating in a confederation MUST support BGP confederations. However, BGP speakers outside the confederation need not support these extensions.

INTERNET-DRAFT

Expires: April 2006

October 2005

## [7](#). Deployment Considerations

BGP confederations have been widely deployed throughout the Internet for a number of years and are supported by multiple vendors.

Improper configuration of BGP confederations can cause routing information within an AS to be duplicated unnecessarily. This duplication of information will waste system resources, cause unnecessary route flaps, and delay convergence.

Care should be taken to manually filter duplicate advertisements caused by reachability information being relayed through multiple Member Autonomous Systems based upon the topology and redundancy requirements of the confederation.

Additionally, confederations (as well as route reflectors), by excluding different reachability information from consideration at different locations in a confederation, have been shown [[RFC 3365](#)] cause permanent oscillation between candidate routes when using the tie breaking rules required by BGP [[BGP-4](#)]. Care must be taken when selecting MED values and tie breaking policy to avoid these situations.

One potential way to avoid this is by configuring inter-Member-AS IGP metrics higher than intra-Member-AS IGP metrics and/or using other tie breaking policies to avoid BGP route selection based on incomparable MEDs.

## [8](#). Security Considerations

This extension to BGP does not change the underlying security issues

inherent in the existing BGP protocol, such as those described in [[RFC 2385](#)] and [[BGP-VULN](#)].

## 9. Acknowledgments

The general concept of BGP confederations was taken from IDRPs Routing Domain Confederations [ISO 10747]. Some of the introductory text in this document was taken from [[RFC 2796](#)].

The authors would like to acknowledge Bruce Cole for his

implementation feedback and extensive analysis of the limitations of the protocol extensions described in this document and [[RFC 3065](#)]. We would also like to acknowledge Srihari Ramachandra, Alex Zinin, Naresh Kumar Paliwal, Jeffrey Haas, Cengiz Alaettinoglu and Bruno Rijsman for their feedback and suggestions.

Finally, we'd like to acknowledge Ravi Chandra and Yakov Rekhter for providing constructive and valuable feedback on earlier versions of this specification.

## [10](#). References

### [10.1](#). Normative References

[BGP-4] Rekhter, Y., Li, T., and Hares, S., "A Border Gateway Protocol 4", Internet-Draft, "Work in Progress".

[RFC 1965] Traina, P. "Autonomous System Confederations for BGP", [RFC 1965](#), June 1996.

[RFC 3065] Traina, P., McPherson, D. and Scudder, J., "Autonomous System Confederations for BGP", [RFC 3065](#), February 2001.

### [10.2](#). Informative References

- [ISO 10747] Kunzinger, C., Editor, "Inter-Domain Routing Protocol", ISO/IEC 10747, October 1993.
- [RFC 1771] Rekhter, Y. and T. Li, "A Border Gateway Protocol 4 (BGP-4)", [RFC 1771](#), March 1995.
- [RFC 1863] Haskin, D., "A BGP/IDRP Route Server alternative to a full mesh routing", [RFC 1863](#), October 1995.
- [RFC 2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [RFC 2119](#), March 1997.
- [RFC 2385] Heffernan, A., "Protection of BGP Sessions via the TCP MD5 Signature Option", [RFC 2385](#), August 1998.
- [RFC 2796] Bates, T., Chandra, R. and E. Chen, "BGP Route Reflection An Alternative to Full Mesh IBGP", [RFC 2796](#), April 2000.
- [RFC 3365] McPherson, D., Gill, V., Walton, D., Retana, A., "Border Gateway Protocol (BGP) Persistent Route Oscillation Condition", [RFC 3345](#), August 2002.
- [BGP-VULN] Murphy, S., "BGP Security Vulnerabilities Analysis", Internet-Draft, "Work in Progress".

Traina, McPherson, Scudder

[Section 10.2](#). [Page 13]

---

INTERNET-DRAFT

Expires: April 2006

October 2005

## 11. Authors' Addresses

Paul Traina  
EMail: pst+confed@spamcatcher.bogus.com

Danny McPherson  
Arbor Networks, Inc.  
Phone: +1 303.470.9257  
EMail: danny@arbor.net

John G. Scudder

Cisco Systems, Inc.  
170 West Tasman Drive  
San Jose, CA 95134  
Phone: +1 734.302.4128  
EMail: jgs@cisco.com

## Intellectual Property Statement

The IETF takes no position regarding the validity or scope of any Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; nor does it represent that it has made any independent effort to identify any such rights. Information on the procedures with respect to rights in RFC documents can be found in [BCP 78](#) and [BCP 79](#).

Copies of IPR disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF on-line IPR repository at <http://www.ietf.org/ipr>.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement this standard. Please address the information to the IETF at [ietf-ipr@ietf.org](mailto:ietf-ipr@ietf.org).

## Disclaimer of Validity

Traina, McPherson, Scudder

[Section 11](#). [Page 14]

---

INTERNET-DRAFT

Expires: April 2006

October 2005

This document and the information contained herein are provided on an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

## Copyright Statement

Copyright (C) The Internet Society (2005). This document is subject to the rights, licenses and restrictions contained in [BCP 78](#), and except as set forth therein, the authors retain all their rights.

## Acknowledgment

Funding for the RFC Editor function is currently provided by the Internet Society.