

IDR
Internet-Draft
Intended status: Standards Track
Expires: June 3, 2017

J. Snijders
NTT
J. Heitz
Cisco
J. Scudder
Juniper
November 30, 2016

**The Shutdown Communication BGP Cease Notification Message subcode
draft-ietf-idr-shutdown-00**

Abstract

This document defines the BGP Cease NOTIFICATION message "Shutdown Communication" subcode for operators to transmit a short freeform message to describe why a BGP session was shutdown.

Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on June 3, 2017.

Copyright Notice

Copyright (c) 2016 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents

(<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	2
2.	Shutdown Communication	2
3.	Operational Considerations	3
4.	Error Handling	3
5.	IANA Considerations	4
6.	Security Considerations	4
7.	Implementation status - RFC EDITOR: REMOVE BEFORE PUBLICATION	4
8.	References	4
8.1.	Normative References	4
8.2.	Informative References	5
Appendix A.	Acknowledgements	5
	Authors' Addresses	5

[1.](#) Introduction

It can be troublesome for an operator to correlate a BGP-4 [[RFC4271](#)] session teardown in the network with a notice that was transmitted via off-line methods such email or telephone calls. This document specifies a mechanism to transmit a short freeform UTF-8 [[RFC3629](#)] message as part of a Cease NOTIFICATION message [[RFC4486](#)] to inform the peer why the BGP session is being shutdown.

[2.](#) Shutdown Communication

If a BGP speaker decides to terminate its session with a BGP neighbor, then the BGP speaker MAY send to the neighbor a NOTIFICATION message with the Error Code "Cease" and the Error Subcode TBD "Shutdown Communication" followed by a freeform UTF-8 encoded string with a REQUIRED maximum length of 128 octets. The contents of the string are at the operator's discretion.

The Shutdown Communication Cease NOTIFICATION message is encoded as following:


```

      0              1              2              3
    0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+
| Error code 6 | subcode TBD | ... |
+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+
| ... Shutdown Communication ... |
+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+
| ... |
+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+

```

To support international characters, the Shutdown Communication field MUST be encoded using UTF-8.

The sending BGP speaker SHOULD avoid octet values below 32 (control characters), however these values are legal. Following UNICODE TR36 [UTR36], Sec 3.1, the sending BGP speaker MUST encode messages in the "shortest form" and MUST NOT interpret messages in the "non shortest form". A receiving BGP speaker MUST NOT interpret invalid UTF-8 sequences.

It is RECOMMENDED that a BGP speaker receiving a Shutdown Communication observe retry behaviour in line with the [RFC4486](#) [RFC4486] behaviour for "Administrative Shutdown" (sec 4.0).

Mechanisms concerning the reporting of information contained in the Shutdown Communication are implementation specific but SHOULD include methods such as SYSLOG [RFC5424].

3. Operational Considerations

Operators are encouraged to use the Shutdown Communication to inform their peers with a reference and reason as to why the BGP session is shut down. An example of a useful Shutdown Communication would be:

```
"[VNOC-1-1438367390] software upgrade, back in 2 hours"
```

"[VNOC-1-1438367390]" is a ticket reference with significance to both the sender and receiver, followed by a brief human readable message regarding the work triggering the BGP session shutdown followed by an indication about the length of the maintenance. The receiver can now use the string 'VNOC-1-1438367390' to search in their email archive to find more details.

4. Error Handling

Any erroneous or malformed Shutdown Communication received SHOULD be logged for the attention of the operator and then MAY be discarded.

5. IANA Considerations

Per this document, IANA is requested to assign a subcode named "Shutdown Communication" in the "Cease NOTIFICATION message subcodes" registry under the "Border Gateway Protocol (BGP) Parameters" group.

6. Security Considerations

This document uses UTF-8 encoding for the Shutdown Communication. There are a number of security issues with UNICODE. Any implementer and operator is advised to review UNICODE TR36 [[UTR36](#)] to learn about these issues. This document guards against the technical issues outlined in UTR36 by REQUIRING "shortest form" encoding. However, the visual spoofing due to character confusion still persists. This document tries to minimize the effects of visual spoofing by allowing UNICODE only where local script is expected and needed, and by limiting the length of the Shutdown Communication.

7. Implementation status - RFC EDITOR: REMOVE BEFORE PUBLICATION

This section records the status of known implementations of the protocol defined by this specification at the time of posting of this Internet-Draft, and is based on a proposal described in [[RFC7942](#)]. The description of implementations in this section is intended to assist the IETF in its decision processes in progressing drafts to RFCs. Please note that the listing of any individual implementation here does not imply endorsement by the IETF. Furthermore, no effort has been spent to verify the information presented here that was supplied by IETF contributors. This is not intended as, and must not be construed to be, a catalog of available implementations or their features. Readers are advised to note that other implementations may exist.

As of today these vendors have produced an implementation of the Shutdown Communication:

- o ExaBGP

8. References

8.1. Normative References

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<http://www.rfc-editor.org/info/rfc2119>>.

- [RFC3629] Yergeau, F., "UTF-8, a transformation format of ISO 10646", STD 63, [RFC 3629](#), DOI 10.17487/RFC3629, November 2003, <<http://www.rfc-editor.org/info/rfc3629>>.
- [RFC4271] Rekhter, Y., Ed., Li, T., Ed., and S. Hares, Ed., "A Border Gateway Protocol 4 (BGP-4)", [RFC 4271](#), DOI 10.17487/RFC4271, January 2006, <<http://www.rfc-editor.org/info/rfc4271>>.
- [RFC4486] Chen, E. and V. Gillet, "Subcodes for BGP Cease Notification Message", [RFC 4486](#), DOI 10.17487/RFC4486, April 2006, <<http://www.rfc-editor.org/info/rfc4486>>.

8.2. Informative References

- [RFC5424] Gerhards, R., "The Syslog Protocol", [RFC 5424](#), DOI 10.17487/RFC5424, March 2009, <<http://www.rfc-editor.org/info/rfc5424>>.
- [RFC7942] Sheffer, Y. and A. Farrel, "Improving Awareness of Running Code: The Implementation Status Section", [BCP 205](#), [RFC 7942](#), DOI 10.17487/RFC7942, July 2016, <<http://www.rfc-editor.org/info/rfc7942>>.
- [UTR36] Davis, M. and M. Suignard, "Unicode Security Considerations", Unicode Technical Report #36, August 2010, <<http://unicode.org/reports/tr36/>>.

Appendix A. Acknowledgements

The author would like to gratefully acknowledge Tom Scholl, David Freedman, and Jared Mauch.

Authors' Addresses

Job Snijders
NTT Communications
Theodorus Majofskistraat 100
Amsterdam 1065 SZ
NL

Email: job@ntt.net

Jakob Heitz
Cisco
170 West Tasman Drive
San Jose, CA 95054
USA

Email: jheitz@cisco.com

John Scudder
Juniper Networks
1194 N. Mathilda Ave
Sunnyvale, CA 94089
USA

Email: jgs@juniper.net

