

Networking Working Group
Internet-Draft
Intended status: Standards Track
Expires: June 16, 2019

L. Ginsberg, Ed.
Cisco Systems, Inc.
S. Previdi
Q. Wu
Huawei
J. Tantsura
Apstra, Inc.
C. Filsfils
Cisco Systems, Inc.
December 13, 2018

**BGP-LS Advertisement of IGP Traffic Engineering Performance Metric
Extensions
draft-ietf-idr-te-pm-bgp-16**

Abstract

This document defines new BGP-LS TLVs in order to carry the IGP Traffic Engineering Extensions defined in the IS-IS and OSPF protocols.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on June 16, 2019.

Copyright Notice

Copyright (c) 2018 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents

carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

- [1.](#) Introduction [2](#)
- [2.](#) Link Attribute TLVs for TE Metric Extensions [2](#)
 - [2.1.](#) Unidirectional Link Delay TLV [3](#)
 - [2.2.](#) Min/Max Unidirectional Link Delay TLV [3](#)
 - [2.3.](#) Unidirectional Delay Variation TLV [4](#)
 - [2.4.](#) Unidirectional Link Loss TLV [5](#)
 - [2.5.](#) Unidirectional Residual Bandwidth TLV [5](#)
 - [2.6.](#) Unidirectional Available Bandwidth TLV [5](#)
 - [2.7.](#) Unidirectional Utilized Bandwidth TLV [6](#)
- [3.](#) Security Considerations [6](#)
- [4.](#) IANA Considerations [7](#)
- [5.](#) Contributors [7](#)
- [6.](#) Acknowledgements [8](#)
- [7.](#) References [8](#)
 - [7.1.](#) Normative References [8](#)
 - [7.2.](#) Informative References [8](#)
- Authors' Addresses [8](#)

[1.](#) Introduction

BGP-LS ([\[RFC7752\]](#)) defines NLRI and attributes in order to carry link-state information. New BGP-LS Link-Attribute TLVs are required in order to carry the Traffic Engineering Metric Extensions defined in [\[I-D.ietf-lsr-isis-rfc7810bis\]](#) and [\[RFC7471\]](#).

[2.](#) Link Attribute TLVs for TE Metric Extensions


The following new Link Attribute TLVs are defined:

TLV code-point	Value
1114	Unidirectional Link Delay
1115	Min/Max Unidirectional Link Delay
1116	Unidirectional Delay Variation
1117	Unidirectional Link Loss
1118	Unidirectional Residual Bandwidth
1119	Unidirectional Available Bandwidth
1120	Unidirectional Bandwidth Utilization

TLV formats are described in detail in the following sub-sections. TLV formats follow the rules defined in [RFC7752].

2.1. Unidirectional Link Delay TLV

This TLV advertises the average link delay between two directly connected IGP link-state neighbors. The semantics of the value field in the TLV are described in [I-D.ietf-lsr-isis-rfc7810bis] and [RFC7471].



where:

Figure 1


Type: 1114

Length: 4.

2.2. Min/Max Unidirectional Link Delay TLV

This sub-TLV advertises the minimum and maximum delay values between two directly connected IGP link-state neighbors. The semantics of

the value field in the TLV are described in [\[I-D.ietf-lsr-isis-rfc7810bis\]](#) and [\[RFC7471\]](#).



where:


Figure 2

Type: 1115

Length: 8.

2.3. Unidirectional Delay Variation TLV

This sub-TLV advertises the average link delay variation between two directly connected IGP link-state neighbors. The semantics of the value field in the TLV are described in [\[I-D.ietf-lsr-isis-rfc7810bis\]](#) and [\[RFC7471\]](#).



where:


Figure 3

Type: 1116

Length: 4.

2.4. Unidirectional Link Loss TLV

This sub-TLV advertises the loss (as a packet percentage) between two directly connected IGP link-state neighbors. The semantics of the value field in the TLV are described in [[I-D.ietf-lsr-isis-rfc7810bis](#)] and [[RFC7471](#)].




where:

Type:1117

Length: 4.

2.5. Unidirectional Residual Bandwidth TLV

This sub-TLV advertises the residual bandwidth between two directly connected IGP link-state neighbors. The semantics of the value field in the TLV are described in [[I-D.ietf-lsr-isis-rfc7810bis](#)] and [[RFC7471](#)].




where:

Type: 1118

Length: 4.

2.6. Unidirectional Available Bandwidth TLV

This sub-TLV advertises the available bandwidth between two directly connected IGP link-state neighbors. The semantics of the value field in the TLV are described in [[I-D.ietf-lsr-isis-rfc7810bis](#)] and [[RFC7471](#)].



where:


Figure 4

Type: 1119

Length: 4.

2.7. Unidirectional Utilized Bandwidth TLV

This sub-TLV advertises the bandwidth utilization between two directly connected IGP link-state neighbors. The semantics of the value field in the TLV are described in [\[I-D.ietf-lsr-isis-rfc7810bis\]](#) and [\[RFC7471\]](#).



where:

Figure 5

Type: 1120

Length: 4.

3. Security Considerations

Procedures and protocol extensions defined in this document do not affect the BGP security model. See the 'Security Considerations' section of [\[RFC4271\]](#) for a discussion of BGP security. Also refer to [\[RFC4272\]](#) and [\[RFC6952\]](#) for analysis of security issues for BGP. Security considerations for acquiring and distributing BGP-LS information are discussed in [\[RFC7752\]](#).

The TLVs introduced in this document are used to propagate IGP defined information ([[I-D.ietf-lsr-isis-rfc7810bis](#)] and [[RFC7471](#)].) These TLVs represent the state and resource availability of the IGP link. The IGP instances originating these TLVs are assumed to support all the required security and authentication mechanisms (as described in [[I-D.ietf-lsr-isis-rfc7810bis](#)] and [[RFC7471](#)]) in order to prevent any security issue when propagating the TLVs into BGP-LS. The advertisement of the link attribute information defined in this document presents no additional risk beyond that associated with the existing set of link attribute information already supported in [[RFC7752](#)].

4. IANA Considerations

IANA has made temporary assignments in the registry "BGP-LS Node Descriptor, Link Descriptor, Prefix Descriptor, and Attribute TLVs" for the new Link Attribute TLVs defined in the table below:

TLV code-point	Value
1114	Unidirectional Link Delay
1115	Min/Max Unidirectional Link Delay
1116	Unidirectional Delay Variation
1117	Unidirectional Link Loss
1118	Unidirectional Residual Bandwidth
1119	Unidirectional Available Bandwidth
1120	Unidirectional Bandwidth Utilization

5. Contributors

The following people have substantially contributed to this document and should be considered co-authors:

Saikat Ray
 Individual
 Email: raysaikat@gmail.com

Hannes Gredler
 RtBrick Inc.
 Email: hannes@rtbrick.com

6. Acknowledgements

The authors wish to acknowledge comments from Ketan Talaulikar.

7. References

7.1. Normative References

- [I-D.ietf-lsr-isis-rfc7810bis]
Ginsberg, L., Previdi, S., Giacalone, S., Ward, D., Drake, J., and Q. Wu, "IS-IS Traffic Engineering (TE) Metric Extensions", [draft-ietf-lsr-isis-rfc7810bis-03](#) (work in progress), November 2018.
- [RFC7471] Giacalone, S., Ward, D., Drake, J., Atlas, A., and S. Previdi, "OSPF Traffic Engineering (TE) Metric Extensions", [RFC 7471](#), DOI 10.17487/RFC7471, March 2015, <<https://www.rfc-editor.org/info/rfc7471>>.
- [RFC7752] Gredler, H., Ed., Medved, J., Previdi, S., Farrel, A., and S. Ray, "North-Bound Distribution of Link-State and Traffic Engineering (TE) Information Using BGP", [RFC 7752](#), DOI 10.17487/RFC7752, March 2016, <<https://www.rfc-editor.org/info/rfc7752>>.

7.2. Informative References

- [RFC4271] Rekhter, Y., Ed., Li, T., Ed., and S. Hares, Ed., "A Border Gateway Protocol 4 (BGP-4)", [RFC 4271](#), DOI 10.17487/RFC4271, January 2006, <<https://www.rfc-editor.org/info/rfc4271>>.
- [RFC4272] Murphy, S., "BGP Security Vulnerabilities Analysis", [RFC 4272](#), DOI 10.17487/RFC4272, January 2006, <<https://www.rfc-editor.org/info/rfc4272>>.
- [RFC6952] Jethanandani, M., Patel, K., and L. Zheng, "Analysis of BGP, LDP, PCEP, and MSDP Issues According to the Keying and Authentication for Routing Protocols (KARP) Design Guide", [RFC 6952](#), DOI 10.17487/RFC6952, May 2013, <<https://www.rfc-editor.org/info/rfc6952>>.

Authors' Addresses

Les Ginsberg (editor)
Cisco Systems, Inc.
US

Email: ginsberg@cisco.com

Stefano Previdi
Huawei
IT

Email: stefano@previdi.net

Qin Wu
Huawei
101 Software Avenue, Yuhua District
Nanjing, Jiangsu 210012
China

Email: bill.wu@huawei.com

Jeff Tantsura
Apstra, Inc.
US

Email: jefftant.ietf@gmail.com

Clarence Filsfils
Cisco Systems, Inc.
Brussels
BE

Email: cfilsfil@cisco.com