

IMAP Extensions Working Group  
Internet-Draft  
Expires: May 25, 2006

C. Daboo  
  
R. Gellens  
QUALCOMM Incorporated  
November 21, 2005

IMAP ANNOTATE Extension  
draft-ietf-imapext-annotate-14

Status of this Memo

By submitting this Internet-Draft, each author represents that any applicable patent or other IPR claims of which he or she is aware have been or will be disclosed, and any of which he or she becomes aware will be disclosed, in accordance with [Section 6 of BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/1id-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

This Internet-Draft will expire on May 25, 2006.

Copyright Notice

Copyright (C) The Internet Society (2005).

Abstract

The ANNOTATE extension to the Internet Message Access Protocol permits clients and servers to maintain "meta data" for messages, or individual message parts, stored in a mailbox on the server.

Change History (to be removed prior to publication as an RFC)

Changes from -13 to -14:

Internet-Draft

IMAP ANNOTATE Extension

November 2005

1. Changed 'string' formal syntax to 'list-mailbox' and 'astring' for entry/attribute names.
2. Updated examples to match new astring syntax.
3. Now requires explicit use of .priv or .shared in SORT.
4. Removed requirement that 'n' right only be present if 'r' right is also present.
5. Changed ANNOTATESIZE response to ANNOTATIONS response.
6. Allow servers to indicate that they do not support private annotations.
7. Added example for extended SELECT including ANNOTATIONS response code.
8. Removed content-type attribute.
9. Removed display-name attribute.
10. Prevent use of \* and % wildcards in attributes.
11. Only allow "value" attributes in SEARCH.
12. Only allow "value" or "size" attributes in SORT.
13. Removed vendor attributes.
14. Removed IMAP flags, though the /flags entry path is reserved.
15. Added internationalization considerations.

Changes from -12 to -13:

1. Sync with change from DC meeting wrt 'r' right for both read and write of .priv.
2. Add text about 'n' right being a 'shared flag right' as defined in 2086upd.
3. Allow NIL in /<section-part>/flags entries.
4. Expand abstract to also indicate that annotations can apply on a per-body part basis as well as per message.
5. Fix resp-text-code to use nil instead of "NIL".
6. Use double-quotes consistently around ANNOTATESIZE etc.
7. Fix typos.
8. Remove redundant second para of Introduction.
9. Added 'Conventions' section with [RFC2119](#) reference..
10. Describe S:, C: example behaviour in conventions section..
11. Clarify that new rights must also be present if only old ACL is present.
12. Entry/attributes MUST NOT contain consecutive or trailing '/' or '.,'.
13. Clarify default charset for content-type text/plain.
14. Recommend use of utf-8 for all non-ascii text.
15. Clarify terminology of ANNOTATESIZE response code.
16. Require servers to return ANNOTATESIZE on SELECT.
17. Change an example to use UID FETCH for variety.

18. Clarify what to do about annotations exceeding allowed ANNOTATESIZE when doing copy.
19. Use ABNFext document for extended SELECT etc.

20. Remove [RFC1891](#) reference.
21. capability syntax extension.
22. Comment on validation content-type attribute.
23. Added recommended content-type in IANA registration.
24. Added use of literal8 for values.
25. Prevent use of 'shared' and 'priv' as separate hierarchy components.
26. Restrict entry/attribute names to ascii and added display-name attribute.
27. Remove references to CATENATE and use ABNFext for extended APPEND syntax.

Changes from -11 to -12:

1. Fixed raw XML in formal syntax.
2. Fixed double \ in IANA section titles.
3. Fixed APPEND formal syntax.
4. Added annotations to CATENATE extension.
5. Reworded text for unsolicited responses.
6. Fixed formal syntax for fetch responses to extend base spec item.

Changes from -10 to -11:

1. Flags are now read-only and exactly match their IMAP counterparts.
2. Added new ACL bits for annotations.
3. Revise security considerations.
4. Fixed some references.

Changes from -09 to -10:

1. Added Content-Language value.
2. Added IANA registrations for entries/attributes in this document.

Changes from -08 to -09:

1. Fix formatting, ID nits etc.
2. Fix subject -> altsubject in examples.
3. Added text to SELECT/EXAMINE optional parameter definition to indicate that the option could trigger a global state change or a

- mailbox specific change.
4. Changed entry/attribute names to be case-sensitive to avoid case mapping issues with utf8 text.
  5. Clarify COPY interaction to indicate that only the current user's '.priv's are copied, not the '.priv's of other users.

Changes from -07 to -08:

1. ANNOTATESIZE response changed to use "NIL" for a mailbox that does not support any type of annotations, and "0" for a mailbox that only supports read-only annotations.

Changes from -06 to -07:

Daboo & Gellens

Expires May 25, 2006

[Page 3]

---

Internet-Draft

IMAP ANNOTATE Extension

November 2005

1. Added text to state entry and attribute names are always case-insensitive.
2. Removed top-level entry namespace.
3. Added server accept minima for annotation size and count.
4. Added [ANNOTATE TOOBIG] & [ANNOTATE TOOMANY] response codes.
5. Added [ANNOTATESIZE <n>] response code.
6. Added comment on suggested CONDSTORE support.
7. Modified append behaviour to account for MULTIAPPEND.
8. Tweaked ABNF.

Changes from -05 to -06:

1. Split references into Normative and Informative.
2. Reworked flags to allow IMAP4 flag prefix to appear in annotation name.
3. Removed smtp-envelope annotation - a future extension can add this.
4. Changed subject to altsubject.
5. Added \$MDNSent flag and reference to document.
6. Cleaned up formal syntax to use IMAP string type for entry and attributes, with requirements on how the string is formatted.
7. Use of ACAP vendor subtree registry for vendor tokens.
8. Fixed STORE syntax.

Changes from -04 to -05:

1. Fixed examples to match formal syntax for FETCH responses where parenthesis do not appear around entry-att items.

Changes from -03 to -04:

1. Fixed attrib/attrib-match grammar to use "." instead of "/".

2. Add text for server to reject unknown <part-specifier>.
3. Do not allow empty part-specifier.
4. Store NIL to value to delete.
5. Comment on COPY interaction with ANNOTATE.
6. Added comment that IMAP flags are mapped one-to-one with their corresponding FLAGS items.
7. Added comment that the recent flag annotation is read-only.

Changes from -02 to -03:

1. Removed reference to status modtime item.
2. Added missing 'notify' and 'ret' dsn annotations for /message/smtp-envelope.
3. Added requirement to store data permanently - no 'session only' annotations.
4. Removed Access Control section. Replaced with comments on read-only/read-write mailboxes and storing private or shared annotations.

5. Removed STORE to default .priv or .shared.
6. Added section on optional select parameters.

Changes from -01 to -02:

1. Now require .priv or .shared on store operations.

Changes from -00 to -01:

1. MODTIME moved to its own draft, which this draft now depends on. Thus, Conditional Annotation STORE and related items deleted from this draft.
2. Private versus Shared Annotations: both are possible (separately addressable using ".priv" and ".shared" suffixes). There is a per-mailbox setting for the default. It is an open issue how this is viewed or changed by the client.
3. In ACLs, the "w" right is needed to updated shared state; the "s" right is needed to update private state.
4. Various clarifications and text modifications.
5. Added 'forwarded' flag for message parts.

Changes from pre-imapext to -00:

1. Clarified text describing attributions, entries, and attributes.
2. Changed 'modifiedsince' to 'modtime'; referenced ACAP spec.

3. Deleted 'queued' flag.
4. Expanded and explained smtp-envelope entry.
5. Restricted including ANNOTATION data in unsolicited responses until the client uses it first. (Open issue as to if needed).
6. Examples now only use valid entries and attributes.
7. Updated Security Considerations.
8. Content-Type now defaults to text/plain.
9. Open Issue: Shared vs. private annotations.
10. Open issue: Annotation Modtime untagged response or VALIDTIME FETCH data.
11. Open issue: Conditional annotation STORE.
12. ANNOTATION criterion available if both "ANNOTATE" and "SORT" in CAPABILITY command response.
13. Prohibition on annotations in lieu of base spec functionality.
14. Specified required ACL rights.
15. ANNOTATION message data item in APPEND.
16. ANNOTATION-MODTIME message data item in STATUS.
17. Replaced ATOM\_CHAR with utf8-char.
18. Updated other ABNF entries.

## Table of Contents

<a href="#">1.</a>	Introduction and Overview . . . . .	<a href="#">7</a>
<a href="#">2.</a>	Conventions Used in This Document . . . . .	<a href="#">7</a>
<a href="#">3.</a>	Data Model . . . . .	<a href="#">8</a>
<a href="#">3.1.</a>	Overview . . . . .	<a href="#">8</a>
<a href="#">3.2.</a>	Namespace of entries and attributes . . . . .	<a href="#">8</a>
<a href="#">3.2.1.</a>	Entry Names . . . . .	<a href="#">9</a>
<a href="#">3.2.2.</a>	Attribute Names . . . . .	<a href="#">10</a>
<a href="#">3.3.</a>	Private versus Shared . . . . .	<a href="#">11</a>
<a href="#">3.4.</a>	Access Control . . . . .	<a href="#">12</a>
<a href="#">3.5.</a>	Access to Standard IMAP Flags and Keywords . . . . .	<a href="#">15</a>
<a href="#">4.</a>	IMAP Protocol Changes . . . . .	<a href="#">15</a>
<a href="#">4.1.</a>	General Considerations . . . . .	<a href="#">15</a>
<a href="#">4.2.</a>	ANNOTATE parameter with the SELECT/EXAMINE commands . . . . .	<a href="#">16</a>

<a href="#">4.3.</a>	<a href="#">ANNOTATION Message Data Item in FETCH Command</a>	<a href="#">16</a>
<a href="#">4.4.</a>	<a href="#">ANNOTATION Message Data Item in FETCH Response</a>	<a href="#">18</a>
<a href="#">4.5.</a>	<a href="#">ANNOTATION Message Data Item in STORE</a>	<a href="#">20</a>
<a href="#">4.6.</a>	<a href="#">ANNOTATION interaction with COPY</a>	<a href="#">21</a>
<a href="#">4.7.</a>	<a href="#">ANNOTATION Message Data Item in APPEND</a>	<a href="#">22</a>
<a href="#">4.8.</a>	<a href="#">ANNOTATION Criterion in SEARCH</a>	<a href="#">22</a>
<a href="#">4.9.</a>	<a href="#">ANNOTATION Key in SORT</a>	<a href="#">23</a>
<a href="#">4.10.</a>	<a href="#">New ACL Rights</a>	<a href="#">24</a>
<a href="#">5.</a>	<a href="#">Formal Syntax</a>	<a href="#">24</a>
<a href="#">6.</a>	<a href="#">IANA Considerations</a>	<a href="#">26</a>
<a href="#">6.1.</a>	<a href="#">Entry and Attribute Registration Template</a>	<a href="#">26</a>
<a href="#">6.2.</a>	<a href="#">Entry Registrations</a>	<a href="#">27</a>
<a href="#">6.2.1.</a>	<a href="#">/comment</a>	<a href="#">27</a>
<a href="#">6.2.2.</a>	<a href="#">/flags</a>	<a href="#">27</a>
<a href="#">6.2.3.</a>	<a href="#">/altsubject</a>	<a href="#">28</a>
<a href="#">6.2.4.</a>	<a href="#">/&lt;section-part&gt;/comment</a>	<a href="#">28</a>
<a href="#">6.2.5.</a>	<a href="#">/&lt;section-part&gt;/flags/seen</a>	<a href="#">29</a>
<a href="#">6.2.6.</a>	<a href="#">/&lt;section-part&gt;/flags/answered</a>	<a href="#">29</a>
<a href="#">6.2.7.</a>	<a href="#">/&lt;section-part&gt;/flags/flagged</a>	<a href="#">30</a>
<a href="#">6.2.8.</a>	<a href="#">/&lt;section-part&gt;/flags/forwarded</a>	<a href="#">30</a>
<a href="#">6.3.</a>	<a href="#">Attribute Registrations</a>	<a href="#">30</a>
<a href="#">6.3.1.</a>	<a href="#">value</a>	<a href="#">31</a>
<a href="#">6.3.2.</a>	<a href="#">size</a>	<a href="#">31</a>
<a href="#">6.3.3.</a>	<a href="#">content-language</a>	<a href="#">32</a>
<a href="#">7.</a>	<a href="#">Internationalization Considerations</a>	<a href="#">32</a>
<a href="#">8.</a>	<a href="#">Security Considerations</a>	<a href="#">32</a>
<a href="#">9.</a>	<a href="#">References</a>	<a href="#">32</a>
<a href="#">9.1.</a>	<a href="#">Normative References</a>	<a href="#">32</a>
<a href="#">9.2.</a>	<a href="#">Informative References</a>	<a href="#">33</a>
<a href="#">Appendix A.</a>	<a href="#">Acknowledgments</a>	<a href="#">33</a>
	<a href="#">Authors' Addresses</a>	<a href="#">34</a>
	<a href="#">Intellectual Property and Copyright Statements</a>	<a href="#">35</a>

## [1.](#) Introduction and Overview

The ANNOTATE extension is present in any IMAP [\[RFC3501\]](#) implementation which returns "ANNOTATE" as one of the supported capabilities in the CAPABILITY response.

This extension makes the following changes to the IMAP protocol:

- a. adds a new ANNOTATION message data item for use in FETCH
- b. adds a new ANNOTATION message data item for use in STORE
- c. adds a new ANNOTATION search criterion for use in SEARCH
- d. adds a new ANNOTATION sort key for use in SORT extension
- e. adds a new ANNOTATION data item for use in APPEND
- f. adds a new requirement on the COPY command
- g. adds a new ANNOTATE parameter for use with the SELECT/EXAMINE commands
- h. adds two new response codes to indicate store failures of annotations.
- i. adds a new untagged response code for the SELECT or EXAMINE commands to indicate the maximum size.
- j. adds a new ACL "bit" for use with the ACL extensions [[RFC2086](#)] and [[I-D.ietf-imapext-2086upd](#)] .

The data model used for the storage of annotations is based on that of the Application Configuration Access Protocol [[RFC2244](#)]. Note that there is no inheritance in annotations.

If a server supports annotations, then it **MUST** store all annotation data permanently, i.e. there is no concept of "session only" annotations that would correspond to the behaviour of "session" flags as defined in the IMAP base specification.

In order to provide optimum support for a disconnected client (one that needs to synchronise annotations for use when offline), servers **SHOULD** also support the Conditional STORE [[I-D.ietf-imapext-condstore](#)] extension.

The rest of this document describes the data model and protocol changes more rigorously.

## [2.](#) Conventions Used in This Document

In examples, "C:" and "S:" indicate lines sent by the client and server respectively.

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this

document are to be interpreted as described in [[RFC2119](#)].



### [3.](#) Data Model

#### [3.1.](#) Overview

The data model used in ANNOTATE is that of a uniquely named entry which contains a set of standard attributes. A single coherent unit of "meta data" for a message is stored as a single entry, made up of several attributes.

For example, a comment annotation added to a message has an entry name of `"/comment"`. This entry is composed of several attributes such as `"value"`, `"size"`, etc. which contain the properties and data of the entry.

The protocol changes to IMAP described below allow a client to access or change the values of any attributes in any entries in a message annotation, assuming it has sufficient access rights to do so (see [Section 3.4](#) for specifics).

#### [3.2.](#) Namespace of entries and attributes

Each message annotation is made up of a set of entries. Each entry has a hierarchical name, with each component of the name separated by a slash (`"/"`). An entry name **MUST NOT** contain two consecutive `"/"` characters and **MUST NOT** end with a `"/"` character.

Each entry is made up of a set of attributes. Each attribute has a hierarchical name, with each component of the name separated by a period (`"."`). An attribute name **MUST NOT** contain two consecutive `"."` characters and **MUST NOT** end with a `"."` character.

The value of an attribute is `"NIL"` (has no value), or is a string of zero or more octets.

Entry and attribute names **MUST NOT** contain asterisk (`"*"`) or percent (`"%"`) characters and **MUST NOT** contain non-ASCII characters or the NULL octet. Invalid entry or attribute names result in a BAD response in any IMAP commands where they are used.

Attribute names **MUST NOT** contain any hierarchical components with the names `"priv"` or `"shared"` as those have special meaning (see [Section 3.3](#)).

Entry and attribute names are case-sensitive.

Use of control or punctuation characters in entry and attribute names is strongly discouraged.

This specification defines an initial set of entry and attribute names available for use in message annotations. In addition, an extension mechanism is described to allow additional names to be added as needed.

### [3.2.1.](#) Entry Names

Entry names **MUST** be specified in a standards track or IESG approved experimental RFC, or fall under the vendor namespace. See [Section 6.1](#) for the registration template.

- /
  - Defines the top-level of entries associated with an entire message. This entry itself does not contain any attributes. All entries that start with a numeric character ("0" - "9") refer to an annotation on a specific body part. All other entries are for annotations on the entire message.
- /comment
  - Defines a comment or note associated with an entire message.
- /flags
  - This entry hierarchy is reserved for future use.
- /altsubject
  - Contains text supplied by the message recipient, to be used by the client instead of the original message Subject.
- /vendor/<vendor-token>
  - Defines the top-level of entries associated with an entire message as created by a particular product of some vendor. These sub-entries can be used by vendors to provide client-specific annotations. The vendor-token **MUST** be registered with IANA, using the [\[RFC2244\]](#) vendor subtree registry.
- /<section-part>
  - Defines the top-level of entries associated with a specific body part of a message. This entry itself does not contain any attributes. The section-part uses the same numeric part specifier syntax as the BODY message data item in the FETCH command [\[RFC3501\]](#). The server **MUST** return a BAD response if the client uses an incorrect part specifier (either incorrect syntax or a specifier referring to a non-existent part). The server **MUST**

return a BAD response if the client uses an empty part specifier (which is used in IMAP to represent the entire message).

`/<section-part>/comment`

Defines a comment or note associated with a specific body part of a message.

`/<section-part>/flags`

Defines the top-level of entries associated with flag state for a specific body part of a message. All sub-entries are maintained entirely by the client. There is no implicit change to any flag by the server.

`/<section-part>/flags/seen`

`/<section-part>/flags/answered`

`/<section-part>/flags/flagged`

`/<section-part>/flags/forwarded`

Defines flags for a specific body part of a message. The "value" attribute of each of the entries described above must be either "1", "0" or "NIL". "1" corresponds to the flag being set.

`/<section-part>/vendor/<vendor-token>`

Defines the top-level of entries associated with a specific body part of a message as created by a particular product of some vendor. This entry can be used by vendors to provide client specific annotations. The vendor-token MUST be registered with IANA.

### [3.2.2.](#) Attribute Names

Attribute names MUST be specified in a standards track or IESG approved experimental RFC. See [Section 6.1](#) for the registration template.

All attribute names implicitly have a ".priv" and a ".shared" suffix which maps to private and shared versions of the entry. Searching or fetching without using either suffix includes both. The client MUST specify either a ".priv" or ".shared" suffix when storing an annotation.

value

A string or binary data representing the value of the annotation. To delete an annotation, the client can store "NIL" into the value. The content represented by the string is determined by the Content-type used to register the entry (see [Section 6.1](#) for entry registration templates). Where applicable, the registered content-type MUST include a charset parameter. Text values SHOULD use the utf-8 [[RFC3629](#)] character set.

Note that binary data (data which may contain the NULL octet) is allowed (e.g. for storing images etc), and this extension uses the "literal8" syntax element [[I-D.melnikov-imap-ext-abnf](#)] to allow such data to be written to or read from the server.

#### size

The size of the value, in octets. Set automatically by the server, read-only to clients.

#### content-language

Indicates the language used for the value. This follows the format described in [[RFC3282](#)]. Clients SHOULD set this value when storing an annotation that uses text that can be presented to the user. It is not required for enumerated or numeric values such as flags etc. If a value is being set, clients MUST ensure that it accurately reflects the content stored in the value attribute. Servers MUST ensure that the "content-language" attribute value is kept in synchronization with the "value" attribute. To ensure that, the server MUST remove any "content-language" attribute value when the client STOREs a "value" attribute without also including a "content-language" attribute in the same STORE command.

### [3.3.](#) Private versus Shared

Some IMAP mailboxes are private, accessible only to the owning user. Other mailboxes are not, either because the owner has set an ACL [[I-D.ietf-imapext-2086upd](#)] which permits access by other users, or because it is a shared mailbox.

This raises the issue of shared versus private annotations.

If all annotations are private, it is impossible to set annotations in a shared or otherwise non-private mailbox that are visible to other users. This eliminates what could be a useful aspect of annotations in a shared environment. An example of such use is a shared IMAP folder containing bug reports. Engineers may want to use annotations to add information to existing messages, indicate assignments, status, etc. This use requires shared annotations.

If all annotations are shared, it is impossible to use annotations for private notes on messages in shared mailboxes. Also, modifying an ACL to permit access to a mailbox by other users may unintentionally expose private information.

There are also situations in which both shared and private annotations are useful. For example, an administrator may want to set shared annotations on messages in a shared folder, which

individual users may wish to supplement with additional notes.

If shared and private annotations are to coexist, we need a clear way to differentiate them. Also, it should be as easy as possible for a client to access both and not overlook either. There is also a danger in allowing a client to store an annotation without knowing if it is shared or private.

This document proposes two standard suffixes for all attributes: ".shared" and ".priv". A SEARCH or FETCH command which specifies neither uses both. STORE, APPEND and SORT commands MUST explicitly use ".priv" or ".shared" suffixes.

If the ANNOTATE extension is present, support for shared annotations in servers is REQUIRED, whilst support for private annotations in servers is OPTIONAL. This recognises the fact that support for private annotations may introduce significantly more complexity to a server in terms of tracking ownership of the annotations, how quota is determined for users based on their own annotations etc. Clients that support the ANNOTATE extension MUST handle both shared and private annotations.

### [3.4.](#) Access Control

A user needs to have appropriate rights in order to read or write

".priv" or ".shared" annotation values. How those rights are calculated depends on whether the ACL [[RFC2086](#)] extension or its update [[I-D.ietf-imapext-2086upd](#)] is present or not. If a client attempts to store or fetch an annotation to which they do not have the appropriate rights, the server MUST respond with a NO response.

When the ACL extension is not present, access to annotation values is governed by the nature of the selected state. In particular whether the mailbox was SELECT'ed or EXAMINE'd in READ-ONLY or READ-WRITE mode.

When the ACL extension is present, the server MUST recognise the new ACL right "n", in addition to the ones defined by the ACL extension itself.

The "r" right controls both read and write access to ".priv" annotation values. When it is on, access to ".priv" annotations is allowed, when it is off, access to ".priv" annotations is disallowed.

The "r" right controls only the read access for ".shared" annotation values. When it is on, ".shared" annotations can be read, when it is off, ".shared" annotations cannot be read.

The "n" right controls only the write access for ".shared" annotation values. When it is on, ".shared" annotations can be changed or created through either a STORE or APPEND command, when it is off, ".shared" annotations cannot be changed or created. The "n" right constitutes a "shared flag right" as defined in [[I-D.ietf-imapext-2086upd](#)] [Section 6.2](#).

A summary of all the access control restrictions is tabulated below

Server Type	Action on annotation	Type of mailbox
	read .priv values	Any mailbox that can be SELECTED or EXAMINED.
	write .priv	Any SELECTED [READ-WRITE] mailbox.

Server without ACL Extension	values	SELECTED [READ-ONLY] mailboxes MAY also permit writes.
	read .shared values	Any mailbox that can be SELECTED or EXAMINED.
	write .shared values	Any mailbox that can be SELECTED or EXAMINED and is [READ-WRITE].
Server with ACL Extension	read .priv values	Any mailbox with the "r" ACL right.
	write .priv values	Any mailbox with the "r" ACL right.
	read .shared values	Any mailbox with the "r" ACL right.
	write .shared values	Any mailbox with the "n" ACL right.

### [3.5.](#) Access to Standard IMAP Flags and Keywords

Due to ambiguity of how private and shared values would map to the base IMAP flag and keyword values, the ANNOTATE extension does not



expose IMAP flags or keywords as entries. However, the /flags annotation entry is reserved for future use and MUST NOT be used by clients or servers supporting this extension.

Clients that need to implement shared and private "flags" can create their own annotation entries for those, completely bypassing the base IMAP flag/keyword behaviour.

## [4.](#) IMAP Protocol Changes

### [4.1.](#) General Considerations

Servers may be able to offer only a limited level of support for annotations in mailboxes, and it is useful for clients to be able to know what level of support is available. Servers MUST return an ANNOTATIONS response during the SELECT or EXAMINE command for a mailbox to indicate the level of support. Possible response codes used with the ANNOTATIONS response are:

"NONE" - this indicates that the mailbox being selected does not support annotations at all. Clients MUST NOT attempt to use annotation extensions in commands.

"READ-ONLY" - this indicates that the annotations supported by the mailbox cannot be changed by the client. Clients MUST NOT attempt to store annotations on any messages in a mailbox with this response code.

"NOPRIVATE" - this indicates that the server does not support private annotations on the mailbox. Only shared annotations are supported. Clients SHOULD only attempt to read or store annotations attributes with the ".shared" suffix. If a client uses an attribute with the ".priv" suffix in a FETCH command, then servers should return the attribute value in the FETCH response as "NIL". If a client uses an attribute with the ".priv" suffix in a STORE command (or an APPEND command targetted at the mailbox) then the server MUST return a NO response.

numeric values - if servers support writable annotations, then the server MUST indicate the maximum size for an annotation value by providing the maximum size value in the response code. Clients MUST NOT store annotation values of a size greater than the amount indicated by the server. Servers MUST accept a minimum annotation

data size of at least 1024 bytes if annotations can be written.

In addition the server MAY limit the total number of annotations for a single message. However, the server MUST provide a minimum annotation count per message of at least 10.

#### [4.2.](#) ANNOTATE parameter with the SELECT/EXAMINE commands

The ANNOTATE extension defines a single optional SELECT parameter [[I-D.melnikov-imap-ext-abnf](#)] "ANNOTATE", which is used to turn on unsolicited responses for annotations as described in [Section 4.4](#). This optional parameter results in a per-mailbox state change, i.e. it must be used in each SELECT/EXAMINE command in order to be effective, irrespective of whether it was used in a previous SELECT/EXAMINE during the same session.

Example:

```
C: a SELECT INBOX ANNOTATE
S: * FLAGS (\Answered \Flagged \Draft \Deleted \Seen)
S: * OK [PERMANENTFLAGS (\Answered \Flagged \Draft
                        \Deleted \Seen \*)]

S: * 10268 EXISTS
S: * 1 RECENT
S: * OK [UNSEEN 10268]
S: * OK [UIDVALIDITY 890061587]
S: * OK [UIDNEXT 34643]
S: * OK [ANNOTATIONS 20480 NOPRIVATE]
S: a OK [READ-WRITE] Completed
```

In the above example, a SELECT command with the ANNOTATE parameter is issued. The response from the server includes the required ANNOTATIONS response that indicates that the server supports annotations up to a maximum size of 20480 bytes and does not support private annotations (only shared).

#### [4.3.](#) ANNOTATION Message Data Item in FETCH Command

This extension adds an ANNOTATION message data item to the FETCH command. This allows clients to retrieve annotations for a range of messages in the currently selected mailbox.

ANNOTATION <entry-specifier> <attribute-specifier>

The ANNOTATION message data item, when used by the client in the FETCH command, takes an entry specifier and an attribute specifier.

Internet-Draft

IMAP ANNOTATE Extension

November 2005

Example:

```
C: a FETCH 1 (ANNOTATION (/comment value))
S: * 1 FETCH (ANNOTATION (/comment
                    (value.priv "My comment"
                    value.shared "Group note")))
S: a OK Fetch complete
```

In the above example, the content of the "value" attribute for the "/comment" entry is requested by the client and returned by the server. Since neither ".shared" nor ".priv" was specified, both are returned.

"\*" and "%" wild card characters can be used in entry specifiers to match one or more characters at that position, with the exception that "%" does not match the "/" hierarchy delimiter. Thus an entry specifier of "/" matches entries such as "/comment" and "/altsubject", but not "/1/comment".

Example:

```
C: a UID FETCH 1123 (UID ANNOTATION
                    (/ * (value.priv size.priv)))
S: * 12 FETCH (UID 1123 ANNOTATION
                (/comment (value.priv "My comment"
                           size.priv "10")
                /altsubject (value.priv "Rhinoceroses!"
                           size.priv "13")
                /vendor/foobar/label.priv
                           (value.priv "label43"
                           size.priv "7")
                /vendor/foobar/personality
                           (value.priv "Tallulah Bankhead"
                           size.priv "17")))
S: a OK Fetch complete
```

In the above example, the contents of the private "value" and "size" attributes for any entries in the "/" hierarchy are requested by the client and returned by the server.

Example:

```
C: a FETCH 1 (ANNOTATION (/ % value.shared))
S: * 1 FETCH (ANNOTATION
  (/comment (value.shared "Patch Mangler")
  /altsubject (value.shared "Patches? We don't
    need no steenkin patches!")))
S: a OK Fetch complete
```

In the above example, the contents of the shared "value" attributes for entries at the top level only of the "/" hierarchy are requested by the client and returned by the server.

Entry and attribute specifiers can be lists of atomic specifiers, so that multiple items of each type may be returned in a single FETCH command.

Example:

```
C: a FETCH 1 (ANNOTATION
  ((/comment /altsubject) value.priv))
S: * 1 FETCH (ANNOTATION
  (/comment (value.priv "What a chowder-head")
  /altsubject (value.priv "How to crush beer cans")))
S: a OK Fetch complete
```

In the above example, the contents of the private "value" attributes for the two entries "/comment" and "/altsubject" are requested by the client and returned by the server.

#### [4.4.](#) ANNOTATION Message Data Item in FETCH Response

The ANNOTATION message data item in the FETCH response displays information about annotations in a message.

ANNOTATION parenthesised list

The response consists of a list of entries, each of which has a list of attribute-value pairs.

Example:

```

C: a FETCH 1 (ANNOTATION (/comment value))
S: * 1 FETCH (ANNOTATION (/comment
                        (value.priv "My comment"
                        value.shared NIL)))

S: a OK Fetch complete

```

In the above example, a single entry with a single attribute-value pair is returned by the server. Since the client did not specify a ".shared" or ".priv" suffix, both are returned. Only the private attribute has a value (the shared value is "NIL").

Example:

```

C: a FETCH 1 (ANNOTATION
              ((/comment /altsubject) value))
S: * 1 FETCH (ANNOTATION
              (/comment (value.priv "My comment"
                              value.shared NIL)
                        /altsubject (value.priv "My subject"
                              value.shared NIL)))

S: a OK Fetch complete

```

In the above example, two entries each with a single attribute-value pair are returned by the server. Since the client did not specify a ".shared" or ".priv" suffix, both are returned. Only the private attributes have values; the shared attributes are "NIL".

Example:

```

C: a FETCH 1 (ANNOTATION
              (/comment (value size)))
S: * 1 FETCH (ANNOTATION
              (/comment
                (value.priv "My comment"
                value.shared NIL
                size.priv "10"
                size.shared "0")))

S: a OK Fetch complete

```

In the above example, a single entry with two attribute-value pairs is returned by the server. Since the client did not specify a ".shared" or ".priv" suffix, both are returned. Only the private attributes have values; the shared attributes are "NIL".

Servers SHOULD send ANNOTATION message data items in unsolicited FETCH responses if an annotation entry is changed by a third-party, and the ANNOTATE select parameter was used. This allows servers to keep clients updated with changes to annotations by other clients.

Unsolicited ANNOTATION responses MUST NOT include ANNOTATION data values - only the entry name of the ANNOTATION that has changed. This restriction avoids sending ANNOTATION data values (which may be large) to a client unless the client explicitly asks for the value.

Example:

```
C: a STORE 1 +FLAGS (\Seen)
S: * 1 FETCH (FLAGS (\Seen))
      ANNOTATION (/comment))
S: a OK STORE complete
```

In the above example, an unsolicited ANNOTATION response is returned during a STORE command. The unsolicited response contains only the entry name of the annotation that changed, and not its value.

#### [4.5.](#) ANNOTATION Message Data Item in STORE

ANNOTATION <parenthesised entry-attribute-value list>

Sets the specified list of entries by adding or replacing the specified attributes with the values provided. Clients can use "NIL" for values of attributes it wants to remove from entries.

The ANNOTATION message data item used with the STORE command has an implicit ".SILENT" behaviour. This means the server does not generate an untagged FETCH in response to the STORE command and assumes that the client updates its own cache if the command succeeds.

If the server is unable to store an annotation because the size of its value is too large, the server MUST return a tagged NO response with a "[ANNOTATE TOOBIG]" response code.

If the server is unable to store a new annotation because the maximum number of allowed annotations has already been reached, the server MUST return a tagged NO response with a "[ANNOTATE TOOMANY]" response code.

Example:

```
C: a STORE 1 ANNOTATION (/comment
                           (value.priv "My new comment"))
S: a OK Store complete
```

In the above example, the entry `/comment` is created (if not already present) and the private attribute `value` with data set to `"My new comment"` is created if not already present, or replaced if it exists.

Example:

```
C: a STORE 1 ANNOTATION (/comment
                           (value.shared NIL))
S: a OK Store complete
```

In the above example, the shared `value` attribute of the entry `/comment` is removed by storing `"NIL"` into the attribute.

Multiple entries can be set in a single STORE command by listing entry-attribute-value pairs in the list.

Example:

```
C: a STORE 1 ANNOTATION (/comment
                           (value.priv "Get tix Tuesday")
                           /altsubject
                           (value.priv "Wots On"))
S: a OK Store complete
```

In the above example, the entries `/comment` and `/altsubject` are

created (if not already present) and the private attribute "value" is created for each entry if not already present, or replaced if they exist.

Multiple attributes can be set in a single STORE command by listing multiple attribute-value pairs in the entry list.

Example:

```
C: a STORE 1 ANNOTATION (/comment
                           (value.priv "My new comment"
                             value.shared "foo's bar"))
S: a OK Store complete
```

In the above example, the entry "/comment" is created (if not already present) and the private and shared "value" attributes are created if not already present, or replaced if they exist.

#### [4.6.](#) ANNOTATION interaction with COPY

The COPY command can be used to move messages from one mailbox to another on the same server. Servers that support the ANNOTATION extension MUST, for each message being copied, copy all ".priv" annotation data for the current user only, and all ".shared" annotation data along with the message to the new mailbox. The only exceptions to this are if the destination mailbox permissions are such that either the ".priv" or ".shared" annotations are not allowed, or if the destination mailbox is of a type that does not support annotations or does not support storing of annotations (a mailbox that returns a "NONE" or "READ-ONLY" response code in its ANNOTATIONS response), or if the destination mailbox cannot support the size of an annotation because it exceeds the ANNOTATIONS value. Servers MUST NOT copy ".priv" annotation data for users other than the current user.

#### [4.7.](#) ANNOTATION Message Data Item in APPEND

ANNOTATION <parenthesised entry-attribute-value list>

Sets the specified list of entries and attributes in the resulting



message.

The APPEND command can include annotations for the message being appended via the addition of a new append data item [I-D.melnikov-imap-ext-abnf]. The new data item can also be used with the multi-append [[RFC3502](#)] extension that allows multiple messages to be appended via a single APPEND command.

Example:

```
C: a APPEND drafts ANNOTATION (/comment
    (value.priv "Don't send until I say so")) {310}
S: + Ready for literal data
C: MIME-Version: 1.0
...
C:
S: a OK APPEND completed
```

In the above example, a comment with a private value is added to a new message appended to the mailbox. The ellipsis represents the bulk of the message.

#### [4.8.](#) ANNOTATION Criterion in SEARCH

ANNOTATION <entry-name> <attribute-name> <value>

The ANNOTATION criterion for the SEARCH command allows a client to search for a specified string in the value of an annotation entry of a message.

Messages that have annotations with entries matching <entry-name> and attributes matching <attribute-name> and the specified string <value> in their values are returned in the SEARCH results. The "\*" character can be used in the entry name field to match any content in those items. The "%" character can be used in the entry name field to match a single level of hierarchy only.

Only the "value", "value.priv" and "value.shared" attributes can be searched. Clients MUST NOT specify an attribute other than either "value", "value.priv" or "value.shared". Servers MUST return a BAD response if the client tries to search any other attribute.

Example:

```
C: a SEARCH ANNOTATION /comment value "IMAP4"  
S: * SEARCH 2 3 5 7 11 13 17 19 23  
S: a OK Search complete
```

In the above example, the message numbers of any messages containing the string "IMAP4" in the shared or private "value" attribute of the "/comment" entry are returned in the search results.

Example:

```
C: a SEARCH ANNOTATION * value.priv "IMAP4"  
S: * SEARCH 1 2 3 5 8 13 21 34  
S: a OK Search complete
```

In the above example, the message numbers of any messages containing the string "IMAP4" in the private "value" attribute of any entry are returned in the search results.

#### [4.9.](#) ANNOTATION Key in SORT

ANNOTATION <entry-name> <attribute-name>

The ANNOTATION criterion for the SORT command [[I-D.ietf-imapext-sort](#)] instructs the server to return the message numbers or UIDs of a mailbox, sorted using the values of the specified annotations. The ANNOTATION criterion is available if the server returns both ANNOTATE and SORT as supported capabilities in the CAPABILITY command response.

Messages are sorted using the values of the <attribute-name> attributes in the <entry-name> entries.

Clients MUST provide either the ".priv" or ".shared" suffix to the attribute name to ensure that the server knows which specific value to sort on.

Only the "value.priv", "value.shared", "size.priv" and "size.shared" attributes can be used for sorting. Clients MUST NOT specify an attribute other than either "value.priv", "value.shared", "size.priv" or "size.shared". Servers MUST return a BAD response if the client tries to search any other attribute.

When either "value.priv" or "value.shared" is being sorted, the server MUST use the character set value specified in the SORT command to determine the appropriate sort order.

When either "size.priv" or "size.shared" is being sorted, the server

Internet-Draft

# IMAP ANNOTATE Extension

November 2005

sorts using the numeric values of those attributes, as it would when the "SIZE" sort key is used.

Example:

```
C: a SORT (ANNOTATION /altsubject value.shared) UTF-8 ALL
S: * SORT 2 3 4 5 1 11 10 6 7 9 8
S: a OK Sort complete
```

In the above example, the message numbers of all messages are returned, sorted according to the shared "value" attribute of the "/altsubject" entry.

Note that the ANNOTATION sort key must include a fully specified entry - wild cards are not allowed.

#### 4.10. New ACL Rights

As discussed in [Section 3.4](#) this extension adds a new "n" right to the list of rights provided by the ACL extensions [[RFC2086](#)] and [[I-D.ietf-imapext-2086upd](#)].

## 5. Formal Syntax

The following syntax specification uses the Augmented Backus-Naur Form (ABNF) notation as specified in [\[RFC2234\]](#).

Non-terminals referenced but not defined below are as defined by [RFC3501] with the new definitions in [I-D.melnikov-imap-ext-abnf] superseding those in [RFC3501].

Except as noted otherwise, all alphabetic characters are case-insensitive. The use of upper or lower case characters to define token strings is for editorial clarity only. Implementations **MUST** accept these strings in a case-insensitive fashion.

```
ann-size      = "NONE" /
                (("READ-ONLY" / nz-size)
                 [SP "NOPRIVATE"])
                ; response codes indicating the level of
                ; support for annotations in a mailbox
```



```

msg-att-dynamic    =/ "ANNOTATION" SP
                    ( "(" entry-att *(SP entry-att) ")" /
                      "(" entry *(SP entry) ")" )
                    ; extends FETCH response with annotation data

resp-text-code     =/ "ANNOTATE" SP "TOOBIG" /
                    "ANNOTATE" SP "TOOMANY" /
                    "ANNOTATIONS" SP ann-size
                    ; new response codes

search-key         =/ "ANNOTATION" SP entry-match SP att-search
                    SP value
                    ; modifies original IMAP search-key

```

```

select-param       =/ "ANNOTATE"
                    ; defines the select parameter used with
                    ; ANNOTATE extension

sort-key           =/ "ANNOTATION" SP entry SP att-sort
                    ; modifies original sort-key

store-att-flags    =/ att-annotate
                    ; modifies original IMAP STORE command

value              = nstring / literal8

```

## [6.](#) IANA Considerations

Entry names **MUST** be specified in a standards track or IESG approved experimental RFC, or fall under the vendor namespace. Vendor names **MUST** be registered.

Attribute names **MUST** be specified in a standards track or IESG approved experimental RFC.

Each entry registration **MUST** include a content-type that is used to indicate the nature of the annotation value. Where applicable a charset parameter **MUST** be included with the content-type.

### [6.1.](#) Entry and Attribute Registration Template

To: iana@iana.org  
Subject: IMAP Annotate Registration

Please register the following IMAP Annotate item:

☐ Entry            ☐ Attribute

Name: \_\_\_\_\_

Description: \_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

Content-Type: \_\_\_\_\_

Contact person: \_\_\_\_\_

Daboo & Gellens

Expires May 25, 2006

[Page 26]

---

Internet-Draft

IMAP ANNOTATE Extension

November 2005

email: \_\_\_\_\_

## [6.2.](#) Entry Registrations

The following templates specify the IANA registrations of annotation entries specified in this document.

### [6.2.1.](#) /comment

To: iana@iana.org  
Subject: IMAP Annotate Registration

Please register the following IMAP Annotate item:

☒ Entry            ☐ Attribute

Name: /comment

Description: Defined in IMAP ANNOTATE extension document.

Content-Type: text/plain; charset=utf-8

Contact person: Cyrus Daboo

email: cyrus@daboo.name

#### [6.2.2.](#) /flags

To: iana@iana.org

Subject: IMAP Annotate Registration

Please register the following IMAP Annotate item:

☒ Entry            ☐ Attribute

Name: /flags

Description: Reserved entry hierarchy.

Content-Type: -

Contact person: Cyrus Daboo

email: cyrus@daboo.name

#### [6.2.3.](#) /altsubject

To: iana@iana.org

Subject: IMAP Annotate Registration

Please register the following IMAP Annotate item:

☒ Entry            ☐ Attribute

Name: /altsubject

Description: Defined in IMAP ANNOTATE extension document.

Content-Type: text/plain; charset=utf-8

Contact person: Cyrus Daboo

email: cyrus@daboo.name

[6.2.4.](#) /<section-part>/comment

To: iana@iana.org

Subject: IMAP Annotate Registration

Please register the following IMAP Annotate item:

☒ Entry            ☐ Attribute

Name: /<section-part>/comment

Description: Defined in IMAP ANNOTATE extension document.

Content-Type: text/plain; charset=utf-8

Contact person: Cyrus Daboo

email: cyrus@daboo.name

[6.2.5.](#) /<section-part>/flags/seen

To: iana@iana.org

Subject: IMAP Annotate Registration

Please register the following IMAP Annotate item:



[X] Entry            [] Attribute

Name: /<section-part>/flags/seen

Description: Defined in IMAP ANNOTATE extension document.

Content-Type: text/plain; charset=utf-8

Contact person: Cyrus Daboo

email: cyrus@daboo.name

[6.2.6.](#) /<section-part>/flags/answered

To: iana@iana.org

Subject: IMAP Annotate Registration

Please register the following IMAP Annotate item:

[X] Entry            [] Attribute

Name: /<section-part>/flags/answered

Description: Defined in IMAP ANNOTATE extension document.

Content-Type: text/plain; charset=utf-8

Contact person: Cyrus Daboo

email: cyrus@daboo.name

#### [6.2.7.](#) /<section-part>/flags/flagged

To: iana@iana.org  
Subject: IMAP Annotate Registration

Please register the following IMAP Annotate item:

☒ Entry            ☐ Attribute

Name: /<section-part>/flags/flagged

Description: Defined in IMAP ANNOTATE extension document.

Content-Type: text/plain; charset=utf-8

Contact person: Cyrus Daboo

email: cyrus@daboo.name

#### [6.2.8.](#) /<section-part>/flags/forwarded

To: iana@iana.org  
Subject: IMAP Annotate Registration

Please register the following IMAP Annotate item:

☒ Entry            ☐ Attribute

Name: /<section-part>/flags/forwarded

Description: Defined in IMAP ANNOTATE extension document.

Content-Type: text/plain; charset=utf-8

Contact person: Cyrus Daboo

email: cyrus@daboo.name

### [6.3.](#) Attribute Registrations

The following templates specify the IANA registrations of annotation attributes specified in this document.

Internet-Draft

IMAP ANNOTATE Extension

November 2005

### [6.3.1.](#) value

To: iana@iana.org

Subject: IMAP Annotate Registration

Please register the following IMAP Annotate item:

☐ Entry            ☒ Attribute

Name: value

Description: Defined in IMAP ANNOTATE extension document.

Contact person: Cyrus Daboo

email: cyrus@daboo.name

### [6.3.2.](#) size

To: iana@iana.org

Subject: IMAP Annotate Registration

Please register the following IMAP Annotate item:

☐ Entry            ☒ Attribute

Name: size

Description: Defined in IMAP ANNOTATE extension document.

Contact person: Cyrus Daboo

email: cyrus@daboo.name

Internet-Draft

IMAP ANNOTATE Extension

November 2005

### [6.3.3.](#) content-language

To: iana@iana.org  
Subject: IMAP Annotate Registration

Please register the following IMAP Annotate item:

☐ Entry            ☒ Attribute

Name: content-language

Description: Defined in IMAP ANNOTATE extension document.

Contact person: Cyrus Daboo

email: cyrus@daboo.name

## [7.](#) Internationalization Considerations

Annotations may contain values that include text strings, and both searching and sorting are possible with annotations. Servers MUST follow standard IMAP text normalization, character set conversion and collation rules when such operations are carried out, as they would for other textual fields being searched or sorted on.

## [8.](#) Security Considerations

Annotations whose values are intended to remain private MUST be stored in ".priv" values, and not ".shared" values which may be accessible to other users.

Excluding the above issues the ANNOTATE extension does not raise any security considerations that are not present in the base IMAP protocol, and these issues are discussed in [[RFC3501](#)].

## [9.](#) References

### [9.1.](#) Normative References

[I-D.ietf-imapext-2086upd]  
Melnikov, A., "IMAP4 ACL extension",  
[draft-ietf-imapext-2086upd-08](#) (work in progress),  
June 2005.

[I-D.ietf-imapext-sort]

Daboo & Gellens

Expires May 25, 2006

[Page 32]

---

Internet-Draft

IMAP ANNOTATE Extension

November 2005

Crispin, M. and K. Murchison, "INTERNET MESSAGE ACCESS  
PROTOCOL - SORT AND THREAD EXTENSION",  
[draft-ietf-imapext-sort-17](#) (work in progress), May 2004.

[I-D.melnikov-imap-ext-abnf]  
Daboo, C. and A. Melnikov, "Collected extensions to IMAP4  
ABNF", [draft-melnikov-imap-ext-abnf-05](#) (work in progress),  
October 2005.

[RFC2086] Myers, J., "IMAP4 ACL extension", [RFC 2086](#), January 1997.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate  
Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.

[RFC2234] Crocker, D., Ed. and P. Overell, "Augmented BNF for Syntax  
Specifications: ABNF", [RFC 2234](#), November 1997.

[RFC2244] Newman, C. and J. Myers, "ACAP -- Application  
Configuration Access Protocol", [RFC 2244](#), November 1997.

[RFC3282] Alvestrand, H., "Content Language Headers", [RFC 3282](#),  
May 2002.

[RFC3501] Crispin, M., "INTERNET MESSAGE ACCESS PROTOCOL - VERSION  
4rev1", [RFC 3501](#), March 2003.

[RFC3502] Crispin, M., "Internet Message Access Protocol (IMAP) -  
MULTIAPPEND Extension", [RFC 3502](#), March 2003.

[RFC3629] Yergeau, F., "UTF-8, a transformation format of ISO 10646", STD 63, [RFC 3629](#), November 2003.

## [9.2.](#) Informative References

[I-D.ietf-imapext-condstore]  
Melnikov, A. and S. Hole, "IMAP Extension for Conditional STORE operation", [draft-ietf-imapext-condstore-06](#) (work in progress), October 2005.

## [Appendix A.](#) Acknowledgments

Many thanks to Chris Newman for his detailed comments on the first draft of this document, and to the participants at the ACAP working dinner in Pittsburgh. The participants of the IMAPext working group made significant contributions to this work.

Daboo & Gellens

Expires May 25, 2006

[Page 33]

---

Internet-Draft

IMAP ANNOTATE Extension

November 2005

### Authors' Addresses

Cyrus Daboo

Email: [cyrus@daboo.name](mailto:cyrus@daboo.name)

Randall Gellens  
QUALCOMM Incorporated  
5775 Morehouse Dr.  
San Diego, CA 92121-2779  
US

Email: [randy@qualcomm.com](mailto:randy@qualcomm.com)

#### Intellectual Property Statement

The IETF takes no position regarding the validity or scope of any Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; nor does it represent that it has made any independent effort to identify any such rights. Information on the procedures with respect to rights in RFC documents can be found in [BCP 78](#) and [BCP 79](#).

Copies of IPR disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this

specification can be obtained from the IETF on-line IPR repository at <http://www.ietf.org/ipr>.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement this standard. Please address the information to the IETF at [ietf-ipr@ietf.org](mailto:ietf-ipr@ietf.org).

#### Disclaimer of Validity

This document and the information contained herein are provided on an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

#### Copyright Statement

Copyright (C) The Internet Society (2005). This document is subject to the rights, licenses and restrictions contained in [BCP 78](#), and except as set forth therein, the authors retain all their rights.

#### Acknowledgment

Funding for the RFC Editor function is currently provided by the Internet Society.