

Internet Area WG  
Internet Draft  
Updates: [791](#), 1122, 2003  
Intended status: Proposed Standard  
Expires: November 2012

J. Touch  
USC/ISI  
May 30, 2012

**Updated Specification of the IPv4 ID Field  
draft-ietf-intarea-ipv4-id-update-05.txt**

Status of this Memo

This Internet-Draft is submitted to IETF in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

This document may contain material from IETF Documents or IETF Contributions published or made publicly available before November 10, 2008. The person(s) controlling the copyright in some of this material may not have granted the IETF Trust the right to allow modifications of such material outside the IETF Standards Process. Without obtaining an adequate license from the person(s) controlling the copyright in such materials, this document may not be modified outside the IETF Standards Process, and derivative works of it may not be created outside the IETF Standards Process, except to format it for publication as an RFC or to translate it into languages other than English.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/1id-abstracts.txt>

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>

This Internet-Draft will expire on November 30, 2012.

## Copyright Notice

Copyright (c) 2012 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Abstract

The IPv4 Identification (ID) field enables fragmentation and reassembly, and as currently specified is required to be unique within the maximum lifetime for all datagrams with a given source/destination/protocol tuple. If enforced, this uniqueness requirement would limit all connections to 6.4 Mbps. Because individual connections commonly exceed this speed, it is clear that existing systems violate the current specification. This document updates the specification of the IPv4 ID field in [RFC791](#), [RFC1122](#), and [RFC2003](#) to more closely reflect current practice and to more closely match IPv6 so that the field's value is defined only when a datagram is actually fragmented. It also discusses the impact of these changes on how datagrams are used.

## Table of Contents

<a href="#">1.</a>	<a href="#">Introduction.....</a>	<a href="#">3</a>
<a href="#">2.</a>	<a href="#">Conventions used in this document.....</a>	<a href="#">3</a>
<a href="#">3.</a>	<a href="#">The IPv4 ID Field.....</a>	<a href="#">4</a>
<a href="#">4.</a>	<a href="#">Uses of the IPv4 ID Field.....</a>	<a href="#">4</a>
<a href="#">5.</a>	<a href="#">Background on IPv4 ID Reassembly Issues.....</a>	<a href="#">5</a>
<a href="#">6.</a>	<a href="#">Updates to the IPv4 ID Specification.....</a>	<a href="#">6</a>
	<a href="#">6.1.</a> <a href="#">IPv4 ID Used Only for Fragmentation.....</a>	<a href="#">7</a>
	<a href="#">6.2.</a> <a href="#">Encourage Safe IPv4 ID Use.....</a>	<a href="#">8</a>
	<a href="#">6.3.</a> <a href="#">IPv4 ID Requirements That Persist.....</a>	<a href="#">8</a>
<a href="#">7.</a>	<a href="#">Impact on Datagram Use.....</a>	<a href="#">9</a>
<a href="#">8.</a>	<a href="#">Updates to Existing Standards.....</a>	<a href="#">9</a>
	<a href="#">8.1.</a> <a href="#">Updates to <a href="#">RFC 791</a>.....</a>	<a href="#">10</a>
	<a href="#">8.2.</a> <a href="#">Updates to <a href="#">RFC 1122</a>.....</a>	<a href="#">10</a>
	<a href="#">8.3.</a> <a href="#">Updates to <a href="#">RFC 2003</a>.....</a>	<a href="#">11</a>

Touch

Expires November 30, 2012

[Page 2]

<a href="#">9.</a>	<a href="#">Impact on Middleboxes.....</a>	<a href="#">11</a>
<a href="#">9.1.</a>	<a href="#">Rewriting Middleboxes.....</a>	<a href="#">12</a>
<a href="#">9.2.</a>	<a href="#">Filtering Middleboxes.....</a>	<a href="#">13</a>
<a href="#">10.</a>	<a href="#">Impact on Header Compression.....</a>	<a href="#">13</a>
<a href="#">11.</a>	<a href="#">Security Considerations.....</a>	<a href="#">13</a>
<a href="#">12.</a>	<a href="#">IANA Considerations.....</a>	<a href="#">14</a>
<a href="#">13.</a>	<a href="#">References.....</a>	<a href="#">14</a>
<a href="#">13.1.</a>	<a href="#">Normative References.....</a>	<a href="#">14</a>
<a href="#">13.2.</a>	<a href="#">Informative References.....</a>	<a href="#">14</a>
<a href="#">14.</a>	<a href="#">Acknowledgments.....</a>	<a href="#">16</a>

## [1.](#) Introduction

In IPv4, the Identification (ID) field is a 16-bit value that is unique for every datagram for a given source address, destination address, and protocol, such that it does not repeat within the Maximum Segment Lifetime (MSL) [[RFC791](#)][[RFC1122](#)]. As currently specified, all datagrams between a source and destination of a given protocol must have unique IPv4 ID values over a period of this MSL, which is typically interpreted as two minutes (120 seconds). This uniqueness is currently specified as for all datagrams, regardless of fragmentation settings.

Uniqueness of the IPv4 ID is commonly violated by high speed devices; if strictly enforced, it would limit the speed of a single protocol between two IP endpoints to 6.4 Mbps for typical MTUs of 1500 bytes [[RFC4963](#)]. It is common for a single connection to operate far in excess of these rates, which strongly indicates that the uniqueness of the IPv4 ID as specified is already moot.

This document updates the specification of the IPv4 ID field to more closely reflect current practice, and to include considerations taken into account during the specification of the similar field in IPv6.

## [2.](#) Conventions used in this document

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC-2119](#) [[RFC2119](#)].

In this document, the characters ">>" preceding an indented line(s) indicates a requirement using the key words listed above. This convention aids reviewers in quickly identifying or finding this document's explicit requirements.

Touch

Expires November 30, 2012

[Page 3]

### **3. The IPv4 ID Field**

IP supports datagram fragmentation, where large datagrams are split into smaller components to traverse links with limited maximum transmission units (MTUs). Fragments are indicated in different ways in IPv4 and IPv6:

- o In IPv4, fragments are indicated using four fields of the basic header: Identification (ID), Fragment Offset, a "Don't Fragment" flag (DF), and a "More Fragments" flag (MF) [[RFC791](#)]
- o In IPv6, fragments are indicated in an extension header that includes an ID, Fragment Offset, and M (more fragments) flag similar to their counterparts in IPv4 [[RFC2460](#)]

IPv4 and IPv6 fragmentation differs in a few important ways. IPv6 fragmentation occurs only at the source, so a DF bit is not needed to prevent downstream devices from initiating fragmentation (i.e., IPv6 always acts as if DF=1). The IPv6 fragment header is present only when a datagram has been fragmented, or when the source has received a "packet too big" ICMPv6 error message when the path cannot support the required minimum 1280-byte IPv6 MTU and is thus subject to translation [[RFC2460](#)][[RFC4443](#)]. The latter case is relevant only for IPv6 datagrams sent to IPv4 destinations to support subsequent fragmentation after translation to IPv4.

With the exception of these two cases, the ID field is not present for non-fragmented datagrams, and thus is meaningful only for datagrams that are already fragmented or datagrams intended to be fragmented as part of IPv4 translation. Finally, the IPv6 ID field is 32 bits, and required unique per source/destination address pair for IPv6, whereas for IPv4 it is only 16 bits and required unique per source/destination/protocol triple.

This document focuses on the IPv4 ID field issues, because in IPv6 the field is larger and present only in fragments.

### **4. Uses of the IPv4 ID Field**

The IPv4 ID field was originally intended for fragmentation and reassembly [[RFC791](#)]. Within a given source address, destination address, and protocol, fragments of an original datagram are matched based on their IPv4 ID. This requires that IDs are unique within the address/protocol triple when fragmentation is possible (e.g., DF=0) or when it has already occurred (e.g., frag\_offset>0 or MF=1).

Touch

Expires November 30, 2012

[Page 4]

The IPv4 ID field can be useful for other purposes. The field has been proposed as a way to detect and remove duplicate datagrams, e.g., at congested routers (noted in Sec. 3.2.1.5 of [[RFC1122](#)]) or in network accelerators. It can similarly be used at end hosts to reduce the impact of duplication on higher-layer protocols (e.g., additional processing in TCP, or the need for application-layer duplicate suppression in UDP).

The IPv4 ID field is also used in some debugging tools to correlate datagrams measured at various locations along a network path. This is already insufficient in IPv6 because unfragmented datagrams lack an ID, so these tools are already being updated to avoid such reliance on the ID field.

The ID clearly needs to be unique (within MSL, within the src/dst/protocol tuple) to support fragmentation and reassembly, but not all datagrams are fragmented or allow fragmentation. This document deprecates non-fragmentation uses, allowing the ID to be repeated (within MSL, within the src/dst/protocol tuple) in those cases.

## 5. Background on IPv4 ID Reassembly Issues

The following is a summary of issues with IPv4 fragment reassembly in high speed environments raised previously [[RFC4963](#)]. Readers are encouraged to consult [RFC 4963](#) for a more detailed discussion of these issues.

With the maximum IPv4 datagram size of 64KB, a 16-bit ID field that does not repeat within 120 seconds means that the aggregate of all TCP connections of a given protocol between two IP endpoints is limited to roughly 286 Mbps; at a more typical MTU of 1500 bytes, this speed drops to 6.4 Mbps [[RFC791](#)][[RFC1122](#)][[RFC4963](#)]. This limit currently applies for all IPv4 datagrams within a single protocol (i.e., the IPv4 protocol field) between two IP addresses, regardless of whether fragmentation is enabled or inhibited, and whether a datagram is fragmented or not.

IPv6, even at typical MTUs, is capable of 18.7 Tbps with fragmentation between two IP endpoints as an aggregate across all protocols, due to the larger 32-bit ID field (and the fact that the IPv6 next-header field, the equivalent of the IPv4 protocol field, is not considered in differentiating fragments). When fragmentation is not used the field is absent, and in that case IPv6 speeds are not limited by the ID field uniqueness.



Touch

Expires November 30, 2012

[Page 5]

Note also that 120 seconds is only an estimate on the maximum datagram lifetime. It is loosely based on half maximum value of the IP TTL field (255), measured in seconds, because the TTL was originally specified as decremented not only for each hop, but also for each second a datagram is held at a router (as implied in [\[RFC791\]](#), although this has long since become a hopcount only). Network delays are incurred in other ways, e.g., satellite links, which can add seconds of delay even though the TTL is not decremented by a corresponding amount. There is thus no enforcement mechanism to ensure that datagrams older than 120 seconds are discarded.

Wireless Internet devices are frequently connected at speeds over 54 Mbps, and wired links of 1 Gbps have been the default for several years. Although many end-to-end transport paths are congestion limited, these devices easily achieve 100+ Mbps application-layer throughput over LANs (e.g., disk-to-disk file transfer rates), and numerous throughput demonstrations with COTS systems over wide-area paths exhibit these speeds for over a decade. This strongly suggests that IPv4 ID uniqueness has been moot for a long time.

## 6. Updates to the IPv4 ID Specification

This document updates the specification of the IPv4 ID field in three distinct ways, as discussed in subsequent subsections:

- o Use the IPv4 ID field only for fragmentation
- o Avoiding a performance impact when the IPv4 ID field is used
- o Encourage safe operation when the IPv4 ID field is used

There are two kinds of datagrams used in the following discussion, named as follows:

- o Atomic datagrams are datagrams not yet fragmented and for which further fragmentation has been inhibited.
- o Non-atomic datagrams are datagrams which either have already been fragmented or for which fragmentation remains possible.

This same definition can be expressed in pseudo code as using common logical operators (equals is ==, logical 'and' is &&, logical 'or' is ||, greater than is >, and parenthesis function typically) as:

- o Atomic datagrams: `(DF==1)&&(MF==0)&&(frag_offset==0)`
- o Non-atomic datagrams: `(DF==0)||((MF==1)||((frag_offset>0))`

Touch

Expires November 30, 2012

[Page 6]

The test for non-atomic datagrams is the logical negative of the test for atomic datagrams, thus all possibilities are considered.

### **6.1. IPv4 ID Used Only for Fragmentation**

Although [RFC1122](#) suggests the IPv4 ID field has other uses, including datagram de-duplication, this document asserts that this field's value is defined only for fragmentation and reassembly:

>> IPv4 ID field MUST NOT be used for purposes other than fragmentation and reassembly.

Datagram de-duplication can be accomplished using hash-based duplicate detection for cases where the ID field is absent.

In atomic datagrams, the IPv4 ID field has no meaning, and thus can be set to an arbitrary value, i.e., the requirement for non-repeating IDs within the address/protocol triple is no longer required for atomic datagrams:

>> Originating sources MAY set the IPv4 ID field of atomic datagrams to any value.

Second, all network nodes, whether at intermediate routers, destination hosts, or other devices (e.g., NATs and other address sharing mechanisms, firewalls, tunnel egresses), cannot rely on the field:

>> All devices that examine IPv4 headers MUST ignore the IPv4 ID field of atomic datagrams.

The IPv4 ID field is thus meaningful only for non-atomic datagrams - datagrams that have either already been fragmented, or those for which fragmentation remains permitted. Atomic datagrams are detected by their DF, MF, and fragmentation offset fields as explained in [Section 6](#), because such a test is completely backward compatible; this document thus does not reserve any IPv4 ID values, including 0, as distinguished.

Deprecating the use of the IPv4 ID field for non-reassembly uses should have little - if any - impact. IPv4 IDs are already frequently repeated, e.g., over even moderately fast connections. Duplicate suppression was only suggested [[RFC1122](#)], and no impacts of IPv4 ID reuse have been noted. Routers are not required to issue ICMPs on any particular timescale, and so IPv4 ID repetition should not have been used for validation, and again repetition occurs and probably could have been noticed [[RFC1812](#)]. ICMP relaying at tunnel ingresses is

Touch

Expires November 30, 2012

[Page 7]

specified to use soft state rather than a datagram cache, and should have been noted if the latter for similar reasons [[RFC2003](#)].

## 6.2. Encourage Safe IPv4 ID Use

This document makes further changes to the specification of the IPv4 ID field and its use to encourage its safe use as corollary requirements changes as follows.

[RFC 1122](#) discusses that if TCP retransmits a segment it may be possible to reuse the IPv4 ID (see [Section 8.2](#)). This can make it difficult for a source to avoid IPv4 ID repetition for received fragments. [RFC 1122](#) concludes that this behavior "is not useful"; this document formalizes that conclusion as follows:

>> The IPv4 ID of non-atomic datagrams MUST NOT be reused when sending a copy of an earlier non-atomic datagram.

[RFC 1122](#) also suggests that fragments can overlap [[RFC1122](#)]. Such overlap can occur if successive retransmissions are fragmented in different ways but with the same reassembly IPv4 ID. This overlap is noted as the result of reusing IPv4 IDs when retransmitting datagrams, which this document deprecates. However, it is also the result of in-network datagram duplication, which can still occur. As a result this document does not change the need to support overlapping fragments.

## 6.3. IPv4 ID Requirements That Persist

This document does not relax the IPv4 ID field uniqueness requirements of [[RFC791](#)] for non-atomic datagrams, i.e.:

>> Sources emitting non-atomic datagrams MUST NOT repeat IPv4 ID values within one MSL for a given source address/destination address/protocol triple.

Such sources include originating hosts, tunnel ingresses, and NATs (including other address sharing mechanisms) (see [Section 9](#)).

This document does not relax the requirement that all network devices honor the DF bit, i.e.:

>> IPv4 datagrams whose DF=1 MUST NOT be fragmented.

>> IPv4 datagram transit devices MUST NOT clear the DF bit.

Touch

Expires November 30, 2012

[Page 8]

In specific, DF=1 prevents fragmenting atomic datagrams. DF=1 also prevents further fragmenting received fragments. In-network fragmentation is permitted only when DF=0; this document does not change that requirement.

## **7. Impact on Datagram Use**

The following is a summary of the recommendations that are the result of the previous changes to the IPv4 ID field specification.

Because atomic datagrams can use arbitrary IPv4 ID values, the ID field no longer imposes a performance impact in those cases. However, the performance impact remains for non-atomic datagrams. As a result:

>> Sources of non-atomic IPv4 datagrams MUST rate-limit their output to comply with the ID uniqueness requirements.

Such sources include, in particular, DNS over UDP [[RFC2671](#)].

Because there is no strict definition of the MSL, reassembly hazards exist regardless of the IPv4 ID reuse interval or the reassembly timeout. As a result:

>> Higher layer protocols SHOULD verify the integrity of IPv4 datagrams, e.g., using a checksum or hash that can detect reassembly errors (the UDP checksum is weak in this regard, but better than nothing), as in SEAL [[RFC5320](#)].

Additional integrity checks can be employed using tunnels, as in SEAL, IPsec, or SCTP [[RFC4301](#)][[RFC4960](#)][[RFC5320](#)]. Such checks can avoid the reassembly hazards that can occur when using UDP and TCP checksums [[RFC4963](#)], or when using partial checksums as in UDP-Lite [[RFC3828](#)]. Because such integrity checks can avoid the impact of reassembly errors:

>> Sources of non-atomic IPv4 datagrams using strong integrity checks MAY reuse the ID within MSL values smaller than is typical.

Note, however, that such frequent reuse can still result in corrupted reassembly and poor throughput, although it would not propagate reassembly errors to higher layer protocols.

## **8. Updates to Existing Standards**

The following sections address the specific changes to existing protocols indicated by this document.



Touch

Expires November 30, 2012

[Page 9]

### **8.1. Updates to [RFC 791](#)**

[RFC 791](#) states that:

The originating protocol module of an internet datagram sets the identification field to a value that must be unique for that source-destination pair and protocol for the time the datagram will be active in the internet system.

And later that:

Thus, the sender must choose the Identifier to be unique for this source, destination pair and protocol for the time the datagram (or any fragment of it) could be alive in the internet.

It seems then that a sending protocol module needs to keep a table of Identifiers, one entry for each destination it has communicated with in the last maximum datagram lifetime for the internet.

However, since the Identifier field allows 65,536 different values, some host may be able to simply use unique identifiers independent of destination.

It is appropriate for some higher level protocols to choose the identifier. For example, TCP protocol modules may retransmit an identical TCP segment, and the probability for correct reception would be enhanced if the retransmission carried the same identifier as the original transmission since fragments of either datagram could be used to construct a correct TCP segment.

This document changes [RFC 791](#) as follows:

- o IPv4 ID uniqueness applies to only non-atomic datagrams.
- o Retransmitted non-atomic IPv4 datagrams are no longer permitted to reuse the ID value.

### **8.2. Updates to [RFC 1122](#)**

[RFC 1122](#) states that:

#### 3.2.1.5 Identification: [RFC-791 Section 3.2](#)

When sending an identical copy of an earlier datagram, a host MAY optionally retain the same Identification field in the copy.

Touch

Expires November 30, 2012

[Page 10]

**DISCUSSION:**

Some Internet protocol experts have maintained that when a host sends an identical copy of an earlier datagram, the new copy should contain the same Identification value as the original. There are two suggested advantages: (1) if the datagrams are fragmented and some of the fragments are lost, the receiver may be able to reconstruct a complete datagram from fragments of the original and the copies; (2) a congested gateway might use the IP Identification field (and Fragment Offset) to discard duplicate datagrams from the queue.

This document changes [RFC 1122](#) as follows:

- o The IPv4 ID field is no longer permitted to be used for duplicate detection. This applies to both atomic and non-atomic datagrams.
- o Retransmitted non-atomic IPv4 datagrams are no longer permitted to reuse the ID value.

**8.3. Updates to [RFC 2003](#)**

This document updates how IPv4-in-IPv4 tunnels create IPv4 ID values for the IPv4 outer header [[RFC2003](#)], but only in the same way as for any other IPv4 datagram source. In specific, [RFC 2003](#) states the following, where ref. [10] is [RFC 791](#):

Identification, Flags, Fragment Offset

These three fields are set as specified in [10]...

This document changes [RFC 2003](#) as follows:

- o The IPv4 ID field is set as permitted by this document.

**9. Impact on Middleboxes**

Middleboxes include rewriting devices that include network address translators (NATs), address/port translators (NAPT), and other address sharing mechanisms (ASMs). They also include devices that inspect and filter datagrams that are not routers, such as accelerators and firewalls.

Touch

Expires November 30, 2012

[Page 11]

### **9.1. Rewriting Middleboxes**

NATs and NAPT rewrite IP fields, and tunnel ingresses (using IPv4 encapsulation) copy and modify some IPv4 fields, so all are considered sources, as do any devices that rewrite any portion of the source address, destination address, protocol, and ID tuple for any datagrams [[RFC3022](#)]. This is also true for other ASMs, including 4rd, IVI, and others in the "A+P" (address plus port) family [[Bo11](#)] [[De11](#)] [[RFC6219](#)]. It is equally true for any other datagram rewriting mechanism. As a result, they are subject to all the requirements of any source, as has been noted.

NATs/ASMs/rewriters present a particularly challenging situation for fragmentation. Because they overwrite portions of the reassembly tuple in both directions, they can destroy tuple uniqueness and result in a reassembly hazard. Whenever IPv4 source address, destination address, or protocol fields are modified, a NAT/ASM/rewriter needs to ensure that the ID field is generated appropriately, rather than simply copied from the incoming datagram. In specific:

>> Address sharing or rewriting devices MUST ensure that the IPv4 ID field of datagrams whose address or protocol are translated comply with these requirements as if the datagram were sourced by that device.

This compliance means that the IPv4 ID field of non-atomic datagrams translated at a NAT/ASM/rewriter needs to obey the uniqueness requirements of any IPv4 datagram source. Unfortunately, fragments already violate that requirement, as they repeat an IPv4 ID within the MSL for a given source address, destination address, and protocol triple.

Such problems with transmitting fragments through NATs/ASMs/rewriters are already known; translation is based on the transport port number, which is present in only the first fragment anyway [[RFC3022](#)]. This document underscores the point that not only is reassembly (and possibly subsequent fragmentation) required for translation, it can be used to avoid issues with IPv4 ID uniqueness.

Note that NATs/ASMs already need to exercise special care when emitting datagrams on their public side, because merging datagrams from many sources onto a single outgoing source address can result in IPv4 ID collisions. This situation precedes this document, and is not affected by it. It is exacerbated in large-scale, so-called "carrier grade" NATs [[Pe11](#)].

Touch

Expires November 30, 2012

[Page 12]

Tunnel ingresses act as sources for the outermost header, but tunnels act as routers for the inner headers (i.e., the datagram as arriving at the tunnel ingress). Ingresses can always fragment as originating sources of the outer header, because they control the uniqueness of that IPv4 ID field and the value of DF on the outer header independent of those values on the inner (arriving datagram) header.

## **9.2. Filtering Middleboxes**

Middleboxes also include devices that filter datagrams, including network accelerators and firewalls. Some such devices reportedly feature datagram de-duplication, which relies on IP ID uniqueness to identify duplicates. Such accelerators already risk dropping non-duplicate datagrams because of early ID reuse, and, as a result of earlier requirements:

>> Datagram de-duplication mechanisms MUST ignore the ID values on atomic datagrams.

## **10. Impact on Header Compression**

Header compression algorithms already accommodate various ways in which the IPv4 ID changes between sequential datagrams [[RFC1144](#)] [[RFC2508](#)] [[RFC3545](#)] [[RFC5225](#)]. Such algorithms currently assume that the IPv4 ID is preserved end-to-end. Some algorithms already allow assuming the ID does not change (e.g., ROHC [[RFC5225](#)]), where others include non-changing IDs via zero deltas (e.g., ECRTTP [[RFC3545](#)]).

When compression assumes a changing ID as a default, having a non-changing ID can make compression less efficient. Such non-changing IDs have been described in various RFCs (e.g., footnote 21 of [[RFC1144](#) and cRTP [[RFC2508](#)]). When compression can assume a non-changing IPv4 ID - as with ROHC and ECRTTP - efficiency can be increased.

## **11. Security Considerations**

When the IPv4 ID is ignored on receipt (e.g., for atomic datagrams), its value becomes unconstrained; that field then can more easily be used as a covert channel. For some atomic datagrams - notably those not protected by IPsec Authentication Header (AH) [[RFC4302](#)] - it is now possible, and may be desirable, to rewrite the IPv4 ID field to avoid its use as such a channel.

The IPv4 ID also now adds much less entropy of the header of a datagram. The IPv4 ID had previously been unique (for a given source/address pair, and protocol field) within one MSL, although



Touch

Expires November 30, 2012

[Page 13]

this requirement was not enforced and clearly is typically ignored. The IPv4 ID of atomic datagrams is not required unique, and so contributes no entropy to the header.

The deprecation of the IPv4 ID field's uniqueness for atomic datagrams can defeat the ability to count devices behind a NAT/ASM/rewriter [Be02]. This is not intended as a security feature, however.

## **12. IANA Considerations**

There are no IANA considerations in this document.

The RFC Editor should remove this section prior to publication

## **13. References**

### **13.1. Normative References**

- [RFC791] Postel, J., "Internet Protocol", [RFC 791](#) / STD 5, September 1981.
- [RFC1122] Braden, R., Ed., "Requirements for Internet Hosts - Communication Layers", [RFC 1122](#) / STD 3, October 1989.
- [RFC1812] Baker, F. (Ed.), "Requirements for IP Version 4 Routers", [RFC 1812](#) / STD 4, Jun. 1995.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [RFC 2119](#) / [BCP 14](#), March 1997.
- [RFC2003] Perkins, C., "IP Encapsulation within IP", [RFC 2003](#), October 1996.

### **13.2. Informative References**

- [Be02] Bellovin, S., "A Technique for Counting NATted Hosts", Internet Measurement Conference, Proceedings of the 2nd ACM SIGCOMM Workshop on Internet Measurement, Nov. 2002.
- [Bo11] Boucadair, M., J. Touch, P. Levis, R. Penno, "Analysis of Solution Candidates to Reveal a Host Identifier in Shared Address Deployments", (work in progress), [draft-boucadair-intarea-nat-reveal-analysis](#), Sept. 2011.

- [De11] Despres, R. (Ed.), S. Matsushima, T. Murakami, O. Troan, "IPv4 Residual Deployment across IPv6-Service networks (4rd)", (work in progress), [draft-despres-intarea-4rd](#), Mar. 2011.
- [Pe11] Perreault, S., (Ed.), I. Yamagata, S. Miyakawa, A. Nakagawa, H. Ashida, "Common requirements of IP address sharing schemes", (work in progress), [draft-ietf-behave-lsn-requirements](#), Mar. 2011.
- [RFC1144] Jacobson, V., "Compressing TCP/IP Headers", [RFC 1144](#), Feb. 1990.
- [RFC2460] Deering, S., R. Hinden, "Internet Protocol, Version 6 (IPv6) Specification", [RFC 2460](#), Dec. 1998.
- [RFC2508] Casner, S., V. Jacobson. "Compressing IP/UDP/RTP Headers for Low-Speed Serial Links", [RFC 2508](#), Feb. 1999.
- [RFC2671] Vixie, P., "Extension Mechanisms for DNS (EDNS0)", [RFC 2671](#), Aug. 1999.
- [RFC3022] Srisuresh, P. and K. Egevang, "Traditional IP Network Address Translator (Traditional NAT)", [RFC 3022](#), Jan. 2001.
- [RFC3545] Koren, T., S. Casner, J. Geevarghese, B. Thompson, P. Ruddy, "Enhanced Compressed RTP (CRTP) for Links with High Delay, Packet Loss and Reordering", [RFC 3545](#), Jul. 2003.
- [RFC3828] Larzon, L-A., M. Degermark, S. Pink, L-E. Jonsson, Ed., G. Fairhurst, Ed., "The Lightweight User Datagram Protocol (UDP-Lite)", [RFC 3828](#), Jul. 2004.
- [RFC4301] Kent, S., K. Seo, "Security Architecture for the Internet Protocol", [RFC 4301](#), Dec. 2005.
- [RFC4302] Kent, S., "IP Authentication Header", [RFC 4302](#), Dec. 2005.
- [RFC4443] Conta, A., S. Deering, M. Gupta (Ed.), "Internet Control Message Protocol (ICMPv6) for the Internet Protocol Version 6 (IPv6) Specification", [RFC 4443](#), March. 2006.
- [RFC4960] Stewart, R. (Ed.), "Stream Control Transmission Protocol", [RFC 4960](#), Sep. 2007.
- [RFC4963] Heffner, J., M. Mathis, B. Chandler, "IPv4 Reassembly Errors at High Data Rates", [RFC 4963](#), Jul. 2007.

Touch

Expires November 30, 2012

[Page 15]

- [RFC5225] Pelletier, G., K. Sandlund, "RObust Header Compression Version 2 (ROHCv2): Profiles for RTP, UDP, IP, ESP and UDP-Lite", [RFC 5225](#), Apr. 2008.
- [RFC5320] Templin, F., Ed., "The Subnetwork Encapsulation and Adaptation Layer (SEAL)", [RFC 5320](#), Feb. 2010.
- [RFC6219] Li, X., C. Bao, M. Chen, H. Zhang, J. Wu, "The China Education and Research Network (CERNET) IVI Translation Design and Deployment for the IPv4/IPv6 Coexistence and Transition", [RFC 6219](#), May 2011.

#### **14. Acknowledgments**

This document was inspired by of numerous discussions among the authors, Jari Arkko, Lars Eggert, Dino Farinacci, and Fred Templin, as well as members participating in the Internet Area Working Group. Detailed feedback was provided by Gorry Fairhurst, Brian Haberman, Ted Hardie, Mike Heard, Erik Nordmark, Carlos Pignataro, and Dan Wing. This document originated as an Independent Stream draft co-authored by Matt Mathis, PSC, and his contributions are greatly appreciated.

This document was prepared using 2-Word-v2.0.template.dot.

#### Author's Address

Joe Touch  
USC/ISI  
4676 Admiralty Way  
Marina del Rey, CA 90292-6695  
U.S.A.

Phone: +1 (310) 448-9151  
Email: touch@isi.edu