

Internet-Draft
<draft-ietf-ip1394-dhcp-03.txt>
Expires: August, 2000

K. Fujisawa
Sony Corporation
February 2000

DHCP for IEEE 1394

Status of this memo

This document is an Internet-Draft and is in full conformance with all provisions of [Section 10 of RFC2026](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/1id-abstracts.txt>

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

Copyright Notice

Copyright (C) The Internet Society (2000). All Rights Reserved.

Abstract

IEEE Std 1394-1995 is a standard for a High Performance Serial Bus. Since 1394 uses a different link-layer addressing method than conventional IEEE802/Ethernet, the usage of some fields must be clarified to achieve interoperability. This memo describes the 1394 specific usage of some fields of DHCP messages.

1. Introduction

IEEE Std 1394-1995 is a standard for a High Performance Serial Bus. IETF IP1394 Working Group specified the method to carry IPv4 datagrams and 1394 ARP packets over an IEEE1394 network [[RFC2734](#)].

The Dynamic Host Configuration Protocol (DHCP) [[RFC2131](#)] provides a framework for passing configuration information to hosts on a TCP/IP network.

Since 1394 uses a different link-layer addressing method than conventional IEEE802/Ethernet, the usage of some fields must be clarified to achieve interoperability. This memo describes the 1394 specific usage of some fields of DHCP. See [[RFC2131](#)] for the mechanism of DHCP and the explanations of each field.

This document is a product of the IP1394 working group within the Internet Engineering Task Force. Comments are solicited and should be addressed to the working group's mailing list at ip1394@mailbag.intel.com and/or the author.

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)].

2. Issues related to 1394 link address

With conventional link-layer protocols, such as an Ethernet, the 'chaddr' (client hardware address) field may be used to return a reply message from a DHCP server (or relay-agent) to a client. Since a 1394 link address (node_ID) is transient and will not be consistent across the 1394 bridge, we have chosen not to put it in the 'chaddr' field. A DHCP client should request that the server sends a broadcast reply by setting the BROADCAST flag when 1394 ARP is not possible yet.

Note: In general, the use of a broadcast reply is discouraged, but we consider the impact in a 1394 network as a non issue.

3. 1394 specific usage of DHCP message fields

Following rules should be used when a DHCP client is connected to an IEEE1394 network.

'htype' (hardware address type) MUST be 24 [[ARPPARAM](#)].

'hlen' (hardware address length) MUST be 0.

The 'chaddr' (client hardware address) field is reserved. The sender MUST set this field to zero, and the recipient and the relay agent MUST ignore its value on receipt.

A DHCP client on 1394 SHOULD set a BROADCAST flag in DHCPDISCOVER and DHCPREQUEST messages (and set 'ciaddr' to zero) to ensure that the server (or the relay agent) broadcasts its reply to the client.

Note: As described in [[RFC2131](#)], 'ciaddr' MUST be filled in with client's IP address during BOUND, RENEWING or REBINDING state, therefore, the BROADCAST flag MUST NOT be set. In these cases, the DHCP server unicasts DHCPACK message to the address in 'ciaddr'. The link address will be resolved by 1394 ARP.

'client identifier' option MUST be used in DHCP messages from the client to the server due to the lack of the 'chaddr'. 'client identifier' option may consist of any data. Because every IP over 1394 node has an EUI-64 (node unique ID) [[EUI64](#)], the EUI-64 makes an obvious 'client identifier'. 1394 clients SHOULD include an EUI-64 identifier in the 'client identifier' option. The type value for the EUI-64 is 27 [[ARPPARAM](#)], and the format is illustrated as follows.

Code	Len	Type	Client-Identifier
61	9	27	EUI-64 (node unique ID)

Note that the use of other 'client identifier' type, such as a fully qualified domain name (FQDN), is not precluded by this memo.

For more details, see "9.14. Client-identifier" in [[RFC2132](#)].

4. Security Considerations

DHCP currently provides no authentication or security mechanisms. Potential exposures to attack are discussed in [section 7](#) of the DHCP protocol specification [[RFC2131](#)].

A malicious client can falsify its EUI-64 identifier, thus masquerading as another client.

Acknowledgments

The author appreciate the members of the Dynamic Host Configuration working group for their review and valuable comments.

References

- [RFC2734] P. Johansson, "IPv4 over IEEE 1394",
[RFC2734](#), December 1999.
- [RFC2119] S. Bradner, "Key words for use in RFCs to Indicate
Requirement Levels", [RFC2119](#), March 1997.
- [RFC2131] R. Droms, "Dynamic Host Configuration Protocol", [RFC2131](#),
March 1997.
- [RFC2132] S. Alexander, R. Droms, "DHCP Options and BOOTP Vendor
Extensions", [RFC2132](#), March 1997.
- [EUI64] <http://standards.ieee.org/regauth/oui/tutorials/EUI64.html>
- [ARPPARAM] <http://www.isi.edu/in-notes/iana/assignments/arp-parameters>

Author's address

Kenji Fujisawa
Sony Corporation
6-7-35, Kitashinagawa,
Shinagawa-ku, Tokyo, 141-0001 Japan
Phone: +81-3-5448-8507
E-mail: fujisawa@sm.sony.co.jp

Full Copyright Statement

Copyright (C) The Internet Society (2000). All Rights Reserved.

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this paragraph are included on all such copies and derivative works. However, this document itself may not be modified in any way, such as by removing the copyright notice or references to the Internet Society or other Internet organizations, except as needed for the purpose of developing Internet standards in which case the procedures for copyrights defined in the Internet Standards process must be followed, or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by the Internet Society or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

----- End of Forwarded Message