

IPFIX Working Group
Internet-Draft
Intended status: Standards Track
Expires: August 30, 2012

B. Trammell
ETH Zurich
A. Wagner
Consecom AG
B. Claise
Cisco Systems, Inc.
February 27, 2012

**Flow Aggregation for the IP Flow Information Export (IPFIX) Protocol
draft-ietf-ipfix-a9n-02.txt**

Abstract

This document describes the export of aggregated Flow information using IPFIX. An Aggregated Flow is essentially an IPFIX Flow representing packets from multiple Original Flows sharing some set of common properties. The document describes Aggregated Flow export within the framework of IPFIX Mediators and defines an interoperable, implementation-independent method for Aggregated Flow export.

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on August 30, 2012.

Copyright Notice

Copyright (c) 2012 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect

to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	4
1.1.	IPFIX Protocol Overview	5
1.2.	IPFIX Documents Overview	5
2.	Terminology	6
3.	Use Cases for IPFIX Aggregation	7
4.	Architecture for Flow Aggregation	8
4.1.	Aggregation within the IPFIX Architecture	8
4.2.	Intermediate Aggregation Process Architecture	12
4.2.1.	Correlation and Normalization	14
5.	IP Flow Aggregation Operations	15
5.1.	Temporal Aggregation through Interval Distribution	15
5.1.1.	Distributing Values Across Intervals	16
5.1.2.	Time Composition	18
5.2.	Spatial Aggregation of Flow Keys	19
5.2.1.	Counting Original Flows	21
5.2.2.	Counting Distinct Key Values	22
5.3.	Spatial Aggregation of Non-Key Fields	22
5.3.1.	Counter Statistics	22
5.3.2.	Derivation of New Values from Flow Keys and non-Key fields	22
5.4.	Aggregation Combination	23
6.	Additional Considerations and Special Cases in Flow Aggregation	24
6.1.	Exact versus Approximate Counting during Aggregation	24
6.2.	Delay and Loss introduced by the IAP	24
6.3.	Considerations for Aggregation of Sampled Flows	24
6.4.	Considerations for Aggregation of Heterogeneous Flows	24
7.	Export of Aggregated IP Flows using IPFIX	25
7.1.	Time Interval Export	25
7.2.	Flow Count Export	26
7.2.1.	originalFlowsPresent	26
7.2.2.	originalFlowsInitiated	26
7.2.3.	originalFlowsCompleted	26
7.2.4.	deltaFlowCount	26
7.3.	Distinct Host Export	27
7.3.1.	distinctCountOfSourceIPAddress	27
7.3.2.	distinctCountOfDestinationIPAddress	27
7.3.3.	distinctCountOfSourceIPv4Address	27
7.3.4.	distinctCountOfDestinationIPv4Address	28
7.3.5.	distinctCountOfSourceIPv6Address	28

7.3.6.	distinctCountOfDestinationIPv6Address	28
7.4.	Aggregate Counter Distribution Export	28
7.4.1.	Aggregate Counter Distribution Options Template	29
7.4.2.	valueDistributionMethod Information Element	29
8.	Examples	31
8.1.	Traffic Time-Series per Source	32
8.2.	Core Traffic Matrix	36
8.3.	Distinct Source Count per Destination Endpoint	40
8.4.	Traffic Time-Series per Source with Counter Distribution	42
9.	Security Considerations	44
10.	IANA Considerations	44
11.	Acknowledgments	45
12.	References	45
12.1.	Normative References	45
12.2.	Informative References	45
	Authors' Addresses	47

1. Introduction

The assembly of packet data into Flows serves a variety of different purposes, as noted in the requirements [RFC3917] and applicability statement [RFC5472] for the IP Flow Information Export (IPFIX) protocol [I-D.ietf-ipfix-protocol-rfc5101bis]. Aggregation beyond the flow level, into records representing multiple Flows, is a common analysis and data reduction technique as well, with applicability to large-scale network data analysis, archiving, and inter-organization exchange. This applicability in large-scale situations, in particular, led to the inclusion of aggregation as part of the IPFIX Mediators Problem Statement [RFC5982], and the definition of an Intermediate Aggregation Process in the Mediator framework [RFC6183].

Aggregation is part of a wide variety of applications, including traffic matrix calculation, generation of time series data for visualizations or anomaly detection, or measurement data reduction. Depending on the keys used for aggregation, it may additionally have an anonymizing affect on the data: for example, aggregation operations which eliminate IP addresses make it impossible to later identify nodes using those addresses.

Aggregation as defined and described in this document covers the applications defined in [RFC5982], including 5.1 "Adjusting Flow Granularity", 5.4 "Time Composition", and 5.5 "Spatial Composition". However, this document specifies a more flexible architecture for an Intermediate Aggregation Process than that envisioned by the original Mediator work, in [Section 4.2](#). Instead of a focus on these specific limited use cases, the Intermediate Aggregation Process is specified to cover any activity commonly described as "flow aggregation".

An Intermediate Aggregation Process may be applied to data collected from multiple Observation Points, as aggregation is natural to apply for data reduction when concentrating measurement data. This document specifically does not address the protocol issues that arise when combining IPFIX data from multiple Observation Points and exporting from a single Mediator, as these issues are general to IPFIX Mediation; they are therefore treated in detail in the Mediator Protocol [I-D.ietf-ipfix-mediation-protocol] document.

Since Aggregated Flows as defined in the following section are essentially Flows, the IPFIX protocol [I-D.ietf-ipfix-protocol-rfc5101bis] can be used to export, and the IPFIX File Format [RFC5655] can be used to store, aggregated data "as-is"; there are no changes necessary to the protocol. This document provides a common basis for the application of IPFIX to the handling of aggregated data, through a detailed terminology, Intermediate Aggregation Process architecture, and methods for

Original Flow counting and counter distribution across intervals.

1.1. IPFIX Protocol Overview

In the IPFIX protocol, { type, length, value } tuples are expressed in templates containing { type, length } pairs, specifying which { value } fields are present in data records conforming to the Template, giving great flexibility as to what data is transmitted. Since Templates are sent very infrequently compared with Data Records, this results in significant bandwidth savings. Various different data formats may be transmitted simply by sending new Templates specifying the { type, length } pairs for the new data format. See [[I-D.ietf-ipfix-protocol-rfc5101bis](#)] for more information.

The IPFIX Information Element Registry [[iana-ipfix-assignments](#)] defines a large number of standard Information Elements which provide the necessary { type } information for Templates. The use of standard elements enables interoperability among different vendors' implementations. Additionally, non-standard enterprise-specific elements may be defined for private use.

1.2. IPFIX Documents Overview

"Specification of the IPFIX Protocol for the Exchange of IP Traffic Flow Information" [[I-D.ietf-ipfix-protocol-rfc5101bis](#)] and its associated documents define the IPFIX Protocol, which provides network engineers and administrators with access to IP traffic flow information.

"Architecture for IP Flow Information Export" [[RFC5470](#)] defines the architecture for the export of measured IP flow information out of an IPFIX Exporting Process to an IPFIX Collecting Process, and the basic terminology used to describe the elements of this architecture, per the requirements defined in "Requirements for IP Flow Information Export" [[RFC3917](#)]. The IPFIX Protocol document [[I-D.ietf-ipfix-protocol-rfc5101bis](#)] then covers the details of the method for transporting IPFIX Data Records and Templates via a congestion-aware transport protocol from an IPFIX Exporting Process to an IPFIX Collecting Process.

This document specifies an Intermediate Process which may be applied at an IPFIX Mediator. "IP Flow Information Export (IPFIX) Mediation: Problem Statement" [[RFC5982](#)] introduces the concept of IPFIX Mediators, and defines the use cases for which they were designed; "IP Flow Information Export (IPFIX) Mediation: Framework" [[RFC6183](#)] then provides an architectural framework for Mediators. Protocol-level issues (e.g., template and observation domain handling across

Mediators) are covered by "Specification of the Protocol for IPFIX Mediation" [[I-D.ietf-ipfix-mediation-protocol](#)].

2. Terminology

Terms used in this document that are defined in the Terminology section of the IPFIX Protocol [[I-D.ietf-ipfix-protocol-rfc5101bis](#)] document are to be interpreted as defined there.

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

In addition, this document defines the following terms

Aggregated Flow: A Flow, as defined by [[I-D.ietf-ipfix-protocol-rfc5101bis](#)], derived from a set of zero or more original Flows within a defined Aggregation Interval. The two primary differences between a Flow and an Aggregated Flow in the general case are (1) that the time interval (i.e., the two-tuple of start and end times) of a Flow is derived from information about the timing of the packets comprising the Flow, while the time interval of an Aggregated Flow are externally imposed; and (2) that an Aggregated Flow may represent zero packets (i.e., an assertion that no packets were seen for a given Flow Key in a given time interval). Note that an Aggregated Flow is defined in the context of an Intermediate Aggregation Process only. Once an Aggregated Flow is exported, it is essentially a Flow as in [[I-D.ietf-ipfix-protocol-rfc5101bis](#)] and can be treated as such.

Intermediate Aggregation Process: an Intermediate Process as in [[RFC6183](#)] that aggregates records, based upon a set of Flow Keys or functions applied to fields from the record.

Aggregation Interval: A time interval imposed upon an Aggregated Flow. Intermediate Aggregation Processes may use a regular Aggregation Interval (e.g. "every five minutes", "every calendar month"), though regularity is not necessary. Aggregation intervals may also be derived from the time intervals of the Original Flows being aggregated.

Partially Aggregated Flow: A Flow during processing within an Intermediate Aggregation Process; refers to an intermediate data structure during aggregation within the Intermediate Aggregation Process architecture detailed in [Section 4.2](#).

Original Flow: A Flow given as input to an Intermediate Aggregation Process in order to generate Aggregated Flows.

Contributing Flow: An Original Flow that is partially or completely represented within an Aggregated Flow. Each Contributing Flow is made up of zero or more Contributing Flows, and an Original Flow may contribute to zero or more Aggregated Flows.

Original Exporter: When the Intermediate Aggregation Process is hosted in an IPFIX Mediator, the Original Exporter is the Exporter from which the Original Flows are received.

The terminology presented herein improves the precision of, but does not supersede or contradict the terms related to mediation and aggregation defined in the problem statement [[RFC5982](#)] and the framework [[RFC6183](#)] documents. Within this document, the terminology defined in this section is to be considered normative.

3. Use Cases for IPFIX Aggregation

Aggregation, as a common data reduction method used in traffic data analysis, has many applications. When used with a regular Aggregation Interval, it generates time series data from a collection of Flows with discrete intervals. This time series data is itself useful for a wide variety of analysis tasks, such as generating input for network anomaly detection systems, or driving visualizations of volume per time for traffic with specific characteristics. As a second example, traffic matrix calculation from flow data is inherently an aggregation action, by aggregating the Flow Key down to input or output interface, address prefix, or autonomous system.

Irregular or data-dependent Aggregation Intervals and key aggregation operations can also be used to provide adaptive aggregation of network flow data. Here, full Flow Records can be kept for Flows of interest, while Flows deemed "less interesting" to a given application can be aggregated. For example, in an IPFIX Mediator equipped with traffic classification capabilities for security purposes, potentially malicious Flows could be exported directly, while known-good or probably-good Flows (e.g. normal web browsing) could be exported simply as time series volumes per web server.

Note that an Intermediate Aggregation Process which removes potentially sensitive information as identified in [[RFC6235](#)] may tend to have an anonymising effect on the Aggregated Flows, as well; however, any application of aggregation as part of a data protection scheme should ensure that all the issues raised in [[RFC6235](#)] are addressed, specifically [Section 4](#) "Anonymization of IP Flow Data",

[Section 7.2](#) "IPFIX-Specific Anonymization Guidelines", and [Section 9](#) "Security Considerations".

While much of the discussion in this document, and all of the examples, apply to the common case that the Original Flows to be aggregated are all of the same underlying type (i.e., are represented with identical or compatible Templates), and that each packet observed by the Metering Process on the far side of the Original Exporter is represented, this is not a necessary assumption. Aggregation can also be applied as part of a technique applying both aggregation and correlation to pull together multiple views of the same traffic from different Observation Points using different Templates. For example, consider a set of applications running at different Observation Points for different purposes -- one generating flows with round-trip-times for passive performance measurement, and one generating billing records. Once correlated, these flows could be used to produce Aggregated Flows containing both volume and performance information together. The correlation and normalization operation described in [Section 4.2.1](#) handles this specific case of correlation. Flow correlation in the general case is outside the scope of this document.

4. Architecture for Flow Aggregation

This section specifies how an Intermediate Aggregation Process fits into the IPFIX Architecture, and the architecture of the Intermediate Aggregation Process itself.

[4.1.](#) Aggregation within the IPFIX Architecture

An Intermediate Aggregation Process could be deployed at any of three places within the IPFIX Architecture. While aggregation is most commonly done within a Mediator which collects Original Flows from an Original Exporter and exports Aggregated Flows, aggregation can also occur before initial export, or after final collection, as shown in Figure 1. The presence of an IAP at any of these points is of course optional.




Figure 1: Potential Aggregation Locations

The Mediator use case is further shown in Figures A and B in [\[RFC6183\]](#).

Aggregation can be applied for either intermediate or final analytic

purposes. In certain circumstances, it may make sense to export Aggregated Flows directly from an original Exporting Process, for example, if the Exporting Process is applied to drive a time-series visualization, or when flow data export bandwidth is restricted and flow or packet sampling is not an option. Note that this case, where the Aggregation Process is essentially integrated into the Metering Process, is essentially covered by the IPFIX architecture [[RFC5470](#)]: the Flow Keys used are simply a subset of those that would normally be used, and time intervals may be chosen other than those available from the cache policies customarily offered by the Metering Process. A Metering Process in this arrangement MAY choose to simulate the generation of larger Flows in order to generate Original Flow counts, if the application calls for compatibility with an Aggregation Process deployed in a separate location.

In the specific case that an Aggregation Process is employed for data reduction for storage purposes, it can take Original Flows from a Collecting Process or File Reader and pass Aggregated Flows to a File Writer for storage.

Deployment of an Intermediate Aggregation Process within a Mediator [[RFC5982](#)] is a much more flexible arrangement. Here, the Mediator consumes Original Flows and produces Contributing Flows; this arrangement is suited to any of the use cases detailed in [Section 3](#). In a Mediator, aggregation can be applied as well to aggregating Original Flows from multiple sources into a single stream of Aggregated Flows; the architectural specifics of this arrangement are not addressed in this document, which is concerned only with the aggregation operation itself; see [[I-D.ietf-ipfix-mediation-protocol](#)] for details.

The data paths into and out of an Intermediate Aggregation Process are shown in Figure 2.




Figure 2: Data paths through the aggregation process

Aggregation may also need to correlate original flows from multiple Metering Processes, each according to a different Template with different Flow Keys and values. This arrangement is shown in Figure 3; in this case, the correlation and normalization operation described in [Section 4.2.1](#) handles merging the Original Flows before




Figure 3: Aggregating Original Flows from multiple Metering Processes

4.2. Intermediate Aggregation Process Architecture

Within this document, an Intermediate Aggregation Process can be seen as hosting a function composed of four types of operations on Partially Aggregated Flows, as illustrated in Figure 4. "Partially Contributing Flows" as defined in [Section 2](#) are essentially the intermediate results of aggregation, internal to the Intermediate Aggregation Process.




Figure 4: Conceptual model of aggregation operations within an IAP

Interval distribution is a temporal aggregation operation which imposes an Aggregation Interval on the partially Contributing Flow. This Aggregation Interval may be regular, irregular, or derived from the timing of the Original Flows themselves. Interval distribution is discussed in detail in [Section 5.1](#).

Key aggregation is a spatial aggregation operation which results in the addition, modification, or deletion of Flow Key fields in the Partially Aggregated Flows. New Flow Keys may be derived from existing Flow Keys (e.g., looking up an AS number for an IP address), or "promoted" from non-Key fields (e.g., when aggregating Flows by packet count per Flow). Key aggregation can also add new non-Key fields derived from Flow Keys that are deleted during key aggregation; mainly counters of unique reduced keys. Key aggregation is discussed in detail in [Section 5.2](#).

Value aggregation is a spatial aggregation operation which results in the addition, modification, or deletion of non-Key fields in the Partially Aggregated Flows. These non-Key fields may be "demoted" from existing Key fields, or derived from existing Key or non-Key fields. Value aggregation is discussed in detail in [Section 5.3](#).

Aggregate combination combines multiple partially Contributing Flows having undergone interval distribution, key aggregation, and value aggregation which share Flow Keys and Aggregation Intervals into a single Contributing Flow per set of Flow Key values and Aggregation Interval. Aggregate combination is discussed in detail in [Section 5.4](#).

Correlation and normalization is required when accepting Original Flows from Metering Processes which export different views of essentially the same Flows before aggregation; the details of correlation and normalization are specified in [Section 4.2.1](#), below.

The first three of these operations may be carried out any number of times in any order, either on Original Flows or on the results of one of the Operations (called Partially Aggregated Flows), with one caveat: since Flows carry their own interval data, any spatial aggregation operation implies a temporal aggregation operation, so at least one interval distribution step, even if implicit, is required by this architecture. This is shown as the first step for the sake of simplicity in the diagram above. Once all aggregation operations are complete, aggregate combination ensures that for a given Aggregation Interval, set of Flow Key values, and Observation Domain, only one Flow is produced by the Intermediate Aggregation Process.

This model describes the operations within a single Intermediate Aggregation Process, and it is anticipated that most aggregation will be applied within a single process. However, as the steps in the model may be applied in any order and aggregate combination is idempotent, any number of Intermediate Aggregation Processes operating in series can be modeled as a single process. This allows aggregation operations to be flexibly distributed across any number of processes, should application or deployment considerations so dictate.

[4.2.1](#). Correlation and Normalization

When accepting Original Flows from multiple Metering Processes, each of which provides a different view of the Original Flow as seen from the point of view of the IAP, an optional correlation and normalization operation combines each of these single Flow Records

into a set of unified partially aggregated Flows before applying interval distribution. These unified Flows appear as if they had been measured at a single Metering Process which used the union of the set of Flow Keys and non-key fields of all Metering Processes sending Original Flows to the IAP.

Since, due to export errors or other slight irregularities in flow metering, the multiple views may not be completely consistent; normalization involves applying a set of aggregation application specific corrections in order to ensure consistency in the unified Flows.

In general, correlation and normalization should take multiple views of essentially the same Flow, as determined by the configuration of the operation itself, and render them into a single unified Flow. Flows which are essentially different should not be unified by the correlation and normalization operation. This operation therefore requires enough information about the configuration and deployment of Metering Processes from which it correlates Original Flows in order to make this distinction correctly and consistently.

The exact steps performed to correlate and normalize flows in this step are application-, implementation-, and deployment-specific, and will not be further specified in this document.

5. IP Flow Aggregation Operations

As stated in [Section 2](#), an Aggregated Flow is simply an IPFIX Flow generated from Original Flows by an Intermediate Aggregation Process. Here, we detail the operations by which this is achieved within an Intermediate Aggregation Process.

5.1. Temporal Aggregation through Interval Distribution

Interval distribution imposes a time interval on the resulting Aggregated Flows. The selection of an interval is specific to the given aggregation application. Intervals may be derived from the Original Flows themselves (e.g., an interval may be selected to cover the entire interval containing the set of all Flows sharing a given Key, as in Time Composition describe in [Section 5.1.2](#)) or externally imposed; in the latter case the externally imposed interval may be regular (e.g., every five minutes) or irregular (e.g., to allow for different time resolutions at different times of day, under different network conditions, or indeed for different sets of Original Flows).

The length of the imposed interval itself has tradeoffs. Shorter intervals allow higher resolution aggregated data and, in streaming

applications, faster reaction time. Longer intervals lead to greater data reduction and simplified counter distribution. Specifically, counter distribution is greatly simplified by the choice of an interval longer than the duration of longest Original Flow, itself generally determined by the Original Flow's Metering Process active timeout; in this case an Original Flow can contribute to at most two Aggregated Flows, and the more complex value distribution methods become inapplicable.




Figure 5: Illustration of interval distribution

In Figure 5, we illustrate three common possibilities for interval distribution as applies with regular intervals to a set of three Original Flows. For Flow A, the start and end times lie within the boundaries of a single interval 0; therefore, Flow A contributes to only one Aggregated Flow. Flow B, by contrast, has the same duration but crosses the boundary between intervals 0 and 1; therefore, it will contribute to two Aggregated Flows, and its counters must be distributed among these Flows, though in the two-interval case this can be simplified somewhat simply by picking one of the two intervals, or proportionally distributing between them. Only Flows like Flow A and Flow B will be produced when the interval is chosen to be longer than the duration of longest Original Flow, as above. More complicated is the case of Flow C, which contributes to more than two Aggregated Flows, and must have its counters distributed according to some policy as in [Section 5.1.1](#).

[5.1.1](#). Distributing Values Across Intervals

In general, counters in Aggregated Flows are treated the same as in any Flow. Each counter is independently calculated as if it were derived from the set of packets in the Original Flow. For the most part, when aggregating Original Flows into Aggregated Flows, this is simply done by summation.

When the Aggregation Interval is guaranteed to be longer than the longest Original Flow, a Flow can cross at most one Interval boundary, and will therefore contribute to at most two Aggregated Flows. Most common in this case is to arbitrarily but consistently choose to account the Original Flow's counters either to the first or the last Contributing Flow to which it could contribute.

However, this becomes more complicated when the Aggregation Interval is shorter than the longest Original Flow in the source data. In such cases, each Original Flow can incompletely cover one or more time intervals, and apply to one or more Aggregated Flows. In this case, the Aggregation Process must distribute the counters in the Original Flows across the multiple Aggregated Flows. There are several methods for doing this, listed here in roughly increasing order of complexity and accuracy; most of these are necessary only in specialized cases.

End Interval: The counters for an Original Flow are added to the counters of the appropriate Aggregated Flow containing the end time of the Original Flow.

Start Interval: The counters for an Original Flow are added to the counters of the appropriate Aggregated Flow containing the start time of the Original Flow.

Mid Interval: The counters for an Original Flow are added to the counters of a single appropriate Aggregated Flow containing some timestamp between start and end time of the Original Flow.

Simple Uniform Distribution: Each counter for an Original Flow is divided by the number of time intervals the Original Flow covers (i.e., of appropriate Aggregated Flows sharing the same Flow Keys), and this number is added to each corresponding counter in each Aggregated Flow.

Proportional Uniform Distribution: This is like simple uniform distribution, but accounts for the fractional portions of a time interval covered by an Original Flow in the first and last time interval. Each counter for an Original Flow is divided by the number of time _units_ the Original Flow covers, to derive a mean count rate. This rate is then multiplied by the number of time units in the intersection of the duration of the Original Flow and the time interval of each Aggregated Flow.

Simulated Process: Each counter of the Original Flow is distributed among the intervals of the Aggregated Flows according to some function the Aggregation Process uses based upon properties of Flows presumed to be like the Original Flow. For example, Flow Records representing bulk transfer might follow a more or less proportional uniform distribution, while interactive processes are far more bursty.

Direct: The Aggregation Process has access to the original packet timings from the packets making up the Original Flow, and uses these to distribute or recalculate the counters.

A method for exporting the distribution of counters across multiple Aggregated Flows is detailed in [Section 7.4](#). In any case, counters MUST be distributed across the multiple Aggregated Flows in such a way that the total count is preserved, within the limits of accuracy of the implementation (e.g., inaccuracy introduced by the use of floating-point numbers is tolerable). This property allows data to be aggregated and re-aggregated without any loss of original count information. To avoid confusion in interpretation of the aggregated data, all the counters for a set of given Original Flows SHOULD be distributed via the same method.

More complex counter distribution methods generally require that the interval distribution process track multiple "current" time intervals at once. This may introduce some delay into the aggregation operation, as an interval should only expire and be available for export when no additional Original Flows applying to the interval are expected to arrive at the Intermediate Aggregation Process.

Note, however, that since there is no guarantee that Flows from the Original Exporter will arrive in any given order, whether for transport-specific reasons (i.e. UDP reordering) or Metering Process implementation-specific reasons, even simpler distribution methods may need to deal with flows arriving in other than start time or end time order. Therefore, the use of larger intervals does not obviate the need to buffer Partially Aggregated Flows within "current" time intervals, to ensure it can accept flow time intervals in any arrival order. More generally, the interval distribution process SHOULD accept flow start and end times in the Original Flows in any reasonable order. The expiration of intervals in interval distribution operations is dependent on implementation and deployment requirements, and SHOULD be made configurable in contexts in which "reasonable order" is not obvious at implementation time. This operation may lead to delay and loss introduced by the IAP, as detailed in [Section 6.2](#).

[5.1.2](#). Time Composition

Time Composition as in [Section 5.4 of \[RFC5982\]](#) (or interval combination) is a special case of aggregation, where interval distribution imposes longer intervals on Flows with matching keys and "chained" start and end times, without any key reduction, in order to join long-lived Flows which may have been split (e.g., due to an active timeout shorter than the actual duration of the Flow.) Here, no Key aggregation is applied, and the Aggregation Interval is chosen

on a per-Flow basis to cover the interval spanned by the set of aggregated Flows. This may be applied alone in order to normalize split Flows, or in combination with other aggregation functions in order to obtain more accurate Original Flow counts.

5.2. Spatial Aggregation of Flow Keys

Key aggregation generates a new set of Flow Key values for the Aggregated Flows from the Original Flow Keys, non-Key fields in the Original Flows, or from correlation of the Original Flow information with some external source. There are two basic operations here. First, Aggregated Flow Keys may be derived directly from Original Flow Keys through reduction, or the dropping of fields or precision in the Original Flow Keys. Second, Aggregated Flow Keys may be derived through replacement, e.g. by removing one or more fields from the Original Flow and replacing them with fields derived from the removed fields. Replacement may refer to external information (e.g., IP to AS number mappings). Replacement may apply to Flow Keys as well as non-key fields. For example, consider an application which aggregates Original Flows by packet count (i.e., generating an Aggregated Flow for all one-packet Flows, one for all two-packet Flows, and so on). This application would promote the packet count to a Flow Key.

Key aggregation may also result in the addition of new non-Key fields to the Aggregated Flows, namely Original Flow counters and unique reduced key counters; these are treated in more detail in [Section 5.2.1](#) and [Section 5.2.2](#), respectively.

In any key aggregation operation, reduction and/or replacement may be applied any number of times in any order. Which of these operations are supported by a given implementation is implementation- and application-dependent. Key aggregation may aggregate Original Flows with different sets of Flow Keys; only the Flow Keys of the resulting Aggregated Flows of any given Key aggregation operation need to contain the same set of fields.

Original Flow Keys

+	-----	+	-----	+	-----	+	-----	+	-----	+	-----	+
	src ip4		dst ip4		src port		dst port		proto		tos	
+	-----	+	-----	+	-----	+	-----	+	-----	+	-----	+
	retain		mask /24		X		X		X		X	
	V		V									
+	-----	+	-----	+	-----	+	-----	+	-----	+	-----	+
	src ip4		dst ip4 /24									
+	-----	+	-----	+	-----	+	-----	+	-----	+	-----	+

Aggregated Flow Keys (by source address and destination class-C)

Figure 6: Illustration of key aggregation by reduction

Figure 6 illustrates an example reduction operation, aggregation by source address and destination class C network. Here, the port, protocol, and type-of-service information is removed from the Flow Key, the source address is retained, and the destination address is masked by dropping the low 8 bits.

Original Flow Keys

+	-----	+	-----	+	-----	+	-----	+	-----	+	-----	+
	src ip4		dst ip4		src port		dst port		proto		tos	
+	-----	+	-----	+	-----	+	-----	+	-----	+	-----	+
					X		X		X		X	
+	-----	+	-----	+	-----	+	-----	+	-----	+	-----	+
	ASN lookup table											
+	-----	+	-----	+	-----	+	-----	+	-----	+	-----	+
	V		V									
+	-----	+	-----	+	-----	+	-----	+	-----	+	-----	+
	src asn		dst asn									
+	-----	+	-----	+	-----	+	-----	+	-----	+	-----	+

Aggregated Flow Keys (by source and dest ASN)

Figure 7: Illustration of key aggregation by reduction and replacement

Figure 7 illustrates an example reduction and replacement operation, aggregation by source and destination Border Gateway Protocol (BGP) Autonomous System Number (ASN) without ASN information available in the Original Flow. Here, the port, protocol, and type-of-service information is removed from the Flow Keys, while the source and destination addresses are run through an IP address to ASN lookup table, and the Aggregated Flow Keys are made up of the resulting source and destination ASNs.

5.2.1. Counting Original Flows

When aggregating multiple Original Flows into an Aggregated Flow, it is often useful to know how many Original Flows are present in the Aggregated Flow. This document introduces four new information elements in [Section 7.2](#) to export these counters.

There are two possible ways to count Original Flows, which we call here conservative and non-conservative. Conservative flow counting has the property that each Original Flow contributes exactly one to the total flow count within a set of Contributing Flows. In other words, conservative flow counters are distributed just as any other counter during interval distribution, except each Original Flow is assumed to have a flow count of one. When a count for an Original Flow must be distributed across a set of Aggregated Flows, and a distribution method is used which does not account for that Original Flow completely within a single Aggregated Flow, conservative flow counting requires a fractional representation.

By contrast, non-conservative flow counting is used to count how many Contributing Flows are represented in an Aggregated Flow. Flow counters are not distributed in this case. An Original Flow which is present within N Aggregated Flows would add N to the sum of non-conservative flow counts, one to each Aggregated Flow. In other words, the sum of conservative flow counts over a set of Aggregated Flows is always equal to the number of Original Flows, while the sum of non-conservative flow counts is strictly greater than or equal to the number of Original Flows.

For example, consider Flows A, B, and C as illustrated in Figure 5. Assume that the key aggregation step aggregates the keys of these three Flows to the same aggregated Flow Key, and that start interval counter distribution is in effect. The conservative flow count for interval 0 is 3 (since Flows A, B, and C all begin in this interval), and for the other two intervals is 0. The non-conservative flow count for interval 0 is also 3 (due to the presence of Flows A, B, and C), for interval 1 is 2 (Flows B and C), and for interval 2 is 1 (Flow C). The sum of the conservative counts $3 + 0 + 0 = 3$, the number of Original Flows; while the sum of the non-conservative counts $3 + 2 + 1 = 6$.

Note that the active and inactive timeouts used to generate Original Flows, as well as the cache policy used to generate those Flows, have an effect on how meaningful either the conservative or non-conservative flow count will be during aggregation. In general, all the Original Exporters producing Original Flows to be aggregated SHOULD be aggregated using caches configured identically or similarly. Original Exporters using the IPFIX Configuration Model

SHOULD be configured to export Flows with equal or similar activeTimeout and inactiveTimeout configuration values, and the same cacheMode, as defined in section 4.3 of [\[I-D.ietf-ipfix-configuration-model\]](#).

5.2.2. Counting Distinct Key Values

One common case in aggregation is counting distinct key values that were reduced away during key aggregation. The most common use case for this is counting distinct hosts per Flow Key; for example, in host characterization or anomaly detection, distinct sources per destination or distinct destinations per source are common metrics. These new non-Key fields are added during key aggregation.

For such applications, Information Elements for distinct counts of IPv4 and IPv6 addresses are defined in [Section 7.3](#). These are named distinctCountOf(KeyName). Additional such Information Elements SHOULD be registered with IANA on an as-needed basis.

5.3. Spatial Aggregation of Non-Key Fields

Aggregation operations may also lead to the addition of value fields demoted from key fields, or derived from other value fields in the Original Flows. Specific cases of this are treated in the subsections below.

5.3.1. Counter Statistics

Some applications of aggregation may benefit from computing different statistics than those native to each non-key field (i.e., union for flags, sum for counters). For example, minimum and maximum packet counts per Flow, mean bytes per packet per Contributing Flow, and so on. Certain Information Elements for these applications are already provided in the IANA IPFIX Information Elements registry (<http://www.iana.org/assignments/ipfix/ipfix.html>) (e.g. minimumIpTotalLength).

A complete specification of additional aggregate counter statistics is outside the scope of this document, and should be added in the future to the IANA IPFIX Information Elements registry on a per-application, as-needed basis.

5.3.2. Derivation of New Values from Flow Keys and non-Key fields

More complex operations may lead to other derived fields being generated from the set of values or Flow Keys reduced away during aggregation. A prime example of this is sample entropy calculation. This counts distinct values and frequency, so is similar to distinct

key counting as in [Section 5.2.2](#), but may be applied to the distribution of values for any flow field.

Sample entropy calculation provides a one-number normalized representation of the value spread and is useful for anomaly detection. The behaviour of entropy statistics is such that a small number of keys showing up very often drives the entropy value down towards zero, while a large number of keys, each showing up with lower frequency drives the entropy value up.

Entropy statistics are generally useful for address-like keys, like IP addresses, port numbers, AS numbers, etc. They can also be done on flow length, flow duration fields and the like, even if this generally yields less distinct value shifts when the traffic mix changes.

As a practical example, one host scanning a lot of other hosts will drive source IP entropy down and target IP entropy up. A similar effect can be observed for ports. This pattern can also be caused by the scan-traffic of a fast Internet worm. A second example would be a DDoS flooding attack against a single target (or small number of targets) which drives source IP entropy up and target IP entropy down.

A complete specification of additional derived values or entropy information elements is outside the scope of this document. Any such Information Elements should be added in the future to the IANA IPFIX Information Elements registry on a per-application, as-needed basis. However, in the special case of entropy calculations, to support comparability of entropies of fields with different bit sizes, entropy SHOULD be represented as a float32 or float64 value normalized to the range [0..1].

[5.4.](#) Aggregation Combination

Interval distribution and key aggregation together may generate multiple Partially Aggregated Flows covering the same time interval with the same set of Flow Key values. The process of combining these Partially Aggregated Flows into a single Aggregated Flow is called aggregation combination. In general, non-Key values from multiple Contributing Flows are combined using the same operation by which values are combined from packets to form Flows for each Information Element. Counters are summed, averages are averaged, flags are unioned, and so on.

6. Additional Considerations and Special Cases in Flow Aggregation

6.1. Exact versus Approximate Counting during Aggregation

In certain circumstances, particularly involving aggregation by devices with limited resources, and in situations where exact aggregated counts are less important than relative magnitudes (e.g. driving graphical displays), counter distribution during key aggregation may be performed by approximate counting means (e.g. Bloom filters). The choice to use approximate counting is implementation- and application-dependent.

6.2. Delay and Loss introduced by the IAP

When accepting Original Flows in export order from traffic captured live, the Intermediate Aggregation Process wait for all Original Flows which may contribute to a given interval during interval distribution. This is generally dominated by the active timeout of the Metering Process measuring the Original Flows. For example, with Metering Processes configured with a 5 minute active timeout, the Intermediate Aggregation Process introduces a delay of at least 5 minutes to all exported Aggregated Flows to ensure it has received all Original Flows.

In certain circumstances, additional delay at the original Exporter may cause an IAP to close an interval before the last Original Flow(s) accountable to the interval arrives; in this case the IAP SHOULD drop the late Original Flow(s). Accounting of flows lost at an Intermediate Process due to such issues is covered in [[I-D.ietf-ipfix-mediation-protocol](#)].

6.3. Considerations for Aggregation of Sampled Flows

The accuracy of Aggregated Flows may also be affected by sampling of the Original Flows, or sampling of packets making up the Original Flows. The effect of sampling on flow aggregation is still an open research question. However, to maximize the comparability of Aggregated Flows, aggregation of sampled Flows SHOULD only use Original Flows sampled using the same sampling rate and sampling algorithm, or Flows created from packets sampled using the same sampling rate and sampling algorithm. For more on packet sampling within IPFIX, see [[RFC5476](#)]. For more on Flow sampling within the IPFIX Mediator Framework, see [[I-D.ietf-ipfix-flow-selection-tech](#)].

6.4. Considerations for Aggregation of Heterogeneous Flows

Aggregation may be applied to Original Flows from different sources and of different types (i.e., represented using different, perhaps

wildly-different Templates). When the goal is to separate the heterogeneous Original Flows and aggregate them into heterogeneous Aggregated Flows, each aggregation should be done at its own Intermediate Aggregation Process. The Observation Domain ID on the Messages containing the output Aggregated Flows can be used to identify the different Processes, and to segregate the output.

However, when the goal is to aggregate these Flows into a single stream of Aggregated Flows representing one type of data, and if the Original Flows may represent the same original packet at two different Observation Points, the Original Flows should be correlated by the correlation and normalization operation within the IAP to ensure that each packet is only represented in a single Aggregated Flow or set of Aggregated Flows differing only by aggregation interval.

7. Export of Aggregated IP Flows using IPFIX

In general, Aggregated Flows are exported in IPFIX as any normal Flow. However, certain aspects of Aggregated Flow export benefit from additional guidelines, or new Information Elements to represent aggregation metadata or information generated during aggregation. These are detailed in the following subsections.

7.1. Time Interval Export

Since an Aggregated Flow is simply a Flow, the existing timestamp Information Elements in the IPFIX Information Model (e.g., flowStartMilliseconds, flowEndNanoseconds) are sufficient to specify the time interval for aggregation. Therefore, this document specifies no new aggregation-specific Information Elements for exporting time interval information.

Each Aggregated Flow SHOULD contain both an interval start and interval end timestamp. If an exporter of Aggregated Flows omits the interval end timestamp from each Aggregated Flow, the time interval for Aggregated Flows within an Observation Domain and Transport Session MUST be regular and constant. However, note that this approach might lead to interoperability problems when exporting Aggregated Flows to non-aggregation-aware Collecting Processes and downstream analysis tasks; therefore, an Exporting Process capable of exporting only interval start timestamps MUST provide a configuration option to export interval end timestamps as well.

7.2. Flow Count Export

The following four Information Elements are defined to count Original Flows as discussed in [Section 5.2.1](#).

7.2.1. originalFlowsPresent

Description: The non-conservative count of Original Flows contributing to this Aggregated Flow. Non-conservative counts need not sum to the original count on re-aggregation.

Abstract Data Type: unsigned64

ElementId: TBD1

Status: Current

7.2.2. originalFlowsInitiated

Description: The conservative count of Original Flows whose first packet is represented within this Aggregated Flow. Conservative counts must sum to the original count on re-aggregation.

Abstract Data Type: unsigned64

ElementId: TBD2

Status: Current

7.2.3. originalFlowsCompleted

Description: The conservative count of Original Flows whose last packet is represented within this Aggregated Flow. Conservative counts must sum to the original count on re-aggregation.

Abstract Data Type: unsigned64

ElementId: TBD3

Status: Current

7.2.4. deltaFlowCount

Description: The conservative count of Original Flows contributing to this Aggregated Flow; may be distributed via any of the methods described in [Section 5.1.1](#). This Information Element is compatible with Information Element 3 as used in NetFlow version 9.

Abstract Data Type: float64

ElementId: 3

Status: Current

7.3. Distinct Host Export

The following four Information Elements represent the distinct counts of source and destination network-layer addresses, used to export distinct host counts reduced away during key aggregation.

7.3.1. distinctCountOfSourceIPAddress

Description: The count of distinct source IP address values for Original Flows contributing to this Aggregated Flow, without regard to version. This Information Element is preferred to the IP-version-specific counters, unless it is important to separate the counts by version.

Abstract Data Type: unsigned64

ElementId: TBD4

Status: Current

7.3.2. distinctCountOfDestinationIPAddress

Description: The count of distinct destination IP address values for Original Flows contributing to this Aggregated Flow, without regard to version. This Information Element is preferred to the version-specific counters below, unless it is important to separate the counts by version.

Abstract Data Type: unsigned64

ElementId: TBD5

Status: Current

7.3.3. distinctCountOfSourceIPv4Address

Description: The count of distinct source IPv4 address values for Original Flows contributing to this Aggregated Flow.

Abstract Data Type: unsigned32

ElementId: TBD6

Status: Current

7.3.4. distinctCountOfDestinationIPv4Address

Description: The count of distinct destination IPv4 address values for Original Flows contributing to this Aggregated Flow.

Abstract Data Type: unsigned32

ElementId: TBD7

Status: Current

7.3.5. distinctCountOfSourceIPv6Address

Description: The count of distinct source IPv6 address values for Original Flows contributing to this Aggregated Flow.

Abstract Data Type: unsigned64

ElementId: TBD8

Status: Current

7.3.6. distinctCountOfDestinationIPv6Address

Description: The count of distinct destination IPv6 address values for Original Flows contributing to this Aggregated Flow.

Abstract Data Type: unsigned64

ElementId: TBD9

Status: Current

7.4. Aggregate Counter Distribution Export

When exporting counters distributed among Aggregated Flows, as described in [Section 5.1.1](#), the Exporting Process MAY export an Aggregate Counter Distribution Record for each Template describing Aggregated Flow records; this Options Template is described below. It uses the valueDistributionMethod Information Element, also defined below. Since in many cases distribution is simple, accounting the counters from Contributing Flows to the first Interval to which they

contribute, this is default situation, for which no Aggregate Counter Distribution Record is necessary; Aggregate Counter Distribution Records are only applicable in more exotic situations, such as using an Aggregation Interval smaller than the durations of Original Flows.

7.4.1. Aggregate Counter Distribution Options Template

This Options Template defines the Aggregate Counter Distribution Record, which allows the binding of a value distribution method to a Template ID. Note that this Options Template causes the valueDistributionMethod to be implicitly scoped to the Observation Domain ID of the IPFIX Message containing the Aggregate Counter Distribution Record. This is used to signal to the Collecting Process how the counters were distributed. The fields are as below:

IE	Description
templateId [scope]	The Template ID of the Template defining the Aggregated Flows to which this distribution option applies. This Information Element MUST be defined as a Scope Field.
valueDistributionMethod	The method used to distribute the counters for the Aggregated Flows defined by the associated Template.

7.4.2. valueDistributionMethod Information Element

Description: A description of the method used to distribute the counters from Contributing Flows into the Aggregated Flow records described by an associated Template. The method is deemed to apply to all the non-key Information Elements in the referenced Template for which value distribution is a valid operation; if the originalFlowsInitiated and/or originalFlowsCompleted Information Elements appear in the Template, they are not subject to this distribution method, as they each infer their own distribution method. The distribution methods are taken from [Section 5.1.1](#) and encoded as follows:

Value	Description
1	Start Interval: The counters for an Original Flow are added to the counters of the appropriate Aggregated Flow containing the start time of the Original Flow. This should be assumed the default if value distribution information is not available at a Collecting Process for an Aggregated Flow.
2	End Interval: The counters for an Original Flow are added to the counters of the appropriate Aggregated Flow containing the end time of the Original Flow.
3	Mid Interval: The counters for an Original Flow are added to the counters of a single appropriate Aggregated Flow containing some timestamp between start and end time of the Original Flow.
4	Simple Uniform Distribution: Each counter for an Original Flow is divided by the number of time intervals the Original Flow covers (i.e., of appropriate Aggregated Flows sharing the same Flow Key), and this number is added to each corresponding counter in each Aggregated Flow.
5	Proportional Uniform Distribution: Each counter for an Original Flow is divided by the number of time _units_ the Original Flow covers, to derive a mean count rate. This mean count rate is then multiplied by the number of time units in the intersection of the duration of the Original Flow and the time interval of each Aggregated Flow. This is like simple uniform distribution, but accounts for the fractional portions of a time interval covered by an Original Flow in the first and last time interval.
6	Simulated Process: Each counter of the Original Flow is distributed among the intervals of the Aggregated Flows according to some function the Aggregation Process uses based upon properties of Flows presumed to be like the Original Flow. This is essentially an assertion that the Aggregation Process has no direct packet timing information but is nevertheless not using one of the other simpler distribution methods. The Aggregation Process specifically makes no assertion as to the correctness of the simulation.
7	Direct: The Aggregation Process has access to the original packet timings from the packets making up the Original Flow, and uses these to distribute or recalculate the counters.

Abstract Data Type: unsigned8

ElementId: TBD10

Status: Current

8. Examples

In these examples, the same data, described by the same template, will be aggregated multiple different ways; this illustrates the various different functions which could be implemented by Intermediate Aggregation Processes. Templates are shown in iespec format as introduced in [[I-D.ietf-ipfix-ie-doctors](#)]. The source data format is a simplified flow: timestamps, traditional 5-tuple, and octet count. The template is shown in Figure 8.

```
flowStartMilliseconds(152)[8]
flowEndMilliseconds(153)[8]
sourceIPv4Address(8)[4]
destinationIPv4Address(12)[4]
sourceTransportPort(7)[2]
destinationTransportPort(11)[2]
protocolIdentifier(4)[1]
octetDeltaCount(1)[8]
```

Figure 8: Input template for examples

The data records given as input to the examples in this section are shown below, in the format "flowStartMilliseconds-flowEndMilliseconds sourceIPv4Address:sourceTransportPort -> destinationIPv4Address: destinationTransportPort (protocolIdentifier) octetDeltaCount"; timestamps are given in H:MM:SS.sss format.

9:00:00.138-9:00:00.138	192.0.2.2:47113	-> 192.0.2.131:53	(17)	119
9:00:03.246-9:00:03.246	192.0.2.2:22153	-> 192.0.2.131:53	(17)	83
9:00:00.478-9:00:03.486	192.0.2.2:52420	-> 198.51.100.2:443	(6)	1637
9:00:07.172-9:00:07.172	192.0.2.3:56047	-> 192.0.2.131:53	(17)	111
9:00:07.309-9:00:14.861	192.0.2.3:41183	-> 198.51.100.67:80	(6)	16838
9:00:03.556-9:00:19.876	192.0.2.2:17606	-> 198.51.100.68:80	(6)	11538
9:00:25.210-9:00:25.210	192.0.2.3:47113	-> 192.0.2.131:53	(17)	119
9:00:26.358-9:00:30.198	192.0.2.3:48458	-> 198.51.100.133:80	(6)	2973
9:00:29.213-9:01:00.061	192.0.2.4:61295	-> 198.51.100.2:443	(6)	8350
9:04:00.207-9:04:04.431	203.0.113.3:41256	-> 198.51.100.133:80	(6)	778
9:03:59.624-9:04:06.984	203.0.113.3:51662	-> 198.51.100.3:80	(6)	883
9:00:30.532-9:06:15.402	192.0.2.2:37581	-> 198.51.100.2:80	(6)	15420
9:06:56.813-9:06:59.821	203.0.113.3:52572	-> 198.51.100.2:443	(6)	1637
9:06:30.565-9:07:00.261	203.0.113.3:49914	-> 197.51.100.133:80	(6)	561
9:06:55.160-9:07:05.208	192.0.2.2:50824	-> 198.51.100.2:443	(6)	1899
9:06:49.322-9:07:05.322	192.0.2.3:34597	-> 198.51.100.3:80	(6)	1284
9:07:05.849-9:07:09.625	203.0.113.3:58907	-> 198.51.100.4:80	(6)	2670
9:10:45.161-9:10:45.161	192.0.2.4:22478	-> 192.0.2.131:53	(17)	75
9:10:45.209-9:11:01.465	192.0.2.4:49513	-> 198.51.100.68:80	(6)	3374
9:10:57.094-9:11:00.614	192.0.2.4:64832	-> 198.51.100.67:80	(6)	138
9:10:59.770-9:11:02.842	192.0.2.3:60833	-> 198.51.100.69:443	(6)	2325
9:02:18.390-9:13:46.598	203.0.113.3:39586	-> 198.51.100.17:80	(6)	11200
9:13:53.933-9:14:06.605	192.0.2.2:19638	-> 198.51.100.3:80	(6)	2869
9:13:02.864-9:14:08.720	192.0.2.3:40429	-> 198.51.100.4:80	(6)	18289

Figure 9: Input data for examples

8.1. Traffic Time-Series per Source

Aggregating flows by source IP address in time series (i.e., with a regular interval) can be used in subsequent heavy-hitter analysis and as a source parameter for statistical anomaly detection techniques. Here, the Intermediate Aggregation Process imposes an interval, aggregates the key to remove all key fields other than the source IP address, then combines the result into a stream of Aggregated Flows. The imposed interval of 5 minutes is longer than the majority of flows; for those flows crossing interval boundaries, the entire flow is accounted to the interval containing the start time of the flow.

In this example the Partially Aggregated Flows after each conceptual operation in the Intermediate Aggregation Process are shown. These are meant to be illustrative of the conceptual operations only, and not to suggest an implementation (indeed, the example shown here would not necessarily be the most efficient method for performing these operations). Subsequent examples will omit the Partially Aggregated Flows for brevity.

The input to this process could be any Flow Record containing a

source IP address and octet counter; consider for this example the template and data from the introduction. The Intermediate Aggregation Process would then output records containing just timestamps, source IP, and octetDeltaCount, as in Figure 10.

```
flowStartMilliseconds(152)[8]
flowEndMilliseconds(153)[8]
sourceIPv4Address(8)[4]
octetDeltaCount(1)[8]
```

Figure 10: Output template for time series per source

Assume the goal is to get 5-minute time series of octet counts per source IP address. The aggregation operations would then be arranged as in Figure 11.




Figure 11: Aggregation operations for time series per source

After the interval distribution step, only the time intervals have changed; the Partially Aggregated flows are shown in Figure 12. Note that interval distribution follows the default Start Interval policy;

that is, the entire flow is accounted to the interval containing the flow's start time.

9:00:00.000-9:05:00.000	192.0.2.2:47113	-> 192.0.2.131:53	(17)	119
9:00:00.000-9:05:00.000	192.0.2.2:22153	-> 192.0.2.131:53	(17)	83
9:00:00.000-9:05:00.000	192.0.2.2:52420	-> 198.51.100.2:443	(6)	1637
9:00:00.000-9:05:00.000	192.0.2.3:56047	-> 192.0.2.131:53	(17)	111
9:00:00.000-9:05:00.000	192.0.2.3:41183	-> 198.51.100.67:80	(6)	16838
9:00:00.000-9:05:00.000	192.0.2.2:17606	-> 198.51.100.68:80	(6)	11538
9:00:00.000-9:05:00.000	192.0.2.3:47113	-> 192.0.2.131:53	(17)	119
9:00:00.000-9:05:00.000	192.0.2.3:48458	-> 198.51.100.133:80	(6)	2973
9:00:00.000-9:05:00.000	192.0.2.4:61295	-> 198.51.100.2:443	(6)	8350
9:00:00.000-9:05:00.000	203.0.113.3:41256	-> 198.51.100.133:80	(6)	778
9:00:00.000-9:05:00.000	203.0.113.3:51662	-> 198.51.100.3:80	(6)	883
9:00:00.000-9:05:00.000	192.0.2.2:37581	-> 198.51.100.2:80	(6)	15420
9:00:00.000-9:05:00.000	203.0.113.3:39586	-> 198.51.100.17:80	(6)	11200
9:05:00.000-9:10:00.000	203.0.113.3:52572	-> 198.51.100.2:443	(6)	1637
9:05:00.000-9:10:00.000	203.0.113.3:49914	-> 197.51.100.133:80	(6)	561
9:05:00.000-9:10:00.000	192.0.2.2:50824	-> 198.51.100.2:443	(6)	1899
9:05:00.000-9:10:00.000	192.0.2.3:34597	-> 198.51.100.3:80	(6)	1284
9:05:00.000-9:10:00.000	203.0.113.3:58907	-> 198.51.100.4:80	(6)	2670
9:10:00.000-9:15:00.000	192.0.2.4:22478	-> 192.0.2.131:53	(17)	75
9:10:00.000-9:15:00.000	192.0.2.4:49513	-> 198.51.100.68:80	(6)	3374
9:10:00.000-9:15:00.000	192.0.2.4:64832	-> 198.51.100.67:80	(6)	138
9:10:00.000-9:15:00.000	192.0.2.3:60833	-> 198.51.100.69:443	(6)	2325
9:10:00.000-9:15:00.000	192.0.2.2:19638	-> 198.51.100.3:80	(6)	2869
9:10:00.000-9:15:00.000	192.0.2.3:40429	-> 198.51.100.4:80	(6)	18289

Figure 12: Interval imposition for time series per source

After the key aggregation step, all Flow Keys except the source IP address have been discarded, as shown in Figure 13. This leaves duplicate Partially Aggregated flows to be combined in the final operation.

9:00:00.000-9:05:00.000	192.0.2.2	119
9:00:00.000-9:05:00.000	192.0.2.2	83
9:00:00.000-9:05:00.000	192.0.2.2	1637
9:00:00.000-9:05:00.000	192.0.2.3	111
9:00:00.000-9:05:00.000	192.0.2.3	16838
9:00:00.000-9:05:00.000	192.0.2.2	11538
9:00:00.000-9:05:00.000	192.0.2.3	119
9:00:00.000-9:05:00.000	192.0.2.3	2973
9:00:00.000-9:05:00.000	192.0.2.4	8350
9:00:00.000-9:05:00.000	203.0.113.3	778
9:00:00.000-9:05:00.000	203.0.113.3	883
9:05:00.000-9:10:00.000	203.0.113.3	1637
9:05:00.000-9:10:00.000	203.0.113.3	561
9:05:00.000-9:10:00.000	192.0.2.2	1899
9:05:00.000-9:10:00.000	192.0.2.3	1284
9:05:00.000-9:10:00.000	203.0.113.3	2670
9:10:00.000-9:15:00.000	192.0.2.4	75
9:10:00.000-9:15:00.000	192.0.2.4	3374
9:10:00.000-9:15:00.000	192.0.2.4	138
9:10:00.000-9:15:00.000	192.0.2.3	2325
9:10:00.000-9:15:00.000	192.0.2.2	2869
9:10:00.000-9:15:00.000	192.0.2.3	18289

Figure 13: Key aggregation for time series per source

Aggregate combination sums the counters per key and interval; the summations of the first two keys and intervals are shown in detail in Figure 14.

9:00:00.000-9:05:00.000	192.0.2.2	119
9:00:00.000-9:05:00.000	192.0.2.2	83
9:00:00.000-9:05:00.000	192.0.2.2	1637
9:00:00.000-9:05:00.000	192.0.2.2	11538
+ 9:00:00.000-9:05:00.000	192.0.2.2	15420

= 9:00:00.000-9:05:00.000	192.0.2.2	28797
9:00:00.000-9:05:00.000	192.0.2.3	111
9:00:00.000-9:05:00.000	192.0.2.3	16838
9:00:00.000-9:05:00.000	192.0.2.3	119
+ 9:00:00.000-9:05:00.000	192.0.2.3	2973

= 9:00:00.000-9:05:00.000	192.0.2.3	20041

Figure 14: Summation during aggregate combination

Applying this to each set of Partially Aggregated Flows to produce the final Aggregated Flows shown in Figure 15 to be exported by the

template in Figure 10.

9:00:00.000-9:05:00.000	192.0.2.2	28797
9:00:00.000-9:05:00.000	192.0.2.3	20041
9:00:00.000-9:05:00.000	192.0.2.4	8350
9:00:00.000-9:05:00.000	203.0.113.3	12861
9:05:00.000-9:10:00.000	192.0.2.2	1899
9:05:00.000-9:10:00.000	192.0.2.3	1284
9:05:00.000-9:10:00.000	203.0.113.3	4868
9:10:00.000-9:15:00.000	192.0.2.2	2869
9:10:00.000-9:15:00.000	192.0.2.3	20594
9:10:00.000-9:15:00.000	192.0.2.4	3587

Figure 15: Aggregated Flows for time series per source

8.2. Core Traffic Matrix

Aggregating flows by source and destination autonomous system number in time series is used to generate core traffic matrices. The core traffic matrix provides a view of the state of the routes within a network, and can be used for long-term planning of changes to network design based on traffic demand. Here, imposed time intervals are generally much longer than active flow timeouts. The traffic matrix is reported in terms of octets, packets, and flows, as each of these values may have a subtly different effect on capacity planning.

This example demonstrates key aggregation using derived keys and original flow counting. While some Original Flows may be generated by Exporting Processes on forwarding devices, and therefore contain the `bgpSourceAsNumber` and `bgpDestinationAsNumber` Information Elements, Original Flows from Exporting Processes on dedicated measurement devices will contain only a `destinationIPv[46]Address`. For these flows, the Mediator must look up a next hop AS from a IP to AS table, replacing source and destination addresses with AS numbers. The table used in this example is shown in Figure 16. (Note that due to limited example address space, in this example we ignore the common practice of routing only blocks of /24 or larger).

prefix	ASN
192.0.2.0/25	64496
192.0.2.128/25	64497
198.51.100/24	64498
203.0.113.0/24	64499

Figure 16: Example Autonomous system number map

The template for Aggregated Flows produced by this example is shown in Figure 17.


```

flowStartMilliseconds(152)[8]
flowEndMilliseconds(153)[8]
bgpSourceAsNumber(16)[4]
bgpDestinationAsNumber(17)[4]
octetDeltaCount(1)[8]

```

Figure 17: Output template for traffic matrix

Assume the goal is to get 60-minute time series of octet counts per source/destination ASN pair. The aggregation operations would then be arranged as in Figure 18.




Figure 18: Aggregation operations for traffic matrix

After the interval distribution step, only the time intervals have changed; the Partially Aggregated flows are shown in Figure 19. Note that the flows are identical to those in interval distribution step in the previous example, except the chosen interval (1 hour, 3600 seconds) is different; therefore, all the flows fit into a single interval.

```

9:00:00.000-10:00:00.000 192.0.2.2:47113 -> 192.0.2.131:53 (17) 119
9:00:00.000-10:00:00.000 192.0.2.2:22153 -> 192.0.2.131:53 (17) 83
9:00:00.000-10:00:00.000 192.0.2.2:52420 -> 198.51.100.2:443 (6) 1637
9:00:00.000-10:00:00.000 192.0.2.3:56047 -> 192.0.2.131:53 (17) 111
9:00:00.000-10:00:00.000 192.0.2.3:41183 -> 198.51.100.67:80 (6) 16838
9:00:00.000-10:00:00.000 192.0.2.2:17606 -> 198.51.100.68:80 (6) 11538
9:00:00.000-10:00:00.000 192.0.2.3:47113 -> 192.0.2.131:53 (17) 119
9:00:00.000-10:00:00.000 192.0.2.3:48458 -> 198.51.100.133:80 (6) 2973
9:00:00.000-10:00:00.000 192.0.2.4:61295 -> 198.51.100.2:443 (6) 8350
9:00:00.000-10:00:00.000 203.0.113.3:41256 -> 198.51.100.133:80 (6) 778
9:00:00.000-10:00:00.000 203.0.113.3:51662 -> 198.51.100.3:80 (6) 883
9:00:00.000-10:00:00.000 192.0.2.2:37581 -> 198.51.100.2:80 (6) 15420
9:00:00.000-10:00:00.000 203.0.113.3:52572 -> 198.51.100.2:443 (6) 1637
9:00:00.000-10:00:00.000 203.0.113.3:49914 -> 197.51.100.133:80 (6) 561
9:00:00.000-10:00:00.000 192.0.2.2:50824 -> 198.51.100.2:443 (6) 1899
9:00:00.000-10:00:00.000 192.0.2.3:34597 -> 198.51.100.3:80 (6) 1284
9:00:00.000-10:00:00.000 203.0.113.3:58907 -> 198.51.100.4:80 (6) 2670
9:00:00.000-10:00:00.000 192.0.2.4:22478 -> 192.0.2.131:53 (17) 75
9:00:00.000-10:00:00.000 192.0.2.4:49513 -> 198.51.100.68:80 (6) 3374
9:00:00.000-10:00:00.000 192.0.2.4:64832 -> 198.51.100.67:80 (6) 138
9:00:00.000-10:00:00.000 192.0.2.3:60833 -> 198.51.100.69:443 (6) 2325
9:00:00.000-10:00:00.000 203.0.113.3:39586 -> 198.51.100.17:80 (6) 11200
9:00:00.000-10:00:00.000 192.0.2.2:19638 -> 198.51.100.3:80 (6) 2869
9:00:00.000-10:00:00.000 192.0.2.3:40429 -> 198.51.100.4:80 (6) 18289

```

Figure 19: Interval imposition for traffic matrix

The next step is to discard irrelevant key fields, and replace the source and destination addresses with source and destination AS numbers in the map; the results of these key aggregation steps are shown in Figure 20.

9:00:00.000-10:00:00.000	AS64496 -> AS64497	119
9:00:00.000-10:00:00.000	AS64496 -> AS64497	83
9:00:00.000-10:00:00.000	AS64496 -> AS64498	1637
9:00:00.000-10:00:00.000	AS64496 -> AS64497	111
9:00:00.000-10:00:00.000	AS64496 -> AS64498	16838
9:00:00.000-10:00:00.000	AS64496 -> AS64498	11538
9:00:00.000-10:00:00.000	AS64496 -> AS64497	119
9:00:00.000-10:00:00.000	AS64496 -> AS64498	2973
9:00:00.000-10:00:00.000	AS64496 -> AS64498	8350
9:00:00.000-10:00:00.000	AS64499 -> AS64498	778
9:00:00.000-10:00:00.000	AS64499 -> AS64498	883
9:00:00.000-10:00:00.000	AS64496 -> AS64498	15420
9:00:00.000-10:00:00.000	AS64499 -> AS64498	1637
9:00:00.000-10:00:00.000	AS64499 -> AS64498	561
9:00:00.000-10:00:00.000	AS64496 -> AS64498	1899
9:00:00.000-10:00:00.000	AS64496 -> AS64498	1284
9:00:00.000-10:00:00.000	AS64499 -> AS64498	2670
9:00:00.000-10:00:00.000	AS64496 -> AS64497	75
9:00:00.000-10:00:00.000	AS64496 -> AS64498	3374
9:00:00.000-10:00:00.000	AS64496 -> AS64498	138
9:00:00.000-10:00:00.000	AS64496 -> AS64498	2325
9:00:00.000-10:00:00.000	AS64499 -> AS64498	11200
9:00:00.000-10:00:00.000	AS64496 -> AS64498	2869
9:00:00.000-10:00:00.000	AS64496 -> AS64498	18289

Figure 20: Key aggregation for traffic matrix: reduction and replacement

Finally, aggregate combination sums the counters per key and interval. The resulting Aggregated Flows containing the traffic matrix, shown in Figure 21, are then exported using the template in Figure 17. Note that these aggregated flows represent a sparse matrix: AS pairs for which no traffic was received have no corresponding record in the output.

9:00:00.000-10:00:00.000	AS64496 -> AS64497	507
9:00:00.000-10:00:00.000	AS64496 -> AS64498	86934
9:00:00.000-10:00:00.000	AS64499 -> AS64498	17729

Figure 21: Aggregated Flows for traffic matrix

The output of this operation is suitable for re-aggregation: that is, traffic matrices from single links or observation points can be aggregated through the same interval imposition and aggregate combination steps in order to build a traffic matrix for an entire network.

8.3. Distinct Source Count per Destination Endpoint

Aggregating flows by destination address and port, and counting distinct sources aggregated away, can be used as part of passive service inventory and host characterization approaches. This example shows aggregation as an analysis technique, performed on source data stored in an IPFIX File. As the Transport Session in this File is bounded, removal of all timestamp information allows summarization of the entire time interval contained within the interval. Removal of timing information during interval imposition is equivalent to an infinitely long imposed time interval. This demonstrates both how infinite intervals work, and how unique counters work. The aggregation operations are summarized in Figure 22.




Figure 22: Aggregation operations for source count

The template for Aggregated Flows produced by this example is shown in Figure 23.

```

destinationIPv4Address(12)[4]
destinationTransportPort(11)[2]
distinctCountOfSourceIPAddress(TBD4)[8]

```

Figure 23: Output template for source count

Interval distribution, in this case, merely discards the timestamp information from the Original Flows, and as such is not shown.

Likewise, the value aggregation step simply discards the `octetDeltaCount` value field. The key aggregation step reduces the key to the `destinationIPv4Address` and `destinationTransportPort`, counting the distinct source addresses. Since this is essentially the output of this aggregation function, the aggregate combination operation is a no-op; the resulting Aggregated Flows are shown in Figure 24.

destination 192.0.2.131:53	3 sources
destination 198.51.100.2:80	1 source
destination 198.51.100.2:443	3 sources
destination 198.51.100.67:80	2 sources
destination 198.51.100.68:80	2 sources
destination 198.51.100.133:80	2 sources
destination 198.51.100.3:80	3 sources
destination 198.51.100.4:80	2 sources
destination 198.51.100.17:80	1 source
destination 198.51.100.69:443	1 source

Figure 24: Aggregated flows for source count

8.4. Traffic Time-Series per Source with Counter Distribution

Returning to the example in [Section 8.1](#), note that our source data contains some flows with durations longer than the imposed interval of five minutes. The default method for dealing with such flows is to account them to the interval containing the flow's start time.

In this example, the same data is aggregated using the same arrangement of operations and the same output template as the as in [Section 8.1](#), but using a different counter distribution policy, Simple Uniform Distribution, as described in [Section 5.1.1](#). In order to do this, the Exporting Process first exports the Aggregate Counter Distribution Options Template, as in Figure 25.

```
templateId(12)[2]{scope}  
valueDistributionMethod(TBD10)[1]
```

Figure 25: Aggregate Counter Distribution Options Template

This is followed by an Aggregate Counter Distribution Record described by this Template; assuming the output template in Figure 10 has ID 257, this would appear as in Figure 26.

```
templateId 257: valueDistributionMethod 4 (Simple Uniform)
```

Figure 26: Aggregate Counter Distribution Record

[EDITOR'S NOTE: redo these in boxdiagrams?]

Following metadata export, the aggregation steps follow as before. However, two long flows are distributed across multiple intervals in the interval imposition step, as indicated with "*" in Figure 27. Note the uneven distribution of the three-interval, 11200-octet flow into three Partially Aggregated Flows of 3733, 3733, and 3734 octets; this ensures no cumulative error is injected by the interval distribution step.

9:00:00.000-9:05:00.000	192.0.2.2:47113	-> 192.0.2.131:53	(17)	119
9:00:00.000-9:05:00.000	192.0.2.2:22153	-> 192.0.2.131:53	(17)	83
9:00:00.000-9:05:00.000	192.0.2.2:52420	-> 198.51.100.2:443	(6)	1637
9:00:00.000-9:05:00.000	192.0.2.3:56047	-> 192.0.2.131:53	(17)	111
9:00:00.000-9:05:00.000	192.0.2.3:41183	-> 198.51.100.67:80	(6)	16838
9:00:00.000-9:05:00.000	192.0.2.2:17606	-> 198.51.100.68:80	(6)	11538
9:00:00.000-9:05:00.000	192.0.2.3:47113	-> 192.0.2.131:53	(17)	119
9:00:00.000-9:05:00.000	192.0.2.3:48458	-> 198.51.100.133:80	(6)	2973
9:00:00.000-9:05:00.000	192.0.2.4:61295	-> 198.51.100.2:443	(6)	8350
9:00:00.000-9:05:00.000	203.0.113.3:41256	-> 198.51.100.133:80	(6)	778
9:00:00.000-9:05:00.000	203.0.113.3:51662	-> 198.51.100.3:80	(6)	883
* 9:00:00.000-9:05:00.000	192.0.2.2:37581	-> 198.51.100.2:80	(6)	7710
* 9:00:00.000-9:05:00.000	203.0.113.3:39586	-> 198.51.100.17:80	(6)	3733
9:05:00.000-9:10:00.000	203.0.113.3:52572	-> 198.51.100.2:443	(6)	1637
9:05:00.000-9:10:00.000	203.0.113.3:49914	-> 197.51.100.133:80	(6)	561
9:05:00.000-9:10:00.000	192.0.2.2:50824	-> 198.51.100.2:443	(6)	1899
9:05:00.000-9:10:00.000	192.0.2.3:34597	-> 198.51.100.3:80	(6)	1284
9:05:00.000-9:10:00.000	203.0.113.3:58907	-> 198.51.100.4:80	(6)	2670
* 9:05:00.000-9:10:00.000	192.0.2.2:37581	-> 198.51.100.2:80	(6)	7710
* 9:05:00.000-9:10:00.000	203.0.113.3:39586	-> 198.51.100.17:80	(6)	3733
9:10:00.000-9:15:00.000	192.0.2.4:22478	-> 192.0.2.131:53	(17)	75
9:10:00.000-9:15:00.000	192.0.2.4:49513	-> 198.51.100.68:80	(6)	3374
9:10:00.000-9:15:00.000	192.0.2.4:64832	-> 198.51.100.67:80	(6)	138
9:10:00.000-9:15:00.000	192.0.2.3:60833	-> 198.51.100.69:443	(6)	2325
* 9:10:00.000-9:15:00.000	203.0.113.3:39586	-> 198.51.100.17:80	(6)	3734
9:10:00.000-9:15:00.000	192.0.2.2:19638	-> 198.51.100.3:80	(6)	2869
9:10:00.000-9:15:00.000	192.0.2.3:40429	-> 198.51.100.4:80	(6)	18289

Figure 27: Distirbuted interval imposition for time series per source

Subsequent steps are as in [Section 8.1](#); the results, to be exported using Figure 10, are shown in Figure 28, with Aggregated Flows differing from the previous example indicated by "*".

*	9:00:00.000-9:05:00.000	192.0.2.2	21087
	9:00:00.000-9:05:00.000	192.0.2.3	20041
	9:00:00.000-9:05:00.000	192.0.2.4	8350
*	9:00:00.000-9:05:00.000	203.0.113.3	9394
*	9:05:00.000-9:10:00.000	192.0.2.2	9609
	9:05:00.000-9:10:00.000	192.0.2.3	1284
*	9:05:00.000-9:10:00.000	203.0.113.3	8601
	9:10:00.000-9:15:00.000	192.0.2.2	2869
	9:10:00.000-9:15:00.000	192.0.2.3	20594
	9:10:00.000-9:15:00.000	192.0.2.4	3587
*	9:10:00.000-9:15:00.000	203.0.113.3	3734

Figure 28: Aggregated Flows for time series per source with counter distribution

9. Security Considerations

This document specifies the operation of an Intermediate Aggregation Process with the IPFIX Protocol; the Security Considerations for the protocol itself in [Section 11](#) [RFC-EDITOR NOTE: verify section number] of [\[I-D.ietf-ipfix-protocol-rfc5101bis\]](#) therefore apply. In the common case that aggregation is performed on a Mediator, the Security Considerations for Mediators in [Section 9 of \[RFC6183\]](#) apply as well.

As mentioned in [Section 3](#), certain aggregation operations may tend to have an anonymizing effect on flow data by obliterating sensitive identifiers. Aggregation may also be combined with anonymization within a Mediator, or as part of a chain of Mediators, to further leverage this effect. In any case in which an Intermediate Aggregation Process is applied as part of a data anonymization or protection scheme, or is used together with anonymization as described in [\[RFC6235\]](#), the Security Considerations in [Section 9 of \[RFC6235\]](#) apply.

10. IANA Considerations

This document specifies the creation of new IPFIX Information Elements in the IPFIX Information Element registry located at <http://www.iana.org/assignments/ipfix>, as defined in [Section 7](#) above. IANA has assigned Information Element numbers to these Information Elements, and entered them into the registry.

[NOTE for IANA: The text TBDn should be replaced with the respective assigned Information Element numbers where they appear in this document. Note that the deltaFlowCount Information Element has been

assigned the number 3, as it is compatible with the corresponding existing (reserved) NetFlow v9 Information Element. Other Information Element numbers should be assigned outside the NetFlow V9 compatibility range, as these Information Elements are not supported by NetFlow V9.]

11. Acknowledgments

Special thanks to Elisa Boschi for early work on the concepts laid out in this document. Thanks to Lothar Braun and Christian Henke for their reviews. This work is materially supported by the European Union Seventh Framework Programme under grant agreement 257315 (DEMONS).

12. References

12.1. Normative References

- [I-D.ietf-ipfix-protocol-rfc5101bis]
Claise, B. and B. Trammell, "Specification of the IP Flow Information eXport (IPFIX) Protocol for the Exchange of IP Traffic Flow Information",
[draft-ietf-ipfix-protocol-rfc5101bis-00](#) (work in progress), November 2011.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.

12.2. Informative References

- [RFC3917] Quittek, J., Zseby, T., Claise, B., and S. Zander, "Requirements for IP Flow Information Export (IPFIX)", [RFC 3917](#), October 2004.
- [RFC5103] Trammell, B. and E. Boschi, "Bidirectional Flow Export Using IP Flow Information Export (IPFIX)", [RFC 5103](#), January 2008.
- [RFC5153] Boschi, E., Mark, L., Quittek, J., Stiernerling, M., and P. Aitken, "IP Flow Information Export (IPFIX) Implementation Guidelines", [RFC 5153](#), April 2008.
- [RFC5470] Sadasivan, G., Brownlee, N., Claise, B., and J. Quittek, "Architecture for IP Flow Information Export", [RFC 5470](#), March 2009.

- [RFC5472] Zseby, T., Boschi, E., Brownlee, N., and B. Claise, "IP Flow Information Export (IPFIX) Applicability", [RFC 5472](#), March 2009.
- [RFC5476] Claise, B., Johnson, A., and J. Quittek, "Packet Sampling (PSAMP) Protocol Specifications", [RFC 5476](#), March 2009.
- [RFC5610] Boschi, E., Trammell, B., Mark, L., and T. Zseby, "Exporting Type Information for IP Flow Information Export (IPFIX) Information Elements", [RFC 5610](#), July 2009.
- [RFC5655] Trammell, B., Boschi, E., Mark, L., Zseby, T., and A. Wagner, "Specification of the IP Flow Information Export (IPFIX) File Format", [RFC 5655](#), October 2009.
- [RFC5835] Morton, A. and S. Van den Berghe, "Framework for Metric Composition", [RFC 5835](#), April 2010.
- [RFC5982] Kobayashi, A. and B. Claise, "IP Flow Information Export (IPFIX) Mediation: Problem Statement", [RFC 5982](#), August 2010.
- [RFC6183] Kobayashi, A., Claise, B., Muenz, G., and K. Ishibashi, "IP Flow Information Export (IPFIX) Mediation: Framework", [RFC 6183](#), April 2011.
- [RFC6235] Boschi, E. and B. Trammell, "IP Flow Anonymization Support", [RFC 6235](#), May 2011.
- [I-D.ietf-ipfix-mediation-protocol]
Claise, B., Kobayashi, A., and B. Trammell, "Specification of the Protocol for IPFIX Mediation", [draft-ietf-ipfix-mediation-protocol-00](#) (work in progress), December 2011.
- [I-D.ietf-ipfix-ie-doctors]
Claise, B. and B. Trammell, "Guidelines for Authors and Reviewers of IPFIX Information Elements", [draft-ietf-ipfix-ie-doctors-01](#) (work in progress), February 2012.
- [I-D.ietf-ipfix-configuration-model]
Muenz, G., Claise, B., and P. Aitken, "Configuration Data Model for IPFIX and PSAMP", [draft-ietf-ipfix-configuration-model-10](#) (work in progress), July 2011.
- [I-D.ietf-ipfix-flow-selection-tech]

Zseby, T. and L. Peluso, "Flow Selection Techniques",
[draft-ietf-ipfix-flow-selection-tech-09](#) (work in
progress), November 2011.

[iana-ipfix-assignments]

Internet Assigned Numbers Authority, "IP Flow Information
Export Information Elements
(<http://www.iana.org/assignments/ipfix/ipfix.xml>)".

Authors' Addresses

Brian Trammell
Swiss Federal Institute of Technology Zurich
Gloriastrasse 35
8092 Zurich
Switzerland

Phone: +41 44 632 70 13
Email: trammell@tik.ee.ethz.ch

Arno Wagner
Consecom AG
Bleicherweg 64a
8002 Zurich
Switzerland

Email: arno@wagner.name

Benoit Claise
Cisco Systems, Inc.
De Kleetlaan 6a b1
1831 Diagem
Belgium

Phone: +32 2 704 5622
Email: bclaise@cisco.com

