

IPFIX Working Group  
Internet-Draft  
Intended status: Standards Track  
Expires: July 23, 2012

T. Dietz, Ed.  
NEC Europe, Ltd.  
A. Kobayashi  
NTT PF Labs.  
B. Claise  
Cisco Systems, Inc.  
G. Muenz  
Technische Universitaet Muenchen  
January 20, 2012

Definitions of Managed Objects for IP Flow Information Export  
draft-ietf-ipfix-rfc5815bis-01.txt

## Abstract

This document defines managed objects for IP Flow Information eXport (IPFIX). These objects provide information for monitoring IPFIX Exporters and IPFIX Collectors including the basic configuration information.

## Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on July 23, 2012.

## Copyright Notice

Copyright (c) 2012 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect

Internet-Draft

IPFIX MIB

January 2012

to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

<a href="#">1.</a>	<a href="#">Introduction . . . . .</a>	<a href="#">3</a>
<a href="#">2.</a>	<a href="#">IPFIX Documents Overview . . . . .</a>	<a href="#">4</a>
<a href="#">3.</a>	<a href="#">The Internet-Standard Management Framework . . . . .</a>	<a href="#">5</a>
<a href="#">4.</a>	<a href="#">Terminology . . . . .</a>	<a href="#">6</a>
<a href="#">5.</a>	<a href="#">Structure of the IPFIX MIB . . . . .</a>	<a href="#">7</a>
<a href="#">5.1.</a>	<a href="#">The Transport Session Table . . . . .</a>	<a href="#">7</a>
<a href="#">5.2.</a>	<a href="#">The Template Table . . . . .</a>	<a href="#">9</a>
<a href="#">5.3.</a>	<a href="#">The Template Definition Table . . . . .</a>	<a href="#">11</a>
<a href="#">5.4.</a>	<a href="#">The Export Table . . . . .</a>	<a href="#">12</a>
<a href="#">5.5.</a>	<a href="#">The Metering Process Table . . . . .</a>	<a href="#">14</a>
<a href="#">5.6.</a>	<a href="#">The Observation Point Table . . . . .</a>	<a href="#">15</a>
<a href="#">5.7.</a>	<a href="#">The Selection Process Table . . . . .</a>	<a href="#">16</a>
<a href="#">5.8.</a>	<a href="#">The Statistical Tables . . . . .</a>	<a href="#">16</a>
<a href="#">5.8.1.</a>	<a href="#">The Transport Session Statistical Table . . . . .</a>	<a href="#">17</a>
<a href="#">5.8.2.</a>	<a href="#">The Template Statistical Table . . . . .</a>	<a href="#">17</a>
<a href="#">5.8.3.</a>	<a href="#">The Metering Process Statistical Table . . . . .</a>	<a href="#">17</a>
<a href="#">5.8.4.</a>	<a href="#">The Selection Process Statistical Table . . . . .</a>	<a href="#">17</a>
<a href="#">6.</a>	<a href="#">Structure of the IPFIX SELECTOR MIB . . . . .</a>	<a href="#">18</a>
<a href="#">6.1.</a>	<a href="#">The Selector Functions . . . . .</a>	<a href="#">18</a>
<a href="#">7.</a>	<a href="#">Relationship to Other MIB Modules . . . . .</a>	<a href="#">21</a>
<a href="#">7.1.</a>	<a href="#">Relationship to the ENTITY MIB and IF MIB . . . . .</a>	<a href="#">21</a>
<a href="#">7.2.</a>	<a href="#">MIB Modules Required for IMPORTS . . . . .</a>	<a href="#">21</a>
<a href="#">8.</a>	<a href="#">MIB Definitions . . . . .</a>	<a href="#">22</a>
<a href="#">8.1.</a>	<a href="#">IPFIX MIB Definition . . . . .</a>	<a href="#">22</a>
<a href="#">8.2.</a>	<a href="#">IPFIX SELECTOR MIB Definition . . . . .</a>	<a href="#">57</a>
<a href="#">9.</a>	<a href="#">Security Considerations . . . . .</a>	<a href="#">62</a>
<a href="#">10.</a>	<a href="#">IANA Considerations . . . . .</a>	<a href="#">64</a>
<a href="#">11.</a>	<a href="#">Acknowledgments . . . . .</a>	<a href="#">65</a>
<a href="#">12.</a>	<a href="#">References . . . . .</a>	<a href="#">66</a>
<a href="#">12.1.</a>	<a href="#">Normative References . . . . .</a>	<a href="#">66</a>
<a href="#">12.2.</a>	<a href="#">Informative References . . . . .</a>	<a href="#">67</a>
	<a href="#">Authors' Addresses . . . . .</a>	<a href="#">68</a>

Internet-Draft

IPFIX MIB

January 2012

## 1. Introduction

This document defines two MIB modules for monitoring IP Flow Information eXport (IPFIX) Devices including Exporters and Collectors. Most of the objects defined by the IPFIX MIB module MUST be implemented. Some objects MAY be implemented corresponding to the functionality implemented in the equipment. Since the IPFIX architecture [[RFC5470](#)] foresees the possibility of using Filtering and/or Sampling functions to reduce the data volume, this document also provides the IPFIX SELECTOR MIB module, which contains the standardized selection methods and is controlled by IANA. The full configuration of the IPFIX Metering Process is out of the scope of these MIB modules.

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)].

## [2.](#) IPFIX Documents Overview

The IPFIX protocol provides network administrators with access to IP Flow information. The architecture for the export of measured IP Flow information out of an IPFIX Exporting Process to a Collecting Process is defined in [\[RFC5470\]](#), per the requirements defined in [\[RFC3917\]](#). The protocol document [\[RFC5101\]](#) specifies how IPFIX Data Records and Templates are carried via a congestion-aware transport protocol from IPFIX Exporting Processes to IPFIX Collecting Processes. IPFIX has a formal description of IPFIX Information Elements, their name, type and additional semantic information, as specified in [\[RFC5102\]](#). Finally, [\[RFC5472\]](#) describes what type of applications can use the IPFIX protocol and how they can use the information provided. It furthermore shows how the IPFIX framework relates to other architectures and frameworks.

It is assumed that Flow metering, export, and collection is performed according to the IPFIX architecture defined in [\[RFC5470\]](#). The monitored configuration parameters of the export and collection of Flow Templates and Data Records is modeled according to [\[RFC5101\]](#). Packet selection methods that may be optionally used by the IPFIX Metering Process are not considered in this MIB module. They are defined in the Packet Sampling (PSAMP) framework [\[RFC5474\]](#) and Sampling techniques [\[RFC5475\]](#) documents. Nevertheless, the basis for defining Sampling and Filtering functions is given with the IPFIX SELECTOR MIB module. Since the PSAMP export protocol [\[RFC5476\]](#) is based on the IPFIX protocol, the Sampling and Filtering functions can be added to the IPFIX SELECTOR MIB module as needed.

---

Internet-Draft

IPFIX MIB

January 2012

### [3.](#) The Internet-Standard Management Framework

For a detailed overview of the documents that describe the current Internet-Standard Management Framework, please refer to [section 7 of RFC 3410](#) [RFC3410].

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. MIB objects are generally accessed through the Simple Network Management Protocol (SNMP). Objects in the MIB are defined using the mechanisms defined in the Structure of Management Information (SMI). This memo specifies MIB modules that are compliant to the SMIV2, which is described in STD 58, [RFC 2578](#) [RFC2578], STD 58, [RFC 2579](#) [RFC2579] and STD 58, [RFC 2580](#) [RFC2580].

#### [4.](#) Terminology

The definitions of the basic terms like IP Traffic Flow, Exporting Process, Collecting Process, Observation Points, etc. can be found in the IPFIX protocol document [[RFC5101](#)].

## [5.](#) Structure of the IPFIX MIB

The IPFIX MIB module consists of seven main tables, the Transport Session table, the Template table and the corresponding Template Definition table, the Export table, the Metering Process table, the Observation Point table, and the Selection Process table. Since the IPFIX architecture [[RFC5470](#)] foresees the possibility of using Filtering and/or Sampling functions to reduce the data volume, the

MIB module provides the basic objects for these functions with the Selection Process table. The IPFIX SELECTOR MIB module defined in the next section provides the standard Filtering and Sampling functions that can be referenced in the ipfixSelectionProcessTable.

All remaining objects contain statistical values for the different tables contained in the MIB module.

The following subsections describe all tables in the IPFIX MIB module.

### [5.1.](#) The Transport Session Table

The Transport Session is the basis of the MIB module. The Transport Session table (ipfixTransportSessionTable) contains all Transport Sessions between Exporter and Collector. The table specifies the transport layer protocol of the Transport Session and, depending on that protocol, further parameters for the Transport Session. In the case of UDP and TCP, these are the source and destination address as well as the source and destination port. For Stream Control Transmission Protocol (SCTP), the table contains the SCTP Assoc Id, which is the index for the SCTP association in the SCTP MIB module [[RFC3873](#)]. The mode of operation of the device, i.e., if the Transport Session is used for collecting or exporting is given in the ipfixTransportSessionDeviceMode object. Further on, it contains the configured refresh parameters for Templates and Options Templates that are used across unreliable connections as UDP. Finally, the IPFIX version that is exported or collected by this Transport Session and a status of the Transport Session is given in the table.

To illustrate the use of the above tables, let us assume the following scenario: we have an Exporter on IP address 192.0.2.22 and a Collector on IP address 192.0.2.37. The Exporter uses TCP to export Templates and Data Records. The same Exporter also exports, with UDP, to a Collector with the IP address of 192.0.2.44. This would lead to the following Transport Session table on the Exporter:



```

|
+- ipfixTransportSessionEntry (1)
|
+- index (5) (ipfixTransportSessionIndex)
|   +- ipfixTransportSessionIndex (1) = 5
|   +- ipfixTransportSessionProtocol (2) = 6 (TCP)
|   +- ipfixTransportSessionSourceAddressType (3) = 1 (ipv4)
|   +- ipfixTransportSessionSourceAddress (4) = 192.0.2.22
|   +- ipfixTransportSessionDestinationAddressType (5) = 1 (ipv4)
|   +- ipfixTransportSessionDestinationAddress (6) = 192.0.2.37
|   +- ipfixTransportSessionSourcePort (7) = 7653
|   +- ipfixTransportSessionDestinationPort (8) = 4739
|   +- ipfixTransportSessionSctpAssocId (9) = 0
|   +- ipfixTransportSessionDeviceMode (10) = exporting(1)
|   +- ipfixTransportSessionTemplateRefreshTimeout (11) = 0
|   +- ipfixTransportSessionOptionTemplateRefreshTimeout (12) = 0
|   +- ipfixTransportSessionTemplateRefreshPacket (13) = 0
|   +- ipfixTransportSessionOptionTemplateRefreshPacket (14) = 0
|   +- ipfixTransportSessionIpfixVersion (15) = 10
|   +- ipfixTransportSessionStatus (16) = 2 (active)
|
|
|
+- index (11) (ipfixTransportSessionIndex)
|   +- ipfixTransportSessionIndex (1) = 11
|   +- ipfixTransportSessionProtocol (2) = 17 (UDP)
|   +- ipfixTransportSessionSourceAddressType (3) = 1 (ipv4)
|   +- ipfixTransportSessionSourceAddress (4) = 192.0.2.22
|   +- ipfixTransportSessionDestinationAddressType (5) = 1 (ipv4)
|   +- ipfixTransportSessionDestinationAddress (6) = 192.0.2.44
|   +- ipfixTransportSessionSourcePort (7) = 14287
|   +- ipfixTransportSessionDestinationPort (8) = 4739
|   +- ipfixTransportSessionSctpAssocId (9) = 0
|   +- ipfixTransportSessionDeviceMode (10) = exporting(1)
|   +- ipfixTransportSessionTemplateRefreshTimeout (11) = 100
|   +- ipfixTransportSessionOptionTemplateRefreshTimeout (12)
|       |
|       | = 100
|   +- ipfixTransportSessionTemplateRefreshPacket (13) = 10
|   +- ipfixTransportSessionOptionTemplateRefreshPacket (14) = 10
|   +- ipfixTransportSessionIpfixVersion (15) = 10
|   +- ipfixTransportSessionStatus (16) = 2 (active)

```

The values in brackets are the OID numbers. The Collectors would then have the same entry except that the index would most likely differ and the ipfixTransportSessionDeviceMode would be collecting(2).

## [5.2.](#) The Template Table

The Template table lists all Templates (including Options Templates) that are sent (by an Exporter) or received (by a Collector). The (Options) Templates are unique per Transport Session, which also gives the device mode (Exporter or Collector) and Observation Domain; thus, the table is indexed by:

- o the Transport Session Index (`ipfixTransportSessionIndex`)
- o and the Observation Domain Id (`ipfixTemplateObservationDomainId`).

It contains the Set Id and an access time denoting the time when the (Options) Template was last sent or received.

To resume the above example, the Exporter may want to export a Template and an Options Template for each Transport Session defined above. This leads to the following Template table defining Template and Options Template:

Internet-Draft

IPFIX MIB

January 2012

```
ipfixTemplateTable (3)
|
+-- ipfixTemplateEntry (1)
|
|   +- index (5) (ipfixTransportSessionIndex)
|   |   +- index (3) (ipfixTemplateObservationDomainId)
|   |   |   + index (257) (ipfixTemplateId)
|   |   |   |   +- ipfixTemplateObservationDomainId (1) = 3
|   |   |   |   +- ipfixTemplateId (2) = 257
|   |   |   |   +- ipfixTemplateSetId (3) = 2
|   |   |   |   +- ipfixTemplateAccessTime (4)
|   |   |   |       = 2008-7-1,12:49:11.2,+2:0
|   |   |   |
|   |   + index (264) (ipfixTemplateId)
|   |   |   +- ipfixTemplateObservationDomainId (1) = 3
|   |   |   +- ipfixTemplateId (2) = 264
|   |   |   +- ipfixTemplateSetId (3) = 3
|   |   |   +- ipfixTemplateAccessTime (4)
|   |   |       = 2008-7-1,12:47:04.8,+2:0
|   |   .
|   |   .
|   |   .
|   +- index (11) (ipfixTransportSessionIndex)
|   |   +- index (3) (ipfixTemplateObservationDomainId)
|   |   |   + index (273) (ipfixTemplateId)
|   |   |   |   +- ipfixTemplateObservationDomainId (1) = 3
|   |   |   |   +- ipfixTemplateId (2) = 273
|   |   |   |   +- ipfixTemplateSetId (3) = 2
|   |   |   |   +- ipfixTemplateAccessTime (4)
|   |   |   |       = 2008-7-1,12:49:11.2,+2:0
|   |   |   |
|   |   + index (289) (ipfixTemplateId)
|   |   |   +- ipfixTemplateObservationDomainId (1) = 3
|   |   |   +- ipfixTemplateId (2) = 289
|   |   |   +- ipfixTemplateSetId (3) = 3
|   |   |   +- ipfixTemplateAccessTime (4)
|   |   |       = 2008-7-1,12:47:04.8,+2:0
```

We assume that the Transport Session that is stored with index 5 in

the Transport Session table of the Exporter is stored with index 17 in the Transport Session table of the (corresponding) Collector. Then, the Template table would look as follows:

```
ipfixTemplateTable (3)
|
+-- ipfixTemplateEntry (1)
|
|   +- index (17) (ipfixTransportSessionIndex)
|   +- index (3) (ipfixTemplateObservationDomainId)
|   + index (257) (ipfixTemplateId)
|   | +- ipfixTemplateObservationDomainId (1) = 3
|   | +- ipfixTemplateId (2) = 257
|   | +- ipfixTemplateSetId (3) = 2
|   | +- ipfixTemplateAccessTime (4)
|   |                                     = 2008-7-1,12:49:11.8,+2:0
|   |
|   + index (264) (ipfixTemplateId)
|   +- ipfixTemplateObservationDomainId (1) = 3
|   +- ipfixTemplateId (2) = 264
|   +- ipfixTemplateSetId (3) = 3
|   +- ipfixTemplateAccessTime (4)
|                                       = 2008-7-1,12:47:05.3,+2:0
```

The table on the second Collector would be analogous to the one shown above.

### [5.3.](#) The Template Definition Table

The Template Definition table lists all the Information Elements contained in a Template or Options Template. Therefore, it has the same indexes as the corresponding Template table plus the Template Id. Its own index denotes the order of the Information Element inside the Template. Besides the Information Element Id and the length of the encoded value, the table contains the enterprise number for enterprise-specific Information Elements and flags for each

Information Element. The flags indicate if the Information Element is used for scoping or as a Flow Key.

To resume the above example again, the Exporter is configured to export the octets received and dropped at the Observation Point since the last export of these values. In addition, it exports the start and end time of the Flow relative to the timestamp contained in the IPFIX header. This leads to the following Template Definition table on the Exporter:

```
ipfixTemplateDefinitionTable (4)
|
+-- ipfixTemplateDefinitionEntry (1)
|
|   +- index (5) (ipfixTransportSessionIndex)
|   |   +- index (3) (ipfixTemplateObservationDomainId)
|   |   |   + index (257) (ipfixTemplateId)
|   |   |   |   +- index (1) (ipfixTemplateDefinitionIndex)
|   |   |   |   |   +- ipfixTemplateDefinitionIndex (1) = 1
|   |   |   |   |   +- ipfixTemplateDefinitionIeId (2) = 158
|   |   |   |   |   |   (flowStartDeltaMicroseconds)
|   |   |   |   |   +- ipfixTemplateDefinitionIeLength (3) = 4
|   |   |   |   |   +- ipfixTemplateDefinitionEnterprise (4) = 0
|   |   |   |   |   +- ipfixTemplateDefinitionFlags (5) = 0
|   |   |   |   |
|   |   |   |   +- index (2) (ipfixTemplateDefinitionIndex)
|   |   |   |   |   +- ipfixTemplateDefinitionIndex (1) = 2
|   |   |   |   |   +- ipfixTemplateDefinitionIeId (2) = 159
|   |   |   |   |   |   (flowEndDeltaMicroseconds)
|   |   |   |   |   +- ipfixTemplateDefinitionIeLength (3) = 4
|   |   |   |   |   +- ipfixTemplateDefinitionEnterprise (4) = 0
|   |   |   |   |   +- ipfixTemplateDefinitionFlags (5) = 0
|   |   |   |   |
|   |   |   |   +- index (3) (ipfixTemplateDefinitionIndex)
|   |   |   |   |   +- ipfixTemplateDefinitionIndex (1) = 3
```

```

|   +- ipfixTemplateDefinitionIeId (2) = 1
|   |
|   |                               (octetDeltaCount)
|   +- ipfixTemplateDefinitionIeLength (3) = 8
|   +- ipfixTemplateDefinitionEnterprise (4) = 0
|   +- ipfixTemplateDefinitionFlags (5) = 0
|
+- index (4) (ipfixTemplateDefinitionIndex)
  +- ipfixTemplateDefinitionIndex (1) = 4
  +- ipfixTemplateDefinitionIeId (2) = 132
  |
  |                               (droppedOctetDeltaCount)
  +- ipfixTemplateDefinitionIeLength (3) = 8
  +- ipfixTemplateDefinitionEnterprise (4) = 0
  +- ipfixTemplateDefinitionFlags (5) = 0

```

The corresponding table entry on the Collector is the same except that it would have another `ipfixTransportSessionIndex`, e.g., 17 as in the previous example.

#### 5.4. The Export Table

On Exporters, the Export table (`ipfixExportTable`) can be used to support features like failover, load-balancing, duplicate export to several Collectors, etc. The table has three indexes that link an

entry with:

- o the Metering Process table (`ipfixMeteringProcessCacheId`, see below)
- o and the Transport Session table (`ipfixTransportSessionIndex`).

Those entries with the same `ipfixExportIndex` and the same `ipfixMeteringProcessCacheId` define a Transport Session group. The member type for each group member describes its functionality. All Transport Sessions referenced in this table MUST have the `ipfixTransportSessionDeviceMode exporting(1)`.

If the Exporter does not use Transport Session grouping, then each `ipfixExportIndex` contains a single `ipfixMeteringProcessCacheId`, and thus a single Transport Session (`ipfixTransportSessionIndex`) and this session MUST have the member type `primary(1)`.

For failover, a Transport Session group can contain one Transport Session with member type "primary" and several Transport Sessions with type secondary(2). Entries with other member types are not allowed for that type of group. For load-balancing or parallel export, all Transport Sessions in the group MUST have the same member type, either loadBalancing(4) or parallel(3).

The algorithms used for failover or load-balancing are out of the scope of this document.

To continue the example, we assume that the Exporter uses the two connections shown in the examples above as one primary Transport Session protected by a secondary Transport Session. The Exporter then has the following entries in the ipfixExportTable:

```
ipfixExportTable (5)
|
+-- ipfixExportEntry (1)
|
|   +- index (7) (ipfixExportIndex)
|   |   +- index (9) (ipfixMeteringProcessCacheId)
|   |   |   +- index (5) (ipfixTransportSessionIndex)
|   |   |   |   +- ipfixExportIndex (1) = 7
|   |   |   |   +- ipfixExportMemberType (2) = 1 (primary)
|   |   |   |
|   |   |   +- index (11) (ipfixTransportSessionIndex)
```

```

|           +- ipfixExportIndex (1) = 7
|           +- ipfixExportMemberType (2) = 2 (secondary)
|
+- index (8) (ipfixExportIndex)
  +- index (9) (ipfixMeteringProcessCacheId)
    +- index (5) (ipfixTransportSessionIndex)
      | +- ipfixExportIndex (1) = 8
      | +- ipfixExportMemberType (2) = 2 (secondary)
    +- index (11) (ipfixTransportSessionIndex)
      +- ipfixExportIndex (1) = 8
      +- ipfixExportMemberType (2) = 1 (primary)

```

The example shows that the Exporter uses the Metering Process Cache 9, explained below, to export IPFIX Data Records for the Transport Sessions 5 and 11. The Templates 257 and 264 defined above are exported within Transport Session 5, and the Templates 273 and 289 are exported within Transport Session 11. If we assume that Templates 257 and 264 are identical, then the Collector that receives Transport Session 11 is a backup for the Collector of Transport Session 5.

#### [5.5.](#) The Metering Process Table

The Metering Process, as defined in [[RFC5101](#)], consists of a set of functions. Maintaining the Flow Records is one of them. This function is responsible for passing the Flow Records to the Exporting Process and also for detecting Flow expiration. The Flow Records that are maintained by the Metering Process can be grouped by the Observation Points at which they are observed. The instance that maintains such a group of Flow Records is a kind of cache. For this reason, the Metering Process table (ipfixMeteringProcessTable) is indexed by cache Ids (ipfixMeteringProcessCacheId). Each cache can be maintained by a separate instance of the Metering Process. To specify the Observation Point(s) where the Flow Records are gathered, the ipfixMeteringProcessObservationPointGroupRef may contain an ipfixObservationPointGroupId from the Observation Point table (ipfixObservationPointTable) described in the next section. If an

Observation Point is not specified for the Flow Records, the ipfixMeteringProcessObservationPointGroupRef MUST be zero(0). The timeouts (ipfixMeteringProcessCacheActiveTimeout and ipfixMeteringProcessCacheInactiveTimeout) specify when Flows are



expired.

```
ipfixMeteringProcessTable (6)
|
+-- ipfixMeteringProcessEntry (1)
   |
   +- index (9) (ipfixMeteringProcessCacheId)
      +- ipfixMeteringProcessCacheId (1) = 9
      +- ipfixMeteringProcessObservationPointGroupRef (2) = 17
      +- ipfixMeteringProcessCacheActiveTimeout (3) = 100
      +- ipfixMeteringProcessCacheInactiveTimeout (4) = 100
```

#### [5.6.](#) The Observation Point Table

The Observation Point table (ipfixObservationPointTable) groups Observation Points with the ipfixObservationPointGroupId. Each entry contains the Observation Domain Id in which the Observation Point is located and a reference to the ENTITY MIB module [[RFC4133](#)] or the IF MIB module [[RFC2863](#)]. The objects in the ENTITY MIB module referenced by ipfixObservationPointPhysicalEntity or IF MIB module referenced by ipfixObservationPointPhysicalInterface denote the Observation Point. If no such index can be given in those modules, the references MUST be 0. If a reference is given in both object ipfixObservationPointPhysicalEntity and ipfixObservationPointPhysicalInterface, then both MUST point to the same physical interface. In addition, a direction can be given to render more specifically which Flow to monitor.

```

ipfixObservationPointTable (7)
|
+-- ipfixObservationPointEntry (1)
|
|   +- index (17) (ipfixObservationPointGroupId)
|   +- index (1) (ipfixObservationPointIndex)
|   |   +- ipfixObservationPointGroupId (1) = 17
|   |   +- ipfixObservationPointIndex (2) = 1
|   |   +- ipfixObservationPointObservationDomainId (3) = 3
|   |   +- ipfixObservationPointPhysicalEntity (4) = 6
|   |   +- ipfixObservationPointPhysicalInterface(5) = 0
|   |   +- ipfixObservationPointPhysicalEntityDirection (6)
|   |                                           = 3 (both)
|   |
|   +- index (2) (ipfixObservationPointIndex)
|   +- ipfixObservationPointGroupId (1) = 17
|   +- ipfixObservationPointIndex (2) = 2
|   +- ipfixObservationPointObservationDomainId (3) = 3
|   +- ipfixObservationPointPhysicalEntity (4) = 0
|   +- ipfixObservationPointPhysicalInterface (5) = 0
|   +- ipfixObservationPointPhysicalEntityDirection (6)
|   |                                           = 1 (ingress)

```

### [5.7.](#) The Selection Process Table

This table supports the usage of Filtering and Sampling functions, as described in [\[RFC5470\]](#). It contains lists of functions per Metering Process cache (ipfixMeteringProcessCacheId). The selection process index ipfixSelectionProcessIndex forms groups of selection methods that are applied to an observed packet stream. The selection process selector index (ipfixSelectionProcessSelectorIndex) indicates the order in which the functions are applied to the packets observed at the Observation Points associated with the Metering Process cache. The selection methods are applied in increasing order, i.e., selection methods with a lower ipfixSelectionProcessSelectorIndex are applied first. The functions are referred by object identifiers pointing to the function with its parameters. If the selection method does not use parameters, then it MUST point to the root of the function subtree (see also [Section 6](#)). If the function uses parameters, then it MUST point to an entry in the parameter table of the selection method. If no Filtering or Sampling function is used for a Metering Process, then an entry for the Metering Process SHOULD be created pointing to the Select All function (ipfixFuncSelectAll).

### [5.8.](#) The Statistical Tables

For the ipfixTransportSessionTable, the ipfixTemplateTable, the

statistical tables are defined that augment those tables. All the statistical tables contain a discontinuity object that holds a timestamp that denotes the time when a discontinuity event occurred to notify the management system that the counters contained in those tables might not be continuous anymore.

#### [5.8.1.](#) The Transport Session Statistical Table

The Transport Session Statistical table (ipfixTransportSessionStatsTable) augments the ipfixTransportSessionTable with statistical values. It contains the rate (in bytes per second) with which it receives or sends out IPFIX Messages, the number of bytes, packets, messages, Records, Templates and Options Templates received or sent and the number of messages that were discarded.

#### [5.8.2.](#) The Template Statistical Table

This table contains a statistical value for each Template. It augments the Template table (ipfixTemplateTable) and specifies the number of Data Records exported or collected for the Template.

#### [5.8.3.](#) The Metering Process Statistical Table

This table augments the Metering Process table (ipfixMeteringProcessTable). It contains the statistical values for the exported Data Records and the number of unused cache entries.

#### [5.8.4.](#) The Selection Process Statistical Table

This table augments the Selection Process table (ipfixSelectionProcessTable) and introduces two generic statistical values, the number of packets observed and the number of packets dropped by the selection method.

Internet-Draft

IPFIX MIB

January 2012

## [6.](#) Structure of the IPFIX SELECTOR MIB

The IPFIX SELECTOR MIB module defined in this section provides the standard Filtering and Sampling functions that can be referenced in the `ipfixSelectionProcessTable`. All standard Filtering and Sampling functions MUST be registered in the subtree under object `ipfixSelectorFunctions` (`iso.org.dod.internet.mgmt.mib-2.ipfixSelectorMIB`, or as numbers `1.3.6.1.2.1.194`). The top-level OIDs in the subtree under object `ipfixSelectorFunctions` MUST be registered in a subregistry maintained by IANA at <http://www.iana.org/assignments/smi-numbers>. The first entry in this subtree is the Select All function (`ipfixFuncSelectAll`) defined in this document as `{ipfixSelectorFunctions 1}`.

Further selector functions MUST be registered at IANA and are subject to Expert Review [[RFC5226](#)], i.e., review by one of a group of experts designated by an IETF Area Director. The group of experts MUST check the requested MIB objects for completeness and accuracy of the description. Requests for MIB objects that duplicate the functionality of existing objects SHOULD be declined. The smallest available OID SHOULD be assigned to a new MIB objects. The specification of new MIB objects SHOULD follow the structure specified in the Section [Section 6.1](#) and MUST be published using a well-established and persistent publication medium. The experts will initially be drawn from the Working Group Chairs and document editors of the IPFIX and PSAMP Working Groups.

### [6.1.](#) The Selector Functions

The following figure shows what the MIB tree usually should look like. It already contains the `ipfixFuncSelectAll`. The subtree in `ipfixFuncF2` gives the basic structure that all selection methods SHOULD follow.

```

ipfixSelectorFunctions
|
+- ipfixFuncSelectAll
| |
| +- ipfixFuncSelectAllAvail (is the function available?)
|
+- ipfixFuncF2
| |
| +- ipfixFuncF2Avail (is the function F2 available?)
| |
| +- ipfixFuncF2Parameters (a table with parameters)
...
|
+- ipfixFuncFn...

```

The selection method SHOULD be designed as a MIB subtree introduced by an object with the name `ipfixFunc` appended by a function name. The objects in this subtree SHOULD be prefixed by this name. If the function is named `Fx`, then we would start a subtree with an OID named `ipfixFuncFx`. This subtree should contain an object `ipfixFuncFxAvail` that has the type `TruthValue`. If a selection method takes parameters, the MIB should contain a table named `ipfixFuncFxParameters`, which should contain all the parameters that the selection method specifies. An entry in this table will be referenced by the IPFIX MIB module if the selection method with the parameters is used.

To illustrate the structure defined above, the following contains an example of a function `MyFunc` that holds three integer parameters `Param1`, `Param2`, and `Param3`. In the example, there are currently two instances of the parameters set defined with indexes 1 and 4.

```

ipfixSelectorFunctions (1)
|
+- ipfixFuncMyFunc (?)
|
| +- ipfixFuncMyFuncAvail (1) = true
| +- ipfixFuncMyFuncParameters (2)
| |
| | +- ipfixFuncMyFuncParametersEntry (1)
| | |

```

```

+- index (1) (ipfixFuncMyFuncParametersIndex)
|   +- ipfixFuncMyFuncParam1 (1) = 47
|   +- ipfixFuncMyFuncParam2 (2) = -128
|   +- ipfixFuncMyFuncParam3 (3) = 19
|
+- index(4) (ipfixFuncMyFuncParametersIndex)
   +- ipfixFuncMyFuncParam1 (1) = 19
   +- ipfixFuncMyFuncParam2 (2) = -1
   +- ipfixFuncMyFuncParam3 (3) = 728

```

If the function defined above is referenced in the IPFIX MIB module, the ipfixSelectionProcessTable would look as follows:

```

ipfixSelectionProcessTable (8)
|
+- ipfixSelectionProcessEntry (1)
|
|   +- index (9) (ipfixMeteringProcessCacheId)
|   +- index (1) (ipfixSelectionProcessIndex)
|   +- index (1) (ipfixSelectionProcessSelectorIndex)
|   |   +- ipfixSelectionProcessSelectorFunction (3)
|   |   |   = ipfixSelectorFunctions.?.2.1.4
|   +- index (2) (ipfixSelectionProcessSelectorIndex)
|   +- ipfixSelectionProcessSelectorFunction (3)
|   |   = ipfixSelectorFunctions.?.2.1.1

```

This means that for the ipfixMeteringProcessCacheId(9), a Selection Process with index 1 is created that applies two times the same function but with different parameter sets. First, the function MyFunc is applied with the parameters of the set with index 4 and the with the parameters of the set with index 1.

## [7.](#) Relationship to Other MIB Modules

Besides the usual imports from the SNMP Standards [[RFC2578](#)], [[RFC2579](#)], and [[RFC2580](#)], the IPFIX MIB module references the ENTITY MIB module [[RFC4133](#)] and the IF MIB module [[RFC2863](#)].

### [7.1.](#) Relationship to the ENTITY MIB and IF MIB

The Observation Point table (ipfixObservationPointTable) contains a reference to the ENTITY MIB module [[RFC4133](#)] (ipfixObservationPointPhysicalEntity) or the IF MIB module [[RFC2863](#)] (ipfixObservationPointPhysicalInterface). If the implementors of the

IPFIX MIB module want to specify the physical entity where Flows are observed, then they SHOULD also implement the ENTITY MIB and/or the IF MIB module. The implementation of the ENTITY MIB and/or IF MIB module is OPTIONAL. If one of them is not implemented, then all values of the respective column `ipfixObservationPointPhysicalEntity` or `ipfixObservationPointPhysicalInterface` in the Observation Point table are zero and the values of the `ipfixObservationPointPhysicalEntityDirection` columns are `unknown(0)`, if none of them are defined.

## 7.2. MIB Modules Required for IMPORTS

The IPFIX MIB module requires the modules SNMPv2-SMI [[RFC2578](#)], SNMPv2-TC [[RFC2579](#)], and SNMPv2-CONF [[RFC2580](#)]. Further on, it imports the textual conventions `InetAddressType` and `InetAddress` from the INET ADDRESS MIB module [[RFC4001](#)].

The IPFIX SELECTOR MIB module also requires the modules SNMPv2-SMI [[RFC2578](#)], SNMPv2-TC [[RFC2579](#)], and SNMPv2-CONF [[RFC2580](#)].

## 8. MIB Definitions

This section contains the definitions of the IPFIX-MIB module and the IPFIX-SELECTOR-MIB module. There are different mandatory groups defined for Collector and Exporter implementations. The statistical



objects are made OPTIONAL.

### 8.1. IPFIX MIB Definition

IPFIX-MIB DEFINITIONS ::= BEGIN

IMPORTS

MODULE-IDENTITY, OBJECT-TYPE, mib-2, Unsigned32, Counter64,  
Gauge32  
FROM SNMPv2-SMI -- [RFC2578](#)  
TimeStamp, DateAndTime  
FROM SNMPv2-TC -- [RFC2579](#)  
MODULE-COMPLIANCE, OBJECT-GROUP  
FROM SNMPv2-CONF -- [RFC2580](#)  
InterfaceIndexOrZero  
FROM IF-MIB -- [RFC2863](#)  
InetAddressType, InetAddress, InetPortNumber  
FROM INET-ADDRESS-MIB -- [RFC4001](#)  
PhysicalIndexOrZero  
FROM ENTITY-MIB; -- [RFC4133](#)

ipfixMIB MODULE-IDENTITY

LAST-UPDATED "201201200000Z" -- 20 January 2012

ORGANIZATION "IETF IPFIX Working Group"

CONTACT-INFO

"WG charter:

<http://www.ietf.org/html.charters/ipfix-charter.html>

Mailing Lists:

General Discussion: [ipfix@ietf.org](mailto:ipfix@ietf.org)

To Subscribe: <http://www1.ietf.org/mailman/listinfo/ipfix>

Archive:

<http://www1.ietf.org/mail-archive/web/ipfix/current/index.html>

Editor:

Thomas Dietz  
NEC Europe Ltd.  
NEC Laboratories Europe  
Network Research Division  
Kurfuersten-Anlage 36  
69115 Heidelberg  
Germany

Phone: +49 6221 4342-128  
Email: Thomas.Dietz@nw.neclab.eu

Atsushi Kobayashi  
NTT Information Sharing Platform Laboratories  
3-9-11 Midori-cho  
Musashino-shi  
180-8585  
Japan  
Phone: +81-422-59-3978  
Email: akoba@nttv6.net

Benoit Claise  
Cisco Systems, Inc.  
De Kleetlaan 6a b1  
Diegem 1831  
Belgium  
Phone: +32 2 704 5622  
Email: bclaise@cisco.com

Gerhard Muenz  
Technische Universitaet Muenchen  
Department of Informatics  
Chair for Network Architectures and Services (I8)  
Boltzmannstr. 3  
85748 Garching  
Germany  
Phone: +49 89 289-18008  
Email: muenz@net.in.tum.de  
URI: <http://www.net.in.tum.de/~muenz>

#### DESCRIPTION

"The IPFIX MIB defines managed objects for IP Flow Information eXport. These objects provide information about managed nodes supporting the IPFIX protocol, for Exporters as well as for Collectors.

Copyright (c) 2010 IETF Trust and the persons identified as authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, is permitted pursuant to, and subject to the license terms contained in, the Simplified BSD License set forth in [Section 4.c](#) of the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>).

- Note for RFC Editor: substitute [ThisRFC] with the newly
- assigned number in the following sections.

Internet-Draft

IPFIX MIB

January 2012

```
-- Revision history
```

```
REVISION      "201201200000Z"          -- 20 January 2012
DESCRIPTION
    "Fixed erratas from RFC 5815. Published as RFC [ThisRFC]."
```

```
REVISION      "201004190000Z"          -- 19 April 2010
DESCRIPTION
    "Initial version, published as RFC 5815."
```

```
::= { mib-2 193 }
```

```
--*****
-- Top Level Structure of the MIB
--*****
```

```
ipfixObjects      OBJECT IDENTIFIER ::= { ipfixMIB 1 }
ipfixConformance OBJECT IDENTIFIER ::= { ipfixMIB 2 }

ipfixMainObjects  OBJECT IDENTIFIER ::= { ipfixObjects 1 }
ipfixStatistics   OBJECT IDENTIFIER ::= { ipfixObjects 2 }
```

```
-----
-- 1.1: Objects used by all IPFIX implementations
-----
-----
-- 1.1.1: Transport Session Table
-----
```

```
ipfixTransportSessionTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF IpfixTransportSessionEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "This table lists the currently established Transport
        Sessions between an Exporting Process and a Collecting
        Process."
    ::= { ipfixMainObjects 1 }
```

```
ipfixTransportSessionEntry OBJECT-TYPE
    SYNTAX      IpfixTransportSessionEntry
    MAX-ACCESS  not-accessible
    STATUS      current
```

DESCRIPTION

"Defines an entry in the ipfixTransportSessionTable."

INDEX { ipfixTransportSessionIndex }

::= { ipfixTransportSessionTable 1 }

IpfixTransportSessionEntry ::=

SEQUENCE {

ipfixTransportSessionIndex	Unsigned32,
ipfixTransportSessionProtocol	Unsigned32,
ipfixTransportSessionSourceAddressType	InetAddressType,
ipfixTransportSessionSourceAddress	InetAddress,
ipfixTransportSessionDestinationAddressType	InetAddressType,
ipfixTransportSessionDestinationAddress	InetAddress,
ipfixTransportSessionSourcePort	InetPortNumber,
ipfixTransportSessionDestinationPort	InetPortNumber,
ipfixTransportSessionSctpAssocId	Unsigned32,
ipfixTransportSessionDeviceMode	INTEGER,
ipfixTransportSessionTemplateRefreshTimeout	Unsigned32,
ipfixTransportSessionOptionsTemplateRefreshTimeout	Unsigned32,
ipfixTransportSessionTemplateRefreshPacket	Unsigned32,
ipfixTransportSessionOptionsTemplateRefreshPacket	Unsigned32,
ipfixTransportSessionIpfixVersion	Unsigned32,
ipfixTransportSessionStatus	INTEGER

}

ipfixTransportSessionIndex OBJECT-TYPE

SYNTAX Unsigned32 (1..4294967295)

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"Locally arbitrary, but unique identifier of an entry in the ipfixTransportSessionTable. The value is expected to remain constant from a re-initialization of the entity's network management agent to the next re-initialization."

::= { ipfixTransportSessionEntry 1 }

ipfixTransportSessionProtocol OBJECT-TYPE

SYNTAX Unsigned32 (1..255)

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The transport protocol used for receiving or transmitting IPFIX Messages. Protocol numbers are assigned by IANA. A current list of all assignments is available from <http://www.iana.org/>."

REFERENCE

"[RFC 5101](#), Specification of the IP Flow Information Export (IPFIX) Protocol for the Exchange of IP Traffic Flow Information, [Section 10](#)."

::= { ipfixTransportSessionEntry 2 }

ipfixTransportSessionSourceAddressType OBJECT-TYPE

SYNTAX InetAddressType

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The type of address used for the source address, as specified in [RFC 4001](#). This object is used with protocols (specified in ipfixTransportSessionProtocol) like TCP (6) and UDP (17) that have the notion of addresses. SCTP (132) should use the ipfixTransportSessionSctpAssocId instead. If SCTP (132) or any other protocol without the notion of addresses is used, the object MUST be set to unknown(0)."

::= { ipfixTransportSessionEntry 3 }

ipfixTransportSessionSourceAddress OBJECT-TYPE

SYNTAX InetAddress

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The source address of the Exporter of the IPFIX Transport Session. This value is interpreted according to the value of ipfixTransportSessionAddressType as specified in [RFC 4001](#). This object is used with protocols (specified in ipfixTransportSessionProtocol) like TCP (6) and UDP (17) that have the notion of addresses. SCTP (132) should use the ipfixTransportSessionSctpAssocId instead. If SCTP (132) or any other protocol without the notion of addresses is used, the object MUST be set to a zero-length string."

::= { ipfixTransportSessionEntry 4 }

ipfixTransportSessionDestinationAddressType OBJECT-TYPE

SYNTAX        InetAddressType  
 MAX-ACCESS   read-only  
 STATUS        current  
 DESCRIPTION  
   "The type of address used for the destination address,  
   as specified in [RFC 4001](#). This object is used with protocols  
   (specified in ipfixTransportSessionProtocol) like TCP (6)  
   and UDP (17) that have the notion of addresses. SCTP (132)  
   should use the ipfixTransportSessionSctpAssocId instead.  
   If SCTP (132) or any other protocol without the notion of  
   addresses is used, the object MUST be set to unknown(0)."  
 ::= { ipfixTransportSessionEntry 5 }

ipfixTransportSessionDestinationAddress OBJECT-TYPE

SYNTAX        InetAddress  
 MAX-ACCESS   read-only  
 STATUS        current

DESCRIPTION

"The destination address of the Collector of the IPFIX

Transport Session. This value is interpreted according to  
 the value of ipfixTransportSessionAddressType, as specified  
 in [RFC 4001](#). This object is used with protocols  
 (specified in ipfixTransportSessionProtocol) like TCP (6)  
 and UDP (17) that have the notion of addresses. SCTP (132)  
 should use the ipfixTransportSessionSctpAssocId instead.  
 If SCTP (132) or any other protocol without the notion of  
 addresses is used, the object MUST be set to a zero-length  
 string"  
 ::= { ipfixTransportSessionEntry 6 }

ipfixTransportSessionSourcePort OBJECT-TYPE

SYNTAX        InetPortNumber  
 MAX-ACCESS   read-only  
 STATUS        current

DESCRIPTION

"The transport protocol port number of the Exporter.  
 This object is used with protocols (specified in  
 ipfixTransportSessionProtocol) like TCP (6)  
 and UDP (17) that have the notion of ports. SCTP (132)  
 should copy the value of sctpAssocLocalPort if the

Transport Session is in collecting mode or  
sctpAssocRemPort if the Transport Session is in  
exporting mode. The association is referenced  
by the ipfixTransportSessionSctpAssocId.  
If any other protocol without the notion of  
ports is used, the object MUST be set to zero."  
::= { ipfixTransportSessionEntry 7 }

ipfixTransportSessionDestinationPort OBJECT-TYPE

SYNTAX InetPortNumber

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The transport protocol port number of the Collector. The  
default value is 4739 for all currently defined transport  
protocol types. This object is used with protocols  
(specified in ipfixTransportSessionProtocol) like TCP (6)  
and UDP (17) that have the notion of ports. SCTP (132)  
should copy the value of sctpAssocRemPort if the  
Transport Session is in collecting mode or  
sctpAssocLocalPort if the Transport Session is in  
exporting mode. The association is referenced  
by the ipfixTransportSessionSctpAssocId.  
If any other protocol without the notion of  
ports is used, the object MUST be set to zero."

::= { ipfixTransportSessionEntry 8 }

ipfixTransportSessionSctpAssocId OBJECT-TYPE

SYNTAX Unsigned32

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The association id used for the SCTP session between the  
Exporter and the Collector of the IPFIX Transport Session.  
It is equal to the sctpAssocId entry in the sctpAssocTable  
defined in the SCTP MIB. This object is only valid if  
ipfixTransportSessionProtocol has the value 132 (SCTP). In  
all other cases, the value MUST be zero."

REFERENCE

"[RFC 3873](https://datatracker.ietf.org/doc/rfc3873), Stream Control Transmission Protocol (SCTP)  
Management Information Base (MIB)."

```

 ::= { ipfixTransportSessionEntry 9 }

ipfixTransportSessionDeviceMode OBJECT-TYPE
    SYNTAX      INTEGER {
                    exporting(1),
                    collecting(2)
                }
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
        "The mode of operation of the device for the given Transport
        Session.  This object can have the following values:

        exporting(1)
            This value MUST be used if the Transport Session is
            used for exporting Records to other IPFIX Devices,
            i.e., this device acts as Exporter.

        collecting(2)
            This value MUST be used if the Transport Session is
            used for collecting Records from other IPFIX Devices,
            i.e., this device acts as Collector."
 ::= { ipfixTransportSessionEntry 10 }

ipfixTransportSessionTemplateRefreshTimeout OBJECT-TYPE
    SYNTAX      Unsigned32
    UNITS        "seconds"
    MAX-ACCESS   read-only
    STATUS       current

    DESCRIPTION
        "On Exporters, this object contains the time in seconds
        after which IPFIX Templates are resent by the
        Exporter.

```

On Collectors, this object contains the lifetime in seconds after which a Template becomes invalid when it is not received again within this lifetime.

This object is only valid if ipfixTransportSessionProtocol has the value 17 (UDP). In all other cases, the value MUST be zero."



#### REFERENCE

"[RFC 5101](#), Specification of the IP Flow Information Export (IPFIX) Protocol for the Exchange of IP Traffic Flow Information, Sections [10.3.6](#) and [10.3.7](#)."

::= { ipfixTransportSessionEntry 11 }

#### ipfixTransportSessionOptionsTemplateRefreshTimeout OBJECT-TYPE

SYNTAX Unsigned32

UNITS "seconds"

MAX-ACCESS read-only

STATUS current

#### DESCRIPTION

"On Exporters, this object contains the time in seconds after which IPFIX Options Templates are resent by the Exporter.

On Collectors, this object contains the lifetime in seconds after which an Options Template becomes invalid when it is not received again within this lifetime.

This object is only valid if ipfixTransportSessionProtocol has the value 17 (UDP). In all other cases the value MUST be zero."

#### REFERENCE

"[RFC 5101](#), Specification of the IP Flow Information Export (IPFIX) Protocol for the Exchange of IP Traffic Flow Information, Sections [10.3.6](#) and [10.3.7](#)."

::= { ipfixTransportSessionEntry 12 }

#### ipfixTransportSessionTemplateRefreshPacket OBJECT-TYPE

SYNTAX Unsigned32

UNITS "packets"

MAX-ACCESS read-only

STATUS current

#### DESCRIPTION

"On Exporters, this object contains the number of exported IPFIX Messages after which IPFIX Templates are resent by the Exporter.

On Collectors, this object contains the lifetime in number

of exported IPFIX Messages after which a Template becomes invalid when it is not received again within this lifetime.

This object is only valid if ipfixTransportSessionProtocol has the value 17 (UDP). In all other cases the value MUST be zero."

#### REFERENCE

"[RFC 5101](#), Specification of the IP Flow Information Export (IPFIX) Protocol for the Exchange of IP Traffic Flow Information, Sections [10.3.6](#) and [10.3.7](#)."

::= { ipfixTransportSessionEntry 13 }

#### ipfixTransportSessionOptionsTemplateRefreshPacket OBJECT-TYPE

SYNTAX Unsigned32

UNITS "packets"

MAX-ACCESS read-only

STATUS current

#### DESCRIPTION

"On Exporters, this object contains the number of exported IPFIX Messages after which IPFIX Options Templates are resent by the Exporter.

On Collectors, this object contains the lifetime in number of exported IPFIX Messages after which an Options Template becomes invalid when it is not received again within this lifetime.

This object is only valid if ipfixTransportSessionProtocol has the value 17 (UDP). In all other cases the value MUST be zero."

#### REFERENCE

"[RFC 5101](#), Specification of the IP Flow Information Export (IPFIX) Protocol for the Exchange of IP Traffic Flow Information, Sections [10.3.6](#) and [10.3.7](#)."

::= { ipfixTransportSessionEntry 14 }

#### ipfixTransportSessionIpfixVersion OBJECT-TYPE

SYNTAX Unsigned32 (0..65535)

MAX-ACCESS read-only

STATUS current

#### DESCRIPTION

"On Exporters the object contains the version number of the IPFIX protocol that the Exporter uses to export its data in this Transport Session.

On Collectors the object contains the version number of the IPFIX protocol it receives for this Transport Session.

Internet-Draft

IPFIX MIB

January 2012

If IPFIX Messages of different IPFIX protocol versions are transmitted or received in this Transport Session, this object contains the maximum version number."

## REFERENCE

"[RFC 5101](#), Specification of the IP Flow Information Export (IPFIX) Protocol for the Exchange of IP Traffic Flow Information, [Section 3.1](#)."

::= { ipfixTransportSessionEntry 15 }

## ipfixTransportSessionStatus OBJECT-TYPE

SYNTAX INTEGER {  
    unknown(0),  
    inactive(1),  
    active(2)  
}

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The status of a Transport Session. This object can have the following values:

## unknown(0)

This value MUST be used if the status of the Transport Session cannot be detected by the equipment. This value should be avoided as far as possible.

## inactive(1)

This value MUST be used for Transport Sessions that are specified in the system but are not currently active. The value can be used, e.g., for Transport Sessions that are backup (secondary) sessions in a Transport Session group.

## active(2)

This value MUST be used for Transport Sessions that are currently active and transmitting or receiving data."

::= { ipfixTransportSessionEntry 16 }

-----  
-- 1.1.2: Template Table  
-----

## ipfixTemplateTable OBJECT-TYPE

SYNTAX SEQUENCE OF IpfixTemplateEntry

MAX-ACCESS not-accessible  
STATUS current  
DESCRIPTION

"This table lists the Templates and Options Templates that are transmitted by the Exporting Process or received by the

Collecting Process.

The table contains the Templates and Options Templates that are received or used for exporting data for a given Transport Session group and Observation Domain.

Withdrawn or invalidated (Options) Template MUST be removed from this table."

::= { ipfixMainObjects 2 }

ipfixTemplateEntry OBJECT-TYPE

SYNTAX IpfixTemplateEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"Defines an entry in the ipfixTemplateTable."

INDEX {

ipfixTransportSessionIndex,  
ipfixTemplateObservationDomainId,  
ipfixTemplateId

}

::= { ipfixTemplateTable 1 }

IpfixTemplateEntry ::=

SEQUENCE {

ipfixTemplateObservationDomainId Unsigned32,  
ipfixTemplateId Unsigned32,  
ipfixTemplateSetId Unsigned32,  
ipfixTemplateAccessTime DateAndTime

}

ipfixTemplateObservationDomainId OBJECT-TYPE

SYNTAX Unsigned32 (0..4294967295)

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The Id of the Observation Domain for which this Template is defined. This value is used when sending IPFIX Messages.

The special value of 0 indicates that the Data Records exported with this (Option Template) cannot be applied to a single Observation Domain."

REFERENCE

"[RFC 5101](#), Specification of the IP Flow Information Export (IPFIX) Protocol for the Exchange of IP Traffic Flow Information, [Section 3.1](#)."

::= { ipfixTemplateEntry 1 }

ipfixTemplateId OBJECT-TYPE

SYNTAX Unsigned32 (256..65535)

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"This number indicates the Template Id in the IPFIX Message. Values from 0 to 255 are not allowed for Template Ids."

REFERENCE

"[RFC 5101](#), Specification of the IP Flow Information Export (IPFIX) Protocol for the Exchange of IP Traffic Flow Information, [Section 3.4.1](#)."

::= { ipfixTemplateEntry 2 }

ipfixTemplateSetId OBJECT-TYPE

SYNTAX Unsigned32 (1..65535)

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"This number indicates the Set Id of the Template. This object allows to easily retrieve the Template type.

Currently, there are two values defined. The value 2 is used for Sets containing Template definitions. The value 3 is used for Sets containing Options Template definitions."

REFERENCE

"[RFC 5101](#), Specification of the IP Flow Information Export (IPFIX) Protocol for the Exchange of IP Traffic Flow Information, [Section 3.3.2](#)."

```
::= { ipfixTemplateEntry 3 }
```

```
ipfixTemplateAccessTime OBJECT-TYPE
```

```
SYNTAX      DateAndTime
```

```
MAX-ACCESS  read-only
```

```
STATUS      current
```

```
DESCRIPTION
```

"If the Transport Session is in exporting mode (ipfixTransportSessionDeviceMode) the time when this (Options) Template was last sent to the Collector(s).

In the specific case of UDP as transport protocol, this time is used to know when a retransmission of the (Options) Template is needed.

If it is in collecting mode, this object contains the time when this (Options) Template was last received from the Exporter. In the specific case of UDP as transport protocol, this time is used to know when this (Options)

Template times out and thus is no longer valid."

```
::= { ipfixTemplateEntry 4 }
```

```
-----  
-- 1.1.3: Exported Template Definition Table  
-----
```

```
ipfixTemplateDefinitionTable OBJECT-TYPE
```

```
SYNTAX      SEQUENCE OF IpfixTemplateDefinitionEntry
```

```
MAX-ACCESS  not-accessible
```

```
STATUS      current
```

```
DESCRIPTION
```

"On Exporters, this table lists the (Options) Template fields of which a (Options) Template is defined. It defines the (Options) Template given in the ipfixTemplateId specified in the ipfixTemplateTable.

On Collectors, this table lists the (Options) Template fields of which a (Options) Template is defined. It defines the (Options) Template given in the ipfixTemplateId specified in the ipfixTemplateTable."

```
::= { ipfixMainObjects 3 }
```

ipfixTemplateDefinitionEntry OBJECT-TYPE  
 SYNTAX IpfixTemplateDefinitionEntry  
 MAX-ACCESS not-accessible  
 STATUS current  
 DESCRIPTION  
 "Defines an entry in the ipfixTemplateDefinitionTable."

INDEX {  
   ipfixTransportSessionIndex,  
   ipfixTemplateObservationDomainId,  
   ipfixTemplateId,  
   ipfixTemplateDefinitionIndex  
 }  
 ::= { ipfixTemplateDefinitionTable 1 }

IpfixTemplateDefinitionEntry ::=  
 SEQUENCE {  
   ipfixTemplateDefinitionIndex Unsigned32,  
   ipfixTemplateDefinitionIeId Unsigned32,  
   ipfixTemplateDefinitionIeLength Unsigned32,  
   ipfixTemplateDefinitionEnterpriseNumber Unsigned32,  
   ipfixTemplateDefinitionFlags BITS  
 }

ipfixTemplateDefinitionIndex OBJECT-TYPE  
 SYNTAX Unsigned32 (1..65535)

MAX-ACCESS not-accessible  
 STATUS current  
 DESCRIPTION

"The ipfixTemplateDefinitionIndex specifies the order in which the Information Elements are used in the (Options) Template Record.

Since a Template Record can contain a maximum of 65535 Information Elements, the index is limited to this value."

#### REFERENCE

"[RFC 5101](https://www.ietf.org/rfc/rfc5101.txt), Specification of the IP Flow Information Export (IPFIX) Protocol for the Exchange of IP Traffic Flow Information, Sections [3.4.1](#) and [3.4.2](#)."

::= { ipfixTemplateDefinitionEntry 1 }

ipfixTemplateDefinitionIeId OBJECT-TYPE

SYNTAX Unsigned32 (1..65535)

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"This indicates the Information Element Id at position ipfixTemplateDefinitionIndex in the (Options) Template ipfixTemplateId. This implicitly specifies the data type of the Information Element. The elements are registered at IANA. A current list of assignments can be found at <<http://www.iana.org/assignments/ipfix>>"

REFERENCE

"[RFC 5101](#), Specification of the IP Flow Information Export (IPFIX) Protocol for the Exchange of IP Traffic Flow Information, [Section 3.2](#).

[RFC 5102](#), Information Model for IP Flow Information Export."

::= { ipfixTemplateDefinitionEntry 2 }

ipfixTemplateDefinitionIeLength OBJECT-TYPE

SYNTAX Unsigned32 (0..65535)

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"This indicates the length of the Information Element Id at position ipfixTemplateDefinitionIndex in the (Options) Template ipfixTemplateId."

REFERENCE

"[RFC 5101](#), Specification of the IP Flow Information Export (IPFIX) Protocol for the Exchange of IP Traffic Flow Information, [Section 3.2](#).

[RFC 5102](#), Information Model for IP Flow Information Export."

::= { ipfixTemplateDefinitionEntry 3 }

ipfixTemplateDefinitionEnterpriseNumber OBJECT-TYPE

SYNTAX Unsigned32

MAX-ACCESS read-only

STATUS current

DESCRIPTION



"IANA enterprise number of the authority defining the Information Element identifier in this Template Record. Enterprise numbers are assigned by IANA. A current list of all assignments is available from  
<<http://www.iana.org/assignments/enterprise-numbers/>>.

This object must be zero(0) for all standard Information Elements registered with IANA. A current list of these elements is available from  
<<http://www.iana.org/assignments/ipfix/ipfix.xhtml>>."

#### REFERENCE

"[RFC 5101](#), Specification of the IP Flow Information Export (IPFIX) Protocol for the Exchange of IP Traffic Flow Information, [Section 3.2](#).

[RFC 5102](#), Information Model for IP Flow Information Export."

::= { ipfixTemplateDefinitionEntry 4 }

ipfixTemplateDefinitionFlags OBJECT-TYPE

SYNTAX BITS {  
scope(0),  
flowKey(1)  
}

MAX-ACCESS read-only

STATUS current

#### DESCRIPTION

"This bitmask indicates special attributes for the Information Element:

scope(0)

This Information Element is used for scope.

flowKey(1)

This Information Element is a Flow Key.

Thus, we get the following values for an Information Element:

If neither bit scope(0) nor bit flowKey(1) are set

The Information Element is neither used for scoping nor as Flow Key.

If only bit scope(0) is set

The Information Element is used for scoping.  
If only bit flowKey(1) is set  
The Information Element is used as Flow Key.

Both bit scope(0) and flowKey(1) MUST NOT be set at the same time. This combination is not allowed."

#### REFERENCE

"[RFC 5101](#), Specification of the IP Flow Information Export (IPFIX) Protocol for the Exchange of IP Traffic Flow Information, Sections [2](#) and [3.4.2.1](#).

[RFC 5102](#), Information Model for IP Flow Information Export."  
::= { ipfixTemplateDefinitionEntry 5 }

---

#### -- 1.1.4: Export Table

---

ipfixExportTable OBJECT-TYPE

SYNTAX SEQUENCE OF IpfixExportEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"This table lists all exports of an IPFIX device.

On Exporters, this table contains all exports grouped by Transport Session, Observation Domain Id, Template Id, and Metering Process represented by the ipfixMeteringProcessCacheId. Thanks to the ipfixExportIndex, the exports can group one or more Transport Sessions to achieve a special functionality like failover management, load-balancing, etc. The entries with the same ipfixExportIndex, ipfixObservationDomainId, and ipfixMeteringProcessCacheId define a Transport Session group. If the Exporter does not use Transport Session grouping, then each ipfixExportIndex contains a single ipfixMeteringProcessCacheId and thus a single Transport Session, and this session MUST have the member type primary(1). Transport Sessions referenced in this table MUST have the ipfixTransportSessionDeviceMode exporting(1).

On Collectors, this table is not needed."

::= { ipfixMainObjects 4 }

ipfixExportEntry OBJECT-TYPE

SYNTAX IpfixExportEntry

MAX-ACCESS not-accessible

---

```
STATUS      current
DESCRIPTION
    "Defines an entry in the ipfixExportTable."
INDEX       {
    ipfixExportIndex,
    ipfixMeteringProcessCacheId,
    ipfixTransportSessionIndex
}
::= { ipfixExportTable 1 }
```

```
IpfixExportEntry ::=
    SEQUENCE {
        ipfixExportIndex      Unsigned32,
        ipfixExportMemberType INTEGER
    }
```

```
ipfixExportIndex OBJECT-TYPE
    SYNTAX      Unsigned32 (1..4294967295)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Locally arbitrary, but unique identifier of an entry in
         the ipfixExportTable. The value is expected
         to remain constant from a re-initialization of the entity's
         network management agent to the next re-initialization.

         A common ipfixExportIndex between two entries from this
         table expresses that there is a relationship between the
         Transport Sessions in ipfixTransportSessionIndex. The type
         of relationship is expressed by the value of
         ipfixExportMemberType."
    ::= { ipfixExportEntry 1 }
```

```
ipfixExportMemberType OBJECT-TYPE
    SYNTAX      INTEGER {
        unknown(0),
        primary(1),
        secondary(2),
        parallel(3),
        loadBalancing(4)
    }
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The type of a member Transport Session in a Transport
         Session group (identified by the value of ipfixExportIndex,
```

ipfixObservationDomainId, and ipfixMeteringProcessCacheId).  
The following values are valid:

unknown(0)

This value MUST be used if the status of the group membership cannot be detected by the equipment. This value should be avoided as far as possible.

primary(1)

This value is used for a group member that is used as the primary target of an Exporter. Other group members (with the same ipfixExportIndex and ipfixMeteringProcessCacheId) MUST NOT have the value primary(1) but MUST have the value secondary(2). This value MUST also be specified if the Exporter does not support Transport Session grouping. In this case, the group contains only one Transport Session.

secondary(2)

This value is used for a group member that is used as a secondary target of an Exporter. The Exporter will use one of the targets specified as secondary(2) within the same Transport Session group when the primary target is not reachable.

parallel(3)

This value is used for a group member that is used for duplicate exporting, i.e., all group members identified by the ipfixExportIndex are exporting the same Records in parallel. This implies that all group members MUST have the same membertype parallel(3).

loadBalancing(4)

This value is used for a group member that is used as one target for load-balancing. This means that a Record is sent to one of the group members in this group identified by ipfixExportIndex. This implies that all group members MUST have the same membertype loadBalancing(4)."

::= { ipfixExportEntry 2 }

-----

### -- 1.1.5: Metering Process Table

-----  
ipfixMeteringProcessTable OBJECT-TYPE  
SYNTAX SEQUENCE OF IpfixMeteringProcessEntry  
MAX-ACCESS not-accessible  
STATUS current  
DESCRIPTION  
"This table lists so-called caches used at the Metering  
Process to store the metering data of Flows observed at

the Observation Points given in the  
ipfixObservationPointGroupReference. The table lists the  
timeouts that specify when the cached metering data is  
expired.

On Collectors, the table is not needed."  
::= { ipfixMainObjects 5 }

ipfixMeteringProcessEntry OBJECT-TYPE  
SYNTAX IpfixMeteringProcessEntry  
MAX-ACCESS not-accessible  
STATUS current  
DESCRIPTION  
"Defines an entry in the ipfixMeteringProcessTable."  
INDEX { ipfixMeteringProcessCacheId }  
::= { ipfixMeteringProcessTable 1 }

IpfixMeteringProcessEntry ::=  
SEQUENCE {  
ipfixMeteringProcessCacheId Unsigned32,  
ipfixMeteringProcessObservationPointGroupRef Unsigned32,  
ipfixMeteringProcessCacheActiveTimeout Unsigned32,  
ipfixMeteringProcessCacheInactiveTimeout Unsigned32  
}

ipfixMeteringProcessCacheId OBJECT-TYPE  
SYNTAX Unsigned32 (1..4294967295)  
MAX-ACCESS not-accessible  
STATUS current  
DESCRIPTION  
"Locally arbitrary, but unique identifier of an entry in the  
ipfixMeteringProcessTable. The value is expected to remain

constant from a re-initialization of the entity's network management agent to the next re-initialization."  
 ::= { ipfixMeteringProcessEntry 1 }

ipfixMeteringProcessObservationPointGroupRef OBJECT-TYPE

SYNTAX Unsigned32

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The Observation Point Group Id that links this table entry to the ipfixObservationPointTable. The matching ipfixObservationPointGroupId in that table gives the Observation Points used in that cache. If the Observation Points are unknown, the ipfixMeteringProcessObservationPointGroupRef MUST be zero."

::= { ipfixMeteringProcessEntry 2 }

ipfixMeteringProcessCacheActiveTimeout OBJECT-TYPE

SYNTAX Unsigned32

UNITS "seconds"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"On the Exporter, this object contains the time after which a Flow is expired (and a Data Record for the template is sent) even though packets matching this Flow are still received by the Metering Process. If this value is 0, the Flow is not prematurely expired."

REFERENCE

"[RFC 5470](http://tools.ietf.org/html/rfc5470), Architecture for IP Flow Information Export, [Section 5.1.1](#), item 3."

::= { ipfixMeteringProcessEntry 3 }

ipfixMeteringProcessCacheInactiveTimeout OBJECT-TYPE

SYNTAX Unsigned32

UNITS "seconds"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"On the Exporter. this object contains the time after which a Flow is expired (and a Data Record for the template is sent) when no packets matching this Flow are received by the

Metering Process for the given number of seconds. If this value is zero, the Flow is expired immediately, i.e., a Data Record is sent for every packet received by the Metering Process."

REFERENCE

"[RFC 5470](#), Architecture for IP Flow Information Export, [Section 5.1.1](#), item 1"

::= { ipfixMeteringProcessEntry 4 }

-----  
-- 1.1.6: Observation Point Table  
-----

ipfixObservationPointTable OBJECT-TYPE

SYNTAX SEQUENCE OF IpfixObservationPointEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"This table lists the Observation Points used within an Exporter by the Metering Process. The index ipfixObservationPointGroupId groups Observation Points and is referenced in the Metering Process table.

On Collectors this table is not needed."

::= { ipfixMainObjects 6 }

ipfixObservationPointEntry OBJECT-TYPE

SYNTAX IpfixObservationPointEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"Defines an entry in the ipfixObservationPointTable."

INDEX {  
    ipfixObservationPointGroupId,  
    ipfixObservationPointIndex  
}

::= { ipfixObservationPointTable 1 }

IpfixObservationPointEntry ::=

SEQUENCE {  
    ipfixObservationPointGroupId Unsigned32,  
    ipfixObservationPointIndex Unsigned32,

```

        ipfixObservationPointObservationDomainId Unsigned32,
        ipfixObservationPointPhysicalEntity      PhysicalIndexOrZero,
        ipfixObservationPointPhysicalInterface    InterfaceIndexOrZero,
        ipfixObservationPointPhysicalEntityDirection INTEGER
    }

ipfixObservationPointGroupId OBJECT-TYPE
    SYNTAX      Unsigned32 (1..4294967295)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Locally arbitrary, but unique identifier of an entry in the
        ipfixObservationPointTable. The value is expected to remain
        constant from a re-initialization of the entity's network
        management agent to the next re-initialization."

        This index represents a group of Observation Points.

        The special value of 0 MUST NOT be used within this table
        but is reserved for the usage in the
        ipfixMeteringProcessTable. An index of 0 for the
        ipfixObservationPointGroupReference index in that table
        indicates that an Observation Point is unknown or
        unspecified for a Metering Process cache."
    ::= { ipfixObservationPointEntry 1 }

ipfixObservationPointIndex OBJECT-TYPE
    SYNTAX      Unsigned32 (1..4294967295)
    MAX-ACCESS  not-accessible
    STATUS      current

```

#### DESCRIPTION

"Locally arbitrary, but unique identifier of an entry in the ipfixObservationPointTable. The value is expected to remain constant from a re-initialization of the entity's network management agent to the next re-initialization.

This index represents a single Observation Point in an Observation Point group."

```
 ::= { ipfixObservationPointEntry 2 }
```

```
ipfixObservationPointObservationDomainId OBJECT-TYPE
```



SYNTAX        Unsigned32  
MAX-ACCESS   read-only  
STATUS        current

DESCRIPTION

"The Id of the Observation Domain in which this Observation Point is included.

The special value of 0 indicates that the Observation Points within this group cannot be applied to a single Observation Domain."

REFERENCE

"[RFC 5101](#), Specification of the IP Flow Information Export (IPFIX) Protocol for the Exchange of IP Traffic Flow Information, [Section 3.1](#)."

::= { ipfixObservationPointEntry 3 }

ipfixObservationPointPhysicalEntity OBJECT-TYPE

SYNTAX        PhysicalIndexOrZero  
MAX-ACCESS   read-only  
STATUS        current

DESCRIPTION

"This object contains the index of a physical entity in the ENTITY MIB. This physical entity is the given Observation Point. If such a physical entity cannot be specified or is not known, then the object is zero."

::= { ipfixObservationPointEntry 4 }

ipfixObservationPointPhysicalInterface OBJECT-TYPE

SYNTAX        InterfaceIndexOrZero  
MAX-ACCESS   read-only  
STATUS        current

DESCRIPTION

"This object contains the index of a physical interface in the IF MIB. This physical interface is the given Observation Point. If such a physical interface cannot be specified or is not known, then the object is zero.

This object MAY be used stand alone or in addition to ipfixObservationPointPhysicalEntity. If ipfixObservationPointPhysicalEntity is not zero, this object MUST point to the same physical interface that is

referenced in ipfixObservationPointPhysicalEntity.  
Otherwise, it may reference any interface in the IF MIB."  
::= { ipfixObservationPointEntry 5 }

ipfixObservationPointPhysicalEntityDirection OBJECT-TYPE

SYNTAX INTEGER {  
    unknown(0),  
    ingress(1),  
    egress(2),  
    both(3)  
}

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The direction of the Flow that is monitored on the given physical entity. The following values are valid:

unknown(0)

This value MUST be used if a direction is not known for the given physical entity.

ingress(1)

This value is used for monitoring incoming Flows on the given physical entity.

egress(2)

This value is used for monitoring outgoing Flows on the given physical entity.

both(3)

This value is used for monitoring incoming and outgoing Flows on the given physical entity."

::= { ipfixObservationPointEntry 6 }

-----  
-- 1.1.7: Selection Process Table  
-----

ipfixSelectionProcessTable OBJECT-TYPE

SYNTAX SEQUENCE OF IpfixSelectionProcessEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"This table contains Selector Functions connected to a Metering Process by the index ipfixMeteringProcessCacheId.

The Selector Functions are grouped into Selection Processes by the `ipfixSelectionProcessIndex`. The Selector Functions are applied within the Selection Process to the packets observed for the given Metering Process cache in increasing order implied by the `ipfixSelectionProcessSelectorIndex`. This means Selector Functions with lower `ipfixSelectionProcessSelectorIndex` are applied first. The remaining packets are accounted for in Flow Records.

Since IPFIX does not define any Selector Function (except selecting every packet), this is a placeholder for future use and a guideline for implementing enterprise-specific Selector Function objects.

The following object tree should visualize how the Selector Function objects should be implemented:

```

ipfixSelectorFunctions
|
+- ipfixFuncSelectAll
| |
| +- ipfixFuncSelectAllAvail (is the function available?)
|
+- ipfixFuncF2
| |
| +- ipfixFuncF2Avail (is the function F2 available?)
| |
| +- ipfixFuncF2Parameters (a table with parameters)
...
|
+- ipfixFuncFn...
```

If a Selector Function takes parameters, the MIB should contain a table with an entry for each set of parameters used at the Exporter."

```
::= { ipfixMainObjects 7 }
```

#### `ipfixSelectionProcessEntry` OBJECT-TYPE

SYNTAX `IpfixSelectionProcessEntry`

MAX-ACCESS `not-accessible`

STATUS `current`

DESCRIPTION

"Defines an entry in the `ipfixSelectionProcessTable`."

INDEX {

`ipfixMeteringProcessCacheId`,

`ipfixSelectionProcessIndex`,

`ipfixSelectionProcessSelectorIndex`

}

Internet-Draft

IPFIX MIB

January 2012

```
::= { ipfixSelectionProcessTable 1 }
```

```
IpfixSelectionProcessEntry ::= SEQUENCE {  
    ipfixSelectionProcessIndex      Unsigned32,  
    ipfixSelectionProcessSelectorIndex Unsigned32,  
    ipfixSelectionProcessSelectorFunction OBJECT IDENTIFIER  
}
```

```
ipfixSelectionProcessIndex OBJECT-TYPE  
    SYNTAX      Unsigned32 (1..4294967295)  
    MAX-ACCESS  not-accessible  
    STATUS      current  
    DESCRIPTION  
        "Locally arbitrary, but unique identifier of an entry in the  
        ipfixSelectionProcessTable. The value is expected to remain  
        constant from a re-initialization of the entity's network  
        management agent to the next re-initialization."  
    ::= { ipfixSelectionProcessEntry 1 }
```

```
ipfixSelectionProcessSelectorIndex OBJECT-TYPE  
    SYNTAX      Unsigned32 (1..4294967295)  
    MAX-ACCESS  not-accessible  
    STATUS      current  
    DESCRIPTION  
        "Index specifying the order in which the referenced  
        ipfixSelectionProcessSelectorFunctions are applied to the  
        observed packet stream within the given Selection Process  
        (identified by the ipfixSelectionProcessIndex). The  
        Selector Functions are applied in increasing order, i.e.,  
        Selector Functions with lower index are applied first."  
    ::= { ipfixSelectionProcessEntry 2 }
```

```
ipfixSelectionProcessSelectorFunction OBJECT-TYPE  
    SYNTAX      OBJECT IDENTIFIER  
    MAX-ACCESS  read-only  
    STATUS      current  
    DESCRIPTION  
        "The pointer to the Selector Function used at position  
        ipfixSelectionProcessSelectorIndex in the list of Selector  
        Functions for the Metering Process cache specified by the
```

index ipfixMeteringProcessCacheId and for the given Selection Process (identified by the ipfixSelectionProcessIndex).

This usually points to an object in the IPFIX SELECTOR MIB. If the Selector Function does not take parameters, then it MUST point to the root of the function subtree. If the function takes parameters, then it MUST point to an entry

in the parameter table of the Selector Function."  
::= { ipfixSelectionProcessEntry 3 }

-----  
-- 1.2.1: Transport Session Statistics Table  
-----

ipfixTransportSessionStatsTable OBJECT-TYPE  
SYNTAX SEQUENCE OF IpfixTransportSessionStatsEntry  
MAX-ACCESS not-accessible  
STATUS current  
DESCRIPTION  
"This table lists Transport Sessions statistics between  
Exporting Processes and Collecting Processes."  
::= { ipfixStatistics 1 }

ipfixTransportSessionStatsEntry OBJECT-TYPE  
SYNTAX IpfixTransportSessionStatsEntry  
MAX-ACCESS not-accessible  
STATUS current  
DESCRIPTION  
"Defines an entry in the ipfixTransportSessionStatsTable."  
AUGMENTS { ipfixTransportSessionEntry }  
::= { ipfixTransportSessionStatsTable 1 }

IpfixTransportSessionStatsEntry ::=

SEQUENCE {	
ipfixTransportSessionRate	Gauge32,
ipfixTransportSessionPackets	Counter64,
ipfixTransportSessionBytes	Counter64,
ipfixTransportSessionMessages	Counter64,
ipfixTransportSessionDiscardedMessages	Counter64,
ipfixTransportSessionRecords	Counter64,
ipfixTransportSessionTemplates	Counter64,

```

        ipfixTransportSessionOptionsTemplates Counter64,
        ipfixTransportSessionDiscontinuityTime TimeStamp
    }

```

#### ipfixTransportSessionRate OBJECT-TYPE

```

SYNTAX      Gauge32
UNITS       "bytes/second"
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The number of bytes per second received by the
    Collector or transmitted by the Exporter. A
    value of zero (0) means that no packets were sent or
    received, yet. This object is updated every second."
 ::= { ipfixTransportSessionStatsEntry 1 }

```

#### ipfixTransportSessionPackets OBJECT-TYPE

```

SYNTAX      Counter64
UNITS       "packets"
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The number of packets received by the Collector
    or transmitted by the Exporter.
    Discontinuities in the value of this counter can occur at
    re-initialization of the management system and at other
    times as indicated by the value of
    ipfixTransportSessionDiscontinuityTime."
 ::= { ipfixTransportSessionStatsEntry 2 }

```

#### ipfixTransportSessionBytes OBJECT-TYPE

```

SYNTAX      Counter64
UNITS       "bytes"
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The number of bytes received by the Collector
    or transmitted by the Exporter.
    Discontinuities in the value of this counter can occur at
    re-initialization of the management system and at other
    times as indicated by the value of
    ipfixTransportSessionDiscontinuityTime."

```

::= { ipfixTransportSessionStatsEntry 3 }

ipfixTransportSessionMessages OBJECT-TYPE

SYNTAX Counter64

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of IPFIX Messages received by the Collector or transmitted by the Exporter. Discontinuities in the value of this counter can occur at re-initialization of the management system and at other times as indicated by the value of ipfixTransportSessionDiscontinuityTime."

::= { ipfixTransportSessionStatsEntry 4 }

ipfixTransportSessionDiscardedMessages OBJECT-TYPE

SYNTAX Counter64

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of received IPFIX Message that are malformed,

cannot be decoded, are received in the wrong order, or are missing according to the sequence number.

If used at the Exporter, the number of messages that could not be sent due to, e.g., internal buffer overflows, network congestion, or routing issues.

Discontinuities in the value of this counter can occur at re-initialization of the management system and at other times as indicated by the value of ipfixTransportSessionDiscontinuityTime."

::= { ipfixTransportSessionStatsEntry 5 }

ipfixTransportSessionRecords OBJECT-TYPE

SYNTAX Counter64

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of Data Records received by the Collector or transmitted by the Exporter.

Discontinuities in the value of this counter can occur at re-initialization of the management system and at other times as indicated by the value of ipfixTransportSessionDiscontinuityTime."  
::= { ipfixTransportSessionStatsEntry 6 }

ipfixTransportSessionTemplates OBJECT-TYPE

SYNTAX Counter64

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of Templates received or transmitted. Discontinuities in the value of this counter can occur at re-initialization of the management system and at other times as indicated by the value of ipfixTransportSessionDiscontinuityTime."

::= { ipfixTransportSessionStatsEntry 7 }

ipfixTransportSessionOptionsTemplates OBJECT-TYPE

SYNTAX Counter64

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of Options Templates received or transmitted. Discontinuities in the value of this counter can occur at re-initialization of the management system and at other times as indicated by the value of ipfixTransportSessionDiscontinuityTime."

::= { ipfixTransportSessionStatsEntry 8 }

ipfixTransportSessionDiscontinuityTime OBJECT-TYPE

SYNTAX TimeStamp

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The value of sysUpTime at the most recent occasion at which one or more of the Transport Session counters suffered a discontinuity.

A value of zero indicates no such discontinuity has occurred since the last re-initialization of the local



```
management subsystem."
::= { ipfixTransportSessionStatsEntry 9 }
```

---

-- 1.2.2: Template Statistics Table

---

```
ipfixTemplateStatsTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF IpfixTemplateStatsEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "This table lists statistics objects per Template."
    ::= { ipfixStatistics 2 }
```

```
ipfixTemplateStatsEntry OBJECT-TYPE
    SYNTAX      IpfixTemplateStatsEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Defines an entry in the ipfixTemplateStatsTable."
    AUGMENTS    { ipfixTemplateEntry }
    ::= { ipfixTemplateStatsTable 1 }
```

```
IpfixTemplateStatsEntry ::=
    SEQUENCE {
        ipfixTemplateDataRecords      Counter64,
        ipfixTemplateDiscontinuityTime TimeStamp
    }
```

```
ipfixTemplateDataRecords OBJECT-TYPE
    SYNTAX      Counter64
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The number of Data Records that are transmitted or received
        per Template."
```

```
Discontinuities in the value of this counter can occur at
re-initialization of the management system, and at other
times as indicated by the value of
ipfixTemplateDiscontinuityTime."
::= { ipfixTemplateStatsEntry 1 }
```

```

ipfixTemplateDiscontinuityTime OBJECT-TYPE
    SYNTAX          TimeStamp
    MAX-ACCESS      read-only
    STATUS          current
    DESCRIPTION
        "The value of sysUpTime at the most recent occasion at which
        the Template counter suffered a discontinuity.
        A value of zero indicates no such discontinuity has
        occurred since the last re-initialization of the local
        management subsystem."
    ::= { ipfixTemplateStatsEntry 2 }

```

---

-- 1.2.3: Metering Process Statistics Table

---

```

ipfixMeteringProcessStatsTable OBJECT-TYPE
    SYNTAX          SEQUENCE OF IpfixMeteringProcessStatsEntry
    MAX-ACCESS      not-accessible
    STATUS          current
    DESCRIPTION
        "This table lists statistic objects that have data per
        Metering Process cache.

        On Collectors, this table is not needed."
    ::= { ipfixStatistics 3 }

```

```

ipfixMeteringProcessStatsEntry OBJECT-TYPE
    SYNTAX          IpfixMeteringProcessStatsEntry
    MAX-ACCESS      not-accessible
    STATUS          current
    DESCRIPTION
        "Defines an entry in the ipfixMeteringProcessStatsTable."
    AUGMENTS        { ipfixMeteringProcessEntry }
    ::= { ipfixMeteringProcessStatsTable 1 }

```

```

IpfixMeteringProcessStatsEntry ::=
    SEQUENCE {
        ipfixMeteringProcessCacheActiveFlows          Gauge32,
        ipfixMeteringProcessCacheUnusedCacheEntries   Gauge32,
        ipfixMeteringProcessCacheDataRecords          Counter64,
        ipfixMeteringProcessCacheDiscontinuityTime    TimeStamp
    }

```

ipfixMeteringProcessCacheActiveFlows OBJECT-TYPE

SYNTAX Gauge32

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of Flows currently active at this cache."

::= { ipfixMeteringProcessStatsEntry 1 }

ipfixMeteringProcessCacheUnusedCacheEntries OBJECT-TYPE

SYNTAX Gauge32

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of unused cache entries."

::= { ipfixMeteringProcessStatsEntry 2 }

ipfixMeteringProcessCacheDataRecords OBJECT-TYPE

SYNTAX Counter64

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of Data Records generated.

Discontinuities in the value of this counter can occur at re-initialization of the management system and at other times as indicated by the value of ipfixTemplateDiscontinuityTime."

::= { ipfixMeteringProcessStatsEntry 3 }

ipfixMeteringProcessCacheDiscontinuityTime OBJECT-TYPE

SYNTAX TimeStamp

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The value of sysUpTime at the most recent occasion at which the Metering Process counter suffered a discontinuity. A value of zero indicates no such discontinuity has occurred since the last re-initialization of the local management subsystem."

::= { ipfixMeteringProcessStatsEntry 4 }

-----  
-- 1.2.4: Selection Process Statistics Table  
-----

ipfixSelectionProcessStatsTable OBJECT-TYPE

SYNTAX SEQUENCE OF IpfixSelectionProcessStatsEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

Internet-Draft

IPFIX MIB

January 2012

"This table contains statistics for the Selector Functions connected to Metering Process by the index ipfixMeteringProcessCacheId.

The indexes MUST match an entry in the ipfixSelectionProcessTable."

::= { ipfixStatistics 4 }

ipfixSelectionProcessStatsEntry OBJECT-TYPE

SYNTAX IpfixSelectionProcessStatsEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"Defines an entry in the ipfixSelectionProcessStatsTable."

AUGMENTS { ipfixSelectionProcessEntry }

::= { ipfixSelectionProcessStatsTable 1 }

IpfixSelectionProcessStatsEntry ::= SEQUENCE {

ipfixSelectionProcessStatsPacketsObserved Counter64,

ipfixSelectionProcessStatsPacketsDropped Counter64,

ipfixSelectionProcessStatsDiscontinuityTime TimeStamp

}

ipfixSelectionProcessStatsPacketsObserved OBJECT-TYPE

SYNTAX Counter64

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of packets observed at the entry point of the function. The entry point may be the Observation Point or the exit point of another Selector Function.

Discontinuities in the value of this counter can occur at re-initialization of the management system and at other times as indicated by the value of

ipfixSelectionProcessStatsDiscontinuityTime."

::= { ipfixSelectionProcessStatsEntry 1 }

ipfixSelectionProcessStatsPacketsDropped OBJECT-TYPE

SYNTAX Counter64

MAX-ACCESS read-only

STATUS current

#### DESCRIPTION

"The number of packets dropped while selecting packets. Discontinuities in the value of this counter can occur at re-initialization of the management system and at other times as indicated by the value of ipfixSelectionProcessStatsDiscontinuityTime."

```
::= { ipfixSelectionProcessStatsEntry 2 }
```

ipfixSelectionProcessStatsDiscontinuityTime OBJECT-TYPE

SYNTAX TimeStamp

MAX-ACCESS read-only

STATUS current

#### DESCRIPTION

"The value of sysUpTime at the most recent occasion at which one or more of the Selector counters suffered a discontinuity.

A value of zero indicates no such discontinuity has occurred since the last re-initialization of the local management subsystem."

```
::= { ipfixSelectionProcessStatsEntry 3 }
```

```
-----  
-- 2: Conformance Information  
-----
```

```
ipfixCompliances OBJECT IDENTIFIER ::= { ipfixConformance 1 }
```

```
ipfixGroups      OBJECT IDENTIFIER ::= { ipfixConformance 2 }
```

```
-----  
-- 2.1: Compliance Statements  
-----
```

ipfixCollectorCompliance MODULE-COMPLIANCE

STATUS current

#### DESCRIPTION

"An implementation that builds an IPFIX Collector that complies to this module MUST implement the objects defined in the mandatory group ipfixCommonGroup.

The implementation of all objects in the other groups is optional and depends on the corresponding functionality implemented in the equipment.

An implementation that is compliant to this MIB module is limited to use only the values TCP (6), UDP (17), and SCTP (132) in the ipfixTransportSessionProtocol object because these are the only protocol currently specified for usage within IPFIX (see [RFC 5101](#))."

MODULE -- this module

MANDATORY-GROUPS {  
 ipfixCommonGroup  
}

GROUP ipfixCommonStatsGroup

DESCRIPTION

"These objects should be implemented if the statistics

function is implemented in the equipment."  
::= { ipfixCompliances 1 }

ipfixExporterCompliance MODULE-COMPLIANCE

STATUS current

DESCRIPTION

"An implementation that builds an IPFIX Exporter that complies to this module MUST implement the objects defined in the mandatory group ipfixCommonGroup. The implementation of all other objects depends on the implementation of the corresponding functionality in the equipment."

MODULE -- this module

MANDATORY-GROUPS {  
 ipfixCommonGroup,  
 ipfixExporterGroup  
}

GROUP ipfixCommonStatsGroup

DESCRIPTION

"These objects should be implemented if the statistics function is implemented in the equipment."

GROUP ipfixExporterStatsGroup

DESCRIPTION

"These objects MUST be implemented if statistical functions are implemented on the equipment."

::= { ipfixCompliances 2 }

-----  
-- 2.2: MIB Grouping  
-----

ipfixCommonGroup OBJECT-GROUP

```
OBJECTS {
    ipfixTransportSessionProtocol,
    ipfixTransportSessionSourceAddressType,
    ipfixTransportSessionSourceAddress,
    ipfixTransportSessionDestinationAddressType,
    ipfixTransportSessionDestinationAddress,
    ipfixTransportSessionSourcePort,
    ipfixTransportSessionDestinationPort,
    ipfixTransportSessionSctpAssocId,
    ipfixTransportSessionDeviceMode,
    ipfixTransportSessionTemplateRefreshTimeout,
    ipfixTransportSessionOptionsTemplateRefreshTimeout,
    ipfixTransportSessionTemplateRefreshPacket,
    ipfixTransportSessionOptionsTemplateRefreshPacket,
    ipfixTransportSessionIpfixVersion,
```

```
    ipfixTransportSessionStatus,
```

```
    ipfixTemplateSetId,
    ipfixTemplateAccessTime,
```

```
    ipfixTemplateDefinitionIeId,
    ipfixTemplateDefinitionIeLength,
    ipfixTemplateDefinitionEnterpriseNumber,
    ipfixTemplateDefinitionFlags
```

```
}
STATUS      current
```

DESCRIPTION

"The main IPFIX objects."

::= { ipfixGroups 1 }

ipfixCommonStatsGroup OBJECT-GROUP

```
OBJECTS {
    ipfixTransportSessionRate,
    ipfixTransportSessionPackets,
    ipfixTransportSessionBytes,
```

```

        ipfixTransportSessionMessages,
        ipfixTransportSessionDiscardedMessages,
        ipfixTransportSessionRecords,
        ipfixTransportSessionTemplates,
        ipfixTransportSessionOptionsTemplates,
        ipfixTransportSessionDiscontinuityTime,

        ipfixTemplateDataRecords,
        ipfixTemplateDiscontinuityTime
    }
    STATUS      current
    DESCRIPTION
        "Common statistical objects."
    ::= { ipfixGroups 2 }

ipfixExporterGroup OBJECT-GROUP
    OBJECTS {
        ipfixExportMemberType,

        ipfixMeteringProcessObservationPointGroupRef,
        ipfixMeteringProcessCacheActiveTimeout,
        ipfixMeteringProcessCacheInactiveTimeout,

        ipfixObservationPointObservationDomainId,
        ipfixObservationPointPhysicalEntity,
        ipfixObservationPointPhysicalInterface,
        ipfixObservationPointPhysicalEntityDirection,
    }

```

```

        ipfixSelectionProcessSelectorFunction
    }
    STATUS      current
    DESCRIPTION
        "The main objects for Exporters."
    ::= { ipfixGroups 3 }

ipfixExporterStatsGroup OBJECT-GROUP
    OBJECTS {
        ipfixMeteringProcessCacheActiveFlows,
        ipfixMeteringProcessCacheUnusedCacheEntries,
        ipfixMeteringProcessCacheDataRecords,
        ipfixMeteringProcessCacheDiscontinuityTime,
    }

```



```

        ipfixSelectionProcessStatsPacketsObserved,
        ipfixSelectionProcessStatsPacketsDropped,
        ipfixSelectionProcessStatsDiscontinuityTime
    }
    STATUS      current
    DESCRIPTION
        "The statistical objects for Exporters."
    ::= { ipfixGroups 4 }

END

```

## 8.2. IPFIX SELECTOR MIB Definition

```

IPFIX-SELECTOR-MIB DEFINITIONS ::= BEGIN

IMPORTS
    MODULE-IDENTITY, OBJECT-TYPE, mib-2
        FROM SNMPv2-SMI
        TruthValue
        FROM SNMPv2-TC
    MODULE-COMPLIANCE, OBJECT-GROUP
        FROM SNMPv2-CONF;

ipfixSelectorMIB MODULE-IDENTITY
    LAST-UPDATED "201201200000Z"          -- 20 January 2012
    ORGANIZATION "IETF IPFIX Working Group"
    CONTACT-INFO
        "WG charter:
         http://www.ietf.org/html.charters/ipfix-charter.html

        Mailing Lists:
        General Discussion: ipfix@ietf.org
        To Subscribe: http://www1.ietf.org/mailman/listinfo/ipfix

```

Dietz, et al.      <draft-ietf-ipfix-rfc5815bis-01.txt>      [Page 57]

---

Internet-Draft

IPFIX MIB

January 2012

Archive:  
<http://www1.ietf.org/mail-archive/web/ipfix/current/index.html>

Editor:  
 Thomas Dietz  
 NEC Europe Ltd.  
 NEC Laboratories Europe

Network Research Division  
Kurfuersten-Anlage 36  
69115 Heidelberg  
Germany  
Phone: +49 6221 4342-128  
Email: Thomas.Dietz@nw.neclab.eu

Atsushi Kobayashi  
NTT Information Sharing Platform Laboratories  
3-9-11 Midori-cho  
Musashino-shi  
180-8585  
Japan  
Phone: +81-422-59-3978  
Email: akoba@nttv6.net

Benoit Claise  
Cisco Systems, Inc.  
De Kleetlaan 6a b1  
Diegem 1831  
Belgium  
Phone: +32 2 704 5622  
Email: bclaise@cisco.com

Gerhard Muenz  
Technische Universitaet Muenchen  
Department of Informatics  
Chair for Network Architectures and Services (I8)  
Boltzmannstr. 3  
85748 Garching  
Germany  
Phone: +49 89 289-18008  
Email: muenz@net.in.tum.de  
URI: <http://www.net.in.tum.de/~muenz>

#### DESCRIPTION

"The IPFIX SELECTOR MIB module defined in this section provides the standard Filtering and Sampling functions that can be referenced in the ipfixSelectionProcessTable. All standard Filtering and Sampling functions MUST be registered in the subtree under object ipfixSelectorFunctions (1.3.6.1.2.1.194.1.1). The toplevel OIDs in the subtree

under object ipfixSelectorFunctions MUST be registered in a subregistry maintained by IANA at <http://www.iana.org/assignments/smi-numbers>.

New selector functions MUST be registered at IANA and are subject to Expert Review [RFC 5226](#), i.e., review by one of a group of experts designated by an IETF Area Director. The group of experts MUST check the requested MIB objects for completeness and accuracy of the description. Requests for MIB objects that duplicate the functionality of existing objects SHOULD be declined. The smallest available OID SHOULD be assigned to a new MIB objects. The specification of new MIB objects SHOULD follow the structure specified in RFC [ThisRFC] and MUST be published using a well-established and persistent publication medium. The experts will initially be drawn from the Working Group Chairs and document editors of the IPFIX and PSAMP Working Groups.

Copyright (c) 2011 IETF Trust and the persons identified as authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, is permitted pursuant to, and subject to the license terms contained in, the Simplified BSD License set forth in [Section 4.c](#) of the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>)."

-- Revision history

REVISION        "201201200000Z"                -- 20 January 2012  
DESCRIPTION  
    "Update to MIB description to reflect updated registration of new Sampling and Filtering Functions. Published as RFC [ThisRFC]."

REVISION        "201003150000Z"                -- 15 March 2010  
DESCRIPTION  
    "Initial version, published as [RFC 5815](#)."

::= { mib-2 194 }

-- Note for RFC Editor: substitute [ThisRFC] with the newly  
-- assigned number in the previous sections.

--\*\*\*\*\*  
-- Top Level Structure of the MIB  
--\*\*\*\*\*

Internet-Draft

IPFIX MIB

January 2012

```
ipfixSelectorObjects      OBJECT IDENTIFIER
    ::= { ipfixSelectorMIB 1 }
ipfixSelectorConformance OBJECT IDENTIFIER
    ::= { ipfixSelectorMIB 2 }

-----
-- 1: Objects used by all IPFIX implementations
-----
-----
-- 1.1: Packet Selector Functions for IPFIX
-----
ipfixSelectorFunctions OBJECT IDENTIFIER
    ::= { ipfixSelectorObjects 1 }

-----
-- 1.1.1: Function 1: Selecting All Packets
-----
ipfixFuncSelectAll OBJECT IDENTIFIER
    ::= { ipfixSelectorFunctions 1 }

ipfixFuncSelectAllAvail OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
        "This object indicates the availability of the trivial
        function of selecting all packets.  This function is always
        available."
    ::= { ipfixFuncSelectAll 1 }

-----
-- 2: Conformance Information
-----
-----
ipfixSelectorCompliances OBJECT IDENTIFIER
    ::= { ipfixSelectorConformance 1 }
ipfixSelectorGroups      OBJECT IDENTIFIER
    ::= { ipfixSelectorConformance 2 }

-----
-- 2.1: Compliance Statements
-----
ipfixSelectorBasicCompliance MODULE-COMPLIANCE
    STATUS   current
```

## DESCRIPTION

"An implementation that builds an IPFIX Exporter that complies to this module MUST implement the objects defined in the mandatory group ipfixBasicGroup. The implementation of all other objects depends on the implementation of the

corresponding functionality in the equipment."

MODULE -- this module

MANDATORY-GROUPS {

    ipfixSelectorBasicGroup

}

::= { ipfixSelectorCompliances 1 }

-----  
-- 2.2: MIB Grouping  
-----

ipfixSelectorBasicGroup OBJECT-GROUP

OBJECTS {

    ipfixFuncSelectAllAvail

}

STATUS        current

DESCRIPTION

    "The main IPFIX objects."

::= { ipfixSelectorGroups 1 }

END

Internet-Draft

IPFIX MIB

January 2012

## 9. Security Considerations

There are no management objects defined in this MIB module that have a MAX-ACCESS clause of read-write and/or read-create. So, if these MIB modules are implemented correctly, then there is no risk that an intruder can alter or create any management objects of these MIB modules via direct SNMP SET operations.

Some of the readable objects in these MIB modules (i.e., objects with a MAX-ACCESS other than not-accessible) may be considered sensitive or vulnerable in some network environments. It is thus important to control even GET and/or NOTIFY access to these objects and possibly to even encrypt the values of these objects when sending them over the network via SNMP. These are the tables and objects and their sensitivity/vulnerability:

- o ipfixTransportSessionTable - contains configuration data that might be sensitive because objects in this table may reveal information about the network infrastructure
- o ipfixExportTable - contains configuration data that might be sensitive because object in this table may reveal information about the network infrastructure as well
- o ipfixMeteringProcessTable - contains configuration data that might be sensitive because objects in this table may reveal information about the IPFIX Device itself
- o ipfixObservationPointTable - contains configuration data that

might be sensitive because objects in this table may reveal information about the IPFIX Device itself and the network infrastructure

- o ipfixSelectorFunctions - currently contains no sensitive data but might want to be secured anyway since it may contain sensitive data in a future version

All other objects and tables contain no data that is considered sensitive.

SNMP versions prior to SNMPv3 did not include adequate security. Even if the network itself is secure (for example by using IPsec), even then, there is no control as to who on the secure network is allowed to access and GET/SET (read/change/create/delete) the objects in these MIB modules.

It is RECOMMENDED that implementers consider the security features as provided by the SNMPv3 framework (see [\[RFC3410\] Section 8](#)), including

full support for the SNMPv3 cryptographic mechanisms (for authentication and privacy).

Further, deployment of SNMP versions prior to SNMPv3 is NOT RECOMMENDED. Instead, it is RECOMMENDED to deploy SNMPv3 and to enable cryptographic security. It is then a customer/operator responsibility to ensure that the SNMP entity giving access to an instance of these MIB modules is properly configured to give access to the objects only to those principals (users) that have legitimate rights to indeed GET or SET (change/create/delete) them.

Internet-Draft

IPFIX MIB

January 2012

## [10](#). IANA Considerations

The MIB module in this document uses the following IANA-assigned OBJECT IDENTIFIER values recorded in the SMI Numbers registry:

Descriptor	OBJECT IDENTIFIER value
-----	-----
ipfixMIB	{ mib-2 193 }
ipfixSelectorMIB	{ mib-2 194 }

NOTE TO RFC EDITOR: substitute ThisRFC with the RFC number of this document after assignment in the following section.

The IPFIX SELECTOR MIB registry as defined in [\[RFC5815\] Section 10](#) will be removed by IANA as its use is discontinued with this



document.

IANA will create and maintain a subregistry at <http://www.iana.org/assignments/smi-numbers> in which the toplevel OIDs in the subtree under object ipfixSelectorFunctions MUST be registered. The initial version of this subregistry should contain the following content:

Sub-registry Name: IPFIX-SELECTOR-MIB Functions

Reference: [ThisRFC]

Registration Procedures: Expert Review [[RFC5226](#)]

Prefix:

mib-2.ipfixSelectorMIB.ipfixSelectorObjects.ipfixSelectorFunctions  
(1.3.6.1.2.1.194.1.1)

Decimal	Name	Description	Reference
-----	----	-----	-----
1	ipfixFuncSelectAll	Select everything	[ThisRFC]

Additions to this subregistry are subject to Expert Review [[RFC5226](#)], i.e., review by one of a group of experts designated by an IETF Area Director. The group of experts MUST check the requested MIB objects for completeness and accuracy of the description. Requests for MIB objects that duplicate the functionality of existing objects SHOULD be declined. The smallest available OID SHOULD be assigned to new MIB objects. The specification of new MIB objects SHOULD follow the structure specified in [Section 6](#) and MUST be published using a well-established and persistent publication medium. The experts will initially be drawn from the Working Group Chairs and document editors of the IPFIX and PSAMP Working Groups.

## [11](#). Acknowledgments

This document is a product of the IPFIX Working Group. The authors would like to thank the following persons: Paul Aitken for his detailed review, Dan Romascanu and the MIB doctors, and many more, for the technical reviews and feedback.



## 12.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC2578] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Structure of Management Information Version 2 (SMIv2)", STD 58, [RFC 2578](#), April 1999.
- [RFC2579] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Textual Conventions for SMIv2", STD 58, [RFC 2579](#), April 1999.
- [RFC2580] McCloghrie, K., Perkins, D., and J. Schoenwaelder, "Conformance Statements for SMIv2", STD 58, [RFC 2580](#), April 1999.
- [RFC4001] Daniele, M., Haberman, B., Routhier, S., and J. Schoenwaelder, "Textual Conventions for Internet Network Addresses", [RFC 4001](#), February 2005.
- [RFC2863] McCloghrie, K. and F. Kastenholz, "The Interfaces Group MIB", [RFC 2863](#), June 2000.
- [RFC3873] Pastor, J. and M. Belinchon, "Stream Control Transmission Protocol (SCTP) Management Information Base (MIB)", [RFC 3873](#), September 2004.
- [RFC4133] Bierman, A. and K. McCloghrie, "Entity MIB (Version 3)", [RFC 4133](#), August 2005.
- [RFC5101] Claise, B., "Specification of the IP Flow Information Export (IPFIX) Protocol for the Exchange of IP Traffic Flow Information", [RFC 5101](#), January 2008.
- [RFC5102] Quittek, J., Bryant, S., Claise, B., Aitken, P., and J. Meyer, "Information Model for IP Flow Information Export", [RFC 5102](#), January 2008.
- [RFC5226] Narten, T. and H. Alvestrand, "Guidelines for Writing an IANA Considerations Section in RFCs", [BCP 26](#), [RFC 5226](#), May 2008.
- [RFC5815] Dietz, T., Kobayashi, A., Claise, B., and G. Muenz, "Definitions of Managed Objects for IP Flow Information Export", [RFC 5815](#), April 2010.

## 12.2. Informative References

- [RFC3410] Case, J., Mundy, R., Partain, D., and B. Stewart, "Introduction and Applicability Statements for Internet-Standard Management Framework", [RFC 3410](#), December 2002.
- [RFC3917] Quittek, J., Zseby, T., Claise, B., and S. Zander, "Requirements for IP Flow Information Export (IPFIX)", [RFC 3917](#), October 2004.
- [RFC5470] Sadasivan, G., Brownlee, N., Claise, B., and J. Quittek, "Architecture for IP Flow Information Export", [RFC 5470](#), March 2009.
- [RFC5472] Zseby, T., Boschi, E., Brownlee, N., and B. Claise, "IP Flow Information Export (IPFIX) Applicability", [RFC 5472](#), March 2009.
- [RFC5474] Duffield, N., Chiou, D., Claise, B., Greenberg, A., Grossglauser, M., and J. Rexford, "A Framework for Packet Selection and Reporting", [RFC 5474](#), March 2009.
- [RFC5475] Zseby, T., Molina, M., Duffield, N., Niccolini, S., and F. Raspall, "Sampling and Filtering Techniques for IP Packet Selection", [RFC 5475](#), March 2009.
- [RFC5476] Claise, B., Johnson, A., and J. Quittek, "Packet Sampling (PSAMP) Protocol Specifications", [RFC 5476](#), March 2009.

Internet-Draft

IPFIX MIB

January 2012

## Authors' Addresses

Thomas Dietz (editor)  
NEC Europe, Ltd.  
NEC Laboratories Europe  
Network Research Division  
Kurfuersten-Anlage 36  
Heidelberg 69115  
DE

Phone: +49 6221 4342-128  
Email: Thomas.Dietz@neclab.eu

Atsushi Kobayashi  
NTT Information Sharing Platform Laboratories  
3-9-11 Midori-cho  
Musashino-shi, Tokyo 180-8585  
JA

Phone: +81-422-59-3978  
Email: akoba@nttv6.net

Benoit Claise  
Cisco Systems, Inc.  
De Kleetlaan 6a b1  
Diegem 1831  
BE

Phone: +32 2 704 5622  
Email: bclaise@cisco.com

Gerhard Muenz  
Technische Universitaet Muenchen  
Department of Informatics  
Chair for Network Architectures and Services (I8)  
Boltzmannstr. 3

Garching 85748  
DE

Email: muenz@net.in.tum.de

Dietz, et al. [draft-ietf-ipfix-rfc5815bis-01.txt](#)

[Page 68]