

INTERNET-DRAFT

[draft-ietf-ipp-implementers-guide-01.txt](#)

T. Hastings  
Xerox Corporation  
C. Manros  
Xerox Corporation  
February 12, 1999

## **Internet Printing Protocol/1.0: Implementer's Guide**

Copyright (C) The Internet Society (1999). All Rights Reserved.

Status of this Memo

This document is an Internet-Draft and is in full conformance with all provisions of [Section 10 of \[RFC2026\]](#). Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress".

The list of current Internet-Drafts can be accessed at  
<http://www.ietf.org/ietf/1id-abstracts.txt>

The list of Internet-Draft Shadow Directories can be accessed as  
<http://www.ietf.org/shadow.html>.

### **Abstract**

This document is one of a set of documents, which together describe all aspects of a new Internet Printing Protocol (IPP). IPP is an application level protocol that can be used for distributed printing using Internet tools and technologies. This document contains information that supplements the IPP Model and Semantics [[IPP-MOD](#)] and the IPP Transport and Encoding [[IPP-PRO](#)] documents. It is intended to help implementers understand IPP/1.0 and some of the considerations that may assist them in the design of their client and/or IPP object implementations. For example, a typical order of processing requests is given, including error checking. Motivation for some of the specification decisions is also included.



Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's Guide February 12, 1999

The full set of IPP documents includes:

- Design Goals for an Internet Printing Protocol [[IPP-REQ](#)]
- Rationale for the Structure and Model and Protocol for the Internet Printing Protocol [[IPP-RAT](#)]
- Internet Printing Protocol/1.0: Model and Semantics [[IPP-MOD](#)]
- Internet Printing Protocol/1.0: Encoding and Transport [[IPP-PRO](#)]
- Mapping between LPD and IPP Protocols [IPP LPD]

The document, "Design Goals for an Internet Printing Protocol", takes a broad look at distributed printing functionality, and it enumerates real-life scenarios that help to clarify the features that need to be included in a printing protocol for the Internet. It identifies requirements for three types of users: end users, operators, and administrators. The design goals document calls out a subset of end user requirements that are satisfied in IPP/1.0. Operator and administrator requirements are out of scope for version 1.0.

The document, "Rationale for the Structure and Model and Protocol for the Internet Printing Protocol", describes IPP from a high level view, defines a roadmap for the various documents that form the suite of IPP specifications, and gives background and rationale for the IETF working group's major decisions.

The document, "Internet Printing Protocol/1.0: Model and Semantics", describes a simplified model with abstract objects, their attributes, and their operations. The model introduces a Printer and a Job. The Job supports multiple documents per Job. The model document also addresses how security, internationalization, and directory issues are addressed.

The document, "Internet Printing Protocol/1.0: Encoding and Transport", is a formal mapping of the abstract operations and attributes defined in the model document onto HTTP/1.1. It also defines the encoding rules for a new Internet media type called "application/ipp".

The document, "Mapping between LPD and IPP Protocols", gives some advice to implementers of gateways between IPP and LPD (Line Printer Daemon) implementations.



Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's GuideFebruary 12, 1999

## TABLE OF CONTENTS

<a href="#">1</a>	Introduction.....	<a href="#">5</a>
<a href="#">1.1</a>	Conformance language.....	<a href="#">5</a>
<a href="#">1.2</a>	Other terminology.....	<a href="#">5</a>
<a href="#">2</a>	Model and Semantics.....	<a href="#">5</a>
<a href="#">2.1</a>	Summary of Operation Attributes.....	<a href="#">5</a>
<a href="#">2.2</a>	Suggested Operation Processing Steps for IPP Objects (Issue 1.21)	<a href="#">9</a>
<a href="#">2.2.1</a>	Suggested Operation Processing Steps for all Operations....	<a href="#">10</a>
<a href="#">2.2.1.1</a>	Validate version number.....	<a href="#">10</a>
<a href="#">2.2.1.2</a>	Validate operation identifier.....	<a href="#">11</a>
<a href="#">2.2.1.3</a>	Validate the request identifier.....	<a href="#">11</a>
<a href="#">2.2.1.4</a>	Validate attribute group and attribute presence and order	<a href="#">11</a>
<a href="#">2.2.1.5</a>	Validate the values of the REQUIRED Operation attributes	<a href="#">18</a>
<a href="#">2.2.1.6</a>	Validate the values of the OPTIONAL Operation attributes	<a href="#">22</a>
<a href="#">2.2.2</a>	Suggested Additional Processing Steps for Operations that Create/Validate Jobs and Add Documents.....	<a href="#">24</a>
<a href="#">2.2.2.1</a>	Default "ipp-attribute-fidelity" if not supplied.....	<a href="#">24</a>
<a href="#">2.2.2.2</a>	Check that the Printer object is accepting jobs.....	<a href="#">24</a>
<a href="#">2.2.2.3</a>	Validate the values of the Job Template attributes.....	<a href="#">24</a>
<a href="#">2.2.3</a>	Algorithm for job validation.....	<a href="#">25</a>
<a href="#">2.2.3.1</a>	Check for conflicting Job Template attributes values....	<a href="#">30</a>
<a href="#">2.2.3.2</a>	Decide whether to REJECT the request.....	<a href="#">30</a>
<a href="#">2.2.3.3</a>	For the Validate-Job operation, RETURN one of the success status codes.....	<a href="#">31</a>
<a href="#">2.2.3.4</a>	Create the Job object with attributes to support.....	<a href="#">31</a>
<a href="#">2.2.3.5</a>	Return one of the success status codes.....	<a href="#">33</a>
<a href="#">2.2.3.6</a>	Accept appended Document Content.....	<a href="#">33</a>
<a href="#">2.2.3.7</a>	Scheduling and Starting to Process the Job.....	<a href="#">33</a>
<a href="#">2.2.3.8</a>	Completing the Job.....	<a href="#">33</a>
<a href="#">2.2.3.9</a>	Destroying the Job after completion.....	<a href="#">34</a>
<a href="#">2.2.3.10</a>	Interaction with "ipp-attribute-fidelity".....	<a href="#">34</a>
<a href="#">2.3</a>	Status codes returned by operation (Issue 1.50).....	<a href="#">34</a>
<a href="#">2.3.1</a>	Printer Operations.....	<a href="#">34</a>
<a href="#">2.3.1.1</a>	Print-Job.....	<a href="#">34</a>
<a href="#">2.3.1.2</a>	Print-URI.....	<a href="#">36</a>
<a href="#">2.3.1.3</a>	Validate-Job.....	<a href="#">37</a>
<a href="#">2.3.1.4</a>	Create-Job.....	<a href="#">37</a>
<a href="#">2.3.1.5</a>	Get-Printer-Attributes.....	<a href="#">37</a>
<a href="#">2.3.1.6</a>	Get-Jobs.....	<a href="#">38</a>

<a href="#">2.3.2</a>	Job Operations.....	<a href="#">38</a>
<a href="#">2.3.2.1</a>	Send-Document.....	<a href="#">38</a>
<a href="#">2.3.2.2</a>	Send-URI.....	<a href="#">39</a>
<a href="#">2.3.2.3</a>	Cancel-Job.....	<a href="#">39</a>
<a href="#">2.3.2.4</a>	Get-Job-Attributes.....	<a href="#">40</a>
<a href="#">2.4</a>	Validate-Job.....	<a href="#">41</a>
<a href="#">2.5</a>	Case Sensitivity in URIs (issue 1.6).....	<a href="#">41</a>
<a href="#">2.6</a>	Character Sets, natural languages, and internationalization....	<a href="#">41</a>
<a href="#">2.6.1</a>	Character set code conversion support (Issue 1.5).....	<a href="#">41</a>
2.6.2	What charset to return when an unsupported charset is requested (Issue 1.19)?.....	<a href="#">42</a>

Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's GuideFebruary 12, 1999

2.6.3	Natural Language Override (NLO) (Issue 1.45).....	43
2.7	The "queued-job-count" Printer Description attribute.....	44
2.7.1	Why is "queued-job-count" RECOMMENDED (Issue 1.14)?.....	44
2.7.2	Is "queued-job-count" a good measure of how busy a printer is (Issue 1.15)?.....	45
2.8	Sending empty attribute groups (Issue 1.16).....	45
2.9	Returning unsupported attributes in Get-Xxxx responses (Issue 1.18).....	45
2.10	Returning job-state in Print-Job response (Issue 1.30).....	46
2.11	Flow controlling the data portion of a Print-Job request (Issue 1.22).....	46
2.12	Multi-valued attributes (Issue 1.31).....	47
2.13	Querying jobs with IPP that were submitted using other job submission protocols (Issue 1.32).....	47
2.14	The 'none' value for empty sets (Issue 1.37).....	48
2.15	Get-Jobs, my-jobs='true', and 'requesting-user-name' (Issue 1.39)? 48	
2.16	The "multiple-document-handling" Job Template attribute and support of multiple document jobs.....	48
3	Encoding and Transport.....	49
3.1	General Headers.....	50
3.2	Request Headers.....	50
3.3	Response Headers.....	52
3.4	Entity Headers.....	52
3.5	Optional support for HTTP/1.0.....	53
3.6	HTTP/1.1 Chunking.....	53
3.6.1	Disabling IPP Server Response Chunking.....	53
3.6.2	Warning About the Support of Chunked Requests.....	54
4	References.....	54
4.1	Authors. Address.....	55
5	Notices.....	<b>Error! Bookmark not defined.</b>
6	Change History.....	56
6.1	Changes to produce the February 12, 1999 version from the January 8, 1999 version:.....	57
6.2	Changes to produce the January 8, 1999 version from the December 6, 1998 version:.....	57
6.3	Changes to produce the December 6, 1998 version from the November 16, 1998 version:.....	57





Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's Guide February 12, 1999

## **1 Introduction**

This document contains information that supplements the IPP Model and Semantics [[IPP-MOD](#)] and the IPP Transport and Encoding [[IPP-PRO](#)] documents. As such this information is not part of the formal specifications. Instead information is presented to help implementers understand the specification, including some of the motivation for decisions taken by the committee in developing the specification. Some of the implementation considerations are intended to help implementers design their client and/or IPP object implementations. If there are any contradictions between this document and [[IPP-MOD](#)] or [[IPP-PRO](#)], those documents take precedence over this document.

### **1.1 Conformance language**

Usually, this document does not contain the terminology MUST, MUST NOT, MAY, NEED NOT, SHOULD, SHOULD NOT, REQUIRED, and OPTIONAL. However, when those terms do appear in this document, their intent is to repeat what the [[IPP-MOD](#)] and [[IPP-PRO](#)] documents require and allow, rather than specifying additional conformance requirements. These terms are defined in [section 13](#) on conformance terminology in [[IPP-MOD](#)], most of which is taken from [RFC 2119](#) [[RFC2119](#)].

Implementers should read section 13 in [[IPP-MOD](#)] in order to understand these capitalized words. The words MUST, MUST NOT, and REQUIRED indicate what implementations are required to support in a client or IPP object in order to be conformant to [[IPP-MOD](#)] and [[IPP-PRO](#)]. MAY, NEED NOT, and OPTIONAL indicate what is merely allowed as an implementer option. The verbs SHOULD and SHOULD NOT indicate suggested behavior, but which is not required or disallowed, respectively, in order to conform to the specification.

### **1.2 Other terminology**

The term "sender" refers to the client that sends a request or an IPP object that returns a response. The term "receiver" refers to the IPP object that receives a request and to a client that receives a response.

## **[2](#) Model and Semantics**

This section discusses various aspects of IPP/1.0 Model and Semantics [[IPP-MOD](#)].

### **[2.1](#) Summary of Operation Attributes**

Legend for the following table:

Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's Guide February 12, 1999

R indicates a REQUIRED operation or attribute for an implementation to support

O indicates an OPTIONAL operation or attribute for an implementation to support

Table 1. Summary of operation attributes

Operation Attributes	Job Operations				
	Requests				Responses
	Send- Documen t (0)	Send- URI (0)	Cancel -Job	Get- Job- Attribu tes	All Opera tions
Operation parameters--REQUIRED to be supplied by the sender					
operation-id	R	R	R	R	
status-code					R
request-id	R	R	R	R	R
version-number	R	R	R	R	R
Operation attributes--REQUIRED to be supplied by the sender					
attributes- charset	R	R	R	R	R
attributes- natural-language	R	R	R	R	R
document-uri		R			
job-id*	R	R	R	R	
job-uri*	R	R	R	R	
last-document	R	R			
printer-uri	R	R	R	R	

Operation attributes.RECOMMENDED to be supplied by the sender

job-name

requesting-user-name	R	R	R	R
----------------------	---	---	---	---

Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's Guide February 12, 1999

## Printer Operations

Operation Attributes	Requests				Responses	
	Print- Job, Valida te-Job	Pri nt- URI (0)	Crea te- Job (0)	Get- Printe r- Attrib utes	Get- Jobs	All Operat ions

Operation attributes.OPTIONAL to be supplied by the sender

status-message 0

compression 0 0

document-format R R 0

document-name 0 0

document-natural-  
language 0 0

ipp-attribute-  
fidelity R R R

job-impressions 0 0 0

job-k-octets 0 0 0

job-media-sheets 0 0 0

limit R

message

my-jobs R

requested-  
attributes R R

which-jobs R

\* "job-id" is REQUIRED only if used together with

"printer-uri" to identify the target job; otherwise, "job-uri" is REQUIRED.

Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's Guide February 12, 1999

Table 2. Summary of operation attributes

Printer Operations						
Operation Attributes	Requests					Responses
	Print- Job, Validate -Job	Pri nt- URI (0)	Crea te- Job (0)	Get- Printer- Attribut es	Get- Jobs	All Opera tions
Operation parameters--REQUIRED to be supplied by the sender						
operation-id	R	R	R	R	R	
status-code						R
request-id	R	R	R	R	R	R
version-number	R	R	R	R	R	R
Operation attributes.REQUIRED to be supplied by the sender						
attributes-charset	R	R	R	R	R	R
attributes- natural-language	R	R	R	R	R	R
document-uri		R				
job-id*						
job-uri*						
last-document						
printer-uri	R	R	R	R	R	
Operation attributes.RECOMMENDED to be supplied by the sender						
job-name	R	R	R			
requesting-user- name	R	R	R	R	R	





Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's Guide February 12, 1999

## Job Operations

Operation Attributes	Requests			Responses	
	Send-Document (0)	Send-URI (0)	Cancel-Job	Get-Job-Attributes	All Operations
Operation attributes.OPTIONAL to be supplied by the sender					
status-message					0
compression	0	0			
document-format	R	R			
document-name	0	0			
document-natural-language	0	0			
ipp-attribute-fidelity					
job-impressions					
job-k-octets					
job-media-sheets					
limit					
message				0	
my-jobs					
requested-attributes				R	
which-jobs					

\* "job-id" is REQUIRED only if used together with "printer-uri" to identify the target job; otherwise, "job-uri" is REQUIRED.

## **2.2 Suggested Operation Processing Steps for IPP Objects (Issue 1.21)**

This section suggests the steps and error checks that an IPP object MAY perform when processing requests and returning responses. An IPP object MAY perform some or all of the error checks. However, some implementations MAY choose to be more forgiving than the error checks shown here, in order to be able to accept requests from non-conforming clients. Not performing all of these error checks is a so-called "forgiving" implementation. On the other hand, clients that successfully submit requests to IPP objects that do perform all the error checks will be more likely to be able to interoperate with other IPP object implementations. Thus an implementer of an IPP object needs to decide whether to be a "forgiving" or a "strict" implementation. Therefore, the error status codes returned may differ between implementations. Consequentially, client SHOULD NOT expect exactly the error code processing described in this section.

When an IPP object receives a request, the IPP object either accepts or rejects the request. In order to determine whether or not to accept or reject the request, the IPP object SHOULD execute the following steps.

Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's Guide February 12, 1999

The order of the steps may be rearranged and/or combined, including making one or multiple passes over the request.

A client **MUST** supply requests that would pass all of the error checks indicated here in order to be a conforming client. Therefore, a client **SHOULD** supply requests that are conforming, in order to avoid being rejected by some IPP object implementations and/or risking different semantics by different implementations of forgiving implementations. For example, a forgiving implementation that accepts multiple occurrences of the same attribute, rather than rejecting the request might use the first occurrences, while another might use the last occurrence. Thus such a non-conforming client would get different results from the two forgiving implementations.

In the following, processing continues step by step until a "RETURNS the xxx status code ." statement is encountered. Error returns are indicated by the verb: "REJECTS". Since clients have difficulty getting the status code before sending all of the document data in a Print-Job request, clients **SHOULD** use the Validate-Job operation before sending large documents to be printed, in order to validate whether the IPP Printer will accept the job or not.

It is assumed that security authentication and authorization has already taken place at a lower layer.

#### 2.2.1 Suggested Operation Processing Steps for all Operations

This section is intended to apply to all operations. The next section contains the additional steps for the Print-Job, Validate-Job, Print-URI, Create-Job, Send-Document, and Send-URI operations that create jobs, adds documents, and validates jobs.

##### [2.2.1.1](#) **Validate version number**

Every request and every response contains the "version-number" attribute. The value of this attribute is the major and minor version number of the syntax and semantics that the client and IPP object is using, respectively. The "version-number" attribute remains in a fixed position across all future versions so that all clients and IPP object that support future versions can determine which version is being used. The IPP object checks to see if the major version number supplied in the request is supported. If not, the Printer object **REJECTS** the request and **RETURNS** the 'server-error-version-not-supported' status code in the

response. The IPP object returns in the "version-number" response attribute the major and minor version for the error response. Thus the client can learn at least one major and minor version that the IPP object supports. The IPP object is encouraged to return the closest version number to the one supplied by the client.

The checking of the minor version number is implementation dependent, however if the client supplied minor version is explicitly supported, the IPP object MUST respond using that identical minor version number. If the requested minor version is not supported (the requested minor

Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's Guide February 12, 1999

version is either higher or lower) than a supported minor version, the IPP object SHOULD return the closest supported minor version.

#### **2.2.1.2 Validate operation identifier**

The Printer object checks to see if the "operation-id" attribute supplied by the client is supported as indicated in the Printer object's "operations-supported" attribute. If not, the Printer REJECTS the request and returns the 'server-error-operation-not-supported' status code in the response.

#### **2.2.1.3 Validate the request identifier**

The Printer object SHOULD NOT check to see if the "request-id" attribute supplied by the client is in range: between 1 and  $2^{31} - 1$  (inclusive), but copies all 32 bits.

Note: The "version-number", "operation-id", and the "request-id" parameters are in fixed octet positions in the IPP/1.0 encoding. The "version-number" parameter will be the same fixed octet position in all versions of the protocol. These fields are validated before proceeding with the rest of the validation.

#### **2.2.1.4 Validate attribute group and attribute presence and order**

The order of the following validation steps depends on implementation.

##### **2.2.1.4.1 Validate the presence and order of attribute groups**

Client requests and IPP object responses contain attribute groups that [Section 3](#) requires to be present and in a specified order. An IPP object verifies that the attribute groups are present and in the correct order in requests supplied by clients (attribute groups without an \* in the following tables).

If an IPP object receives a request with (1) required attribute groups missing, or (2) the attributes groups are out of order, or (3) the groups are repeated, the IPP object REJECTS the request and RETURNS the 'client-error-bad-request' status code. For example, it is an error for the Job Template Attributes group to occur before the Operation Attributes group, for the Operation Attributes group to be omitted, or for an attribute group to occur more than once, except in the Get-Jobs

response.

Since this kind of attribute group error is most likely to be an error detected by a client developer rather than by a customer, the IPP object NEED NOT return an indication of which attribute group was in error in either the Unsupported Attributes group or the Status Message. Also, the IPP object NEED NOT find all attribute group errors before returning this error.

Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's Guide February 12, 1999

#### **2.2.1.4.2 Ignore unknown attribute groups in the expected position**

Future attribute groups may be added to the specification at the end of requests just before the Document Content and at the end of response, except for the Get-Jobs response, where it maybe there or before the first job attributes returned. If an IPP object receives an unknown attribute group in these positions, it ignores the entire group, rather than returning an error, since that group may be a new group in a later minor version of the protocol that can be ignored. (If the new attribute group cannot be ignored without confusing the client, the major version number would have been increased in the protocol document and in the request). If the unknown group occurs in a different position, the IPP object REJECTS the request and RETURNS the 'client-error-bad-request' status code.

Clients also ignore unknown attribute groups returned in a response.

Note: By validating that requests are in the proper form, IPP objects force clients to use the proper form which, in turn, increases the chances that customers will be able to use such clients from multiple vendors with IPP objects from other vendors.

#### **2.2.1.4.3 Validate the presence of a single occurrence of required Operation attributes**

Client requests and IPP object responses contain Operation attributes that [IPP-MOD] [Section 3](#) requires to be present. Attributes within a group may be in any order, except for the ordering of target, charset, and natural languages attributes. These attributes MUST be first, and MUST be supplied in the following order: charset, natural language, and then target. An IPP object verifies that the attributes that [Section 4](#) requires to be supplied by the client have been supplied in the request (attributes without an \* in the following tables). An asterisk (\*) indicates groups and Operation attributes that the client may omit in a request or an IPP object may omit in a response.

If an IPP object receives a request with required attributes missing or repeated from a group or in the wrong position, the behavior of the IPP object is IMPLEMENTATION DEPENDENT. Some of the possible implementations are:

1. REJECTS the request and RETURNS the 'client-error-bad-request' status code
2. accepts the request and uses the first occurrence of the

attribute no matter where it is

3.accepts the request and uses the last occurrence of the  
attribute no matter where it is

4.accept the request and assume some default value for the missing  
attribute



Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's Guide February 12, 1999

Therefore, client MUST send conforming requests, if they want to receive the same behavior from all IPP object implementations. For example, it is an error for the "attributes-charset" or "attributes-natural-language" attribute to be omitted in any operation request, or for an Operation attribute to be supplied in a Job Template group or a Job Template attribute to be supplied in an Operation Attribute group in a create request. It is also an error to supply the "attributes-charset" attribute twice.

Since these kinds of attribute errors are most likely to be detected by a client developer rather than by a customer, the IPP object NEED NOT return an indication of which attribute was in error in either the Unsupported Attributes group or the Status Message. Also, the IPP object NEED NOT find all attribute errors before returning this error.

The following tables list all the attributes for all the operations by attribute group in each request and each response. The order of the groups is the order that the client supplies the groups as specified in [\[IPP-MOD\] Section 3](#). The order of the attributes within a group is arbitrary, except as noted for some of the special operation attributes (charset, natural language, and target). The tables below use the following notation:

- R indicates a REQUIRED attribute that an IPP object MUST support
- O indicates an OPTIONAL attribute that an IPP object NEED NOT support
- \* indicates that a client MAY omit the attribute in a request and that an IPP object MAY omit the attribute in a response. The absence of an \* means that a client MUST supply the attribute in a request and an IPP object MUST supply the attribute in a response.

#### Operation Requests

The tables below show the attributes in their proper attribute groups for operation requests:

Note: All operation requests contain "version-number", "operation-id", and "request-id" parameters.



Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's Guide February 12, 1999

Print-Job Request:

- Group 1: Operation Attributes (R)
  - attributes-charset (R)
  - attributes-natural-language (R)
  - printer-uri (R)
  - requesting-user-name (R\*)
  - job-name (R\*)
  - ipp-attribute-fidelity (R\*)
  - document-name (R\*)
  - document-format (R\*)
  - document-natural-language (O\*)
  - compression (O\*)
  - job-k-octets (O\*)
  - job-impressions (O\*)
  - job-media-sheets (O\*)
- Group 2: Job Template Attributes (R\*)
  - <Job Template attributes> (O\*)
  - (see [[IPP-MOD](#)] [Section 4.2](#))
- Group 3: Document Content (R)
  - <document content>

Validate-Job Request:

- Group 1: Operation Attributes (R)
  - attributes-charset (R)
  - attributes-natural-language (R)
  - printer-uri (R)
  - requesting-user-name (R\*)
  - job-name (R\*)
  - ipp-attribute-fidelity (R\*)
  - document-name (R\*)
  - document-format (R\*)
  - document-natural-language (O\*)
  - compression (O\*)
  - job-k-octets (O\*)
  - job-impressions (O\*)
  - job-media-sheets (O\*)
- Group 2: Job Template Attributes (R\*)
  - <Job Template attributes> (O\*)
  - (see [[IPP-MOD](#)] [Section 4.2](#))

Create-Job Request:

- Group 1: Operation Attributes (R)
  - attributes-charset (R)
  - attributes-natural-language (R)

printer-uri (R)  
requesting-user-name (R\*)  
job-name (R\*)  
ipp-attribute-fidelity (R\*)  
job-k-octets (0\*)  
job-impressions (0\*)  
job-media-sheets (0\*)  
Group 2: Job Template Attributes (R\*)  
    <Job Template attributes> (0\*) (see  
        (see [[IPP-MOD](#)] [Section 4.2](#))

Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's Guide February 12, 1999

Print-URI Request:

Group 1: Operation Attributes (R)  
attributes-charset (R)  
attributes-natural-language (R)  
printer-uri (R)  
document-uri (R)  
requesting-user-name (R\*)  
job-name (R\*)  
ipp-attribute-fidelity (R\*)  
document-name (R\*)  
document-format (R\*)  
document-natural-language (O\*)  
compression (O\*)  
job-k-octets (O\*)  
job-impressions (O\*)  
job-media-sheets (O\*)  
Group 2: Job Template Attributes (R\*)  
<Job Template attributes> (O\*) (see  
(see [[IPP-MOD](#)] [Section 4.2](#))

Send-Document Request:

Group 1: Operation Attributes (R)  
attributes-charset (R)  
attributes-natural-language (R)  
(printer-uri & job-id) | job-uri (R)  
last-document (R)  
requesting-user-name (R\*)  
document-name (R\*)  
document-format (R\*)  
document-natural-language (O\*)  
compression (O\*)  
Group 2: Document Content (R\*)  
<document content>

Send-URI Request:

Group 1: Operation Attributes (R)  
attributes-charset (R)  
attributes-natural-language (R)  
(printer-uri & job-id) | job-uri (R)  
last-document (R)  
document-uri (R)  
requesting-user-name (R\*)  
document-name (R\*)

document-format (R\*)  
document-natural-language (0\*)  
compression (0\*)

Cancel-Job Request:

Group 1: Operation Attributes (R)  
attributes-charset (R)  
attributes-natural-language (R)  
(printer-uri & job-id) | job-uri (R)  
requesting-user-name (R\*)

Hastings, Manros

[page 15]

Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's Guide February 12, 1999

message (0\*)

Get-Printer-Attributes Request:

Group 1: Operation Attributes (R)  
attributes-charset (R)  
attributes-natural-language (R)  
printer-uri (R)  
requesting-user-name (R\*)  
requested-attributes (R\*)  
document-format (R\*)

Get-Job-Attributes Request:

Group 1: Operation Attributes (R)  
attributes-charset (R)  
attributes-natural-language (R)  
(printer-uri & job-id) | job-uri (R)  
requesting-user-name (R\*)  
requested-attributes (R\*)

Get-Jobs Request:

Group 1: Operation Attributes (R)  
attributes-charset (R)  
attributes-natural-language (R)  
printer-uri (R)  
requesting-user-name (R\*)  
limit (R\*)  
requested-attributes (R\*)  
which-jobs (R\*)  
my-jobs (R\*)

## Operation Responses

The tables below show the response attributes in their proper attribute groups for responses.

Note: All operation responses contain "version-number", "status-code", and "request-id" parameters.





Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's Guide February 12, 1999

Print-Job Response:

Print-URI Response:

Create-Job Response:

Send-Document Response:

Send-URI Response:

Group 1: Operation Attributes (R)

attributes-charset (R)

attributes-natural-language (R)

status-message (0\*)

Group 2: Unsupported Attributes (R\*) (see Note 3)

<unsupported attributes> (R\*)

Group 3: Job Object Attributes (R\*) (see Note 2)

job-uri (R)

job-id (R)

job-state (R)

job-state-reasons (0\*)

job-state-message (0\*)

number-of-intervening-jobs (0\*)

Validate-Job Response:

Cancel-Job Response:

Group 1: Operation Attributes (R)

attributes-charset (R)

attributes-natural-language (R)

status-message (0\*)

Group 2: Unsupported Attributes (R\*) (see Note 3)

<unsupported attributes> (R\*)

Note 2 - the Job Object Attributes and Printer Object Attributes are returned only if the IPP object returns one of the success status codes.

Note 3 - the Unsupported Attributes Group is present only if the client included some Operation and/or Job Template attributes or values that the Printer doesn't support whether a success or an error return.

Get-Printer-Attributes Response:

Group 1: Operation Attributes (R)

attributes-charset (R)

attributes-natural-language (R)

status-message (0\*)

Group 2: Unsupported Attributes (R\*) (see Note 4)

<unsupported attributes> (R\*)

Group 3: Printer Object Attributes(R\*) (see Note 2)

<requested attributes> (R\*)

Note 4 - the Unsupported Attributes Group is present only if the client included some Operation attributes that the Printer doesn't support whether a success or an error return.

Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's Guide February 12, 1999

Get-Job-Attributes Response:

- Group 1: Operation Attributes (R)
  - attributes-charset (R)
  - attributes-natural-language (R)
  - status-message (O\*)
- Group 2: Unsupported Attributes (R\*) (see Note 4)
  - <unsupported attributes> (R\*)
- Group 3: Job Object Attributes(R\*) (see Note 2)
  - <requested attributes> (R\*)

Get-Jobs Response:

- Group 1: Operation Attributes (R)
  - attributes-charset (R)
  - attributes-natural-language (R)
  - status-message (O\*)
- Group 2: Unsupported Attributes (R\*) (see Note 4)
  - <unsupported attributes> (R\*)
- Group 3: Job Object Attributes(R\*) (see Note 2, 5)
  - <requested attributes> (R\*)

Note 5: for the Get-Jobs operation the response contains a separate Job Object Attributes group 3 to N containing requested-attributes for each job object in the response.

#### **2.2.1.5 Validate the values of the REQUIRED Operation attributes**

An IPP object validates the values supplied by the client of the REQUIRED Operation attribute that the IPP object MUST support. The next section specifies the validation of the values of the OPTIONAL Operation attributes that IPP objects MAY support.

The IPP object performs the following syntactic validation checks of each Operation attribute value:

- a)that the length of each Operation attribute value is correct for the attribute syntax tag supplied by the client according to [\[IPP-MOD\] Section 4.1](#),
- b)that the attribute syntax tag is correct for that Operation attribute according to [\[IPP-MOD\] Section 3](#),

c)that the value is in the range specified for that Operation attribute according to [[IPP-MOD](#)] [Section 3](#),

d)that multiple values are supplied by the client only for operation attributes that are multi-valued, i.e., that are 1setOf X according to [[IPP-MOD](#)] [Section 3](#).

If any of these checks fail, the IPP object REJECTS the request and RETURNS the 'client-error-bad-request' or the 'client-error-request-value-too-long' status code. Since such an error is most likely to be an error detected by a client developer, rather than by an end-user, the

Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's Guide February 12, 1999

IPP object NEED NOT return an indication of which attribute had the error in either the Unsupported Attributes Group or the Status Message. The description for each of these syntactic checks is explicitly expressed in the first IF statement in the following table.

In addition, the IPP object checks each Operation attribute value against some Printer object attribute or some hard-coded value if there is no "xxx-supported" Printer object attribute defined. If its value is not among those supported or is not in the range supported, then the IPP object REJECTS the request and RETURNS the error status code indicated in the table by the second IF statement. If the value of the Printer object's "xxx-supported" attribute is 'no-value' (because the system administrator hasn't configured a value), the check always fails.

-----

attributes-charset (charset)

IF NOT a single non-empty 'charset' value, REJECT/RETURN 'client-error-request-bad-request'.  
IF the value length is greater than 63 octets, REJECT/RETURN 'client-error-request-value-too-long'.  
IF NOT in the Printer object's "charset-supported" attribute, REJECT/RETURN "client-error-charset-not-supported".

attributes-natural-language(naturalLanguage)

IF NOT a single non-empty 'naturalLanguage' value, REJECT/RETURN 'client-error-request-bad-request'.  
IF the value length is greater than 63 octets, REJECT/RETURN 'client-error-request-value-too-long'.  
ACCEPT the request even if not a member of the set in the Printer object's "generated-natural-language-supported" attribute. If the supplied value is not a member of the Printer object's "generated-natural-language-supported" attribute, use the Printer object's "natural-language-configured" value.

requesting-user-name

IF NOT a single 'name' value, REJECT/RETURN 'client-error-request-bad-request'.  
IF the value length is greater than 255 octets, REJECT/RETURN

'client-error-request-value-too-long'.

IF the IPP object can obtain a better authenticated name, use it instead.

job-name(name)

IF NOT a single 'name' value, REJECT/RETURN 'client-error-request-bad-request'.

IF the value length is greater than 255 octets, REJECT/RETURN 'client-error-request-value-too-long'.

IF NOT supplied by the client, the Printer object creates a name from the document-name or document-uri.

Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's Guide February 12, 1999

document-name (name)

IF NOT a single 'name' value, REJECT/RETURN 'client-error-request-bad-request'.

IF the value length is greater than 255 octets, REJECT/RETURN 'client-error-request-value-too-long'.

ipp-attribute-fidelity (boolean)

IF NEITHER a single 'true' NOR a single 'false' 'boolean' value, REJECT/RETURN 'client-error-bad-request'.

IF the value length is NOT equal to 1 octet, REJECT/RETURN 'client-error-request-value-too-long'

IF NOT supplied by the client, the IPP object assumes the value 'false'.

document-format (mimeType)

IF NOT a single non-empty 'mimeType' value, REJECT/RETURN 'client-error-request-bad-request'.

IF the value length is greater than 255 octets, REJECT/RETURN 'client-error-request-value-too-long'.

IF NOT in the Printer object's "document-format-supported" attribute, REJECT/RETURN 'client-error-document-format-not-supported'

IF NOT supplied by the client, the IPP object assumes the value of the Printer object's "document-format-default" attribute.

document-uri (uri)

IF NOT a single non-empty 'uri' value, REJECT/RETURN 'client-error-request-bad-request'.

IF the value length is greater than 1023 octets, REJECT/RETURN 'client-error-request-value-too-long'.

IF the URI syntax is not valid, REJECT/RETURN 'client-error-bad-request'.

IF scheme is NOT in the Printer object's "reference-uri-schemes-supported" attribute, REJECT/RETURN 'client-error-uri-scheme-not-supported'.

The Printer object MAY check to see if the document exists and is accessible. If the document is not found or is not accessible, REJECT/RETURN 'client-error-not found'.

last-document (boolean)

IF NEITHER a single 'true' NOR a single 'false' 'boolean' value,  
REJECT/RETURN 'client-error-bad-request'.

IF the value length is NOT equal to 1 octet, REJECT/RETURN 'client-  
error-request-value-too-long'

job-id (integer(1:MAX))

IF NOT an single 'integer' value equal to 4 octets AND in the range 1  
to MAX, REJECT/RETURN 'client-error-bad-request'.



Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's Guide February 12, 1999

IF NOT a job-id of an existing Job object, REJECT/RETURN 'client-error-not-found' or 'client-error-gone' status code, if keep track of recently deleted jobs.

requested-attributes (1setOf keyword)

IF NOT one or more 'keyword' values, REJECT/RETURN 'client-error-request-bad-request'.

IF the value length is greater than 255 octets, REJECT/RETURN 'client-error-request-value-too-long'.

Ignore unsupported values which are the keyword names of unsupported attributes. Don't bother to copy such requested (unsupported) attributes to the Unsupported Attribute response group since the response will not return them.

which-jobs (type2 keyword)

IF NOT a single 'keyword' value, REJECT/RETURN 'client-error-request-bad-request'.

IF the value length is greater than 255 octets, REJECT/RETURN 'client-error-request-value-too-long'.

IF NEITHER 'completed' NOR 'not-completed', copy the attribute and the unsupported value to the Unsupported Attributes response group and REJECT/RETURN 'client-error-attributes-or-values-not-supported'.

Note: a Printer still supports the 'completed' value even if it keeps no completed/canceled/aborted jobs: by returning no jobs when so queried.

IF NOT supplied by the client, the IPP object assumes the 'not-completed' value.

my-jobs (boolean)

IF NEITHER a single 'true' NOR a single 'false' 'boolean' value, REJECT/RETURN 'client-error-bad-request'.

IF the value length is NOT equal to 1 octet, REJECT/RETURN 'client-error-request-value-too-long'

IF NOT supplied by the client, the IPP object assumes the 'false' value.

limit (integer(1:MAX))

IF NOT a single 'integer' value equal to 4 octets AND in the range 1  
to MAX, REJECT/RETURN 'client-error-bad-request'.  
IF NOT supplied by the client, the IPP object returns all jobs, no  
matter how many.

-----

Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's Guide February 12, 1999

#### **2.2.1.6 Validate the values of the OPTIONAL Operation attributes**

OPTIONAL Operation attributes are those that an IPP object MAY or MAY NOT support. An IPP object validates the values of the OPTIONAL attributes supplied by the client. The IPP object performs the same syntactic validation checks for each OPTIONAL attribute value as in [Section 2.2.1.5](#). As in [Section 2.2.1.5](#), if any fail, the IPP object REJECTS the request and RETURNS the 'client-error-bad-request' or the 'client-error-request-value-too-long' status code.

In addition, the IPP object checks each Operation attribute value against some Printer attribute or some hard-coded value if there is no "xxx-supported" Printer attribute defined. If its value is not among those supported or is not in the range supported, then the IPP object REJECTS the request and RETURNS the error status code indicated in the table. If the value of the Printer object's "xxx-supported" attribute is 'no-value' (because the system administrator hasn't configured a value), the check always fails.

If the IPP object doesn't recognize/support an attribute, the IPP object treats the attribute as an unknown or unsupported attribute (see the last row in the table below).

-----

document-natural-language (naturalLanguage)

IF NOT a single non-empty 'naturalLanguage' value, REJECT/RETURN 'client-error-request-bad-request'.  
IF the value length is greater than 63 octets, REJECT/RETURN 'client-error-request-value-too-long'.  
IF NOT a value that the Printer object supports in document formats, (no corresponding "xxx-supported" Printer attribute), REJECT/RETURN 'client-error-natural-language-not-supported'.

compression (type3 keyword)

IF NOT a single 'keyword' value, REJECT/RETURN 'client-error-request-bad-request'.  
IF the value length is greater than 255 octets, REJECT/RETURN 'client-error-request-value-too-long'.  
IF NOT in the Printer object's "compression-supported" attribute, copy the attribute and the unsupported value to the Unsupported

Attributes response group and REJECT/RETURN 'client-error-attributes-or-values-not-supported'.

job-k-octets (integer(0:MAX))

IF NOT a single 'integer' value equal to 4 octets,  
REJECT/RETURN 'client-error-bad-request'.

IF NOT in the range of the Printer object's "job-k-octets-supported" attribute, copy the attribute and the unsupported value to the Unsupported Attributes response group and REJECT/RETURN 'client-error-attributes-or-values-not-supported'.

Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's Guide February 12, 1999

job-impressions (integer(0:MAX))

IF NOT a single 'integer' value equal to 4 octets,  
REJECT/RETURN 'client-error-bad-request'.

IF NOT in the range of the Printer object's "job-impressions-  
supported" attribute, copy the attribute and the unsupported value  
to the Unsupported Attributes response group and REJECT/RETURN  
'client-error-attributes-or-values-not-supported'.

job-media-sheets (integer(0:MAX))

IF NOT a single 'integer' value equal to 4 octets,  
REJECT/RETURN 'client-error-bad-request'.

IF NOT in the range of the Printer object's "job-media-sheets-  
supported" attribute, copy the attribute and the unsupported value  
to the Unsupported Attributes response group and REJECT/RETURN  
'client-error-attributes-or-values-not-supported'.

message (text(127))

IF NOT a single 'text' value, REJECT/RETURN 'client-error-request-  
bad-request'.

IF the value length is greater than 127 octets,  
REJECT/RETURN 'client-error-request-value-too-long'.

unknown or unsupported attribute

IF the attribute syntax supplied by the client is supported but the  
length is not legal for that attribute syntax, REJECT/RETURN  
'client-error-request-value-too-long'.

ELSE copy the attribute and value to the Unsupported Attributes  
response group and change the attribute value to the "out-of-band"  
'unsupported' value, but otherwise ignore the attribute.

Note: Future Operation attributes may be added to the protocol  
specification that may occur anywhere in the specified group. When  
the operation is otherwise successful, the IPP object returns the  
'successful-ok-ignored-or-substituted-attributes' status code.  
Ignoring unsupported Operation attributes in all operations is  
analogous to the handling of unsupported Job Template attributes in  
the create and Validate-Job operations when the client supplies the

"ipp-attribute-fidelity" Operation attribute with the 'false' value. This last rule is so that we can add OPTIONAL Operation attributes to future versions of IPP so that older clients can inter-work with new IPP objects and newer clients can inter-work with older IPP objects. (If the new attribute cannot be ignored without performing unexpectedly, the major version number would have been increased in the protocol document and in the request). This rule for Operation attributes is independent of the value of the "ipp-attribute-fidelity" attribute. For example, if an IPP object doesn't support the OPTIONAL "job-k-octets" attribute', the IPP object treats "job-k-octets" as an unknown attribute and only checks the length for the 'integer' attribute syntax supplied by the client. If it is not four

Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's Guide February 12, 1999

octets, the IPP object REJECTS the request and RETURNS the 'client-error-bad-request' status code, else the IPP object copies the attribute to the Unsupported Attribute response group, setting the value to the "out-of-band" 'unsupported' value, but otherwise ignores the attribute.

#### 2.2.2 Suggested Additional Processing Steps for Operations that Create/Validate Jobs and Add Documents

This section in combination with the previous section recommends the processing steps for the Print-Job, Validate-Job, Print-URI, Create-Job, Send-Document, and Send-URI operations that IPP objects SHOULD use. These are the operations that create jobs, validate a Print-Job request, and add documents to a job.

##### [2.2.2.1](#) Default "ipp-attribute-fidelity" if not supplied

The Printer object checks to see if the client supplied an "ipp-attribute-fidelity" Operation attribute. If the attribute is not supplied by the client, the IPP object assumes that the value is 'false'.

##### [2.2.2.2](#) Check that the Printer object is accepting jobs

If the value of the Printer object's "printer-is-accepting-jobs" is 'false', the Printer object REJECTS the request and RETURNS the 'server-error-not-accepting-jobs' status code.

##### [2.2.2.3](#) Validate the values of the Job Template attributes

An IPP object validates the values of all Job Template attribute supplied by the client. The IPP object performs the analogous syntactic validation checks of each Job Template attribute value that it performs for Operation attributes (see [Section 2.2.1.5](#)):

- a) that the length of each value is correct for the attribute syntax tag supplied by the client according to [[IPP-MOD](#)] [Section 4.1](#).
- b) that the attribute syntax tag is correct for that attribute

according to [[IPP-MOD](#)] Sections [4.2](#) to [4.4](#).

c)that multiple values are supplied only for multi-valued attributes, i.e., that are 1setOf X according to [[IPP-MOD](#)] Sections [4.2](#) to [4.4](#).

As in [Section 2.2.1.5](#), if any of these syntactic checks fail, the IPP object REJECTS the request and RETURNS the 'client-error-bad-request' or 'client-error-request-value-too-long' status code as appropriate, independent of the value of the "ipp-attribute-fidelity". Since such an error is most likely to be an error detected by a client developer, rather than by an end-user, the IPP object NEED NOT return an indication



Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's Guide February 12, 1999

of which attribute had the error in either the Unsupported Attributes Group or the Status Message. The description for each of these syntactic checks is explicitly expressed in the first IF statement in the following table.

Each Job Template attribute MUST occur no more than once. If an IPP Printer receives a create request with multiple occurrences of a Job Template attribute, it MAY:

1. reject the operation and return the 'client-error-bad syntax' error status code
2. accept the operation and use the first occurrence of the attribute
3. accept the operation and use the last occurrence of the attribute

depending on implementation. Therefore, clients MUST NOT supply multiple occurrences of the same Job Template attribute in the Job Attributes group in the request.

#### 2.2.3 Algorithm for job validation

The process of validating a Job-Template attribute "xxx" against a Printer attribute "xxx-supported" can use the following validation algorithm (see section 3.2.1.2 in [\[ipp-mod\]](#)).

To validate the value U of Job-Template attribute "xxx" against the value V of Printer "xxx-supported", perform the following algorithm:

1. If U is multi-valued, validate each value X of U by performing the algorithm in Table 3 with each value X. Each validation is separate from the standpoint of returning unsupported values.

Example: If U is "finishings" that the client supplies with 'staple', 'bind' values, then X takes on the successive values: 'staple', then 'bind'

2. If V is multi-valued, validate X against each Z of V by performing the algorithm in Table 3 with each value Z. If a value Z validates, the validation for the attribute value X succeeds. If it fails, the algorithm is applied to the next

value Z of V. If there are no more values Z of V, validation fails.

Example" If V is "sides-supported" with values: 'one-sided', 'two-sided-long', and 'two-sided-short', then Z takes on the successive values: 'one-sided', 'two-sided-long', and 'two-sided-short'. If the client supplies "sides" with 'two-sided-long', the first comparison fails ('one-sided' is not equal to 'two-sided-long'), the second comparison succeeds ('two-sided-

Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's Guide February 12, 1999

long' is equal to 'two-sided-long'), and the third comparison ('two-sided-short' with 'two-sided-long') is not even performed.

3.If both U and V are single-valued, let X be U and Z be V and use the validation rules in Table 3.

Table 3 - Rules for validating single values X against Z

attribute syntax of X	attribute syntax of Z	validated if:
integer	rangeOfInteger	X is within the range of Z
uri	uriScheme	the uri scheme in X is equal to Z
any	boolean	the value of Z is TRUE
any	any	X and Z are of the same type and are equal.

If the value of the Printer object's "xxx-supported" attribute is 'no-value' (because the system administrator hasn't configured a value), the check always fails. If the check fails, the IPP object copies the attribute to the Unsupported Attributes response group with its unsupported value. If the attribute contains more than one value, each value is checked and each unsupported value is separately copied, while supported values are not copied. If an IPP object doesn't recognize/support a Job Template attribute, i.e., there is no corresponding Printer object "xxx-supported" attribute, the IPP object treats the attribute as an unknown or unsupported attribute (see the last row in the table below).

If some Job Template attributes are supported for some document formats and not for others or the values are different for different document formats, the IPP object SHOULD take that into account in this validation using the value of the "document-format" supplied by the client (or defaulted to the value of the Printer's "document-format-default" attribute, if not supplied by the client). For example, if "number-up" is supported for the 'text/plain' document format, but not for the 'application/postscript' document format, the check SHOULD (though it NEED NOT) depend on the value of the "document-format" operation attribute. See "document-format" in [[IPP-MOD](#)] [section 3.2.1.1](#) and

#### 3.2.5.1.

Note: whether the request is accepted or rejected is determined by the value of the "ipp-attribute-fidelity" attribute in a subsequent step, so that all Job Template attribute supplied are examined and all unsupported attributes and/or values are copied to the Unsupported Attributes response group.

-----  
job-priority (integer(1:100))

Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's Guide February 12, 1999

IF NOT a single 'integer' value with a length equal to 4 octets,  
REJECT/RETURN 'client-error-bad-request'.  
IF NOT supplied by the client, use the value of the Printer object's  
"job-priority-default" attribute at job submission time.  
IF NOT in the range 1 to 100, inclusive, copy the attribute and the  
unsupported value to the Unsupported Attributes response group.  
Map the value to the nearest supported value in the range 1:100 as  
specified by the number of discrete values indicated by the value  
of the Printer's "job-priority-supported" attribute. See the  
formula in [[IPP-MOD](#)] [Section 4.2.1](#).

job-hold-until (type3 keyword | name)

IF NOT a single 'keyword' or 'name' value, REJECT/RETURN 'client-  
error-request-bad-request'.  
IF the value length is greater than 255 octets, REJECT/RETURN  
'client-error-request-value-too-long'.  
IF NOT supplied by the client, use the value of the Printer object's  
"job-hold-until" attribute at job submission time.  
IF NOT in the Printer object's "job-hold-until-supported" attribute,  
copy the attribute and the unsupported value to the Unsupported  
Attributes response group.

job-sheets (type3 keyword | name)

IF NOT a single 'keyword' or 'name' value, REJECT/RETURN 'client-  
error-request-bad-request'.  
IF the value length is greater than 255 octets, REJECT/RETURN  
'client-error-request-value-too-long'.  
IF NOT in the Printer object's "job-sheets-supported" attribute, copy  
the attribute and the unsupported value to the Unsupported  
Attributes response group.

multiple-document-handling (type2 keyword)

IF NOT a single 'keyword' value, REJECT/RETURN 'client-error-request-  
bad-request'.  
IF the value length is greater than 255 octets, REJECT/RETURN  
'client-error-request-value-too-long'.  
IF NOT in the Printer object's "multiple-document-handling-supported"  
attribute, copy the attribute and the unsupported value to the  
Unsupported Attributes response group.

`copies (integer(1:MAX))`

IF NOT a single 'integer' value with a length equal to 4 octets,  
REJECT/RETURN 'client-error-bad-request'.

IF NOT in range of the Printer object's "copies-supported" attribute  
copy the attribute and the unsupported value to the Unsupported  
Attributes response group.

`finishings (1setOf type2 enum)`

Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's Guide February 12, 1999

IF NOT an 'enum' value(s) each with a length equal to 4 octets,  
REJECT/RETURN 'client-error-bad-request'.  
IF NOT in the Printer object's "finishings-supported" attribute, copy  
the attribute and the unsupported value(s), but not any supported  
values, to the Unsupported Attributes response group.

page-ranges (1setOf rangeOfInteger(1:MAX))

IF NOT a 'rangeOfInteger' value(s) each with a length equal to 8  
octets, REJECT/RETURN 'client-error-bad-request'.  
IF first value is greater than second value in any range, the ranges  
are not in ascending order, or ranges overlap, REJECT/RETURN  
'client-error-bad-request'.  
IF the value of the Printer object's "page-ranges-supported"  
attribute is 'false', copy the attribute to the Unsupported  
Attributes response group and set the value to the "out-of-band"  
'unsupported' value.

sides (type2 keyword)

IF NOT a single 'keyword' value, REJECT/RETURN 'client-error-request-  
bad-request'.  
IF the value length is greater than 255 octets, REJECT/RETURN  
'client-error-request-value-too-long'.  
IF NOT in the Printer object's "sides-supported" attribute, copy the  
attribute and the unsupported value to the Unsupported Attributes  
response group.

number-up (integer(1:MAX))

IF NOT a single 'integer' value with a length equal to 4 octets,  
REJECT/RETURN 'client-error-bad-request'.  
IF NOT a value or in the range of one of the values of the Printer  
object's "number-up-supported" attribute, copy the attribute and  
value to the Unsupported Attribute response group.

orientation-requested (type2 enum)

IF NOT a single 'enum' value with a length equal to 4 octets,  
REJECT/RETURN 'client-error-bad-request'.  
IF NOT in the Printer object's "orientation-requested-supported"

attribute, copy the attribute and the unsupported value to the Unsupported Attributes response group.

media (type3 keyword | name)

IF NOT a single 'keyword' or 'name' value, REJECT/RETURN 'client-error-request-bad-request'.

IF the value length is greater than 255 octets, REJECT/RETURN 'client-error-request-value-too-long'.

IF NOT in the Printer object's "media-supported" attribute, copy the attribute and the unsupported value to the Unsupported Attributes response group.



Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's Guide February 12, 1999

printer-resolution (resolution)

IF NOT a single 'resolution' value with a length equal to 9 octets,  
REJECT/RETURN 'client-error-bad-request'.

IF NOT in the Printer object's "printer-resolution-supported"  
attribute, copy the attribute and the unsupported value to the  
Unsupported Attributes response group.

print-quality (type2 enum)

IF NOT a single 'enum' value with a length equal to 4 octets,  
REJECT/RETURN 'client-error-bad-request'.

IF NOT in the Printer object's "print-quality-supported" attribute,  
copy the attribute and the unsupported value to the Unsupported  
Attributes response group.

unknown or unsupported attribute (i.e., there is no corresponding  
Printer object "xxx-supported" attribute)

IF the attribute syntax supplied by the client is supported but the  
length is not legal for that attribute syntax,  
REJECT/RETURN 'client-error-bad-request' if the length of the  
attribute syntax is fixed or 'client-error-request-value-too-long'  
if the length of the attribute syntax is variable.  
ELSE copy the attribute and value to the Unsupported Attributes  
response group and change the attribute value to the "out-of-band"  
'unsupported' value. Any remaining Job Template Attributes are  
either unknown or unsupported Job Template attributes and are  
validated algorithmically according to their attribute syntax for  
proper length (see below).

-----

If the attribute syntax is supported AND the length check fails, the IPP  
object REJECTS the request and RETURNS the 'client-error-bad-request' if  
the length of the attribute syntax is fixed or the 'client-error-  
request-value-too-long' status code if the length of the attribute  
syntax is variable. Otherwise, the IPP object copies the unsupported Job  
Template attribute to the Unsupported Attributes response group and  
changes the attribute value to the "out-of-band" 'unsupported' value.  
The following table shows the length checks for all attribute syntaxes.

In the following table: " $\leq$ " means less than or equal, "=" means equal to:

Hastings, Manros

[page 29]

Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's Guide February 12, 1999

Name	Octet length check for read-write attributes
-----	-----
'textWithLanguage'	<= 1023 AND 'naturalLanguage' <= 63
'textWithoutLanguage'	<= 1023
'nameWithLanguage'	<= 255 AND 'naturalLanguage' <= 63
'nameWithoutLanguage'	<= 255
'keyword'	<= 255
'enum'	= 4
'uri'	<= 1023
'uriScheme'	<= 63
'charset'	<= 63
'naturalLanguage'	<= 63
'mimeType'	<= 255
'octetString'	<= 1023
'boolean'	= 1
'integer'	= 4
'rangeOfInteger'	= 8
'dateTime'	= 11
'resolution'	= 9
'1setOf X'	

#### **2.2.3.1 Check for conflicting Job Template attributes values**

Once all the Operation and Job Template attributes have been checked individually, the Printer object SHOULD check for any conflicting values among all the supported values supplied by the client. For example, a Printer object might be able to staple and to print on transparencies, however due to physical stapling constraints, the Printer object might not be able to staple transparencies. The IPP object copies the supported attributes and their conflicting attribute values to the Unsupported Attributes response group. The Printer object only copies over those attributes that the Printer object either ignores or substitutes in order to resolve the conflict, and it returns the original values which were supplied by the client. For example suppose the client supplies "finishings" equals 'staple' and "media" equals 'transparency', but the Printer object does not support stapling transparencies. If the Printer chooses to ignore the stapling request in order to resolve the conflict, the Printer objects returns "finishings" equal to 'staple' in the Unsupported Attributes response group. If any attributes are multi-valued, only the conflicting values of the attributes are copied.

Note: The decisions made to resolve the conflict (if there is a choice)

is implementation dependent.

#### **2.2.3.2    Decide whether to REJECT the request**

If there were any unsupported Job Template attributes or unsupported/conflicting Job Template attribute values and the client supplied the "ipp-attribute-fidelity" attribute with the 'true' value, the Printer object REJECTS the request and return the status code:

Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's Guide February 12, 1999

- (1) 'client-error-conflicting-attributes' status code, if there were any conflicts between attributes supplied by the client.
- (2) 'client-error-attributes-or-values-not-supported' status code, otherwise.

Note: Unsupported Operation attributes or values that are returned do not affect the status returned in this step. If the unsupported Operation attribute was a serious error, the above already rejected the request in a previous step. If control gets to this step with unsupported Operation attributes being returned, they are not serious errors.

#### **2.2.3.3 For the Validate-Job operation, RETURN one of the success status codes**

If the requested operation is the Validate-Job operation, the Printer object returns:

- (1) the "successful-ok" status code, if there are no unsupported or conflicting Job Template attributes or values.
- (2) the "successful-ok-conflicting-attributes", if there are any conflicting Job Template attribute or values.
- (3) the "successful-ok-ignored-or-substituted-attributes", if there are only unsupported Job Template attributes or values.

Note: Unsupported Operation attributes or values that are returned do not affect the status returned in this step. If the unsupported Operation attribute was a serious error, the above already rejected the request in a previous step. If control gets to this step with unsupported Operation attributes being returned, they are not serious errors.

#### **2.2.3.4 Create the Job object with attributes to support**

If "ipp-attribute-fidelity" is set to 'false' (or it was not supplied by the client), the Printer object:

- (1) creates a Job object, assigns a unique value to the job's "job-uri" and "job-id" attributes, and initializes all of the job's other supported Job Description attributes.
- (2) removes all unsupported attributes from the Job object.
- (3) for each unsupported value, removes either the unsupported value

or substitutes the unsupported attribute value with some supported value. If an attribute has no values after removing unsupported values from it, the attribute is removed from the Job object (so that the normal default behavior at job processing time will take place for that attribute).

- (4) for each conflicting value, removes either the conflicting value or substitutes the conflicting attribute value with some other supported value. If an attribute has no values after removing conflicting values from it, the attribute is removed from the Job

Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's Guide February 12, 1999

object (so that the normal default behavior at job processing time will take place for that attribute).

If there were no attributes or values flagged as unsupported, or the value of 'ipp-attribute-fidelity' was 'false', the Printer object is able to accept the create request and create a new Job object. If the "ipp-attribute-fidelity" attribute is set to 'true', the Job Template attributes that populate the new Job object are necessarily all the Job Template attributes supplied in the create request. If the "ipp-attribute-fidelity" attribute is set to 'false', the Job Template attributes that populate the new Job object are all the client supplied Job Template attributes that are supported or that have value substitution. Thus, some of the requested Job Template attributes may not appear in the Job object because the Printer object did not support those attributes. The attributes that populate the Job object are persistently stored with the Job object for that Job. A Get-Job-Attributes operation on that Job object will return only those attributes that are persistently stored with the Job object.

Note: All Job Template attributes that are persistently stored with the Job object are intended to be "override values"; that is, they take precedence over whatever other embedded instructions might be in the document data itself. However, it is not possible for all Printer objects to realize the semantics of "override". End users may query the Printer's "pdl-override-supported" attribute to determine if the Printer either attempts or does not attempt to override document data instructions with IPP attributes.

There are some cases, where a Printer supports a Job Template attribute and has an associated default value set for that attribute. In the case where a client does not supply the corresponding attribute, the Printer does not use its default values to populate Job attributes when creating the new Job object; only Job Template attributes actually in the create request are used to populate the Job object. The Printer's default values are only used later at Job processing time if no other IPP attribute or instruction embedded in the document data is present.

Note: If the default values associated with Job Template attributes that the client did not supply were to be used to populate the Job object, then these values would become "override values" rather than defaults. If the Printer supports the 'attempted' value of the "pdl-override-supported" attribute, then these override values could replace values specified within the document data. This is not the intent of the default value mechanism. A default value for an attribute is used only

if the create request did not specify that attribute (or it was ignored when allowed by "ipp-attribute-fidelity" being 'false') and no value was provided within the content of the document data.

If the client does not supply a value for some Job Template attribute, and the Printer does not support that attribute, as far as IPP is concerned, the result of processing that Job (with respect to the missing attribute) is undefined.



Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's Guide February 12, 1999

#### **2.2.3.5 Return one of the success status codes**

Once the Job object has been created, the Printer object accepts the request and returns to the client:

- (1) the 'successful-ok' status code, if there are no unsupported or conflicting Job Template attributes or values.
- (2) the 'successful-ok-conflicting-attributes' status code, if there are any conflicting Job Template attribute or values.
- (3) the 'successful-ok-ignored-or-substituted-attributes' status code, if there are only unsupported Job Template attributes or values.

Note: Unsupported Operation attributes or values that are returned do not affect the status returned in this step. If the unsupported Operation attribute was a serious error, the above already rejected the request in a previous step. If control gets to this step with unsupported Operation attributes being returned, they are not serious errors.

The Printer object also returns Job status attributes that indicate the initial state of the Job ('pending', 'pending-held', 'processing', etc.), etc. See Print-Job Response, [[IPP-MOD](#)] [section 3.2.1.2](#).

#### **2.2.3.6 Accept appended Document Content**

The Printer object accepts the appended Document Content data and either starts it printing, or spools it for later processing.

#### **2.2.3.7 Scheduling and Starting to Process the Job**

The Printer object uses its own configuration and implementation specific algorithms for scheduling the Job in the correct processing order. Once the Printer object begins processing the Job, the Printer changes the Job's state to 'processing'. If the Printer object supports PDL override (the "pdl-override-supported" attribute set to 'attempted'), the implementation does its best to see that IPP attributes take precedence over embedded instructions in the document data.

#### **2.2.3.8 Completing the Job**

The Printer object continues to process the Job until it can move the Job into the 'completed' state. If an Cancel-Job operation is received, the implementation eventually moves the Job into the 'canceled' state. If the system encounters errors during processing that do not allow it to progress the Job into a completed state, the implementation halts all processing, cleans up any resources, and moves the Job into the 'aborted' state.

Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's Guide February 12, 1999

#### **2.2.3.9 Destroying the Job after completion**

Once the Job moves to the 'completed', 'aborted', or 'canceled' state, it is an implementation decision as to when to destroy the Job object and release all associated resources. Once the Job has been destroyed, the Printer would return either the "client-error-not-found" or "client-error-gone" status codes for operations directed at that Job.

Note: the Printer object SHOULD NOT re-use a "job-uri" or "job-id" value for a sufficiently long time after a job has been destroyed, so that stale references kept by clients are less likely to access the wrong (newer) job.

#### **2.2.3.10 Interaction with "ipp-attribute-fidelity"**

Some Printer object implementations may support "ipp-attribute-fidelity" set to 'true' and "pdl-override-supported" set to 'attempted' and yet still not be able to realize exactly what the client specifies in the create request. This is due to legacy decisions and assumptions that have been made about the role of job instructions embedded within the document data and external job instructions that accompany the document data and how to handle conflicts between such instructions. The inability to be 100% precise about how a given implementation will behave is also compounded by the fact that the two special attributes, "ipp-attribute-fidelity" and "pdl-override-supported", apply to the whole job rather than specific values for each attribute. For example, some implementations may be able to override almost all Job Template attributes except for "number-up".

### **2.3 Status codes returned by operation (Issue 1.50)**

This section lists all status codes once in the first operation (Print-Job). Then it lists the status codes that are different or specialized for subsequent operations under each operation.

#### **2.3.1 Printer Operations**

##### **2.3.1.1 Print-Job**

The Printer object MUST return one of the following "status-code" values

for the indicated reason. Whether all of the document data has been accepted or not before returning the success or error response depends on implementation. See [Section 14](#) for a more complete description of each status code.

For the following success status codes, the Job object has been created and the "job-id", and "job-uri" assigned and returned in the response:

- successful-ok: no request attributes were substituted or ignored.
- successful-ok-ignored-or-substituted-attributes: some supplied (1) attributes were ignored or (2) unsupported attribute syntaxes or values were substituted with supported values or were ignored.

Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's Guide February 12, 1999

Unsupported attributes, attribute syntaxes, or values MUST be returned in the Unsupported Attributes group of the response.

successful-ok-conflicting-attributes: some supplied attribute values conflicted with the values of other supplied attributes and were either substituted or ignored. Attributes or values which conflict with other attributes and have been substituted or ignored MUST be returned in the Unsupported Attributes group of the response as supplied by the client.

[ipp-mod] [section 3.1.6](#) Operation Status Codes and Messages states (Issue 1.19):

If the Printer object supports the "status-message" operation attribute, it SHOULD use the REQUIRED 'utf-8' charset to return a status message for the following error status codes (see [section 14](#)): 'client-error-bad-request', 'client-error-charset-not-supported', 'server-error-internal-error', 'server-error-operation-not-supported', and 'server-error-version-not-supported'. In this case, it MUST set the value of the "attributes-charset" operation attribute to 'utf-8' in the error response.

For the following error status codes, no job is created and no "job-id" or "job-uri" is returned:

client-error-bad-request: The request syntax does not conform to the specification.

client-error-forbidden: The request is being refused for authorization or authentication reasons. The implementation security policy is to not reveal whether the failure is one of authentication or authorization.

client-error-not-authenticated: Either the request requires authentication information to be supplied or the authentication information is not sufficient for authorization.

client-error-not-authorized: The requester is not authorized to perform the request on the target object.

client-error-not-possible: The request cannot be carried out because of the state of the system. See also 'server-error-not-accepting-jobs' status code which MUST take precedence if the Printer object's "printer-accepting-jobs" attribute is 'false'.

client-error-timeout: not applicable.

client-error-not-found: the target object does not exist.

client-error-gone: the target object no longer exists and no forwarding address is known.

client-error-request-entity-too-large: the size of the request

and/or print data exceeds the capacity of the IPP Printer to process it.

client-error-request-value-too-long: the size of request variable length attribute values, such as 'text' and 'name' attribute syntaxes, exceed the maximum length specified in [[IPP-MOD](#)] for the attribute and MUST be returned in the Unsupported Attributes Group.

client-error-document-format-not-supported: the document format supplied is not supported. The "document-format" attribute with the unsupported value MUST be returned in the Unsupported Attributes Group. This error SHOULD take precedence over any other

Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's Guide February 12, 1999

'xxx-not-supported' error, except 'client-error-charset-not-supported'.

client-error-attributes-or-values-not-supported: one or more supplied attributes, attribute syntaxes, or values are not supported and the client supplied the "ipp-attributes-fidelity" operation attribute with a 'true' value. They MUST be returned in the Unsupported Attributes Group as explained below.

client-error-uri-scheme-not-supported: not applicable.

client-error-charset-not-supported: the charset supplied in the "attributes-charset" operation attribute is not supported. The Printer's "configured-charset" MUST be returned in the response as the value of the "attributes-charset" operation attribute and used for any 'text' and 'name' attributes returned in the error response. This error SHOULD take precedence over any other error, unless the request syntax is so bad that the client's supplied "attributes-charset" cannot be determined.

client-error-conflicting-attributes: one or more supplied attribute values conflicted with each other and the client supplied the "ipp-attributes-fidelity" operation attribute with a 'true' value. They MUST be returned in the Unsupported Attributes Group as explained below.

server-error-internal-error: an unexpected condition prevents the request from being fulfilled.

server-error-operation-not-supported: not applicable (since Print-Job is REQUIRED).

server-error-service-unavailable: the service is temporarily overloaded.

server-error-version-not-supported: the version in the request is not supported. The "closest" version number supported MUST be returned in the response.

server-error-device-error: a device error occurred while receiving or spooling the request or document data or the IPP Printer object can only accept one job at a time.

server-error-temporary-error: a temporary error such as a buffer full write error, a memory overflow, or a disk full condition occurred while receiving the request and/or the document data.

server-error-not-accepting-jobs: the Printer object's "printer-is-not-accepting-jobs" attribute is 'false'.

server-error-busy: the Printer is too busy processing jobs to accept another job at this time.

server-error-job-canceled: the job has been canceled by an operator or the system while the client was transmitting the document data.

### [2.3.1.2](#) Print-URI

All of the Print-Job status codes described in [Section 3.2.1.2](#) Print-Job Response are applicable to Print-URI with the following specializations and differences. See [Section 14](#) for a more complete description of each status code.

server-error-uri-scheme-not-supported: the URI scheme supplied in the "document-uri" operation attribute is not supported and is returned in the Unsupported Attributes group.



Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's Guide February 12, 1999

#### [2.3.1.3](#) **Validate-Job**

All of the Print-Job status codes described in [Section 3.2.1.2](#) Print-Job Response are applicable to Validate-Job. See [Section 14](#) for a more complete description of each status code.

#### [2.3.1.4](#) **Create-Job**

All of the Print-Job status codes described in [Section 3.2.1.2](#) Print-Job Response are applicable to Create-Job with the following specializations and differences. See [Section 14](#) for a more complete description of each status code.

server-error-operation-not-supported: the Create-Job operation is not supported.

#### [2.3.1.5](#) **Get-Printer-Attributes**

All of the Print-Job status codes described in [Section 3.2.1.2](#) Print-Job Response are applicable to the Get-Printer-Attributes operation with the following specializations and differences. See [Section 14](#) for a more complete description of each status code.

For the following success status codes, the requested attributes are returned in Group 3 in the response:

successful-ok: no request attributes were substituted or ignored (same as Print-Job) and no requested attributes were unsupported.  
successful-ok-ignored-or-substituted-attributes: same as Print-Job, except the "requested-attributes" operation attribute MAY, but NEED NOT, be returned with the unsupported values.  
successful-ok-conflicting-attributes: same as Print-Job.

For the error status codes, Group 3 is returned containing no attributes or is not returned at all:

client-error-not-possible: Same as Print-Job, in addition the Printer object is not accepting any requests.  
client-error-request-entity-too-large: same as Print-job, except that no print data is involved.  
client-error-attributes-or-values-not-supported: not applicable, since unsupported operation attributes MUST be ignored and 'successful-ok-ignored-or-substituted-attributes' returned.  
client-error-conflicting-attributes: same as Print-Job, except that

"ipp-attribute-fidelity" is not involved.  
server-error-operation-not-supported: not applicable (since Get-Printer-Attributes is REQUIRED).  
server-error-device-error: same as Print-Job, except that no document data is involved.  
server-error-temporary-error: same as Print-Job, except that no document data is involved.  
server-error-not-accepting-jobs: not applicable..  
server-error-busy: same as Print-Job, except the IPP object is too busy to accept even query requests.  
server-error-job-canceled: not applicable..

Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's Guide February 12, 1999

#### **2.3.1.6 Get-Jobs**

All of the Print-Job status codes described in [Section 3.2.1.2](#) Print-Job Response are applicable to the Get-Jobs operation with the following specializations and differences. See [Section 14](#) for a more complete description of each status code.

For the following success status codes, the requested attributes are returned in Group 3 in the response:

- successful-ok: no request attributes were substituted or ignored (same as Print-Job) and no requested attributes were unsupported.
- successful-ok-ignored-or-substituted-attributes: same as Print-Job, except the "requested-attributes" operation attribute MAY, but NEED NOT, be returned with the unsupported values.
- successful-ok-conflicting-attributes: same as Print-Job.

For any error status codes, Group 3 is returned containing no attributes or is not returned at all. The following brief error status code descriptions contain unique information for use with Get-Jobs operation. See [section 14](#) for the other error status codes that apply uniformly to all operations:

- client-error-not-possible: Same as Print-Job, in addition the Printer object is not accepting any requests.
- client-error-request-entity-too-large: same as Print-job, except that no print data is involved.
- client-error-document-format-not-supported: not applicable.
- client-error-attributes-or-values-not-supported: not applicable, since unsupported operation attributes MUST be ignored and 'successful-ok-ignored-or-substituted-attributes' returned.
- client-error-conflicting-attributes: same as Print-Job, except that "ipp-attribute-fidelity" is not involved.
- server-error-operation-not-supported: not applicable (since Get-Jobs is REQUIRED).
- server-error-device-error: same as Print-Job, except that no document data is involved.
- server-error-temporary-error: same as Print-Job, except that no document data is involved.
- server-error-not-accepting-jobs: not applicable.
- server-error-job-canceled: not applicable.

#### **2.3.2 Job Operations**

#### **2.3.2.1 Send-Document**

All of the Print-Job status codes described in [Section 3.2.1.2](#) Print-Job Response are applicable to the Get-Printer-Attributes operation with the following specializations and differences. See [Section 14](#) for a more complete description of each status code.

For the following success status codes, the document has been added to the specified Job object and the job's "number-of-documents" attribute has been incremented:

Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's Guide February 12, 1999

successful-ok: no request attributes were substituted or ignored  
(same as Print-Job).

successful-ok-ignored-or-substituted-attributes: same as Print-Job.

successful-ok-conflicting-attributes: same as Print-Job.

For the error status codes, no document has been added to the Job object and the job's "number-of-documents" attribute has not been incremented:

client-error-not-possible: Same as Print-Job, except that the Printer's "printer-is-accepting-jobs" attribute is not involved, so that the client is able to finish submitting a multi-document job after this attribute has been set to 'true'. Another condition is that the state of the job precludes Send-Document, i.e., the job has already been closed out by the client. However, if the IPP Printer closed out the job due to timeout, the 'client-error-timeout' error status SHOULD be returned instead.

client-error-timeout: This request was sent after the Printer closed the job, because it has not received a Send-Document or Send-URI operation within the Printer's "multiple-operation-time-out" period.

client-error-request-entity-too-large: same as Print-Job.

client-error-conflicting-attributes: same as Print-Job, except that "ipp-attributes-fidelity" operation attribute is not involved..

server-error-operation-not-supported: the Send-Document request is not supported.

server-error-not-accepting-jobs: not applicable.

server-error-job-canceled: the job has been canceled by an operator or the system while the client was transmitting the data.

#### **2.3.2.2 Send-URI**

All of the Print-Job status code descriptions in [Section 3.2.1.2](#) Print-Job Response with the specializations described for Send-Document are applicable to Send-URI. See [Section 14](#) for a more complete description of each status code.

server-error-uri-scheme-not-supported: the URI scheme supplied in the "document-uri" operation attribute is not supported and the "document-uri" attribute MUST be returned in the Unsupported Attributes group.

#### **2.3.2.3 Cancel-Job**

All of the Print-Job status codes described in [Section 3.2.1.2](#) Print-Job Response are applicable to Cancel-Job with the following specializations

and differences. See [Section 14](#) for a more complete description of each status code.

For the following success status codes, the Job object is being canceled or has been canceled:

successful-ok: no request attributes were substituted or ignored  
(same as Print-Job).

successful-ok-ignored-or-substituted-attributes: same as Print-Job.

successful-ok-conflicting-attributes: same as Print-Job.

Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's Guide February 12, 1999

For any of the error status codes, the Job object has not been canceled or was previously canceled.

client-error-not-possible: The request cannot be carried out because of the state of the Job object ('completed', 'canceled', or 'aborted') or the state of the system.

client-error-not-found: the target Printer and/or Job object does not exist.

client-error-gone: the target Printer and/or Job object no longer exists and no forwarding address is known.

client-error-request-entity-too-large: same as Print-Job, except no document data is involved.

client-error-document-format-not-supported: not applicable.

client-error-attributes-or-values-not-supported: not applicable, since unsupported operation attributes and values MUST be ignored.

client-error-conflicting-attributes: same as Print-Job, except that the Printer's "printer-is-accepting-jobs" attribute is not involved.

server-error-operation-not-supported: not applicable (Cancel-Job is REQUIRED).

server-error-device-error: same as Print-Job, except no document data is involved.

server-error-temporary-error: same as Print-Job, except no document data is involved.

server-error-not-accepting-jobs: not applicable..

server-error-job-canceled: not applicable.

#### **2.3.2.4 Get-Job-Attributes**

All of the Print-Job status codes described in [Section 3.2.1.2](#) Print-Job Response are applicable to Get-Job-Attributes with the following specializations and differences. See [Section 14](#) for a more complete description of each status code.

For the following success status codes, the requested attributes are returned in Group 3 in the response:

successful-ok: no request attributes were substituted or ignored (same as Print-Job) and no requested attributes were unsupported.

successful-ok-ignored-or-substituted-attributes: same as Print-Job, except the "requested-attributes" operation attribute MAY, but NEED NOT, be returned with the unsupported values.

successful-ok-conflicting-attributes: same as Print-Job.

For the error status codes, Group 3 is returned containing no attributes

or is not returned at all.

client-error-not-possible: Same as Print-Job, in addition the  
Printer object is not accepting any requests.  
client-error-document-format-not-supported: not applicable.  
client-error-attributes-or-values-not-supported: not applicable.  
client-error-uri-scheme-not-supported: not applicable.  
client-error-conflicting-attributes: not applicable  
server-error-operation-not-supported: not applicable (since Get-Job-  
Attributes is REQUIRED).



Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's Guide February 12, 1999

server-error-device-error: same as Print-Job, except no document data is involved.  
server-error-temporary-error: sane as Print-Job, except no document data is involved..  
server-error-not-accepting-jobs: not applicable.  
server-error-job-canceled: not applicable.

## **2.4 Validate-Job**

The Validate-Job operation has been designed so that its implementation may be a part of the Print-Job operation. Therefore, requiring Validate-Job is not a burden on implementers. Also it is useful for client's to be able to count on its presence in all conformance implementations, so that the client can determine before sending a long document, whether the job will be accepted by the IPP Printer or not.

## **2.5 Case Sensitivity in URIs (issue 1.6)**

IPP client and server implementations must be aware of the diverse uppercase/lowercase nature of URIs. [RFC 2396](#) defines URL schemes and Host names as case insensitive but reminds us that the rest of the URL may well demonstrate case sensitivity. When creating URL's for fields where the choice is completely arbitrary, it is probably best to select lower case. However, this cannot be guaranteed and implementations MUST NOT rely on any fields being case-sensitive or case-insensitive in the URL beyond the URL scheme and host name fields.

The reason that the IPP specification does not make any restrictions on URIs, is so that implementations of IPP may use off-the-shelf components that conform to the standards that define URIs, such as [RFC 2396](#) and the HTTP/1.1 specifications [[RFC2068](#)]. See these specifications for rules of matching, comparison, and case-sensitivity.

It is also recommended that System Administrators and implementations avoid creating URLs for different printers that differ only in their case. For example, don't have Printer1 and printer1 as two different IPP Printers.

The HTTP/1.1 specification [[RFC2068](#)] contains more details on comparing URLs.

## **2.6 Character Sets, natural languages, and internationalization**

This section discusses character set support, natural language support and internationalization.

### **2.6.1**Character set code conversion support (Issue 1.5)

IPP clients and IPP objects are REQUIRED to support UTF-8. They MAY support additional charsets. It is RECOMMENDED that an IPP object also support US-ASCII, since many clients support US-ASCII, and indicate that

Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's Guide February 12, 1999

UTF-8 and US-ASCII are supported by populating the Printer's "charset-supported" with 'utf-8' and 'us-ascii' values. An IPP object is required to code covert with as little loss as possible between the charsets that it supports, as indicated in the Printer's "charsets-supported" attribute.

How should the server handle the situation where the "attributes-charset" of the response itself is "us-ascii", but one or more attributes in that response is in the "utf-8" format?

Example: Consider a case where a client sends a Print-Job request with "utf-8" as the value of "attributes-charset" and with the "job-name" attribute supplied. Later another client submits a Get-Job-Attribute or Get-Jobs request. This second request contains the "attributes-charset" with value "us-ascii" and "requested-attributes" attribute with exactly one value "job-name".

According to the IPP-Mod document ([section 3.1.4.2](#)), the value of the "attributes-charset" for the response of the second request must be "us-ascii" since that is the charset specified in the request. The "job-name" value, however, is in "utf-8" format. Should the request be rejected even though both "utf-8" and "us-ascii" charsets are supported by the server? or should the "job-name" value be converted to "us-ascii" and return "successful-ok-conflicting-attributes" (0x0002) as the status code?

Answer: An IPP object that supports both utf-8 (REQUIRED) and us-ascii, the second paragraph of [section 3.1.4.2](#) applies so that the IPP object MUST accept the request, perform code set conversion between these two charsets with "the highest fidelity possible" and return 'successful-ok', rather than a warning 'successful-ok-conflicting-attributes, or an error. The printer will do the best it can to convert between each of the character sets that it supports--even if that means providing a string of question marks because none of the characters are representable in US ASCII. If it can't perform such conversion, it MUST NOT advertise us-ascii as a value of its "attributes-charset-supported" and MUST reject any request that requests 'us-ascii'.

One IPP object implementation strategy is to convert all request text and name values to a Unicode internal representation. This is 16-bit and virtually universal. Then convert to the specified operation attributes-charset on output.

Also it would be smarter for a client to ask for 'utf-8', rather than

'us-ascii' and throw away characters that it doesn't understand, rather than depending on the code conversion of the IPP object.

2.6.2 What charset to return when an unsupported charset is requested (Issue 1.19)?

[Section 3.1.4.1](#) Request Operation attributes was clarified in November **1998** as follows:

Hastings, Manros

[page 42]

Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's Guide February 12, 1999

All clients and IPP objects MUST support the 'utf-8' charset [[RFC2044](#)] and MAY support additional charsets provided that they are registered with IANA [IANA-CS]. If the Printer object does not support the client supplied charset value, the Printer object MUST reject the request, set the "attributes-charset" to 'utf-8' in the response, and return the 'client-error-charset-not-supported' status code and any 'text' or 'name' attributes using the 'utf-8' charset.

Since the client and IPP object MUST support UTF-8, returning any text or name attributes in UTF-8 when the client requests a charset that is not supported should allow the client to display the text or name.

Since such an error is a client error, rather than a user error, the client should check the status code first so that it can avoid displaying any other returned 'text' and 'name' attributes that are not in the charset requested.

Furthermore, [[ipp-mod](#)] [section 14.1.4.14](#) client-error-charset-not-supported (0x040D) was clarified in November 1998 as follows:

For any operation, if the IPP Printer does not support the charset supplied by the client in the "attributes-charset" operation attribute, the Printer MUST reject the operation and return this status and any 'text' or 'name' attributes using the 'utf-8' charset (see [Section 3.1.4.1](#)).

### 2.6.3 Natural Language Override (NLO) (Issue 1.45)

The 'text' and 'name' attributes each have two forms. One has an implicit natural language, and the other has an explicit natural language. The 'textWithoutLanguage' and 'textWithLanguage' are the two 'text' forms. The 'nameWithoutLanguage' and 'nameWithLanguage' are the two 'name' forms. If a receiver (IPP object or IPP client) supports an attribute with attribute syntax 'text', it MUST support both forms in a request and a response. A sender (IPP client or IPP object) MAY send either form for any such attribute. When a sender sends a WithoutLanguage form, the implicit natural language is specified in the "attributes-natural-language" operation attribute which all senders MUST include in every request and response.

When a sender sends a WithLanguage form, it MAY be different from the implicit natural language supplied by the sender or it MAY be the same. The receiver MUST treat either form equivalently.

There is an implementation decision for senders, whether to always send the WithLanguage forms or use the WithoutLanguage form when the attribute's natural language is the same as the request or response. The former approach makes the sender implementation simpler. The latter approach is more efficient on the wire and allows inter-working with non-conforming receivers that fail to support the WithLanguage forms. As each approach have advantages, the choice is completely up to the implementer of the sender.

Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's Guide February 12, 1999

Furthermore, when a client receives a 'text' or 'name' job attribute that it had previously supplied, that client MUST NOT expect to see the attribute in the same form, i.e., in the same WithoutLanguage or WithLanguage form as the client supplied when it created the job. The IPP object is free to transform the attribute from the WithLanguage form to the WithoutLanguage form and vice versa, as long as the natural language is preserved. However, in order to meet this latter requirement, it is usually simpler for the IPP object implementation to store the natural language explicitly with the attribute value, i.e., to store using an internal representation that resembles the WithLanguage form.

The IPP Printer MUST copy the natural language of a job, i.e., the value of the "attributes-natural-language" operation attribute supplied by the client in the create operation, to the Job object as a Job Description attribute, so that a client is able to query it. In returning a Get-Job-Attributes response, the IPP object MAY return one of three natural language values in the response's "attributes-natural-language" operation attribute: (1) that requested by the requester, (2) the natural language of the job, or (3) the configured natural language of the IPP Printer, if the requested language is not supported by the IPP Printer.

This "attributes-natural-language" Job Description attribute is useful for an IPP object implementation that prints start sheets in the language of the user who submitted the job. This same Job Description attribute is useful to a multi-lingual operator who has to communicate with different job submitters in different natural languages. This same Job Description attribute is expected to be used in the future to generate notification messages in the natural language of the job submitter.

Early drafts of [[IPP-MOD](#)] contained a job-level natural language override (NLO) for the Get-Jobs response. A job-level (NLO) is an (unrequested) Job Attribute which then specified the implicit natural language for any other WithoutLanguage job attributes returned in the response for that job. Interoperability testing of early implementations showed that no one was implementing the job-level NLO in Get-Job responses. So the job-level NLO was eliminated from the Get-Jobs response. This simplification makes all requests and responses consistent in that the implicit natural language for any WithoutLanguage 'text' or 'name' form is always supplied in the request's or response's "attributes-natural-language" operation attribute.

## [2.7](#) The "queued-job-count" Printer Description attribute

### 2.7.1 Why is "queued-job-count" RECOMMENDED (Issue 1.14)?

The reason that "queued-job-count" is RECOMMENDED, is that some clients look at that attribute alone when summarizing the status of a list of printers, instead of doing a Get-Jobs to determine the number of jobs in the queue. Implementations that fail to support the "queued-job-count"



Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's Guide February 12, 1999

will cause that client to display 0 jobs when there are actually queued jobs.

We would have made it a REQUIRED Printer attribute, but some implementations had already been completed before the issue was raised, so making it a SHOULD was a compromise.

2.7.2 Is "queued-job-count" a good measure of how busy a printer is (Issue 1.15)?

The "queued-job-count" is not a good measure of how busy the printer is when there are held jobs. A future registration could be to add a "held-job-count" (or an "active-job-count") Printer Description attribute if experience shows that such an attribute (combination) is needed to quickly indicate how busy a printer really is.

## **2.8 Sending empty attribute groups (Issue 1.16)**

The [[IPP-MOD](#)] and [[IPP-PRO](#)] specifications RECOMMEND that a sender not send an empty attribute group in a request or a response. However, they REQUIRE a receiver to accept an empty attribute group as equivalent to the omission of that group. So a client SHOULD omit the Job Template Attributes group entirely in a create operation that is not supplying any Job Template attributes. Similarly, an IPP object SHOULD omit an empty Unsupported Attributes group if there are no unsupported attributes to be returned in a response.

The [[IPP-PRO](#)] specification REQUIRES a receiver to be able to receive either an empty attribute group or an omitted attribute group and treat them equivalently. The term "receiver" means an IPP object for a request and a client for a response. The term "sender" means a client for a request and an IPP object for a response.

There is an exception to the rule for Get-Jobs when there are no attributes to be returned. [ipp-pro] contains the following paragraph:

The syntax allows an xxx-attributes-tag to be present when the xxx-attribute-sequence that follows is empty. The syntax is defined this way to allow for the response of Get-Jobs where no attributes are returned for some job-objects. Although it is RECOMMENDED that the sender not send an xxx-attributes-tag if there are no attributes (except in the Get-Jobs response just mentioned), the

receiver MUST be able to decode such syntax.

## **[2.9](#) Returning unsupported attributes in Get-Xxxx responses (Issue 1.18)**

In the Get-Printer-Attributes, Get-Jobs, or Get-Job-Attributes responses, the client cannot depend on getting unsupported attributes returned in the Unsupported Attributes group that the client requested, but are not supported by the IPP object. However, such unsupported requested attributes will not be returned in the Job Attributes or

Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's Guide February 12, 1999

Printer Attributes group (since they are unsupported). Furthermore, the IPP object is REQUIRED to return the 'successful-ok-ignored-or-substituted-attributes' status code, so that the client knows that not all that was requested has been returned.

## 2.10 Returning job-state in Print-Job response (Issue 1.30)

An IPP client submits a small job via Print-Job. By the time the IPP printer/print server is putting together a response to the operation, the job has finished printing and been removed as an object from the print system. What should the job-state be in the response?

The Model suggests that the Printer return a response before it even accepts the document content. The Job Object Attributes are returned only if the IPP object returns one of the success status codes. Then the job-state would always be "pending" or "pending-held".

This issue comes up for the implementation of an IPP Printer object as a server that forwards jobs to devices that do not provide job status back to the server. If the server is reasonably certain that the job completed successfully, then it should return the job-state as 'completed'. Also the server can keep the job in its "job history" long after the job is no longer in the device. Then a user could query the server and see that the job was in the 'completed' state and completed as specified by the job's "time-at-completed" time which would be the same as the server submitted the job to the device.

An alternative is for the server to respond to the client before or while sending the job to the device, instead of waiting until the server has finished sending the job to the device. In this case, the server can return the job's state as 'pending' with the 'job-outgoing' value in the job's "job-state-reasons" attribute.

If the server doesn't know for sure whether the job completed successfully (or at all), it could return the (out-of-band) 'unknown' value.

On the other hand, if the server is able to query the device and/or setup some sort of event notification that the device initiates when the job makes state transitions, then the server can return the current job state in the Print-Job response and in subsequent queries because the server knows what the job state is in the device (or can query the device).

All of these alternatives depend on implementation of the server and the device.

#### 2.11Flow controlling the data portion of a Print-Job request (Issue 1.22)

A paused printer (or one that is stopped due to paper out or jam or spool space full or buffer space full, may flow control the data of a

Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's Guide February 12, 1999

Print-Job operation (at the TCP/IP layer), so that the client is not able to send all the document data. Consequently, the Printer will not return a response until the condition is changed.

The Printer should not return a Print-Job response with an error code in any of these conditions, since either the printer will be resumed and/or the condition will be freed either by human intervention or as jobs print.

In writing test scripts to test IPP Printers, the script must also be written not to expect a response, if the printer has been paused, until the printer is resumed, in order to work with all possible implementations.

## 2.12 Multi-valued attributes (Issue 1.31)

What is the attribute syntax for a multi-valued attribute? Since some attributes support values in more than one data type, such as "media", "job-hold-until", and "job-sheets", IPP semantics associate the attribute syntax with each value, not with the attribute as a whole. The protocol associates the attribute syntax tag with each value. Don't be fooled, just because the attribute syntax tag comes before the attribute keyword. All attribute values after the first have a zero length attribute keyword as the indication of a subsequent value of the same attribute.

## 2.13 Querying jobs with IPP that were submitted using other job submission protocols (Issue 1.32)

The following clarification was added to [[ipp-mod](#)] [section 8.5](#):

### 8.5 Queries on jobs submitted using non-IPP protocols

If the device that an IPP Printer is representing is able to accept jobs using other job submission protocols in addition to IPP, it is RECOMMEND that such an implementation at least allow such "foreign" jobs to be queried using Get-Jobs returning "job-id" and "job-uri" as 'unknown'. Such an implementation NEED NOT support all of the same IPP job attributes as for IPP jobs. The IPP object returns the 'unknown' out-of-band value for any requested attribute of a foreign job that is supported for IPP jobs, but not for foreign

jobs.

It is further RECOMMENDED, that the IPP Printer generate "job-id" and "job-uri" values for such "foreign jobs", if possible, so that they may be targets of other IPP operations, such as Get-Job-Attributes and Cancel-Job. Such an implementation also needs to deal with the problem of authentication of such foreign jobs. One approach would be to treat all such foreign jobs as belonging to users other than the user of the IPP client. Another approach would be for the foreign job to belong to 'anonymous'. Only if the IPP client has been authenticated as an operator or administrator of the IPP Printer object, could the foreign jobs be queried by an

Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's Guide February 12, 1999

IPP request. Alternatively, if the security policy is to allow users to query other users' jobs, then the foreign jobs would also be visible to an end-user IPP client using Get-Jobs and Get-Job-Attributes.

Thus IPP MAY be implemented as a "universal" protocol that provides access to jobs submitted with any job submission protocol. As IPP becomes widely implemented, providing a more universal access makes sense.

#### 2.14 The 'none' value for empty sets (Issue 1.37)

[ipp-mod] states that the 'none' value should be used as the value of a 1SetOf when the set is empty. In most cases, sets that are potentially empty contain keywords so the keyword 'none' is used, but for the 3 finishings attributes, the values are enums and thus the empty set is represented by the enum 3. Currently there are no other attributes with 1SetOf values which can be empty and can contain values that are not keywords. This exception requires special code and is a potential place for bugs. It would have been better if we had chosen an out-of-band value, either "no-value" or some new value, such as 'none'. Since we didn't, implementations have to deal with the different representations of 'none', depending on the attribute syntax.

#### 2.15 Get-Jobs, my-jobs='true', and 'requesting-user-name' (Issue 1.39)?

In [ipp-mod] [section 3.2.6.1](#) 'Get-Jobs Request', if the attribute 'my-jobs' is present and set to TRUE, MUST the 'requesting-user-name' attribute be there to, and if it's not present what should the IPP printer do?

[ipp-mod] [Section 8.3](#) describes the various cases of "requesting-user-name" being present or not for any operation. If the client does not supply a value for "requesting-user-name", the printer MUST assume that the client is supplying some anonymous name, such as "anonymous".

#### 2.16 The "multiple-document-handling" Job Template attribute and support of multiple document jobs

ISSUE: IPP/1.0 is silent on which of the four effects an implementation would perform if it supports Create-Job, but does not support "multiple-document-handling".

A fix to IPP/1.0 would be to require implementing all four values of "multiple-document-handling" if Create-Job is supported at all. Or at least 'single-document-new-sheet' and 'separate-documents-uncollated-copies'. In any case, an implementation that supports Create-Job SHOULD also support "multiple-document-handling". Support for all four values is RECOMMENDED, but at least the 'single-document-new-sheet' and 'separate-documents-uncollated-copies' values, along with the "multiple-document-handling-default" indicating the default behavior and



Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's Guide February 12, 1999

"multiple-document-handling-supported" values. If an implementation spools the data, it should also support the 'separate-documents-collated-copies' value as well.

### **3 Encoding and Transport**

This section discusses various aspects of IPP/1.0 Encoding and Transport [[IPP-PRO](#)].

A server is not required to send a response until after it has received the client's entire request. Hence, a client must not expect a response until after it has sent the entire request. However, we recommend that the server return a response as soon as possible if an error is detected while the client is still sending the data, rather than waiting until all of the data is received. Therefore, we also recommend that a client listen for an error response that an IPP server MAY send before it receives all the data. In this case a client, if chunking the data, can send a premature zero-length chunk to end the request before sending all the data (and so the client can keep the connection open for other requests, rather than closing it). If the request is blocked for some reason, a client MAY determine the reason by opening another connection to query the server using Get-Printer-Attributes.

In the following sections, there are a tables of all HTTP headers which describe their use in an IPP client or server. The following is an explanation of each column in these tables.

- @ the .header. column contains the name of a header
- @ the .request/client. column indicates whether a client sends the header.
- @ the .request/ server. column indicates whether a server supports the header when received.
- @ the .response/ server. column indicates whether a server sends the header.
- @ the .response /client. column indicates whether a client supports the header when received.
- @ the .values and conditions. column specifies the allowed header values and the conditions for the header to be present in a request/response.

The table for .request headers. does not have columns for responses, and the table for .response headers. does not have columns for requests.

The following is an explanation of the values in the .request/client.

and .response/ server. columns.

- @ must: the client or server MUST send the header,
- @ must-if: the client or server MUST send the header when the condition described in the .values and conditions. column is met,
- @ may: the client or server MAY send the header
- @ not: the client or server SHOULD NOT send the header. It is not relevant to an IPP implementation.

Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's Guide February 12, 1999

The following is an explanation of the values in the .response/client. and .request/ server. columns.

- @ must: the client or server MUST support the header,
- @ may: the client or server MAY support the header
- @ not: the client or server SHOULD NOT support the header. It is not relevant to an IPP implementation.

### **3.1 General Headers**

The following is a table for the general headers.

General-Header	Request		Response		Values and Conditions
	Client	Server	Server	Client	
Cache-Control	must	not	must	not	.no-cache. only
Connection	must-if	must	must-if	must	.close. only. Both client and server SHOULD keep a connection for the duration of a sequence of operations. The client and server MUST include this header for the last operation in such a sequence.
Date	may	may	must	may	per <a href="#">RFC 1123</a> [ <a href="#">RFC1123</a> ] from <a href="#">RFC 2068</a> [ <a href="#">RFC2068</a> ]
Pragma	must	not	must	not	.no-cache. only
Transfer-Encoding	must-if	must	must-if	must	.chunked. only . Header MUST be present if Content-Length is absent.
Upgrade	not	not	not	not	

Via                    not           not           not           not

### [3.2](#) Request Headers

The following is a table for the request headers.

Request-Header	Client	Server	Request Values and Conditions
Accept	may	must	.application/ipp. only. This value is the default if the

Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's Guide February 12, 1999

Request-Header	Client	Server	Request Values and Conditions
			client omits it
Accept-Charset	not	not	Charset information is within the application/ipp entity
Accept-Encoding	may	must	empty and per <a href="#">RFC 2068</a> [ <a href="#">RFC2068</a> ] and IANA registry for content-codings
Accept-Language	not	not	language information is within the application/ipp entity
Authorization	must-if	must	per <a href="#">RFC 2068</a> . A client MUST send this header when it receives a 401 .Unauthorized. response and does not receive a .Proxy-Authenticate. header.
>From	not	not	per <a href="#">RFC 2068</a> . Because RFC recommends sending this header only with the user.s approval, it is not very useful
Host	must	must	per <a href="#">RFC 2068</a>
If-Match	not	not	
If-Modified-Since	not	not	
If-None-Match	not	not	
If-Range	not	not	
If-Unmodified-Since	not	not	
Max-Forwards	not	not	
Proxy- Authorization	must-if	not	per <a href="#">RFC 2068</a> . A client MUST send this header when it receives a 401 .Unauthorized. response and a .Proxy-Authenticate. header.

Range	not	not
Referer	not	not
User-Agent	not	not

Hastings, Manros

[page 51]

Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's GuideFebruary 12, 1999

### **3.3 Response Headers**

The following is a table for the request headers.

Response-Header	Server	Client	Response Values and Conditions
Accept-Ranges	not	not	
Age	not	not	
Location	must-if	may	per <a href="#">RFC 2068</a> . When URI needs redirection.
Proxy-Authenticate	not	must	per <a href="#">RFC 2068</a>
Public	may	may	per <a href="#">RFC 2068</a>
Retry-After	may	may	per <a href="#">RFC 2068</a>
Server	not	not	
Vary	not	not	
Warning	may	may	per <a href="#">RFC 2068</a>
WWW-Authenticate	must-if	must	per <a href="#">RFC 2068</a> . When a server needs to authenticate a client.

### **3.4 Entity Headers**

The following is a table for the entity headers.

Entity-Header	Request		Response		Values and Conditions
	Client	Server	Server	Client	
Allow	not	not	not	not	
Content-Base	not	not	not	not	

Content-Encoding	may	must	must	must	per <a href="#">RFC 2068</a> and IANA registry for content codings.
Content-Language	not	not	not	not	Application/ipp handles language
Content-Length	must-if	must	must-if	must	the length of the message-body per <a href="#">RFC 2068</a> . Header MUST be present if Transfer-



Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's GuideFebruary 12, 1999

Entity-Header	Request		Response		Values and Conditions
	Client	Server	Server	Client	
					Encoding is absent..
Content-Location	not	not	not	not	
Content-MD5	may	may	may	may	per <a href="#">RFC 2068</a>
Content-Range	not	not	not	not	
Content-Type	must	must	must	must	.application/ipp. only
ETag	not	not	not	not	
Expires	not	not	not	not	
Last-Modified	not	not	not	not	

### [3.5](#) Optional support for HTTP/1.0

IPP implementations consist of an HTTP layer and an IPP layer. In the following discussion, the term "client" refers to the HTTP client layer and the term "server" refers to the HTTP server layer. The Encoding and Transport document [[IPP-PRO](#)] requires that HTTP 1.1 MUST be supported by all clients and all servers. However, a client and/or a server implementation may choose to also support HTTP 1.0.

@ This option means that a server may choose to communicate with a (non-conforming) client that only supports HTTP 1.0. In such cases the server should not use any HTTP 1.1 specific parameters or features and should respond using HTTP version number 1.0.

@ This option also means that a client may choose to communicate with a (non-conforming) server that only supports HTTP 1.0. In such cases, if the server responds with an HTTP .unsupported version number. to an HTTP 1.1 request, the client should retry using HTTP version number 1.0.

### [3.6](#) HTTP/1.1 Chunking

### 3.6.1 Disabling IPP Server Response Chunking

Clients MUST anticipate that the HTTP/1.1 server may chunk responses and MUST accept them in responses. However, a (non-conforming) HTTP client that is unable to accept chunked responses may attempt to request an HTTP 1.1 server not to use chunking in its response to an operation by using the following HTTP header:

Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's Guide February 12, 1999

TE: identity

This mechanism should not be used by a server to disable a client from chunking a request, since chunking of document data is an important feature for clients to send long documents.

### 3.6.2 Warning About the Support of Chunked Requests

This section describes some problems with the use of chunked requests and HTTP/1.1 servers.

The HTTP/1.1 standard [[HTTP](#)] requires that conforming servers support chunked requests for any method. However, in spite of this requirement, some HTTP/1.1 implementations support chunked responses in the GET method, but do not support chunked POST method requests. Some HTTP/1.1 implementations that support CGI scripts [[CGI](#)] and/or servlets [[Servlet](#)] require that the client supply a Content-Length. These implementations might reject a chunked POST method and return a 411 status code (Length Required), might attempt to buffer the request and run out of room returning a 413 status code (Request Entity Too Large), or might successfully accept the chunked request.

Because of this lack of conformance of HTTP servers to the HTTP/1.1 standard, the IPP standard [[IPP-PRO](#)] REQUIRES that a conforming IPP Printer object implementation support chunked requests and that conforming clients accept chunked responses. Therefore, IPP object implementers are warned to seek HTTP server implementations that support chunked POST requests in order to conform to the IPP standard and/or use implementation techniques that support chunked POST requests.

## [4](#) References

[CGI]

CGI/1.1 (<http://www.ietf.org/internet-drafts/draft-coar-cgi-v11-00.txt>).

[HTTP]

HTTP/1.1 (<http://www.ietf.org/internet-drafts/draft-ietf-http-v11-spec-rev-06.txt>)

[IPP LPD]

Herriot, R., Hastings, T., Jacobs, N., Martin, J., "Mapping between LPD and IPP Protocols", [draft-ietf-ipp-lpd-ipp-map-04.txt](#), June

1998.

[IPP-MOD]

R. deBry, T. Hastings, R. Herriot, S. Isaacson, P. Powell,  
"Internet Printing Protocol/1.0: Model and Semantics", [draft-ietf-ipp-model-11.txt](#), November, 1998.

Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's Guide February 12, 1999

[IPP-PRO]

Herriot, R., Butler, S., Moore, P., Tuner, R., "Internet Printing Protocol/1.0: Encoding and Transport", [draft-ietf-ipp-protocol-07.txt](#), November, 1998.

[IPP-RAT]

Zilles, S., "Rationale for the Structure and Model and Protocol for the Internet Printing Protocol", [draft-ietf-ipp-rat-03.txt](#), June, 1998.

[IPP-REQ]

Wright, D., "Design Goals for an Internet Printing Protocol", [draft-ietf-ipp-req-02.txt](#), June, 1998.

[RFC1123]

Braden, S., "Requirements for Internet Hosts - Application and Support", [RFC 1123](#), October, 1989.

[RFC2026]

S. Bradner, "The Internet Standards Process -- Revision 3", [RFC 2026](#), October 1996.

[RFC2068]

R Fielding, et al, .Hypertext Transfer Protocol . HTTP/1.1. [RFC 2068](#), January 1997.

[rfc2119]

S. Bradner, "Key words for use in RFCs to Indicate Requirement Levels", [RFC 2119](#) , March 1997.

[RFC2396]

Berners-Lee, T., Fielding, R., Masinter, L., "Uniform Resource Identifiers (URI): Generic Syntax", [RFC 2396](#), August 1998.

[Servlet]

Servlet Specification Version 2.1  
(<http://java.sun.com/products/servlet/2.1/index.html>).

[SSL]

Netscape, The SSL Protocol, Version 3, (Text version 3.02), November 1996.

#### **4.1 Authors. Address**

Thomas N. Hastings  
Xerox Corporation  
**701 Aviation Blvd.**  
El Segundo, CA 90245  
hastings@cp10.es.xerox.com

Carl-Uno Manros

Hastings, Manros

[page 55]

Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's Guide February 12, 1999

Xerox Corporation  
[701 Aviation Blvd.](#)  
El Segundo, CA 90245  
manros@cp10.es.xerox.com

## **5 Notices**

The IETF takes no position regarding the validity or scope of any intellectual property or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; neither does it represent that it has made any effort to identify any such rights. Information on the IETF's procedures with respect to rights in standards-track and standards-related documentation can be found in [BCP-11](#)[BCP-11]. Copies of claims of rights made available for publication and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF Secretariat.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights which may cover technology that may be required to practice this standard. Please address the information to the IETF Executive Director.

Copyright (C) The Internet Society (1999). All Rights Reserved.

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this paragraph are included on all such copies and derivative works. However, this document itself may not be modified in any way, such as by removing the copyright notice or references to the Internet Society or other Internet organizations, except as needed for the purpose of developing Internet standards in which case the procedures for copyrights defined in the Internet Standards process must be followed, or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by the Internet Society or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.



Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's Guide February 12, 1999

## **6 Change History**

The change history is in reverse chronological order:

### **6.1 Changes to produce the February 12, 1999 version from the January 8, 1999 version:**

1. [Section 2.2.1.5](#): added check for document not found or accessible in Print-URI and Send-URI
2. [Section 3.6.2](#): Clarified that the IPP standard requires that servers MUST accept chunked requests and that clients MUST accept chunked responses, in spite of the lack of conformance of HTTP servers to the HTTP/1.1 requirement to support chunking.

### **6.2 Changes to produce the January 8, 1999 version from the December 6, 1998 version:**

1. Added [section 3.6.2](#): Warning About the Use of Chunked Requests with CGI Script Implementations
2. [Section 2.2.1.2](#): changed "printer-operations-supported" to "operations-supported".
3. [Section 2.2.1.6](#): changed "job-media-supported" to "job-media-sheets-supported"
4. [Section 2.2.3](#): separated the validation checks for variable length attributes into two separate tests: one for correct attribute syntax and one for correct length.
5. [Section 2.2.3](#): changed "multiple-document-handling-supported" to "printer-resolution-supported"
6. [Section 2.6.1](#): recommended that an IPP object also support US-ASCII charset.
7. [Section 3](#): Clarified that a server is not required to send a response until after it has received the client's entire request, but recommend that the server return a response as soon as possible if an error is detected while the client is still sending the data, rather than waiting until all of the data is received. Also

recommended that a client listen for an error response that an IPP server MAY send before it receives all the data.

### **6.3 Changes to produce the December 6, 1998 version from the November 16, 1998 version:**

Included all of the remaining agreed issues raised before the November 16, 1998 production of the Internet-Drafts for IPP/1.0 that included adding explanations to the Implementers Guide.

Expires August 12, 1999

INTERNET-DRAFT IPP/1.0: Implementer's Guide February 12, 1999



Expires August 12, 1999