Robert Herriot (editor)
Sun Microsystems, Inc.
Tom Hastings
Xerox Corporation
Norm Jacobs
Sun Microsystems, Inc.
Jay Martin
Underscore, Inc.
July 30, 1997

Mapping between LPD and IPP Protocols <<u>draft-ietf-ipp-lpd-ipp-map-01.txt</u>> Expires Jan 30, 1998

Status of this Memo

This document is an Internet-Draft. Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

To learn the current status of any Internet-Draft, please check the "1id-abstracts.txt" listing contained in the Internet-Drafts Shadow Directories on ftp.is.co.za (Africa), nic.nordu.net (Europe), munnari.oz.au (Pacific Rim), ds.internic.net (US East Coast), or ftp.isi.edu (US West Coast).

Abstract

This Internet-Draft specifies the mapping between (1) the commands and operands of the "Line Printer Daemon (LPD) Protocol" specified in RFC 1179 and (2) the operations and parameters of the Internet Printing Protocol (IPP). One of the purposes of this document is to compare the functionality of the two protocols. Another purpose is to facilitate implementation of gateways between LPD and IPP.

WARNING: RFC 1179 was not on standards track. While RFC 1179 was intended to record existing practice, it fell short in some areas. However, this specification maps between (1) the actual current practice of RFC 1179 and (2) IPP. This document does not attempt to map the numerous divergent extensions to the LPD protocol that have been made by many implementers.

Herriot, Hastings, July 30, 1997,

[Page 1]

TABLE OF CONTENTS

${ t 1}$. Introduction	<u>3</u>
2. Terminology	<u>3</u>
3. Mapping from LPD Commands to IPP Operations	<u>4</u>
3.1 Print any waiting jobs	<u>4</u>
3.2 Receive a printer job	<u>4</u>
3.2.1 Abort job	<u>5</u>
3.2.2 Receive control file	<u>6</u>
<u>3.2.3</u> Receive data file	<u>6</u>
3.3 Send queue state (short)	<u>6</u>
3.4 Send queue state (long)	<u>8</u>
3.5 Remove jobs	<u>9</u>
4. Mapping of LPD Control File Lines to IPP Parameters	. <u>10</u>
4.1 Required Job Functions	
4.2 Optional Job Functions	
4.3 Required Document Functions	
4.4 Recommended Document Functions	
5. Mapping from IPP operations to LPD commands	
<u>5.1</u> Get-Operations	
<u>5.2</u> Print-Job	
<u>5.3</u> Print-URI	
<u>5.4</u> Validate-Job	
<u>5.5</u> Create-Job	
<u>5.6</u> Send-Document	
<u>5.7</u> Send-URI	
<u>5.8</u> Cancel-Job	
<u>5.9</u> Get-Attributes	
<u>5.10</u> Get-Jobs	
6. Mapping of IPP Parameters to LPD Control File Lines	
<u>6.1</u> Required Job Functions	
6.2 Optional Job Functions	
<u>6.3</u> Required Document Functions	
7. References	
8. Author's Addresses	
9. <u>Appendix A</u> : ABNF Syntax for response of Send-queue-state (short)	
<u>10</u> . <u>Appendix B</u> : ABNF Syntax for response of Send-queue-state (long)	
11. Appendix C: Unsupported LPD functions	.21

Herriot, Hastings, July 30, 1997,

[Page 2]

Mapping between the LPD and IPP Protocols

1. Introduction

The reader of this specification is expected to be familiar with the IPP Model and Semantics specification $[\underline{1}]$, the IPP Protocol specification $[\underline{2}]$, and the Line Printer Daemon (LPD) protocol specification $[\underline{3}]$ as described in RFC 1179.

RFC 1179 was written in 1990 in an attempt to document existing LPD protocol implementations. Since then, a number of undocumented extensions have been made by vendors to support functionality specific to their printing solutions. All of these extensions consist of additional control file commands. This document does not address any of these vendor extensions. Rather it addresses existing practice within the context of the features described by RFC 1179. Deviations of existing practice from RFC 1179 are so indicated.

Other LPD control file commands in <u>RFC 1179</u> are obsolete. They are intended to work on "text" only formats and are inappropriate for many contemporary document formats that completely specify each page. This document does not address the support of these obsolete features.

In the area of document formats, also known as page description languages (PDL), RFC 1179 defines a fixed set with no capability for extension. Consequently, some new PDL's are not supported, and some of those that are supported are sufficiently unimportant now that they have not been registered for use with the Printer MIB[4] and IPP[1] [2], though they could be registered if desired. See the Printer MIB specification [4] and/or the IPP Model specification [1] for instructions for registration of document-formats with IANA. IANA lists the registered document-formats as "printer languages".

This document addresses the protocol mapping for both directions: mapping of the LPD protocol to the IPP protocol and mapping of the IPP protocol to the LPD protocol. The former is called the "LPD-to-IPP mapper" and the latter is called the "IPP-to-LPD mapper".

2. Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in RFC 2119 [6].

RFC 1179 uses the word "command" in two contexts: for over-the-wire operations and for command file functions. This document SHALL use the word "command" for the former and the phrase "functions" for the latter. The syntax of the LPD commands is given using ABNF $[\underline{6}]$.

The following tokens are used in order to make the syntax more readable:

LF stands for %x0A (linefeed)
Herriot, Hastings, July 30, 1997, [Page 3]

```
SP stands for %x20. (space)
DIGIT stands for %x30-39 ("0" to "9")
```

3. Mapping from LPD Commands to IPP Operations

This section describes the mapping from LPD commands to IPP operations. Each of the following sub-sections appear as sub-sections of $\frac{5}{5}$ of RFC 1179.

The following table summarizes the IPP operation that the mapper uses when it receives an LPD command. Each section below gives more detail.

LPD command IPP operation

print-any-waiting-jobs ignore

receive-a-printer-job Print-Job or Create-Job/Send-Document send queue state Get-Attributes (printer) and Get-Jobs

(short or long)

remove-jobs Cancel-Job

3.1 Print any waiting jobs

Command syntax:

```
print-waiting-jobs = %x01 printer-name LF
```

This command causes the LPD daemon check its queue and print any waiting jobs. An IPP printer handles waiting jobs without such a nudge.

If the mapper receives this LPD command, it SHALL ignore it and send no IPP operation.

3.2 Receive a printer job

Command syntax:

```
receive-job = %x02 printer-name LF
```

The control file and data files mentioned in the following paragraphs are received via LPD sub-commands that follow this command. Their mapping to IPP commands and attributes is described later in this section.

The mapper maps the 'Receive a printer job' command to either:

. the Print-Job operation which includes a single data file or

. the Create-Job operation followed by one Send-Document operation for each data file.

If the IPP printer supports both Create-Job and Send-Document, and if a job consists of:

Herriot, Hastings, July 30, 1997,

[Page 4]

Mapping between LPD and IPP Protocols July 30, 1997 INTERNET DRAFT

- . a single data file, the mapper SHOULD use the PrintJob operation, but MAY use the Create-Job and Send-Document operations.
- . more than one data file, the mapper SHALL use Create Job followed by one Send-Document for each received LPD data file.

If the IPP printer does not support both Create-Job and Send-Document, and if a job consists of:

- . a single data file, the mapper SHALL use the PrintJob operation.
- . more than one data file, the mapper SHALL submit each received LPD data file as a separate Print-Job operation (thereby converting a single LPD job into multiple IPP jobs).

If the mapper uses Create-Job and Send-Document, it MUST send the Create-Job operation before it sends any Send-Document operations whether the LPD control file, which supplies attributes for Create-Job, arrives before or after all LPD data files.

NOTE: This specification does not specify how the mapper maps: the LPD Printer-name operand to the IPP "printer-uri" parameter.

The following 3 sub-sections gives further details about the mapping from LPD receive-a-printer-job sub-commands. Each of the following sub-sections appear as sub-sections of section 6 of RFC 1179.

ISSUE: the mapper needs to maintain information such as the mapping of each job-number to its corresponding job-URI. It would be nice for IPP to support an "scratch-pad" attribute for the mapper to encode such information. Then it wouldn't have to maintain this information separately.

3.2.1 Abort job

Sub-command syntax:

abort-job = %x1 LF

This sub-command of receive-a-printer-job is intended to abort any job transfer in process.

If the mapper receives this sub-command, it SHALL cancel the job that it is in the process of transmitting.

If the mapper is in the process of sending a Print-Job or Create-Job operation, it terminates the job either by closing the connection, or performing the Cancel-Job operation with the job-uri that it received from the Print-Job or Create-Job operation.

NOTE: This sub-command is implied if at any time the connection between the LPD client and server is terminated before an entire print job has been transferred via an LPD Receive-a-printer-job request.

Herriot, Hastings,

July 30, 1997,

[Page 5]

3.2.2 Receive control file

Sub-command syntax:

This sub-command is roughly equivalent to the IPP Create-Job operation.

The mapper SHALL use the contents of the received LPD control file to create IPP parameter and attribute values to transmit with the Print-Job or Create-Job operation.

3.2.3 Receive data file

Sub-command syntax: %x3 number-of-bytes-in-data-file Name-of-data-file

This sub-command is roughly equivalent to the IPP Send-Document operation.

The mapper SHALL use the contents of the received LPD data file as the data to transmit with the IPP Print-Job or Send-Document operation.

Although RFC-1179 alludes to a method for passing an unspecified length data file by using an octet-count of zero, no implementations support this feature.. The mapper SHALL reject a job that has a value of on the number-of-bytes field.

3.3 Send queue state (short)

Command syntax:

```
send-queue-short = %x03 printer-name *(SP(user-name / job-number)) LF
```

The mapper's response to this command includes information about the printer and its jobs. RFC 1179 specifies neither the information nor the format of its response. This document requires the mapper to follow existing practice as specified in this document.

Herriot, Hastings, July 30, 1997, [Page 6]

The mapper SHALL produce a response in the following format which consists of a printer-status line optionally followed by a heading line, and a list of jobs. This format is defined by examples below. Appendix A contains the ABNF syntax.

For an printer with no jobs, the response starts in column 1 and is:

no entries

For a printer with jobs, an example of the response is:

killtree is ready and printing

Rank	0wner	Job	Files	Total Size
active	fred	123	stuff	1204 bytes
1st	smith	124	resume, foo	34576 bytes
2nd	fred	125	more	99 bytes
3rd	mary	126	mydoc	378 bytes
4th	jones	127	statistics.ps	4567 bytes
5th	fred	128	data.txt	9 bytes

The column numbers of above headings and job entries are:

<u>01</u>	08	19	35	63

The mapper SHALL produce each field above from the following IPP attribute:

LPD field	IPP attribute	special conversion details
printer- status	printer-state and printer-state-reasons	For a printer-state of idle or processing, the mapper SHALL use the formats above. For stopped, the mapper SHALL use printer-state-reasons to produce an unspecified format for the error.
rank	number-of- intervening-jobs	the mapper SHALL the format above
owner	job-originating-user	unspecified conversion; job- originating-user may be the mapper's user-name
job	job-uri	unspecified conversion
files	document-name	the mapper shall create a comma separated list of the document- names and then truncate this list to the first 24 characters

total- job-k-octets the mapper shall multiple the size value of job-k-octets by 1024.

A mapper SHOULD use the job attribute number-of-intervening-jobs rather than the job's position in a list of jobs to determine `rank' because a Printer may omit jobs that it wants to keep secret. If a printer doesn't

Herriot, Hastings, July 30, 1997, [Page 7]

support the job attribute number-of-intervening-jobs, a mapper MAY use the job's position.

ISSUE: is job-k-octets the sum of the bytes of each document times the number of copies? If so, "total-size" is 1024 times job-k-octets. The model document needs clarification.

In order to obtain the information specified above, The LPD-to-IPP mapper SHALL use the Get-Attributes operation of the printer to get printer-status and SHOULD use the Get-Jobs operation to get information about all of the jobs. If the LPD command contains job-numbers or usernames, the mapper handles the filtering of the response because Get-Jobs has no way to limit jobs to those of a particular user. If the LPD command contains job-numbers but no user-names, the mapper MAY use Get-Attributes on each converted job-number rather than Get-Jobs.

NOTE: This specification does not define how the mapper maps the LPD Printer-name operand to the IPP "printer-uri" parameter.

3.4 Send queue state (long)

Command syntax:

send-queue-long = %x04 printer-name *(SP(user-name / job-number)) LF

The mapper's response to this command includes information about the printer and its jobs. RFC 1179 specifies neither the information nor the format of its response. This document requires the mapper to follow existing practice as specified in this document.

The mapper SHALL produce a response in the following format which consists of a printer-status line optionally followed a list of jobs, where each job consists of a blank line, a description line, and one line for each file. The description line contains the user-name, rank, job-number and host. This format is defined by examples below. Appendix B contain the ABNF syntax.

For an printer with no jobs the response is:

no entries

For a printer with jobs, an example of the response is:

killtree is ready and printing

fred: active [job 123 tiger]

2 copies of stuff 602 bytes

smith: 1st [job 124 snail]

2 copies of resume 7088 bytes 2 copies of foo 10200 bytes

fred: 2nd [job 125 tiger]

Herriot, Hastings, July 30, 1997, [Page 8]


Jacobs, Martin

Expires January 30, 1998

INTERNET DRAFT Mapping between LPD and IPP Protocols July 30, 1997

more 99 bytes

The column numbers of above headings and job entries are:



Although the format of the long form is different from the format of the short form, their fields are identical except for the copies and host fields which are only in the long form. For fields other than the host and copies fields, see the preceding section. For the host field see the table below.

LPD field IPP attribute special conversion details

host job-originating-host unspecified conversion; joboriginating-host may be the
mapper's host

copies copies the mapper shall assume the
value of copies precedes the
string "copies of "; otherwise,
the value of copies is 1.

NOTE: This specification does not define how the mapper maps the LPD Printer-name operand to the IPP printer-uri parameter.

3.5 Remove jobs

Command syntax:

The agent operand is the user-name of the user initiating the removejobs command. The special user-name 'root' indicates a privileged user who can remove jobs whose user-name differs from the agent..

The mapper SHALL issue one Cancel-Job operation for each job referenced by the remove-jobs command. Each job-number in the remove-jobs command references a single job. Each user-name in the remove-jobs command implicitly references all jobs owned by the specified user. The active job is implicitly referenced when the remove-jobs command contains neither job-numbers nor user-names. The mapper MAY use Get-Job to determine the job-uri of implicitly referenced jobs.

The mapper SHALL not use the agent name of `root' when end-users cancel their own jobs. Violation of this rule creates a potential security violation, and it may cause the printer to issue a notification that misleads a user into thinking that some other person canceled the job.

If the agent of a remove-jobs command for a job J is the same as the user name specified with the `P' function in the control file for job J, Herriot, Hastings, July 30, 1997, [Page 9]

then the mapper SHALL ensure that the caller of the Cancel-Job command for job J is the same as job-originating-user for job J.

Note: This requirement means that a mapper must be consistent in who the receiver perceives as the caller of IPP operations. The mapper either acts as itself or acts on behalf of another user. The latter is preferable if it is possible. This consistency is necessary between Print-Job/Create-Job and Cancel-Job in order for Cancel-Job to work, but it is also desirable for other operations. For example, Get-Jobs may give more information about job submitted by the caller of this operation.

NOTE: This specification does not define how the mapper maps: (1) the LPD printer-name to the IPP "printer-uri" or (2) the LPD job-number to the IPP "job-uri".

NOTE: This specification does not specify how the mapper maps the LPD user-name to the IPP job-originating-user because the mapper may use its own user-name with jobs.

4. Mapping of LPD Control File Lines to IPP Parameters

This section describes the mapping from LPD control file lines (called `functions') to IPP operation input parameters. The mapper receives the control file lines via the LPD receive-control-file sub-command.. Each of the LPD functions appear as sub-sections of section 7 of RFC 1179.

In LPD control file lines, the text operands have a maximum length of 31 or 99 while IPP input parameters have a maximum of 255 characters. Therefore, no data is lost.

The mapper converts each supported LPD function to its corresponding IPP parameter as defined by tables in the subsections that follow. These subsections group functions according to whether they are:

- . required with a job,
- . optional with a job
- . required with each document.

In the tables below, each LPD value is given a name, such as `h'. If an IPP value uses the LPD value, then the IPP value column contains the LPD name, such as `h' to denote this. Otherwise, the IPP value column specifies the literal value.

4.1 Required Job Functions

The following LPD functions MUST be in a received LPD job. The mapper SHALL receive each of the following LPD functions and SHALL include the information as a parameter with each IPP job. The functions SHOULD be in the order `H', `P' and they SHOULD be the first two functions in the control file, but they MAY be anywhere in the control file and in any order.

Herriot, Hastings,

July 30, 1997,

[Page 10]

LPD	function		IPP	
name	value	description	name	value
Н	h	Originating Host		h (in security layer)
Р	u	User identification		u (in security layer)
		none	best-effort	`true'

A mapper MAY sends its own host rather than the client's host, and a mapper MAY send its own user-name as user identification rather than the client user. But in any case, the values sent SHALL be compatible with the Cancel-Job operation. The IPP operation MAY have no way to specify an originating host-name.

ISSUE: what do we do about job-orginating-host?

The mapper SHALL include best-effort=true so that it doesn't have to determine which attributes a printer supports.

4.2 Optional Job Functions

The following LPD functions MAY be in a received job. These function SHOULD follow the required job functions and precede the document functions, but they MAY be anywhere in the control file.

If the mapper receives such an LPD function, the mapper SHALL include the corresponding IPP attribute with the value converted as specified in the table below. If the mapper does not receive such an LPD attribute, the mapper SHALL NOT include the corresponding IPP attribute, except the `L' LPD function whose absence has a special meaning as noted in the table.

L	PD funct	ion	IPP	
n	ame valu	e description	name	value
J	j	Job name for banner page	job-name	j
L	1	Print banner page	job-sheets	`standard' if `L' is present `none' if `L' is present
M	m	Mail When Printed	notification- events notification- method	`job-completion' 'mailto://'m`@'h

Note: `m' is the user name and not an email address. The mapper can fabricate an email address with the source host. This email address

mail fail when the `h' is some intermediary host that doesn't know about user `m'. But there is no better solution.

Herriot, Hastings, July 30, 1997, [Page 11]

4.3 Required Document Functions

The mapper SHALL receive one set of the required document functions with each copy of a document, and SHALL include the converted information as parameters with each IPP document

If the control file contains required and recommended document functions, the required functions SHOULD precede the recommended ones and if the job contains multiple documents, all the functions for each document are grouped together as shown in the example of section 6.3 "Required Document Functions". However, the document functions MAY be in any order.

LPD function		IPP		
name	valu	description	name	value
	е			
f	fff	Print formatted file	document-format	37 (langAutomatic)
1	fff	Print file leaving control characters	document-format	37 (langAutomatic)
0	fff	Print Postscript output file	document-format	6 (langPS).
			conies	see note

Note: In practice, the `f' LPD function is often overloaded. It is often used with any format of document data including PostScript and PCL data.

Note: In practice, the `l' LPD function is often used as a rough equivalent to the `f' function.

Note: When RFC 1179 was written, no implementation supported the `o' function; instead `f' was used for PostScript. Windows NT now sends `o' function for a PostScript file.

Note: the value `fff' of the `f', `l' and `o' functions is the name of the data file as transferred, e.g. "dfA123woden".

If the mapper receives any other lower case letter, the mapper SHALL reject the job because the document contains a format that the mapper does not support.

The mapper determines the number of copies by counting the number of occurrences of each `fff' file with one of the lower-case functions above. For example, if `f dfA123woden' occurs 4 times, then copies has a value of 4. Although the LPD protocol allows the value of copies to be different for each document, the commands and the receiving print systems don't support this.

ISSUE: should we register DVI, ditroff and troff. At least DVI and one of the troff is still in use.

Herriot, Hastings, July 30, 1997, [Page 12]

4.4 Recommended Document Functions

The mapper SHOULD receive one set of the recommended document functions with each document, and SHOULD include the converted information as parameters with each IPP document. The functions SHOULD be received in the order `U' and `N', but they MAY arrive in any order.

LPD function IPP name value description name value

U fff ignored

N n Name of source file document-name n

Note: the value `fff' of the `U' function is the name of the data file as transferred, e.g. "dfA123woden".

5. Mapping from IPP operations to LPD commands

If the IPP-to-LPD mapper receives an IPP operation, the following table summarizes the LPD command that it uses. Each section below gives the detail. Each of the following sub-sections appear as sub-sections of section 3 in the document "Internet Printing Protocol/1.0: Model and Semantics" [1].

IPP operation LPD command

Get-Operations implemented by the mapper Print-Job or Print-URI or receive-a-printer-job

Create-Job/Send-Document/Send-URI and then print-any-waiting-jobs Validate-Job implemented by the mapper

Cancel-Job remove-jobs

Get-Attributes (printer or job) send queue state (short or long)

or Get-Jobs

5.1 Get-Operations

The mapper SHALL return a list of the operations that it supports. It SHALL support at least those operations that are mandatory according to the IPP model document $[\underline{1}]$.

5.2 Print-Job

The mapper SHALL send the following commands in the order listed below:

- . receive-a-printer-job command
- . both receive-control-file sub-command and receive-data-file $\operatorname{sub-command}$

(unspecified order, see Note below)

. print-any-waiting-jobs command,

except that if the mapper is sending a sequence of receive-a-Herriot, Hastings, July 30, 1997, [Page 13]

printer-job commands, it MAY omit sending print-any-waitingjobs after any receive-a printer-job command that is neither the first nor last command in this sequence

Note: it is recommended that the order of the receive-control-file subcommand and the receive-data-file sub-command be configurable because either order fails for some print systems. Some print systems assume that the control file follows all data files and start printing immediately on receipt of the control file. When such a print system tries to print a data file that has not arrived, it produces an error. Other print systems assume that the control file arrives before the data files and start printing when the first data file arrives. Such a system ignores the control information, such as banner page or copies.

NOTE: This specification does not define the mapping between the IPP printer-uri and the LPD printer-name.

The mapper SHALL send the IPP parameters and attributes received from the operation to the LPD printer by using the LPD receive-control-file sub-command. The mapper SHALL create the job-number for use in the control file name, but the receiving printer MAY, in some circumstances, assign a different job-number to the job. The mapper SHALL create the job-uri returned in the Print-Job response.

NOTE: This specification does not specify how the mapper determines the job-number or the job-uri of a job that it creates nor does it specify the relation ship between the job-uri and the job-number, both of which the mapper creates.

The mapper SHALL send data received in the IPP operation to the LPD printer by using the LPD receive-data-file sub-command. The mapper SHALL specify the exact number of bytes being transmitted in the number-ofbytes field of the receive-data-file sub-command. It SHALL NOT use a value of 0 in this field.

If the mapper, while it is transmitting a receive-a-printer-job command or sub-command, either detects that its IPP connection has closed or receives a Cancel-Job operation, the mapper SHALL terminate the LPD job either with the abort sub-command or the remove-jobs command.

ISSUE: error code conversion.

5.3 Print-URI

The mapper SHALL handle this operation in the same way as a Print-Job

operation except that it SHALL obtain data referenced by the "documenturi" parameter and SHALL then treat that data as if it had been received via a Print-Job operation.

Herriot, Hastings, July 30, 1997, [Page 14]

5.4 Validate-Job

The mapper SHALL perform this operation directly. Because LPD supports very few attributes, this operation doesn't have much to check.

5.5 Create-Job

The mapper SHALL handle this operation like Print-Job, except

- the mapper SHALL send the control file after it has received the last Send-Document or Send-URI operation because the control file contains all the document-name and document-format values specified in the Send-Document and Send-URI operations.
- . the mapper SHALL perform one receive-data-file sub-command for each Send-Document or Send-URI operation received and in the same order received.
- . the mapper SHALL send the control file either before all data files or after all data files. (See the note in the section on Print-Job about the dilemma of sending the control file either before or after the data files.

5.6 Send-Document

The mapper performs a receive-data-file sub-command on the received data. See the preceding <u>section 5.5</u> "Create-Job" for the details.

5.7 Send-URI

The mapper SHALL obtain the data referenced by the "document-uri" parameter, and SHALL then treat that data as if it had been received via a Send-Document operation. See the preceding <u>section 5.6</u> "Send-Document" for the details.

5.8 Cancel-Job

The mapper SHALL perform a remove-jobs command with the following parameters:

- . the printer is the one containing the job specified by the IPP job-uri,
- . the agent is the authenticated user-name of the IPP client,

. the job-number is the one corresponding to the IPP job-uri parameter.

NOTE: This specification does not specify how the mapper maps the IPP "job-uri" to the LPD printer-name or LPD job-number.

Herriot, Hastings, July 30, 1997, [Page 15]

ISSUE: the model needs to offer a solution for mapping jobs to printers either with a new job attribute "printer-uri" or with all operation targets being a printer-uri.

5.9 Get-Attributes

LPD severely limits the set of attributes that the mapper is able to return in its response for this operation.

When the mapper receives a Get-Attributes operation for a printer object, it SHALL support, at most, the following printer attributes:

- . printer-state
- . printer-state-reasons

When the mapper receives a Get-Attributes operation for a job object, it SHALL support, at most, the following job attributes:

- . number-of-intervening-jobs
- job-originating-user
- . job-uri
- job-originating-host
- document-name
- iob-k-octets
- copies

The mapper uses either the long or short form of the "send queue state" command. If it receives a request for the "job-originating-host" or "copies" and supports those attribute it SHALL use the long form; otherwise, it SHALL use the short form.

Note: the value of job-k-octets is the value in the short form, but it can be computed from the copies and file size fields in the long form.

The mapper SHALL assume that the LPD response that it receives has the format and information specified in section 3.3 "Send queue state (short)" and section 3.4 "Send queue state (long)". The mapper SHALL determine the value of each requested attribute by using the inverse of the mapping specified in the two aforementioned sections.

Note: when the mapper receives the Get-Attributes operation for a printer, it can determine the response from the printer-status line without examining the rest of the LPD response. When the mapper receives the Get-Attributes operation for a job and uses the LPD short form, it can determine the response from the single line that pertains to the job specified by the Get-Attributes operation.

NOTE: For Get-Attributes of a job, this specification does not specify how the mapper maps the IPP "job-uri" to the LPD printer-name or LPD job-number.

Herriot, Hastings, July 30, 1997,

[Page 16]

5.10 Get-Jobs

The mapper SHALL perform this operation in the same way as Get-Attributes of a printer except that the mapper converts the job-lines, and the IPP response contains one job object for each job in the LPD response..

6. Mapping of IPP Parameters to LPD Control File Lines

This section describes the mapping from IPP operation input parameters to LPD control file lines (called `functions'). The mapper receives the IPP operation input parameters via the IPP operation. Each of the IPP operation input parameters appear as sub-sections of section 3 and 4.2 in the IPP model document [1].

In the context of LPD control file lines, the text operands have a maximum length of 31 or 99 while IPP input parameters have a maximum of 255 characters. Therefore, there may be some data loss if the IPP parameters exceed the maximum length of the LPD equivalent operands.

The mapper converts each supported IPP parameter to its corresponding LPD function as defined by tables in the subsections that follow. These subsections group functions according to whether they are:

- . required with a job,
- . optional with a job
- required with each document.

In the tables below, each IPP value is given a name, such as `h'. If an LPD value uses the IPP value, then the LPD value column contains the IPP name, such as `h' to denote this. Otherwise, the LPD value column specifies the literal value.

6.1 Required Job Functions

The mapper SHALL include the following LPD functions with each job, and they SHALL have the specified value. They SHALL be the first functions in the control file and they SHALL be in the order "H" and then "P".

IPP	LPD function			
name	value	name	value	description
(in security layer)	h	Н	gateway host	Originating Host
(in security layer)	u	Р	u	User identification

A mapper SHALL sends its own host rather than the client's host, because some LPD systems require that it be the same as the host from which the remove-jobs command comes. A mapper MAY send its own user name as user identification rather than the client user. But in any case, the values sent SHALL be compatible with the LPD remove-jobs operation.

Herriot, Hastings, July 30, 1997,

[Page 17]

INTERNET DRAFT Mapping

Mapping between LPD and IPP Protocols July 30, 1997

6.2 Optional Job Functions

The mapper MAY include the following LPD functions with each job. They SHALL have the specified value if they are sent. These functions, if present, SHALL follow the require job functions, and they SHALL precede the required document functions.

IPP attribute		LPD	function	
name	value	nam	value	description
		е		
job-name	j	J	j	Job name for banner
				page
job-sheets	`standard'	L	u	Print banner page
job-sheets	`none'			omit `L' function
notification-	`job-completion'		user	Mail When Printed
	user`@'			
M events	`mailto://'			
notification- method	host			

Note: `L' has special meaning when it is omitted. If `M' is omitted, there is no notification. If `J' is omitted, some undefined behavior occurs with respect to the banner page.

Note: the `user' for the `M' function comes from a substring of the notification-method's value.

6.3 Required Document Functions

The mapper SHALL include one set of the following LPD functions with each document, and they SHALL have the specified values. For each document, the order of the functions SHALL be f', f', f', and then f', where f' is replicated once for each copy.

```
IPP attribute LPD function

name value name value description

document- `37' (langAutomatic) f fff Print formatted file format or `6' (langPS).

copies c replicate `f' `c' times
```

Note: the value `fff' of the `f' and `U' functions is the name of the data file as transferred, e.g. "dfA123woden".

Note: the mapper SHALL not send the `o' function

ISSUE: should we register DVI, troff or ditroff? Herriot, Hastings, July 30, 1997,

[Page 18]

If the mapper receives no "best-effort" or it has a value of false, then the mapper SHALL reject the job if it specifies attributes or attribute values that are not among those supported in the above tables.

Below is an example of the minimal control file for a job with three copies of two files `foo' and `bar':

- H tiger
- P jones
- f dfA123woden
- f dfA123woden
- f dfA123woden
- U dfA123woden
- N foo
- f dfB123woden
- f dfB123woden
- f dfB123woden
- U dfB123woden
- N bar

7. References

- [1] R. deBry, T. Hastings, R. Herriot, S. Isaacson, P. Powell, "Internet Printing Protocol/1.0: Model and Semantics", <draft-ietf-ipp-model-02.txt>, July 1997.
- [2] R. Herriot, S. Butler, P. Moore, R. Turner, "Internet Printing Protocol/1.0: Protocol specification", <draft-ietf-ipp-protocol-00.txt>, July 1997.
- [3] L. McLaughlin, "Line Printer Daemon Protocol", RFC 1179, August 1990.
- [4] Smith, R., Wright, F., Hastings, T., Zilles, S., and Gyllenskog, J., "Printer MIB", <u>RFC 1759</u>, March 1995.
- [5] S. Bradner, "Key words for use in RFCs to Indicate Requirement Levels", <u>RFC 2119</u> , March 1997
- [6] D. Crocker et al., "Augmented BNF for Syntax Specifications: ABNF", draft-ietf-drums-abnf-03.txt.

8. Author's Addresses

Robert Herriot (editor)

Norm Jacobs

Sun Microsystems Inc.

901 San Antonio.Road., MPK-17

Sun Microsystems Inc.

1430 Owl Ridge Rd.

Mountain View, CA 94043 Colorado Springs, CO 80919

Phone: 650-786-8995 Phone: 719-532-9927 Fax: 650-786-7077 Fax: 719-535-0956

Email: robert.herriot@eng.sun.com Email:

Norm.Jacobs@Central.sun.com

Herriot, Hastings, July 30, 1997, [Page 19]

Thomas N. Hastings Jay Martin Xerox Corporation Underscore, Inc.

701 S. Aviation Blvd., ESAE-231 41-C Sagamore Park Road El Segundo, CA 90245 Hudson, NH 03051-4915

Phone: 310-333-6413 Phone: 603-889-7000 310-333-5514 Fax: 603-889-2699 Fax:

EMail: hastings@cp10.es.xerox.com Email: jkm@underscore.com

9. Appendix A: ABNF Syntax for response of Send-queue-state (short)

The syntax in ABNF for the response to the LPD command `send-queue-state (long)' is:

```
status-response = empty-queue / nonempty-queue
empty-queue = "no-entries" LF
nonempty-queue = printer-status LF heading LF *(job LF)
printer-status = OK-status / error-status
OK-status = printer-name SP "ready and printing" LF
error-status = < implementation dependent status information >
heading = "Rank" 3SP Owner 6SP "Job" 13SP "Files"
                23SP "Total Size" LF
                   ; the column headings and their values below begin
at the columns
                   ; 1, 8, 19, 35 and 63
job = rank *SP owner *SP job *SP files *SP total-size "bytes"
                  ; jobs are in order of oldest to newest
rank = "active" / "1st" / "2nd" / "3rd" / integer "th"
                  ; job that is printing is "active"
                  ; other values show position in the queue
owner = <user name of person who submitted the job>
job = 1*3DIGIT ; job-number
files = <file name> *( "," <file name>); truncated to 24 characters
total-size = 1*DIGIT ; combined size in bytes of all documents
```

10. Appendix B: ABNF Syntax for response of Send-queue-state (long)

The syntax in ABNF for the response to the LPD command `send-queue-state (long)' is:

```
status-response = empty-queue / nonempty-queue
empty-queue = "no-entries" LF
nonempty-queue = printer-status LF *job
```

```
; job that is printing is "active"
        ; other values show position in the queue
owner = <user name of person who submitted the job>
job = 1*3DIGIT
file-name = [ 1*DIGIT "copies of" SP ] <file name>
              ; truncated to 24 characters
document-size = 1*DIGIT ; size of single copy of the document.
```

11. Appendix C: Unsupported LPD functions

The follow LPD functions have no IPP equivalent. The LPD-to-IPP mapper ignores them and the IPP-to-LPD mapper does not send them.

LPD command name description С Class for banner page Indent Printing Ι Symbolic link data S Т Title for pr W Width of output troff R font 1 2 troff I font 3 troff B font troff S font

The follow LPD functions specify document-formats which have no IPP equivalent, unless someone registers them. The LPD-to-IPP mapper rejects jobs that request such a document format, and the IPP-to-LPD mapper does not send them.

```
LPD command
       description
name
      Plot CIF file
С
d
      Print DVI file
      Plot file
       reserved for Kerberized clients and servers
       Print ditroff output file
n
       Print file with 'pr' format
      File to print with FORTRAN carriage control
      Print troff output file
V
       Print raster file
       reserved for future use with the Palladium
Z
       print system
```

ISSUE: we may move some of these to the supported list.

Herriot, Hastings, July 30, 1997, [Page 21]