

Network Working Group
Internet-Draft
Intended status: Standards Track
Expires: May 2, 2018

A. Morton
AT&T Labs
M. Bagnulo
UC3M
P. Eardley
BT
K. D'Souza
AT&T Labs
October 29, 2017

Initial Performance Metric Registry Entries
draft-ietf-ippm-initial-registry-05

Abstract

This memo defines the Initial Entries for the Performance Metrics Registry. This version includes:

- * Revised several Poisson streams to Periodic, sections [4](#) & [5](#).
- * Addition of ICMP (ping) metrics in [section 9](#).
- * First implementation of Passive TCP RTT metrics in [section 10](#).

Still need: Add MBM metric entry.

Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)].

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

Internet-Draft

Initial Registry

October 2017

This Internet-Draft will expire on May 2, 2018.

Copyright Notice

Copyright (c) 2017 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](https://trustee.ietf.org/bcp78) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	7
2.	Scope	8
3.	Registry Categories and Columns	8
4.	UDP Round-trip Latency and Loss Registry Entries	9
4.1.	Summary	10
4.1.1.	ID (Identifier)	10
4.1.2.	Name	10
4.1.3.	URIs	10
4.1.4.	Description	10
4.1.5.	Change Controller	10
4.1.6.	Version (of Registry Format)	10
4.2.	Metric Definition	11
4.2.1.	Reference Definition	11
4.2.2.	Fixed Parameters	12
4.3.	Method of Measurement	12
4.3.1.	Reference Method	13
4.3.2.	Packet Stream Generation	14
4.3.3.	Traffic Filtering (observation) Details	14
4.3.4.	Sampling Distribution	15
4.3.5.	Run-time Parameters and Data Format	15
4.3.6.	Roles	15
4.4.	Output	16
4.4.1.	Type	16
4.4.2.	Reference Definition	16

4.4.3.	Metric Units	17
4.4.4.	Calibration	17
4.5.	Administrative items	18
4.5.1.	Status	18
4.5.2.	Requestor (keep?)	18

4.5.3.	Revision	18
4.5.4.	Revision Date	18
4.6.	Comments and Remarks	18
5.	Packet Delay Variation Registry Entry	18
5.1.	Summary	18
5.1.1.	ID (Identifier)	18
5.1.2.	Name	18
5.1.3.	URIs	19
5.1.4.	Description	19
5.1.5.	Change Controller	19
5.1.6.	Version (of Registry Format)	19
5.2.	Metric Definition	19
5.2.1.	Reference Definition	19
5.2.2.	Fixed Parameters	20
5.3.	Method of Measurement	21
5.3.1.	Reference Method	21
5.3.2.	Packet Stream Generation	22
5.3.3.	Traffic Filtering (observation) Details	22
5.3.4.	Sampling Distribution	23
5.3.5.	Run-time Parameters and Data Format	23
5.3.6.	Roles	23
5.4.	Output	23
5.4.1.	Type	24
5.4.2.	Reference Definition	24
5.4.3.	Metric Units	24
5.4.4.	Calibration	25
5.5.	Administrative items	25
5.5.1.	Status	25
5.5.2.	Requestor (keep?)	26
5.5.3.	Revision	26
5.5.4.	Revision Date	26
5.6.	Comments and Remarks	26
6.	DNS Response Latency and Loss Registry Entries	26
6.1.	Summary	26
6.1.1.	ID (Identifier)	26
6.1.2.	Name	27

6.1.3.	URI	27
6.1.4.	Description	27
6.1.5.	Change Controller	27
6.1.6.	Version (of Registry Format)	27
6.2.	Metric Definition	27
6.2.1.	Reference Definition	27
6.2.2.	Fixed Parameters	28
6.3.	Method of Measurement	30
6.3.1.	Reference Method	30
6.3.2.	Packet Stream Generation	31
6.3.3.	Traffic Filtering (observation) Details	32
6.3.4.	Sampling Distribution	32

6.3.5.	Run-time Parameters and Data Format	32
6.3.6.	Roles	33
6.4.	Output	34
6.4.1.	Type	34
6.4.2.	Reference Definition	34
6.4.3.	Metric Units	34
6.4.4.	Calibration	35
6.5.	Administrative items	35
6.5.1.	Status	35
6.5.2.	Requestor	35
6.5.3.	Revision	35
6.5.4.	Revision Date	35
6.6.	Comments and Remarks	35
7.	UDP Poisson One-way Delay and Loss Registry Entries	36
7.1.	Summary	36
7.1.1.	ID (Identifier)	36
7.1.2.	Name	36
7.1.3.	URI and URL	37
7.1.4.	Description	37
7.2.	Metric Definition	37
7.2.1.	Reference Definition	37
7.2.2.	Fixed Parameters	38
7.3.	Method of Measurement	39
7.3.1.	Reference Method	39
7.3.2.	Packet Stream Generation	40
7.3.3.	Traffic Filtering (observation) Details	41
7.3.4.	Sampling Distribution	41
7.3.5.	Run-time Parameters and Data Format	41
7.3.6.	Roles	42

7.4.	Output	42
7.4.1.	Type	42
7.4.2.	Reference Definition	42
7.4.3.	Metric Units	45
7.4.4.	Calibration	45
7.5.	Administrative items	46
7.5.1.	Status	46
7.5.2.	Requestor (keep?)	46
7.5.3.	Revision	46
7.5.4.	Revision Date	46
7.6.	Comments and Remarks	46
8.	UDP Periodic One-way Delay and Loss Registry Entries	47
8.1.	Summary	47
8.1.1.	ID (Identifier)	47
8.1.2.	Name	47
8.1.3.	URIs	48
8.1.4.	Description	48
8.2.	Metric Definition	48
8.2.1.	Reference Definition	48

8.2.2.	Fixed Parameters	49
8.3.	Method of Measurement	50
8.3.1.	Reference Method	50
8.3.2.	Packet Stream Generation	51
8.3.3.	Traffic Filtering (observation) Details	52
8.3.4.	Sampling Distribution	52
8.3.5.	Run-time Parameters and Data Format	52
8.3.6.	Roles	53
8.4.	Output	53
8.4.1.	Type	53
8.4.2.	Reference Definition	53
8.4.3.	Metric Units	56
8.4.4.	Calibration	56
8.5.	Administrative items	57
8.5.1.	Status	57
8.5.2.	Requestor (keep?)	57
8.5.3.	Revision	57
8.5.4.	Revision Date	57
8.6.	Comments and Remarks	57
9.	ICMP Round-trip Latency and Loss Registry Entries	57
9.1.	Summary	58
9.1.1.	ID (Identifier)	58

9.1.2.	Name	58
9.1.3.	URIs	58
9.1.4.	Description	58
9.1.5.	Change Controller	59
9.1.6.	Version (of Registry Format)	59
9.2.	Metric Definition	59
9.2.1.	Reference Definition	59
9.2.2.	Fixed Parameters	60
9.3.	Method of Measurement	61
9.3.1.	Reference Method	61
9.3.2.	Packet Stream Generation	62
9.3.3.	Traffic Filtering (observation) Details	63
9.3.4.	Sampling Distribution	63
9.3.5.	Run-time Parameters and Data Format	63
9.3.6.	Roles	64
9.4.	Output	64
9.4.1.	Type	64
9.4.2.	Reference Definition	64
9.4.3.	Metric Units	66
9.4.4.	Calibration	66
9.5.	Administrative items	67
9.5.1.	Status	67
9.5.2.	Requestor (keep?)	67
9.5.3.	Revision	67
9.5.4.	Revision Date	67
9.6.	Comments and Remarks	67

10.	TCP Round-Trip Delay and Loss Registry Entries	67
10.1.	Summary	67
10.1.1.	ID (Identifier)	68
10.1.2.	Name	68
10.1.3.	URIs	68
10.1.4.	Description	68
10.1.5.	Change Controller	69
10.1.6.	Version (of Registry Format)	69
10.2.	Metric Definition	69
10.2.1.	Reference Definitions	69
10.2.2.	Fixed Parameters	71
10.3.	Method of Measurement	72
10.3.1.	Reference Methods	72
10.3.2.	Packet Stream Generation	74
10.3.3.	Traffic Filtering (observation) Details	74

10.3.4.	Sampling Distribution	74
10.3.5.	Run-time Parameters and Data Format	74
10.3.6.	Roles	75
10.4.	Output	75
10.4.1.	Type	75
10.4.2.	Reference Definition	76
10.4.3.	Metric Units	78
10.4.4.	Calibration	78
10.5.	Administrative items	78
10.5.1.	Status	78
10.5.2.	Requestor (keep?)	78
10.5.3.	Revision	78
10.5.4.	Revision Date	78
10.6.	Comments and Remarks	78
11.	ver08 BLANK Registry Entry	79
11.1.	Summary	79
11.1.1.	ID (Identifier)	79
11.1.2.	Name	79
11.1.3.	URIs	79
11.1.4.	Description	79
11.1.5.	Reference	79
11.1.6.	Change Controller	79
11.1.7.	Version (of Registry Format)	79
11.2.	Metric Definition	79
11.2.1.	Reference Definition	80
11.2.2.	Fixed Parameters	80
11.3.	Method of Measurement	80
11.3.1.	Reference Method	80
11.3.2.	Packet Stream Generation	80
11.3.3.	Traffic Filtering (observation) Details	80
11.3.4.	Sampling Distribution	80
11.3.5.	Run-time Parameters and Data Format	80
11.3.6.	Roles	80

11.4.	Output	81
11.4.1.	Type	81
11.4.2.	Reference Definition	81
11.4.3.	Metric Units	81
11.4.4.	Calibration	81
11.5.	Administrative items	81
11.5.1.	Status	81
11.5.2.	Requestor	81

11.5.3.	Revision	81
11.5.4.	Revision Date	81
11.6.	Comments and Remarks	81
12.	Example RTCP-XR Registry Entry	82
12.1.	Registry Indexes	82
12.1.1.	Identifier	82
12.1.2.	Name	82
12.1.3.	URI	82
12.1.4.	Status	82
12.1.5.	Requestor	82
12.1.6.	Revision	82
12.1.7.	Revision Date	82
12.1.8.	Description	82
12.1.9.	Reference Specification(s)	83
12.2.	Metric Definition	83
12.2.1.	Reference Definition	83
12.2.2.	Fixed Parameters	83
12.3.	Method of Measurement	84
12.3.1.	Reference Method	84
12.3.2.	Stream Type and Stream Parameters	84
12.3.3.	Output Type and Data Format	84
12.3.4.	Metric Units	84
12.3.5.	Run-time Parameters and Data Format	85
12.4.	Comments and Remarks	86
13.	Revision History	86
14.	Security Considerations	87
15.	IANA Considerations	87
16.	Acknowledgements	87
17.	References	88
17.1.	Normative References	88
17.2.	Informative References	90
	Authors' Addresses	92

1. Introduction

Note: Efforts to synchronize structure and terminology with [\[I-D.ietf-ippm-metric-registry\]](#) will likely be incomplete until both drafts are stable.

Metric Registry. It uses terms and definitions from the IPPM literature, primarily [[RFC2330](#)].

Although there are several standard templates for organizing specifications of performance metrics (see [[RFC2679](#)] for an example of the traditional IPPM template, based to large extent on the Benchmarking Methodology Working Group's traditional template in [[RFC1242](#)], and see [[RFC6390](#)] for a similar template), none of these templates were intended to become the basis for the columns of an IETF-wide registry of metrics. While examining aspects of metric specifications which need to be registered, it became clear that none of the existing metric templates fully satisfies the particular needs of a registry.

Therefore, [[I-D.ietf-ippm-metric-registry](#)] defines the overall format for a Performance Metric Registry. Section 5 of [[I-D.ietf-ippm-metric-registry](#)] also gives guidelines for those requesting registration of a Metric, that is the creation of entry(s) in the Performance Metric Registry: "In essence, there needs to be evidence that a candidate Registered Performance Metric has significant industry interest, or has seen deployment, and there is agreement that the candidate Registered Performance Metric serves its intended purpose." The process in [[I-D.ietf-ippm-metric-registry](#)] also requires that new entries are administered by IANA through Expert Review, which will ensure that the metrics are tightly defined.

[2.](#) Scope

This document defines the initial set of Performance Metrics Registry entries, for which IETF approval (following development in the IP Performance Metrics (IPPM) Working Group) will satisfy the requirement for Expert Review. Most are Active Performance Metrics, which are based on RFCs prepared in the IPPM working group of the IETF, according to their framework [[RFC2330](#)] and its updates.

[3.](#) Registry Categories and Columns

This section provides the categories and columns of the registry, for easy reference. An entry (row) therefore gives a complete description of a Registered Metric.

Registry Categories and Columns, shown as

```

Category
-----
Column | Column |

```

Summary

```

-----
Identifier | Name | URIs | Desc. | Reference | Change Controller | Ver |

```

Metric Definition

```

-----
Reference Definition | Fixed Parameters |

```

Method of Measurement

```

-----
Reference | Packet      | Traffic | Sampling | Run-time | Role |
Method    | Stream      | Filter  | Distribution | Parameters |      |
          | Generation  |         |              |           |      |

```

Output

```

-----
Type | Reference | Units | Calibration |
     | Definition |       |              |

```

Administrative Information

```

-----
Status | Request | Rev | Rev.Date |

```

Comments and Remarks

4. UDP Round-trip Latency and Loss Registry Entries

This section specifies an initial registry entry for the UDP Round-trip Latency, and another entry for UDP Round-trip Loss Ratio.

Note: Each Registry entry only produces a "raw" output or a statistical summary. To describe both "raw" and one or more statistics efficiently, the Identifier, Name, and Output Categories can be split and a single section can specify two or more closely-related metrics. This section specifies two Registry entries with many common columns. See [Section 7](#) for an example specifying multiple Registry entries with many common columns.

All column entries beside the ID, Name, Description, and Output Reference Method categories are the same, thus this section proposes

two closely-related registry entries. As a result, IANA is also asked to assign corresponding URNs and URLs to each Named Metric.

[4.1.](#) Summary

This category includes multiple indexes to the registry entry: the element ID and metric name.

[4.1.1.](#) ID (Identifier)

<insert a numeric identifier, an integer, TBD>

IANA is asked to assign different numeric identifiers to each of the two Named Metrics.

[4.1.2.](#) Name

<insert name according to metric naming convention>

RTDelay_Active_IP-UDP-Periodic_RFCXXXXsecY_Seconds_95Percentile

RTLoss_Active_IP-UDP-Periodic_RFCXXXXsecY_Percent_LossRatio

[4.1.3.](#) URIs

URN: Prefix urn:ietf:metrics:perf:<name>

URL: http://<TBD by IANA>/<name>

[4.1.4.](#) Description

RTDelay: This metric assesses the delay of a stream of packets exchanged between two hosts (which are the two measurement points), and the Output is the Round-trip delay for all successfully exchanged packets expressed as the 95th percentile of their conditional delay distribution.

RTLoss: This metric assesses the loss ratio of a stream of packets exchanged between two hosts (which are the two measurement points), and the Output is the Round-trip loss ratio for all successfully exchanged packets expressed as a percentage.

[4.1.5.](#) Change Controller

IETF

[4.1.6.](#) Version (of Registry Format)

1.0

Morton, et al.

Expires May 2, 2018

[Page 10]

Internet-Draft

Initial Registry

October 2017

[4.2.](#) Metric Definition

This category includes columns to prompt the entry of all necessary details related to the metric definition, including the RFC reference and values of input factors, called fixed parameters.

[4.2.1.](#) Reference Definition

<Full bibliographic reference to an immutable doc.>

Almes, G., Kalidindi, S., and M. Zekauskas, "A Round-trip Delay Metric for IPPM", [RFC 2681](#), September 1999.

[RFC2681]

<specific section reference and additional clarifications, if needed>

[Section 2.4 of \[RFC2681\]](#) provides the reference definition of the singleton (single value) Round-trip delay metric. [Section 3.4 of \[RFC2681\]](#) provides the reference definition expanded to cover a multi-singleton sample. Note that terms such as singleton and sample are defined in [Section 11 of \[RFC2330\]](#).

Note that although the [\[RFC2681\]](#) definition of "Round-trip-Delay between Src and Dst" is directionally ambiguous in the text, this metric tightens the definition further to recognize that the host in the "Src" role will send the first packet to "Dst", and ultimately receive the corresponding return packet from "Dst" (when neither are lost).

Finally, note that the variable "dT" is used in [\[RFC2681\]](#) to refer to the value of Round-trip delay in metric definitions and methods. The

variable "dT" has been re-used in other IPPM literature to refer to different quantities, and cannot be used as a global variable name.

Morton, A., "Round-trip Packet Loss Metrics", [RFC 6673](#), August 2012.

[RFC6673]

Both delay and loss metrics employ a maximum waiting time for received packets, so the count of lost packets to total packets sent is the basis for the loss ratio calculation as per [Section 6.1 of \[RFC6673\]](#).

Morton, et al.

Expires May 2, 2018

[Page 11]

Internet-Draft

Initial Registry

October 2017

[4.2.2.](#) Fixed Parameters

<list and specify Fixed Parameters, input factors that must be determined and embedded in the measurement system for use when needed>

Type-P as defined in [Section 13 of \[RFC2330\]](#):

- o IPv4 header values:
 - * DSCP: set to 0
 - * TTL: set to 255
 - * Protocol: Set to 17 (UDP)
- o IPv6 header values:
 - * DSCP: set to 0
 - * Hop Count: set to 255
 - * Protocol: Set to 17 (UDP)
- o UDP header values:

- * Checksum: the checksum MUST be calculated and included in the header
- o UDP Payload
 - * total of 100 bytes

Other measurement parameters:

- o Tmax: a loss threshold waiting time
 - * 3.0, expressed in units of seconds, as a positive value of type decimal64 with fraction digits = 4 (see [section 9.3 of \[RFC6020\]](#)) and with resolution of 0.0001 seconds (0.1 ms), with lossless conversion to/from the 32-bit NTP timestamp as per [section 6 of \[RFC5905\]](#).

[4.3.](#) Method of Measurement

This category includes columns for references to relevant sections of the RFC(s) and any supplemental information needed to ensure an unambiguous methods for implementations.

[4.3.1.](#) Reference Method

<for metric, insert relevant section references and supplemental info>

The methodology for this metric is defined as Type-P-Round-trip-Delay-Poisson-Stream in [section 2.6 of RFC 2681 \[RFC2681\]](#) and [section 3.6 of RFC 2681 \[RFC2681\]](#) using the Type-P and Tmax defined under Fixed Parameters. However, the Periodic stream will be generated according to [\[RFC3432\]](#).

The reference method distinguishes between long-delayed packets and lost packets by implementing a maximum waiting time for packet arrival. Tmax is the waiting time used as the threshold to declare a packet lost. Lost packets SHALL be designated as having undefined delay, and counted for the RTLoss metric.

The calculations on the delay (RTT) SHALL be performed on the

conditional distribution, conditioned on successful packet arrival within T_{max} . Also, when all packet delays are stored, the process which calculates the RTT value MAY enforce the T_{max} threshold on stored values before calculations. See [section 4.1 of \[RFC3393\]](#) for details on the conditional distribution to exclude undefined values of delay, and [Section 5 of \[RFC6703\]](#) for background on this analysis choice.

The reference method requires some way to distinguish between different packets in a stream to establish correspondence between sending times and receiving times for each successfully-arriving packet. Sequence numbers or other send-order identification MUST be retained at the Src or included with each packet to disambiguate packet reordering if it occurs.

If a standard measurement protocol is employed, then the measurement process will determine the sequence numbers or timestamps applied to test packets after the Fixed and Runtime parameters are passed to that process. The chosen measurement protocol will dictate the format of sequence numbers and time-stamps, if they are conveyed in the packet payload.

Refer to [Section 4.4 of \[RFC6673\]](#) for expanded discussion of the instruction to "send a Type-P packet back to the Src as quickly as possible" in [Section 2.6 of RFC 2681 \[RFC2681\]](#). [Section 8 of \[RFC6673\]](#) presents additional requirements which MUST be included in the method of measurement for this metric.

[4.3.2](#). Packet Stream Generation

<list of generation parameters and section/spec references if needed>

This section gives the details of the packet traffic which is the basis for measurement. In IPPM metrics, this is called the Stream, and can easily be described by providing the list of stream parameters.

[Section 3 of \[RFC3432\]](#) prescribes the method for generating Periodic streams using associated parameters.

incT the nominal duration of inter-packet interval, first bit to first bit, with value 0.0200, expressed in units of seconds, as a positive value of type decimal64 with fraction digits = 4 (see [section 9.3 of \[RFC6020\]](#)) and with resolution of 0.0001 seconds (0.1 ms).

dT the duration of the interval for allowed sample start times, with value 1.0, expressed in units of seconds, as a positive value of type decimal64 with fraction digits = 4 (see [section 9.3 of \[RFC6020\]](#)) and with resolution of 0.0001 seconds (0.1 ms).

T0 the actual start time of the periodic stream, (format "date-and-time" as specified in [Section 5.6 of \[RFC3339\]](#), see also [Section 3 of \[RFC6991\]](#)).

NOTE: an initiation process with a number of control exchanges resulting in unpredictable start times (within a time interval) may be sufficient to avoid synchronization of periodic streams, and therefore a valid replacement for selecting a start time at random from a fixed interval.

The T0 parameter will be reported as a measured parameter. Parameters incT and dT are Fixed Parameters.

[4.3.3.](#) Traffic Filtering (observation) Details

The measured results based on a filtered version of the packets observed, and this section provides the filter details (when present).

<section reference>.

NA

[4.3.4.](#) Sampling Distribution

<insert time distribution details, or how this is diff from the filter>

NA

4.3.5. Run-time Parameters and Data Format

Run-time Parameters are input factors that must be determined, configured into the measurement system, and reported with the results for the context to be complete.

<list of run-time parameters, and their data formats>

Src the IP address of the host in the Src Role (format ipv4-address-no-zone value for IPv4, or ipv6-address-no-zone value for IPv6, see [Section 4 of \[RFC6991\]](#))

Dst the IP address of the host in the Dst Role (format ipv4-address-no-zone value for IPv4, or ipv6-address-no-zone value for IPv6, see [section 4 of \[RFC6991\]](#))

T0 a time, the start of a measurement interval, (format "date-and-time" as specified in [Section 5.6 of \[RFC3339\]](#), see also [Section 3 of \[RFC6991\]](#)). The UTC Time Zone is required by [Section 6.1 of \[RFC2330\]](#). When T0 is "all-zeros", a start time is unspecified and Tf is to be interpreted as the Duration of the measurement interval. The start time is controlled through other means.

Tf a time, the end of a measurement interval, (format "date-and-time" as specified in [Section 5.6 of \[RFC3339\]](#), see also [Section 3 of \[RFC6991\]](#)). The UTC Time Zone is required by [Section 6.1 of \[RFC2330\]](#). When T0 is "all-zeros", a end time date is ignored and Tf is interpreted as the Duration of the measurement interval.

4.3.6. Roles

<lists the names of the different roles from the measurement method>

Src launches each packet and waits for return transmissions from Dst.

Dst waits for each packet from Src and sends a return packet to Src.

[4.4.](#) Output

This category specifies all details of the Output of measurements using the metric.

[4.4.1.](#) Type

<insert name of the output type, raw or a selected summary statistic>

Percentile -- for the conditional distribution of all packets with a valid value of Round-trip delay (undefined delays are excluded), a single value corresponding to the 95th percentile, as follows:

See [section 4.1 of \[RFC3393\]](#) for details on the conditional distribution to exclude undefined values of delay, and [Section 5 of \[RFC6703\]](#) for background on this analysis choice.

The percentile = 95, meaning that the reported delay, "95Percentile", is the smallest value of Round-trip delay for which the Empirical Distribution Function (EDF), $F(95\text{Percentile}) \geq 95\%$ of the singleton Round-trip delay values in the conditional distribution. See [section 11.3 of \[RFC2330\]](#) for the definition of the percentile statistic using the EDF.

LossRatio -- the count of lost packets to total packets sent is the basis for the loss ratio calculation as per [Section 6.1 of \[RFC6673\]](#).

[4.4.2.](#) Reference Definition

<describe the reference data format for each type of result>

For all outputs ---

T0 the start of a measurement interval, (format "date-and-time" as specified in [Section 5.6 of \[RFC3339\]](#), see also [Section 3 of \[RFC6991\]](#)). The UTC Time Zone is required by [Section 6.1 of \[RFC2330\]](#).

Tf the end of a measurement interval, (format "date-and-time" as specified in [Section 5.6 of \[RFC3339\]](#), see also [Section 3 of \[RFC6991\]](#)). The UTC Time Zone is required by [Section 6.1 of \[RFC2330\]](#).

TotalPkts the count of packets sent by the Src to Dst during the measurement interval.

For

Internet-Draft

Initial Registry

October 2017

RTDelay_Active_IP-UDP-Periodic_RFCXXXsecY_Seconds_95Percentile:

95Percentile The time value of the result is expressed in units of seconds, as a positive value of type decimal64 with fraction digits = 9 (see [section 9.3 of \[RFC6020\]](#)) with resolution of 0.000000001 seconds (1.0 ns), and with lossless conversion to/from the 64-bit NTP timestamp as

For

RTLoss_Active_IP-UDP-Periodic_RFCXXXsecY_Percent_LossRatio:

Percentile The numeric value of the result is expressed in units of lost packets to total packets times 100%, as a positive value of type decimal64 with fraction digits = 9 (see [section 9.3 of \[RFC6020\]](#)) with resolution of 0.0000000001.

[4.4.3.](#) Metric Units

<insert units for the measured results, and the reference specification>.

The 95th Percentile of Round-trip Delay is expressed in seconds.

The Round-trip Loss Ratio is expressed as a percentage of lost packets to total packets sent.

[4.4.4.](#) Calibration

[Section 3.7.3 of \[RFC7679\]](#) provides a means to quantify the systematic and random errors of a time measurement. In-situ calibration could be enabled with an internal loopback at the Source host that includes as much of the measurement system as possible, performs address manipulation as needed, and provides some form of isolation (e.g., deterministic delay) to avoid send-receive interface contention. Some portion of the random and systematic error can be characterized this way.

When a measurement controller requests a calibration measurement, the loopback is applied and the result is output in the same format as a

normal measurement with additional indication that it is a calibration result.

Both internal loopback calibration and clock synchronization can be used to estimate the *available accuracy* of the Output Metric Units. For example, repeated loopback delay measurements will reveal the portion of the Output result resolution which is the result of system noise, and thus inaccurate.

Morton, et al.

Expires May 2, 2018

[Page 17]

Internet-Draft

Initial Registry

October 2017

[4.5.](#) Administrative items

[4.5.1.](#) Status

<current or deprecated>

[4.5.2.](#) Requestor (keep?)

name or RFC, etc.

[4.5.3.](#) Revision

1.0

[4.5.4.](#) Revision Date

YYYY-MM-DD

[4.6.](#) Comments and Remarks

Additional (Informational) details for this entry

[5.](#) Packet Delay Variation Registry Entry

This section gives an initial registry entry for a Packet Delay Variation metric.

Note: If each Registry entry should only produce a "raw" output or a statistical summary, then the "Output" Category can be split and this section can become two closely-related metrics.

[5.1.](#) Summary

This category includes multiple indexes to the registry entries, the element ID and metric name.

<skipping some Summary columns for now>

[5.1.1.](#) ID (Identifier)

<insert numeric identifier, an integer>

[5.1.2.](#) Name

<insert name according to metric naming convention>

OWPDV_Active_IP-UDP-Periodic_RFCXXXsecY_Seconds_95Percentile

Morton, et al.

Expires May 2, 2018

[Page 18]

Internet-Draft

Initial Registry

October 2017

[5.1.3.](#) URIs

URI: Prefix urn:ietf:metrics:perf:<name>

URL: http://<TBD by IANA>/<name>

[5.1.4.](#) Description

An assessment of packet delay variation with respect to the minimum delay observed on the periodic stream, and the Output is expressed as the 95th percentile of the packet delay variation distribution.

[5.1.5.](#) Change Controller

<org or person >

IETF

[5.1.6.](#) Version (of Registry Format)

1.0

[5.2.](#) Metric Definition

This category includes columns to prompt the entry of all necessary details related to the metric definition, including the RFC reference

and values of input factors, called fixed parameters.

5.2.1. Reference Definition

<Full bibliographic reference to an immutable doc.>

Paxson, V., Almes, G., Mahdavi, J., and M. Mathis, "Framework for IP Performance Metrics", [RFC 2330](#), May 1998. [[RFC2330](#)]

Demichelis, C. and P. Chimento, "IP Packet Delay Variation Metric for IP Performance Metrics (IPPM)", [RFC 3393](#), November 2002. [[RFC3393](#)]

Morton, A. and B. Claise, "Packet Delay Variation Applicability Statement", [RFC 5481](#), March 2009. [[RFC5481](#)]

Mills, D., Martin, J., Burbank, J., and W. Kasch, "Network Time Protocol Version 4: Protocol and Algorithms Specification", [RFC 5905](#), June 2010. [[RFC5905](#)]

<specific section reference and additional clarifications, if needed>

Morton, et al.

Expires May 2, 2018

[Page 19]

Internet-Draft

Initial Registry

October 2017

See sections [2.4](#) and [3.4](#) of [[RFC3393](#)]. Singleton delay differences measured are referred to by the variable name "ddT" (applicable to all forms of delay variation). However, this metric entry specifies the PDV form defined in [section 4.2 of \[\[RFC5481\]\(#\)\]](#), where the singleton PDV for packet *i* is referred to by the variable name "PDV(*i*)".

5.2.2. Fixed Parameters

<list and specify Fixed Parameters, input factors that must be determined and embedded in the measurement system for use when needed>

o IPv4 header values:

- * DSCP: set to 0
- * TTL: set to 255
- * Protocol: Set to 17 (UDP)

- o IPv6 header values:
 - * DSCP: set to 0
 - * Hop Count: set to 255
 - * Protocol: Set to 17 (UDP)
- o UDP header values:
 - * Checksum: the checksum MUST be calculated and included in the header
- o UDP Payload
 - * total of 200 bytes

Other measurement parameters:

Tmax: a loss threshold waiting time with value 3.0, expressed in units of seconds, as a positive value of type decimal64 with fraction digits = 4 (see [section 9.3 of \[RFC6020\]](#)) and with resolution of 0.0001 seconds (0.1 ms), with lossless conversion to/from the 32-bit NTP timestamp as per [section 6 of \[RFC5905\]](#).

F a selection function unambiguously defining the packets from the stream selected for the metric. See [section 4.2 of \[RFC5481\]](#) for the PDV form.

See the Packet Stream generation category for two additional Fixed Parameters.

[5.3](#). Method of Measurement

This category includes columns for references to relevant sections of the RFC(s) and any supplemental information needed to ensure an unambiguous methods for implementations.

[5.3.1](#). Reference Method

<for metric, insert relevant section references and supplemental

info>

See [section 2.6](#) and 3.6 of [\[RFC3393\]](#) for general singleton element calculations. This metric entry requires implementation of the PDV form defined in [section 4.2 of \[RFC5481\]](#). Also see measurement considerations in [section 8 of \[RFC5481\]](#).

The reference method distinguishes between long-delayed packets and lost packets by implementing a maximum waiting time for packet arrival. Tmax is the waiting time used as the threshold to declare a packet lost. Lost packets SHALL be designated as having undefined delay.

The calculations on the one-way delay SHALL be performed on the conditional distribution, conditioned on successful packet arrival within Tmax. Also, when all packet delays are stored, the process which calculates the one-way delay value MAY enforce the Tmax threshold on stored values before calculations. See [section 4.1 of \[RFC3393\]](#) for details on the conditional distribution to exclude undefined values of delay, and [Section 5 of \[RFC6703\]](#) for background on this analysis choice.

The reference method requires some way to distinguish between different packets in a stream to establish correspondence between sending times and receiving times for each successfully-arriving packet. Sequence numbers or other send-order identification MUST be retained at the Src or included with each packet to disambiguate packet reordering if it occurs.

If a standard measurement protocol is employed, then the measurement process will determine the sequence numbers or timestamps applied to test packets after the Fixed and Runtime parameters are passed to that process. The chosen measurement protocol will dictate the format of sequence numbers and time-stamps, if they are conveyed in the packet payload.

[5.3.2.](#) Packet Stream Generation

<list of generation parameters and section/spec references if needed>

This section gives the details of the packet traffic which is the

basis for measurement. In IPPM metrics, this is called the Stream, and can easily be described by providing the list of stream parameters.

[Section 3 of \[RFC3432\]](#) prescribes the method for generating Periodic streams using associated parameters.

incT the nominal duration of inter-packet interval, first bit to first bit, with value 0.0200, expressed in units of seconds, as a positive value of type decimal64 with fraction digits = 4 (see [section 9.3 of \[RFC6020\]](#)) and with resolution of 0.0001 seconds (0.1 ms).

dT the duration of the interval for allowed sample start times, with value 1.0, expressed in units of seconds, as a positive value of type decimal64 with fraction digits = 4 (see [section 9.3 of \[RFC6020\]](#)) and with resolution of 0.0001 seconds (0.1 ms).

T0 the actual start time of the periodic stream, (format "date-and-time" as specified in [Section 5.6 of \[RFC3339\]](#), see also [Section 3 of \[RFC6991\]](#)).

NOTE: an initiation process with a number of control exchanges resulting in unpredictable start times (within a time interval) may be sufficient to avoid synchronization of periodic streams, and therefore a valid replacement for selecting a start time at random from a fixed interval.

The T0 parameter will be reported as a measured parameter. Parameters incT and dT are Fixed Parameters.

[5.3.3](#). Traffic Filtering (observation) Details

<insert the measured results based on a filtered version of the packets observed, and this section provides the filter details (when present), and section reference>.

NA

[5.3.4.](#) Sampling Distribution

<insert time distribution details, or how this is diff from the filter>

NA

[5.3.5.](#) Run-time Parameters and Data Format

<list of run-time parameters, and their data formats>

Src the IP address of the host in the Src Role (format ipv4-address-no-zone value for IPv4, or ipv6-address-no-zone value for IPv6, see [Section 4 of \[RFC6991\]](#))

Dst the IP address of the host in the Dst Role (format ipv4-address-no-zone value for IPv4, or ipv6-address-no-zone value for IPv6, see [section 4 of \[RFC6991\]](#))

T0 a time, the start of a measurement interval, (format "date-and-time" as specified in [Section 5.6 of \[RFC3339\]](#), see also [Section 3 of \[RFC6991\]](#)). The UTC Time Zone is required by [Section 6.1 of \[RFC2330\]](#). When T0 is "all-zeros", a start time is unspecified and Tf is to be interpreted as the Duration of the measurement interval. The start time is controlled through other means.

Tf a time, the end of a measurement interval, (format "date-and-time" as specified in [Section 5.6 of \[RFC3339\]](#), see also [Section 3 of \[RFC6991\]](#)). The UTC Time Zone is required by [Section 6.1 of \[RFC2330\]](#). When T0 is "all-zeros", a end time date is ignored and Tf is interpreted as the Duration of the measurement interval.

[5.3.6.](#) Roles

<lists the names of the different roles from the measurement method>

Src launches each packet to Dst.

Dst waits for each packet from Src.

[5.4.](#) Output

This category specifies all details of the Output of measurements using the metric.

Internet-Draft

Initial Registry

October 2017

[5.4.1.](#) Type

<insert name of the output type, raw or a selected summary statistic>

Percentile -- for the conditional distribution of all packets with a valid value of one-way delay (undefined delays are excluded), a single value corresponding to the 95th percentile, as follows:

See [section 4.1 of \[RFC3393\]](#) for details on the conditional distribution to exclude undefined values of delay, and [Section 5 of \[RFC6703\]](#) for background on this analysis choice.

The percentile = 95, meaning that the reported delay, "95Percentile", is the smallest value of one-way PDV for which the Empirical Distribution Function (EDF), $F(95\text{Percentile}) \geq 95\%$ of the singleton one-way PDV values in the conditional distribution. See [section 11.3 of \[RFC2330\]](#) for the definition of the percentile statistic using the EDF.

[5.4.2.](#) Reference Definition

<the output type and data format for each type of result>

T0 the start of a measurement interval, (format "date-and-time" as specified in [Section 5.6 of \[RFC3339\]](#), see also [Section 3 of \[RFC6991\]](#)). The UTC Time Zone is required by [Section 6.1 of \[RFC2330\]](#).

Tf the end of a measurement interval, (format "date-and-time" as specified in [Section 5.6 of \[RFC3339\]](#), see also [Section 3 of \[RFC6991\]](#)). The UTC Time Zone is required by [Section 6.1 of \[RFC2330\]](#).

95Percentile The time value of the result is expressed in units of seconds, as a positive value of type decimal64 with fraction digits = 9 (see [section 9.3 of \[RFC6020\]](#)) with resolution of 0.000000001 seconds (1.0 ns), and with lossless conversion to/from the 64-bit NTP timestamp as per [section 6](#) of RFC [\[RFC5905\]](#)

[5.4.3.](#) Metric Units

<insert units for the measured results, and the reference

specification>.

The 95th Percentile of one-way PDV is expressed in seconds.

[5.4.4.](#) Calibration

[Section 3.7.3 of \[RFC7679\]](#) provides a means to quantify the systematic and random errors of a time measurement. In-situ calibration could be enabled with an internal loopback that includes as much of the measurement system as possible, performs address manipulation as needed, and provides some form of isolation (e.g., deterministic delay) to avoid send-receive interface contention. Some portion of the random and systematic error can be characterized this way.

For one-way delay measurements, the error calibration must include an assessment of the internal clock synchronization with its external reference (this internal clock is supplying timestamps for measurement). In practice, the time offsets of clocks at both the source and destination are needed to estimate the systematic error due to imperfect clock synchronization (the time offsets are smoothed, thus the random variation is not usually represented in the results).

`time_offset` The time value of the result is expressed in units of seconds, as a signed value of type `decimal64` with fraction digits = 9 (see [section 9.3 of \[RFC6020\]](#)) with resolution of 0.000000001 seconds (1.0 ns), and with lossless conversion to/from the 64-bit NTP timestamp as per [section 6](#) of RFC [\[RFC5905\]](#)

When a measurement controller requests a calibration measurement, the loopback is applied and the result is output in the same format as a normal measurement with additional indication that it is a calibration result. In any measurement, the measurement function SHOULD report its current estimate of time offset as an indicator of the degree of synchronization.

Both internal loopback calibration and clock synchronization can be used to estimate the *available accuracy* of the Output Metric Units.

For example, repeated loopback delay measurements will reveal the portion of the Output result resolution which is the result of system noise, and thus inaccurate.

[5.5.](#) Administrative items

[5.5.1.](#) Status

<current or deprecated>

Morton, et al.

Expires May 2, 2018

[Page 25]

Internet-Draft

Initial Registry

October 2017

[5.5.2.](#) Requestor (keep?)

<name of individual or RFC, etc.>

[5.5.3.](#) Revision

1.0

[5.5.4.](#) Revision Date

YYYY-MM-DD

[5.6.](#) Comments and Remarks

<Additional (Informational) details for this entry>

Lost packets represent a challenge for delay variation metrics. See [section 4.1 of \[RFC3393\]](#) and the delay variation applicability statement[RFC5481] for extensive analysis and comparison of PDV and an alternate metric, IPDV.

[6.](#) DNS Response Latency and Loss Registry Entries

This section gives initial registry entries for DNS Response Latency and Loss. [RFC 2681](#) [RFC2681] defines a Round-trip delay metric. We build on that metric by specifying several of the input parameters to precisely define two metrics for measuring DNS latency and loss.

Note to IANA: Each Registry "Name" below specifies a single registry entry, whose output format varies in accordance with the name.

All column entries beside the ID, Name, Description, and Output Reference Method categories are the same, thus this section proposes two closely-related registry entries. As a result, IANA is also asked to assign corresponding URNs and URLs to each Named Metric.

[6.1.](#) Summary

This category includes multiple indexes to the registry entries, the element ID and metric name.

<skipping some admin columns for now>

[6.1.1.](#) ID (Identifier)

<insert numeric identifier, an integer>

Morton, et al.

Expires May 2, 2018

[Page 26]

Internet-Draft

Initial Registry

October 2017

IANA is asked to assign different numeric identifiers to each of the two Named Metrics.

[6.1.2.](#) Name

<insert name according to metric naming convention>

RTDNS_Active_IP-UDP-Poisson_RFCXXXXsecY_Seconds_Raw

RLDNS_Active_IP-UDP-Poisson_RFCXXXXsecY_Logical_Raw

[6.1.3.](#) URI

URI: Prefix urn:ietf:metrics:perf:<name>

URL: http://<TBD by IANA>/<name>

[6.1.4.](#) Description

RTDNS: This metric assesses the response time, the interval from the query transmission to the response.

RLDNS: This metric indicates that the response was deemed lost. In other words, the response time exceeded the maximum waiting time.

[6.1.5.](#) Change Controller

IETF

[6.1.6.](#) Version (of Registry Format)

1.0

[6.2.](#) Metric Definition

This category includes columns to prompt the entry of all necessary details related to the metric definition, including the RFC reference and values of input factors, called fixed parameters.

[6.2.1.](#) Reference Definition

<Full bibliographic reference to an immutable doc.>

Mockapetris, P., "Domain names - implementation and specification", STD 13, [RFC 1035](#), November 1987. (and updates)

[RFC1035]

Morton, et al.

Expires May 2, 2018

[Page 27]

Internet-Draft

Initial Registry

October 2017

Almes, G., Kalidindi, S., and M. Zekauskas, "A Round-trip Delay Metric for IPPM", [RFC 2681](#), September 1999.

[RFC2681]

<specific section reference and additional clarifications, if needed>

[Section 2.4 of \[RFC2681\]](#) provides the reference definition of the singleton (single value) Round-trip delay metric. [Section 3.4 of \[RFC2681\]](#) provides the reference definition expanded to cover a multi-singleton sample. Note that terms such as singleton and sample are defined in [Section 11 of \[RFC2330\]](#).

For DNS Response Latency, the entities in [\[RFC1035\]](#) must be mapped to

[RFC2681]. The Local Host with its User Program and Resolver take the role of "Src", and the Foreign Name Server takes the role of "Dst".

Note that although the [RFC2681] definition of "Round-trip-Delay between Src and Dst at T" is directionally ambiguous in the text, this metric tightens the definition further to recognize that the host in the "Src" role will send the first packet to "Dst", and ultimately receive the corresponding return packet from "Dst" (when neither are lost).

Morton, A., "Round-trip Packet Loss Metrics", RFC 6673, August 2012.

[RFC6673]

Both response time and loss metrics employ a maximum waiting time for received responses, so the count of lost packets to total packets sent is the basis for the loss determination as per [Section 4.3 of \[RFC6673\]](#).

[6.2.2.](#) Fixed Parameters

<list and specify Fixed Parameters, input factors that must be determined and embedded in the measurement system for use when needed>

Type-P as defined in [Section 13 of \[RFC2330\]](#):

- o IPv4 header values:
 - * DSCP: set to 0
 - * TTL set to 255

- * Protocol: Set to 17 (UDP)
- o IPv6 header values:
 - * DSCP: set to 0
 - * Hop Count: set to 255

- * Protocol: Set to 17 (UDP)
- o UDP header values:
 - * Source port: 53
 - * Destination port: 53
 - * Checksum: the checksum must be calculated and included in the header
- o Payload: The payload contains a DNS message as defined in [RFC 1035](#) [[RFC1035](#)] with the following values:
 - * The DNS header section contains:
 - + Identification (see the Run-time column)
 - + QR: set to 0 (Query)
 - + OPCODE: set to 0 (standard query)
 - + AA: not set
 - + TC: not set
 - + RD: set to one (recursion desired)
 - + RA: not set
 - + RCODE: not set
 - + QDCOUNT: set to one (only one entry)
 - + ANCOUNT: not set
 - + NSCOUNT: not set
 - + ARCOUNT: not set

- * The Question section contains:
 - + QNAME: the Fully Qualified Domain Name (FQDN) provided as input for the test, see the Run-time column
 - + QTYPE: the query type provided as input for the test, see the Run-time column
 - + QCLASS: set to 1 for IN
- * The other sections do not contain any Resource Records.

Other measurement parameters:

- o Tmax: a loss threshold waiting time (and to help disambiguate queries)
 - * 5.0, expressed in units of seconds, as a positive value of type decimal64 with fraction digits = 4 (see [section 9.3 of \[RFC6020\]](#)) and with resolution of 0.0001 seconds (0.1 ms), with lossless conversion to/from the 32-bit NTP timestamp as per [section 6 of \[RFC5905\]](#).

Observation: reply packets will contain a DNS response and may contain RRs.

[6.3.](#) Method of Measurement

This category includes columns for references to relevant sections of the RFC(s) and any supplemental information needed to ensure unambiguous methods for implementations.

[6.3.1.](#) Reference Method

<for metric, insert relevant section references and supplemental info>

The methodology for this metric is defined as Type-P-Round-trip-Delay-Poisson-Stream in [section 2.6 of RFC 2681 \[RFC2681\]](#) and [section 3.6 of RFC 2681 \[RFC2681\]](#) using the Type-P and Timeout defined under Fixed Parameters.

The reference method distinguishes between long-delayed packets and lost packets by implementing a maximum waiting time for packet arrival. Tmax is the waiting time used as the threshold to declare a packet lost. Lost packets SHALL be designated as having undefined delay, and counted for the RLDNS metric.

Internet-Draft

Initial Registry

October 2017

The calculations on the delay (RTT) SHALL be performed on the conditional distribution, conditioned on successful packet arrival within T_{max} . Also, when all packet delays are stored, the process which calculates the RTT value MAY enforce the T_{max} threshold on stored values before calculations. See [section 4.1 of \[RFC3393\]](#) for details on the conditional distribution to exclude undefined values of delay, and [Section 5 of \[RFC6703\]](#) for background on this analysis choice.

The reference method requires some way to distinguish between different packets in a stream to establish correspondence between sending times and receiving times for each successfully-arriving reply. Therefore, sequence numbers or other send-order identification MUST be retained at the Src or included with each packet to disambiguate packet reordering if it occurs. Sequence number is part of the payload described under Fixed Parameters.

DNS Messages bearing Queries provide for random ID Numbers in the Identification header field, so more than one query may be launched while a previous request is outstanding when the ID Number is used.

IF a DNS response does not arrive within T_{max} , the response time is undefined, and $RTD_{NS} = 1$. The Message ID SHALL be used to disambiguate the successive queries.

@@@ This would require support of ID generation and population in the Message. An alternative would be to use a random Source port on the Query Message, but we would choose ONE before proceeding.

Refer to [Section 4.4 of \[RFC6673\]](#) for expanded discussion of the instruction to "send a Type-P packet back to the Src as quickly as possible" in [Section 2.6 of RFC 2681 \[RFC2681\]](#). [Section 8 of \[RFC6673\]](#) presents additional requirements which shall be included in the method of measurement for this metric.

In addition to operations described in [\[RFC2681\]](#), the Src MUST parse the DNS headers of the reply and prepare the information for subsequent reporting as a measured result, along with the Round-Trip Delay.

[6.3.2](#). Packet Stream Generation

This section gives the details of the packet traffic which is the

basis for measurement. In IPPM metrics, this is called the Stream, and can easily be described by providing the list of stream parameters.

<list of generation parameters and section/spec references if needed>

Morton, et al.

Expires May 2, 2018

[Page 31]

Internet-Draft

Initial Registry

October 2017

[Section 11.1.3 of RFC 2681](#) [[RFC2330](#)] provides three methods to generate Poisson sampling intervals. The reciprocal of lambda is the average packet rate, thus the Run-time Parameter is `Reciprocal_lambda = 1/lambda`, in seconds.

Method 3 is used, where given a start time (Run-time Parameter), the subsequent send times are all computed prior to measurement by computing the pseudo-random distribution of inter-packet send times, (truncating the distribution as specified in the Run-time Parameters), and the Src sends each packet at the computed times.

Note that Trunc is the upper limit on inter-packet times in the Poisson distribution. A random value greater than Trunc is set equal to Trunc instead.

[6.3.3. Traffic Filtering \(observation\) Details](#)

The measured results based on a filtered version of the packets observed, and this section provides the filter details (when present).

<section reference>.

NA

[6.3.4. Sampling Distribution](#)

<insert time distribution details, or how this is diff from the filter>

NA

[6.3.5. Run-time Parameters and Data Format](#)

Run-time Parameters are input factors that must be determined, configured into the measurement system, and reported with the results

for the context to be complete.

<list of run-time parameters, and their data formats>

Src the IP address of the host in the Src Role (format ipv4-address-no-zone value for IPv4, or ipv6-address-no-zone value for IPv6, see [Section 4 of \[RFC6991\]](#))

Dst the IP address of the host in the Dst Role (format ipv4-address-no-zone value for IPv4, or ipv6-address-no-zone value for IPv6, see [section 4 of \[RFC6991\]](#))

T0 a time, the start of a measurement interval, (format "date-and-time" as specified in [Section 5.6 of \[RFC3339\]](#), see also [Section 3 of \[RFC6991\]](#)). The UTC Time Zone is required by [Section 6.1 of \[RFC2330\]](#). When T0 is "all-zeros", a start time is unspecified and Tf is to be interpreted as the Duration of the measurement interval. The start time is controlled through other means.

Tf a time, the end of a measurement interval, (format "date-and-time" as specified in [Section 5.6 of \[RFC3339\]](#), see also [Section 3 of \[RFC6991\]](#)). The UTC Time Zone is required by [Section 6.1 of \[RFC2330\]](#). When T0 is "all-zeros", a end time date is ignored and Tf is interpreted as the Duration of the measurement interval.

Reciprocal_lambda average packet interval for Poisson Streams expressed in units of seconds, as a positive value of type decimal64 with fraction digits = 4 (see [section 9.3 of \[RFC6020\]](#)) with resolution of 0.0001 seconds (0.1 ms), and with lossless conversion to/from the 32-bit NTP timestamp as per [section 6 of \[RFC5905\]](#).

Trunc Upper limit on Poisson distribution expressed in units of seconds, as a positive value of type decimal64 with fraction digits = 4 (see [section 9.3 of \[RFC6020\]](#)) with resolution of 0.0001 seconds (0.1 ms), and with lossless conversion to/from the 32-bit NTP timestamp as per [section 6 of \[RFC5905\]](#) (values above this limit will be clipped and set to the limit value). (if fixed, Trunc = 30.0000 seconds.)

ID The 16-bit identifier assigned by the program that generates the

query, and which must vary in successive queries, see [Section 4.1.1 of \[RFC1035\]](#). This identifier is copied into the corresponding reply and can be used by the requester (Src) to match-up replies to outstanding queries.

QNAME The domain name of the Query, formatted as specified in [section 4 of \[RFC6991\]](#).

QTYPE The Query Type, which will correspond to the IP address family of the query (decimal 1 for IPv4 or 28 for IPv6, formatted as a uint16, as per [section 9.2 of \[RFC6020\]](#)).

[6.3.6.](#) Roles

<lists the names of the different roles from the measurement method>

Src launches each packet and waits for return transmissions from Dst.

Morton, et al.

Expires May 2, 2018

[Page 33]

Internet-Draft

Initial Registry

October 2017

Dst waits for each packet from Src and sends a return packet to Src.

[6.4.](#) Output

This category specifies all details of the Output of measurements using the metric.

[6.4.1.](#) Type

<insert name of the output type, raw or a selected summary statistic>

Raw -- for each DNS Query packet sent, sets of values as defined in the next column, including the status of the response, only assigning delay values to successful query-response pairs.

[6.4.2.](#) Reference Definition

<describe the data format for each type of result>

For all outputs:

T the time the DNS Query was sent during the measurement interval,

(format "date-and-time" as specified in [Section 5.6 of \[RFC3339\]](#), see also [Section 3 of \[RFC6991\]](#)). The UTC Time Zone is required by [Section 6.1 of \[RFC2330\]](#).

dT The time value of the round-trip delay to receive the DNS response, expressed in units of seconds, as a positive value of type decimal64 with fraction digits = 9 (see [section 9.3 of \[RFC6020\]](#)) with resolution of 0.000000001 seconds (1.0 ns), and with lossless conversion to/from the 64-bit NTP timestamp as per [section 6](#) of RFC [\[RFC5905\]](#). This value is undefined when the response packet is not received at Src within waiting time Tmax seconds.

Rcode The value of the Rcode field in the DNS response header, expressed as a uint64 as specified in [section 9.2 of \[RFC6020\]](#). Non-zero values convey errors in the response, and such replies must be analyzed separately from successful requests.

[6.4.3. Metric Units](#)

<insert units for the measured results, and the reference specification>.

RTDNS: Round-trip Delay, dT, is expressed in seconds.

RTLDNS: the Logical value, where 1 = Lost and 0 = Received.

[6.4.4. Calibration](#)

[Section 3.7.3 of \[RFC7679\]](#) provides a means to quantify the systematic and random errors of a time measurement. In-situ calibration could be enabled with an internal loopback at the Source host that includes as much of the measurement system as possible, performs address and payload manipulation as needed, and provides some form of isolation (e.g., deterministic delay) to avoid send-receive interface contention. Some portion of the random and systematic error can be characterized this way.

When a measurement controller requests a calibration measurement, the loopback is applied and the result is output in the same format as a normal measurement with additional indication that it is a calibration result.

Both internal loopback calibration and clock synchronization can be used to estimate the *available accuracy* of the Output Metric Units. For example, repeated loopback delay measurements will reveal the portion of the Output result resolution which is the result of system noise, and thus inaccurate.

[6.5.](#) Administrative items

[6.5.1.](#) Status

<current or deprecated>

[6.5.2.](#) Requestor

name or RFC, etc.

[6.5.3.](#) Revision

1.0

[6.5.4.](#) Revision Date

YYYY-MM-DD

[6.6.](#) Comments and Remarks

Additional (Informational) details for this entry

Morton, et al.

Expires May 2, 2018

[Page 35]

Internet-Draft

Initial Registry

October 2017

[7.](#) UDP Poisson One-way Delay and Loss Registry Entries

This section specifies five initial registry entries for the UDP Poisson One-way Delay, and one for UDP Poisson One-way Loss.

IANA Note: Registry "Name" below specifies a single registry entry, whose output format varies according to the <statistic> element of the name that specifies one form of statistical summary. There is an

additional metric name for the Loss metric.

All column entries beside the ID, Name, Description, and Output Reference Method categories are the same, thus this section proposes six closely-related registry entries. As a result, IANA is also asked to assign corresponding URNs and URLs to each Named Metric.

[7.1.](#) Summary

This category includes multiple indexes to the registry entries, the element ID and metric name.

[7.1.1.](#) ID (Identifier)

<insert numeric identifier, an integer, one corresponding to each name below>

IANA is asked to assign different numeric identifiers to each of the six Metrics.

[7.1.2.](#) Name

<insert name according to metric naming convention>

OWDelay_Active_IP-UDP-Poisson-
Payload250B_RFCXXXXsecY_Seconds_<statistic>

where <statistic> is one of:

- o 95Percentile
- o Mean
- o Min
- o Max
- o StdDev

Payload250B_RFCXXXXsecY_Percent_LossRatio

[7.1.3.](#) URI and URL

URI: Prefix urn:ietf:metrics:perf:<name>

URL: http:\\www.iana.org\ ... <name>

[7.1.4.](#) Description

OWDelay: This metric assesses the delay of a stream of packets exchanged between two hosts (or measurement points), and reports the <statistic> One-way delay for all successfully exchanged packets based on their conditional delay distribution.

where <statistic> is one of:

- o 95Percentile
- o Mean
- o Min
- o Max
- o StdDev

OWLoss: This metric assesses the loss ratio of a stream of packets exchanged between two hosts (which are the two measurement points), and the Output is the One-way loss ratio for all successfully received packets expressed as a percentage.

[7.2.](#) Metric Definition

This category includes columns to prompt the entry of all necessary details related to the metric definition, including the RFC reference and values of input factors, called fixed parameters.

[7.2.1.](#) Reference Definition

<Full bibliographic reference to an immutable doc.>

For Delay:

Almes, G., Kalidindi, S., Zekauskas, M., and A. Morton, Ed., "A One-Way Delay Metric for IP Performance Metrics (IPPM)", STD 81, RFC

7679, DOI 10.17487/RFC7679, January 2016, <<http://www.rfc-editor.org/info/rfc7679>>.

[RFC7679]

Morton, A., and Stephan, E., "Spatial Composition of Metrics", [RFC 6049](#), January 2011.

[RFC6049]

<specific section reference and additional clarifications, if needed>

[Section 3.4 of \[RFC7679\]](#) provides the reference definition of the singleton (single value) One-way delay metric. [Section 4.4 of \[RFC7679\]](#) provides the reference definition expanded to cover a multi-value sample. Note that terms such as singleton and sample are defined in [Section 11 of \[RFC2330\]](#).

Only successful packet transfers with finite delay are included in the sample, as prescribed in [section 4.1.2 of \[RFC6049\]](#).

For loss:

Almes, G., Kalidini, S., Zekauskas, M., and A. Morton, Ed., "A One-Way Loss Metric for IP Performance Metrics (IPPM)", [RFC 7680](#), DOI 10.17487/RFC7680, January 2016, <<http://www.rfc-editor.org/info/rfc7680>>.

[Section 2.4 of \[RFC7680\]](#) provides the reference definition of the singleton (single value) one-way loss metric. [Section 3.4 of \[RFC7680\]](#) provides the reference definition expanded to cover a multi-singleton sample. Note that terms such as singleton and sample are defined in [Section 11 of \[RFC2330\]](#).

[7.2.2. Fixed Parameters](#)

<list and specify Fixed Parameters, input factors that must be determined and embedded in the measurement system for use when needed>

Type-P:

- o IPv4 header values:

- * DSCP: set to 0

- * TTL: set to 255

- * Protocol: Set to 17 (UDP)
- o IPv6 header values:
 - * DSCP: set to 0
 - * Hop Count: set to 255
 - * Protocol: Set to 17 (UDP)
- o UDP header values:
 - * Checksum: the checksum MUST be calculated and included in the header
- o UDP Payload: TWAMP Test Packet Formats, [Section 4.1.2 of \[RFC5357\]](#)
 - * Security features in use influence the number of Padding octets.
 - * 250 octets total, including the TWAMP format

Other measurement parameters:

Tmax: a loss threshold waiting time with value 3.0, expressed in units of seconds, as a positive value of type decimal64 with fraction digits = 4 (see [section 9.3 of \[RFC6020\]](#)) and with resolution of 0.0001 seconds (0.1 ms), with lossless conversion to/from the 32-bit NTP timestamp as per [section 6 of \[RFC5905\]](#).

See the Packet Stream generation category for two additional Fixed Parameters.

[7.3.](#) Method of Measurement

This category includes columns for references to relevant sections of the RFC(s) and any supplemental information needed to ensure an unambiguous methods for implementations.

7.3.1. Reference Method

<for metric, insert relevant section references and supplemental info>

The methodology for this metric is defined as Type-P-One-way-Delay-Poisson-Stream in [section 3.6 of \[RFC7679\]](#) and [section 4.6 of \[RFC7679\]](#) using the Type-P and Tmax defined under Fixed Parameters.

Morton, et al.

Expires May 2, 2018

[Page 39]

Internet-Draft

Initial Registry

October 2017

The reference method distinguishes between long-delayed packets and lost packets by implementing a maximum waiting time for packet arrival. Tmax is the waiting time used as the threshold to declare a packet lost. Lost packets SHALL be designated as having undefined delay, and counted for the OWLoss metric.

The calculations on the one-way delay SHALL be performed on the conditional distribution, conditioned on successful packet arrival within Tmax. Also, when all packet delays are stored, the process which calculates the one-way delay value MAY enforce the Tmax threshold on stored values before calculations. See [section 4.1 of \[RFC3393\]](#) for details on the conditional distribution to exclude undefined values of delay, and [Section 5 of \[RFC6703\]](#) for background on this analysis choice.

The reference method requires some way to distinguish between different packets in a stream to establish correspondence between sending times and receiving times for each successfully-arriving packet. Sequence numbers or other send-order identification MUST be retained at the Src or included with each packet to disambiguate packet reordering if it occurs.

Since a standard measurement protocol is employed [\[RFC5357\]](#), then the measurement process will determine the sequence numbers or timestamps applied to test packets after the Fixed and Runtime parameters are passed to that process. The measurement protocol dictates the format of sequence numbers and time-stamps conveyed in the TWAMP-Test packet payload.

7.3.2. Packet Stream Generation

This section gives the details of the packet traffic which is the

basis for measurement. In IPPM metrics, this is called the Stream, and can easily be described by providing the list of stream parameters.

<list of generation parameters and section/spec references if needed>

[Section 11.1.3 of RFC 2681 \[RFC2330\]](#) provides three methods to generate Poisson sampling intervals. The reciprocal of lambda is the average packet spacing, thus the Run-time Parameter is $\text{Reciprocal_lambda} = 1/\text{lambda}$, in seconds.

Method 3 SHALL be used, where given a start time (Run-time Parameter), the subsequent send times are all computed prior to measurement by computing the pseudo-random distribution of inter-packet send times, (truncating the distribution as specified in the

Parameter Trunc), and the Src sends each packet at the computed times.

Note that Trunc is the upper limit on inter-packet times in the Poisson distribution. A random value greater than Trunc is set equal to Trunc instead.

`Reciprocal_lambda` average packet interval for Poisson Streams expressed in units of seconds, as a positive value of type decimal64 with fraction digits = 4 (see [section 9.3 of \[RFC6020\]](#)) with resolution of 0.0001 seconds (0.1 ms), and with lossless conversion to/from the 32-bit NTP timestamp as per [section 6 of \[RFC5905\]](#). $\text{Reciprocal_lambda} = 1$ packet per second.

`Trunc` Upper limit on Poisson distribution expressed in units of seconds, as a positive value of type decimal64 with fraction digits = 4 (see [section 9.3 of \[RFC6020\]](#)) with resolution of 0.0001 seconds (0.1 ms), and with lossless conversion to/from the 32-bit NTP timestamp as per [section 6 of \[RFC5905\]](#) (values above this limit will be clipped and set to the limit value). `Trunc = 30.0000` seconds.

[7.3.3.](#) Traffic Filtering (observation) Details

[7.3.4.](#) Sampling Distribution

NA

[7.3.5.](#) Run-time Parameters and Data Format

Run-time Parameters are input factors that must be determined, configured into the measurement system, and reported with the results for the context to be complete.

<list of run-time parameters, and their data formats>

Src the IP address of the host in the Src Role (format ipv4-address-no-zone value for IPv4, or ipv6-address-no-zone value for IPv6, see [Section 4 of \[RFC6991\]](#))

Dst the IP address of the host in the Dst Role (format ipv4-address-no-zone value for IPv4, or ipv6-address-no-zone value for IPv6, see [section 4 of \[RFC6991\]](#))

T0 a time, the start of a measurement interval, (format "date-and-time" as specified in [Section 5.6 of \[RFC3339\]](#), see also [Section 3](#)

of [\[RFC6991\]](#)). The UTC Time Zone is required by [Section 6.1 of \[RFC2330\]](#). When T0 is "all-zeros", a start time is unspecified and Tf is to be interpreted as the Duration of the measurement interval. The starttime is controlled through other means.

Tf a time, the end of a measurement interval, (format "date-and-time" as specified in [Section 5.6 of \[RFC3339\]](#), see also [Section 3 of \[RFC6991\]](#)). The UTC Time Zone is required by [Section 6.1 of \[RFC2330\]](#). When T0 is "all-zeros", a end time date is ignored and Tf is interpreted as the Duration of the measurement interval.

[7.3.6.](#) Roles

<lists the names of the different roles from the measurement method>

Src launches each packet and waits for return transmissions from Dst. This is the TWAMP Session-Sender.

Dst waits for each packet from Src and sends a return packet to Src.
This is the TWAMP Session-Reflector.

[7.4.](#) Output

This category specifies all details of the Output of measurements using the metric.

[7.4.1.](#) Type

<insert name of the output type, raw or a selected summary statistic>

See subsection titles below for Types.

[7.4.2.](#) Reference Definition

<describe the data format for each type of result>

For all output types ---

T0 the start of a measurement interval, (format "date-and-time" as specified in [Section 5.6 of \[RFC3339\]](#), see also [Section 3 of \[RFC6991\]](#)). The UTC Time Zone is required by [Section 6.1 of \[RFC2330\]](#).

Tf the end of a measurement interval, (format "date-and-time" as specified in [Section 5.6 of \[RFC3339\]](#), see also [Section 3 of \[RFC6991\]](#)). The UTC Time Zone is required by [Section 6.1 of \[RFC2330\]](#).

For LossRatio -- the count of lost packets to total packets sent is the basis for the loss ratio calculation as per [Section 4.1 of \[RFC7680\]](#).

For each <statistic>, one of the following sub-sections apply:

[7.4.2.1.](#) Percentile95

The 95th percentile SHALL be calculated using the conditional distribution of all packets with a finite value of One-way delay (undefined delays are excluded), a single value as follows:

See [section 4.1 of \[RFC3393\]](#) for details on the conditional distribution to exclude undefined values of delay, and [Section 5 of \[RFC6703\]](#) for background on this analysis choice.

See [section 4.3 of \[RFC3393\]](#) for details on the percentile statistic (where Round-trip delay should be substituted for "ipdv").

The percentile = 95, meaning that the reported delay, "95Percentile", is the smallest value of one-way delay for which the Empirical Distribution Function (EDF), $F(95\text{Percentile}) \geq 95\%$ of the singleton one-way delay values in the conditional distribution. See [section 11.3 of \[RFC2330\]](#) for the definition of the percentile statistic using the EDF.

95Percentile The time value of the result is expressed in units of seconds, as a positive value of type decimal64 with fraction digits = 9 (see [section 9.3 of \[RFC6020\]](#)) with resolution of 0.000000001 seconds (1.0 ns), and with lossless conversion to/from the 64-bit NTP timestamp as per [section 6](#) of RFC [\[RFC5905\]](#)

[7.4.2.2.](#) Mean

The mean SHALL be calculated using the conditional distribution of all packets with a finite value of One-way delay (undefined delays are excluded), a single value as follows:

See [section 4.1 of \[RFC3393\]](#) for details on the conditional distribution to exclude undefined values of delay, and [Section 5 of \[RFC6703\]](#) for background on this analysis choice.

See [section 4.2.2 of \[RFC6049\]](#) for details on calculating this statistic, and 4.2.3 of [\[RFC6049\]](#).

Mean The time value of the result is expressed in units of seconds, as a positive value of type decimal64 with fraction digits = 9 (see [section 9.3 of \[RFC6020\]](#)) with resolution of 0.000000001

seconds (1.0 ns), and with lossless conversion to/from the 64-bit NTP timestamp as per [section 6](#) of RFC [\[RFC5905\]](#)

[7.4.2.3.](#) Min

The minimum SHALL be calculated using the conditional distribution of all packets with a finite value of One-way delay (undefined delays are excluded), a single value as follows:

See [section 4.1 of \[RFC3393\]](#) for details on the conditional distribution to exclude undefined values of delay, and [Section 5 of \[RFC6703\]](#) for background on this analysis choice.

See [section 4.3.2 of \[RFC6049\]](#) for details on calculating this statistic, and 4.3.3 of [\[RFC6049\]](#).

Min The time value of the result is expressed in units of seconds, as a positive value of type decimal64 with fraction digits = 9 (see [section 9.3 of \[RFC6020\]](#)) with resolution of 0.000000001 seconds (1.0 ns), and with lossless conversion to/from the 64-bit NTP timestamp as per [section 6](#) of RFC [\[RFC5905\]](#)

[7.4.2.4](#). Max

The maximum SHALL be calculated using the conditional distribution of all packets with a finite value of One-way delay (undefined delays are excluded), a single value as follows:

See [section 4.1 of \[RFC3393\]](#) for details on the conditional distribution to exclude undefined values of delay, and [Section 5 of \[RFC6703\]](#) for background on this analysis choice.

See [section 4.3.2 of \[RFC6049\]](#) for a closely related method for calculating this statistic, and 4.3.3 of [\[RFC6049\]](#). The formula is as follows:

$$\text{Max} = (\text{FiniteDelay } [j])$$

such that for some index, j , where $1 \leq j \leq N$
 $\text{FiniteDelay}[j] \geq \text{FiniteDelay}[n]$ for all n

Max The time value of the result is expressed in units of seconds, as a positive value of type decimal64 with fraction digits = 9 (see [section 9.3 of \[RFC6020\]](#)) with resolution of 0.000000001 seconds (1.0 ns), and with lossless conversion to/from the 64-bit NTP timestamp as per [section 6](#) of RFC [\[RFC5905\]](#)

[7.4.2.5](#). Std_Dev

The Std_Dev SHALL be calculated using the conditional distribution of all packets with a finite value of One-way delay (undefined delays are excluded), a single value as follows:

See [section 4.1 of \[RFC3393\]](#) for details on the conditional distribution to exclude undefined values of delay, and [Section 5 of \[RFC6703\]](#) for background on this analysis choice.

See [section 4.3.2 of \[RFC6049\]](#) for a closely related method for calculating this statistic, and 4.3.3 of [\[RFC6049\]](#). The formula is the classic calculation for standard deviation of a population.

Std_Dev The time value of the result is expressed in units of seconds, as a positive value of type decimal64 with fraction digits = 9 (see [section 9.3 of \[RFC6020\]](#)) with resolution of 0.000000001 seconds (1.0 ns), and with lossless conversion to/from the 64-bit NTP timestamp as per [section 6](#) of RFC [\[RFC5905\]](#)

[7.4.3](#). Metric Units

<insert units for the measured results, and the reference specification>.

The <statistic> of One-way Delay is expressed in seconds.

The One-way Loss Ratio is expressed as a percentage of lost packets to total packets sent.

[7.4.4](#). Calibration

[Section 3.7.3 of \[RFC7679\]](#) provides a means to quantify the systematic and random errors of a time measurement. In-situ calibration could be enabled with an internal loopback that includes as much of the measurement system as possible, performs address manipulation as needed, and provides some form of isolation (e.g., deterministic delay) to avoid send-receive interface contention. Some portion of the random and systematic error can be characterized this way.

For one-way delay measurements, the error calibration must include an assessment of the internal clock synchronization with its external reference (this internal clock is supplying timestamps for measurement). In practice, the time offsets of clocks at both the source and destination are needed to estimate the systematic error due to imperfect clock synchronization (the time offsets are

Internet-Draft

Initial Registry

October 2017

smoothed, thus the random variation is not usually represented in the results).

`time_offset` The time value of the result is expressed in units of seconds, as a signed value of type `decimal64` with fraction digits = 9 (see [section 9.3 of \[RFC6020\]](#)) with resolution of 0.000000001 seconds (1.0 ns), and with lossless conversion to/from the 64-bit NTP timestamp as per [section 6](#) of RFC [\[RFC5905\]](#)

When a measurement controller requests a calibration measurement, the loopback is applied and the result is output in the same format as a normal measurement with additional indication that it is a calibration result. In any measurement, the measurement function SHOULD report its current estimate of time offset as an indicator of the degree of synchronization.

Both internal loopback calibration and clock synchronization can be used to estimate the **available accuracy** of the Output Metric Units. For example, repeated loopback delay measurements will reveal the portion of the Output result resolution which is the result of system noise, and thus inaccurate.

[7.5.](#) Administrative items

[7.5.1.](#) Status

<current or deprecated>

[7.5.2.](#) Requestor (keep?)

name or RFC, etc.

[7.5.3.](#) Revision

1.0

[7.5.4.](#) Revision Date

YYYY-MM-DD

[7.6.](#) Comments and Remarks

Additional (Informational) details for this entry

Morton, et al.

Expires May 2, 2018

[Page 46]

Internet-Draft

Initial Registry

October 2017

[8.](#) UDP Periodic One-way Delay and Loss Registry Entries

This section specifies five initial registry entries for the UDP Periodic One-way Delay, and one for UDP Periodic One-way Loss.

IANA Note: Registry "Name" below specifies a single registry entry, whose output format varies according to the <statistic> element of the name that specifies one form of statistical summary. There is an additional metric name for the Loss metric.

All column entries beside the ID, Name, Description, and Output Reference Method categories are the same, thus this section proposes six closely-related registry entries. As a result, IANA is also asked to assign corresponding URNs and URLs to each Named Metric.

[8.1.](#) Summary

This category includes multiple indexes to the registry entries, the element ID and metric name.

[8.1.1.](#) ID (Identifier)

<insert numeric identifier, an integer, one corresponding to each name below>

IANA is asked to assign a different numeric identifiers to each of the six Metrics.

[8.1.2.](#) Name

<insert name according to metric naming convention>

OWDelay_Active_IP-UDP-Periodic-

Payload142B_RFCXXXXsecY_Seconds_<statistic>

where <statistic> is one of:

- o 95Percentile
- o Mean
- o Min
- o Max
- o StdDev

OWLoss_Active_IP-UDP-Periodic-
Payload142B_RFCXXXXsecY_Percent_LossRatio

[8.1.3.](#) URIs

URI: Prefix urn:iETF:metrics:perf:<name>

URL: http:\\www.iana.org\ ... <name>

[8.1.4.](#) Description

OWDelay: This metric assesses the delay of a stream of packets exchanged between two hosts (or measurement points), and reports the <statistic> One-way delay for all successfully exchanged packets based on their conditional delay distribution.

where <statistic> is one of:

- o 95Percentile
- o Mean
- o Min
- o Max

o StdDev

OWLoss: This metric assesses the loss ratio of a stream of packets exchanged between two hosts (which are the two measurement points), and the Output is the One-way loss ratio for all successfully received packets expressed as a percentage.

8.2. Metric Definition

This category includes columns to prompt the entry of all necessary details related to the metric definition, including the RFC reference and values of input factors, called fixed parameters.

8.2.1. Reference Definition

<Full bibliographic reference to an immutable doc.>

For Delay:

Almes, G., Kalidindi, S., Zekauskas, M., and A. Morton, Ed., "A One-Way Delay Metric for IP Performance Metrics (IPPM)", STD 81, RFC

Morton, et al.

Expires May 2, 2018

[Page 48]

Internet-Draft

Initial Registry

October 2017

7679, DOI 10.17487/RFC7679, January 2016, <<http://www.rfc-editor.org/info/rfc7679>>.

[RFC7679]

Morton, A., and Stephan, E., "Spatial Composition of Metrics", [RFC 6049](#), January 2011.

[RFC6049]

<specific section reference and additional clarifications, if needed>

[Section 3.4 of \[RFC7679\]](#) provides the reference definition of the singleton (single value) One-way delay metric. [Section 4.4 of \[RFC7679\]](#) provides the reference definition expanded to cover a multi-value sample. Note that terms such as singleton and sample are defined in [Section 11 of \[RFC2330\]](#).

Only successful packet transfers with finite delay are included in

the sample, as prescribed in [section 4.1.2 of \[RFC6049\]](#).

For loss:

Almes, G., Kalidini, S., Zekauskas, M., and A. Morton, Ed., "A One-Way Loss Metric for IP Performance Metrics (IPPM)", [RFC 7680](#), DOI 10.17487/RFC7680, January 2016, <<http://www.rfc-editor.org/info/rfc7680>>.

[Section 2.4 of \[RFC7680\]](#) provides the reference definition of the singleton (single value) one-way loss metric. [Section 3.4 of \[RFC7680\]](#) provides the reference definition expanded to cover a multi-singleton sample. Note that terms such as singleton and sample are defined in [Section 11 of \[RFC2330\]](#).

[8.2.2](#). Fixed Parameters

<list and specify Fixed Parameters, input factors that must be determined and embedded in the measurement system for use when needed>

Type-P:

- o IPv4 header values:
 - * DSCP: set to 0
 - * TTL: set to 255

- * Protocol: Set to 17 (UDP)
- o IPv6 header values:
 - * DSCP: set to 0
 - * Hop Count: set to 255
 - * Protocol: Set to 17 (UDP)
- o UDP header values:

- * Checksum: the checksum MUST be calculated and included in the header
- o UDP Payload: TWAMP Test Packet Formats, [Section 4.1.2 of \[RFC5357\]](#)
 - * Security features in use influence the number of Padding octets.
 - * 142 octets total, including the TWAMP format

Other measurement parameters:

Tmax: a loss threshold waiting time with value 3.0, expressed in units of seconds, as a positive value of type decimal64 with fraction digits = 4 (see [section 9.3 of \[RFC6020\]](#)) and with resolution of 0.0001 seconds (0.1 ms), with lossless conversion to/from the 32-bit NTP timestamp as per [section 6 of \[RFC5905\]](#).

See the Packet Stream generation category for two additional Fixed Parameters.

[8.3.](#) Method of Measurement

This category includes columns for references to relevant sections of the RFC(s) and any supplemental information needed to ensure unambiguous methods for implementations.

[8.3.1.](#) Reference Method

<for metric, insert relevant section references and supplemental info>

The methodology for this metric is defined as Type-P-One-way-Delay-Poisson-Stream in [section 3.6 of \[RFC7679\]](#) and [section 4.6 of \[RFC7679\]](#) using the Type-P and Tmax defined under Fixed Parameters. However, a Periodic stream is used, as defined in [\[RFC3432\]](#).

The reference method distinguishes between long-delayed packets and lost packets by implementing a maximum waiting time for packet arrival. Tmax is the waiting time used as the threshold to declare a packet lost. Lost packets SHALL be designated as having undefined delay, and counted for the OWLoss metric.

The calculations on the one-way delay SHALL be performed on the conditional distribution, conditioned on successful packet arrival within T_{max} . Also, when all packet delays are stored, the process which calculates the one-way delay value MAY enforce the T_{max} threshold on stored values before calculations. See [section 4.1 of \[RFC3393\]](#) for details on the conditional distribution to exclude undefined values of delay, and [Section 5 of \[RFC6703\]](#) for background on this analysis choice.

The reference method requires some way to distinguish between different packets in a stream to establish correspondence between sending times and receiving times for each successfully-arriving packet. Sequence numbers or other send-order identification MUST be retained at the Src or included with each packet to disambiguate packet reordering if it occurs.

Since a standard measurement protocol is employed [[RFC5357](#)], then the measurement process will determine the sequence numbers or timestamps applied to test packets after the Fixed and Runtime parameters are passed to that process. The measurement protocol dictates the format of sequence numbers and time-stamps conveyed in the TWAMP-Test packet payload.

[8.3.2](#). Packet Stream Generation

<list of generation parameters and section/spec references if needed>

This section gives the details of the packet traffic which is the basis for measurement. In IPPM metrics, this is called the Stream, and can easily be described by providing the list of stream parameters.

[Section 3 of \[RFC3432\]](#) prescribes the method for generating Periodic streams using associated parameters.

incT the nominal duration of inter-packet interval, first bit to first bit

dT the duration of the interval for allowed sample start times

T0 the actual start time of the periodic stream

NOTE: an initiation process with a number of control exchanges resulting in unpredictable start times (within a time interval) may be sufficient to avoid synchronization of periodic streams, and therefore a valid replacement for selecting a start time at random from a fixed interval.

These stream parameters will be specified as Run-time parameters.

[8.3.3.](#) Traffic Filtering (observation) Details

NA

[8.3.4.](#) Sampling Distribution

NA

[8.3.5.](#) Run-time Parameters and Data Format

Run-time Parameters are input factors that must be determined, configured into the measurement system, and reported with the results for the context to be complete.

<list of run-time parameters, and their data formats>

Src the IP address of the host in the Src Role (format ipv4-address-no-zone value for IPv4, or ipv6-address-no-zone value for IPv6, see [Section 4 of \[RFC6991\]](#))

Dst the IP address of the host in the Dst Role (format ipv4-address-no-zone value for IPv4, or ipv6-address-no-zone value for IPv6, see [section 4 of \[RFC6991\]](#))

T0 a time, the start of a measurement interval, (format "date-and-time" as specified in [Section 5.6 of \[RFC3339\]](#), see also [Section 3 of \[RFC6991\]](#)). The UTC Time Zone is required by [Section 6.1 of \[RFC2330\]](#). When T0 is "all-zeros", a start time is unspecified and Tf is to be interpreted as the Duration of the measurement interval. The start time is controlled through other means.

Tf a time, the end of a measurement interval, (format "date-and-time" as specified in [Section 5.6 of \[RFC3339\]](#), see also [Section 3 of \[RFC6991\]](#)). The UTC Time Zone is required by [Section 6.1 of \[RFC2330\]](#). When T0 is "all-zeros", a end time date is ignored and Tf is interpreted as the Duration of the measurement interval.

@@@ should Periodic run-time params be fixed instead? Probably yes if modeling a specific version of tests. Note in the NAME, i.e. Poisson3.3

Internet-Draft

Initial Registry

October 2017

[8.3.6.](#) Roles

<lists the names of the different roles from the measurement method>

Src launches each packet and waits for return transmissions from Dst. This is the TWAMP Session-Sender.

Dst waits for each packet from Src and sends a return packet to Src. This is the TWAMP Session-Reflector.

[8.4.](#) Output

This category specifies all details of the Output of measurements using the metric.

[8.4.1.](#) Type

<insert name of the output type, raw or a selected summary statistic>

See subsection titles in Reference Definition for Latency Types.

[8.4.2.](#) Reference Definition

<describe the data format for each type of result>

For all output types ---

T0 the start of a measurement interval, (format "date-and-time" as specified in [Section 5.6 of \[RFC3339\]](#), see also [Section 3 of \[RFC6991\]](#)). The UTC Time Zone is required by [Section 6.1 of \[RFC2330\]](#).

Tf the end of a measurement interval, (format "date-and-time" as specified in [Section 5.6 of \[RFC3339\]](#), see also [Section 3 of \[RFC6991\]](#)). The UTC Time Zone is required by [Section 6.1 of \[RFC2330\]](#).

For LossRatio -- the count of lost packets to total packets sent is the basis for the loss ratio calculation as per [Section 4.1 of \[RFC7680\]](#).

For each <statistic>, one of the following sub-sections apply:

[8.4.2.1](#). Percentile95

The 95th percentile SHALL be calculated using the conditional distribution of all packets with a finite value of One-way delay (undefined delays are excluded), a single value as follows:

Morton, et al.

Expires May 2, 2018

[Page 53]

Internet-Draft

Initial Registry

October 2017

See [section 4.1 of \[RFC3393\]](#) for details on the conditional distribution to exclude undefined values of delay, and [Section 5 of \[RFC6703\]](#) for background on this analysis choice.

See [section 4.3 of \[RFC3393\]](#) for details on the percentile statistic (where Round-trip delay should be substituted for "ipdv").

The percentile = 95, meaning that the reported delay, "95Percentile", is the smallest value of one-way delay for which the Empirical Distribution Function (EDF), $F(95\text{Percentile}) \geq 95\%$ of the singleton one-way delay values in the conditional distribution. See [section 11.3 of \[RFC2330\]](#) for the definition of the percentile statistic using the EDF.

95Percentile The time value of the result is expressed in units of seconds, as a positive value of type decimal64 with fraction digits = 9 (see [section 9.3 of \[RFC6020\]](#)) with resolution of 0.000000001 seconds (1.0 ns), and with lossless conversion to/from the 64-bit NTP timestamp as per [section 6](#) of RFC [\[RFC5905\]](#)

[8.4.2.2](#). Mean

The mean SHALL be calculated using the conditional distribution of all packets with a finite value of One-way delay (undefined delays are excluded), a single value as follows:

See [section 4.1 of \[RFC3393\]](#) for details on the conditional distribution to exclude undefined values of delay, and [Section 5 of \[RFC6703\]](#) for background on this analysis choice.

See [section 4.2.2 of \[RFC6049\]](#) for details on calculating this statistic, and 4.2.3 of [\[RFC6049\]](#).

Mean The time value of the result is expressed in units of seconds, as a positive value of type decimal64 with fraction digits = 9

(see [section 9.3 of \[RFC6020\]](#)) with resolution of 0.000000001 seconds (1.0 ns), and with lossless conversion to/from the 64-bit NTP timestamp as per [section 6](#) of RFC [\[RFC5905\]](#)

[8.4.2.3](#). Min

The minimum SHALL be calculated using the conditional distribution of all packets with a finite value of One-way delay (undefined delays are excluded), a single value as follows:

See [section 4.1 of \[RFC3393\]](#) for details on the conditional distribution to exclude undefined values of delay, and [Section 5 of \[RFC6703\]](#) for background on this analysis choice.

Morton, et al.

Expires May 2, 2018

[Page 54]

Internet-Draft

Initial Registry

October 2017

See [section 4.3.2 of \[RFC6049\]](#) for details on calculating this statistic, and 4.3.3 of [\[RFC6049\]](#).

Min The time value of the result is expressed in units of seconds, as a positive value of type decimal64 with fraction digits = 9 (see [section 9.3 of \[RFC6020\]](#)) with resolution of 0.000000001 seconds (1.0 ns), and with lossless conversion to/from the 64-bit NTP timestamp as per [section 6](#) of RFC [\[RFC5905\]](#)

[8.4.2.4](#). Max

The maximum SHALL be calculated using the conditional distribution of all packets with a finite value of One-way delay (undefined delays are excluded), a single value as follows:

See [section 4.1 of \[RFC3393\]](#) for details on the conditional distribution to exclude undefined values of delay, and [Section 5 of \[RFC6703\]](#) for background on this analysis choice.

See [section 4.3.2 of \[RFC6049\]](#) for a closely related method for calculating this statistic, and 4.3.3 of [\[RFC6049\]](#). The formula is as follows:

$$\text{Max} = (\text{FiniteDelay } [j])$$

such that for some index, j , where $1 \leq j \leq N$
 $\text{FiniteDelay}[j] \geq \text{FiniteDelay}[n]$ for all n

Max The time value of the result is expressed in units of seconds, as a positive value of type decimal64 with fraction digits = 9 (see [section 9.3 of \[RFC6020\]](#)) with resolution of 0.000000001 seconds (1.0 ns), and with lossless conversion to/from the 64-bit NTP timestamp as per [section 6](#) of RFC [\[RFC5905\]](#)

[8.4.2.5](#). Std_Dev

The Std_Dev SHALL be calculated using the conditional distribution of all packets with a finite value of One-way delay (undefined delays are excluded), a single value as follows:

See [section 4.1 of \[RFC3393\]](#) for details on the conditional distribution to exclude undefined values of delay, and [Section 5 of \[RFC6703\]](#) for background on this analysis choice.

See [section 4.3.2 of \[RFC6049\]](#) for a closely related method for calculating this statistic, and 4.3.3 of [\[RFC6049\]](#). The formula is the classic calculation for standard deviation of a population.

Std_Dev The time value of the result is expressed in units of seconds, as a positive value of type decimal64 with fraction digits = 9 (see [section 9.3 of \[RFC6020\]](#)) with resolution of 0.000000001 seconds (1.0 ns), and with lossless conversion to/from the 64-bit NTP timestamp as per [section 6](#) of RFC [\[RFC5905\]](#)

[8.4.3](#). Metric Units

<insert units for the measured results, and the reference specification>.

The <statistic> of One-way Delay is expressed in seconds, where <statistic> is one of:

- o 95Percentile
- o Mean
- o Min
- o Max

- o StdDev

The One-way Loss Ratio is expressed as a percentage of lost packets to total packets sent.

8.4.4. Calibration

[Section 3.7.3 of \[RFC7679\]](#) provides a means to quantify the systematic and random errors of a time measurement. In-situ calibration could be enabled with an internal loopback that includes as much of the measurement system as possible, performs address manipulation as needed, and provides some form of isolation (e.g., deterministic delay) to avoid send-receive interface contention. Some portion of the random and systematic error can be characterized this way.

For one-way delay measurements, the error calibration must include an assessment of the internal clock synchronization with its external reference (this internal clock is supplying timestamps for measurement). In practice, the time offsets of clocks at both the source and destination are needed to estimate the systematic error due to imperfect clock synchronization (the time offsets are smoothed, thus the random variation is not usually represented in the results).

time_offset The time value of the result is expressed in units of seconds, as a signed value of type decimal64 with fraction digits = 9 (see [section 9.3 of \[RFC6020\]](#)) with resolution of 0.000000001 seconds (1.0 ns), and with lossless conversion to/from the 64-bit NTP timestamp as per [section 6](#) of RFC [\[RFC5905\]](#)

When a measurement controller requests a calibration measurement, the loopback is applied and the result is output in the same format as a normal measurement with additional indication that it is a calibration result. In any measurement, the measurement function SHOULD report its current estimate of time offset as an indicator of the degree of synchronization.

Both internal loopback calibration and clock synchronization can be

used to estimate the *available accuracy* of the Output Metric Units. For example, repeated loopback delay measurements will reveal the portion of the Output result resolution which is the result of system noise, and thus inaccurate.

[8.5.](#) Administrative items

[8.5.1.](#) Status

<current or deprecated>

[8.5.2.](#) Requestor (keep?)

name or RFC, etc.

[8.5.3.](#) Revision

1.0

[8.5.4.](#) Revision Date

YYYY-MM-DD

[8.6.](#) Comments and Remarks

Additional (Informational) details for this entry

[9.](#) ICMP Round-trip Latency and Loss Registry Entries

This section specifies three initial registry entries for the ICMP Round-trip Latency, and another entry for ICMP Round-trip Loss Ratio.

This section specifies four Registry entries with many common columns.

Morton, et al.

Expires May 2, 2018

[Page 57]

Internet-Draft

Initial Registry

October 2017

All column entries beside the ID, Name, Description, and Output Reference Method categories are the same, thus this section proposes two closely-related registry entries. As a result, IANA is also asked to assign four corresponding URNs and URLs to each Named Metric.

[9.1.](#) Summary

This category includes multiple indexes to the registry entry: the element ID and metric name.

[9.1.1.](#) ID (Identifier)

<insert a numeric identifier, an integer, TBD>

IANA is asked to assign different numeric identifiers to each of the four Named Metrics.

[9.1.2.](#) Name

<insert name according to metric naming convention>

RTDelay_Active_IP-ICMP-SendOnRcv_RFCXXXXsecY_Seconds_<statistic>

where <statistic> is one of:

- o Mean
- o Min
- o Max

RTLoss_Active_IP-ICMP-SendOnRcv_RFCXXXXsecY_Percent_LossRatio

[9.1.3.](#) URIs

URN: Prefix urn:iETF:metrics:perf:<name>

URL: http://<TBD by IANA>/<name>

[9.1.4.](#) Description

RTDelay: This metric assesses the delay of a stream of ICMP packets exchanged between two hosts (which are the two measurement points), and the Output is the Round-trip delay for all successfully exchanged packets expressed as the <statistic> of their conditional delay distribution, where <statistic> is one of:

- o Mean
- o Min
- o Max

RTLoss: This metric assesses the loss ratio of a stream of ICMP packets exchanged between two hosts (which are the two measurement points), and the Output is the Round-trip loss ratio for all successfully exchanged packets expressed as a percentage.

[9.1.5.](#) Change Controller

IETF

[9.1.6.](#) Version (of Registry Format)

1.0

[9.2.](#) Metric Definition

This category includes columns to prompt the entry of all necessary details related to the metric definition, including the RFC reference and values of input factors, called fixed parameters.

[9.2.1.](#) Reference Definition

<Full bibliographic reference to an immutable doc.>

Almes, G., Kalidindi, S., and M. Zekauskas, "A Round-trip Delay Metric for IPPM", [RFC 2681](#), September 1999.

[RFC2681]

<specific section reference and additional clarifications, if needed>

[Section 2.4 of \[RFC2681\]](#) provides the reference definition of the singleton (single value) Round-trip delay metric. [Section 3.4 of \[RFC2681\]](#) provides the reference definition expanded to cover a multi-singleton sample. Note that terms such as singleton and sample are defined in [Section 11 of \[RFC2330\]](#).

Note that although the [\[RFC2681\]](#) definition of "Round-trip-Delay between Src and Dst" is directionally ambiguous in the text, this metric tightens the definition further to recognize that the host in the "Src" role will send the first packet to "Dst", and ultimately receive the corresponding return packet from "Dst" (when neither are lost).

Internet-Draft

Initial Registry

October 2017

Finally, note that the variable "dT" is used in [\[RFC2681\]](#) to refer to the value of Round-trip delay in metric definitions and methods. The variable "dT" has been re-used in other IPPM literature to refer to different quantities, and cannot be used as a global variable name.

Morton, A., "Round-trip Packet Loss Metrics", [RFC 6673](#), August 2012.

[RFC6673]

Both delay and loss metrics employ a maximum waiting time for received packets, so the count of lost packets to total packets sent is the basis for the loss ratio calculation as per [Section 6.1 of \[RFC6673\]](#).

[9.2.2.](#) Fixed Parameters

<list and specify Fixed Parameters, input factors that must be determined and embedded in the measurement system for use when needed>

Type-P as defined in [Section 13 of \[RFC2330\]](#):

- o IPv4 header values:
 - * DSCP: set to 0
 - * TTL: set to 255
 - * Protocol: Set to 01 (ICMP)
- o IPv6 header values:
 - * DSCP: set to 0
 - * Hop Limit: set to 255
 - * Protocol: Set to 01 (ICMP)
- o ICMP header values:
 - * Type: 8 (Echo Request)
 - * Code: 0

- * Checksum: the checksum MUST be calculated and included in the header
- * (Identifier and Sequence Number set at Run-Time)

Morton, et al.

Expires May 2, 2018

[Page 60]

Internet-Draft

Initial Registry

October 2017

- o ICMP Payload

- * total of 32 bytes of random info

Other measurement parameters:

- o Tmax: a loss threshold waiting time

- * 3.0, expressed in units of seconds, as a positive value of type decimal64 with fraction digits = 4 (see [section 9.3 of \[RFC6020\]](#)) and with resolution of 0.0001 seconds (0.1 ms), with lossless conversion to/from the 32-bit NTP timestamp as per [section 6 of \[RFC5905\]](#).

[9.3.](#) Method of Measurement

This category includes columns for references to relevant sections of the RFC(s) and any supplemental information needed to ensure an unambiguous methods for implementations.

[9.3.1.](#) Reference Method

<for metric, insert relevant section references and supplemental info>

The methodology for this metric is defined as Type-P-Round-trip-Delay-Poisson-Stream in [section 2.6 of RFC 2681 \[RFC2681\]](#) and [section 3.6 of RFC 2681 \[RFC2681\]](#) using the Type-P and Tmax defined under Fixed Parameters.

The reference method distinguishes between long-delayed packets and lost packets by implementing a maximum waiting time for packet arrival. Tmax is the waiting time used as the threshold to declare a packet lost. Lost packets SHALL be designated as having undefined delay, and counted for the RTLoss metric.

The calculations on the delay (RTD) SHALL be performed on the conditional distribution, conditioned on successful packet arrival within Tmax. Also, when all packet delays are stored, the process which calculates the RTD value MAY enforce the Tmax threshold on stored values before calculations. See [section 4.1 of \[RFC3393\]](#) for details on the conditional distribution to exclude undefined values of delay, and [Section 5 of \[RFC6703\]](#) for background on this analysis choice.

The reference method requires some way to distinguish between different packets in a stream to establish correspondence between sending times and receiving times for each successfully-arriving

packet. Sequence numbers or other send-order identification MUST be retained at the Src or included with each packet to disambiguate packet reordering if it occurs.

The measurement process will determine the sequence numbers applied to test packets after the Fixed and Runtime parameters are passed to that process. The ICMP measurement process and protocol will dictate the format of sequence numbers and other identifiers.

Refer to [Section 4.4 of \[RFC6673\]](#) for expanded discussion of the instruction to "send a Type-P packet back to the Src as quickly as possible" in [Section 2.6 of RFC 2681 \[RFC2681\]](#). [Section 8 of \[RFC6673\]](#) presents additional requirements which MUST be included in the method of measurement for this metric.

9.3.2. Packet Stream Generation

This section gives the details of the packet traffic which is the basis for measurement. In IPPM metrics, this is called the Stream, and can easily be described by providing the list of stream parameters.

The ICMP metrics use a sending discipline called "SendOnRcv" or Send On Receive. This is a modification of [Section 3 of \[RFC3432\]](#), which prescribes the method for generating Periodic streams using associated parameters:

incT the nominal duration of inter-packet interval, first bit to first bit

dT the duration of the interval for allowed sample start times

T0 the actual start time of the periodic stream

The incT and T0 stream parameters will be specified as Run-time parameters, dT is not used in SendOnRcv.

A SendOnRcv sender behaves exactly like a Periodic stream generator while all reply packets arrive with $RTD < incT$, and the inter-packet interval will be constant.

If a reply packet arrives with $RTD \geq incT$, then the inter-packet interval for the next sending time is nominally RTD.

If a reply packet fails to arrive within Tmax, then the inter-packet interval for the next sending time is nominally Tmax.

If an immediate send on reply arrival is desired, then set $incT=0$.

[9.3.3.](#) Traffic Filtering (observation) Details

The measured results based on a filtered version of the packets observed, and this section provides the filter details (when present).

<section reference>.

NA

[9.3.4.](#) Sampling Distribution

<insert time distribution details, or how this is diff from the filter>

NA

[9.3.5.](#) Run-time Parameters and Data Format

Run-time Parameters are input factors that must be determined, configured into the measurement system, and reported with the results for the context to be complete.

<list of run-time parameters, and their data formats>

Src the IP address of the host in the Src Role (format ipv4-address-no-zone value for IPv4, or ipv6-address-no-zone value for IPv6, see [Section 4 of \[RFC6991\]](#))

Dst the IP address of the host in the Dst Role (format ipv4-address-no-zone value for IPv4, or ipv6-address-no-zone value for IPv6, see [section 4 of \[RFC6991\]](#))

T0 a time, the start of a measurement interval, (format "date-and-time" as specified in [Section 5.6 of \[RFC3339\]](#), see also [Section 3 of \[RFC6991\]](#)). The UTC Time Zone is required by [Section 6.1 of \[RFC2330\]](#). When T0 is "all-zeros", a start time is unspecified and Tf is to be interpreted as the Duration of the measurement interval. The start time is controlled through other means.

Count The total count of ICMP Echo Requests to send, formatted as a uint16, as per [section 9.2 of \[RFC6020\]](#).

(see the Packet Stream Generation section for additional Run-time parameters)

[9.3.6.](#) Roles

<lists the names of the different roles from the measurement method>

Src launches each packet and waits for return transmissions from Dst.

Dst waits for each packet from Src and sends a return packet to Src.

[9.4.](#) Output

This category specifies all details of the Output of measurements using the metric.

[9.4.1.](#) Type

<insert name of the output type, raw or a selected summary statistic>

See subsection titles in Reference Definition for Latency Types.

LossRatio -- the count of lost packets to total packets sent is the basis for the loss ratio calculation as per [Section 6.1 of \[RFC6673\]](#).

[9.4.2.](#) Reference Definition

<describe the data format for each type of result>

For all output types ---

T0 the start of a measurement interval, (format "date-and-time" as specified in [Section 5.6 of \[RFC3339\]](#), see also [Section 3 of \[RFC6991\]](#)). The UTC Time Zone is required by [Section 6.1 of \[RFC2330\]](#).

Tf the end of a measurement interval, (format "date-and-time" as specified in [Section 5.6 of \[RFC3339\]](#), see also [Section 3 of \[RFC6991\]](#)). The UTC Time Zone is required by [Section 6.1 of \[RFC2330\]](#).

TotalCount the count of packets actually sent by the Src to Dst during the measurement interval.

For LossRatio -- the count of lost packets to total packets sent is the basis for the loss ratio calculation as per [Section 4.1 of \[RFC7680\]](#).

For each <statistic>, one of the following sub-sections apply:

[9.4.2.1.](#) Mean

The mean SHALL be calculated using the conditional distribution of all packets with a finite value of Round-trip delay (undefined delays are excluded), a single value as follows:

See [section 4.1 of \[RFC3393\]](#) for details on the conditional distribution to exclude undefined values of delay, and [Section 5 of](#)

[\[RFC6703\]](#) for background on this analysis choice.

See [section 4.2.2 of \[RFC6049\]](#) for details on calculating this statistic, and 4.2.3 of [\[RFC6049\]](#).

Mean The time value of the result is expressed in units of seconds, as a positive value of type decimal64 with fraction digits = 9 (see [section 9.3 of \[RFC6020\]](#)) with resolution of 0.000000001 seconds (1.0 ns), and with lossless conversion to/from the 64-bit NTP timestamp as per [section 6](#) of RFC [\[RFC5905\]](#)

[9.4.2.2.](#) Min

The minimum SHALL be calculated using the conditional distribution of all packets with a finite value of Round-trip delay (undefined delays are excluded), a single value as follows:

See [section 4.1 of \[RFC3393\]](#) for details on the conditional distribution to exclude undefined values of delay, and [Section 5 of \[RFC6703\]](#) for background on this analysis choice.

See [section 4.3.2 of \[RFC6049\]](#) for details on calculating this statistic, and 4.3.3 of [\[RFC6049\]](#).

Min The time value of the result is expressed in units of seconds, as a positive value of type decimal64 with fraction digits = 9 (see [section 9.3 of \[RFC6020\]](#)) with resolution of 0.000000001 seconds (1.0 ns), and with lossless conversion to/from the 64-bit NTP timestamp as per [section 6](#) of RFC [\[RFC5905\]](#)

[9.4.2.3.](#) Max

The maximum SHALL be calculated using the conditional distribution of all packets with a finite value of Round-trip delay (undefined delays are excluded), a single value as follows:

See [section 4.1 of \[RFC3393\]](#) for details on the conditional distribution to exclude undefined values of delay, and [Section 5 of \[RFC6703\]](#) for background on this analysis choice.

calculating this statistic, and 4.3.3 of [\[RFC6049\]](#). The formula is as follows:

$$\text{Max} = (\text{FiniteDelay } [j])$$

such that for some index, j , where $1 \leq j \leq N$
 $\text{FiniteDelay}[j] \geq \text{FiniteDelay}[n]$ for all n

Max The time value of the result is expressed in units of seconds, as a positive value of type decimal64 with fraction digits = 9 (see [section 9.3 of \[RFC6020\]](#)) with resolution of 0.000000001 seconds (1.0 ns), and with lossless conversion to/from the 64-bit NTP timestamp as per [section 6](#) of RFC [\[RFC5905\]](#)

[9.4.3.](#) Metric Units

<insert units for the measured results, and the reference specification>.

The <statistic> of Round-trip Delay is expressed in seconds, where <statistic> is one of:

- o Mean
- o Min
- o Max

The Round-trip Loss Ratio is expressed as a percentage of lost packets to total packets sent.

[9.4.4.](#) Calibration

[Section 3.7.3 of \[RFC7679\]](#) provides a means to quantify the systematic and random errors of a time measurement. In-situ calibration could be enabled with an internal loopback at the Source host that includes as much of the measurement system as possible, performs address manipulation as needed, and provides some form of isolation (e.g., deterministic delay) to avoid send-receive interface contention. Some portion of the random and systematic error can be characterized this way.

When a measurement controller requests a calibration measurement, the loopback is applied and the result is output in the same format as a normal measurement with additional indication that it is a calibration result.

Both internal loopback calibration and clock synchronization can be used to estimate the *available accuracy* of the Output Metric Units. For example, repeated loopback delay measurements will reveal the portion of the Output result resolution which is the result of system noise, and thus inaccurate.

[9.5.](#) Administrative items

[9.5.1.](#) Status

<current or deprecated>

[9.5.2.](#) Requestor (keep?)

name or RFC, etc.

[9.5.3.](#) Revision

1.0

[9.5.4.](#) Revision Date

YYYY-MM-DD

[9.6.](#) Comments and Remarks

Additional (Informational) details for this entry

[10.](#) TCP Round-Trip Delay and Loss Registry Entries

This section specifies three initial registry entries for the Passive assessment of TCP Round-Trip Delay (RTD) and another entry for TCP Round-trip Loss Count.

This section specifies four Registry entries with many common columns.

All column entries beside the ID, Name, Description, and Output Reference Method categories are the same, thus this section proposes four closely-related registry entries. As a result, IANA is also asked to assign four corresponding URNs and URLs to each Named Metric.

[10.1.](#) Summary

This category includes multiple indexes to the registry entry: the

element ID and metric name.

[10.1.1.](#) ID (Identifier)

<insert a numeric identifier, an integer, TBD>

IANA is asked to assign different numeric identifiers to each of the four Named Metrics.

[10.1.2.](#) Name

<insert name according to metric naming convention>

RTDelay_Passive_IP-TCP_RFCXXXXsecY_Seconds_<statistic>

where <statistic> is one of:

- o Mean
- o Min
- o Max

RTLoss_Passive_IP-TCP_RFCXXXXsecY_Packet_Count

[10.1.3.](#) URIs

URN: Prefix urn:iETF:metrics:perf:<name>

URL: http://<TBD by IANA>/<name>

[10.1.4.](#) Description

RTDelay: This metric assesses the round-trip delay of TCP packets constituting a single connection, exchanged between two hosts. The Observation Point [[RFC7011](#)] is assumed to be in the network at a remote point from the end hosts. The Output is the Round-trip delay for all successfully exchanged packets expressed as the <statistic> of their conditional delay distribution, where <statistic> is one of:

- o Mean

- o Min
- o Max

RTLoss: This metric assesses the estimated loss count for TCP packets constituting a single connection, exchanged between two hosts. The Observation Point [[RFC7011](#)] is assumed to be in the network at a

remote point from the end hosts. The Output is the estimated Loss Count for the measurement interval.

[10.1.5.](#) Change Controller

IETF

[10.1.6.](#) Version (of Registry Format)

1.0

[10.2.](#) Metric Definition

This category includes columns to prompt the entry of all necessary details related to the metric definition, including the RFC reference and values of input factors, called fixed parameters.

[10.2.1.](#) Reference Definitions

<Full bibliographic reference to an immutable doc.>

Although there is no RFC that describes passive measurement of Round-Trip Delay,

@@@ is this true??? Searches seem to say so.

the parallel definition for Active measurement is:

Almes, G., Kalidindi, S., and M. Zekauskas, "A Round-trip Delay Metric for IPPM", [RFC 2681](#), September 1999.

[RFC2681]

<specific section reference and additional clarifications, if needed>

This metric definition uses the terms singleton and sample as defined in [Section 11 of \[RFC2330\]](#). ([Section 2.4 of \[RFC2681\]](#) provides the reference definition of the singleton (single value) Round-trip delay metric. [Section 3.4 of \[RFC2681\]](#) provides the reference definition expanded to cover a multi-singleton sample.)

With the Observation Point [\[RFC7011\]](#) (OP) located between the hosts participating in the TCP connection, the Round-trip Delay metric requires two individual measurements between the OP and each host, such that the Spatial Composition [\[RFC6049\]](#) of the measurements yields a Round-trip Delay singleton.

Morton, et al.

Expires May 2, 2018

[Page 69]

Internet-Draft

Initial Registry

October 2017

Using the direction of TCP SYN transmission to anchor the nomenclature, host A sends the SYN and host B replies with SYN-ACK during connection establishment. The direction of SYN transfer is the Forward direction of transmission, from A through OP to B (Reverse is B through OP to A).

Traffic filters reduce the packet stream at the OP to a Qualified bidirectional flow packets.

In the definitions below, Corresponding Packets are transferred in different directions and convey a common value in a TCP header field that establishes correspondence (to the extent possible). Examples may be found in the TCP timestamp fields.

@@@ Note the first-bit last bit questions in the definitions below.

For a real number, RTD_{fwd} , >> the Round-trip Delay in the Forward direction from OP to host B at time T' is RTD_{fwd} << REQUIRES that OP observed (the first bit of ?) a Qualified packet to host B at wire-time T' , that host B received that packet and sent a Corresponding Packet back to host A, and that OP observed (the last bit of ?) that packet at wire-time $T' + RTD_{fwd}$.

For a real number, RTD_{rev} , >> the Round-trip Delay in the Reverse direction from OP to host A at time T'' is RTD_{rev} << REQUIRES that

OP observed (the first bit of ?) a Qualified packet to host A at wire-time T' , that host A received that packet and sent a Corresponding Packet back to host B, and that OP observed (the last bit of ?) that packet at wire-time $T' + \text{RTD_rev}$.

Ideally, the packet sent from host B to host A in both definitions above SHOULD be the same packet (or, when measuring RTD_rev first, the packet from host A to host B in both definitions should be the same).

The REQUIRED Composition Function for a singleton of Round-trip Delay at time T (where T is the earliest of T' and $T' + \text{RTD_rev}$ above) is:

$$\text{RTDelay} = \text{RTD_fwd} + \text{RTD_rev}$$

Note that when OP is located at host A or host B, one of the terms in RTDelay will be zero or negligible.

The definition of Round-trip Loss Count uses the nomenclature developed above, based on observation of the TCP header sequence numbers and storing the sequence number gaps observed. Packet Losses can be inferred from:

- o Out-of-order segments: TCP segments are normally monotonically increasing. [Section 3 of \[RFC4737\]](#) describes the notion of "next expected" sequence numbers which can be adapted to TCP segments (for the purpose of detecting reordered packets). Observation of out-of-order segments indicates loss on the path prior to the OP, and creates a gap.
- o Duplicate segments: [Section 2 of \[RFC5560\]](#) defines identical packets and is suitable for evaluation of TCP packets to detect duplication. Observation of duplicate segments *without a corresponding gap* indicates loss on the path following the OP (because they overlap part of the delivered sequence numbers already observed at OP).

Each observation of an out-of-order or duplicate infers a singleton of loss, but composition of Round-trip Loss Counts will be conducted over a measurement interval which is synonymous with a single TCP connection.

With the above observations in the Forward direction over a measurement interval, the count of out-of-order and duplicate segments is defined as RTL_fwd. Comparable observations in the Reverse direction are defined as RTL_rev.

For a measurement interval (corresponding to a single TCP connection), T0 to Tf, the REQUIRED Composition Function for a the two single-direction counts of inferred loss is:

$$RTL_{Loss} = RTL_{fwd} + RTL_{rev}$$

[10.2.2.](#) Fixed Parameters

<list and specify Fixed Parameters, input factors that must be determined and embedded in the measurement system for use when needed>

Traffic Filters:

- o IPv4 header values:
 - * DSCP: set to 0
 - * Protocol: Set to 06 (TCP)
- o IPv6 header values:
 - * DSCP: set to 0

- * Protocol: Set to 06 (TCP)
- o TCP header values:
 - * Flags: ACK, SYN, others??
 - * Checksum: the checksum MUST be calculated and included in the header
 - * Timestamp Option (TSopt): Set

- + Kind: 8
- + Length: 10 bytes

o

10.3. Method of Measurement

This category includes columns for references to relevant sections of the RFC(s) and any supplemental information needed to ensure an unambiguous methods for implementations.

10.3.1. Reference Methods

<for metric, insert relevant section references and supplemental info>

The foundation methodology for this metric is defined in [Section 4 of \[RFC7323\]](#) using the Timestamp Option with modifications that allow application at a mid-path Observation Point (OP) [\[RFC7011\]](#). Further details and applicable heuristics were derived from [\[Strowes\]](#) and [\[Trammell-14\]](#).

The Traffic Filter at the OP is configured to observe a single TCP connection. When the SYN, SYN-ACK, ACK handshake occurs, it offers the first opportunity to measure both RTD_fwd (on the SYN to SYN-ACK pair) and RTD_rev (on the SYN-ACK to ACK pair). Label this singleton of RTDelay as RTDelay-SA (SYN-ACK = SA, composed using the forward and reverse measurement pair). RTDelay-SA SHOULD be treated separately from other RTDelays on data-bearing packets and their ACKs. The RTDelay-SA value MAY be used as a sanity check on other Composed values of RTDelay.

@@@ Should we add a separate singleton metric for RTDelay-SA ??
(seems reasonable and useful, but no loss metric however)

For payload bearing packets, the OP measures the time interval between observation of a packet with Sequence Number *s*, and the corresponding ACK with same Sequence number. When the payload is transferred from host A to host B, the observed interval is RTD_fwd.

Because many data transfers are unidirectional (say, in the Forward direction from host A to host B), it is necessary to use pure ACK packets with Timestamp (TSval) and their Timestamp value echo to perform a RTD_rev measurement. The time interval between observation of the ACK from B to A, and the corresponding packet with Timestamp echo (TSecr) is the RTD_rev.

Delay Measurement Filtering Heuristics:

If Data payloads were transferred in both Forward and Reverse directions, then the Round-Trip Time Measurement Rule in [Section 4.1 of \[RFC7323\]](#) could be applied. This rule essentially excludes any measurement using a packet unless it makes progress in the transfer (advances the left edge of the send window, consistent with [Strowes]).

A different heuristic from [\[Trammell-14\]](#) is to exclude any RTD_rev that is larger than previously observed values. This would tend to exclude Reverse measurements taken when the Application has no data ready to send, because considerable time could be added to RTD_rev from this source of error.

The statistic calculations to summarize the delay (RTDelay) SHALL be performed on the conditional distribution, conditioned on successful Forward and Reverse measurements which follow the Heuristics.

Method for Inferring Loss:

The OP tracks sequence numbers and stores gaps for each direction of transmission, as well as the next-expected sequence number as in [\[Trammell-14\]](#) and [\[RFC4737\]](#). Loss is inferred from Out-of-order segments and Duplicate segments.

Loss Measurement Filtering Heuristics:

[\[Trammell-14\]](#) adds a window of evaluation based on the RTDelay.

Spurious (unneeded) retransmissions (observed as duplicates) can also be reduced this way, as described in [\[Trammell-14\]](#).

Sources of Error:

The principal source of RTDelay error is the host processing time to return a packet that defines the termination of a time interval. The heuristics above intend to mitigate these errors by excluding measurements where host processing time is a significant part of RTD_fwd or RTD_rev.

A key source of RTLoss error is observation loss, described in section 3 of [[Trammell-14](#)].

[10.3.2.](#) Packet Stream Generation

This section gives the details of the packet traffic which is the basis for measurement. In IPPM metrics, this is called the Stream, and can easily be described by providing the list of stream parameters.

NA

[10.3.3.](#) Traffic Filtering (observation) Details

The measured results based on a filtered version of the packets observed, and this section provides the filter details (when present).

The Fixed Parameters above give a portion of the Traffic Filter. Other aspects will be supplied as Run-time Parameters (below).

[10.3.4.](#) Sampling Distribution

<insert time distribution details, or how this is diff from the filter>

This metric requires a complete sample of all packets that qualify according to the Traffic Filter criteria.

[10.3.5.](#) Run-time Parameters and Data Format

Run-time Parameters are input factors that must be determined, configured into the measurement system, and reported with the results for the context to be complete.

<list of run-time parameters, and their data formats>

Src the IP address of the host in the host A Role (format ipv4-address-no-zone value for IPv4, or ipv6-address-no-zone value for IPv6, see [Section 4 of \[RFC6991\]](#))

Internet-Draft

Initial Registry

October 2017

Dst the IP address of the host in the host B (format ipv4-address-no-zone value for IPv4, or ipv6-address-no-zone value for IPv6, see [section 4 of \[RFC6991\]](#))

T0 a time, the start of a measurement interval, (format "date-and-time" as specified in [Section 5.6 of \[RFC3339\]](#), see also [Section 3 of \[RFC6991\]](#)). The UTC Time Zone is required by [Section 6.1 of \[RFC2330\]](#). When T0 is "all-zeros", a start time is unspecified and Td is to be interpreted as the Duration of the measurement interval. The start time is controlled through other means.

Td Optionally, the end of a measurement interval, (format "date-and-time" as specified in [Section 5.6 of \[RFC3339\]](#), see also [Section 3 of \[RFC6991\]](#)), or the duration (see T0). The UTC Time Zone is required by [Section 6.1 of \[RFC2330\]](#). Alternatively, the end of the measurement interval MAY be controlled by the measured connection, where the second pair of FIN and ACK packets exchanged between host A and B effectively ends the interval.

... ..

[10.3.6.](#) Roles

<lists the names of the different roles from the measurement method>

host A launches the SYN packet to open the connection, and synonymous with an IP address.

host B replies with the SYN-ACK packet to open the connection, and synonymous with an IP address.

[10.4.](#) Output

This category specifies all details of the Output of measurements using the metric.

[10.4.1.](#) Type

<insert name of the output type, raw or a selected summary statistic>

See subsection titles in Reference Definition for RTDelay Types.

For RTLoss -- the count of lost packets.

Morton, et al.

Expires May 2, 2018

[Page 75]

Internet-Draft

Initial Registry

October 2017

[10.4.2.](#) Reference Definition

<describe the data format for each type of result>

For all output types ---

T0 the start of a measurement interval, (format "date-and-time" as specified in [Section 5.6 of \[RFC3339\]](#), see also [Section 3 of \[RFC6991\]](#)). The UTC Time Zone is required by [Section 6.1 of \[RFC2330\]](#).

Tf the end of a measurement interval, (format "date-and-time" as specified in [Section 5.6 of \[RFC3339\]](#), see also [Section 3 of \[RFC6991\]](#)). The UTC Time Zone is required by [Section 6.1 of \[RFC2330\]](#). The end of the measurement interval MAY be controlled by the measured connection, where the second pair of FIN and ACK packets exchanged between host A and B effectively ends the interval.

... ..

For RTLoss -- the count of lost packets.

For each <statistic>, one of the following sub-sections apply:

[10.4.2.1.](#) Mean

The mean SHALL be calculated using the conditional distribution of all packets with a finite value of Round-trip delay (undefined delays are excluded), a single value as follows:

See [section 4.1 of \[RFC3393\]](#) for details on the conditional distribution to exclude undefined values of delay, and [Section 5 of](#)

[\[RFC6703\]](#) for background on this analysis choice.

See [section 4.2.2 of \[RFC6049\]](#) for details on calculating this statistic, and 4.2.3 of [\[RFC6049\]](#).

Mean The time value of the result is expressed in units of seconds, as a positive value of type decimal64 with fraction digits = 9 (see [section 9.3 of \[RFC6020\]](#)) with resolution of 0.000000001 seconds (1.0 ns), and with lossless conversion to/from the 64-bit NTP timestamp as per [section 6](#) of RFC [\[RFC5905\]](#)

Morton, et al.

Expires May 2, 2018

[Page 76]

Internet-Draft

Initial Registry

October 2017

[10.4.2.2.](#) Min

The minimum SHALL be calculated using the conditional distribution of all packets with a finite value of Round-trip delay (undefined delays are excluded), a single value as follows:

See [section 4.1 of \[RFC3393\]](#) for details on the conditional distribution to exclude undefined values of delay, and [Section 5 of \[RFC6703\]](#) for background on this analysis choice.

See [section 4.3.2 of \[RFC6049\]](#) for details on calculating this statistic, and 4.3.3 of [\[RFC6049\]](#).

Min The time value of the result is expressed in units of seconds, as a positive value of type decimal64 with fraction digits = 9 (see [section 9.3 of \[RFC6020\]](#)) with resolution of 0.000000001 seconds (1.0 ns), and with lossless conversion to/from the 64-bit NTP timestamp as per [section 6](#) of RFC [\[RFC5905\]](#)

[10.4.2.3.](#) Max

The maximum SHALL be calculated using the conditional distribution of all packets with a finite value of Round-trip delay (undefined delays are excluded), a single value as follows:

See [section 4.1 of \[RFC3393\]](#) for details on the conditional

distribution to exclude undefined values of delay, and [Section 5 of \[RFC6703\]](#) for background on this analysis choice.

See [section 4.3.2 of \[RFC6049\]](#) for a closely related method for calculating this statistic, and 4.3.3 of [\[RFC6049\]](#). The formula is as follows:

$$\text{Max} = (\text{FiniteDelay } [j])$$

such that for some index, j , where $1 \leq j \leq N$
 $\text{FiniteDelay}[j] \geq \text{FiniteDelay}[n]$ for all n

Max The time value of the result is expressed in units of seconds, as a positive value of type decimal64 with fraction digits = 9 (see [section 9.3 of \[RFC6020\]](#)) with resolution of 0.000000001 seconds (1.0 ns), and with lossless conversion to/from the 64-bit NTP timestamp as per [section 6](#) of RFC [\[RFC5905\]](#)

[10.4.3.](#) Metric Units

<insert units for the measured results, and the reference specification>.

The <statistic> of Round-trip Delay is expressed in seconds, where <statistic> is one of:

- o Mean
- o Min
- o Max

The Round-trip Loss Count is expressed as a number of packets.

[10.4.4.](#) Calibration

Passive measurements at an OP could be calibrated against an active

measurement (with loss emulation) at host A or B, where the active measurement represents the ground-truth.

[10.5.](#) Administrative items

[10.5.1.](#) Status

<current or deprecated>

[10.5.2.](#) Requestor (keep?)

name or RFC, etc.

[10.5.3.](#) Revision

1.0

[10.5.4.](#) Revision Date

YYYY-MM-DD

[10.6.](#) Comments and Remarks

Additional (Informational) details for this entry

Morton, et al.

Expires May 2, 2018

[Page 78]

Internet-Draft

Initial Registry

October 2017

[11.](#) ver08 BLANK Registry Entry

This section gives an initial registry entry for

[11.1.](#) Summary

This category includes multiple indexes to the registry entries, the element ID and metric name.

[11.1.1.](#) ID (Identifier)

<insert numeric identifier, an integer>

[11.1.2.](#) Name

<insert name according to metric naming convention>

[11.1.3.](#) URIs

URI: Prefix urn:ietf:metrics:perf:<name>

URL:

[11.1.4.](#) Description

TBD.

[11.1.5.](#) Reference

<reference to the RFC of spec where the registry entry is defined>

[11.1.6.](#) Change Controller

<org or person >

[11.1.7.](#) Version (of Registry Format)

<currently 1.0>

[11.2.](#) Metric Definition

This category includes columns to prompt the entry of all necessary details related to the metric definition, including the RFC reference and values of input factors, called fixed parameters.

[11.2.1.](#) Reference Definition

<Full bibliographic reference to an immutable doc.>

<specific section reference and additional clarifications, if needed>

[11.2.2.](#) Fixed Parameters

<list and specify Fixed Parameters, input factors that must be determined and embedded in the measurement system for use when needed>

[11.3.](#) Method of Measurement

This category includes columns for references to relevant sections of the RFC(s) and any supplemental information needed to ensure an unambiguous methods for implementations.

[11.3.1.](#) Reference Method

<for metric, insert relevant section references and supplemental info>

[11.3.2.](#) Packet Stream Generation

<list of generation parameters and section/spec references if needed>

[11.3.3.](#) Traffic Filtering (observation) Details

<insert the measured results based on a filtered version of the packets observed, and this section provides the filter details (when present), and section reference>.

[11.3.4.](#) Sampling Distribution

<insert time distribution details, or how this is diff from the filter>

[11.3.5.](#) Run-time Parameters and Data Format

<list of run-time parameters, and any reference(s)>.

[11.3.6.](#) Roles

<lists the names of the different roles from the measurement method>

[11.4.](#) Output

This category specifies all details of the Output of measurements using the metric.

[11.4.1.](#) Type

<insert name of the output type, raw or a selected summary statistic>

[11.4.2.](#) Reference Definition

<pointer to section/spec where output type/format is defined>

[11.4.3.](#) Metric Units

<insert units for the measured results, and the reference specification>.

[11.4.4.](#) Calibration

<describe the error calibration, a way to indicate that the results were collected in a calibration mode of operation, and a way to report internal status metrics related to calibration, such as time offset>

[11.5.](#) Administrative items

[11.5.1.](#) Status

<current or deprecated>

[11.5.2.](#) Requestor

<name of individual or Internet Draft, etc.>

[11.5.3.](#) Revision

1.0

[11.5.4.](#) Revision Date

YYYY-MM-DD

[11.6.](#) Comments and Remarks

Additional (Informational) details for this entry

Internet-Draft

Initial Registry

October 2017

[12.](#) Example RTCP-XR Registry Entry

This section is MAY BE DELETED or adapted before submission.

This section gives an example registry entry for the end-point metric described in [RFC 7003](#) [[RFC7003](#)], for RTCP-XR Burst/Gap Discard Metric reporting.

[12.1.](#) Registry Indexes

This category includes multiple indexes to the registry entries, the element ID and metric name.

[12.1.1.](#) Identifier

An integer having enough digits to uniquely identify each entry in the Registry.

[12.1.2.](#) Name

A metric naming convention is TBD.

[12.1.3.](#) URI

Prefix urn:iETF:metrics:param:<name>

[12.1.4.](#) Status

current

[12.1.5.](#) Requestor

Alcelip Mornuley

[12.1.6.](#) Revision

1.0

[12.1.7.](#) Revision Date

2014-07-04

[12.1.8.](#) Description

TBD.

Morton, et al.

Expires May 2, 2018

[Page 82]

Internet-Draft

Initial Registry

October 2017

[12.1.9.](#) Reference Specification(s)

[\[RFC3611\]](#) [\[RFC4566\]](#) [\[RFC6776\]](#) [\[RFC6792\]](#) [\[RFC7003\]](#)

[12.2.](#) Metric Definition

This category includes columns to prompt the entry of all necessary details related to the metric definition, including the RFC reference and values of input factors, called fixed parameters. [Section 3.2 of \[\\[RFC7003\\]\]\(#\)](#) provides the reference information for this category.

[12.2.1.](#) Reference Definition

Packets Discarded in Bursts:

The total number of packets discarded during discard bursts. The measured value is unsigned value. If the measured value exceeds 0xFFFFFD, the value 0xFFFFFE MUST be reported to indicate an over-range measurement. If the measurement is unavailable, the value 0xFFFFF MUST be reported.

[12.2.2.](#) Fixed Parameters

Fixed Parameters are input factors that must be determined and embedded in the measurement system for use when needed. The values of these parameters is specified in the Registry.

Threshold: 8 bits, set to value = 3 packets.

The Threshold is equivalent to Gmin in [\[RFC3611\]](#), i.e., the number of successive packets that must not be discarded prior to and following a discard packet in order for this discarded packet to be regarded as part of a gap. Note that the Threshold is set in accordance with the Gmin calculation defined in [Section 4.7.2 of \[\\[RFC3611\\]\]\(#\)](#).

Interval Metric flag: 2 bits, set to value 11=Cumulative Duration

This field is used to indicate whether the burst/gap discard metrics are Sampled, Interval, or Cumulative metrics [[RFC6792](#)]:

I=10: Interval Duration - the reported value applies to the most recent measurement interval duration between successive metrics reports.

I=11: Cumulative Duration - the reported value applies to the accumulation period characteristic of cumulative measurements.

Senders MUST NOT use the values I=00 or I=01.

[12.3.](#) Method of Measurement

This category includes columns for references to relevant sections of the RFC(s) and any supplemental information needed to ensure unambiguous methods for implementations. For the Burst/Gap Discard Metric, it appears that the only guidance on methods of measurement is in [Section 3.0 of \[RFC7003\]](#) and its supporting references.

Relevant information is repeated below, although there appears to be no section titled "Method of Measurement" in [[RFC7003](#)].

[12.3.1.](#) Reference Method

Metrics in this block report on burst/gap discard in the stream arriving at the RTP system. Measurements of these metrics are made at the receiving end of the RTP stream. Instances of this metrics block use the synchronization source (SSRC) to refer to the separate auxiliary Measurement Information Block [[RFC6776](#)], which describes measurement periods in use (see [[RFC6776](#)], [Section 4.2](#)).

This metrics block relies on the measurement period in the Measurement Information Block indicating the span of the report. Senders MUST send this block in the same compound RTCP packet as the Measurement Information Block. Receivers MUST verify that the measurement period is received in the same compound RTCP packet as this metrics block. If not, this metrics block MUST be discarded.

[12.3.2.](#) Stream Type and Stream Parameters

Since RTCP-XR Measurements are conducted on live RTP traffic, the complete description of the stream is contained in SDP messages that proceed the establishment of a compatible stream between two or more communicating hosts. See Run-time Parameters, below.

[12.3.3.](#) Output Type and Data Format

The output type defines the type of result that the metric produces.

- o Value: Packets Discarded in Bursts
- o Data Format: 24 bits
- o Reference: [Section 3.2 of \[RFC7003\]](#)

[12.3.4.](#) Metric Units

The measured results are apparently expressed in packets, although there is no section of [\[RFC7003\]](#) titled "Metric Units".

[12.3.5.](#) Run-time Parameters and Data Format

Run-Time Parameters are input factors that must be determined, configured into the measurement system, and reported with the results for the context to be complete. However, the values of these parameters is not specified in the Registry, rather these parameters are listed as an aid to the measurement system implementor or user (they must be left as variables, and supplied on execution).

The Data Format of each Run-time Parameter SHALL be specified in this column, to simplify the control and implementation of measurement devices.

SSRC of Source: 32 bits As defined in [Section 4.1 of \[RFC3611\]](#).

SDP Parameters: As defined in [\[RFC4566\]](#)

Session description v= (protocol version number, currently only 0)

o= (originator and session identifier : username, id, version number, network address)

s= (session name : mandatory with at least one UTF-8-encoded character)

i=* (session title or short information) u=* (URI of description)

e=* (zero or more email address with optional name of contacts)

p=* (zero or more phone number with optional name of contacts)

c=* (connection information--not required if included in all media)

b=* (zero or more bandwidth information lines) One or more Time descriptions ("t=" and "r=" lines; see below)

z=* (time zone adjustments)

k=* (encryption key)

a=* (zero or more session attribute lines)

Zero or more Media descriptions (each one starting by an "m=" line; see below)

m= (media name and transport address)

i=* (media title or information field)

c=* (connection information -- optional if included at session level)

b=* (zero or more bandwidth information lines)

k=* (encryption key)

a=* (zero or more media attribute lines -- overriding the Session attribute lines)

An example Run-time SDP description follows:

v=0

o=jdoe 2890844526 2890842807 IN IP4 192.0.2.5

s=SDP Seminar i=A Seminar on the session description protocol
u=http://www.example.com/seminars/sdp.pdf e=j.doe@example.com (Jane Doe)
c=IN IP4 233.252.0.12/127
t=2873397496 2873404696
a=recvonly
m=audio 49170 RTP/AVP 0
m=video 51372 RTP/AVP 99
a=rtpmap:99 h263-1998/90000

12.4. Comments and Remarks

TBD.

13. Revision History

This section may be removed for publication. It contains overview information on updates.

This draft replaced [draft-mornuley-ippm-initial-registry](#).

In version 02, [Section 4](#) has been edited to reflect recent discussion on the ippm-list: * Removed the combination of "Raw" and left 95th percentile. * Hanging Indent on Run-time parameters (Fixed parameters use bullet lists and other indenting formats. * Payload format for

measurement has been removed. * Explanation of Conditional delay distribution.

Version 03 addressed Phil Eardley's comments and suggestions in sections [1-4](#). and resolved the definition of Percentiles.

Version 04 * All [section 4](#) parameters reference YANG types for

alternate data formats. * Discussion has concluded that usecase(s) for machine parse-able registry columns are not needed.

Version 05 * Revised several Poisson streams to Periodic, sections [4](#) & [5](#). * Addition of ICMP (ping) metrics in [section 9](#). * First implementation of Passive TCP RTT metrics in [section 10](#).

[14](#). Security Considerations

These registry entries represent no known security implications for Internet Security. Each referenced Metric contains a Security Considerations section.

[15](#). IANA Considerations

IANA is requested to populate The Performance Metric Registry defined in [[I-D.ietf-ippm-metric-registry](#)] with the values defined above.

See the IANA Considerations section of [[I-D.ietf-ippm-metric-registry](#)] for additional requests and considerations.

[16](#). Acknowledgements

The authors thank Brian Trammell for suggesting the term "Run-time Parameters", which led to the distinction between run-time and fixed parameters implemented in this memo, for identifying the IPFIX metric with Flow Key as an example, for suggesting the Passive TCP RTD metric and supporting references, and for many other productive suggestions. Thanks to Peter Koch, who provided several useful suggestions for disambiguating successive DNS Queries in the DNS Response time metric.

The authors also acknowledge the constructive reviews and helpful suggestions from Barbara Stark, Juergen Schoenwaelder, Tim Carey, and participants in the LMAP working group. Thanks to Michelle Cotton for her early IANA review, and to Amanda Barber for answering questions related to the presentation of the registry and accessibility of the complete template via URL.

17. References

17.1. Normative References

- [I-D.ietf-ippm-metric-registry]
Bagnulo, M., Claise, B., Eardley, P., and A. Morton,
"Registry for Performance Metrics", Internet Draft (work
in progress) [draft-ietf-ippm-metric-registry](#), 2014.
- [RFC1035] Mockapetris, P., "Domain names - implementation and
specification", STD 13, [RFC 1035](#), DOI 10.17487/RFC1035,
November 1987, <<https://www.rfc-editor.org/info/rfc1035>>.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate
Requirement Levels", [BCP 14](#), [RFC 2119](#),
DOI 10.17487/RFC2119, March 1997,
<<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC2330] Paxson, V., Almes, G., Mahdavi, J., and M. Mathis,
"Framework for IP Performance Metrics", [RFC 2330](#),
DOI 10.17487/RFC2330, May 1998,
<<https://www.rfc-editor.org/info/rfc2330>>.
- [RFC2679] Almes, G., Kalidindi, S., and M. Zekauskas, "A One-way
Delay Metric for IPPM", [RFC 2679](#), DOI 10.17487/RFC2679,
September 1999, <<https://www.rfc-editor.org/info/rfc2679>>.
- [RFC2680] Almes, G., Kalidindi, S., and M. Zekauskas, "A One-way
Packet Loss Metric for IPPM", [RFC 2680](#),
DOI 10.17487/RFC2680, September 1999,
<<https://www.rfc-editor.org/info/rfc2680>>.
- [RFC2681] Almes, G., Kalidindi, S., and M. Zekauskas, "A Round-trip
Delay Metric for IPPM", [RFC 2681](#), DOI 10.17487/RFC2681,
September 1999, <<https://www.rfc-editor.org/info/rfc2681>>.
- [RFC3339] Klyne, G. and C. Newman, "Date and Time on the Internet:
Timestamps", [RFC 3339](#), DOI 10.17487/RFC3339, July 2002,
<<https://www.rfc-editor.org/info/rfc3339>>.
- [RFC3393] Demichelis, C. and P. Chimento, "IP Packet Delay Variation
Metric for IP Performance Metrics (IPPM)", [RFC 3393](#),
DOI 10.17487/RFC3393, November 2002,
<<https://www.rfc-editor.org/info/rfc3393>>.

Internet-Draft

Initial Registry

October 2017

- [RFC3432] Raisanen, V., Grotefeld, G., and A. Morton, "Network performance measurement with periodic streams", [RFC 3432](#), DOI 10.17487/RFC3432, November 2002, <<https://www.rfc-editor.org/info/rfc3432>>.
- [RFC4737] Morton, A., Ciavattone, L., Ramachandran, G., Shalunov, S., and J. Perser, "Packet Reordering Metrics", [RFC 4737](#), DOI 10.17487/RFC4737, November 2006, <<https://www.rfc-editor.org/info/rfc4737>>.
- [RFC5357] Hedayat, K., Krzanowski, R., Morton, A., Yum, K., and J. Babiarez, "A Two-Way Active Measurement Protocol (TWAMP)", [RFC 5357](#), DOI 10.17487/RFC5357, October 2008, <<https://www.rfc-editor.org/info/rfc5357>>.
- [RFC5560] Uijterwaal, H., "A One-Way Packet Duplication Metric", [RFC 5560](#), DOI 10.17487/RFC5560, May 2009, <<https://www.rfc-editor.org/info/rfc5560>>.
- [RFC5905] Mills, D., Martin, J., Ed., Burbank, J., and W. Kasch, "Network Time Protocol Version 4: Protocol and Algorithms Specification", [RFC 5905](#), DOI 10.17487/RFC5905, June 2010, <<https://www.rfc-editor.org/info/rfc5905>>.
- [RFC6020] Bjorklund, M., Ed., "YANG - A Data Modeling Language for the Network Configuration Protocol (NETCONF)", [RFC 6020](#), DOI 10.17487/RFC6020, October 2010, <<https://www.rfc-editor.org/info/rfc6020>>.
- [RFC6049] Morton, A. and E. Stephan, "Spatial Composition of Metrics", [RFC 6049](#), DOI 10.17487/RFC6049, January 2011, <<https://www.rfc-editor.org/info/rfc6049>>.
- [RFC6673] Morton, A., "Round-Trip Packet Loss Metrics", [RFC 6673](#), DOI 10.17487/RFC6673, August 2012, <<https://www.rfc-editor.org/info/rfc6673>>.
- [RFC6991] Schoenwaelder, J., Ed., "Common YANG Data Types", [RFC 6991](#), DOI 10.17487/RFC6991, July 2013, <<https://www.rfc-editor.org/info/rfc6991>>.
- [RFC7011] Claise, B., Ed., Trammell, B., Ed., and P. Aitken, "Specification of the IP Flow Information Export (IPFIX)

Protocol for the Exchange of Flow Information", STD 77, [RFC 7011](#), DOI 10.17487/RFC7011, September 2013, <<https://www.rfc-editor.org/info/rfc7011>>.

Morton, et al.

Expires May 2, 2018

[Page 89]

Internet-Draft

Initial Registry

October 2017

- [RFC7323] Borman, D., Braden, B., Jacobson, V., and R. Scheffenegger, Ed., "TCP Extensions for High Performance", [RFC 7323](#), DOI 10.17487/RFC7323, September 2014, <<https://www.rfc-editor.org/info/rfc7323>>.
- [RFC7679] Almes, G., Kalidindi, S., Zekauskas, M., and A. Morton, Ed., "A One-Way Delay Metric for IP Performance Metrics (IPPM)", STD 81, [RFC 7679](#), DOI 10.17487/RFC7679, January 2016, <<https://www.rfc-editor.org/info/rfc7679>>.
- [RFC7680] Almes, G., Kalidindi, S., Zekauskas, M., and A. Morton, Ed., "A One-Way Loss Metric for IP Performance Metrics (IPPM)", STD 82, [RFC 7680](#), DOI 10.17487/RFC7680, January 2016, <<https://www.rfc-editor.org/info/rfc7680>>.

17.2. Informative References

- [RFC1242] Bradner, S., "Benchmarking Terminology for Network Interconnection Devices", [RFC 1242](#), DOI 10.17487/RFC1242, July 1991, <<https://www.rfc-editor.org/info/rfc1242>>.
- [RFC3611] Friedman, T., Ed., Caceres, R., Ed., and A. Clark, Ed., "RTP Control Protocol Extended Reports (RTCP XR)", [RFC 3611](#), DOI 10.17487/RFC3611, November 2003, <<https://www.rfc-editor.org/info/rfc3611>>.
- [RFC4148] Stephan, E., "IP Performance Metrics (IPPM) Metrics Registry", [BCP 108](#), [RFC 4148](#), DOI 10.17487/RFC4148, August 2005, <<https://www.rfc-editor.org/info/rfc4148>>.
- [RFC4566] Handley, M., Jacobson, V., and C. Perkins, "SDP: Session Description Protocol", [RFC 4566](#), DOI 10.17487/RFC4566, July 2006, <<https://www.rfc-editor.org/info/rfc4566>>.
- [RFC5472] Zseby, T., Boschi, E., Brownlee, N., and B. Claise, "IP Flow Information Export (IPFIX) Applicability", [RFC 5472](#),

DOI 10.17487/RFC5472, March 2009,
<<https://www.rfc-editor.org/info/rfc5472>>.

[RFC5477] Dietz, T., Claise, B., Aitken, P., Dressler, F., and G. Carle, "Information Model for Packet Sampling Exports", [RFC 5477](#), DOI 10.17487/RFC5477, March 2009, <<https://www.rfc-editor.org/info/rfc5477>>.

[RFC5481] Morton, A. and B. Claise, "Packet Delay Variation Applicability Statement", [RFC 5481](#), DOI 10.17487/RFC5481, March 2009, <<https://www.rfc-editor.org/info/rfc5481>>.

Morton, et al.

Expires May 2, 2018

[Page 90]

Internet-Draft

Initial Registry

October 2017

[RFC6248] Morton, A., "[RFC 4148](#) and the IP Performance Metrics (IPPM) Registry of Metrics Are Obsolete", [RFC 6248](#), DOI 10.17487/RFC6248, April 2011, <<https://www.rfc-editor.org/info/rfc6248>>.

[RFC6390] Clark, A. and B. Claise, "Guidelines for Considering New Performance Metric Development", [BCP 170](#), [RFC 6390](#), DOI 10.17487/RFC6390, October 2011, <<https://www.rfc-editor.org/info/rfc6390>>.

[RFC6703] Morton, A., Ramachandran, G., and G. Maguluri, "Reporting IP Network Performance Metrics: Different Points of View", [RFC 6703](#), DOI 10.17487/RFC6703, August 2012, <<https://www.rfc-editor.org/info/rfc6703>>.

[RFC6776] Clark, A. and Q. Wu, "Measurement Identity and Information Reporting Using a Source Description (SDS) Item and an RTCP Extended Report (XR) Block", [RFC 6776](#), DOI 10.17487/RFC6776, October 2012, <<https://www.rfc-editor.org/info/rfc6776>>.

[RFC6792] Wu, Q., Ed., Hunt, G., and P. Arden, "Guidelines for Use of the RTP Monitoring Framework", [RFC 6792](#), DOI 10.17487/RFC6792, November 2012, <<https://www.rfc-editor.org/info/rfc6792>>.

[RFC7003] Clark, A., Huang, R., and Q. Wu, Ed., "RTP Control Protocol (RTCP) Extended Report (XR) Block for Burst/Gap Discard Metric Reporting", [RFC 7003](#), DOI 10.17487/RFC7003,

September 2013, <<https://www.rfc-editor.org/info/rfc7003>>.

[RFC7594] Eardley, P., Morton, A., Bagnulo, M., Burbridge, T., Aitken, P., and A. Akhter, "A Framework for Large-Scale Measurement of Broadband Performance (LMAP)", [RFC 7594](#), DOI 10.17487/RFC7594, September 2015, <<https://www.rfc-editor.org/info/rfc7594>>.

[Strowes] Strowes, S., "Passively Measuring TCP Round Trip Times", September 2013.

[Trammell-14]
Trammell, B., "Inline Data Integrity Signals for Passive Measurement", March 2014.

Morton, et al.

Expires May 2, 2018

[Page 91]

Internet-Draft

Initial Registry

October 2017

Authors' Addresses

Al Morton
AT&T Labs
200 Laurel Avenue South
Middletown,, NJ 07748
USA

Phone: +1 732 420 1571
Fax: +1 732 368 1192
Email: acmorton@att.com
URI: <http://home.comcast.net/~acmacm/>

Marcelo Bagnulo
Universidad Carlos III de Madrid
Av. Universidad 30
Leganes, Madrid 28911
SPAIN

Phone: 34 91 6249500
Email: marcelo@it.uc3m.es

URI: <http://www.it.uc3m.es>

Philip Eardley
BT
Adastral Park, Martlesham Heath
Ipswich
ENGLAND

Email: philip.eardley@bt.com

Kevin D'Souza
AT&T Labs
200 Laurel Avenue South
Middletown,, NJ 07748
USA

Phone: +1 732 420 xxxx
Email: kld@att.com