

Workgroup: IPPM
Internet-Draft: draft-ietf-ippm-ioam-yang-04
Published: 7 July 2022
Intended Status: Standards Track
Expires: 8 January 2023
Authors: T. Zhou, Ed. J. Guichard F. Brockners
 Huawei Futurewei Cisco Systems
 S. Raghavan
 Cisco Systems

A YANG Data Model for In-Situ OAM

Abstract

In-situ Operations, Administration, and Maintenance (IOAM) records operational and telemetry information in user packets while the packets traverse a path between two points in the network. This document defines a YANG module for the IOAM function.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 8 January 2023.

Copyright Notice

Copyright (c) 2022 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Revised BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Revised BSD License.

Table of Contents

- [1. Introduction](#)
- [2. Conventions used in this document](#)
 - [2.1. Tree Diagrams](#)
- [3. Design of the IOAM YANG Data Model](#)
 - [3.1. Overview](#)
 - [3.2. Preallocated Tracing Profile](#)
 - [3.3. Incremental Tracing Profile](#)
 - [3.4. Direct Export Profile](#)
 - [3.5. Proof of Transit Profile](#)
 - [3.6. Edge to Edge Profile](#)
- [4. IOAM YANG Module](#)
- [5. Security Considerations](#)
- [6. IANA Considerations](#)
- [7. Acknowledgements](#)
- [8. References](#)
 - [8.1. Normative References](#)
 - [8.2. Informative References](#)
- [Appendix A. Examples](#)
- [Authors' Addresses](#)

1. Introduction

In-situ Operations, Administration, and Maintenance (IOAM) [[I-D.ietf-ippm-ioam-data](#)] records OAM information within user packets while the packets traverse a network. The data types and data formats for IOAM data records have been defined in [[I-D.ietf-ippm-ioam-data](#)]. The IOAM data can be embedded in many protocol encapsulations such as Network Services Header (NSH) and IPv6.

This document defines a data model for IOAM capabilities using the [YANG data modeling language](#) [[RFC7950](#)]. This YANG model supports five IOAM options, which are:

- *[Incremental Tracing Option](#) [[I-D.ietf-ippm-ioam-data](#)]
- *[Pre-allocated Tracing Option](#) [[I-D.ietf-ippm-ioam-data](#)]
- *[Direct Export Option](#) [[I-D.ietf-ippm-ioam-direct-export](#)]
- *[Proof of Transit \(PoT\) Option](#) [[I-D.ietf-ippm-ioam-data](#)]
- *[Edge-to-Edge Option](#) [[I-D.ietf-ippm-ioam-data](#)]

2. Conventions used in this document

The keywords "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in

BCP14, [[RFC2119](#)], [[RFC8174](#)] when, and only when, they appear in all capitals, as shown here.

The following terms are defined in [[RFC7950](#)] and are used in this specification:

- *augment

- *data model

- *data node

The terminology for describing YANG data models is found in [[RFC7950](#)].

2.1. Tree Diagrams

Tree diagrams used in this document follow the notation defined in [[RFC8340](#)].

3. Design of the IOAM YANG Data Model

3.1. Overview

The IOAM model is organized as list of profiles as shown in the following figure. Each profile associates with one flow and the corresponding IOAM information.

The "ioam-info" is a container for all the read only assistant information, so that monitoring systems can interpret the IOAM data.

```

module: ietf-ioam
+--rw ioam
  +--ro ioam-info
    | +--ro timestamp-type?      identityref
    | +--ro available-interface* [if-name]
    |   +--ro if-name      if:interface-ref
  +--rw ioam-profiles
    +--rw admin-config
      | +--rw enabled?    boolean
    +--rw ioam-profile* [profile-name]
      +--rw profile-name          string
      +--rw filter
        | +--rw filter-type?    ioam-filter-type
        | +--rw ace-name?      -> /acl:acls/acl/aces/ace/name
      +--rw protocol-type?          ioam-protocol-type
      +--rw incremental-tracing-profile {incremental-trace}?
        | ...
      +--rw preallocated-tracing-profile {preallocated-trace}?
        | ...
      +--rw direct-export-profile {direct-export}?
        | ...
      +--rw pot-profile {proof-of-transit}?
        | ...
      +--rw e2e-profile {edge-to-edge}?
        ...

```

In the "ioam-profiles", the "enabled" is an administrative configuration. When it is set to true, IOAM configuration is enabled for the system. Meanwhile, the IOAM data-plane functionality is enabled.

The "filter" is used to identify a flow, where the IOAM profile can apply. There may be multiple filter types. [ACL](#) [[RFC8519](#)] is a common way to specify a flow. Each IOAM profile can associate with an ACE(Access Control Entry). IOAM actions MUST be driven by the accepted packets, when the matched ACE "forwarding" action is "accept".

The IOAM data can be encapsulated into multiple protocols, e.g., [IPv6](#) [[I-D.ietf-ippm-ioam-ipv6-options](#)] and [NSH](#) [[I-D.ietf-sfc-ioam-nsh](#)]. The "protocol-type" is used to indicate where the IOAM is applied. For example, if the "protocol-type" is IPv6, the IOAM ingress node will encapsulate the associated flow with the [IPv6-IOAM](#) [[I-D.ietf-ippm-ioam-ipv6-options](#)] format.

IOAM data includes five encapsulation types, i.e., incremental tracing data, preallocated tracing data, direct export data, proof of transit data and end to end data. In practice, multiple IOAM data types can be encapsulated into the same IOAM header. The "ioam-

profile" contains a set of sub-profiles, each of which relates to one encapsulation type. The configured object may not support all the sub-profiles. The supported sub-profiles are indicated by 5 defined features, i.e., "incremental-trace", "preallocated-trace", "direct export", "proof-of-transit", "edge-to-edge".

3.2. Preallocated Tracing Profile

The IOAM tracing data is expected to be collected at every node that a packet traverses to ensure visibility into the entire path a packet takes within an IOAM domain. The preallocated tracing option will create pre-allocated space for each node to populate its information. The "preallocated-tracing-profile" contains the detailed information for the preallocated tracing data. The information includes:

- *enabled: indicates whether the preallocated tracing profile is enabled.
- *node-action: indicates the operation (e.g., encapsulate IOAM header, transit the IOAM data, or decapsulate IOAM header) applied to the dedicated flow.
- *use-namespace: indicate the namespace used for the trace types.
- *trace-type: indicates the per-hop data to be captured by the IOAM enabled nodes and included in the node data list.
- *Loopback mode is used to send a copy of a packet back towards the source.
- *Active mode indicates that a packet is used for active measurement.

```
+--rw preallocated-tracing-profile {preallocated-trace}?
  +--rw enabled?                boolean
  +--rw node-action?            ioam-node-action
  +--rw trace-types
  |   +--rw use-namespace?      ioam-namespace
  |   +--rw trace-type*         ioam-trace-type
  +--rw enable-loopback-mode?    boolean
  +--rw enable-active-mode?      boolean
```

3.3. Incremental Tracing Profile

The incremental tracing option contains a variable node data fields where each node allocates and pushes its node data immediately following the option header. The "incremental-tracing-profile" contains the detailed information for the incremental tracing data. The detailed information is the same as the Preallocated Tracing

Profile, but with one more variable, "max-length", which restricts the length of the IOAM header.

```
+--rw incremental-tracing-profile {incremental-trace}?
  +--rw enabled?          boolean
  +--rw node-action?      ioam-node-action
  +--rw trace-types
  |  +--rw use-namespace?  ioam-namespace
  |  +--rw trace-type*     ioam-trace-type
  +--rw enable-loopback-mode?  boolean
  +--rw enable-active-mode?   boolean
  +--rw max-length?         uint32
```

3.4. Direct Export Profile

The direct export option is used as a trigger for IOAM nodes to export IOAM data to a receiving entity (or entities). The "direct-export-profile" contains the detailed information for the direct export data. The detailed information is the same as the Preallocated Tracing Profile, but with one more optional variable, "flow-id", which is used to correlate the exported data of the same flow from multiple nodes and from multiple packets.

```
+--rw direct-export-profile {direct-export}?
  +--rw enabled?          boolean
  +--rw node-action?      ioam-node-action
  +--rw trace-types
  |  +--rw use-namespace?  ioam-namespace
  |  +--rw trace-type*     ioam-trace-type
  +--rw enable-loopback-mode?  boolean
  +--rw enable-active-mode?   boolean
  +--rw flow-id?           uint32
```

3.5. Proof of Transit Profile

The IOAM Proof of Transit data is to support the path or service function chain verification use cases. The "pot-profile" contains the detailed information for the proof of transit data. "pot-type" indicates a particular POT variant that specifies the POT data that is included. There may be several POT types, which have different configuration data. To align with [\[I-D.ietf-ippm-ioam-data\]](#), this document only defines IOAM POT type 0. User need to augment this module for the configuration of a specific POT type.

```
+--rw pot-profile {proof-of-transit}?
  +--rw enabled?      boolean
  +--rw pot-type?     ioam-pot-type
```

3.6. Edge to Edge Profile

The IOAM edge to edge option is to carry data that is added by the IOAM encapsulating node and interpreted by IOAM decapsulating node. The "e2e-profile" contains the detailed information for the edge to edge data. The detailed information includes:

*enabled: indicates whether the edge to edge profile is enabled.

*node-action is the same semantic as in Section 2.2.

*use-namespace: indicate the namespace used for the edge to edge types.

*e2e-type indicates data to be carried from the ingress IOAM node to the egress IOAM node.

```
+--rw e2e-profile {edge-to-edge}?
  +--rw enabled?          boolean
  +--rw node-action?      ioam-node-action
  +--rw e2e-types
    +--rw use-namespace?  ioam-namespace
    +--rw e2e-type*       ioam-e2e-type
```

4. IOAM YANG Module

<CODE BEGINS> file "ietf-ioam@2022-07-07.yang"

```
module ietf-ioam {
  yang-version 1.1;
  namespace "urn:ietf:params:xml:ns:yang:ietf-ioam";
  prefix "ioam";

  import ietf-access-control-list {
    prefix "acl";
    reference
      "RFC 8519: YANG Data Model for Network Access Control
       Lists (ACLs)";
  }

  import ietf-interfaces {
    prefix "if";
    reference
      "RFC 8343: A YANG Data Model for Interface Management";
  }

  import ietf-lime-time-types {
    prefix "lime";
    reference
      "RFC 8532: Generic YANG Data Model for the Management of
       Operations, Administration, and Maintenance (OAM) Protocols
       That Use Connectionless Communications";
  }

  organization
    "IETF IPPM (IP Performance Metrics) Working Group";

  contact
    "WG Web: <https://datatracker.ietf.org/wg/ippm>
    WG List: <ippm@ietf.org>
    Editor: zhoutianran@huawei.com
    Editor: james.n.guichard@futurewei.com
    Editor: fbrockne@cisco.com
    Editor: srihari@cisco.com";

  description
    "This YANG module specifies a vendor-independent data
    model for the In Situ OAM (IOAM)."
```

Copyright (c) 2021 IETF Trust and the persons identified as
authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or
without modification, is permitted pursuant to, and subject
to the license terms contained in, the Simplified BSD License
set forth in Section 4.c of the IETF Trust's Legal Provisions

Relating to IETF Documents
(<http://trustee.ietf.org/license-info>).

This version of this YANG module is part of RFC XXXX; see the RFC itself for full legal notices.";

```
revision 2022-07-07 {
  description "First revision.";
  reference "RFC XXXX: A YANG Data Model for In-Situ OAM";
}

/*
 * FEATURES
 */

feature incremental-trace
{
  description
    "This feature indicated that the incremental tracing option is
    supported";
  reference "RFC 9197: Data Fields for In-situ OAM";
}

feature preallocated-trace
{
  description
    "This feature indicated that the preallocated tracing option is
    supported";
  reference "RFC 9197: Data Fields for In-situ OAM";
}

feature direct-export
{
  description
    "This feature indicated that the direct export option is
    supported";
  reference "RFC XXXX: In-situ OAM Direct Exporting";
}

feature proof-of-transit
{
  description
    "This feature indicated that the proof of transit option is
    supported";
  reference "RFC 9197: Data Fields for In-situ OAM";
}

feature edge-to-edge
{
  description
```

```

        "This feature indicated that the edge to edge option is
        supported";
    reference "RFC 9197: Data Fields for In-situ OAM";
}

/*
 * IDENTITIES
 */
identity filter {
    description
        "Base identity to represent a filter. A filter is used to
        specify the flow to apply the IOAM profile. ";
}

identity acl-filter {
    base filter;
    description
        "Apply ACL rules to specify the flow.";
}

identity protocol {
    description
        "Base identity to represent the carrier protocol. It's used to
        indicate what layer and protocol the IOAM data is embedded.";
}

identity ipv6 {
    base protocol;
    description
        "The described IOAM data is embedded in IPv6 protocol.";
    reference "RFC XXXX: In-situ OAM IPv6 Options";
}

identity nsh {
    base protocol;
    description
        "The described IOAM data is embedded in NSH.";
    reference
        "RFC XXXX: Network Service Header (NSH) Encapsulation
        for In-situ OAM (IOAM) Data";
}

identity node-action {
    description
        "Base identity to represent the node actions. It's used to
        indicate what action the node will take.";
}

identity action-encapsulate {

```

```

    base node-action;
    description
        "It indicates the node is to encapsulate the IOAM packet";
}

identity action-decapsulate {
    base node-action;
    description
        "It indicates the node is to decapsulate the IOAM packet";
}

identity trace-type {
    description
        "Base identity to represent trace types.";
}

identity trace-hop-lim-node-id {
    base trace-type;
    description
        "It indicates the presence of Hop_Lim and node_id in the
        node data.";
}

identity trace-if-id {
    base trace-type;
    description
        "It indicates presence of ingress_if_id and egress_if_id
        (short format) in the node data.";
}

identity trace-timestamp-seconds {
    base trace-type;
    description
        "It indicates presence of timestamp seconds in the node data.";
}

identity trace-timestamp-fraction {
    base trace-type;
    description
        "It indicates presence of timestamp fraction in the node data.";
}

identity trace-transit-delay {
    base trace-type;
    description
        "It indicates presence of transit delay in the node data.";
}

identity trace-namespace-data {
    base trace-type;

```

```

    description
        "It indicates presence of name space specific data (short format)
        in the node data.";
}

identity trace-queue-depth {
    base trace-type;
    description
        "It indicates presence of queue depth in the node data.";
}

identity trace-checksum-complement {
    base trace-type;
    description
        "It indicates presence of the Checksum Complement node data.";
}

identity trace-hop-lim-node-id-wide {
    base trace-type;
    description
        "It indicates presence of Hop_Lim and node_id in wide format
        in the node data.";
}

identity trace-if-id-wide {
    base trace-type;
    description
        "It indicates presence of ingress_if_id and egress_if_id in
        wide format in the node data.";
}

identity trace-namespace-data-wide {
    base trace-type;
    description
        "It indicates presence of IOAM-Namespace specific data in wide
        format in the node data.";
}

identity trace-buffer-occupancy {
    base trace-type;
    description
        "It indicates presence of buffer occupancy in the node data.";
}

identity trace-opaque-state-snapshot {
    base trace-type;
    description
        "It indicates presence of variable length Opaque State Snapshot
        field.";
}

```

```

}

identity pot-type {
    description
        "Base identity to represent Proof of Transit (PoT) types.";
}

identity pot-type-0 {
    base pot-type;
    description
        "The IOAM POT Type field value is 0, and POT data is a 16
        Octet field to carry data associated to POT procedures.";
}

identity e2e-type {
    description
        "Base identity to represent e2e types";
}

identity e2e-seq-num-64 {
    base e2e-type;
    description
        "It indicates presence of a 64-bit sequence number.";
}

identity e2e-seq-num-32 {
    base e2e-type;
    description
        "It indicates the presence of a 32-bit sequence number.";
}

identity e2e-timestamp-seconds {
    base e2e-type;
    description
        "It indicates the presence of timestamp seconds representing
        the time at which the packet entered the IOAM-domain";
}

identity e2e-timestamp-fraction {
    base e2e-type;
    description
        "It indicates the presence of timestamp fraction representing
        the time at which the packet entered the IOAM-domain.";
}

identity namespace {
    description
        "Base identity to represent the Namespace-ID.";
}

```

```

identity default-namespace {
    base namespace;
    description
        "The Namespace-ID value of 0x0000 is defined as the
        Default-Namespace-ID and must be known to all the nodes
        implementing IOAM.";
}

/*
 * TYPE DEFINITIONS
 */
typedef ioam-filter-type {
    type identityref {
        base filter;
    }
    description
        "It specifies a known type of filter.";
}

typedef ioam-protocol-type {
    type identityref {
        base protocol;
    }
    description
        "It specifies a known type of carrier protocol for the IOAM
        data.";
}

typedef ioam-node-action {
    type identityref {
        base node-action;
    }
    description
        "It specifies a known type of node action.";
}

typedef ioam-trace-type {
    type identityref {
        base trace-type;
    }
    description
        "It specifies a known trace type.";
}

typedef ioam-pot-type {
    type identityref {
        base pot-type;
    }
    description

```

```

        "It specifies a known pot type.";
    }

typedef ioam-e2e-type {
    type identityref {
        base e2e-type;
    }
    description
        "It specifies a known e2e type.";
}

typedef ioam-namespace {
    type identityref {
        base namespace;
    }
    description
        "It specifies the supported namespace.";
}

/*
 * GROUP DEFINITIONS
 */

grouping ioam-filter {
    description "A grouping for IOAM filter definition";

    leaf filter-type {
        type ioam-filter-type;
        description "filter type";
    }

    leaf ace-name {
        when "derived-from-or-self(..../filter-type, 'ioam:acl-filter')";
        type leafref {
            path "/acl:acls/acl:acl/acl:aces/acl:ace/acl:name";
        }
        description "The Access Control Entry name is used to
            refer to an ACL specification.";
    }
}

grouping encap-tracing {
    description
        "A grouping for the generic configuration for
            tracing profile.";

    container trace-types {
        description
            "It indicates the list of trace types for encapsulation";
    }
}

```

```

leaf use-namespace {
    type ioam-namespace;
    description
        "It indicates the name space used for encapsulation";
}

leaf-list trace-type {
    type ioam-trace-type;
    description
        "The trace type is only defined at the encapsulation node.";
}
}

leaf enable-loopback-mode {
    type boolean;
    default false;
    description
        "Loopback mode is used to send a copy of a packet back towards
        the source. The loopback mode is only defined at the
        encapsulation node.";
}

leaf enable-active-mode {
    type boolean;
    default false;
    description
        "Active mode indicates that a packet is used for active
        measurement. An IOAM decapsulating node that receives a
        packet with the Active flag set in one of its Trace options
        must terminate the packet.";
}
}

grouping ioam-incremental-tracing-profile {
    description
        "A grouping for incremental tracing profile.";

    leaf node-action {
        type ioam-node-action;
        description
            "This object indicates the action the node need to
            take, e.g. encapsulation.";
    }

    uses encap-tracing {
        when "derived-from-or-self(node-action,
            'ioam:action-encapsulate')";
    }
}

```



```

leaf max-length {
  when "derived-from-or-self(..../node-action,
    'ioam:action-encapsulate')";
  type uint32;
  units bytes;
  description
    "This field specifies the maximum length of the node data list
    in octets. The max-length is only defined at the
    encapsulation node, and it's only used for the incremental
    tracing mode.";
}
}

grouping ioam-preallocated-tracing-profile {
  description
    "A grouping for incremental tracing profile.";

  leaf node-action {
    type ioam-node-action;
    description "This indicates what action the node will take,
      e.g. encapsulation.";
  }

  uses encap-tracing {
    when "derived-from-or-self(node-action,
      'ioam:action-encapsulate')";
  }
}

grouping ioam-direct-export-profile {
  description
    "A grouping for direct export profile.";

  leaf node-action {
    type ioam-node-action;
    description "This indicates what action the node will take,
      e.g. encapsulation.";
  }

  uses encap-tracing {
    when "derived-from-or-self(node-action,
      'ioam:action-encapsulate')";
  }

  leaf flow-id {
    when "derived-from-or-self(..../node-action,
      'ioam:action-encapsulate')";
    type uint32;
    description

```

```

        "A 32-bit flow identifier. The field is set at the
        encapsulating node. The Flow ID can be uniformly assigned
        by a central controller or algorithmically generated by the
        encapsulating node. The latter approach cannot guarantee
        the uniqueness of Flow ID, yet the conflict probability is
        small due to the large Flow ID space.flow-id is used to
        correlate the exported data of the same flow from multiple
        nodes and from multiple packets.";
    }
}

grouping ioam-e2e-profile {
    description
        "A grouping for edge-to-edge profile.";

    leaf node-action {
        type ioam-node-action;
        description
            "It indicates how the node acts for this profile";
    }

    container e2e-types {
        when "derived-from-or-self(..../node-action,
            'ioam:action-encapsulate')";

        description
            "It indicates the list of e2e types for encapsulation";

        leaf use-namespace {
            type ioam-namespace;
            description
                "It indicates the name space used for encapsulation";
        }

        leaf-list e2e-type {
            type ioam-e2e-type;
            description
                "The e2e type is only defined at the encapsulation node.";
        }
    }
}

grouping ioam-admin-config {
    description
        "IOAM top-level administrative configuration.";

    leaf enabled {
        type boolean;
        default false;
        description

```

```

        "This object is to control the availability of configuration.
        It must be true before anything in the
        /ioam/ioam-profiles/ioam-profile subtree can be edited.
        If false, any configuration in place is not used.";
    }
}

/*
 * DATA NODES
 */

container ioam {
    description "IOAM top level container";

    container ioam-info {
        config false;
        description
            "Describes assistant information such as units or timestamp
            format. So that monitoring systems can interpret the IOAM
            data.";

        leaf timestamp-type {
            type identityref {
                base lime:timestamp-type;
            }
            description
                "Type of timestamp, such as Truncated PTP or NTP.";
        }

        list available-interface {
            key "if-name";
            description
                "A list of available interfaces that support IOAM.";
            leaf if-name {
                type if:interface-ref;
                description "This is a reference to the Interface name.";
            }
        }
    }

    container ioam-profiles {
        description
            "Contains a list of IOAM profiles.";

        container admin-config {
            description
                "Contains all the administrative configurations related to
                the IOAM functionalities and all the IOAM profiles.";

            uses ioam-admin-config;
        }
    }
}

```

```

}

list ioam-profile {
  key "profile-name";
  description
    "A list of IOAM profiles that configured on the node.
    There is no mandatory type of profile (e.g.,
    incremental-trace, preallocated-trace.) in the list.
    But at least one profile should be added.";

  leaf profile-name {
    type string{
      length "1 .. max";
    }
    description
      "Unique identifier for each IOAM profile";
  }

  container filter {
    uses ioam-filter;
    description
      "The filter which is used to indicate the flow to apply
      IOAM.";
  }

  leaf protocol-type {
    type ioam-protocol-type;
    description
      "This item is used to indicate the carrier protocol where
      the IOAM is applied.";
  }

  container incremental-tracing-profile {
    if-feature incremental-trace;
    description
      "It describes the profile for incremental tracing option";

    leaf enabled {
      type boolean;
      default false;
      description
        "When true, apply incremental tracing option to the
        specified flow identified by the filter.";
    }

    uses ioam-incremental-tracing-profile;
  }

  container preallocated-tracing-profile {
    if-feature preallocated-trace;

```

```

description
    "It describes the profile for preallocated tracing option";

leaf enabled {
    type boolean;
    default false;
    description
        "When true, apply preallocated tracing option to the
        specified flow identified by the following filter.";
}

uses ioam-preallocated-tracing-profile;
}

container direct-export-profile {
    if-feature direct-export;
    description
        "It describes the profile for direct-export option";

    leaf enabled {
        type boolean;
        default false;
        description
            "When true, apply direct-export option to the
            specified flow identified by the following filter.";
    }

    uses ioam-direct-export-profile;
}

container pot-profile {
    if-feature proof-of-transit;
    description
        "It describes the profile for PoT option";

    leaf enabled {
        type boolean;
        default false;
        description
            "When true, apply Proof of Transit option to the
            specified flow identified by the following filter.";
    }

    leaf pot-type {
        type ioam-pot-type;
        description
            "The type of a particular POT variant that specifies
            the POT data that is included..";
    }
}
}

```

```

    container e2e-profile {
      if-feature edge-to-edge;
      description
        "It describes the profile for e2e option";

      leaf enabled {
        type boolean;
        default false;
        description
          "When true, apply edge-to-edge option to the
            specified flow identified by the following filter.";
      }

      uses ioam-e2e-profile;
    }
  }
}
}
}
<CODE ENDS>

```

5. Security Considerations

The YANG module specified in this document defines a schema for data that is designed to be accessed via network management protocols such as [NETCONF](#) [RFC6241] or [RESTCONF](#) [RFC8040]. The lowest NETCONF layer is the secure transport layer, and the mandatory-to-implement secure transport is [Secure Shell \(SSH\)](#) [RFC6242]. The lowest RESTCONF layer is HTTPS, and the mandatory-to-implement secure transport is [TLS](#) [RFC8446].

The [Network Configuration Access Control Model \(NACM\)](#) [RFC8341] provides the means to restrict access for particular NETCONF or RESTCONF users to a preconfigured subset of all available NETCONF or RESTCONF protocol operations and content.

There are a number of data nodes defined in this YANG module that are writable/creatable/deletable (i.e., config true, which is the default). These data nodes may be considered sensitive or vulnerable in some network environments. Write operations (e.g., edit-config) to these data nodes without proper protection can have a negative effect on network operations. These are the subtrees and data nodes and their sensitivity/vulnerability:

```

*/ioam/ioam-profiles/admin-config

```

The items in the container above include the top level administrative configurations related to the IOAM functionalities and all the IOAM profiles. Unexpected changes to these items could lead to the IOAM function disruption and/ or misbehavior of all the IOAM profiles.

`*/ioam/ioam-profiles/ioam-profile`

The entries in the list above include the whole IOAM profile configurations which indirectly create or modify the device configurations. Unexpected changes to these entries could lead to the mistake of the IOAM behavior for the corresponding flows.

6. IANA Considerations

RFC Ed.: In this section, replace all occurrences of 'XXXX' with the actual RFC number (and remove this note).

IANA is requested to assign a new URI from the [IETF XML Registry](#) [[RFC3688](#)]. The following URI is suggested:

URI: urn:ietf:params:xml:ns:yang:ietf-ioam
Registrant Contact: The IESG.
XML: N/A; the requested URI is an XML namespace.

This document also requests a new YANG module name in the [YANG Module Names registry](#) [[RFC7950](#)] with the following suggestion:

name: ietf-ioam
namespace: urn:ietf:params:xml:ns:yang:ietf-ioam
prefix: ioam
reference: RFC XXXX

7. Acknowledgements

For their valuable comments, discussions, and feedback, we wish to acknowledge Greg Mirsky, Reshad Rahman, Tom Petch and Mickey Spiegel.

8. References

8.1. Normative References

[I-D.ietf-ippm-ioam-data] Brockners, F., Bhandari, S., and T. Mizrahi, "Data Fields for In Situ Operations, Administration, and Maintenance (IOAM)", Work in Progress, Internet-Draft, draft-ietf-ippm-ioam-data-17, 13 December 2021, <<https://www.ietf.org/archive/id/draft-ietf-ippm-ioam-data-17.txt>>.

[I-D.ietf-ippm-ioam-direct-export]

Song, H., Gafni, B., Brockners, F., Bhandari, S., and T. Mizrahi, "In-situ OAM Direct Exporting", Work in Progress, Internet-Draft, draft-ietf-ippm-ioam-direct-export-09, 15 June 2022, <<https://www.ietf.org/archive/id/draft-ietf-ippm-ioam-direct-export-09.txt>>.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.

[RFC3688] Mealling, M., "The IETF XML Registry", BCP 81, RFC 3688, DOI 10.17487/RFC3688, January 2004, <<https://www.rfc-editor.org/info/rfc3688>>.

[RFC6241] Enns, R., Ed., Bjorklund, M., Ed., Schoenwaelder, J., Ed., and A. Bierman, Ed., "Network Configuration Protocol (NETCONF)", RFC 6241, DOI 10.17487/RFC6241, June 2011, <<https://www.rfc-editor.org/info/rfc6241>>.

[RFC6242] Wasserman, M., "Using the NETCONF Protocol over Secure Shell (SSH)", RFC 6242, DOI 10.17487/RFC6242, June 2011, <<https://www.rfc-editor.org/info/rfc6242>>.

[RFC7950] Bjorklund, M., Ed., "The YANG 1.1 Data Modeling Language", RFC 7950, DOI 10.17487/RFC7950, August 2016, <<https://www.rfc-editor.org/info/rfc7950>>.

[RFC8040] Bierman, A., Bjorklund, M., and K. Watsen, "RESTCONF Protocol", RFC 8040, DOI 10.17487/RFC8040, January 2017, <<https://www.rfc-editor.org/info/rfc8040>>.

[RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in RFC 2119 Key Words", BCP 14, RFC 8174, DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.

[RFC8340] Bjorklund, M. and L. Berger, Ed., "YANG Tree Diagrams", BCP 215, RFC 8340, DOI 10.17487/RFC8340, March 2018, <<https://www.rfc-editor.org/info/rfc8340>>.

[RFC8341] Bierman, A. and M. Bjorklund, "Network Configuration Access Control Model", STD 91, RFC 8341, DOI 10.17487/RFC8341, March 2018, <<https://www.rfc-editor.org/info/rfc8341>>.

[RFC8446] Rescorla, E., "The Transport Layer Security (TLS) Protocol Version 1.3", RFC 8446, DOI 10.17487/RFC8446, August 2018, <<https://www.rfc-editor.org/info/rfc8446>>.

[RFC8519]

Jethanandani, M., Agarwal, S., Huang, L., and D. Blair,
"YANG Data Model for Network Access Control Lists
(ACLs)", RFC 8519, DOI 10.17487/RFC8519, March 2019,
<<https://www.rfc-editor.org/info/rfc8519>>.

[RFC8532]

Kumar, D., Wang, Z., Wu, Q., Ed., Rahman, R., and S.
Raghavan, "Generic YANG Data Model for the Management of
Operations, Administration, and Maintenance (OAM)
Protocols That Use Connectionless Communications", RFC
8532, DOI 10.17487/RFC8532, April 2019, <<https://www.rfc-editor.org/info/rfc8532>>.

8.2. Informative References

[I-D.ietf-ippm-ioam-ipv6-options] Bhandari, S. and F. Brockners,
"In-situ OAM IPv6 Options", Work in Progress, Internet-
Draft, draft-ietf-ippm-ioam-ipv6-options-08, 16 June
2022, <<https://www.ietf.org/archive/id/draft-ietf-ippm-ioam-ipv6-options-08.txt>>.

[I-D.ietf-sfc-ioam-nsh] Brockners, F. and S. Bhandari, "Network
Service Header (NSH) Encapsulation for In-situ OAM (IOAM)
Data", Work in Progress, Internet-Draft, draft-ietf-sfc-
ioam-nsh-10, 18 May 2022, <<https://www.ietf.org/archive/id/draft-ietf-sfc-ioam-nsh-10.txt>>.

Appendix A. Examples

This appendix is non-normative.

tbd

Authors' Addresses

Tianran Zhou
Huawei
156 Beiqing Rd.
Beijing
100095
China

Email: zhoutianran@huawei.com

Jim Guichard
Futurewei
United States of America

Email: james.n.guichard@futurewei.com

Frank Brockners
Cisco Systems
Hansaallee 249, 3rd Floor
40549 Duesseldorf
Germany

Email: fbrockne@cisco.com

Srihari Raghavan
Cisco Systems
Tril Infopark Sez, Ramanujan IT City
Neville Block, 2nd floor, Old Mahabalipuram Road
Chennai 600113
Tamil Nadu
India

Email: srihari@cisco.com