

Network Working Group
INTERNET-DRAFT
Expiration Date: December 1998

G. Almes
S. Kalidindi
M. Zekauskas
Advanced Network & Services
June 1998

A Packet Loss Metric for IPPM
<[draft-ietf-ippm-loss-03.txt](#)>

1. Status of this Memo

This document is an Internet-Draft. Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet Drafts.

Internet-Drafts are draft documents valid for a maximum of six months, and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

To view the entire list of current Internet-Drafts, please check the "1id-abstracts.txt" listing contained in the Internet-Drafts shadow directories on ftp.is.co.za (Africa), nic.nordu.net (Northern Europe), ftp.nis.garr.it (Southern Europe), munnari.oz.au (Pacific Rim), ftp.ietf.org (US East Coast), or ftp.isi.edu (US West Coast).

This memo provides information for the Internet community. This memo does not specify an Internet standard of any kind. Distribution of this memo is unlimited.

2. Introduction

This memo defines a metric for packet loss across Internet paths. It builds on notions introduced and discussed in the IPPM Framework document, [RFC 2330](#) [1]; the reader is assumed to be familiar with that document.

This memo is intended to be parallel in structure to a companion document for One-way Delay (currently "A One-way Delay Metric for IPPM" <[draft-ietf-ippm-delay-02.txt](#)>) [2]; the reader is assumed to be familiar with that document.

The structure of the memo is as follows:

INTERNET-DRAFT

Packet Loss

June 1998

- + A 'singleton' analytic metric, called Type-P-One-way-Loss, is introduced to measure a single observation of packet transmission or loss.
- + Using this singleton metric, a 'sample', called Type-P-One-way-Loss-Poisson-Stream, is introduced to measure a sequence of singleton transmissions and/or losses measured at times taken from a Poisson process.
- + Using this sample, several 'statistics' of the sample are defined and discussed.

This progression from singleton to sample to statistics, with clear separation among them, is important.

Whenever a technical term from the IPPM Framework document is first used in this memo, it will be tagged with a trailing asterisk. For example, "term*" indicates that "term" is defined in the Framework.

2.1. Motivation:

Understanding one-way packet loss of type-P* packets from a source host* to a destination host is useful for several reasons:

- + Some applications do not perform well (or at all) if end-to-end loss between hosts is large relative to some threshold value.
- + Excessive packet loss may make it difficult to support certain real-time applications (where the precise threshold of "excessive" depends on the application).
- + The larger the value of packet loss, the more difficult it is for transport-layer protocols to sustain high bandwidths.
- + The sensitivity of real-time applications and of transport-layer protocols to loss become especially important when very large delay-bandwidth products must be supported.

It is outside the scope of this document to say precisely how loss metrics would be applied to specific problems.

[2.2.](#) General Issues Regarding Time

Whenever a time (i.e., a moment in history) is mentioned here, it is understood to be measured in seconds (and fractions) relative to UTC.

As described more fully in the Framework document, there are four distinct, but related notions of clock uncertainty:

synchronization*

Synchronization measures the extent to which two clocks agree on what time it is. For example, the clock on one host might be 5.4 msec ahead of the clock on a second host.

accuracy*

Accuracy measures the extent to which a given clock agrees with UTC. For example, the clock on a host might be 27.1 msec behind UTC.

resolution*

Resolution measures the precision of a given clock. For example, the clock on an old Unix host might advance only once every 10 msec, and thus have a resolution of only 10 msec.

skew*

Skew measures the change of accuracy, or of synchronization, with time. For example, the clock on a given host might gain 1.3 msec per hour and thus be 27.1 msec behind UTC at one time and only 25.8 msec an hour later. In this case, we say that the clock of the given host has a skew of 1.3 msec per hour relative to UTC, and this threatens accuracy. We might also speak of the skew of one clock relative to another clock, and this threatens synchronization.

[3.](#) A Singleton Definition for One-way Packet Loss

[3.1.](#) Metric Name:

Type-P-One-way-Packet-Loss

Almes et al.

[Page 3]

INTERNET-DRAFT

Packet Loss

June 1998

[3.2.](#) Metric Parameters:

- + Src, the IP address of a host
- + Dst, the IP address of a host
- + T, a time

[3.3.](#) Metric Units:

The value of a Type-P-One-way-Packet-Loss is either a zero (signifying successful transmission of the packet) or a one (signifying loss).

[3.4.](#) Definition:

>>The *Type-P-One-way-Packet-Loss* from Src to Dst at T is 0<< means that Src sent the first bit of a type-P packet to Dst at wire-time* T and that Dst received that packet.

>>The *Type-P-One-way-Packet-Loss* from Src to Dst at T is 1<< means that Src sent the first bit of a type-P packet to Dst at wire-time T and that Dst did not receive that packet.

[3.5.](#) Discussion:

Thus, Type-P-One-way-Packet-Loss is 0 exactly when Type-P-One-way-Delay is a finite positive value, and it is 1 exactly when Type-P-One-way-Delay is undefined.

The following issues are likely to come up in practice:

- + A given methodology will have to include a way to distinguish between a packet loss and a very large (but finite) delay. As noted by Mahdavi and Paxson [3], simple upper bounds (such as the 255 seconds theoretical upper bound on the lifetimes of IP packets [4]) could be used, but good engineering, including an understanding of packet lifetimes, will be needed in practice. {Comment: Note that, for many applications of these metrics, there may be no harm in treating a large delay as packet loss. An audio playback packet, for example, that arrives only after the playback point may as well have been lost.}

- + The context in which the metric is measured must be carefully considered, and should always be reported along with metric results.

As noted in the Framework document [1], the value of the metric may depend on the type of IP packets used to make the measurement, or "type-P". The value of Type-P-One-way-Delay could change if the protocol (UDP or TCP), port number, size, or arrangement for special treatment (e.g., IP precedence or RSVP) changes. The exact Type-P used to make the measurements must be accurately reported.

In addition, the threshold (or methodology to distinguish) between a large finite delay and loss should be reported.

Finally, the path traversed by the packet should be reported, if possible. In general it is impractical to know the precise path a given packet takes through the network. The precise path may be known for certain Type-P on short or stable paths. If Type-P includes the record route (or loose-source route) option in the IP header, and the path is short enough, and all routers* on the path support record (or loose-source) route, then the path will be

precisely recorded. This is impractical because the route must be short enough, many routers do not support (or are not configured for) record route, and use of this feature would often artificially worsen the performance observed by removing the packet from common-case processing. However, partial information is still valuable context. For example, if a host can choose between two links* (and hence two separate routes from src to dst), then the initial link used is valuable context. {Comment: For example, with Merit's NetNow setup, a Src on one NAP can reach a Dst on another NAP by either of several different backbone networks.}

The above list is not exhaustive; any additional information that could be useful in interpreting applications of the metrics should be reported.

- + If the packet arrives, but is corrupted, then it is counted as lost. {Comment: one is tempted to count the packet as received since corruption and packet loss are related but distinct phenomena. If the IP header is corrupted, however, one cannot be sure about the source or destination IP addresses and is thus on shaky grounds about knowing that the corrupted received packet corresponds to a given sent test packet. Similarly, if other parts of the packet needed by the methodology to know that the corrupted received packet corresponds to a given sent test packet, then such a packet would have to be counted as lost. Counting

these packets as lost but packet with corruption in other parts of the packet as not lost would be inconsistent.}

- + If the packet is duplicated along the path (or paths) so that multiple non-corrupt copies arrive at the destination, then the packet is counted as received.
- + If the packet is fragmented and if, for whatever reason, reassembly does not occur, then the packet will be deemed lost.

[3.6. Methodologies:](#)

As with other Type-P-* metrics, the detailed methodology will depend on the Type-P (e.g., protocol number, UDP/TCP port number, size,

precedence).

Generally, for a given Type-P, one possible methodology would proceed as follows:

- + Arrange that Src and Dst have clocks that are synchronized with each other. The degree of synchronization is a parameter of the methodology, and depends on the threshold used to determine loss (see below).
- + At the Src host, select Src and Dst IP addresses, and form a test packet of Type-P with these addresses.
- + At the Dst host, arrange to receive the packet.
- + At the Src host, place a timestamp in the prepared Type-P packet, and send it towards Dst.
- + If the packet arrives within a reasonable period of time, the one-way packet-loss is taken to be zero.
- + If the packet fails to arrive within a reasonable period of time, the one-way packet-loss is taken to be one. Note that the threshold of "reasonable" here is a parameter of the methodology.

{Comment: The definition of reasonable is intentionally vague, and is intended to indicate a value "Th" so large that any value in (Th-delta,Th+delta) is an equivalent threshold for loss. Here, delta encompasses all error in clock synchronization along the measured path. If there is a single value after which the packet must be counted as lost, then we reintroduce the need for a degree of clock synchronization similar to that needed for one-way delay. Therefore, if a measure of packet loss parameterized by a specific

non-huge "reasonable" time-out value is needed, one can always measure one-way delay and see what percentage of packets from a given stream exceed a given time-out value.}

Issues such as the packet format, the means by which Dst knows when to expect the test packet, and the means by which Src and Dst are synchronized are outside the scope of this document. {Comment: We plan to document elsewhere our own work in describing such more

detailed implementation techniques and we encourage others to as well.}

[3.7.](#) Errors and Uncertainties:

The description of any specific measurement method should include an accounting and analysis of various sources of error/uncertainty. The Framework document provides general guidance on this point.

Errors due to gross lack of synchronization between the Src and Dst hosts should be dealt with. Since the sensitivity of packet loss measurement to lack of synchronization is much less than for delay, we refer the reader to the treatment of synchronization errors in the One-way Delay metric.

[4.](#) A Definition for Samples of One-way Packet Loss

Given the singleton metric Type-P-One-way-Packet-Loss, we now define one particular sample of such singletons. The idea of the sample is to select a particular binding of the parameters Src, Dst, and Type-P, then define a sample of values of parameter T. The means for defining the values of T is to select a beginning time T_0 , a final time T_f , and an average rate λ , then define a pseudo-random Poisson arrival process of rate λ , whose values fall between T_0 and T_f . The time interval between successive values of T will then average $1/\lambda$.

[4.1.](#) Metric Name:

Type-P-One-way-Packet-Loss-Poisson-Stream

[4.2.](#) Metric Parameters:

- + Src, the IP address of a host
- + Dst, the IP address of a host
- + T0, a time
- + Tf, a time
- + lambda, a rate in reciprocal seconds

[4.3.](#) Metric Units:

A sequence of pairs; the elements of each pair are:

- + T, a time, and
- + L, either a zero or a one

The values of T in the sequence are monotonic increasing. Note that T would be a valid parameter to Type-P-One-way-Packet-Loss, and that L would be a valid value of Type-P-One-way-Packet-Loss.

[4.4.](#) Definition:

Given T0, Tf, and lambda, we compute a pseudo-random Poisson process beginning at or before T0, with average arrival rate lambda, and ending at or after Tf. Those time values greater than or equal to T0 and less than or equal to Tf are then selected. At each of the times in this process, we obtain the value of Type-P-One-way-Packet-Loss at this time. The value of the sample is the sequence made up of the resulting <time, loss> pairs. If there are no such pairs, the sequence is of length zero and the sample is said to be empty.

[4.5.](#) Discussion:

Note first that, since a pseudo-random number sequence is employed, the sequence of times, and hence the value of the sample, is not fully specified. Pseudo-random number generators of good quality will be needed to achieve the desired qualities.

The sample is defined in terms of a Poisson process both to avoid the effects of self-synchronization and also capture a sample that is statistically as unbiased as possible. {Comment: there is, of

course, no claim that real Internet traffic arrives according to a Poisson arrival process.

It is important to note that, in contrast to this metric, loss rates observed by transport connections do not reflect unbiased samples. For example, TCP transmissions both (1) occur in bursts, which can induce loss due to the burst volume that would not otherwise have been observed, and (2) adapt their transmission rate in an attempt to minimize the loss rate observed by the connection.}

All the singleton Type-P-One-way-Packet-Loss metrics in the sequence will have the same values of Src, Dst, and Type-P.

Note also that, given one sample that runs from T_0 to T_f , and given new time values T_0' and T_f' such that $T_0 \leq T_0' \leq T_f' \leq T_f$, the subsequence of the given sample whose time values fall between T_0' and T_f' are also a valid Type-P-One-way-Packet-Loss-Poisson-Stream sample.

4.6. Methodologies:

The methodologies follow directly from:

- + the selection of specific times, using the specified Poisson arrival process, and
- + the methodologies discussion already given for the singleton Type-P-One-way-Packet-Loss metric.

Care must be given to correctly handle out-of-order arrival of test packets; it is possible that the Src could send one test packet at $TS[i]$, then send a second one (later) at $TS[i+1]$, while the Dst could receive the second test packet at $TR[i+1]$, and then receive the first one (later) at $TR[i]$.

4.7. Errors and Uncertainties:

In addition to sources of errors and uncertainties associated with methods employed to measure the singleton values that make up the sample, care must be given to analyze the accuracy of the Poisson arrival process of the wire-time of the sending of the test packets. Problems with this process could be caused by either of several things, including problems with the pseudo-random number techniques

used to generate the Poisson arrival process. The Framework document shows how to use an Anderson-Darling test for this.

[5.](#) Some Statistics Definitions for One-way Packet Loss

Given the sample metric Type-P-One-way-Packet-Loss-Poisson-Stream, we now offer several statistics of that sample. These statistics are offered mostly to be illustrative of what could be done.

[5.1.](#) Type-P-One-way-Packet-Loss-Average

Given a Type-P-One-way-Packet-Loss-Poisson-Stream, the average of all the L values in the Stream. In addition, the Type-P-One-way-Packet-Loss-Average is undefined if the sample is empty.

Example: suppose we take a sample and the results are:

```
Stream1 = <
  <T1, 0>
  <T2, 0>
  <T3, 1>
  <T4, 0>
  <T5, 0>
  >
```

Then the average would be 0.2.

Note that, since healthy Internet paths should be operating at loss rates below 1% (particularly if high delay-bandwidth products are to be sustained), the sample sizes needed might be larger than one would like. Thus, for example, if one wants to discriminate between various fractions of 1% over one-minute periods, then several hundred samples per minute might be needed. This would result in larger values of lambda than one would ordinarily want.

[6.](#) Security Considerations

Conducting Internet measurements raises both security and privacy concerns. This memo does not specify an implementation of the metrics, so it does not directly affect the security of the Internet nor of applications which run on the Internet. However, implementations of these metrics must be mindful of security and

privacy concerns.

There are two types of security concerns: potential harm caused by the measurements, and potential harm to the measurements. The measurements could cause harm because they are active, and inject packets into the network. The measurement parameters must be carefully selected so that the measurements inject trivial amounts of additional traffic into the networks they measure. If they inject "too much" traffic, they can skew the results of the measurement, and

Almes et al.

[Page 10]

INTERNET-DRAFT

Packet Loss

June 1998

in extreme cases cause congestion and denial of service.

The measurements themselves could be harmed by routers giving measurement traffic a different priority than "normal" traffic, or by an attacker injecting artificial measurement traffic. If routers can recognize measurement traffic and treat it separately, the measurements will not reflect actual user traffic. If an attacker injects artificial traffic that is accepted as legitimate, the loss rate will be artificially lowered. Therefore, the measurement methodologies should include appropriate techniques to reduce the probability measurement traffic can be distinguished from "normal" traffic. Authentication techniques, such as digital signatures, may be used where appropriate to guard against injected traffic attacks.

The privacy concerns of network measurement are limited by the active measurements described in this memo. Unlike passive measurements, there can be no release of existing user data.

7. Acknowledgements

Thanks are due to Matt Mathis for encouraging this work and for calling attention on so many occasions to the significance of packet loss.

Thanks are due also to Vern Paxson for his valuable comments on early drafts.

8. References

- [1] V. Paxson, G. Almes, J. Mahdavi, and M. Mathis, "Framework for IP Performance Metrics", [RFC 2330](#), May 1998.
- [2] G. Almes, S. Kalidindi, and M. Zekauskas, "A One-way Delay Metric for IPPM", Internet-Draft <[draft-ietf-ippm-delay-02.txt](#)>, June 1998.
- [3] J. Mahdavi and V. Paxson, "Connectivity", Work in Progress, November 1997.
- [4] J. Postel, "Internet Protocol", [RFC 791](#), September 1981.

Almes et al.

[Page 11]

INTERNET-DRAFT

Packet Loss

June 1998

9. Authors' Addresses

Guy Almes
Advanced Network & Services, Inc.
200 Business Park Drive
Armonk, NY 10504
USA

Phone: +1 914 765 1120
EMail: almes@advanced.org

Sunil Kalidindi
Advanced Network & Services, Inc.
200 Business Park Drive
Armonk, NY 10504
USA

Phone: +1 914 765 1128
EMail: kalidindi@advanced.org

Matthew J. Zekauskas
Advanced Network & Services, Inc.
200 Business Park Drive

Armonk, NY 10504
USA

Phone: +1 914 765 1112
EMail: matt@advanced.org

Expiration date: December, 1998